Mineral Survey No. 5024

FEET	
	All lines and connections of this survey were run by direct methods except as noted.
	The magnetic declination observed at each cor. gave a uniform value of 16°30' E.
	GOOSE 39 LODE
	At Cor. No. 1 of the Goose 39 lode, identical with Cor. No. 1 of the Goose 41 lode, Cor. No. 1 of the Goose 155 lode, and Cor. No. 1 of the Goose 157 lode, all of this survey.
	Set an iron post, 24 ins. long, 2 ins. diam., 20 ins. in the ground with a brass cap mkd. G39-1-G41-1-G155-1-G157-1-5024; from which
	The W ½ sec. cor. of Sec. 3, T. 10 N., R. 36 E., Mt. Diablo Meridian, bears N. 37°50'12" E., 2,066.97 ft. dist., monumented with an aluminum post and properly mkd. aluminum cap, 7 ins. above ground.
	Cor. No. 1, M.S. No. 5023 BD 440 lode, identical with Cor. No. 1, M.S. No. 5023 BD 442A lode, and Cor. No. 1, M.S. No. 5023 BD 443A lode, bears S. 64°00'42" E., 2,516.86 ft. dist., monumented with an iron post and properly mkd. brass cap, 6 ins. above ground.
	No local bearing objects or bearing trees available.
	Thence N. 89°58'48" W.
300.00	Lode line; discovery point bears S. 0°00'28" W., 10 ft. dist.
465.	Leave dump, toe bears N. 5°45' E. and S. 11°48" E.
540.00	Witness Cor. No. 2.
	Set an iron post, 24 ins. long, 2 ins. diam., 20 ins. in the ground, with a brass cap mkd. WC-G39-2-G155-2-5024.
	No local bearing objects or bearing trees available.
555.	Enter cyanide pond, edge bears N. 7° E. and S. 7° W.