Mineral Survey No. 5027

	· · · · · · · · · · · · · · · · · · ·
FEET	
	BD 425A LODE
	At Cor. No. 1 of the BD 425A lode, identical with Cor. No. 1 of the BD 427A lode of this survey, Cor. No. 2, M.S. No. 5022 BD 424 lode, and Cor. No. 2, M.S. No. 5022 BD 426 lode.
	The original monument set for M.S. No. 5022 was found destroyed and now falls in a pit mine development area where a permanent monument cannot be set; from which
	The N $\frac{1}{4}$ sec. cor. of Sec. 10, T. 10 N., R. 36 E., Mt. Diablo Meridian, bears N. 12°43'23" W., 2,250.60 ft. dist., monumented with an aluminum post and properly mkd. aluminum cap, 23 ins. above the ground, surrounded by a mound of stone, 4 ft. diam.
	Cor. No. 1, M.S. No. 5024 Goose 166 lode, bears N. 32°04'58" W., 3,777.33 ft. dist., monumented with an iron post and properly mkd. brass cap, 6 ins. above the ground.
	No local bearing objects or bearing trees available.
	Thence S. 45°37'04" E.
300.00	Lode line; discovery point bears N. 45°01'27" E., 10.0 ft. dist.
494.5	Leave pit mine development area, edge bears N. 23°23' E. and S. 23°23' W.
600.00	Cor. No. 2, identical with Cor. No. 1, M.S. No. 5022 BD 424 lode.
	Found an iron post, 2 ins. diam., firmly set, 5 ins. showing above the ground, with a brass cap mkd. BD424-1-5022. Added BD425A-2-5027.
	No local bearing objects or bearing trees available.
	Thence N. 45°01'27" E.
1057.	Wire fence, 6 ft. high, bears N. 24°33' W. and S. 24°33' E.
1450.00	Witness Cor. No. 3.
	Set an iron post, 24 ins. long, 2 ins. diam., 21 ins. in the ground, with a brass cap mkd. WC-BD425A-3-5027.
·	No local bearing objects or bearing trees available.