

Mineral Survey No. 5016

FEET	
1490.00	<p>Cor. No. 3, identical with Cor. No. 3 Sleeper No. 15 lode of this survey, previously described.</p> <p style="text-align: center;">Thence S. 89°58' E.</p>
295.00	<p>Lode line; discovery point bears S. 0°02' W., 20.0 ft. dist.</p>
554.	<p>Barb wire fence, 4 ft. high, bears North and South.</p>
590.00	<p>Cor. No. 4, identical with Cor. No. 4 Sleeper No. 19 lode of this survey.</p> <p>Set an aluminum post, 2½ ft. long, 2½ ins. diam., 26 ins. in the ground, with aluminum cap mkd. MS 5016 SLEEPER 17-4 SLEEPER 19-4; from which</p> <p style="padding-left: 40px;">The 1/4 sec. cor. of secs. 15 and 16, T. 40 N., R. 35 E., Mount Diablo Meridian, bears N. 7°29'05" W., 257.52 ft. dist., monumented with an iron post, 2½ ins. diam., 5 ins. above ground, firmly set, with brass cap properly mkd.</p> <p>No local bearing objects or bearing trees available.</p> <p style="text-align: center;">Thence S. 0°02' W.</p>
1067.	<p>Barb wire fence, 4 ft. high, bears N. 89° W. and S. 89° E.</p>
1490.00	<p>Cor. No. 1, and place of beginning.</p> <hr/> <p style="text-align: center;">SLEEPER NO. 18 LODE</p> <p>Beginning at Cor. No. 1 of the Sleeper No. 18 lode, identical with Cor. No. 1 Sleeper No. 17, Cor. No. 1 Sleeper No. 19 and Cor. No. 1 Sleeper No. 20 lodes,</p>