

Mineral Survey No. 5016

FEET	<p>Set an aluminum post, 2½ ft. long, 2½ ins. diam., 28 ins. in the ground, with aluminum cap mkd. MS 5016 SLEEPER 18-4 SLEEPER 20-4 SLEEPER 43-4 SLEEPER 45-4; from which</p> <p>The cor. of secs. 15, 16, 21 and 22, T. 40 N., R. 35 E., Mount Diablo Meridian, bears N. 3°02'49" W., 596.48 ft. dist., monumented with an iron post, 2½ ins. diam., 7 ins. above ground, firmly set, with brass cap properly mkd.</p> <p>No local bearing objects or bearing trees available.</p> <p>Thence N. 0°02' E.</p> <p>126. Center of overhead power line, bears N. 16° E. and S. 16° W.</p> <p>298. Center line of road, 27 ft. wide, bears N. 16° E. and S. 16° W.</p> <p>485. Barb wire fence, 4 ft. high, bears N. 16° E. and S. 16° W.</p> <p>1490.00 Cor. No. 1, and place of beginning.</p> <hr/> <p>SLEEPER No. 19 LODE</p> <p>Beginning at Cor. No. 1 of the Sleeper No. 19 lode, identical with Cor. No. 1 Sleeper No. 17, Cor. No. 1 Sleeper No. 18 and Cor. No. 1 Sleeper No. 20 lodes, all of this survey, previously described.</p> <p>Thence S. 89°58' E.</p> <p>295.00 Lode line; discovery point bears N. 0°02' E., 30.0 ft. dist.</p> <p>502. Barb wire fence, 4 ft. high, bears N. 30° E. and S. 27° W.</p> <p>Page 27</p>
------	--