

Mineral Survey No. 5017

FEET	
	<p>The magnetic declination observed at each corner of the survey gave a uniform value of 17° East.</p> <p>The lines were measured with a Benchmark Surveyor III-X electronic distance meter, serial No. 878 with a specified accuracy of +/- (5 MM + 5 PPM). The electronic distance meter was in good condition at the time of the survey and all adjustments were in good order.</p> <hr/> <p style="text-align: center;">Mineral Survey No. 5017</p> <hr/> <p style="text-align: center;">SIDE LINE NO. 1 LODE</p> <p>At Cor. No. 1 of the SIDE LINE NO. 1 lode, on line 4-1 of the SIDE LINE NO. 30 lode of this survey.</p> <p>Set a 1 in. diam. aluminum shaft, 30 ins. long, 24 ins. in the ground, with a 3-1/4 in. diam. aluminum cap mkd. 1 SL 1 USMS 5017. Set a steel fence post within a 2 ft. radius of the monument; from which</p> <p style="padding-left: 40px;">The 1/4 sec. cor. between Secs. 32 and 33, T. 39 N., R. 42 E., M.D.M., bears S. 00°04'30" E., 2740.67 ft. dist., monumented with a 2-1/2 in. diam. iron pipe and brass cap properly mkd.</p> <p style="padding-left: 40px;">The witness cor. to the cor. of Secs. 28, 29, 32 and 33, T. 39 N., R. 42 E., M.D.M., bears S. 19°56'17" E., 398.20 ft. dist., monumented with a 2-1/2 in. diam. iron pipe and brass cap properly mkd.</p> <p>No local bearing objects or bearing trees available.</p> <p style="padding-left: 40px;">Thence S. 63°17'46" W.</p>
273.27	Intersect the line between Secs. 29 and 32, at a point from which the true point for the cor. of Secs. 28, 29, 32 and 33, T. 39 N., R. 42 E., M.D.M., bears N. 89°17'56" E., 393.97 ft. dist. Leave patented land.
291.71	Lode line; discovery point bears S. 00°32'46" W., 554.50 ft. dist.