

Mineral Survey No. 5017

FEET	
600.00	Cor. No. 4, identical with Cor. No. 3 of the SIDE LINE NO. 13 lode of this survey.
	Thence S. 0°52'14" E.
1229.28	Intersect line 2-3 of the SIDE LINE NO. 27 of this survey.
1500.00	Cor. No. 1 and place of beginning.
	<p style="text-align: center;">SIDE LINE NO. 19 LODE</p> <p>At Cor. No. 1 of the SIDE LINE NO. 19 lode.</p> <p>This corner position falls at a point on a large sloping granite boulder where a permanent monument cannot be set; from which</p> <p style="padding-left: 40px;">The 1/4 sec. cor. between Secs. 32 and 33, T. 39 N., R. 42 E., M.D.M., bears N. 28°40'01" E., 3098.32 ft. dist. heretofore described.</p> <p>No local bearing objects or bearing trees are available.</p> <p style="text-align: center;">Thence N. 0°32'46" E.</p>
60.04	Intersect the line between Secs. 5 and 32, Tps. 38 and 39 N., Rs. 42 E., M.D.M., at a point from which the cor. of Secs. 4, 5, 32 and 33, bears N. 88°12'32" E. 1343.09 ft. dist., monumented with a 2-1/2 in. diam. iron pipe and brass cap properly mkd. Leave patented land.
300.00	Lode line; discovery point bears N. 88°17'16" E., 1200.00 ft. dist.
600.00	<p>Cor. No. 2.</p> <p>Set a 1 in. diam. aluminum shaft, 30 ins. long, 24 ins. in the ground, in an existing earth mound approx. 1 ft. high and 6 ft. in diam., with a 3-1/4 in. diam. aluminum cap mkd. 2 SL 19 USMS 5017. Set a steel fence post within a 2 ft. radius of the monument.</p> <p>No local bearing objects or bearing trees are available.</p>