

Mineral Survey No. 5017

FEET	
	No local bearing objects or bearing trees are available.
	Thence S. 63°17'46" W.
1500.00	Cor. No. 3.
	Set a 1 in. diam. aluminum shaft, 30 ins. long, 24 ins. in the ground, in an existing earth mound, approx. 1 ft. high and 6 ft. in diam., with a 3-1/4 in. diam. aluminum cap mkd. 3 SL 32 USMS 5017. Set a steel fence post within a 2 ft. radius of monument.
	No local bearing objects or bearing trees are available.
	Thence S. 0°32'46" W.
58.91	Intersect the line between Secs. 29 and 32, T. 39 N., R. 42 E., M.D.M., at a point from which the 1/4 sec. cor. between Sec. 32 and 29 bears N. 89°18'31" E., 83.86 ft. dist. Monumented with a 2-1/2 in. diam. iron pipe and brass cap properly mkd. Leave patented land.
300.00	Lode line; discovery point bears N. 63°17'46" E., 300.00 ft. dist.
600.00	Cor. No. 4, identical with Cor. No. 4 of the SIDE LINE NO. 9 lode of this survey.
	Thence N. 63°17'46" E.
1233.86	Intersect the line between Secs. 29 and 32, T. 39 N., R. 42 E., M.D.M., at a point from which the 1/4 sec. cor. between Secs. 29 and 32 bears S. 89°17'56" W., 1013.33 ft. dist., heretofore described. Enter patented land.
1500.00	Cor. No. 1 and place of beginning.
	SIDELINE 1F LODE
	At Cor. No. 1 of the Sideline 1F lode, identical with Cor. No. 1 of the Sideline 31F lode, and on