

## Mineral Survey No. 5018

FEET	
	<p>The geographic position of Cor. No. 4 of the SIDE LINE EXTENSION NO. 7 lode is: latitude <math>41^{\circ}12'22''</math> N. and longitude <math>117^{\circ}15'20''</math> W.</p> <p>The magnetic declination observed at each corner of the survey gave a uniform value of <math>17^{\circ}</math>E.</p> <p>The lines were measured with a Benchmark Surveyor III-X electronic distance meter, Serial No. 878 with a specified accuracy of <math>\pm(5 \text{ MM} + 5 \text{ PPM})</math>. The electronic distance meter was in good condition at the time of the survey and all adjustments were in good order.</p> <hr/> <p style="text-align: center;">Mineral Survey No. 5018</p> <hr/> <p style="text-align: center;">SIDE LINE EXTENSION NO. 1 LODGE</p> <p>At Cor. No. 1 of the SIDE LINE EXTENSION NO. 1 lode, identical with Cor. No. 1 of the SIDE LINE EXTENSION NO. 2 lode of this survey.</p> <p>Set a 1 in. diam. aluminum shaft, 30 ins. long, 24 ins. in the ground, with a 3-1/4 in. diam. aluminum cap mkd. 1 SLE 1 1 SLE 2 USMS 5018. Set a steel fence post within a 2 ft. radius of the monument; from which</p> <p style="padding-left: 40px;">The cor. of Secs. 4, 5, 32 and 33, Tps. 38 and 39 N., Rs. 42 E., M.D.M., bears N. <math>60^{\circ}50'37''</math> W., 2781.99 ft. dist.; monumented with a 2 1/2 in. diam. iron pipe and brass cap properly mkd.</p> <p>No local bearing objects or bearing trees are available.</p> <p style="padding-left: 40px;">Thence S. <math>89^{\circ}13'24''</math> W.</p>
300.00	Lode line; discovery point bears N. $15^{\circ} 46' 36''$ W., 750.00 ft. dist.
600.00	Cor. No. 2, identical with Cor. No. 2 of the SIDE LINE EXTENSION NO. 2 lode, and on line 2-3 of the