

Mineral Survey No. 5019

FEET	
	<p>The geographic position of Cor. No. 4 of the SIDE LINE EXTENSION NO. 12 lode is: latitude $41^{\circ}12'28''$ N. and longitude $117^{\circ}15'07''$ W.</p> <p>The magnetic declination observed at each corner of the survey gave a uniform value of 17° East.</p> <p>The lines were measured with a Benchmark Surveyor III-X electronic distance meter, serial No. 878 with a specified accuracy of $\pm(5 \text{ MM} + 5 \text{ PPM})$. The electronic distance meter was in good condition at the time of the survey and all adjustments were in good order.</p> <hr/> <p style="text-align: center;">Mineral Survey No. 5019</p> <hr/> <p style="text-align: center;">SIDE LINE EXTENSION NO. 10 LODE</p> <p>At Cor. No. 1 of the SIDE LINE EXTENSION NO. 10 lode, identical with Cor. No. 1 of the SIDE LINE EXT. NO. 17 lode of this survey; and identical with Cor. No. 1 of the SIDE LINE EXTENSION NO. 3 lode and Cor. No. 1 of the SIDE LINE EXTENSION NO. 14 lode, both of USMS No. 5018.</p> <p>A 1 in. diam. aluminum shaft, with a 3-1/4 in. diam. aluminum cap mkd. 1 SLE 3 1 SLE 14 USMS 5018; add the marks 1 SLE 10 1 SLE 17 USMS 5019; from which</p> <p style="padding-left: 40px;">The cor. of Secs. 4, 5, 32 and 33, Tps. 38 and 39 N., Rs. 42 E., M.D.M., bears N. $35^{\circ}36'34''$ W., 5266.01 ft. dist.; monumented with a 2-1/2 in. diam. iron pipe and with a brass cap properly mkd.</p> <p>No local bearing objects or bearing trees are available.</p> <p style="padding-left: 40px;">Thence N. $89^{\circ}13'24''$ E.</p>
300.00	<p>Lode line; discovery point bears N. $8^{\circ}46'36''$ W., 750.00 ft. dist.</p>