

| FEET | |
|---------|--|
| | <p>At Cor. No. 1 of the 2NVE No. 15 lode, identical with Cor. No. 1 of the 2NVE No. 5 lode of this survey.</p> |
| | <p>Set an iron post, 24 ins. long, 2 ins. diam., 20 ins. in the ground, with a 3/4 ins. diam. aluminum cap mkd. 2NVE15-1-2NVE5-1-5044; from which</p> |
| | <p>The witness cor. for the cor. of Secs. 25, 30, 31, and 36, Tps. 36 N., Rs. 49 and 50 E., M.D.M., bears N. 27°33'59" E., 3166.79 ft. dist., hereinbefore described.</p> |
| | <p>The standard cor. of Secs. 31 and 36, Tps. 36 N., Rs. 49 and 50 E., M.D.M., bears S. 31°58'27" E., 2752.79 ft. dist., monumented with an iron post, 3 ins. diam., 12 ins. above the ground, firmly set, with a properly mkd. brass cap with RLS 6805 added.</p> |
| | <p>The standard 1/4 sec. cor. of Sec. 36, T. 36 N., R. 49 E., M.D.M., bears S. 26°44'34" W., 2664.69 ft. dist., monumented with an iron post, 1 inch diam., 18 ins. above the ground, with a brass cap firmly set, properly mkd.</p> |
| | <p>No local bearing objects or bearing trees available.</p> |
| | <p>Thence N. 89°38'17" W.</p> |
| 340. | <p>Center of road, 12 ft. wide, bears N. 40° W. and S. 40° E.</p> |
| 820. | <p>Center of road, 12 ft. wide, bears N. 35° W. and S. 35° E.</p> |
| 960. | <p>Center of road, 12 ft. wide, bears N. 77° E. and S. 77° W.</p> |
| 1245. | <p>Center of road, 12 ft. wide, bears North and South.</p> |
| 1482.80 | <p>Cor. No. 2.</p> |
| | <p>Set an iron post, 24 ins. long, 2 ins. diam., 20 ins. in the ground, with a 3/4 ins. diam. aluminum cap mkd. 2NVE15-2-5044.</p> |
| | <p>No local bearing objects or bearing trees available.</p> |
| | <p>Thence N. 0°14'34" E.</p> |