

Mineral Survey No. 5051

7

FEET

to face. Thence N. 58°00' W., 35.1 ft. to Sta. No. 5, thence N. 74°00' W., 33.0 ft. to Sta. No. 6, thence N. 42°00' W., 20.7 ft. to Sta. No. 7, thence N. 61°00' W., 27.9 ft. to Sta. No. 8, thence N. 68°35'50" W., 29.05 ft. to Sta. "B" a point on line 4-1 of the CALAVERAS No. 10 lode, from which Cor. No. 1 bears S. 30°56'51" E., 186.92 ft. dist., thence N. 68°35'50" W., 21.8 ft. to the face. Adit, Sta. No. 1 to faces 398.58 ft. dist., value \$39,858.00. Underground vertical shaft, 80 ft. deep, value \$8,000.00.

Value of adit, drift and shaft, \$47,858.00.

Total value of expenditures this survey: \$101,650.50. Number of mining claims included in this survey: 2. Allocation of proportionate share of expenditures to this survey \$101,650.50 divided by 2 = \$50,825.25 per lode.

The improvements are in progress for the development of the two lodes of this survey, which are all the contiguous lode claims owned in common within the range of benefit of said improvements.

These improvements afford the most practical and economical means of developing each of the lodes.

Five hundred dollars or over has been expended in these improvements in such a manner as tends to the development of each lode of this survey, subsequent to its location and to the time since which common ownership and contiguity have prevailed; therefore, an undivided one-half interest in their value is hereby credited to each of the lodes.

No portion of or interest in these improvements has been credited heretofore as patent expenditure to any lode claims.

OTHER CORNER DESCRIPTIONS AND SUPPLEMENTAL DATA

The 1/4 sec. cor. of Secs. 3 and 34, Tps. 43 and 44 N., R. 52 E., M.D.M., was found to be monumented with an iron post and brass cap firmly set and properly marked, 12 ins. above the ground.

U.S.G.S. Triangulation Station "WILSON", monumented with a brass cap, 8 ins. above the ground mkd. WILSON 1947. Reference mark Nos. 1 and No. 2 were both found in good condition.