

MINERAL SURVEY NO. 5059

FEET	
	ft. dist.
554.	Center dirt road, 20 ft. wide, bears N. 20° W. and S. 20° E.
599.80	Intersect the line bet. secs. 19 and 24, Tps. 36 N., Rs. 49 and 50 E., at a point from which the $\frac{1}{4}$ sec. cor. of sections 19 and 24, bears S. 0°03'36" W., 380.56 ft. dist.
600.00	Cor. No. 3. Set an iron post, 24 ins. long, 2½ ins. diam., 18 ins. in the ground, with an aluminum cap marked P05-3-5059. No local bearing objects or bearing trees available. Thence S. 0°01'44" W.
155.	Center dirt road, 20 ft. wide, bears N. 80° E. and S. 80° W.
170.	Water pipe, 18 ins. diam., bears N. 80° E. and S. 80° W.
360.	Center haul road, 75 ft. wide, bears N. 60° E. and S. 60° W.
380.56	Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 24, Tps. 36 N., Rs. 49 and 50 E. The monument for this corner has been destroyed by mining activity. The position was calculated based upon the recorded Map of Amended Goldstrike and POST Lode Mining Claims, file No. 136730, of the Eureka County Official Records. The point for this corner is located within a haul road, point not monumented.
1500.00	Cor. No. 4, identical with Cor. No. 4 of the POST No. 1 lode of this survey, hereinbefore described. Thence N. 89°42'46" E.
37.65	Intersect top of slope, top bears N. 1°40'31" E. and S. 1°40'31" W.
300.00	Lode line, discovery point bears N. 0°01'44" E. 100.00 ft. dist.
501.6	Toe of slope, bears N. 1° E. and S. 1° W.
600.00	Cor. No. 1, and place of beginning.