FEET

Electronic Distance Meter No. B31084; which was compared with the Kingman Calibration Base Line at the time of beginning the survey, and found to be working correctly.

All lines and connections of this survey were run by traverses, upon the ground and submitted in a separate report herewith. The open nature of the traverses used required the following procedure so as to verify the data gathered. All angles were doubled and the horizon closed. All distances were measured in feet and meters and the suitable reductions made. Additional solar observations were made near the northwest cor. sec. 3 and convergence of meridians was allowed for.

The magnetic declination observed at each corner of the survey gave a uniform value of 13°30'E.

Mineral Survey No. 5053

MOCKINGBIRD MILLSITE

At Cor. No. 1 of the Mockingbird Millsite, identical with easterly right-of-way sta. P.C. 49+41.27 of Nevada State Route 60 in latitude 35°42'20"N and longitude 114°48'57"W.

Found a 1 in. diam. iron pipe, extending 6 ins. above ground, with aluminum cap, 2 ins. diam. marked PLS 6719, add the marks MMS-1-5053; from which

> The cor. of secs. 3, 4, 33, and 34, Tps.25 and 26 S., Rs.64 E., Mount Diablo Meridian, bears N.36°43'00"W., 6878.78 ft. dist.; monumented with an iron pipe, 2 1/2 ins. diam., extending 14 ins. above ground in a mound of stone, firmly set, with brass cap properly mkd. A local monument for the cor. of secs. 3, 4, 9, and 10, T.26 S., R.64 E., Mount Diablo Meridian, bears N.87°03'10"W., 3823.46 ft. dist.; monumented with a drill steel, 1 5/8 ins. diam., extending 6 ins. above ground.

Thence northerly along the easterly right-of-way of Nevada State Route 60 along the arc of a circular