

124. Center of road, 12 ft. wide, bears N. 42° W. and S. 42° E.
- 659.74 Cor. No. 2, identical with Cor. No. 2 of the PG #1 placer of this survey, hereinbefore described.
- Thence N. 0°07'16" W.
589. Center of road, 12 ft. wide, bears N. 42° W. and S. 42° E.
648. Buried gas line, 8 ins. diam., bears N. 42°25' W. and S. 42°25' E.
787. Center and end of road, 12 ft. wide, bears East.
- 799.75 Cor. No. 3, identical with the cor. of Secs. 1, 2, 35, and 36, Tps. 19 and 20 S., R. 63 E., M.D.M., monumented with an iron post, firmly set, extending 10 ins. above ground, with a GLO brass cap properly marked, surrounded by a collar of stone, 5.0 ft. diam. Marked the vertical edge of the brass cap PG 111-3-5030; from which
- Point "A" bears N. 89°58'19" E., 25.78 ft. dist., monumented with a rebar 18" long, 3/4 in. diam., set flush with the ground.
- No local bearing object or bearing trees available.
- Thence N. 89°58'19" E.
- 659.85 Cor. No. 4, identical with Cor. No. 4 of the PG #112 placer of this survey.
- Set an iron post, 24 ins. long, 2 ins. diam., 22 ins. in the ground, with a 3 1/4 ins. diam. aluminum cap mkd. PG111-4-PG112-4-5030; from which
- Location monument bears West, 10.0 ft. dist.
- No local bearing objects or bearing trees available.
- Thence S. 0°06'50" E.
18. Center of road, 15 ft. wide, bears East and West.
- 31.9 Center of trench, 13 ft. wide, bears N. 70° W. and S. 70° E.
- 799.48 Cor. No. 1 and place of beginning.