

Mineral Survey No. 5070

FEET	
	RUSS NO. 14 LODGE
	At Cor. No. 1 of the Russ No. 14 lode, identical with Cor. No. 1 of the Russ No. 5A lode, Cor. No. 1 of the Russ No. 6A lode, and Cor. No. 1 of the TS #51 lode, all of this survey.
	Set an iron post, 24 ins. long, 1½ ins. diam., 16 ins. in the ground, with a ¾ ins. diam. aluminum cap mkd. R14-1-R5A-1-R6A-1-TS51-1-5070-1992; from which
	The cor. of secs. 10, 11, 14, and 15, T. 40 N., R. 53 E., MDM, bears S. 80°07'57" E., 2231.79 ft. dist., hereinafter described.
	Cor. No. 3, M.S. No. 5069 MA #3 lode, bears S. 75°46'59" W., 1208.14 ft. dist., hereinafter described.
	Cor. No. 3, M.S. No. 5071 Russ No. 18 lode, identical with Cor. No. 3 of the SAV No. 7 lode and Cor. No. 3 of the TS #52 lode, both of this survey, bears S. 76°49'18" E., 1528.41 ft. dist., hereinafter described.
	No local bearing objects or bearing trees available.
	Thence S. 2°06'36" W.
300.00	Lode line, discovery point bears S. 88°08'29" E., 750.00 ft. dist.
584.61	Intersect the line bet. secs. 10 and 15, T. 40 N., R. 53 E., MDM, at a point from which the E 1/16 sec. cor. of secs. 10 and 15 bears N. 84°49'21" E., 921.96 ft. dist., hereinafter described. Enter patented land.
600.00	Cor. No. 2, identical with Cor. No. 2 of the SAV No. 6A lode, and Cor. No. 2 of the Russ No. 5A lode, both of this survey, and Cor. No. 2, M.S. No. 5069 Russ No. 4 lode. Situated within patented land.
	An existing iron post, 24 ins. long, 1½ ins. diam., 7 ins. above the ground, with a ¾ ins. diam. aluminum cap mkd. R4-2-5069-1992, added R5A-2-R14-2-SAV6A-2-5070.
	No local bearing objects or bearing trees available.
	Thence S. 88°08'29" E.
923.15	Intersect the N-S center line of the NE 1/4 of sec. 15, T. 40 N., R. 53 E., MDM, at a point from which the E 1/16 sec. cor. of secs. 10 and 15 bears N. 1°44'03" W., 128.58 ft. dist., hereinafter described.
1430.	Ridge, bears N. 10° E. and S. 10° W.
1500.00	Cor. No. 3, on line 2-3, M.S. No. 5071 Russ No. 18 lode. Situated within patented land.
	Set an iron post, 24 ins. long, 1½ ins. diam., 17 ins. in the ground, with a ¾ ins. diam. aluminum cap mkd. R14-3-5070-1992.
	No local bearing objects or bearing trees available.