

Mineral Survey No. 5072

FEET	
	<p>Drill Hole No. TARA 73 bears S. 14°04' W., 914.5 ft. dist., from Cor. No. 1 of the TARA 40 lode, 5.75 ins. diam., inclined -45°, azimuth 270°, total depth of drill hole, 200 ft. Value \$665.00</p>
	<p>Drill Hole No. TARA 62 bears N. 11°03' W., 1402.3 ft. dist., from Cor. No. 1 of the TARA 48 lode, 4.5 ins. diam., inclined -45°, azimuth 270°, total depth of drill hole, 500 ft., 275 ft. of which is within TARA 48 lode. Value \$2,108.00</p>
	<p>Drill Hole No. TARA 61 bears N. 17°10' W., 1419.6 ft. dist., from Cor. No. 1 of the TARA 49 lode, vertical hole, 4.5 ins. diam., 150 ft. deep. Value \$1,229.00</p>
	<p>Drill Hole No. TARA 65 bears N. 4°42' E., 997.6 ft. dist., from Cor. No. 1 of the TARA 50 lode, 4.5 ins. diam., inclined -45°, azimuth 270°, total depth of drill hole, 150 ft. Value \$788.00</p>
	<p>Total value of expenditures this survey: \$109,058.00. Number of mining claims included in this survey: 16. Allocation of proportionate share of expenditures to this survey: \$109,058.00 divided by 16 = \$6,816.13 per lode. These improvements are in progress for the development of the sixteen lodes of this survey, which are all the contiguous lode claims owned in common within the range of benefit of said improvements. These improvements afford the most practical and economical means of developing each of the lodes. Five hundred dollars or over has been expended in these improvements in such a manner as tends to the development of each lode of this survey, subsequent to its location and to the time since which common ownership and contiguity have prevailed; therefore, an undivided one-sixteenth interest in their value is hereby credited to each of the lodes. No portion of or interest in these improvements has been credited theretofore as patent expenditures to any lode claims.</p>
	<p style="text-align: center;">OTHER CORNER DESCRIPTIONS AND SUPPLEMENTAL DATA</p>
	<p>The cor. of secs. 10, 11, 14, and 15, T. 36 N., R. 49 E., MDM, was found monumented with an iron post and brass cap, 1.35 ft. above the ground, surrounded by a mound of stone and earth, firmly set and mkd. S10-S11-S14-S15-T36N-R49E-1970-RLS 1404-Chilton Engineering, Elko, Nevada.</p>
	<p>The $W^{1/16}$ sec. cor. of secs. 11 and 14, T. 36 N., R. 49 E., MDM, was found monumented with an iron post and brass cap, firmly set and mkd. $W^{1/16}$-S11-S14-1970-Chilton Engineering-RLS 1404-Elko, Nevada.</p>
	<p>The $1/4$ sec. cor. of secs. 11 and 14, T. 36 N., R. 49 E., MDM, was found monumented with an iron post and aluminum cap, firmly set and mkd. $1/4$-S11-S14-T36N-R49E-1990-PLS 3535.</p>