

Mineral Survey No. 5106

FEET	
	Uniform declination for this survey was observed to be 16°00' East at each corner.
	Mineral Survey No. 5106
	GRM 753 LODE
	At Cor. No. 1 of the GRM 753 lode.
	Set an aluminum post, 2½ ft. long, 2½ ins. in diam., 25 ins. in the ground, with aluminum cap mkd. MS5106 GRM 753-1; from which
	The cor. of secs. 5, 6, 31 and 32, Tps. 27 and 28 N., R. 47 E., M.D.M., bears S. 16°56'11" W., 3715.33 ft. dist., monumented with a galvanized pipe, 2½ ins. in diam., firmly set, surrounded by a mound of stone, 30 in. base, 12 ins. high, with a 3¼ in. aluminum cap mkd. T 28 N R 47 E S31 S32 1993 PLS 6196 and UNSURVEYED for the township to the south.
	No local bearing objects or bearing trees available.
	Thence S. 0°55' W.
300.00	Lode line; discovery point bears N. 87°36' W., 25.00 ft. dist.
535.	Power line, bears N. 83° E. and S. 83° W.
544.	Center of road, 16 ft. wide, bears N. 83° E. and S. 83° W.
600.00	Cor. No. 2, identical with Cor. No. 2 GRM 755 lode of this survey.
	Set an aluminum post, 2½ ft. long, 2½ ins. in diam., 26 ins. in the ground, with aluminum cap mkd. MS5106 GRM 753-2 GRM 755-2.
	No local bearing objects or bearing trees available.
	Thence N. 87°36' W.
338.	Center of road, 16 ft. wide, bears N. 83° E. and S. 81° W.