

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

A PORTION OF THE EAST BOUNDARY

AND

A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF CERTAIN SECTIONS,

TOWNSHIP 10 SOUTH, RANGE 62 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATE OF NEVADA

EXECUTED BY

Don R. Aschenbach, Cadastral Surveyor

Under Special Instructions dated July 12, 2005,

and approved July 12, 2005,

which provided for the surveys included under Group No. 828,

and Assignment Instructions dated July 12, 2005.

Survey commenced July 15, 2005

Survey completed June 12, 2008

INDEX DIAGRAM

TOWNSHIP 10 SOUTH, RANGE 62 EAST, MOUNT DIABLO MERIDIAN, NEVADA

6	5	4	3	19 2	1
7	8	9	10	17 11 17	12 13
18	17	16	15	16 14 15	12 13 4 11
19	20	21	22	14 23 14	10 24 3 9
30	29	28	27	26	7 25 2 5
31	32	33	34	35	36

Subdivision of Section 13 pp. 19 - 21.
 Subdivision of Section 14 pp. 21 - 22.
 Subdivision of Section 23 pp. 22 - 24.
 Subdivision of Section 24 p. 24.
 Subdivision of Section 25 pp. 24 - 27.

TOWNSHIP 10 SOUTH, RANGE 62 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>The following field notes are those of the dependent resurvey of a portion of the east boundary and a portion of the subdivisional lines, and the subdivision of certain sections, Township 10 South, Range 62 East, Mount Diablo Meridian, Nevada.</p> <p>The exterior boundaries and subdivisional lines were surveyed by U.S. Deputy Surveyors W.F. Benson and C.F. Putnam in 1881 under Contract No. 125.</p> <p>The north boundary was retraced and resurveyed by U.S. Transitsmen H.G. Mason and E.R. Bunbury in 1916-1917 under Group No. 49. A second set of corners referring to T. 9 S., R. 62 E. only, was established during the course of this survey.</p> <p>A dependent resurvey of a portion of the north boundary was executed concurrently under T. 9 S., R. 62 E., of this same Group.</p> <p>Before restoring the corners, the lines of the original surveys were retraced and diligent search made for any evidence of the original corners and other calls of the field note record.</p> <p>The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.</p> <p>The survey as executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 828, dated July 12, 2005.</p> <p>Measurements were made with Trimble 5700 Global Positioning System (GPS) receivers using the real-time kinematic (RTK) method and refer to the true meridian based on geodetic methods. The mean bearings of the lines and horizontal equivalents of ground distances only are entered in the field notes.</p> <p>The NAD 83 (CORS 96) geographic position of the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., determined from Global Positioning System (GPS) static observations processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS), LVWD LAS VEGAS VALLEY CORS ARP, NVCS CARLTON SQUARE CORS ARP and NVLK A M SMITH WTF CORS ARP, in 2006, is as follows:</p> <p>Latitude: 37°02'33.004" N. Longitude: 114°58'44.384" W.</p> <p>The mean magnetic declination is 15 1/2° E., as shown on U.S.G.S. 7 1/2 minute quadrangle map "LOWER PAHRANAGAT LAKE SE, NEV.", dated 1969.</p> <hr/>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 10 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Reestablishment of the Survey Executed by U.S. Deputy Surveyors W.F. Benson and C.F. Putnam in 1881																
	<p>Beginning at the cor. of secs. 25, 30, 31 and 36, perpetuated by R.L. Carpenter, Nevada Professional Land Surveyor No. 2708, not recorded, monumented with a rebar, 5/8 in. diam., firmly set in a mound of stone, 4 ft. base, 3 ft. high, with aluminum cap mkd. LAPS L67 RLS 2708, alongside of which is a basalt stone 16x12x10 ins., loosely set, mkd. with 1 groove on S. and 5 grooves on N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <table border="0" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T10S</td></tr> <tr><td style="text-align: center;">R62E</td><td style="text-align: center;">R63E</td></tr> <tr><td style="text-align: center;">S25</td><td style="text-align: center;">S30</td></tr> <tr><td style="text-align: center;">S36</td><td style="text-align: center;">S31</td></tr> </table> <p style="text-align: center;">2005</p> <p>A careful search was made for evidence of the position determined as the cor. of secs. 25, 30, 31 and 36, by Richard J. Baughman, Nevada Professional Land Surveyor No. 2162, as recorded in Lincoln County, Nevada, Plat Book No. A, Page 83, Inst. No. 50129. No monument was found.</p> <p>Deposit the rebar and the original stone alongside the stainless steel post.</p> <p>N. 1°52'10" E., bet. secs. 25 and 30.</p> <p>Over rolling land covered with creosote, chaparral and scattered cacti.</p> <p>17.50 Enter wash, drains SW.</p> <p>22.00 Leave wash, ascend.</p> <p>38.00 Ridge, bears NE. and SW.</p> <p>40.522 The 1/4 sec. cor. of secs. 25 and 30, monumented with a limestone, 15x8x7 ins., loosely set in a mound of stone, 3 ft. base, 1 1/2 ft. high, dimly mkd. 1/4 on W. face.</p> <p>At the corner point</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, flush in rock, with top mkd.</p> <table border="0" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T10S</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">R62E</td><td style="text-align: center;">R63E</td></tr> <tr><td style="text-align: center;">S25</td><td style="text-align: center;">S30</td></tr> </table> <p style="text-align: center;">2005</p>	T10S		R62E	R63E	S25	S30	S36	S31	T10S		1/4		R62E	R63E	S25	S30
T10S																	
R62E	R63E																
S25	S30																
S36	S31																
T10S																	
1/4																	
R62E	R63E																
S25	S30																

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 10 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor. and deposit the original stone in the mound.</p> <hr/> <p>N. 0°16'50" E., beginning new measurement.</p> <p>1.80 Draw, drains SW.</p> <p>8.00 Top of spur, slopes SW.</p> <p>10.00 Channel, 10 lks. wide, course SW.</p> <p>17.00 Ridge, bears E. and W.</p> <p>31.90 Dry creek, 15 lks. wide, course W.</p> <p>38.769 The cor. of secs. 19, 24, 25 and 30, perpetuated by Timothy J. Wolf, Nevada Professional Land Surveyor, No. 9677, not recorded, monumented with a rebar, 5/8 in. diam., firmly set in mound of stone, 3 ft. base, 1 1/2 ft. high, with aluminum cap mkd. LVVWD S24 S25 PLS 9677, alongside of which is a limestone, 15x9x8 ins., loosely set, mkd. with 2 notches on S. and 4 notches on N. edge.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, over a plastic-encased magnet, and in mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T10S</td></tr> <tr><td>R62E</td><td>R63E</td></tr> <tr><td>S24</td><td>S19</td></tr> <tr><td>S25</td><td>S30</td></tr> </table> <p style="text-align: center;">2005</p> <p>Deposit the rebar and the original stone alongside the stainless steel post.</p> <hr/> <p>N. 0°02'40" E., bet. secs. 19 and 24.</p> <p>Over mountainous land covered with creosote, chaparral and scattered cacti.</p> <p>7.00 Spur, slopes W.</p> <p>32.00 Ravine, drains W.</p> <p>38.115 The 1/4 sec. cor. of secs. 19 and 24, monumented with an unmkd. limestone, 29x15x6 ins., firmly set in a mound of stone, 3 ft. base, 1 ft. high. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p>	T10S		R62E	R63E	S24	S19	S25	S30
T10S									
R62E	R63E								
S24	S19								
S25	S30								

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 10 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>T10S 1/4 R62E R63E S24 S19</p> <p>2007</p> <p>Deposit the unmkd. stone alongside the stainless steel post.</p> <hr/> <p>N. 0°02'20" W., beginning new measurement.</p>
23.50	Spur, slopes W.
38.056	<p>The cor. of secs. 13, 18, 19 and 24, perpetuated by person(s) unknown, monumented with a rebar, 3/4 in. diam., firmly set in a mound of stone, 4 ft. base, 1 1/2 ft. high, alongside of which is a limestone, 11x8x6 ins., loosely set, mkd. with 3 grooves on S. and 3 grooves on N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam. 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p>T10S R62E R63E S13 S18 S24 S19</p> <p>2005</p> <p>Deposit the rebar and the original stone alongside the stainless steel post.</p> <hr/> <p>N. 0°15'40" W., bet. secs. 13 and 18.</p> <p>Over rolling land covered with creosote, chaparral and scattered cacti.</p>
43.809	<p>Point for the 1/4 sec. cor. of secs. 13 and 18, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p>T10S 1/4 R62E R63E S13 S18</p> <p>2006</p>
47.60	Dry wash, 30 lks. wide, drains NW.
78.60	Dry wash, 10 lks. wide, drains SW.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 10 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS									
83.60	Spur, slopes W.								
87.618	<p>The cor. of secs. 7, 12, 13 and 18, perpetuated by R.L. Carpenter, Nevada Professional Land Surveyor No. 2708, not recorded, monumented with a rebar, 3/4 in. diam., firmly set flush with the ground, with aluminum cap mkd. LAPS RLS 2708, alongside of which is a limestone, 15x12x10 ins., loosely set, mkd. with 2 grooves on N. face only.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T10S</td></tr> <tr><td style="text-align: center;">R62E</td><td style="text-align: center;">R63E</td></tr> <tr><td style="text-align: center;">S12</td><td style="text-align: center;">S 7</td></tr> <tr><td style="text-align: center;">S13</td><td style="text-align: center;">S18</td></tr> </table> <p style="text-align: center;">2005</p> <p>Deposit the rebar and the original stone alongside the stainless steel post.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 10 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of the Survey Executed by U.S. Deputy Surveyors W.F. Benson and C.F. Putnam in 1881</p> <hr/> <p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°11'20" W., bet. secs. 25 and 36.</p> <p>Over rolling land covered with creosote, chaparral and scattered cacti.</p>	T10S		R62E	R63E	S12	S 7	S13	S18
T10S									
R62E	R63E								
S12	S 7								
S13	S18								
10.00	Spur, slopes SW.								
16.20	Old highway, 40 lks. wide, bears S. 10 1/2° E., and N. 10 1/2° W., over nearly level land.								
19.278	<p>Point for the E 1/16 sec. cor. of secs. 25 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">E 1/16</td></tr> <tr><td style="text-align: center;">S25</td><td style="text-align: center;">S36</td></tr> <tr><td colspan="2" style="text-align: center;">2006</td></tr> </table>	E 1/16		S25	S36	2006			
E 1/16									
S25	S36								
2006									

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From this corner, a point determined as the E 1/16 sec. cor. of secs. 25 and 36, by Richard J. Baughman, Nevada Professional Land Surveyor No. 2162, monumented with a rebar, 5/8 in. diam., firmly set flush with ground, with aluminum cap mkd. RJ BAUGHMAN RLS 2162, as recorded in Lincoln County, Nevada, Plat Book No. A, Page 83, Inst. No. 50129, bears S. 89°19'50" E., 0.753 chs. dist. This point was determined using improper control and is not utilized in this survey.</p>
23.60	Underground fiber optic cable, parallels highway.
26.10	U.S. Highway No. 93, 40 lks. wide, bears S. 5 1/4° E. and N. 5 1/4° W.
28.40	Underground fiber optic cable, parallels highway.
38.556	<p>The 1/4 sec. cor. of secs. 25 and 36, perpetuated by Richard J. Baughman, Nevada Professional Land Surveyor No. 2162, monumented with a rebar, 5/8 in. diam., projecting 1 in. above the ground, with aluminum cap mkd. RJ BAUGHMAN RLS 2162, as recorded in Lincoln County, Nevada, Plat Book No. A, Page 83, Inst. No. 50129. The original corner stone was not found. This is accepted as a careful and faithful perpetuation of the position of the original corner.</p>
	At the corner point
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T10S R62E S25 1/4 <u> </u> S36</p>
	2006
	Deposit the rebar alongside stainless steel post.
	<p>From this corner, a point determined as the 1/4 sec. cor. of secs. 25 and 36, by Timothy J. Wolf, Nevada Professional Land Surveyor No. 9677, monumented with a rebar, 5/8 in. diam., flush with ground, with aluminum cap mkd. LVVWD PLS 9677, bears N. 48°40' W., 0.011 chs. dist.</p>
	<p>From this corner, a rebar, 3/4 in. diam., firmly set, projecting 1 in. above the ground, with aluminum cap, 3 1/4 in. diam., mkd. LADWP SURVEY POINT R50 L65M RLS 27 08 POWER SYSTEM, bears N. 89°14'00" W., 0.634 chs. dist.</p>
	<p style="text-align: center;">_____</p> <p>N. 89°12'00" W., beginning new measurement.</p>
7.50	Power transmission line, bears S. 8° E. and N. 8° W.
8.60	Powerline road, 20 lks. wide, parallels power transmission line.
16.40	Enter rolling land.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 20.031</p>	<p>The W 1/16 sec. cor. of secs. 25 and 36, determined by Richard J. Baughman, Nevada Professional Land Surveyor No. 2162, monumented with a rebar, 5/8 in. diam., projecting 6 ins. above the ground, with aluminum cap mkd. RJ BAUGHMAN RLS 2162, as recorded in Lincoln County, Nevada, Plat Book No. A, Page 83, Inst. No. 50129. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> $\begin{array}{r} \text{W } 1/16 \quad \frac{\text{S25}}{\text{S36}} \\ \hline 2006 \end{array}$ <p>Deposit the rebar alongside the stainless steel post.</p> <hr/> <p>N. 89°13'30" W., beginning new measurement.</p>
<p>19.994</p>	<p>The cor. of secs. 25, 26, 35 and 36, monumented with a basalt stone, 12x8x8 ins., firmly set in a small mound of stone, mkd. with 1 groove on S. and 1 groove on E. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> $\begin{array}{r} \text{T10S R62E} \\ \frac{\text{S26} \text{S25}}{\text{S35} \text{S36}} \\ \hline 2005 \end{array}$ <p>Deposit the original stone alongside the stainless steel post.</p> <hr/> <p>N. 0°10'10" E., bet. secs. 25 and 26.</p> <p>Over rolling land covered with creosote, chaparral and scattered cacti.</p>
<p>14.00</p>	<p>Spur, slopes E.</p>
<p>15.40</p>	<p>Wash, 200 lks. wide, drains E.</p>
<p>20.097</p>	<p>The S 1/16 sec. cor. of secs. 25 and 26, determined by Richard J. Baughman, Nevada Professional Land Surveyor No. 2162, monumented with a rebar, 5/8 in. diam., firmly set, projecting 1 in. above the ground, with aluminum cap mkd. RJ BAUGHMAN RLS 2162, as recorded in Lincoln County, Nevada, Plat Book No. A, Page 83, Inst. No. 50129. This is accepted as a careful and faithful determination of the position of the corner.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p> <p>15.00</p> <p>20.097</p> <p>1.50</p> <p>40.299</p>	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S26 S25</p> <p style="text-align: center;">2006</p> <p>Deposit the rebar alongside the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°10'10" E., beginning new measurement.</p> <p>Spur, slopes E.</p> <p>The 1/4 sec. cor. of secs. 25 and 26, perpetuated by Richard J. Baughman, Nevada Professional Land Surveyor No. 2162, monumented with a rebar, 5/8 in. diam., firmly set in mound of stone, 3 ft. base, 1 ft. high, with aluminum cap mkd. RJ BAUGHMAN RLS 2162, as recorded in Lincoln County, Nevada, Plat Book No. A, Page 83, Inst. No. 50129, alongside of which is lying a limestone, 15x8x4 ins., dimly mkd. 1/4 on one face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T10S R62E 1/4 S26 S25</p> <p style="text-align: center;">2005</p> <p>Deposit the rebar and the original stone alongside the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°20'50" E., beginning new measurement.</p> <p>Dry wash, 20 lks. wide, drains E.</p> <p>The cor. of secs. 23, 24, 25 and 26, perpetuated by Timothy J. Wolf, Nevada Professional Land Surveyor No. 9677, not recorded, monumented with a rebar, 5/8 in. diam., firmly set in a mound of stone, 3 ft. base, 1/2 ft. high, with aluminum cap mkd. LVVWD 23 24 25 26 PLS 9677, alongside of which is a limestone, 21x8x8 ins., loosely set, mkd. with 2 notches on S. and 1 notch on E. edge.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p>
--	---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">T10S R62E S23 S24 <hr/>S26 S25</p> <p style="text-align: center;">2005</p> <p>Deposit the rebar and the original stone alongside the stainless steel post.</p> <p>From this corner, a rebar, 1/2 in. diam., firmly set flush with ground, bears S. 0°11' W., 1.530 chs. dist. This position is in agreement with the position determined as the cor. of secs. 23, 24, 25 and 26, by Richard J. Baughman, Nevada Professional Land Surveyor No. 2162, as recorded in Lincoln County, Nevada, Plat Book No. A, Page 86, Inst. No. 50690.</p> <hr/> <p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 88°19'20" W., bet. secs. 24 and 25.</p> <p>Over rolling land covered with creosote, chaparral and scattered cacti.</p> <p>19.950 Point for the E 1/16 sec. cor. of secs. 24 and 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">E 1/16 $\frac{S24}{S25}$</p> <p style="text-align: center;">2006</p> <p>25.00 Enter nearly level land.</p> <p>32.40 Underground fiber optic cable, parallels highway.</p> <p>35.00 U.S. Highway No. 93, 40 lks. wide, bears S. 5 1/4° E. and N. 5 1/4° W.</p> <p>37.20 Underground fiber optic cable, parallels highway.</p> <p>39.900 The 1/4 sec. cor. of secs. 24 and 25, monumented with a basalt stone, 16x8x4 ins., firmly set 10 ins. in the ground, mkd. 1/4 on S. face, alongside of which is a rebar, 5/8 in. diam., firmly set, with aluminum cap mkd. RLS 2162.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T10S R62E S24 1/4 $\frac{S24}{S25}$</p> <p style="text-align: center;">2005</p>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Deposit the rebar and the original stone alongside the stainless steel post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <hr/> <p>N. 88°20'40" W., beginning new measurement.</p> <p>9.80 Dry wash, 40 lks. wide, drains S.</p> <p>18.80 Power transmission line, bears S. 8° E. and N. 8° W.</p> <p>19.80 Powerline road, 20 lks. wide, parallels power transmission line.</p> <p>35.00 Enter gently rolling land.</p> <p>39.841 The cor. of secs. 23, 24, 25 and 26.</p> <hr/> <p>N. 0°11'50" W., bet. secs. 23 and 24.</p> <p>Over gently rolling land covered with creosote, chaparral and scattered cacti.</p> <p>17.00 Dry wash, 125 lks. wide, drains S. 85° E.</p> <p>40.130 The 1/4 sec. cor. of secs. 23 and 24, perpetuated by person(s) unknown, monumented with a rebar, 3/4 in. diam., firmly set in mound of stone, 2 ft. base, 1/2 ft. high, alongside of which is a basalt stone, 14x10x6 ins., loosely set, mkd. 1/4 on W. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T10S R62E 1/4 S23 S24 2005</p> <p>Deposit the rebar and the original stone alongside the stainless steel post.</p> <hr/> <p>N. 0°09'40" W., beginning new measurement.</p> <p>2.50 Dry wash, 20 lks. wide drains SE.; over nearly level land.</p> <p>18.40 Dry wash, 30 lks. wide, drains SE.</p> <p>20.145 Point for the N 1/16 sec. cor. of secs. 23 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">N 1/16 S23 S24</p>
	<p style="text-align: center;">2006</p>
40.290	<p>The cor. of secs. 13, 14, 23 and 24, perpetuated by person(s) unknown, monumented with a rebar, 3/4 in. diam., firmly set in a small mound of stone, alongside of which is a limestone, 12x9x8 ins., loosely set, mkd. with 3 grooves on S. and 1 groove on E. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T10S R62E S14 S13 S23 S24</p> <p style="text-align: center;">2005</p> <p>Deposit the rebar and the original stone alongside the stainless steel post.</p> <hr/>
	<p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 88°28'10" W., bet. secs. 13 and 24.</p> <p>Over rolling land covered with creosote, chaparral and scattered cacti.</p>
40.101	<p>The 1/4 sec. cor. of secs. 13 and 24, monumented with a basalt stone, 11x7x5 ins., firmly set in a mound of stone, 3 ft. base, 1 ft. high, mkd. 1/4 on S. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T10S R62E S13 1/4 ——— S24</p> <p style="text-align: center;">2005</p> <p>Deposit the original stone alongside the stainless steel post.</p> <hr/> <p>N. 82°08'30" W., beginning new measurement.</p> <p>Over nearly level land.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
4.20	Underground fiber optic cable, parallels highway.
6.80	U.S. Highway No. 93, 40 lks. wide, bears S. 9 3/4° E. and N. 9 3/4° W.
9.10	Underground fiber optic cable, parallels highway.
29.80	Powerline road, 20 lks. wide, parallels power transmission line.
30.10	Power transmission line, bears S. 8° E. and N. 8° W.
40.239	The cor. secs. 13, 14, 23 and 24.
	N. 0°09'40" W., bet. secs. 13 and 14.
	Over nearly level, gently rolling land covered with creosote, chaparral and scattered cacti.
20.228	Point for the S 1/16 sec. cor. of secs. 13 and 14.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.
	S 1/16 S14 S13 2005
28.50	Dry wash, 10 lks. wide, drains SW.
40.456	The 1/4 sec. cor. of secs. 13 and 14, monumented with a granite stone, 16x10x7 ins., firmly set in mound of stone, 2 ft. base, 1 ft. high, dimly mkd. 1/4 on E. face.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.
	T10S R62E 1/4 S14 S13 2005
	Deposit the original stone alongside the stainless steel post.
	N. 0°22'00" E., beginning new measurement.
25.50	Powerline road, 20 lks. wide, parallels power transmission line.
29.50	Power transmission line, bears S. 8° E. and N. 8° W.
40.291	The cor. of secs. 11, 12, 13 and 14, monumented with a limestone, 17x9x6 ins., firmly set in a mound of stone, 3 ft. base, 1 ft. high, plainly mkd. with an X on top, 1 groove on E. face and dimly mkd. with grooves on S. face.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T10S</td> <td>R62E</td> </tr> <tr> <td>S11</td> <td>S12</td> </tr> <tr> <td>S14</td> <td>S13</td> </tr> </table> <p style="text-align: center;">2005</p> <p>Deposit the original stone alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°39'30" W., bet. secs. 12 and 13.</p> <p>Over gently rolling land covered with creosote, chaparral and scattered cacti.</p> <p>15.00 Dry wash, 20 lks. wide, drains SW.</p> <p>39.685 The 1/4 sec. cor. of secs. 12 and 13, perpetuated by person(s) unknown, monumented with a rebar, 3/4 in. diam., firmly set in mound of stone, 2 ft. base, 1/2 ft. high, alongside of which is a limestone, 8x8x5 ins., loosely set, mkd. 1/4 on N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T10S</td> <td>R62E</td> </tr> <tr> <td>1/4</td> <td>S12</td> </tr> <tr> <td></td> <td>S13</td> </tr> </table> <p style="text-align: center;">2005</p> <p>Deposit the rebar and the original stone alongside the stainless steel post.</p> <hr/> <p>S. 89°54'10" W., beginning new measurement.</p> <p>19.40 Underground fiber optic cable, bears S. 10 1/4° E. and N. 10 1/4° W.</p> <p>21.30 U.S. Highway No. 93, 40 lks. wide, bears S. 9 3/4° E. and N. 9 3/4° W.</p> <p>23.30 Underground fiber optic cable, parallels highway.</p> <p>39.706 The cor. of secs. 11, 12, 13 and 14.</p> <hr/>	T10S	R62E	S11	S12	S14	S13	T10S	R62E	1/4	S12		S13
T10S	R62E												
S11	S12												
S14	S13												
T10S	R62E												
1/4	S12												
	S13												

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	From the cor. of secs. 23, 24, 25 and 26.
	N. 87°05'10" W., bet. secs. 23 and 26.
	Over rolling land covered with creosote, chaparral and scattered cacti.
40.789	The 1/4 sec. cor. of secs. 23 and 26, monumented with a basalt stone, 11x8x7 ins., firmly set 6 ins. in the ground, mkd. 1/4 on S. face, with a mound of stone, 2 ft. base, 1 ft. high, W. of cor.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.
	$\begin{array}{r} \text{T10S R62E} \\ \text{S23} \\ 1/4 \frac{\quad}{\quad} \\ \text{S26} \end{array}$
	2005
	Deposit the original stone alongside the stainless steel post.
	N. 89°59'40" W., beginning new measurement.
39.714	The cor. of secs. 22, 23, 26 and 27, monumented with a mound of stone, 3 ft. base, 1 1/2 ft. high. No marked stone found. This is accepted as the best available evidence of the position of the original corner.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.
	$\begin{array}{r} \text{T10S R62E} \\ \text{S22} \text{S23} \\ \hline \text{S27} \text{S26} \end{array}$
	2007
	N. 0°37'00" E., bet. secs. 22 and 23.
	Over mountainous land covered with chaparral and scattered cacti.
9.50	Spur, slopes E.
32.00	Ravine, drains NE.
39.120	The 1/4 sec. cor. of secs. 22 and 23, monumented with a basalt stone, 18x11x6 ins., firmly set 8 ins. in the ground, mkd. 1/4 on E. face, with a mound of stone, 2 ft. base, 1 1/2 ft. high, S. of cor.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T10S R62E 1/4 S22 S23</p> <p style="text-align: center;">2005</p> <p>Deposit the original stone alongside the stainless steel post.</p> <hr/> <p>N. 0°37'20" W., beginning new measurement.</p> <p>19.00 Spur, slopes NE.</p> <p>35.00 Ravine, drains NE.</p> <p>39.600 The cor. of secs. 14, 15, 22 and 23, monumented with a porphyry stone, 12x8x3 ins., firmly set in a mound of stone, 3 ft. base, 1 ft. high, mkd. with 3 grooves on S. and 2 grooves on E. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T10S R62E S14 S13 S23 S24</p> <p style="text-align: center;">2007</p> <p>Deposit the original stone alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>N. 89°50'30" W., bet. secs. 14 and 23.</p> <p>Over nearly level land covered with creosote, chaparral and scattered cacti.</p> <p>20.125 Point for the E 1/16 sec. cor. of secs. 14 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">E 1/16 $\frac{S14}{S23}$</p> <p style="text-align: center;">2005</p> <p>23.00 Enter rolling land.</p>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.250	<p>The 1/4 sec. cor. of secs. 14 and 23, monumented with a limestone, 12x9x5 ins., firmly set in mound of stone, 2 ft. base, 1 ft. high, mkd. 1/4 on S. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T10S R62E S14 1/4 <u> </u> S23</p> <p style="text-align: center;">2005</p> <p>Deposit the original stone alongside the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 89°37'30" W., beginning new measurement.</p>
16.00	Dry wash, 20 lks. wide, drains SE.
27.00	Low spur, slopes NE.
35.80	Dry wash, 50 lks. wide, drains NE.
39.944	The cor. of secs. 14, 15, 22 and 23.
	<hr/> <p>N. 0°14'30" E., bet. secs. 14 and 15.</p> <p>Over rolling land covered with chaparral and scattered cacti.</p>
8.30	Spur, slopes NE.
39.60	Dry wash, 30 lks. wide, drains E.
40.594	<p>The 1/4 sec. cor. of secs. 14 and 15, monumented with a lava stone, 14x9x8 ins., firmly set in a mound of stone, 3 ft. base, 1 1/2 ft. high, dimly mkd. 1/4 on W. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T10S R62E 1/4 S15 S14</p> <p style="text-align: center;">2005</p> <p>Deposit the original stone alongside the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°37'00" W., beginning new measurement.						
8.50	Wash, 30 lks. wide, drains E.						
39.536	The cor. of secs. 10, 11, 14 and 15, monumented with a granite stone, 23x16x9 ins., firmly set in a mound of stone, 2 ft. base, 1 ft. high, mkd. with 4 grooves on S. and 2 grooves on E. face. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd. <div style="text-align: center;"> <table border="1"> <tr><td>T10S</td><td>R62E</td></tr> <tr><td>S10</td><td>S11</td></tr> <tr><td>S15</td><td>S14</td></tr> </table> <p>2005</p> </div> Deposit the original stone alongside the stainless steel post. <hr/>	T10S	R62E	S10	S11	S15	S14
T10S	R62E						
S10	S11						
S15	S14						
	From the cor. of secs. 11, 12, 13 and 14. S. 89°49'30" W., bet. secs. 11 and 14. Over nearly level, gently rolling land covered with creosote, chaparral and scattered cacti.						
1.50	Power transmission line, bears S. 8° E. and N. 8° W.						
2.20	Powerline road, 20 lks. wide, parallels power transmission line.						
36.20	Pahranaagat Wash, 40 lks. wide, drains SE.						
40.289	Point for the 1/4 sec. cor. of secs. 11 and 14, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over plastic-encased magnet, with brass cap mkd. <div style="text-align: center;"> <table border="1"> <tr><td>T10S</td><td>R62E</td></tr> <tr><td>1/4</td><td>S11</td></tr> <tr><td></td><td>S14</td></tr> </table> <p>2005</p> </div>	T10S	R62E	1/4	S11		S14
T10S	R62E						
1/4	S11						
	S14						
80.578	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor. The cor. of secs. 10, 11, 14 and 15. <hr/> N. 0°51'40" W., bet. secs. 10 and 11. Over rolling land covered with creosote, chaparral and scattered cacti.						

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
14.60	Dry wash, 20 lks. wide, drains NE.
32.50	Ridge, bears NE. and SW.
37.60	Dry wash, 60 lks. wide, drains NE.
40.307	<p>The 1/4 sec. cor. of secs. 10 and 11, monumented with an unmkd. porphyry stone, 10x9x8 ins., firmly set in a mound of stone, 3 ft. base, 1 1/2 ft. high. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T10S R62E 1/4 S10 S11 2005</p> <p>Deposit the unmkd. stone alongside the stainless steel post.</p> <hr/> <p>N. 0°20'30" W., beginning new measurement.</p>
3.00	Dry wash, 10 lks. wide, drains NE.
23.00	Ridge, bears NE. and SW.
27.00	Dry wash, 20 lks. wide, drains NE.
30.00	Spur, slopes NE.
36.20	Dry wash, 20 lks. wide, drains NE.
40.767	<p>The cor. of secs. 2, 3, 10 and 11, monumented with an unmkd. porphyry stone, 12x10x8 ins., firmly set in a mound of stone, 3 ft. base, 1 1/2 ft. high. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T10S R62E S 3 S 2 S10 S11 2005</p> <p>Deposit the unmkd. stone alongside the stainless steel post.</p> <hr/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°14'00" W., bet. secs. 2 and 3. Over rolling land covered with creosote, chaparral and scattered cacti.
10.50	Spur, slopes NE.
22.00	Dry wash, 100 lks. wide, drains NE.
40.305	The 1/4 sec. cor. of secs. 2 and 3, monumented with an unmkd. porphyry stone, 14x8x8 ins., firmly set in a mound of stone, 3 ft. base, 1 1/2 ft. high. This is accepted as the best available evidence of the position of the original corner. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd. T10S R62E 1/4 S 3 S 2 2005 Deposit the unmkd. stone alongside the stainless steel post. <hr/>
	N. 0°22'30" E., beginning new measurement.
9.30	Dry wash, 20 lks. wide, drains SE.
16.50	Top of low ridge, bears SE. and NW.
22.50	Dry wash, 30 lks. wide, drains SE.
40.192	The cor. of secs. 2 and 3, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set in a collar of stone, with brass cap mkd. as described in the field notes of the north boundary of T. 10 S., R. 62 E., executed concurrently under this same Group. From this corner, the cor. of secs. 34 and 35, T. 9 S., R. 62 E., monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. as described in the field notes of the south boundary of T. 9 S., R. 62 E., executed under Group No. 49, bears S. 89°29'20" E., 3.066 chs. dist. <hr/>
	SUBDIVISION OF SECTION 13, T. 10 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA <hr/>
	From the 1/4 sec. cor. of secs. 13 and 24. N. 0°00'10" W., on the N-S center line of sec. 13.
22.172	Point for the C-S 1/16 sec. cor. of sec. 13.

SUBDIVISION OF SECTION 13,
T. 10 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;"> $\begin{array}{c} C \\ S\ 1/16\ \ S13 \\ C \end{array}$ </p> <p style="text-align: center;">2006</p>
44.344	<p>Point for the center 1/4 sec. cor. of sec. 13, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;"> T10S R62E C 1/4 S13 </p> <p style="text-align: center;">2006</p>
86.311	<p>The 1/4 sec. cor. of secs. 12 and 13.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp.</p> <p>N. 87°41'40" W., on the E-W center line of sec. 13.</p>
1.10	Spur, slopes NW.
39.918	The center 1/4 sec. cor. of sec. 13.
52.00	Underground fiber optic cable, bears S. 10 1/4° E. and N. 10 1/4° W.
54.20	U.S. Highway No. 93, 40 lks. wide, bears S. 9 3/4° E. and N. 9 3/4° W.
56.20	Underground fiber optic cable, parallels highway.
75.60	Power transmission line, bears S. 8° E. and N. 8° W.
76.00	Powerline road, 20 lks. wide, parallels power transmission line.
79.920	The 1/4 sec. cor. of secs. 13 and 14.
	<hr/> <p>From the C-S 1/16 sec. cor. of sec. 13.</p> <p>N. 84°54'50" W., on the E-W center line of the SW1/4 of sec. 13.</p>
8.00	Underground fiber optic cable, bears S. 10 1/4° E. and N. 10 1/4° W.
10.50	U.S. Highway No. 93, 40 lks. wide, bears S. 9 3/4° E. and N. 9 3/4° W.
12.50	Underground fiber optic cable, parallels highway.

SUBDIVISION OF SECTION 13,
T. 10 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
32.90	Power transmission line, bears S. 8° E. and N. 8° W.
37.90	Powerline road, 20 lks. wide, bears NE. and SW.
40.074	The S 1/16 sec. cor. of secs. 13 and 14.
<hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 14, T. 10 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>	
	From the 1/4 sec. cor. of secs. 14 and 23.
	N. 0°04'10" E., on the N-S center line of sec. 14.
20.301	Point for the C-S 1/16 sec. cor. of sec. 14. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	$\begin{array}{c} C \\ S\ 1/16\ S14 \\ C \end{array}$
	2005
40.10	Dry wash, 30 lks. wide, drains NE.
40.602	Point for the center 1/4 sec. cor. of sec. 14, at intersection with the E-W center line. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	$\begin{array}{c} T10S\ R62E \\ C\ 1/4\ S14 \end{array}$
	2005
59.00	Dry wash, 30 lks. wide, drains SE.
80.513	The 1/4 sec. cor. of secs. 11 and 14.
<hr/>	
	From the 1/4 sec. cor. of secs. 13 and 14.
	N. 89°37'50" W., on the E-W center line of sec. 14.
20.042	Point for the C-E 1/16 sec. cor. of sec. 14. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.
	$\begin{array}{c} E\ 1/16 \\ C\ \hline S14 \\ C \end{array}$
	2005

SUBDIVISION OF SECTION 14,
T. 10 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
21.40	Pahrnagat Wash, 30 lks. wide, drains SE.
24.00	Dry wash, 30 lks. wide, drains SE.
40.084	The center 1/4 sec. cor. of sec. 14.
79.902	The 1/4 sec. cor. of secs. 14 and 15.
	<hr/>
	From the E 1/16 sec. cor. of secs. 14 and 23.
	N. 0°02'50" W., on the N-S center line of the SE1/4 of sec. 14.
20.265	Point for the SE 1/16 sec. cor. of sec. 14, at intersection with the E-W center line of the SE1/4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.
	SE 1/16 S14
	2005
24.10	Pahrnagat Wash, 20 lks. wide, drains SE.
40.530	The C-E 1/16 sec. cor. of sec. 14.
	<hr/>
	From the S 1/16 sec. cor. of secs. 13 and 14.
	N. 89°44'20" W., on the E-W center line of the SE1/4 of sec. 14.
19.30	Pahrnagat Wash, 20 lks. wide, drains SE.
20.083	The SE 1/16 sec. cor. of sec. 14.
40.166	The C-S 1/16 sec. cor. of sec. 14.
	<hr/>
	SUBDIVISION OF SECTION 23, T. 10 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA
	<hr/>
	From the 1/4 sec. cor. of secs. 23 and 26.
	N. 0°10'00" E., on the N-S center line of sec. 23.
38.596	Point for the center 1/4 sec. cor. of sec. 23, at intersection with the E-W center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	T10S R62E C 1/4 S23
	2006

SUBDIVISION OF SECTION 23,
T. 10 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
52.30	Dry wash, 30 lks. wide, drains SE.
58.526	Point for the C-N 1/16 sec. cor. of sec. 23. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd. <div style="text-align: center;"> $\begin{array}{c} C \\ N\ 1/16 \left S23 \\ C \end{array}$ <p>2006</p> </div>
64.40	Dry wash, 200 lks. wide, drains SE.
78.456	The 1/4 sec. cor. of secs. 14 and 23. <hr/>
	From the 1/4 sec. cor. of secs. 23 and 24. N. 89°14'10" W., on the E-W center line of sec. 23.
20.243	Point for the C-E 1/16 sec. cor. of sec. 23. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd. <div style="text-align: center;"> $\begin{array}{c} E\ 1/16 \\ C \text{---} C \\ S23 \end{array}$ <p>2006</p> </div>
40.486	The center 1/4 sec. cor. of sec. 23.
67.40	Dry wash, 30 lks. wide, drains NE.
79.891	The 1/4 sec. cor. of secs. 22 and 23. <hr/>
	From the C-E 1/16 sec. cor. of sec. 23. N. 0°00'10" E., on the N-S center line of the NE1/4 of sec. 23.
13.20	Dry wash, 30 lks. wide, drains E.
20.038	Point for the NE 1/16 sec. cor. of sec. 23, at intersection with the E-W center line of the NE1/4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd. <div style="text-align: center;"> <p>NE 1/16 S23</p> <p>2006</p> </div>

SUBDIVISION OF SECTION 23,
T. 10 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
30.80	Dry wash, 40 lks. wide, drains ENE.
40.076	The E 1/16 sec. cor. of secs. 14 and 23.
	<hr/>
	From the N 1/16 sec. cor. of secs. 23 and 24.
	N. 89°32'20" W., on the E-W center line of the NE1/4 of sec. 23.
0.80	Dry wash, 30 lks. wide, drains SE.
20.184	The NE 1/16 sec. cor. of sec. 23.
40.368	The C-N 1/16 sec. cor. of sec. 23.
	<hr/>
	SUBDIVISION OF SECTION 24, T. 10 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA
	<hr/>
	From the 1/4 sec. cor. of secs. 24 and 25.
	N. 0°09'20" W., on the N-S center line of sec. 24.
27.85	Underground fiber optic cable, bears S. 5 1/4° E. and N. 5 1/4° W.
38.20	U.S. Highway No. 93, 40 lks. wide, bears S. 9 3/4° E. and N. 9 3/4° W.
52.85	Underground fiber optic cable, parallels highway.
76.075	The 1/4 sec. cor. of secs. 13 and 24.
	<hr/>
	SUBDIVISION OF SECTION 25, T. 10 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA
	<hr/>
	From the 1/4 sec. cor. of secs. 25 and 36.
	N. 0°07'30" E., on the N-S center line of sec. 25.
20.174	Point for the C-S 1/16 sec. cor. of sec. 25.
	NOT MONUMENTED
40.346	Point for the center 1/4 sec. cor. of sec. 25, at intersection with the E-W center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. below the surface of the ground, with brass cap mkd.
	T10S R62E C 1/4 S25
	2008

SUBDIVISION OF SECTION 25,
T. 10 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 42°16'00" E., 40.40 ft. with brass cap mkd. RM C1/4 S25 40.4 FT TO COR 2008 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 33°48'40" E., 44.2 ft. with brass cap mkd. RM C1/4 S25 44.2 FT TO COR 2008 and an arrow pointing to the corner.</p>
79.892	<p>The 1/4 sec. cor. of secs. 24 and 25.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 25 and 30, on the E. bdy. of the Tp.</p> <p>N. 89°26'30" W., on the E-W center line of sec. 25.</p>
19.908	<p>The C-E 1/16 sec. of sec. 25, determined by Richard J. Baughman, Nevada Professional Land Surveyor No. 2162, monumented with a rebar, 5/8 in. diam., firmly set, projecting 5 ins. above the ground, with aluminum cap mkd. RJ BAUGHMAN RLS 2162, as recorded in Lincoln County, Nevada, Plat Book No. A, Page 86, Inst. No. 50690. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> $\begin{array}{c} \text{E } 1/16 \\ \text{C} \text{---} \text{C} \\ \text{S25} \\ \\ 2006 \end{array}$ <p>Deposit the rebar alongside the stainless steel post.</p> <hr/> <p>N. 89°25'50" W., beginning new measurement.</p>
8.70	Underground fiber optic cable, parallels highway.
11.30	U.S. Highway No. 93, 40 lks. wide, bears S. 5 1/4° E. and N. 5 1/4° W.
11.50	Underground fiber optic cable, parallels highway.
19.875	The center 1/4 sec. cor. of sec. 25.
33.10	Power transmission line, bears S. 8° E. and N. 8° W.

SUBDIVISION OF SECTION 25,
T. 10 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
34.30	Powerline road, 20 lks. wide, parallels power transmission line.
39.870	Point for the C-W 1/16 sec. cor. of sec. 25.
	NOT MONUMENTED
59.865	The 1/4 sec. cor. of secs. 25 and 26.
	<hr/>
	From the C-E 1/16 sec. cor. of sec. 25.
	N. 0°13'30" E., on the N-S center line of the NE1/4 of sec. 25.
25.60	Spur, slopes W.
39.159	The E 1/16 sec. cor. of secs. 24 and 25.
	<hr/>
	From the E 1/16 sec. cor. of secs. 25 and 36.
	N. 0°58'40" E., on the N-S center line of the SE1/4 of sec. 25.
18.35	Old highway, 40 lks. wide, bears S. 10 1/2° E. and N. 10 1/2° W.
40.428	The C-E 1/16 sec. cor. of sec. 25.
	<hr/>
	From the W 1/16 sec. cor. of secs. 25 and 36.
	N. 0°09'30" E., on the N-S center line of the SW1/4 of sec. 25.
20.139	The SW 1/16 sec. cor. of sec. 25, determined by Richard J. Baughman, Nevada Professional Land Surveyor No. 2162, monumented with a rebar, 5/8 in. diam., firmly set, projecting 6 ins. above the ground, with aluminum cap mkd. RJ BAUGHMAN RLS 2162, as recorded in Lincoln County, Nevada, Plat Book No. A, Page 83, Inst No. 50129. This is accepted as a careful and faithful determination of the position of the corner.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	SW 1/16 S25
	2006
	Deposit the rebar alongside the stainless steel post.
	<hr/>
	N. 0°11'30" E., beginning new measurement.
20.126	The point for the C-W 1/16 sec. cor. of sec. 25.
	<hr/>

SUBDIVISION OF SECTION 25,
T. 10 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the point for the C-S 1/16 sec. cor. of sec. 25.</p> <p>N. 89°17'40" W., on the E-W center line of the SW1/4 of sec. 25.</p> <p>9.80 Power transmission line, bears S. 8° E. and N. 8° W.</p> <p>11.30 Powerline road, 20 lks. wide, bears SSE and NNW.</p> <p>20.019 The SW 1/16 sec. cor. of sec. 25.</p> <hr/> <p>N. 89°20'50" W., beginning new measurement.</p> <p>19.988 The S 1/16 sec. cor. of secs. 25 and 26.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The land encompassed in this survey is located in Lincoln County, Nevada, about 70 miles north of the City of Las Vegas, Nevada. The area drains southeasterly and the average elevation is about 3000 feet above sea level. Most of the area surveyed varies from rolling to nearly level land, covered with creosote, chaparral and cacti with very little grass. No mineral formations of consequence were noted during the survey.</p> <hr/>
--------	--

UNITED STATES
DEPARTMENT OF INTERIOR
BUREAU OF LAND MAAGEMENT

FIELD ASSISTANTS

Steven E. Dagitz	Land Surveyor (Student Trainee)
Derrick J. Rader	Supervisory Range Technician
Antwan R. Dickson	Surveying Technician
David J. Roderiques	Surveying Technician
David L. Schroeder	Survey Aid

CERTIFICATE OF SURVEY

I, Don R. Aschenbach, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 12th day of July, 2005, I have dependently resurveyed a portion of the east boundary and a portion of the subdivisional lines, and subdivided certain sections, Township 10 South, Range 62 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

November 21, 2008
(Date)

Don R. Aschenbach
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of the dependent resurvey of a portion of the east boundary and a portion of the subdivisional lines, and the subdivision of certain sections, Township 10 South, Range 62 East, Mount Diablo Meridian, Nevada, executed by Don R. Aschenbach, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

December 2, 2008
(Date)

David D. Moran
(Chief Cadastral Surveyor, Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above described surveys in T. 10 S., R. 62 E., M.D.M., Nevada, is a true copy of the original field notes.~~

~~_____~~
(Date)

~~_____~~
(Chief Cadastral Surveyor, Nevada)