

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

PORTIONS OF THE SOUTH AND NORTH BOUNDARIES

AND

A PORTION OF THE SUBDIVISIONAL LINES,
AND THE SUBDIVISION OF SECTIONS 4, 9, 16, 27 AND 33,
TOWNSHIP 11 SOUTH, RANGE 47 EAST,
OF THE MOUNT DIABLO MERIDIAN,
IN THE STATE OF NEVADA

EXECUTED BY

Richard A. Zaninovich, Cadastral Surveyor

Clay W. Morrow, Surveying Technician

Under Special Instructions dated January 26, 1998,
and approved January 26, 1998,
which provided for the surveys included under Group No. 772,
and Assignment Instructions dated January 26, 1998, and January 22, 2004.

Survey commenced January 26, 1998

Survey completed April 6, 2005

INDEX DIAGRAM

TOWNSHIP 11 SOUTH, RANGE 47 EAST, MOUNT DIABLO MERIDIAN, NEVADA

6	5	5 23 4 21	4 16 3	2	1
7	8	9 21	14 10	11	12
18	17	16 20 19	14 15	14	13
19	20	21 18	13 22 12	23	24
30	29	28 17	11 27 11	8 26	25
31	32 3	16 33 1	10 34	35	36

Subdivision of Section 4 Pages 24 - 26
 Subdivision of Section 9 Pages 26 - 28
 Subdivision of Section 16 Pages 28 - 29
 Subdivision of Section 27 Pages 29 - 31
 Subdivision of Section 33 Pages 31 - 34

TOWNSHIP 11 SOUTH, RANGE 47 EAST, MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p>	<p>The following field notes are those of the dependent resurvey of portions of the south and north boundaries and a portion of the subdivisional lines, and the subdivision of sections 4, 9, 16, 27 and 33, T. 11 S., R. 47 E., Mount Diablo Meridian, Nevada.</p> <p>The boundaries and subdivisional lines were surveyed by U.S. Deputy Surveyor O.E. Brashears in 1906. The north boundary was resurveyed by U.S. Deputy Surveyor A.B. Rich in 1909; during this resurvey corners were set which refer to T. 10 S., only.</p> <p>Before restoring the corners, the lines of the original surveys were retraced and diligent search made for any evidence of the original corners and other calls of the original field note record.</p> <p>The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.</p> <p>The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and Special Instructions for Group No. 772, dated January 26, 1998.</p> <p>Measurements were made with Trimble 4400 and 5700 GPS receivers. The mean bearings of the lines and horizontal equivalents of ground distances only are entered in the field notes.</p> <p>The geographic position of the 1/4 section corner of sections 21 and 22, is at Latitude 36°57'57.897" N. and Longitude 116°42'58.223" W. (NAD 83), as determined by a GPS tie made to National Geodetic Survey control (formerly U.S.C. & G.S. triangulation) station "HOT SPRING", located in section 21.</p> <p>The mean magnetic declination is 15° E., as shown on U.S.G.S. quadrangle map "BEATTY MTN., NEV." dated 1987.</p> <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY, T. 11 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of the Survey Executed by O.E. Brashears, U.S. Deputy Surveyor, in 1906</p> <hr/> <p>From the cor. of secs. 3, 4, 33 and 34 on the S. bdy. of the Tp., perpetuated by Kenneth L. Haskew, Nevada Professional Land Surveyor No. 3849, in 1996, monumented with a PVC post, 2 ins. diam., set in a mound of stone, with aluminum cap mkd. "T11S R47E 33 34 4 3 PLS 3849", as recorded in Nye County, Nevada, Parcel Map 410299. A basalt stone, 16x10x8 ins., mkd. with 3 notches on an edge and 3 notches on opposite edge is lying alongside the mound of stone. This is accepted as a careful and faithful perpetuation of position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
---------------	--

252

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 11 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<div style="text-align: center;"> T11S R47E S33 S34 <hr style="width: 50%; margin: 0 auto;"/> S 4 S 3 T12S 1998 </div> <p>Deposit the original stone and PVC post alongside the stainless steel post.</p> <p>Raise a mound of stone west of the corner.</p> <p>N. 89°11'40" W., bet. secs. 4 and 33.</p>
20.067	A rebar, 1/2 in. diam., with an aluminum cap mkd. E 1/16 S33 S4 RLS 3849; this rebar was set by Kenneth L. Haskew, Nevada Professional Land Surveyor No. 3849, in 1989, as shown on Parcel Map 232114, recorded in Nye County, Nevada.
40.100	<p>The 1/4 sec. cor. of secs. 4 and 33, monumented with a basalt stone, 14x12x8 ins., mkd. 1/4 on the north face, and a mound of stone north of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> T11S R47E S33 1/4 — S 4 T12S 1998 </div> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>S. 89°45'10" W., beginning new measurement.</p>
20.098	<p>Point for the W 1/16 sec. cor. of secs. 4 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> S33 W 1/16 — S 4 1998 </div> <p>Raise a mound of stone north of the corner.</p>
34.00	Powerline, NE-SW.
38.30	U.S. Highway No. 95, NE-SW.

CHAINS

The cor. of secs. 4, 5, 32 and 33, monumented with an iron rod, 1/2 in. diam., 18 ins. long, firmly set in a mound of stone, 3 ft. diam. This iron rod is in agreement with the position as shown on Parcel Map File No. 179091, by Ben Lewis, Nevada Professional Land Surveyor No. 1553, in 1986, and Parcel Map File No. 254116 by Wallace T. Boundy, Nevada Professional Land Surveyor No. 2518, recorded in Nye County, Nevada and is accepted as the best available evidence of the position of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet and in a collar of stone, with brass cap mkd.

$$\begin{array}{c} \text{S } 5 \mid \text{S } 4 \\ \text{T12S} \end{array}$$

Deposit the iron rod inside the stainless steel post.

Powerline, NE-SW.

Point for the E 1/16 sec. cor. of secs. 5 and 32.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

1998

Raise a mound of stone north of the corner.

The 1/4 sec. cor. of secs. 5 and 32, monumented with a basalt stone, 14x10x8 ins. (Record, 14x12x12 ins.), mkd. 1/4 on the north face, and a mound of stone north of the corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

T11S R47E
S32
1/4 —
S 5
T12S

1998

254

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 11 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p> <p>40.424</p>	<p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr/> <p>S. 89°55'40" W., beginning new measurement.</p> <p>The cor. of secs. 5, 6, 31 and 32, perpetuated by Lisle Lowe, Nevada Professional Land Surveyor No. 8423, in 1996, monumented with a rebar, 5/8 in. diam., with plastic cap mkd. RLS 8423, with a basalt stone, 20x14x6 ins., mkd. with 4 notches on the east and 1 notch on the south edges, set alongside and in a mound of stone, as recorded in Nye County Nevada, Record of Survey 411077.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td>T11S</td><td>R47E</td></tr> <tr><td>S31</td><td>S32</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 6</td><td>S 5</td></tr> <tr><td colspan="2">T12S</td></tr> </table> <p>2004</p> </div> <p>Deposit the mkd. stone alongside the stainless steel post, insert the rebar inside the stainless steel post and raise a mound of stone west of the corner.</p> <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY, T. 11 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of the Survey Executed by O.E. Brashears, U.S. Deputy Surveyor, in 1906, and the Resurvey Executed by A.B. Rich, U.S. Deputy Surveyor, in 1909</p> <hr/> <p>From the 1/4 sec. cor. of sec. 3 only, on the N. bdy. of the Tp., monumented with a basalt stone, 12x8x6 ins., mkd. 1/4 on the north face and a mound of stone north of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, over a plastic-encased magnet and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td>T10S</td><td>R47E</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>1/4</td><td>S3</td></tr> <tr><td colspan="2">T11S R47E</td></tr> </table> <p>2004</p> </div> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <p>S. 89°43'00" W., on the N. bdy. of sec. 3.</p>	T11S	R47E	S31	S32	<hr/>		S 6	S 5	T12S		T10S	R47E	<hr/>		1/4	S3	T11S R47E	
T11S	R47E																		
S31	S32																		
<hr/>																			
S 6	S 5																		
T12S																			
T10S	R47E																		
<hr/>																			
1/4	S3																		
T11S R47E																			

255

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 11 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p> <p>38.730</p>	<p>The cor. of secs. 33 and 34 only, T. 10 S., R. 47 E., monumented with a basalt stone, 18x6x4 ins. (Record, 14x12x10 ins.), mkd. with 3 notches on the east and west edges, and a mound of stone west of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td>T10S</td><td>R47E</td></tr> <tr><td>S33</td><td>S34</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td colspan="2">S 3</td></tr> <tr><td colspan="2">T11S R47E</td></tr> </table> <p>2004</p> </div> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <p>From this corner a rebar, 1/2 in. diam., with plastic cap, 1 in. diam., mkd. RLS 1553, set in the mound of stone west of the corner, bears S. 67°53' W., 0.036 chs. dist.</p>	T10S	R47E	S33	S34	<hr/>		S 3		T11S R47E	
T10S	R47E										
S33	S34										
<hr/>											
S 3											
T11S R47E											
<p>40.120</p>	<p>The cor. of secs. 3 and 4 only, on the N. bdy. of the Tp., monumented with a basalt stone, 12x10x8 ins., mkd. with 3 notches on the east and west edges, and a mound of stone west of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td colspan="2">T10S R47E</td></tr> <tr><td colspan="2">S33</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 4</td><td>S 3</td></tr> <tr><td colspan="2">T11S R47E</td></tr> </table> <p>1998</p> </div> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr/> <p>S. 89°35'50" W., on the N. bdy. of sec. 4.</p>	T10S R47E		S33		<hr/>		S 4	S 3	T11S R47E	
T10S R47E											
S33											
<hr/>											
S 4	S 3										
T11S R47E											
<p>18.616</p>	<p>Point for the E 1/16 sec. cor. of sec. 33 only, T. 10 S., R. 47 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td colspan="2">T10S R47E</td></tr> <tr><td colspan="2">E 1/16 S33</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td colspan="2">T11S R47E</td></tr> </table> <p>2004</p> </div>	T10S R47E		E 1/16 S33		<hr/>		T11S R47E			
T10S R47E											
E 1/16 S33											
<hr/>											
T11S R47E											

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 11 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From this corner a rebar, 1/2 in. diam., with plastic cap mkd. RLS 1553, located at the corner of fences bearing west and north, bears S. 81°58' W., 0.051 chs. dist. This position was determined using improper control and is not utilized in this survey.</p>
34.40	Abandoned Railroad grade, bears N. 30° W. and S. 30° E.
38.622	<p>Point for the 1/4 sec. cor. of sec. 33 only, T. 10 S., R. 47 E., at proportionate distance, there is no remaining evidence of the original corner. Point falls on a basalt stone, 13x8x6 ins., no mks. visible.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T10S R47E 1/4 S33</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">T11S R47E</p> <p style="text-align: center;">2004</p> <p>Bury unmarked stone alongside stainless steel post.</p> <p>From this corner a rebar, 1/2 in. diam., with plastic cap, 1 in. diam., mkd. RLS 1553, located at the corner of fences bearing east and north, bears S. 87°45' W., 0.059 chs. dist. This position was determined using improper control and is not utilized in this survey.</p>
40.222	<p>Point for the 1/4 sec. cor. of sec. 4 only, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T10S R47E</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">1/4 S4 T11S R47E</p> <p style="text-align: center;">2004</p> <p>Raise a mound of stone 3 ft. base, 2 1/2 ft. high, south of the corner.</p>
49.50	Graded road, NE-SW.
53.60	Powerline, NE-SW.
58.667	<p>The W 1/16 sec. cor. of sec. 33 only, T. 10 S., R. 47 E., determined by Kenneth L. Haskew, Nevada Professional Land Surveyor No. 3849, in 1982, monumented with a rebar, 1/2 in. diam., firmly set projecting 6 ins. above the ground, with an aluminum cap mkd. HASKEW ENG RLS 3849, as recorded in Nye County, Nevada, Record of Survey 61094. This is accepted as a careful and faithful determination of the corner position.</p> <p>At the corner point</p>

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 11 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T10S R47E W 1/16 S33 <hr/>T11S R47E 2004</p> <p>Insert the rebar inside the stainless steel post.</p> <p>59.40 Powerline, NW-SE.</p> <p>60.318 The W 1/16 sec. cor. of sec. 4 only, determined by Kenneth L. Haskew, Nevada Professional Land Surveyor No. 3849, in 1982, monumented with a rebar, 1/2 in. diam., firmly set, projecting 6 ins. above the ground, with an aluminum cap mkd. HASKEW ENG RLS 3849, as recorded in Nye County, Nevada, Record of Survey 61094. This is accepted as a careful and faithful determination of the corner position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T10S R47E <hr/>W 1/16 S4 T11S R47E 2004</p> <p>Insert the rebar inside the stainless steel post.</p> <p style="text-align: center;"><hr/></p> <p>S. 89°35'50" W., beginning new measurement.</p> <p>11.30 Powerline, NW-SE.</p> <p>14.00 U.S. Highway No. 95, NW-SE.</p> <p>18.394 The cor. of secs. 32 and 33 only, T. 10 S., R. 47 E., monumented with a basalt stone, 15x10x6 ins., mkd. with 4 notches the east and 2 notches on the west edges, and a mound of stone west of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T10S R47E S32 S33 <hr/>S 4 T11S R47E 2004</p>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 11 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

20.096

The cor. of secs. 4 and 5 only, perpetuated by Kenneth L. Haskew, Nevada Professional Land Surveyor No. 3849, in 1982, monumented with a rebar, 5/8 in. diam., firmly set in concrete and in a mound of stone, with aluminum cap mkd. HASKEW ENG T10S R47E S32 S5 S4 T11S R47E RLS3849, as recorded in Nye County, Nevada, Record of Survey 61094. This is accepted as a careful and faithful perpetuation of the position of the original corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 11 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by O.E. Brashears,
U.S. Deputy Surveyor, in 1906

From the cor. of secs. 26, 27, 34 and 35, monumented with a basalt stone, 18x10x8 ins., firmly set, mkd. with 1 notch on the south and 2 notches on the east edges, and a mound of stone west of the corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet and in a collar of stone, with brass cap mkd.

T11S R47E
S27 S26
S34 S35

2004

Deposit the mkd. stone alongside the stainless steel post and rebuild the mound of stone west of the corner.

N. 0°01'30" E., bet. secs. 26 and 27.

40.321

The 1/4 sec. cor. of secs. 26 and 27, monumented with a basalt stone, 16x12x6 ins., firmly set, mkd. 1/4 on the west face and a mound of stone west of the corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet and in a collar of stone, with brass cap mkd.

T11S R47E
1/4
S27 S26

1998

Deposit the mkd. stone alongside the stainless steel post.

N. 0°08'10" W., beginning new measurement.

259

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 11 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
0.80	Draw, drains NW.
6.70	Spur, slopes W.
22.40	Wash, drains SW.
24.00	Trail road in wash, NE-SW.
27.20	Wash, drains SW.
33.00	Spur, slopes SW.
40.278	Point for the cor. of secs. 22, 23, 26 and 27, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<div><div>T11S R47E</div><div>S22 S23</div><div></div><div>S27 S26</div><div>2004</div></div>
	Raise a mound of stone west of the corner.
	From this corner, the 1/4 sec. cor. of secs. 22 and 23, monumented with a basalt stone, 14x10x6 ins., firmly set, mkd. 1/4 on the west face, bears N. 0°07'20" E., 40.278 chs. dist.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	<div><div>T11S R47E</div><div>1/4</div><div>S22 S23</div><div>2004</div></div>
	Deposit the mkd. stone alongside the stainless steel post.
	From this same corner, the 1/4 sec. cor. of secs. 23 and 26, monumented with a basalt stone, 12x10x8 ins., firmly set, mkd. 1/4 on the north face, bears S. 89°55'30" E., 40.197 chs. dist.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	<div><div>T11S R47E</div><div>S23</div><div>1/4 —</div><div>S26</div><div>2004</div></div>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 11 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°06'10" W., bet. secs. 33 and 34.</p>
2.10	Wash, drains NW.
10.00	Wash, drains NW.
10.223	Intersect a rebar, 5/8 in. diam., with aluminum cap mkd. HASKEW ENG RLS 3849.
20.446	Intersect a rebar, 5/8 in. diam., with aluminum cap mkd. HASKEW ENG RLS 3849.
30.669	Intersect a rebar, 5/8 in. diam., with plastic cap mkd. RLS 2518.
40.892	<p>Point for the 1/4 sec. cor. of secs. 33 and 34, determined latitudinally at proportionate distance and longitudinally in a fence, bears N-S, based on the position of the original corner monument as shown on Parcel Maps 410299 and 055247 recorded in Nye County, Nevada.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T11S R47E 1/4 S33 S34 1998</p> <p>Corner is located in a fence which bears N-S, 50 lks. south of the corner of fences projecting south and west; a basalt stone, 14x12x10 ins., mkd. 1/4 on a face, was found lying loosely on the ground near this fence corner.</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr/> <p>N. 0°02'00" E., beginning new measurement.</p>
8.50	Wash, drains NW.
12.50	Low ridge, E-W.
16.80	Trail road in wash, E-W.
37.60	Wash, drains NW.
40.120	<p>The cor. of secs. 27, 28, 33 and 34, monumented with a basalt stone, 18x12x8 ins., set in a mound of stone, mkd. with 3 notches on the east and 1 notch on the south edges; a steel fence post with metal tag mkd. RLS 451 is set alongside the mkd. stone.</p> <p>At the corner point</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 11 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T11S R47E S28 S27 ----- S33 S34</p> <p>1998</p> </div> <p>Deposit the mkd. stone and metal tag alongside the stainless steel post.</p> <p>Raise a mound of stone west of the corner.</p> <hr/> <p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>S. 89°43'30" W., bet. secs. 27 and 34.</p> <p>40.262 The 1/4 sec. cor. of secs. 27 and 34, monumented with a basalt stone, 20x10x6 ins., firmly set, mkd. 1/4 on the north face and a mound of stone north of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, over a plastic-encased magnet and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T11S R47E S27 1/4 ----- S34</p> <p>1998</p> </div> <p>Deposit mkd. stone alongside the stainless steel post.</p> <hr/> <p>S. 89°45'20" W., beginning new measurement.</p> <p>20.114 Point for the W 1/16 sec. cor. of secs. 27 and 34; not monumented.</p> <p>40.228 The cor. of secs. 27, 28, 33 and 34.</p> <hr/> <p>N. 0°02'50" W., bet. secs. 27 and 28.</p> <p>13.10 Powerline, NE-SW.</p> <p>19.80 U.S. Highway No. 95, NE-SW.</p> <p>20.115 Point for the S 1/16 sec. cor. of secs. 27 and 28; not monumented.</p> <p>27.20 Powerline, E-W.</p> <p>40.230 The 1/4 sec. cor. of secs. 27 and 28, monumented with a basalt stone, 18x10x6 ins., mkd. 1/4 on the west face, and a mound of stone west of the corner.</p>
--------	---

262

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 11 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T11S R47E 1/4 S28 S27</p> <p style="text-align: center;">1998</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr/> <p>N. 0°11'00" W., beginning new measurement.</p>
0.90	Amargosa River, course SE.
9.30	Enter meadow land.
22.00	Leave meadow land.
36.20	U.S. Highway No. 95, NW-SE.
40.224	<p>Point for the cor. of secs. 21, 22, 27 and 28, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T11S R47E S21 S22 <hr/>S28 S27</p> <p style="text-align: center;">1998</p> <p>Raise a mound of stone west of the corner.</p> <hr/> <p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>S. 89°33'20" W., bet. secs. 22 and 27.</p>
5.80	Spur, slopes SW.
8.10	Wash, drains SW.
11.00	Spur, slopes SW.
17.90	Wash, drains SW.
38.60	Top of ridge, NE-SW.
40.359	<p>The 1/4 sec. cor. of secs. 22 and 27, monumented with a basalt stone, 16x12x10 ins., mkd. 1/4 on the north face, and a mound of stone north of the corner.</p> <p>At the corner point</p>

263

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 11 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T11S R47E S22 1/4 — S27 1998</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr/> <p>S. 89°43'10" W., beginning new measurement.</p>
29.40	Powerline, NW-SE.
30.50	Wash, drains SW.
40.202	The cor. of secs. 21, 22, 27 and 28.
	<hr/> <p>N. 0°07'20" E., bet. secs. 21 and 22.</p>
38.80	Powerline, NW-SE.
40.224	<p>The 1/4 sec. cor. of secs. 21 and 22, monumented with a basalt stone, 14x8x8 ins. (Record, 14x12x8 ins.), mkd. 1/4 on the west face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T11S R47E 1/4 S21 S22 1998</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <p>Corner is located in a fence which bears N-S.</p> <p>From this corner, National Geodetic Survey control (formerly U.S.C. & G.S. triangulation) station "HOT SPRING", monumented with a standard brass tablet set in concrete, mkd. HOT SPRING 1949, bears S. 73°53'20" W., 12.810 chs. dist.</p> <hr/> <p>N. 0°04'50" E., beginning new measurement.</p>
1.40	Low spur, slopes SW.
23.10	Wash, drains SW.
29.00	Wash, drains SE.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 11 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.237	<p>The cor. of secs. 15, 16, 21 and 22, determined at the corner of fences projecting south and west and monumented with the 4 in. diam. cornerpost; not remonumented. The original corner monument, a quartzite stone, 18x12x8 ins., mkd. with 3 notches on two edges and T11S R47E on faces, was found set in concrete at the base of the cornerpost.</p>
40.217	<p>N. 0°00'40" E., bet. secs. 15 and 16.</p> <p>The 1/4 sec. cor. of secs. 15 and 16, monumented with a basalt stone, 18x12x10 ins., mkd. 1/4 on the west face, and a mound of stone west of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T11S R47E 1/4 S16 S15 1998</p> </div> <p>Deposit the mkd. stone alongside the stainless steel post.</p>
40.151	<p>N. 0°05'00" E., beginning new measurement.</p> <p>The cor. of secs. 9, 10, 15 and 16, monumented with a basalt stone, 16x10x6 ins., mkd. with 4 notches on the south and 3 notches on the east edges, and a mound of stone west of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T11S R47E S 9 S10 S16 S15 1998</p> </div> <p>Deposit the mkd. stone alongside the stainless steel post.</p>
7.00	<p>N. 0°00'30" W., bet. secs. 9 and 10.</p>
16.50	<p>Spur, slopes SW.</p>
16.50	<p>Enter gravel pit.</p>
20.094	<p>Point for the S 1/16 sec. cor. of secs. 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 11 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>S 1/16 S 9 S10</p> <p>1998</p>
30.50	Enter meadow land.
34.50	Leave meadow land.
40.188	<p>Point for the 1/4 sec. cor. of secs. 9 and 10, at proportionate distance; a basalt stone, 14x12x6 ins., mkd. 1/4 on a face, was found lying loosely on the ground a short distance away.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p>T11S R47E 1/4 S 9 S10</p> <p>1998</p> <p>Raise a mound of stone west of the corner; deposit mkd. stone in the mound of stone.</p>
55.20	Bladed dirt road, E-W.
60.282	<p>Point for the N 1/16 sec. cor. of secs. 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p>N 1/16 S 9 S10</p> <p>1998</p>
61.10	Spur, slopes SW.
80.376	<p>The cor. of secs. 3, 4, 9 and 10, monumented with a basalt stone, 18x12x10 ins., mkd. with 3 notches on the east and 4 notches on the south edges, and a mound of stone west of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p>T11S R47E S 4 S 3 ----- S 9 S10</p> <p>1998</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 11 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°01'50" W., bet. secs. 3 and 4.
7.80	Powerline and phone cable at north edge of graded road NE-SW.
20.100	Point for the S 1/16 sec. cor. of secs. 3 and 4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. S 1/16 S 4 S 3 1998 Raise a mound of stone west of the corner.
40.200	The 1/4 sec. cor. of secs. 3 and 4, monumented with a basalt stone, 20x10x8 ins., mkd. 1/4 on the west face and a mound of stone west of the corner. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T11S R47E 1/4 S 4 S 3 1998 Deposit the mkd. stone alongside the stainless steel post. N. 0°05'50" E., beginning new measurement.
40.188	The cor. of secs. 3 and 4 only, on the N. bdy. of the Tp., hereinbefore described. From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., hereinbefore described. N. 0°09'20" W., bet. secs. 32 and 33.
2.50	Powerline, NE-SW.
20.016	Point for the S 1/16 sec. cor. of secs. 32 and 33; not monumented.
40.032	The 1/4 sec. cor. of secs. 32 and 33, monumented with a rebar, 1/2 in. diam., with plastic cap mkd. RLS 1553, set alongside a basalt stone, 14x10x6 ins., mkd. 1/4 on the west face, and in a mound of stone. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

267

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 11 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div data-bbox="867 258 1015 338"> T11S R47E 1/4 S32 S33 </div> <div data-bbox="906 363 971 388">1998</div> <div data-bbox="418 415 1458 468">Deposit the mkd. stone alongside and the rebar inside the stainless steel post.</div> <div data-bbox="418 495 1094 520">Raise a mound of stone west of the corner.</div> <hr/> <div data-bbox="418 573 1089 598">N. 0°05'50" E., beginning new measurement.</div> <div data-bbox="261 625 358 651">40.264</div> <div data-bbox="418 625 1458 709">The cor. of secs. 28, 29, 32 and 33, monumented with a basalt stone, 14x10x8 ins., mkd. with 1 notch on the south and 4 notches on the east edges, and a mound of stone west of the cor.</div> <div data-bbox="418 735 724 760">At the corner point</div> <div data-bbox="418 787 1458 861">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</div> <div data-bbox="860 892 1008 997"> <div data-bbox="860 892 1008 945"> T11S R47E S29 S28 </div> <hr/> <div data-bbox="860 966 1008 997"> S32 S33 </div> </div> <div data-bbox="899 1022 964 1047">1998</div> <div data-bbox="418 1075 1347 1100">Deposit the mkd. stone alongside the stainless steel post.</div> <hr/> <div data-bbox="418 1152 1073 1178">From the cor. of secs. 27, 28, 33 and 34.</div> <div data-bbox="418 1205 1019 1230">S. 89°45'50" W., bet. secs. 28 and 33.</div> <div data-bbox="272 1257 337 1283">9.20</div> <div data-bbox="418 1257 683 1283">Powerline, NE-SW.</div> <div data-bbox="256 1310 337 1335">13.30</div> <div data-bbox="418 1310 846 1335">U.S. Highway No. 95, NE-SW.</div> <div data-bbox="256 1362 337 1388">19.20</div> <div data-bbox="418 1362 683 1388">Powerline, NE-SW.</div> <div data-bbox="256 1415 354 1440">20.050</div> <div data-bbox="418 1415 1214 1440">Point for the E 1/16 sec. cor. of secs. 28 and 33.</div> <div data-bbox="418 1467 1458 1541">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</div> <div data-bbox="789 1575 954 1654"> <div data-bbox="789 1575 954 1627"> E 1/16 <div data-bbox="906 1575 954 1600">S28</div> <hr/> <div data-bbox="906 1627 954 1654">S33</div> </div> </div> <div data-bbox="894 1682 959 1707">1998</div> <div data-bbox="256 1734 354 1759">40.100</div> <div data-bbox="418 1734 1458 1808">The 1/4 sec. cor. of secs. 28 and 33, monumented with a basalt stone, 20x16x4 ins. (Record, 18x14x8 ins.), mkd. 1/4 on the north face.</div> <div data-bbox="418 1835 716 1860">At the corner point</div>
--------	---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 11 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T11S R47E S28 1/4 — S33 1998</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr/> <p>S. 89°46'20" W., beginning new measurement.</p>
20.082	<p>Point for the W 1/16 sec. cor. of secs. 28 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S28 W 1/16 — S33 1998</p> <p>Raise a mound of stone north of the corner.</p> <p>From this corner, a rebar, 1/2 in. diam., with plastic cap mkd. RLS 1553, set by Ben Lewis, Nevada Professional Land Surveyor No. 1553, in 1987, as shown on Parcel Map 191449, recorded in Nye County, Nevada, bears N. 4°00' W., 0.483 chs. dist. This rebar is not in agreement with the position of the W 1/16 sec. cor. of secs. 28 and 33, as shown on the Parcel Map and is not utilized in this survey.</p> <p>From this same corner a rebar, 1/2 in. diam., with plastic cap mkd. RLS 1553, set by Ben Lewis, Nevada Professional Land Surveyor No. 1553, in 1987, as shown on Parcel Map 191449, recorded in Nye County, Nevada, bears S. 1°44' W., 1.033 chs. dist.</p>
40.164	<p>The cor. of secs. 28, 29, 32 and 33.</p> <hr/> <p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>S. 89°31'40" W., bet. secs. 21 and 28.</p>
1.00	U.S. Highway No. 95, NW-SE.
20.041	<p>Point for the E 1/16 sec. cor. of secs. 21 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S21 E 1/16 — S28 1998</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 11 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
22.90	Fence line, N-S.
23.20	Remains of old trail road, N-S.
23.50	Powerline, N-S.
40.082	<p>The 1/4 sec. cor. of secs. 21 and 28, perpetuated by Wallace T. Boundy, Nevada Professional Land Surveyor No. 2518, recorded in Nye County, Nevada, Record of Survey 274328, monumented with a rebar, 5/8 in. diam., with plastic cap mkd. RLS 2518, set alongside a basalt stone, 14x6x6 ins. (Record, 16x10x8 ins.), mkd. 1/4 on the north face, and a mound of stone north of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T11S R47E</p> <p>S21</p> <p>1/4 ———</p> <p>S28</p> <p>1998</p> </div> <p>Deposit the mkd. stone alongside and the rebar inside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>S. 89°30'20" W., bet. secs. 16 and 21.</p>
19.970	<p>Point for the E 1/16 sec. cor. of secs. 16 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>S16</p> <p>E 1/16 ———</p> <p>S21</p> <p>1998</p> </div> <p>Corner is located 3 ft. SW of the corner of fences projecting north, south and east.</p>
22.80	Powerline, NW-SE.
27.00	Leave meadow land.
31.60	U.S. Highway No. 95, NW-SE.
33.00	Amargosa River, course S.
36.00	Powerline, NW-SE.

270

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 11 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p> <p>39.940</p>	<p>The 1/4 sec. cor. of secs. 16 and 21, perpetuated by Wallace T. Boundy, Nevada Professional Land Surveyor No. 2518, recorded in Nye County, Nevada, Record of Survey 274328, monumented with a rebar, 5/8 in. diam., with plastic cap mkd. RLS 2518, set alongside a basalt stone, 12x10x8 ins., mkd. 1/4 on the north face, and a mound of stone north of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T11S R47E</p> <p>S16</p> <p>1/4 —</p> <p>S21</p> <p>1998</p> </div> <p>Deposit the mkd. stone alongside and the rebar inside the stainless steel post.</p> <hr/> <p>S. 89°42'20" W., beginning new measurement.</p> <p>40.196</p> <p>The cor. of secs. 16, 17, 20 and 21, monumented with a rebar, 5/8 in. diam., with aluminum cap, 2 ins. diam., mkd. T11S R47E S16 S17 S20 S21 RLS 4248 set alongside a basalt stone, 18x12x8 ins., mkd. with 3 notches on the south and 4 notches on the east edges, and a mound of stone west of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T11S R47E</p> <table border="1" style="margin: auto;"> <tr> <td>S17</td> <td>S16</td> </tr> <tr> <td>S20</td> <td>S21</td> </tr> </table> <p>2004</p> </div> <p>Deposit the mkd. stone alongside and insert the rebar inside the stainless steel post.</p> <hr/> <p>N. 0°08'00" W., bet. secs. 16 and 17.</p> <p>40.571</p> <p>The 1/4 sec. cor. of secs. 16 and 17, monumented with a basalt stone, 16x12x8 ins., mkd. 1/4 in the west face, and a mound of stone west of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>	S17	S16	S20	S21
S17	S16				
S20	S21				

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 11 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>T11S R47E 1/4 S17 S16</p> <p>2004</p> <p>Deposit the mkd. stone alongside the stainless steel post and rebuild the mound of stone west of the corner.</p> <hr/> <p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>S. 89°44'30" W., bet. secs. 9 and 16.</p>
20.115	<p>Point for the E 1/16 sec. cor. of secs. 9 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 9 E 1/16 — S16</p> <p style="text-align: center;">1998</p> <p>Raise a mound of stone north of the corner.</p>
27.70	Powerline, N-S.
32.10	Powerline, NE-SW.
39.40	U.S. Highway No. 95, NW-SE.
40.230	<p>The 1/4 sec. cor. of secs. 9 and 16, monumented with an iron rod, 1/2 in. diam., no cap; this is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T11S R47E S 9 1/4 — S16</p> <p style="text-align: center;">1998</p> <p>Deposit the iron rod inside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>S. 89°45'50" W., bet. secs. 4 and 9.</p>
8.20	Powerline and phone cable at west edge of graded road NE-SW.
10.80	Wash, courses SW.
14.00	Prospect hole, bears N., 0.70 chs. dist.

272

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 11 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
16.00	Spur, slopes SW.
17.00	Abandoned Railroad grade, bears N-S
20.076	Point for the E 1/16 sec. cor. of secs. 4 and 9. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;"> $\begin{array}{r} S\ 4 \\ E\ 1/16\ \hline S\ 9 \end{array}$ </div> <div style="text-align: center;">1998</div> Raise a mound of stone north of the corner.
20.10	Fence, bears N-S; enter meadow land.
28.50	Powerline, NW-SE.
31.10	Leave meadow land.
33.00	Amargosa River, course S.
38.40	Powerline, NW-SE.
40.152	Point for the 1/4 sec. cor. of secs. 4 and 9, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;"> $\begin{array}{r} T11S\ R47E \\ S\ 4 \\ 1/4\ \hline S\ 9 \end{array}$ </div> <div style="text-align: center;">1998</div> Raise a mound of stone north of the corner.
43.20	U.S. Highway No. 95, NW-SE.
60.228	Point for the W 1/16 sec. cor. of secs. 4 and 9. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;"> $\begin{array}{r} S\ 4 \\ W\ 1/16\ \hline S\ 9 \end{array}$ </div> <div style="text-align: center;">1998</div> Raise a mound of stone north of the corner.
80.304	The cor. of secs. 4, 5, 8 and 9, monumented with a basalt stone, 16x12x8 ins., projecting 6 ins. above the ground, mkd. with 5 notches on the south and east edges.

273

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 11 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <table> <tr> <td>T11S R47E</td><td></td></tr> <tr> <td>S 5</td><td>S 4</td></tr> <tr> <td>S 8</td><td>S 9</td></tr> </table> <p>1998</p> <p>Deposit the mkd. stone alongside the stainless steel post and raise a mound of stone west of the corner.</p> <hr/> <p>N. 0°01'20" E., bet. secs. 4 and 5.</p> <p>2.90 Wash, drains SE.</p> <p>8.10 Spur slopes SE.</p> <p>20.020 Point for the S 1/16 sec. cor. of secs. 4 and 5, not monumented.</p> <p>28.20 Wash, drains SE.</p> <p>38.50 Ridge, E-W.</p> <p>40.040 The 1/4 sec. cor. of secs. 4 and 5, monumented with a basalt stone, 14x10x6 ins., mkd. 1/4 on the west face, and a mound of stone west of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <table> <tr> <td>T11S R47E</td><td></td></tr> <tr> <td>1/4</td><td></td></tr> <tr> <td>S 5</td><td>S 4</td></tr> </table> <p>1998</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <p>Rebuild the mound of stone west of the corner.</p> <hr/> <p>N. 0°08'10" W., beginning new measurement.</p> <p>20.063 The N 1/16 sec. cor. of secs. 4 and 5, determined by Kenneth L. Haskew, Nevada Professional Land Surveyor No. 3849, in 1982, monumented with a rebar, 1/2 in. diam., firmly set in concrete and a mound of stone, with aluminum cap mkd. HASKEW ENG RLS 3849, as recorded in Nye County, Nevada, Record of Survey 61094. This is accepted as a careful and faithful determination of the corner position.</p> <hr/> <p>N. 0°08'10" W., beginning new measurement.</p>	T11S R47E		S 5	S 4	S 8	S 9	T11S R47E		1/4		S 5	S 4
T11S R47E													
S 5	S 4												
S 8	S 9												
T11S R47E													
1/4													
S 5	S 4												

274

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 11 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.050	The cor. of secs. 4 and 5 only, on the N. bdy. of the Tp., hereinbefore described.
	<hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 4, T. 11 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>
	From the 1/4 sec. cor. of secs. 4 and 9.
	N. 0°01'20" W., on the N-S center line of sec. 4.
7.60	Powerline, NW-SE.
20.060	Point for the C-S 1/16 sec. cor. of sec. 4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<p style="text-align: center;"> $\begin{array}{c} C \\ S\ 1/16 \mid S\ 4 \\ C \end{array}$ </p> <p style="text-align: center;">1998</p>
40.120	Point for the center 1/4 sec. cor. of sec. 4, at intersection with the E-W center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<p style="text-align: center;">T11S R47E C 1/4 S 4</p> <p style="text-align: center;">1998</p>
49.70	Powerline, NW-SE.
60.208	Point for the C-N 1/16 sec. cor. of sec. 4; not monumented.
80.266	The 1/4 sec. cor. of sec. 4 only, on the N. bdy. of the Tp., hereinbefore described.
	<hr/> <p>From the 1/4 sec. cor. of secs. 3 and 4.</p> <p>S. 89°39'00" W., on the E-W center line of sec. 4.</p>
20.072	Point for the C-E 1/16 sec. cor. of sec. 4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<p style="text-align: center;"> $\begin{array}{c} E\ 1/16 \\ C \text{ --- } C \\ S\ 4 \end{array}$ </p> <p style="text-align: center;">1998</p>
	Raise a mound of stone north of the corner.

SUBDIVISION OF SECTION 4,
T. 11 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
24.70	Fence, N-S.
36.60	Powerline, NW-SE.
40.144	The center 1/4 sec. cor.
44.60	Powerline, NW-SE.
48.00	U.S. Highway No. 95, NW-SE.
60.202	Point for the C-W 1/16 sec. cor. of sec. 4; not monumented.
80.260	The 1/4 sec. cor. of secs. 4 and 5.
	<hr/>
	From the E 1/16 sec. cor. of secs. 4 and 9.
	N. 0°01'30" W., on the N-S center line of the SE1/4 of sec. 4.
40.160	The C-E 1/16 sec. cor. of sec. 4.
	<hr/>
	From the W 1/16 sec. cor. of secs. 4 and 9.
	N. 0°00'10" W., on the N-S center line of the SW1/4 of sec. 4.
20.038	Point for the SW 1/16 sec. cor. of sec. 4, at intersection with the E-W center line of the SW1/4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	SW 1/16 S 4
	1998
	Raise a mound of stone west of the corner.
40.076	The point for the C-W 1/16 sec. cor. of sec. 4.
	<hr/>
	From the C-S 1/16 sec. cor. of sec. 4.
	S. 89°42'30" W., on the E-W center line of the SW1/4 of sec. 4.
2.00	Powerline, NW-SE.
5.00	U.S. Highway No. 95, NW-SE.
20.067	The SW 1/16 sec. cor.
40.134	The point for the S 1/16 sec. cor. of secs. 4 and 5.
	<hr/>
	From the point for the C-W 1/16 sec. cor. of sec. 4.
	N. 0°04'50" W., on the N-S center line of the NW1/4 of sec. 4.

276

SUBDIVISION OF SECTION 4,
T. 11 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.075	Point for the NW 1/16 sec. cor. of sec. 4, at intersection with the E-W center line of the NW1/4. This point falls at a position occupied by a rebar, 1/2 in. diam., set in concrete, with aluminum cap mkd. HASKEW ENG RLS 3849; as shown on a plat by Kenneth L. Haskew, Nevada Professional Land Surveyor No. 3849, recorded in Nye County, Nevada, Record of Survey 61094 in 1982. Although the Record of Survey indicates this position was determined utilizing an incorrect proportionate relationship for the C-N 1/16 sec. cor of sec. 4, this rebar physically occupies the correct position on the ground.
22.30	U.S. Highway No. 95, NW-SE.
27.80	Powerline, NW-SE.
40.129	The W 1/16 sec. cor. of sec. 4 only, on the N. bdy. of the Tp., hereinbefore described.
	From the point for the C-N 1/16 sec. cor. of sec. 4.
	S. 89°37'30" W., on the E-W center line of the NW1/4 of sec. 4.
4.00	Powerline, NW-SE.
10.10	Graded road, N-S.
14.30	Powerline, NW-SE.
18.30	U.S. Highway No. 95, NW-SE.
20.077	The NW 1/16 sec. cor.
40.154	The N 1/16 sec. cor. of secs. 4 and 5.
	SUBDIVISION OF SECTION 9, T. 11 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA
	From the 1/4 sec. cor. of secs. 9 and 16.
	N. 0°02'30" E., on the N-S center line of sec. 9.
40.206	Point for the center 1/4 sec. cor. of sec. 9, at intersection with the E-W center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T11S R47E C 1/4 S 9 1998
60.300	Point for the C-N 1/16 sec. cor. of sec. 9.
	Set a railroad spike flush with the surface of the pavement of U.S Highway No. 95 near the east edge with top mkd.

SUBDIVISION OF SECTION 9,
T. 11 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div style="text-align: center;"> BLM C N 1/16 S 9 C 1998 </div>
80.394	<p>The 1/4 sec. cor. of secs. 4 and 9.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 9 and 10.</p> <p>S. 89°45'50" W., on the E-W center line of sec. 9.</p>
20.096	<p>Point for the C-E 1/16 sec. cor. of sec. 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> E 1/16 C ——— C S 9 1998 </div>
28.10	Powerline, N-S.
37.20	Powerline, N-S.
40.192	The center 1/4 sec. cor.
40.60	U.S. Highway No. 95, N-S.
80.370	<p>The 1/4 sec. cor. of secs. 8 and 9, monumented with a basalt stone, 18x12x8 ins., mkd. 1/4 on the west face, and a mound of stone west of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> T11S R47E 1/4 S 8 S 9 1998 </div> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <p>Rebuild the mound of stone west of the corner.</p> <hr/> <p>From the C-E 1/16 sec. cor. of sec. 9.</p> <p>N. 0°01'10" E., on the N-S center line of the NE1/4 of sec. 9.</p>
20.094	<p>Point for the NE 1/16 sec. cor. of sec. 9, at intersection with the E-W center line of the NE1/4.</p>

SUBDIVISION OF SECTION 9,
T. 11 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S 9</p> <p style="text-align: center;">1998</p> <p>Raise a mound of stone west of the corner.</p>
40.188	<p>The E 1/16 sec. cor. of secs. 4 and 9.</p> <hr/> <p>From the N 1/16 sec. cor. of secs. 9 and 10.</p> <p>S. 89°45'50" W., on the E-W center line of the NE1/4 of sec. 9.</p>
20.086	The NE 1/16 sec. cor.
28.30	Powerline, N-S.
37.30	Powerline, N-S.
40.172	<p>The C-N 1/16 sec. cor. of sec. 9.</p> <hr/> <p>From the E 1/16 sec. cor. of secs. 9 and 16.</p> <p>N. 0°01'00" E., on the N-S center line of the SE1/4 of sec. 9.</p>
40.197	<p>The C-E 1/16 sec. cor. of sec. 9.</p> <hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 16, T. 11 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 16 and 21.</p> <p>N. 0°10'00" W., on the N-S center line of sec. 16.</p>
40.463	<p>Point for the center 1/4 sec. cor. of sec. 16, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T11S R47E C 1/4 S16</p> <p style="text-align: center;">1998</p>
80.531	<p>The 1/4 sec. cor. of secs. 9 and 16.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 15 and 16.</p> <p>S. 89°51'20" W., on the E-W center line of sec. 16.</p>
20.030	Point for the C-E 1/16 sec. cor. of sec. 16.

279

SUBDIVISION OF SECTION 16,
T. 11 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">E 1/16 C ——— C S16 1998</p> <p>Raise a mound of stone north of the corner.</p>
27.20	Powerline, N-S.
34.30	U.S. Highway No. 95, NS-SE.
37.40	Powerline, NW-SE.
40.060	The center 1/4 sec. cor.
80.227	The 1/4 sec. cor. of secs. 16 and 17.
<hr/>	
40.340	<p>From the E 1/16 sec. cor. of secs. 16 and 21.</p> <p>N. 0°04'40" W., on the N-S center line of the SE1/4 of sec. 16.</p> <p>The C-E 1/16 sec. cor. of sec. 16.</p>
<hr/>	
<p style="text-align: center;">SUBDIVISION OF SECTION 27, T. 11 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA</p>	
<hr/>	
20.144	<p>From the 1/4 sec. cor. of secs. 27 and 34.</p> <p>N. 0°07'40" W., on the N-S center line of sec. 27.</p> <p>Point for the C-S 1/16 sec. cor. of sec. 27; not monumented.</p>
40.288	<p>Point for the center 1/4 sec. cor. of sec. 27, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T11S R47E C 1/4 S27 1998</p>
80.480	The 1/4 sec. cor. of secs. 22 and 27.
<hr/>	
40.366	<p>From the 1/4 sec. cor. of secs. 26 and 27.</p> <p>S. 89°40'30" W., on the E-W center line of sec. 27.</p> <p>The center 1/4 sec. cor.</p>
60.449	Point for the C-W 1/16 sec. cor. of sec. 27; not monumented.
66.00	Powerline, N-S.

SUBDIVISION OF SECTION 27,
T. 11 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
74.30	U.S. Highway No. 95, N-S.
80.532	The 1/4 sec. cor. of secs. 27 and 28.
	<hr/>
	From the point for the W 1/16 sec. cor. of secs. 27 and 34.
	N. 0°05'20" W., on the N-S center line of the SW1/4 of sec. 27.
20.129	Point for the SW 1/16 sec. cor. of sec. 27, at intersection with the E-W center line of the SW1/4; not monumented.
40.258	The point for the C-W 1/16 sec. cor. of sec. 27.
	<hr/>
	From the point for the C-S 1/16 sec. cor. of sec. 27.
	S. 89°42'50" W., on the E-W center line of the SW1/4 of sec. 27.
20.100	The point for the SW 1/16 sec. cor.
30.150	Point for the C-W-SW 1/64 sec. cor. of sec. 27.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	S 27 C-W-SW 1/64 1998
	From this corner, an iron post, 1 in. diam., set flush with the surface of the ground, with metal tag mkd. RLS 3115, bears N. 2°31'00" W., 0.140 chs. dist.; this position does not represent a proper subdivision of the section and is not utilized in this survey.
35.175	Point for the C-W-W-SW 1/256 sec. cor. of sec. 27.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	S 27 C-W-W-SW 1/256 1998
	From this corner an iron post, 1 in. diam., set flush with the surface of the ground, with metal tag mkd. RLS 3115, bears N. 2°43'30" W., 0.072 chs. dist.; this position does not represent a proper subdivision of the section and is not utilized in this survey.
40.200	The point for the S 1/16 sec. cor. of secs. 27 and 28.
	<hr/>
	From the C-W-SW 1/64 sec. cor. of sec. 27.

SUBDIVISION OF SECTION 27,
T. 11 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°04'00" W., on a portion of the computed N-S center line of the NW1/4SW1/4 of sec. 27.
10.061	<p>Point for the NW-SW 1/64 sec. cor. of sec. 27, at its computed position.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 27 NW-SW 1/64 1998</p> <p>From this corner an iron post, 1 in. diam., set flush with the surface of the ground, with metal tag mkd. RLS 3115, bears N. 39°13'00" W., 0.288 chs. dist.; this position does represent a proper subdivision of the section and is not utilized in this resurvey.</p>
5.023	<p>S. 89°41'40" W., on a portion of the computed E-W center line of the NW1/4SW1/4 of sec. 27.</p> <p>Point for the C-W-NW-SW 1/256 sec. cor. of sec. 27, at its computed position.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 36 ins. in the ground, over a plastic-encased magnet, on the east shoulder of U.S. Highway No. 95, with brass cap mkd.</p> <p style="text-align: center;">S 27 C-W-NW-SW 1/256 1998</p>
10.059	<p>S. 0°03'30" E., on the N-S center line of the SW1/4NW1/4SW1/4.</p> <p>The C-W-W-SW 1/256 sec. cor. of sec. 27.</p>
20.044	<p style="text-align: center;">SUBDIVISION OF SECTION 33, T. 11 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 4 and 33, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°01'30" W., on the N-S center line of sec. 33.</p> <p>The C-S 1/16 sec. cor., monumented with a rebar, 1/2 in. diam., with illegible plastic cap, set in concrete at the corner of fences projecting north and west. This rebar has been accepted and recorded by numerous professional land surveyors as indicated on land survey records recorded in Nye County, Nevada and is accepted as a careful and faithful determination of the corner position. Not remonumented.</p>

SUBDIVISION OF SECTION 33,
T. 11 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°03'30" W., beginning new measurement.
19.00	Powerline, NE-SW.
20.044	The center 1/4 sec. cor., determined by Wallace T. Boundy, Nevada Professional Land Surveyor No. 2518, in 1981, monumented with a rebar, 1/2 in. diam., firmly set, projecting 6 ins. above the ground, with plastic cap mkd. RLS 2518, as recorded in Nye County, Nevada, Parcel Map 55247. This is accepted as a careful and faithful determination of the corner position. Corner is located in a fence which bears N-S.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T11S R47E C 1/4 S33
	1998
	Deposit rebar inside the stainless steel post.
	<hr/>
	N. 0°03'00" W., beginning new measurement.
4.00	U.S. Highway No. 95, NE-SW.
8.70	Powerline, NE-SW.
12.50	East edge of runway, NE-SW.
13.80	West edge of runway, NE-SW.
40.192	The 1/4 sec. cor. of secs. 28 and 33.
	<hr/>
	From the 1/4 sec. cor. of secs. 33 and 34.
	S. 89°39'30" W., on the E-W center line of sec. 33.
39.10	Powerline, NE-SW.
40.047	The center 1/4 sec. cor.
	<hr/>
	S. 89°40'20" W., beginning new measurement.
3.50	U.S. Highway No. 95, NE-SW.
7.60	Powerline, NE-SW.
10.70	East edge of runway, NE-SW.
11.70	West edge of runway, NE-SW.
20.135	Point for the C-W 1/16 sec. cor. of sec. 33.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

SUBDIVISION OF SECTION 33,
T. 11 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div style="text-align: center;"> W 1/16 C ——— C S33 1998 </div>
	<p>Raise a mound of stone north of the corner.</p> <p>From this corner, a rebar, 1/2 in. diam., with plastic cap mkd. RLS 1553, firmly set, projecting 3 ins. above the ground, set by Ben Lewis, Nevada Professional Land Surveyor No. 1553, in 1987, recorded in Nye County, Nevada, Parcel Map 191449, bears S. 88°03' W., 0.13 chs. dist. This rebar is not in agreement with the position of the C-W 1/16 sec. cor. of sec. 33 as shown on the Parcel Map and is not utilized in this survey.</p>
40.270	<p>The 1/4 sec. cor. of secs. 32 and 33.</p> <hr/> <p>From the W 1/16 sec. cor. of secs. 4 and 33, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°05'50" W., on the N-S center line of the SW1/4 of sec. 33.</p>
15.80	<p>Powerline, NE-SW.</p>
20.030	<p>Point for the SW 1/16 sec. cor. of sec. 33, at intersection with the E-W center line of the SW1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> SW 1/16 S33 1998 </div>
20.80	<p>U.S. Highway No. 95, NE-SW.</p>
25.60	<p>Powerline, NE-SW.</p>
40.060	<p>The C-W 1/16 sec. cor. of sec. 33.</p> <hr/> <p>From the C-S 1/16 sec. cor. of sec. 33.</p> <p>S. 89°42'50" W., on the E-W center line of the SW1/4 of sec. 33.</p>
16.50	<p>Powerline, NE-SW.</p>
20.122	<p>The SW 1/16 sec. cor.</p>
20.90	<p>U.S. Highway No. 95, NE-SW.</p>
25.00	<p>Powerline, NE-SW.</p>
40.239	<p>The point for the S 1/16 sec. cor. of secs. 32 and 33.</p> <hr/> <p>From the C-W 1/16 sec. cor. of sec. 33.</p> <p>N. 0°01'30" E., on the N-S center line of the NW1/4 of sec. 33.</p>

SUBDIVISION OF SECTION 33,
T. 11 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 40.228</p>	<p>The W 1/16 sec. cor. of secs. 28 and 33.</p> <hr/> <p>GENERAL DESCRIPTION</p> <p>The average elevation of the area surveyed is about 1100 meters. Vegetation consists of creosote and cacti. General drainage is to the south.</p> <hr/>
--------------------------	---

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Thomas E. Casinger.....Cadastral Surveyor
Mary J.M. Hartel.....Cadastral Surveyor
Robert H. Thompson.....Cadastral Surveyor
Ronald E. Williams.....Cadastral Surveyor
Michelle E. Martin.....Survey Aid

CERTIFICATE OF SURVEY

We, Richard A. Zaninovich, Cadastral Surveyor, and Clay W. Morrow, Surveying Technician, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 26th day of January, 1998, we have dependently resurveyed portions of the south and north boundaries and a portion of the subdivisional lines, and subdivided sections 4, 9, 16, 27 and 33, Township 11 South, Range 47 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

April 19, 2005

(Date)

Richard A. Zaninovich

/For Richard A. Zaninovich
(Cadastral Surveyor)

April 11, 2005

(Date)

Clay W. Morrow

(Surveying Technician)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of dependent resurvey of portions of the south and north boundaries and a portion of the subdivisional lines, and the subdivision of sections 4, 9, 16, 27 and 33, Township 11 South, Range 47 East, Mount Diablo Meridian, Nevada, executed by Richard A. Zaninovich, Cadastral Surveyor, and Clay W. Morrow, Surveying Technician, having been critically examined and found correct, are hereby approved.

April 19, 2005

(Date)

Richard A. Zaninovich

(Chief Cadastral Surveyor, Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 11 S., R. 47 E., M.D.M., Nevada, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor, Nevada)~~