

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF

PORTIONS OF THE SOUTH, WEST AND NORTH BOUNDARIES

AND PORTIONS OF THE SUBDIVISIONAL LINES,

THE SURVEY OF

A PORTION OF THE SOUTH BOUNDARY AND A PORTION OF THE SUBDIVISIONAL LINES,

AND THE SUBDIVISION OF CERTAIN SECTIONS,

TOWNSHIP 12 NORTH, RANGE 28 EAST,

AND THE REMONUMENTATION OF CERTAIN CORNERS ON THE EAST BOUNDARY OF

TOWNSHIP 12 NORTH, RANGE 27 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATE OF NEVADA

EXECUTED BY

Michael O. Harmening, Cadastral Surveyor

Mark G. Petrosine, Surveying Technician

Under Special Instructions dated May 24, 2011, approved May 24, 2011, and
Supplemental Instructions, dated August 10, 2012, approved August 10, 2012

which provided for the surveys included under Group No. 906,

and Assignment Instructions dated July 8, 2011.

Survey commenced July 8, 2011

Survey completed December 4, 2012

INDEX DIAGRAM

TOWNSHIP 12 NORTH, RANGE 28 EAST, MOUNT DIABLO MERIDIAN, NEVADA

3	6	5	4	3	2	6	1	8	6
19	7	21	8	9	10	11	12	9	
		22							
18	28	17	17	16	15	14	13	10	
		27		18					
19	20	27	21	14	22	23	24		
		26	16						
30	29	28	16	27	12	26	25		
					13				
31	32	33	34	35	11	36			
26	25	24	23				2		

Subdivision of Sec. 1 ... pp. 29-36

Subdivision of Sec. 2 ... pp. 36-39

Subdivision of Sec. 6 ... pp. 39-40

Subdivision of Sec. 12 .. pp. 40-45

Subdivision of Sec. 13 .. pp. 45-50

Subdivision of Sec. 17 .. pp. 50-51

Subdivision of Sec. 21 .. pp. 51-52

Subdivision of Sec. 27 .. p. 52

Subdivision of Sec. 36 .. pp. 52-53

Remonumentation p. 54

TOWNSHIP 12 NORTH, RANGE 28 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>The following field notes are those of the dependent resurvey of portions of the south, west and north boundaries and portions of the subdivisional lines, the survey of a portion of the south boundary and a portion of the subdivisional lines, and the subdivision of certain sections, Township 12 North, Range 28 East, Mount Diablo Meridian, Nevada.</p> <p>The west boundary was surveyed by U.S. Deputy Surveyor R.A. Chase in 1869-70 under Contract No. 29. A portion of the west boundary was retraced, the north and east boundaries, a portion of the south boundary and a portion of the subdivisional lines were surveyed by U.S. Deputy Surveyors H.E. Franks and J.S. Mullen in 1904 under Contract No. 237. The corner of Tps. 11 and 12 N., Rs. 27 and 28 E., M.D.M. was perpetuated by U.S. Transitman A. Nelson in 1915 under Group No. 32. A portion of the north boundary was dependently resurveyed by U.S. Cadastral Engineer E. Voigt in 1922 under Group No. 66. A portion of the south boundary was dependently resurveyed by U.S. Cadastral Engineer G.W. Ridgway in 1929 under Group No. 124. The corner of Tps. 12 and 13 N., Rs. 28 and 29 E., M.D.M. was perpetuated by U.S. Cadastral Engineer C.S. Swanholm, and Transitsmen R.F. Guinn, C. Pettengill and H. Westfall in 1936 under Group No. 181. Portions of the east boundary and subdivisional lines and the meanders of Walker Lake were dependently resurveyed, section 25 was subdivided and a portion of the east boundary and Tract Nos. 37, 38, and 39 were surveyed by Cadastral Surveyor D.R. Bauer in 1973 under Group No. 497. Portions of the north and east boundaries were dependently resurveyed by J.A. Mack in 1986-87 under Group No. 635. A portion of the north boundary was dependently resurveyed by Cadastral Surveyor R.A. Pratt in 1989 under Group No. 670. A portion of the east boundary was dependently resurveyed by Cadastral Surveyor D.R. Aschenbach and Surveying Technician M.G. Petrosine in 2005-07 under Group No. 827. The corner of Tps. 12 and 13 N., Rs. 27 and 28 E., M.D.M. was perpetuated by Cadastral Surveyor D.J. Clark and Surveying Technician M.G. Petrosine in 2008-09 under Group No. 855. A portion of the north boundary was dependently resurveyed by Cadastral Surveyor L.A. Barney and Surveying Technician M.G. Petrosine in 2009-11 under Group No. 878.</p> <p>Before restoring corners, the lines of the original surveys were retraced and a diligent search was made for any evidence of the original corners and other calls of the original field note record.</p> <p>The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.</p> <p>The survey was executed in accordance with the specifications set forth in the <u>Manual of Surveying Instructions, 2009</u>, the <u>Special Instructions</u>, dated May 24, 2011, and the <u>Supplemental Special Instructions</u>, dated August 10, 2012, for Group No. 906.</p> <p>Measurements were made with Trimble 5700, 5800 and R8 Global Positioning System (GPS) receivers using the real-time kinematic (RTK) method and refer to the true meridian based on geodetic methods. The mean bearings of the lines and horizontal</p>
--------	---

TOWNSHIP 12 NORTH, RANGE 28 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>equivalents of ground distances only are entered in the field notes.</p> <p>The NAD 1983 (CORS96) (2002) geographic position of the corners listed below, as determined from GPS static observations processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuous Operating Reference Stations (CORS) FERNLY COOP CORS ARP, CARSON CITY COOP CORS ARP, ZOLEZZI COOP CORS ARP, and carried forward by RTK observations:</p> <p>The cor. of Tps. 12 N., Rs. 28 and 29 E., on the N. bdy. of Tp. 11 N., R. 28 E. is as follows:</p> <p style="padding-left: 40px;">Latitude: 38°51'07.519" N. Longitude: 118°47'31.726" W.</p> <p>The cor. of Tps. 12 and 13 N., Rs. 27 and 28 E. is as follows:</p> <p style="padding-left: 40px;">Latitude: 38°56'20.645" N. Longitude: 118°54'11.495" W.</p> <p>The mean magnetic declination is 15°30' E., as shown on U.S. Geological Survey 7 1/2 minute quadrangle map "SCHURZ, NEVADA PROVISIONAL EDITION", dated 1988.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY, T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyors H.E. Franks and J.S. Mullen in 1904, and a Portion of the Dependent Resurvey Executed by U.S. Cadastral Engineer G.W. Ridgeway in 1929</p> <hr/> <p>Beginning at the cor. of Tps. 12 N., Rs. 28 and 29 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 6 ins. above a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, with brass cap mkd. as described in the dependent resurvey of a portion of the north boundary, T. 11 N., R. 29 E., executed under Group No. 124, with a mound of stone, 3 1/2 ft. base, 2 ft. high, W. of cor.</p> <p>N. 89°54'50" W., on the S. bdy. of sec. 36.</p> <p>14.20 Top of small hill.</p> <p>34.20 Spur, bears NE.</p> <p>40.224 Point for the 1/4 sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of the position of the original corner. This point will now function as the 1/4 sec. cor. of sec. 36 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	T12N R28E
	<u>1/4 S36</u>
	2011
42.30	Wash, 50 lks. wide, drains NE.
80.448	The cor. of secs. 1, 2, 35 and 36, monumented with a lava stone, 6x6x17 ins. high, firmly set, projecting 6 ins. above the ground, mkd. with 1 notch on the E. edge and 5 notches on the W. edge, with a mound of stone, 3 ft. base, 2 ft. high, N. of cor. This point will now function as the cor. of secs. 35 and 36 only.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	T12N R28E
	<u>S35 S36</u>
	T11N R28E
	2011
	Deposit mkd. stone alongside stainless steel post, into base of mound.
<p>DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY, T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor R.A. Chase in 1869-70, and a Portion of the Retracement Executed by U.S. Deputy Surveyors H.E. Franks and J.S. Mullen in 1904</p> <p>From the cor. secs. 1, 6, 7 and 12, monumented with a mound of stone, 4 ft. base, 1 1/2 ft. high, with no mkd. stone found. Accepted the center of the mound of stone as the best available evidence for the position of the original corner, from which the original bearing trees</p> <p>A root hole bears S. 86 3/4° E., 87 1/2 lks. dist., with a downed pinon pine, 14 ins. diam., with an unmkd. weathered blaze, laying alongside. (Record: S. 83° E., 30 lks.)</p> <p>A pinon pine, 12 ins. diam., bears S. 69° E., 103 1/2 lks. dist., with healed blaze opened to reveal unmkd. axe cut face. (Record: S. 33° E., 40 lks.)</p>	

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>A downed pinon pine, 10 ins. diam., with an unmkd. partially healed weathered blaze, bears S. 20° W., 73 lks. dist. (Record: S. 66° W., 50 lks.)</p> <p>A pinon pine, 11 1/2 ins. diam., bears N. 80° W., 23 lks. dist., with a partially healed blaze, opened to reveal unmkd. axe cut face. (Record: N. 34° W., 20 lks.)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T12N</td></tr> <tr><td>R27E</td><td>R28E</td></tr> <tr><td>S 1</td><td>S 6</td></tr> <tr><td>S12</td><td>S 7</td></tr> </table> <p>2012</p> </div> <p>N. 5°39'00" E., bet. secs. 1 and 6.</p> <p>Across mountainous terrain, covered with pinon pine, sagebrush, cheat and bunchgrass.</p> <p>32.50 Spur, slopes SE., continue across E. face of Black Mountain.</p> <p>36.70 Easterly end of sharp basalt spur, slopes E.</p> <p>42.060 The 1/4 sec. cor. of secs. 1 and 6, monumented with a pinon pine, 18 ins. diam., with scribe marks 1/4 S remaining on a partially healed and weathered blaze on NW. face of tree, from which the original bearing trees</p> <p>A pinon pine, 14 ins. diam., bears N. 8° E., 80 1/2 lks. dist., with an unmkd. partially healed blaze on SSW face of tree. (Record: N. 15° E., 50 lks.)</p> <p>The down and weathered remains of a pinon pine snag, 6 ins. diam. remaining, bears N. 58° W., 12 lks. dist., with scribe marks 1/4 S visible on partially healed blaze, original position indeterminate. (Record: S. 60° W., 60 lks. dist.)</p> <p>from which new bearing objects</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 16 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, for a reference monument, bears N. 34°03' E., 17.7 lks. dist., with brass cap mkd. RM 1/4 S6 11.7 FT TO COR 2012 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 16 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, for a</p>	T12N		R27E	R28E	S 1	S 6	S12	S 7
T12N									
R27E	R28E								
S 1	S 6								
S12	S 7								

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>reference monument, bears N. 49°18' W., 25.5 lks. dist., with brass cap mkd. RM 1/4 S1 16.8 FT TO COR 2012 and an arrow pointing to the corner.</p> <hr/> <p>N. 0°56'50" W., beginning new measurement.</p> <p>Begin posting the boundary of the Walker River Indian Reservation with steel sign posts.</p> <p>41.013 The cor. of Tps. 12 and 13 N., Rs. 27 and 28 E., monumented with a stainless steel post, firmly set flush with the top of a mound of stone, 3 ft. base, 6 ins. high, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the north boundary, T.12 N., R. 27 E., executed under Group No. 855, from which the original bearing trees</p> <p>A pinon pine, 8 ins. diam., bears N. 42° E., 19 lks. dist., with scribe marks T12N R 9 S1 BT visible on a partially healed blaze. (Record: N. 40° E., 80 lks.)</p> <p>A down pinon pine, 10 ins. diam., on E. fork, bears S. 36° E., 43 lks. dist., with illegible scribe marks visible on a partially healed blaze. (Record: S. 60° E., 20 lks.)</p> <p>A down pinon pine, 14 ins. diam., bears S. 68° W., 60 lks. dist., with scribe marks T12R N9E BT visible on weathered blaze. (Record: S. 50° W., 70 lks.)</p> <p>A dead standing pinon pine, 10 ins. diam., bears N. 37 1/4° W., 39 1/2 lks. dist., with illegible scribe marks visible on upper blaze and T13N R27E on lower blaze. (Record: N. 4° W., 45 lks.)</p> <p>and the 2008 bearing objects</p> <p>A chiseled X followed by the letters BO, bears S. 66°52' E., 158.7 lks. dist., mkd. on the top of a granite boulder, 2x2x1 ft. high.</p> <p>A chiseled X followed by the letters BO, bears S. 62°54' W., 90.8 lks. dist., mkd. on the top of a igneous outcrop, 4x2x2 1/2 ft. high.</p> <p>A chiseled X followed by the letters BO, bears N. 12°22' W., 90.4 lks. dist., mkd. on the top of a granite boulder, 2x1 1/2x1 ft. high.</p> <hr/>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUDARY,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyors H.E. Franks and J.S. Mullen in 1904, and a Portion of the Dependent Resurvey Executed by Cadastral Surveyor L.A. Barney and Surveying Technician M.G. Petrosine in 2009-11</p> <hr/> <p>From the witness E 1/16 sec. cor. of secs. 1 and 36, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the a portion of the south boundary, T.13 N., R. 28 E., executed under Group No. 878.</p> <p>N. 89°57'50" W., bet. secs. 1 and 36.</p> <p>Across level land, covered with shadescale, cheat and bunchgrass.</p> <p>0.20 Left bank of the Walker River, bears NW. and S., thence across river, course S.</p> <p>0.948 True point for the E 1/16 sec. cor. of secs. 1 and 36, at proportionate dist., falls in the Walker River where a permanent monument cannot be established.</p> <p>1.50 Right bank of the Walker River, bears NW. and S., continue across level land.</p> <p>10.951 The E-W 1/64 sec. cor. of secs. 1 and 36, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. as described in the dependent resurvey of a portion of the south boundary, T.13 N., R. 28 E., executed under Group No. 635.</p> <hr/> <p>DEPENDENT RESURVEY OF PORTIONS OF THE SUBDIVISIONAL LINES, T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyors H.E. Franks and J.S. Mullen in 1904</p> <hr/> <p>From the cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., monumented with the lower portion of a concrete filled iron post, 2 ins. diam., 24 ins. long, recovered 6 ins. below the surface of lawn covered ground, with the upper portion found laying alongside, with brass cap mkd. as described in the dependent resurvey of a portion of the S. bdy. of Tp. 13 N., R. 28 E., executed under Group No. 66.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. below the surface of the lawn covered ground, over a plastic-encased magnet, with brass cap mkd.</p>
--------	--

DEPENDENT RESURVEY OF PORTIONS OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T13N R28E S35 S36 S 2 S 1 T12N 2012 Bury lower portion alongside and below top of stainless steel post and insert upper portion inside stainless steel post. S. 0°00'40" E., bet. secs. 1 and 2. Across level, developed land of the State Route Hwy. No. 95 corridor.
14.358	Point determined by Rick P. Christian, Nevada Professional Land Surveyor No. 11178, monumented with a rebar, 5/8 in. diam., firmly set, flush with the ground, with aluminum cap, 1 1/2 ins. diam., mkd. PLS 11178, as shown on Map No. 96118-99, on file with the Mineral County Recorder's Office as Document No. 116759.
20.000	The N 1/16 sec. cor. of secs. 1 and 2, determined by Rick P. Christian, Nevada Professional Land Surveyor No. 11178, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 2 ins. above the ground, with aluminum cap, 1 1/2 ins. diam., mkd. PLS 1/16 11178, as shown on Map No. 96118-99, on file with the Mineral County Recorder's Office as Document No. 116759, and is accepted as a careful and faithful determination of the corner point. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. N 1/16 S 2 S 1 2012 Bury rebar alongside stainless steel post. S. 0°00'40" E., beginning new measurement. Begin posting the boundary of the Walker River Indian Reservation with steel sign posts.
0.55	Barbed wire fence, bears N. 30° W. and S. 30° E.
0.800	Point determined by Rick P. Christian, Nevada Professional Land Surveyor No. 11178, monumented with a rebar, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with plastic cap mkd. PLS 11178, as shown on Map No. 96118-99, on file with the Mineral County Recorder's Office as Document No. 116759.

DEPENDENT RESURVEY OF PORTIONS OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.000	<p>The 1/4 sec. cor. of secs. 1 and 2, reestablished by Rick P. Christian, Nevada Professional Land Surveyor No. 11178, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 5 ins. above the ground, with aluminum cap, 3 1/4 ins. diam., mkd. 1/4 PLS 11178, as shown on Map No. 96118-99, on file with the Mineral County Recorder's Office as Document No. 116759, and is accepted as a careful and faithful reestablishment of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 3 1/2 base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T12N R28E</p> <p>1/4</p> <p>S 2 S 1</p> <p>2012</p> </div> <p>Bury rebar alongside stainless steel post.</p> <hr/> <p>S. 0°00'40" E., beginning new measurement.</p> <p>Discontinue posting the boundary of the Walker River Indian Reservation with steel sign posts.</p>
26.80	Buried fiber optic line, bears N. 14° W. and S. 14° E.
40.000	<p>The cor. of secs. 1, 2, 11 and 12, monumented with a granite stone, 10x5x14 ins. high, firmly set, in a mound of stone, 3 ft. base, 1/2 ft. high, mkd. with 1 notch on the E. edge and 5 notches on the S. edge. (Record:18x10x5 ins.)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T12N R28E</p> <p>S 2 S 1</p> <hr/> <p>S11 S12</p> <p>2012</p> </div> <p>Bury mkd. stone alongside stainless steel post.</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., monumented with an aluminum post, 2 1/2 ins. diam., firmly set flush with the top of a mound of stone, 3 ft. base, 1/2 ft. high, with brass cap mkd. as described in the dependent resurvey</p>

DEPENDENT RESURVEY OF PORTIONS OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>of the west boundary, T.12 N., R. 29 E., executed under Group No. 635.</p> <p>S. 89°57'00" W., bet. secs. 1 and 12.</p> <p>Across gentle E. slope covered with shadescale, cheat and bunchgrass.</p>
20.043	<p>Point for the E 1/16 sec. cor. of secs. 1 and 12.</p> <p>POINT NOT MONUMENTED</p>
40.086	<p>The 1/4 sec. cor. of secs. 1 and 12, monumented with a wood post, 4x3x28 ins. high, firmly set, projecting 12 ins. above the ground, mkd. 4 S1 on the N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T12N R28E S 1 1/4 — S12 2011</p> <p>Bury wood post alongside stainless steel post.</p> <hr/> <p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the dependent resurvey of a portion the E. bdy., T.12 N., R. 28 E., executed under Group No. 497.</p> <p>S. 89°42'10" W., bet. secs. 12 and 13.</p> <p>Across nearly level land covered with shadescale, cheat and bunchgrass.</p>
9.908	<p>Point for the E-E 1/64 sec. cor. of secs. 12 and 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S12 E-E 1/64 S13 2011</p>
19.816	<p>Point for the E 1/16 sec. cor. of secs. 12 and 13.</p>

DEPENDENT RESURVEY OF PORTIONS OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S12 E 1/16 — S13 2011</p>
39.632	<p>The 1/4 sec. cor. of secs. 12 and 13, monumented with a mound of stone, 3 1/2 ft. base, 1 ft. high, with a marble like granite stone, 16x14x4 ins., no marks visible, laying loosely in mound. Accepted south side of mound of stone as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T12N R28E S12 1/4 — S13 2011</p> <p>Bury unmkd. stone alongside stainless steel post.</p>
	<p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the dependent resurvey of a portion of the E. bdy., T.12 N., R. 28 E., executed under Group No. 497.</p> <p>Cor. is located 23 lks. N. of barbed wire fence, bears E. and W. S. 89°40'50" W., bet. secs. 13 and 24.</p> <p>Across nearly level land, covered with shadescale, cheat and bunchgrass, and along N. side of barbed wire fence.</p>
20.002	<p>Point for the E 1/16 sec. cor. of secs. 13 and 24.</p> <p>POINT NOT MONUMENTED</p>
40.004	<p>The 1/4 sec. cor. of secs. 13 and 24, monumented with an unmkd. granite stone, 7x6x24 ins. high, firmly set, projecting 8 ins. above a collar of stone, accepted as the best available evidence of the original corner.</p> <p>At the corner point</p>

DEPENDENT RESURVEY OF PORTIONS OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T12N R28E S13 1/4 — S24 2011</p> <p>Bury unmkd. stone alongside stainless steel post.</p> <hr/> <p>From the cor. of secs. 25, 26, 35 and 36, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. as described in the dependent resurvey of a portion of the subdivisional lines, T.12 N., R. 28 E., executed under Group No. 497, with a mound of stone, 2 ft. base, 2 ft. high, W. of cor.</p> <p>S. 0°18'00" W., bet. secs. 35 and 36.</p> <p>Across mountainous land, covered with shadescale, sagebrush, cheat and bunchgrass.</p> <p>2.00 Ravine, drains ENE.</p> <p>9.70 Spur, slopes NE.</p> <p>20.60 Ravine, drains NE.</p> <p>22.80 Spur, slopes NE.</p> <p>30.40 Ravine, drains NE.</p> <p>39.980 Point for the 1/4 sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the position of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 4 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T12N R28E 1/4 S35 S36 2011</p> <p>47.90 Spur, slopes NE.</p> <p>79.790 The cor. of secs. 35 and 36, on the S. bdy. of the Tp., hereinbefore described.</p> <hr/>
--------	--

DEPENDENT RESURVEY OF PORTIONS OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the cor. of secs. 22, 23, 26 and 27, monumented with an unmkd. granite stone, 9x6x15 ins. high, set upright on top of boulder, 4x1x1/2 ft. high, with a scattered mound of stone, 2 ft. base, 1 ft. high, W. of cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T12N R28E</p> <table> <tr> <td>S22</td><td>S23</td></tr> <tr> <td>S27</td><td>S26</td></tr> </table> <p>2012</p> </div> <p>Bury mkd. stone alongside stainless steel post and incorporate 4 ft. boulder into base of mound.</p> <p>Cor. is located 3.40 chs. S. of spur sloping NE. and 6.50 chs. E. of same spur, bears NE.</p> <p>S. 0°22'50" E., bet. secs. 26 and 27.</p> <p>Across mountainous land, covered with sagebrush, cheat and bunchgrass, with scattered pinon pines on portions of the N. slopes.</p>	S22	S23	S27	S26
S22	S23				
S27	S26				
11.50	Ravine, drains E.				
32.00	Spur, slopes ESE.				
38.30	Ravine, drains ESE.				
39.506	<p>Point for the 1/4 sec. cor. of secs. 26 and 27, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T12N R28E</p> <p>1/4</p> <table> <tr> <td>S27</td><td>S26</td></tr> </table> <p>2012</p> </div> <p>Point is located on spur, slopes ESE., 2.60 chs. WNW. of confluence of ravines, drains E.</p> <p>Begin posting the boundary of the Walker River Indian Reservation with steel sign posts.</p>	S27	S26		
S27	S26				
40.30	Ravine, drains ENE.				
55.80	Top of steep NE. slope.				

DEPENDENT RESURVEY OF PORTIONS OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p> <p>79.012</p>	<p>The cor. of secs. 26, 27, 34 and 35, monumented with a granite stone, 12x12x15 ins. high, firmly set, projecting 5 ins. above the ground, mkd. with 1 notch on S. edge and 2 notches on the E. edge, with a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T12N R28E</p> <table border="1"> <tr> <td>S27</td><td>S26</td></tr> <tr> <td>S34</td><td>S35</td></tr> </table> <p>2011</p> </div> <p>Bury mkd. stone alongside stainless steel post.</p> <hr/> <p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>S. 89°55'30" W., bet. secs. 26 and 35.</p> <p>Across mountainous land, covered with sagebrush, cheat and bunchgrass, posting the boundary of the Walker River Indian Reservation with steel sign posts.</p> <p>2.00 Ravine, drains SE.</p> <p>40.052 The 1/4 sec. cor. of secs. 26 and 35, monumented with a granite stone, 8x6x14 ins. high, firmly set, projecting 6 ins. above the ground, mkd. 1/4 on N. face, with a mound of stone, 4 ft. base, 2 ft. high, N. of cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T12N R28E</p> <p>S26</p> <p>1/4 —</p> <p>S35</p> <p>2011</p> </div> <p>Bury mkd. stone alongside stainless steel post.</p> <hr/> <p>S. 89°58'00" W. beginning new measurement.</p>	S27	S26	S34	S35
S27	S26				
S34	S35				

DEPENDENT RESURVEY OF PORTIONS OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 39.642</p>	<p>The cor. of secs. 26, 27, 34 and 35.</p> <hr/> <p>From the cor. of secs. 15, 16, 21 and 22, determined at intersection of record distances from the original northeasterly and southeasterly bearing trees, from which the original bearing trees</p> <p>A pinon pine, 10 ins. diam., bears N. 72° E., 55 lks. dist., with scribe marks T12NR2E S BT visible on a partially healed blaze. (Record: N. 67° E.)</p> <p>A pinon pine snag, 7 ins. diam., bears S. 32° E., 58 lks. dist., with illegible scribe marks on an open weathered blaze. (Record: S. 33° E.)</p> <p>A down pinon pine, 4 ins. diam., bears S. 43 1/2° W., 73 lks. dist., with scribe marks T12NR visible on open weathered blaze. (Record: S. 48° W., 70 lks.)</p> <p>A pinon pine, 11 1/2 ins. diam., bears S. 89° W., 34 lks. dist., with scribe marks T12 B visible on open weathered blaze. (Record: N. 81° 30' W., 32 lks.)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T12N R28E</p> <table border="1"> <tr> <td>S16</td><td>S15</td></tr> <tr> <td>S21</td><td>S22</td></tr> </table> <p>2012</p> </div> <p>S. 0°42'00" E., bet. secs. 21 and 22.</p> <p>Across mountainous lands, covered with pinon pine, sagebrush, cheat and bunchgrass.</p> <p>2.40 Spur, slopes NE.</p> <p>7.80 Ravine, drains NE.</p> <p>27.40 Spur, slopes NE.</p> <p>33.70 Ravine, drains NE.</p> <p>39.834 Point for the 1/4 sec. cor. of secs. 21 and 22, at proportionate dist.; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>	S16	S15	S21	S22
S16	S15				
S21	S22				

DEPENDENT RESURVEY OF PORTIONS OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>T12N R28E 1/4 S21 S22 2012</p>
	<p>From this cor., U.S.G.S. triangulation station "REESE", monumented with a U.S.G.S. standard brass disk, 4 ins. diam., cemented into rock surface, bears S. 60°11'00" W., 19.205 chs. dist., mkd. REESE 1963, from which the U.S.G.S. reference marks:</p> <p>A U.S.G.S. standard brass disk, 4 ins. diam., cemented into rock surface, bears S. 54°27' E., 47.6 lks. dist., mkd. No. 2.</p> <p>A U.S.G.S. standard brass disk, 4 ins. diam., cemented into rock surface, bears S. 27°58' W., 56.5 lks. dist., mkd. No. 1.</p>
49.00	Spur, and summit of line, slopes E.
60.80	Ravine, drains E.
63.70	Spur, slopes E.
76.70	Ravine, drains E.
79.668	<p>The cor. of secs. 21, 22, 27 and 28, monumented with a basalt stone, 9x7x15 ins. high, firmly set, projecting 5 ins. above ground, mkd. with 2 notches on the S. edge, and 3 notches on the E. edge, from which the original bearing trees</p> <p>A down pinon pine, 14 ins. diam., bears N. 65° E., 14 lks. dist., with scribe marks T12N R2 visible on an open weathered blaze.</p> <p>A pinon pine, 8 ins. diam., bears S. 46° E., 14 lks. dist., with scribe marks T12N R28E visible on a partially healed blaze.</p> <p>A pinon pine stump, 10 ins. diam., bears S. 38° W., 15 lks. dist., with scribe marks 28E S28 visible on an open weathered blaze.</p> <p>A forked pinon pine, 24 ins. diam. at base, bears N. 45° W., 30 lks. dist., with scribe marks T12N R28E S21 BT visible on a partially healed.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

DEPENDENT RESURVEY OF PORTIONS OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div style="text-align: center;"> T12N R28E S21 S22 <hr/> S28 S27 2011 </div>
39.220	<hr/> <p>S. 89°32'20" W., bet. secs. 21 and 28.</p> <p>Across mountainous terrain, covered with pinon pine, sagebrush, cheat and bunchgrass, posting the boundary of the Walker River Indian Reservation with steel sign posts.</p> <p>The 1/4 sec. cor. of secs. 21 and 28, determined at record bearing and dist. from the original S. bearing tree and at record bearing from the NW bearing tree, from which the original bearing trees</p> <p style="padding-left: 40px;">The W. fork, 13 ins. diam., of a pinon pine, bears SOUTH, 17 lks. dist., with scribe marks 1/4 S28 BT visible on a partially healed blaze.</p> <p style="padding-left: 40px;">The S. fork, 8 ins. diam., of a pinon pine, bears N. 25° W., 28 lks. dist., with scribe marks 1/4 S21 BT visible on a partially healed blaze (Record: 18 lks.)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> T12N R28E S21 1/4 — S28 2011 </div>
2.00 10.00 18.00 31.00	<hr/> <p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>S. 2°03'20" W., bet. secs. 27 and 28.</p> <p>Across mountainous terrain, covered with pinon pines, sagebrush, cheat and bunchgrass, posting the boundary of the Walker River Indian Reservation with steel sign posts.</p> <p>Spur, slopes E.</p> <p>Ravine, drains E.</p> <p>Divide of mountains, bears NW. and SE., and summit of line.</p> <p>Descend steep SW. slope.</p>

DEPENDENT RESURVEY OF PORTIONS OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>The 1/4 sec. cor. of secs. 27 and 28, monumented with a granite stone, 9x6x24ins. high, projecting 12 ins. above a scattered mound of stone and talus.(Record: 19x9x6 ins.)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> T12N R28E 1/4 S28 S27 2011 </div> <p>Bury mkd. stone alongside stainless steel post.</p>
	<hr/> <p>From the cor. of secs. 8, 9, 16 and 17, monumented with a granite stone, 9x6x13 ins. high, firmly set, projecting 6 ins. above the ground, mkd. with 4 notches on the S. edge and 4 notches on the E. edge, from which the remaining original bearing trees</p> <p style="padding-left: 40px;">A pinon pine snag, 16 ins. diam., bears N. 55° E., 19 1/2 lks. dist., with scribe marks T12NR28E S9 BT visible on a partially healed blaze. (Record: N. 53° E., 30 lks.)</p> <p style="padding-left: 40px;">The S. fork, 8 ins. diam., of a tri-forked pinon pine, bears S. 26° W., 31 lks. dist., with scribe marks T12NR28E S18 BT visible on a partially healed blaze. (Record: S. 13° W., 17 lks.)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> T12N R28E S 8 S 9 <hr style="width: 50%; margin: 0 auto;"/> S17 S16 2012 </div> <p>Bury mkd. stone alongside stainless steel post.</p> <p>S. 2°40'10" E., bet. secs. 16 and 17.</p> <p>Across mountainous land, covered with pinon pine, sagebrush, cheat and bunchgrass.</p>
15.80	<p>Ravine, drains NE.</p>

DEPENDENT RESURVEY OF PORTIONS OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
24.00	Spur, slopes E.
38.674	<p>The 1/4 sec. cor. of secs. 16 and 17, monumented with the bottom portion of a broken granite stone, 10x6x22 ins., firmly set, the upper portion found lying loose W. of cor., mkd. 1/4, with a mound of stone, 3 ft. base, 1 ft. high, W. of cor. No evidence of original bearing trees was found.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T12N R28E 1/4 S17 S16</p> <p style="text-align: center;">2011</p> <p>Bury mkd. stone portions alongside stainless steel post.</p> <hr/> <p>S. 3°16'40" W., beginning new measurement.</p>
3.00	Ravine, drains NE.
15.00	Ridge, bears E. and W., and summit of line.
23.50	Ravine, drains SE.
35.20	Divide of mountains, bears NW. and SE.
42.104	<p>The cor. of secs. 16, 17, 20 and 21, determined at the E. side of a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, with a granite stone, 16x9x7 ins., mkd. with 3 notches on an edge and 4 notches on an adjacent edge, laying loose on downhill side of mound.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T12N R28E S17 S16 S20 S21</p> <p style="text-align: center;">2011</p> <p>Bury mkd. stone alongside stainless steel post.</p> <hr/> <p>From the cor. of secs. 15, 16, 21 and 22.</p>

DEPENDENT RESURVEY OF PORTIONS OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 89°11'20" W., bet. secs. 16 and 21.
	Across mountainous land, covered with sagebrush, cheat and bunchgrass.
40.496	<p>The 1/4 sec. cor. of secs. 16 and 21, determined at record bearing and distance from evidence of the only remaining original bearing tree</p> <p>A root hole, bears NORTH, 10 lks. dist., with down pinon pine, 15 ins. diam., with scribe marks 1/4 S16 BT visible on a partially healed blaze, laying alongside.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T12N R28E S16 1/4 — S21 2012</p> <p>Cor. is located 1 ch. SE. of confluence of ravines, drains N.</p> <hr/> <p>S. 89°01'30" W., beginning new measurement.</p>
31.70	Divide of mountains, bears NW. and SE.
40.204	<p>The cor. of secs. 16, 17, 20 and 21.</p> <hr/> <p>From the cor. of secs. 5, 6, 7 and 8, determined at record bearing and dist. from the positively identified root hole of the original NW bearing tree, from which the remaining original bearing trees</p> <p>A pinon pine snag, 8 ins. diam., bears N. 76 1/2° E., 73 lks. dist., with scribe marks T12N S visible on a weathered blaze. (Record: N. 73° E., 90 lks.). The weathered blaze faces the determined position and closely agrees with record bearing; however this tree is located on a very steep slope and the record distance does not corroborate the position of the original corner with other bearing tree evidence and was not used in the corner point determination.</p> <p>A downed pinon pine, 9 ins. diam., original position indeterminate, bears S. 72 1/2° E., 100 lks. dist., with scribe marks T12NR28E S7 on upper blaze and BT on lower blaze. (Record: S. 50° E., 78 lks.)</p> <p>A root hole bears N. 24° W., 69 lks. dist., with the down remains of a pinon pine, 8 ins. diam., with scribe marks T12N visible on a weathered blaze, alongside.</p>

DEPENDENT RESURVEY OF PORTIONS OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 3 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 4 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T12N R28E</p> <table> <tr> <td>S 6</td><td>S 5</td></tr> <tr> <td>S 7</td><td>S 8</td></tr> </table> <p>2012</p> </div> <p>from which new bearing objects</p> <p style="padding-left: 40px;">A chiseled X followed by the letters BO, bears S. 30°28' W., 19.0 lks. dist., mkd. on top of a granite boulder, 19x3x1 1/2 ft. high.</p> <p style="padding-left: 40px;">A chiseled X followed by the letters BO, bears S. 84°28' W., 61.6 lks. dist., mkd. on top of a granite boulder, 5x1 1/2x4 ft. high.</p> <p>S. 88°18'20" W., bet. secs. 6 and 7.</p> <p>Across mountainous land, covered with pinon pine, sagebrush, cheat and bunchgrass, posting the boundary of the Walker River Indian Reservation with steel sign posts.</p> <p>1.40 Spur, bears NE. and SW.</p> <p>10.30 Ravine, drains NE.</p> <p>23.00 Bald spur, slopes NE.</p> <p>28.30 Ravine, drains N.</p> <p>41.674 Point for the 1/4 sec. cor. of secs. 6 and 7, at proportionate dist.; there is no remaining evidence of the position of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 13 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T12N R28E</p> <p>S 6</p> <p>1/4 —</p> <p>S 7</p> <p>2012</p> </div> <p>Discontinue posting the boundary of the Walker River Indian Reservation with steel sign posts.</p>	S 6	S 5	S 7	S 8
S 6	S 5				
S 7	S 8				

DEPENDENT RESURVEY OF PORTIONS OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
46.70	Four-wheel drive road, 10 lks. wide, on divide of mountain range, bears N. and S..
82.410	The cor. of secs. 1, 6, 7 and 12 on the W. bdy. of the Tp., hereinbefore described.
	<hr/> <p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>S. 0°01'30" E., bet. secs. 7 and 8.</p> <p>Across mountainous land, covered with pinon pine, sagebrush, cheat and bunchgrass, posting the boundary of the Walker River Indian Reservation with steel sign posts.</p>
13.30	Spur slopes NE.
16.70	Ravine, drains NE.
39.20	Ridge, bears E. and W.
39.660	<p>The 1/4 cor. of secs. 7 and 8, monumented with a pinon pine, 10 ins. diam., mkd. 1/4 S8 on partially healed blaze on E. face, and 1/4 S7 on partially healed blaze on W. face, from which the original bearing trees:</p> <p style="padding-left: 40px;">A forked pinon pine, 12 ins. diam. at base, bears S. 52 3/4° E., 70 lks. dist., with scribe marks 1/4 S8 BT visible on a partially healed blaze at base of tree. (Record: S. 46° E., 60 lks.)</p> <p style="padding-left: 40px;">A forked pinon pine, 12 ins. diam. at base, bears S. 67°3/4 E., 30 1/2 lks. dist., with scribe marks 1/4 S7 BT visible on a weathered blaze at base of tree. (Record: S. 71° W., 25 lks.)</p> <p>from which new bearing objects</p> <p style="padding-left: 40px;">A chiseled X followed by the letters BO, bears N. 40°41' E., 14.6 lks. dist., mkd. on top of a granite boulder, 2x3x1 ft. high.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 21 ins. in the ground over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, for a reference monument, bears S. 19°09' W., 19.7 lks. dist., with brass cap mkd. RM 1/4 S7 2012 13.0 FT TO COR and an arrow pointing to the corner.</p> <hr/> <p>S. 1°25'20" W., beginning new measurement.</p>
23.00	Spur, slopes SE., and divide of mountains.
39.176	The cor. of secs. 7, 8, 17 and 18, monumented with a granite stone, 18x8x8 ins., mkd. with 4 notches on an edge and 5 notches on an adjacent edge, laying loose on the southeast side of a scattered mound of stone, 2 ft. base. Accepted base of stone as

DEPENDENT RESURVEY OF PORTIONS OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>the best available evidence of the position of the corner, from which the original bearing trees</p> <p>A pinon pine, 12 ins. diam., bears N. 23 1/2° E., 101 lks. dist., with scribe marks T12NR28E S8 BT visible on a partially healed blaze. (Record: N. 31° E., 120 lks.)</p> <p>A pinon pine, 12 ins. diam., bears S. 57 1/4° E., 80 lks. dist., with illegible scribe marks visible on a partially healed blaze. (Record: S. 50° E., 85 lks.)</p> <p>A pinon pine, 19 ins. diam., bears N. 27 1/4° W., 71 1/2 lks. dist. with scribe marks T12NR28E S7 BT visible on a partially healed blaze. (Record: N. 47° W., 96 lks.)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <table border="1" data-bbox="876 840 1023 955"> <tr> <td colspan="2">T12N R28E</td></tr> <tr> <td>S 7</td><td>S 8</td></tr> <tr> <td>S18</td><td>S17</td></tr> </table> <p>2011</p> <p>Bury mkd. stone alongside stainless steel post.</p> <p>from which</p> <p>A chiseled X followed by the letters BO, bears N. 79°33' E., 15.6 lks. dist., mkd. on exposed rock surface, size indeterminate.</p> <p>A chiseled X followed by the letters BO, bears N. 28°49' W., 21.4 lks. dist., mkd. on exposed rock face, 6x2 ft. high, 1.5 ft. from bottom edge.</p> <hr/> <p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>N. 89°17'50" W., bet. secs. 8 and 17.</p> <p>Across mountainous terrain, covered with pinon pine, sagebrush, cheat and bunchgrass.</p> <p>40.756 The 1/4 sec. cor. of secs. 8 and 17, determined at intersection of record distances, from the original bearing trees measured from the face of tree blazes for best fit with the record bearings</p> <p>A pinon pine, 12 ins. diam., bears N. 10° E., 71 lks. dist. from center of crown, with scribe marks S8 BT visible on a partially healed blaze.</p>	T12N R28E		S 7	S 8	S18	S17
T12N R28E							
S 7	S 8						
S18	S17						

<p>CHAINS</p>	<div data-bbox="527 258 1458 336"> <p>A pinon pine, 12 ins. diam., bears SOUTH, 26 1/2 lks. dist. from center of crown, with scribe marks. S17 BT visible on a partially healed blaze.</p> </div> <div data-bbox="431 361 737 386"> <p>At the corner point</p> </div> <div data-bbox="431 413 1458 493"> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 3 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> </div> <div data-bbox="859 520 1019 703"> <p>T12N R28E S 8 1/4 — S17 2012</p> </div> <hr/> <div data-bbox="431 770 1117 795"> <p>N. 89°44'30" W., beginning new measurement.</p> </div> <div data-bbox="431 823 1281 875"> <p>Begin posting the boundary of the Walker River Indian Reservation with steel sign posts.</p> </div> <div data-bbox="285 900 1036 928"> <p>12.00 Divide of mountains, bears NW. and SE.</p> </div> <div data-bbox="285 953 972 978"> <p>40.348 The cor. of secs. 7, 8, 17 and 18.</p> </div> <hr/> <div data-bbox="552 1039 1338 1094"> <p>SURVEY OF A PORTION OF THE SOUTH BOUNDARY, T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA</p> </div> <hr/> <div data-bbox="431 1155 1458 1291"> <p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., monumented with a granite stone, 7x6x22ins. high, firmly set 10 ins. in the ground, mkd. with 2 notches on the E edge and with 4 notches on the W. edge. (Record: 32x7x6 ins.) This cor. will now function as the cor. of secs. 34 and 35 only.</p> </div> <div data-bbox="431 1316 734 1344"> <p>At the corner point</p> </div> <div data-bbox="431 1369 1458 1451"> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> </div> <div data-bbox="873 1476 1019 1583"> <p>T12N R28E S34 S35 T11N R28E</p> </div> <div data-bbox="914 1617 977 1644"> <p>2011</p> </div> <div data-bbox="431 1669 1179 1694"> <p>Bury mkd. stone alongside stainless steel post.</p> </div> <div data-bbox="431 1722 1114 1747"> <p>S. 89°47'50" W., on the S. bdy. of sec. 34.</p> </div> <div data-bbox="431 1772 1373 1827"> <p>Across mountainous land, covered with shadscale, cheat and bunchgrass.</p> </div>
---------------	---

SURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.000	<p>Point for the 1/4 sec. cor. of sec. 34 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 4 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> T12N R28E 1/4 S34 <hr/> T11N R28E 2012 </div>
80.000	<p>Point for the cor. of secs. 33 and 34 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> T12N R28E S33 S34 <hr/> T11N R28E 2012 </div> <p>from which</p> <p style="padding-left: 40px;">A chiseled X followed by the letters BO, bears N. 40°48' W., 77.3 lks. dist., mkd. on top of granite boulder, 3x3x2 ft. high.</p> <p>Cor. is located near top W. bank of ravine, drains S.</p> <hr/> <p>S. 89°47'50" W., on the S. bdy. of sec. 33.</p> <p>Across mountainous land, covered with shadescall, cheat and bunchgrass.</p>
6.50	Graded dirt road, 20 lks. wide, bears NE. and SW.
10.50	Power line, bears N. 60° W. and S. 60° E.
17.30	Graded dirt road, 20 lks. wide, bears NW. and SE.
34.30	Top of small hill.
40.000	<p>Point for the 1/4 sec. cor. of sec. 33 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 4 1/2 ft. base, to top, with brass cap mkd.</p>

SURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div style="text-align: center;"> T12N R28E <u>1/4 S33</u> T11N R28E 2012 </div>
80.000	Point for the cor. of secs. 32 and 33 only. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd. <div style="text-align: center;"> T12N R28E <u>S32 S33</u> T11N R28E 2012 </div> <p>From this cor., Bureau of Land Management project marker "PARKER 3-STEP" bears N. 7°20'40" E., 43.024 chs. dist., monumented with an iron post, 1 1/2 ins. diam., projecting 30 ins. above the ground, with aluminum cap, 3 1/2 ins. diam., mkd. BLM PROJECT WR-4 PARKER 3-STEP SEC32 T12 R28 1963</p> <hr/> <p>S. 89°47'50" W., on the S. bdy. of sec. 32.</p> <p>Across mountainous land, covered with shadescale, cheat and bunchgrass, with scattered pinon pine over summit of line.</p>
15.70	Spur, slopes NNE. summit of line.
32.60	Spur, slopes NW. and divide of mountains.
40.000	Point for the 1/4 sec. cor. of sec. 32 only. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd. <div style="text-align: center;"> T12N R28E <u>1/4 S32</u> T11N R28E 2012 </div>
42.40	Ravine, drains SW.
80.000	Point for the cor. of secs. 31 and 32 only. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

SURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">T12N R28E <u>S31 S32</u> T11N R28E 2012</p>
<p>40.000</p>	<p>S. 89°47'50" W., on the S. bdy. of sec. 31.</p> <p>Across rolling land, covered with shadescale, cheat and bunchgrass.</p> <p>Point for the 1/4 sec. cor. of sec. 31 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T12N R28E <u>1/4 S31</u> T11N R28E 2012</p>
<p>71.60</p>	<p>Ravine, drains NW.</p>
<p>75.016</p>	<p>The cor. of Tps. 11 and 12 N., Rs. 27 and 28 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of the east boundary, T. 11 N., R. 27 E., executed under Gp. No. 32, with a displaced stone, 14x13x6 ins., mkd. with 6 notches on an edge and 6 grooves on adjacent face found within a mound of stone, 3 ft. base, 2 ft. high, S. of cor.</p>
	<p style="text-align: center;">SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 21 and 28, hereinbefore described.</p> <p>S. 89°52'00" W., bet. secs. 21 and 28.</p> <p>Across mountainous terrain, covered with pinon pine, sagebrush, cheat and bunchgrass.</p> <p>42.154 Point for the cor. of secs. 20, 21, 28 and 29, determined latitudinally at 160.000 chs. north of the cor. of secs. 32 and 33, on the S. bdy. of the Tp., and longitudinally on a line connecting the cor. of secs. 32 and 33, on the S. bdy. of the Tp. with the cor. of secs. 16, 17, 20 and 21, both hereinbefore described.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, to bedrock, over a plastic-encased</p>

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T12N R28E <div style="display: flex; justify-content: center; align-items: center;"> <div style="border-right: 1px solid black; padding: 0 5px;">S20</div> <div style="padding: 0 5px;">S21</div> </div> <div style="display: flex; justify-content: center; align-items: center;"> <div style="border-right: 1px solid black; padding: 0 5px;">S29</div> <div style="padding: 0 5px;">S28</div> </div> </p> <p style="text-align: center;">2012</p> <p>From this point, the cor. of secs. 32 and 33, on the S. bdy. of the Tp., bears S. 0°13'10" E., 160.001 chs. dist</p> <hr/> <p>N. 0°13'10" W., on the W. bdy. of sec. 21.</p> <p>Across mountainous terrain, covered with pinon pine, sagebrush, cheat and bunchgrass.</p> <p>39.955 The 1/4 sec. cor. of sec. 21 only, determined at intersection with the E-W centerline of sec. 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T12N R28E <div style="display: flex; justify-content: center; align-items: center;"> <div style="border-right: 1px solid black; padding: 0 5px;">1/4</div> <div style="padding: 0 5px;">S21</div> </div> </p> <p style="text-align: center;">2012</p> <p>From this cor., a granite stone, 6x6x24 ins. high, set loosely in a mound of stone, 3 ft. base, 1 ft. high, set by person(s) unknown, bears S. 16°00' W., 1.142 chs. dist., not utilized in the course of this survey.</p> <p>Begin posting the boundary of the Walker River Indian Reservation with steel sign posts.</p> <p>41.20 Spur slopes NW.</p> <p>79.963 The cor. of secs. 16, 17, 20 and 21, hereinbefore described.</p> <hr/> <p>S. 89°49'50." W., on the S. bdy. of sec. 17</p> <p>Across mountainous terrain, covered with pinon pine, sagebrush, cheat and bunchgrass.</p> <p>40.766 Point for the 1/4 sec. cor. of sec. 17 only, determined at intersection with the N-S center line of sec. 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p>
--------	--

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div style="text-align: center;">T12N R28E 1/4 S17</div> <hr style="width: 10%; margin: auto;"/>
	<div style="text-align: center;">2012</div>
80.136	<p>Point for the cor. of secs. 17, 18, 19 and 20, determined latitudinally at 240.000 chs. north of the cor. of secs. 31 and 32, on the S. bdy. of the Tp., and longitudinally on a line connecting the cor. of secs. 31 and 32, on the S. bdy. of the Tp. with the cor. of secs. 7, 8, 17 and 18, both hereinbefore described.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;">T12N R28E S18 S17 <hr style="width: 10%; margin: auto;"/>S19 S20</div> <div style="text-align: center;">2012</div> <p>From this point, the cor. of secs. 31 and 32, on the S. bdy. of the Tp., bears S. 0°15'50" E., 240.002 chs. dist.</p> <p>From this same point, the Bureau of Land Management project marker "HUSSMAN" bears S. 52°03'40" E., 12.226 chs. dist., monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with aluminum cap, 4 ins. diam., mkd. BLM PROJECT HUSSMAN NE1/4 SE1/4 T12N R28E 1954</p> <hr style="width: 80%; margin: 10px auto;"/>
	<p>N. 0°15'50" W., on the W. bdy. of sec. 17.</p> <p>Across mountainous terrain, covered with pinon pine, sagebrush, cheat and bunchgrass.</p>
42.970	<p>Point for the 1/4 sec. cor. of sec. 17 only, determined at intersection with the E-W centerline of sec. 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;">T12N R28E 1/4 S17</div> <div style="text-align: center;">2012</div>
81.589	<p>The cor. of secs. 7, 8, 17 and 18, hereinbefore described.</p> <hr style="width: 80%; margin: 10px auto;"/>

SUBDIVISION OF SECTION 1,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the 1/4 sec. cor. of secs. 1 and 12.</p>
	<p>N. 0°04'20" E., on the N-S centerline of sec. 1.</p>
	<p>Across nearly level land, covered with shadescale, cheat and bunchgrass.</p>
39.958	<p>The center 1/4 sec. cor. of sec. 1, determined by Rick P. Christian, Nevada Professional Land Surveyor No. 11178, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 4 ins. above the ground, with aluminum cap, 1 1/2 ins. diam., mkd. C 1/4 SEC. 1 PLS 11178, as shown on Map No. 96118-99, on file with the Mineral County Recorder's Office as Document No. 116759, and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T12N R28E C 1/4 S 1</p> <p style="text-align: center;">2011</p> <p>Bury rebar alongside stainless steel post.</p> <hr/> <p>N. 0°04'20" E., beginning new measurement.</p> <p>Begin posting the boundary of the Walker River Indian Reservation with steel sign posts.</p>
19.984	<p>The C-N 1/16 sec. cor. of sec. 1, determined by Rick P. Christian, Nevada Professional Land Surveyor No. 11178, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 1 in. above the ground, with aluminum cap, 1 1/2 ins. diam., mkd. PLS 1/16 11178, as shown on Map No. 96118-99, on file with the Mineral County Recorder's Office as Document No. 116759, and is accepted as a careful and faithful determination of the position of the corner, with a weathered redwood post set by person(s) unknown, 2 ins. square, 24 ins. long, sharpened to a point at one end, mkd. 83, laying loose alongside, original position indeterminate.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

SUBDIVISION OF SECTION 1,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div style="text-align: center;"> C N 1/16 S 1 C </div> <div style="text-align: center;">2011</div> <p>Bury rebar and wood post alongside stainless steel post. Discontinue posting the boundary of the Walker River Indian Reservation with steel sign posts.</p> <hr/> <p>N. 0°04'20" E., beginning new measurement.</p> <p>4.996 Point for the C-S-N-N 1/256 sec. cor. of sec. 1.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> C S-N-N 1/256 S 1 C </div> <div style="text-align: center;">2012</div> <p>7.00 Descend into river bottom lands, bears NW. and SE.</p> <p>9.992 Point for the C-N-N 1/64 sec. cor. of sec. 1.</p> <p>POINT NOT MONUMENTED</p> <p>10.70 Graded dirt road, 15 lks. wide, bears NW. and SE., continue across level cultivated land.</p> <p>19.984 The 1/4 sec. cor. of secs. 1 and 36, on the N. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the dependent resurvey of a portion of the S. bdy. of T. 13 N., R. 28 E., executed under Group No. 66 and further described in the dependent resurvey of a portion of the south boundary, T. 13 N., R. 28 E., executed under Group No. 635.</p> <p>Cor. is located on the E. side of a corner of barbed wire fences extending N. and E.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 1 and 6, on the E. bdy. of the Tp., monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. as described in the dependent resurvey of a portion of the west boundary, T. 12 N., R. 29 E., executed under Group No. 635. N. 89°57'00" W., on the E-W center line of sec. 1.</p> <p>Across river bottom lands, covered with shadescale, scattered cottonwoods, cheat and bunchgrass.</p>
--------	--

SUBDIVISION OF SECTION 1,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
9.983	<p>Point for the C-E-E 1/64 sec. cor. of sec. 1, falls in center of graded dirt road, 15 lks. wide, bears NW. and SE.</p> <p>Set a copper coated steel rod, 1/2 in. diam., 24 ins. long, 3 ins. below the surface of the road, with brass cap, 1 1/2 ins. diam., mkd.</p> <div style="text-align: center;"> <p>BLM</p> <p>E-E 1/64</p> <p>C———C</p> <p>S 1</p> <p>2012</p> </div> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 60°40' E., 39.6 lks. dist., with brass cap mkd. RM C-E-E 1/64 S6 26.1 FT TO COR 2012 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 28°56' W., 63.6 lks. dist., with brass cap mkd. RM C-E-E 1/64 S6 42.0 FT TO COR 2012 and an arrow pointing to the corner.</p> <p>From this point, an unmarked rebar, 5/8 in. diam., firmly set, flush with surface of graded dirt road, established by George M. Wilson, Nevada Professional Land Surveyor No. 3806, as shown on the Parcel Map of Allotment No. 212, on file with the Mineral County Recorder's Office as Document No. 26528, bears N. 6°30' W., 0.038 chs. dist., cannot be reconciled with proper procedures, not utilized in the course of this survey.</p>
11.80	<p>From this point, the E. end of a barbed wire fence extending W., bears N., 13 lks. dist., at top of old river cut, leave river bottom lands and scattered cottonwoods, continue along S. side of barbed wire fence.</p>
19.966	<p>Point for the C-E 1/16 sec. cor. of sec. 1.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>E 1/16</p> <p>C———C</p> <p>S 1</p> <p>2012</p> </div> <p>From this point, an unmarked rebar, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, established by George M. Wilson, Nevada Professional Land Surveyor No. 3806, as shown on the Parcel Map of Allotment No. 212, on file with the Mineral</p>

SUBDIVISION OF SECTION 1,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>County Recorder's Office as Document No. 26528, bears N. 28°51' W., 0.070 chs. dist., cannot be reconciled with proper procedures, not utilized in the course of this survey.</p> <p>From this same point, the corner of barbed wire fences extending N. and E., bears N. 22° W., 0.07 chs. dist.</p>
29.949	<p>Point for the C-W-E 1/64 sec. cor. of sec. 1.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>W-E 1/64</p> <p>C——C</p> <p>S 1</p> <p>2012</p> </div>
39.932	<p>The center 1/4 sec. cor. of sec. 1.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°57'00" W., beginning new measurement.</p>
19.928	<p>The C-W 1/16 sec. cor. of sec. 1, determined by Rick P. Christian, Nevada Professional Land Surveyor No. 11178, monumented with a rebar, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with aluminum cap, 1 1/2 ins. diam., mkd. PLS 1/16 11178, as shown on Map No. 96118-99, on file with the Mineral County Recorder's Office as Document No. 116759, and is accepted as a careful and faithful determination of the position of the corner.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°57'00" W., beginning new measurement.</p> <p>Begin posting the boundary of the Walker River Indian Reservation with steel sign posts.</p>
10.40	<p>Asphalt surface, State Hwy. No. 95, 50 lks. wide, bears N. 11° W. and S. 11° E.</p>
10.70	<p>Barbed wire fence, parallels highway.</p>
19.928	<p>The 1/4 sec. cor. of secs. 1 and 2.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the C-E 1/16 sec. cor. of sec. 1.</p> <p>N. 0°07'40" E., on the N-S center line of the NE 1/4 of sec. 1.</p> <p>Across nearly level land, covered with shadescale, cheat and bunchgrass, along barbed wire fence.</p>
11.90	<p>From this point, the N. end of barbed wire fence bears E., 7 lks. dist., descend into river bottom lands, continue through scattered cottonwoods.</p>

SUBDIVISION OF SECTION 1,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
12.70	Graded dirt road, 15 lks. wide, bears NW. and SE.
14.10	Corner of barbed wire fences, extending N. and W., continue along E. side of cultivated field.
19.990	Point for the NE 1/16 sec. cor. of sec. 1, at intersection with the E-W center line of the NE1/4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. NE 1/16 S 1 2012 From this point, a rebar, 5/8 in. diam., firmly set 6 ins. below the surface of the ground, no marks found, established by George M. Wilson, Nevada Professional Land Surveyor No. 3806, as shown on the Parcel Map of Allotment No. 212, on file with the Mineral County Recorder's Office as Document No. 26528, bears S. 18°35' E., 0.056 chs. dist., cannot be reconciled with proper methods, not utilized in the course of this survey. Rebar is located on the N. side of a corner of barbed wire fences extending N., irregularly E., and S.
21.80	Corner of barbed wire fences, extending S. and SW., leave E. side of cultivated field, continue through dense willows.
25.60	Right bank of the Walker River, bears NW. and SE., thence across river, course SE.
26.00	Left bank of the Walker River, bears NW. and SE.
31.00	Left bank of the Walker River, bears NNE. and SW., thence across river, course SW.
39.977	The true point for the E. 1/16 sec. cor. of secs. 1 and 36, on the N. bdy. of the Tp. <hr/> From the N 1/16 sec. cor. of secs. 1 and 6, on the E. bdy. of the Tp., monumented with an aluminum post, 2 1/2 ins. diam., firmly set flush with the ground, with aluminum cap mkd. as described in the dependent resurvey of a portion of the west boundary, T.13 N., R. 28 E., executed under Group No. 635. Cor. is located on the W. side of a corner of barbed wire fences, bearing E., S. and W. N. 89°57'40" W., on the E-W center line of the NE 1/4 of sec. 1. Across level river bottomlands, covered with scattered cottonwoods, shadescale, and cheat grass, and along barbed wire fence.
9.994	Point for the C-E-NE 1/64 sec. cor. of sec. 1, occupied with an unmarked rebar, 5/8 in. diam., 21 ins. long, projecting 6 ins.

SUBDIVISION OF SECTION 1,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>above the ground, established by George M. Wilson, Nevada Professional Land Surveyor No. 3806, as shown on the Parcel Map of Allotment No. 212, on file with the Mineral County Recorder's Office as Document No. 26528.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 1 C-E-NE 1/64 2012</p> <p>Deposit rebar inside stainless steel post.</p> <p>12.00 Left bank of the Walker River, bears NW. and SE., thence across river, course SE.</p> <p>13.00 Right bank of the Walker River, bears NW. and SE.</p> <p>19.98 Barbed wire fence, bears N. and S.</p> <p>19.988 The NE 1/16 sec. cor. of sec. 1.</p> <p>Continue across cultivated field.</p> <p>29.50 Barbed wire fence, bears N. and S., leave cultivated field.</p> <p>29.981 Point for the C-W-NE 1/16 sec. cor. of sec. 1. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 1 C-W-NE 1/64 2012</p> <p>31.00 Graded dirt road, 15 lks. wide, bears NNE. and SSW.</p> <p>Leave river bottom lands, continue across rolling land, through shadescale, cheat and bunchgrass.</p> <p>39.974 The C-N 1/16 sec. cor. of sec. 1.</p> <hr/> <p>From the C-E-NE 1/64 sec. cor. of sec. 1.</p> <p>N. 0°09'40" E., on the N-S center line of the NE1/4NE1/4 of sec. 1.</p> <p>Across river bottomlands, covered with scattered cottonwoods, and shadescale.</p>
--------	---

SUBDIVISION OF SECTION 1,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
2.00	Enter cultivated field, bears NW. and SE.
19.987	The E-E 1/64 sec. cor. of secs. 1 and 36, on the N. bdy. of the Tp., monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. as described in the dependent resurvey of a portion of the south boundary, T. 13 N., R. 28 E., executed under Group No. 635.
	From the C-E-E 1/64 sec. cor. of sec. 1.
	N. 0°09'30" E., on the N-S center line of the SE1/4NE1/4 of sec. 1.
	Across level river bottomlands, covered with scattered cottonwoods, shadescale, with willows along river.
0.08	S. end, barbed wire fence, continue along barbed wire fence.
15.00	Right bank of the Walker River, bears NW. and SE., thence across river, course SE.
16.00	Left bank of the Walker River, bears NW. and SE.
19.96	Corner of barbed wire fences, extending E. and S.
19.993	The C-E-NE 1/64 sec. cor. of sec. 1.
	From the C-W-E 1/64 sec. cor. of sec. 1.
	N. 0°06'00" E., on the N-S center line of the SW1/4NE1/4 of sec. 1.
	Across nearly level land, covered with scattered cottonwoods, shadescale, cheat and bunchgrass.
2.30	Dirt road, 15 lks. wide, bears WNW. and SE.
12.50	Descend into river bottom lands, continue through scattered cottonwoods.
13.80	Graded dirt road, 15 lks. wide, bears NW. and SE., from this point, the corner of barbed wire fences, extending N. and irregularly SE., bears E., 0.58 chs. dist., continue along W. side of barbed wire fence.
19.988	The C-W-NE 1/64 sec. cor. of sec. 1.
	N. 0°05'20" E., on the N-S center line of the NW1/4NE1/4 of sec. 1.
	Across level river bottomlands, covered with scattered cottonwoods, and along erratic barbed wire fence.
4.00	Graded dirt road, 15 lks. wide., bears NE. and SW.

SUBDIVISION OF SECTION 1,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
4.996	<p>Point for the C-S-NW-NE 1/256 sec. cor. of sec. 1.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 1 C-S-NW-NE 1/256 2012</p> <p>Point is located at base of slope ascending from river bottomlands.</p>
6.20	<p>Graded dirt road, 15 lks. wide, bears NW. and SE., continue across cultivated lands, and along barbed wire fence, extending irregularly N.</p>
9.992	<p>Point for the NW-NE 1/64 sec. cor. of sec. 1.</p> <p>POINT NOT MONUMENTED</p>
19.983	<p>The W-E 1/64 sec. cor. of secs. 1 and 36, on the N. bdy. of the Tp., monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with aluminum cap mkd. as described in the dependent resurvey of a portion of the south boundary, T. 13 N., R. 28 E., executed under Group No. 635.</p> <hr/> <p>From the C-S-NW-NE 1/256 cor. of sec. 1.</p> <p>N. 89°57'40" W., on the E-W center line of the SW1/4NW1/4NE1/4 of sec. 1.</p> <p>Ascend from river bottom lands, covered with scattered shadescall, cheat and bunchgrass.</p>
1.00	<p>Top of ascent from river bottom lands, bears NW. and S., continue across nearly level lands covered with shadescall, cheat and bunchgrass.</p>
9.994	<p>The C-S-N-N 1/256 sec. cor. of sec. 1.</p> <hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 2, T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 2 and 11, monumented with a granite stone, 6x4x15 ins. high, firmly set, projecting 10 ins. above the ground, mkd. 1/4 on N. face, with a mound of stone, 3 ft. base, 1 1/2 ft. high.</p> <p>At the corner point</p>

SUBDIVISION OF SECTION 2,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T12N R28E S 2 1/4 — S11 2011</p> <p>Bury mkd. stone alongside stainless steel post.</p> <p>N. 0°04'20" W., on the N-S center line of sec. 2.</p> <p>Across gentle NE. slope, covered with shadescall, cheat and bunchgrass.</p>
40.102	<p>Point for the center 1/4 sec. cor. of sec. 2, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T12N R28E C 1/4 S 2 2011</p>
53.30	Dirt road, 10 lks. wide, bears NW. and SE.
57.00	Dirt road, 10 lks. wide, bears NE. and SW.
60.084	<p>Point for the C-N 1/16 sec. cor. of sec. 2.</p> <p>POINT NOT MONUMENTED</p>
70.50	Dirt road, 10 lks. wide, bears NE. and SW.
80.066	<p>The 1/4 sec. cor. of secs. 2 and 35, on the N. bdy. of the Tp., monumented with a stainless steel post, firmly set, projecting 2 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion the south boundary, T.12 N., R. 29 E., executed under Group No. 827, with a mound of stone, 2 ft. base, 1 ft. high, N. of cor.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 1 and 2.</p> <p>N. 89°51'50" W., on the E-W center line of sec. 2.</p> <p>Across gentle NE. slope, covered with shadescall, cheat and bunchgrass.</p>
6.70	Buried fiber optic line, bears N. 14° W. and S. 14° E.
20.104	Point for the C-E 1/16 sec. cor. of sec. 2.

SUBDIVISION OF SECTION 2,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	POINT NOT MONUMENTED
40.208	The center 1/4 sec. cor. of sec. 2.
53.70	Dirt road, 10 lks. wide, bears NE. and SW.
80.626	The 1/4 sec. cor. of secs. 2 and 3, monumented with a granite stone, 8x7x14 ins. high, firmly set, projecting 6 ins. above the ground, mkd. 1/4 on the W. face, with a mound of stone, 2 1/2 ft. base, 1 ft. high, W. of cor. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T12N R28E 1/4 S 3 S 2 2011 Deposit mkd. stone alongside stainless steel post. <hr/>
	From the point for the C-E 1/16 sec. cor. of sec. 2. N. 0°02'30" W., on the N-S center line of the NE1/4 of sec. 2. Across gentle NE. slope, covered with shadescale, cheat and bunchgrass.
7.40	Dirt road, 10 lks. wide, bears NW. and SE.
19.991	Point for the NE 1/16 sec. cor. of sec. 2, at intersection with the E-W center line of the NE1/4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. NE 1/16 S 2 2011 Begin posting the boundary of the Walker River Indian Reservation with steel sign posts.
32.10	Buried fiber optic line, bears N. 40° W. and S. 40° E.
39.985	The E 1/16 sec. cor. of secs. 2 and 35, on the N. bdy. of the Tp., monumented with a stainless steel post, firmly set, projecting 2 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion the south boundary, T.12 N., R. 29 E., executed under Group No. 827. <hr/>

SUBDIVISION OF SECTION 2,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the N 1/16 sec. cor. of secs. 1 and 2.</p> <p>N. 89°53'30" W., on the E-W center line of the NE1/4 of sec. 2.</p> <p>Across gentle NE. slope, covered with shadescall, cheat and bunchgrass.</p>
11.50	Buried fiber optic line, bears N. 14° W. and S. 14° E.
20.114	<p>The NE 1/16 sec. cor. of sec. 2.</p> <p>Discontinue posting the boundary of the Walker River Indian Reservation with steel sign posts.</p>
35.20	Dirt road, 10 lks. wide, bears NE. and SW.
40.228	The point for the C-N 1/16 sec. cor. of sec. 2.
<p style="text-align: center;">SUBDIVISION OF SECTION 6, T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA</p>	
	<p>From the 1/4 sec. cor. of secs. 6 and 7.</p> <p>N. 0°52'20" E., on the N-S center line of sec. 6.</p> <p>Across mountainous terrain, covered with pinon pine, sagebrush, cheat and bunchgrass, posting the boundary of the Walker River Indian Reservation with steel sign posts.</p>
12.00	Spur bears NE. and summit of line.
37.60	Ravine, drains ENE.
40.865	<p>Point for the center 1/4 sec. cor. of sec. 6, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 2 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 4 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T12N R28E C 1/4 S 6 2012</p> <p>Discontinue posting the boundary of the Walker River Indian Reservation with steel sign posts.</p>
53.00	Ravine, drains ENE.
64.20	Ravine, drains ENE.
81.623	The 1/4 sec. cor. of secs. 1 and 36, on the N. bdy. of the Tp., monumented with a stainless steel post, firmly set, flush with the top of a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd. as described in the field notes of the dependent

SUBDIVISION OF SECTION 6,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>resurvey of a portion of the south boundary, T.13 N., R. 28 E., executed under Group No. 878.</p> <p>from which</p> <p style="padding-left: 40px;">An unrecorded pinon pine, 8 ins. diam., bears N. 71 1/2° E., 25 1/2 lks. dist., with scribe marks T12N R visible on a partially healed weathered blaze facing cor.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 5 and 6, monumented with a faint chiseled X mkd near the N. edge of flat top surface of a granite boulder, 8x11x5 ft. high, from which the original bearing trees</p> <p style="padding-left: 40px;">A pinon pine, 8 ins. diam., bears S. 83° E., 15 lks. dist., with scribe marks 4 B visible on a partially healed blaze. (Record: EAST)</p> <p style="padding-left: 40px;">A down pinon pine, 5 ins. diam., bears S. 72° E., 46 lks. dist., with scribe marks 1/4 S6 BT visible on a weathered blaze. (Record: S. 76° W., 37 lks.)</p> <p>At the corner point</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 in. stem, cemented into a drill hole, 3/4 in. diam, 3 1/2 ins. deep, 1 ft. from N. edge of boulder 12 x 10 x 4 ft. high with top mkd.</p> <p style="text-align: center;">T12N R28E 1/4 S 6 S 5 2012</p> <p>S. 89°40'30" W., on the E-W center line of sec. 6.</p> <p>Across mountainous terrain, covered with pinon pine, sagebrush, cheat and bunchgrass.</p> <p>4.70 Ravine, drains NE.</p> <p>30.70 Ravine, drains NE.</p> <p>41.092 The center 1/4 sec. cor. of sec. 6.</p> <p>78.289 The 1/4 sec. cor. of secs. 1 and 6, on the W. bdy. of the Tp.</p> <hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 12, T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 12 and 13.</p> <p>N. 0°11'40" W., on the N-S center line of sec. 12.</p>
--------	--

SUBDIVISION OF SECTION 12,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Across gentle E. slope, covered with shadescale, cheat and bunchgrass.
15.00	Dirt road, 15 lks. wide, bears NW. and SE.
19.971	Point for the C-S 1/16 sec. cor. of sec. 12.
	POINT NOT MONUMENTED
28.30	Dirt road, 15 lks. wide, bears NNW. and SSE.
39.942	Point for the center 1/4 sec. cor. of sec. 12, at intersection with the E-W center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.
	T12N R28E C 1/4 S12
	2011
48.50	Dirt road, 15 lks. wide, bears NNW. and SSE.
50.60	Dirt road, 15 lks. wide, bears NE. and SW.
59.984	Point for the C-N 1/16 sec. cor. of sec. 12.
	POINT NOT MONUMENTED
80.026	The 1/4 sec. cor. of secs. 1 and 12.
	From the 1/4 sec. cor. of secs. 7 and 12, on the E. bdy. of the Tp., monumented with a stainless steel post, firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion the west boundary, T.12 N., R. 29 E., executed under Group No. 827.
	N. 89°56'50" W., on the E-W center line of sec. 12.
	Across gentle E. slope, covered with shadescale, cheat and bunchgrass.
9.953	Point for the C-E-E 1/64 sec. cor. of sec. 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a supporting collar of stone, with brass cap mkd.
	E-E 1/64 C——C S12
	2011

SUBDIVISION OF SECTION 12,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	From this point, a steel fence post set by person(s) unknown, projecting 3 1/2 ft. above a collar of stone, bears S. 65°54' W., 0.060 chs. dist., not utilized in the course of this survey.
19.906	<p>Point for the C-E 1/16 sec. cor. of sec. 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>E 1/16</p> <p>C——C</p> <p>S12</p> <p>2012</p> </div> <p>From this point, a redwood post set by person(s) unknown, 2x3 ins., firmly set, projecting 16 ins. above the ground, with illegible scribe marks visible on E. face, bears S. 83°02' W., 0.101 chs. dist., not utilized in the course of this survey.</p> <p>From this same point, a steel fence post set by person(s) unknown, projecting 4 ft. above a collar of stone, bears S. 74°43' W., 0.114 chs. dist., not utilized in the course of this survey.</p>
29.40	Dirt road, 15 lks. wide, bears NW. and SE.
39.812	The center 1/4 sec. cor. of sec. 12.
55.20	Asphalt surface, Nevada State Hwy. No. 95, 50 lks. wide, bears N. 11° W. and S. 11° E.
79.740	<p>The 1/4 sec. cor. of secs. 11 and 12, monumented with a granite stone, 13x5x16 ins. high, firmly set, projecting 5 ins. above the ground, mkd. 1/4 on the W. face, with a mound of stone 3 ft. base, 1 ft. high, W. of cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T12N R28E</p> <p>1/4</p> <p>S11 S12</p> <p>2011</p> </div> <p>Bury mkd. stone alongside stainless steel post.</p> <hr/> <p>From the C-E-E 1/64 sec. cor. of sec. 12.</p>

SUBDIVISION OF SECTION 12,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>N. 0°06'00" E., on a portion of the computed N-S center line of the SE1/4NE1/4 of sec. 12.</p> <p>Across gentle E. slope, covered with shadescale, cheat and bunchgrass.</p>
10.034	<p>The computed point for the SE-NE 1/64 sec. cor. of sec. 12, at intersection with the computed E-W center line of the SE1/4NE1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: right;">S12 SE-NE 1/64 2011</p>
9.971	<p>S. 89°58'30" E., on a portion of the computed E-W center line of the SE1/4NE1/4 of sec. 12.</p> <p>Across gentle E. slope, covered with shadescale, cheat and bunchgrass.</p> <p>The S-N 1/64 sec. cor. of secs. 7 and 12, on the E. bdy. of the Tp., monumented with a stainless steel post, firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the W. bdy of T.12 N., R. 29 E., executed under Group No. 827.</p> <p>From this cor., a steel fence post set by person(s) unknown, projecting 4 1/2 ft. above the ground, bears NW., 0.034 chs. dist., not utilized in the course of this survey.</p>
6.10	<p>From the E 1/16 sec. cor. of secs. 12 and 13.</p> <p>N. 0°03'40" W., on the N-S center line of the SE1/4 of sec. 12.</p> <p>Across gentle E. slope, covered with shadescale, cheat and bunchgrass.</p>
19.910	<p>Dirt road, 15 lks. wide, bears NW. and SE.</p> <p>Point for the SE 1/16 sec. cor. of sec. 12, at intersection with the E-W center line of the SE1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a supporting stone base set around the post below surface of ground, with brass cap mkd.</p> <p style="text-align: right;">SE 1/16 S12 2011</p>

SUBDIVISION OF SECTION 12,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From this point, a steel fence post set by person(s) unknown, projecting 4 ft. above a collar of stone, bears N. 56°33' W., 0.158 chs. dist., not utilized in the course of this survey.</p>
39.820	<p>The C-E 1/16 sec. cor. of sec. 12.</p> <hr/> <p>From the S 1/16 sec. cor. of secs. 7 and 12, on the E. bdy. of the Tp., monumented with a stainless steel post, firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the dependent resurvey of a portion of the west boundary, T.12 N., R. 29 E., executed under Group No. 827.</p> <p>S. 89°52'40" W., on the E-W center line of the SE1/4 of sec. 12.</p> <p>Across gentle E. slope, covered with shadescale, cheat and bunchgrass.</p>
9.930	<p>Point for the C-E-SE 1/64 sec. cor. of sec. 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">S12 C-E-SE 1/64 2011</p> <p>From this point, a redwood post set by person(s) unknown, 2 ins. square, laying loose on top of mound of stone, 1 ft. base, 1/2 ft. high, bears N. 17°14' W., 0.046 chs. dist., not utilized in the course of this survey.</p> <p>From this same point, a steel fence post set by person(s) unknown, projecting 4 ft. above a collar of stone, bears N. 55°45' W., 0.085 chs. dist., not utilized in the course of this survey.</p>
19.860	<p>The SE 1/16 sec. cor. of sec. 12.</p>
39.721	<p>The point for the C-S 1/16 sec. cor. of sec. 12.</p> <hr/> <p>From the C-E-SE 1/64 sec. cor. of sec. 12.</p> <p>N. 0°00'30" E., on the N-S center line of the NE1/4SE1/4 of sec. 12.</p> <p>Across gentle E. slope, covered with shadescale, cheat and bunchgrass.</p>
19.879	<p>The C-E-E 1/64 sec. cor. of sec. 12.</p> <hr/> <p>From the E-E 1/64 sec. cor. of secs. 12 and 13.</p>

SUBDIVISION OF SECTION 12,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>N. 0°00'30" E., on the N-S center line of the SE1/4SE1/4 of sec. 12.</p> <p>Across gentle E. slope, covered with shadescale, cheat and bunchgrass.</p>
19.879	<p>The C-E-SE 1/64 sec. cor. of sec. 12.</p>
<p style="text-align: center;">SUBDIVISION OF SECTION 13, T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA</p>	
	<p>From the 1/4 sec. cor. of secs. 13 and 24.</p> <p>N. 0°17'50" E., on the N-S center line of sec. 13.</p> <p>Across nearly level land covered with shadescale, cheat and bunchgrass.</p>
11.70	<p>Buried fiber optic line, bears N. 14° W. and S. 14° E.</p>
20.061	<p>Point for the C-S 1/16 sec. cor. of sec. 13.</p>
	<p>POINT NOT MONUMENTED</p>
	<p>From this point, a Nevada Highway Dept. brass tablet, 3 1/2 ins. diam., firmly set flush in a concrete base, 1 1/2 ft. square, flush with the ground, bears S. 32°53'50" E., 5.199 chs. dist., mkd. DIST 100 STA C4678718POT ANGLE 90.</p>
38.50	<p>Asphalt surface, Nevada State Highway No. 95, 50 lks. wide, bears N. 11° W. and S. 11° E.</p>
40.122	<p>Point for the center 1/4 sec. cor. of sec. 13, at intersection with the E-W center line, falls on the E. shoulder of Nevada State Highway No. 95.</p> <p>Set a copper coated steel rod, 1/2 in. diam., 24 ins. long, flush with surface of the ground, with brass cap, 1 1/2 ins. diam., mkd.</p>
	<p style="text-align: center;">BLM T12N R28E C 1/4 S13</p>
	<p style="text-align: center;">2011</p>
	<p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, for a reference monument, bears N. 22°58' E., 142.6 lks. dist., with brass cap mkd. RM C 1/4 S13 94.1 FT TO COR 2012 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground over a plastic-encased magnet, and in collar of stone, for a reference monument, bears</p>

SUBDIVISION OF SECTION 13,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	S. 63°18' E., 103.9 lks. dist., with brass cap mkd. RM C 1/4 S13 68.6 FT TO COR 2012 and an arrow pointing to the corner.
60.070	Point for the C-N 1/16 sec. cor. of sec. 13. POINT NOT MONUMENTED
80.018	The 1/4 sec. cor. of secs. 12 and 13. From the 1/4 sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp., monumented with an iron post, firmly set, projecting 4 ins. above the ground, with brass cap erroneously described as being marked for the 1/4 sec. cor. of secs. 7 and 12 in the field notes of the dependent resurvey of a portion of the east boundary, T.12 N., R. 28 E., executed under Group No. 497. Markings were found correct with brass cap mkd: <div style="text-align: center;">T12N R28E R29E 1/4 S13 S18 1973</div> <p>From this cor., a decomposed granite stone of unknown origin, 16x7x5 ins., firmly set projecting 10 ins. above the ground, no marks visible, bears S. 3°00' W., 0.61 chs. dist., with a wood post, 6x8 ins., firmly set, projecting 6 ft. above ground, set on S. side of unmarked stone. This stone was not noted or recognized in the 1973 dependent resurvey of a portion of the east boundary, T.12 N., R. 28 E., executed under Group No. 497, was not utilized during the dependent resurvey of a portion of the west boundary, T.12 N., R. 29 E., executed under Group No. 827 and is not utilized in the course of this survey.</p> <p>S. 89°50'40" W., on the E-W center line of sec. 13.</p> <p>Across nearly level land covered with shadegrass, cheat and bunchgrass.</p>
9.957	Point for the C-E-E 1/64 sec. cor. of sec. 13. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;">E-E 1/64 C——C S13 2011</div> <p>From this point, the weathered remains of a redwood post set by person(s) unknown, 2 ins. square, firmly set, projecting 6 ins. above a mound of stone, 3 ft. base, 1/2 ft. high, bears</p>

SUBDIVISION OF SECTION 13,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>S. 3°17' W., 0.479 chs. dist. This position cannot be reconciled with controlling corners and is not utilized in the course of this survey.</p>
19.914	<p>Point for the C-E 1/16 sec. cor. of sec. 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>E 1/16</p> <p>C———C</p> <p>S13</p> <p>2011</p> </div> <p>From this cor., a weathered redwood post set by person(s) unknown, 3x2 ins., firmly set, projecting 10 ins. above the ground, mkd. 85 on the N. side, bears S. 3°17' W., 0.479 chs. dist. This position cannot be reconciled with controlling corners and is not utilized in the course of this survey.</p>
38.00	Graded dirt road, 20 lks. wide, bears NE. and SW.
39.828	The center 1/4 sec. cor. of sec. 13.
39.91	E. edge of asphalt surface, Nevada State Highway No. 95, 50 lks. wide, bears N. 11° W. and S. 11° E.
47.00	Buried fiber optic line, bears N. 14° W. and S. 14° E.
79.876	<p>The 1/4 sec. cor. of secs. 13 and 14, monumented with a granite stone, 12x6x14 ins. high, firmly set, projecting 6 ins. above the ground, mkd. 1/4 on W. face, with a mound of stone, 2 1/2 ft. base, 1 ft. high, W. of cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T12N R28E</p> <p>1/4</p> <p>S14 S13</p> <p>2011</p> </div> <p>Bury mkd. stone alongside stainless steel post.</p> <p>Cor. is located in bottom of small ravine, drains E.</p> <hr/> <p>From the C-E 1/16 sec. cor. of sec. 13.</p> <p>N. 0°09'30" E., on the N-S center line of the NE1/4 of sec. 13.</p>

SUBDIVISION OF SECTION 13,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Across nearly level land covered with shadescale, cheat and bunchgrass.
19.972	Point for the NE 1/16 sec. cor. of sec. 13, at intersection with the E-W center line of the NE1/4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. NE 1/16 S13 2011
39.944	The E 1/16 sec. cor. of secs. 12 and 13. <hr/> From the N 1/16 sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp., monumented with a stainless steel post, firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the west boundary, T. 12 N., R. 29 E., executed under Group No. 827. S. 89°46'20" W., on the E-W center line of the NE1/4 of sec. 13. Across nearly level land covered with shadescale, cheat and bunchgrass.
9.932	Point for the C-E-NE 1/64 sec. cor. of sec. 13. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. S13 C-E-NE 1/64 2011
19.864	The NE 1/16 sec. cor. of sec. 13.
39.728	The point for the C-N 1/16 sec. cor. of sec. 13. <hr/> From the C-E-NE 1/64 sec. cor. of sec. 13. N. 0°05'20" E., on the N-S center line of the NE1/4NE1/4 of sec. 13. Across nearly level land covered with shadescale, cheat and bunchgrass.
19.984	The E-E 1/64 sec. cor. of secs. 12 and 13. <hr/> From the C-E-E 1/64 sec. cor. of sec. 13.

SUBDIVISION OF SECTION 13,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°05'20" E., on the N-S center line of the SE1/4NE1/4 of sec. 13. Across nearly level land covered with shadescall, cheat and bunchgrass.
19.985	The C-E-NE 1/64 sec. cor. of sec. 13. <hr/>
	From the point for the E 1/16 sec. cor. of secs. 13 and 24. N. 0°10'30" E., on the N-S center line of the SE1/4 of sec. 13. Across nearly level land covered with shadescall, cheat and bunchgrass.
20.031	Point for the SE 1/16 sec. cor. of sec. 13, at intersection with the E-W center line of the SE1/4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. SE 1/16 S13 2011
40.063	The C-E 1/16 sec. cor. of sec. 13. <hr/>
	From the S 1/16 sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp., monumented with a stainless steel post, firmly set, projecting 3 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the west boundary, T. 12 N., R. 29 E., executed under Group No. 827. S. 89°45'40" W., on the E-W center line of the SE1/4 of sec. 13. Across nearly level land covered with shadescall, tamarisk, cheat and bunchgrass.
9.979	Point for the C-E-SE 1/64 sec. cor. of sec. 13. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. S13 C-E-SE 1/64 2011
	Cor. is located on northerly edge of tamarisk.
19.958	The SE 1/16 sec. cor. of sec. 13.

SUBDIVISION OF SECTION 13,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.916	The point for the C-S 1/16 sec. cor. of sec. 13.
	<hr/> <p>From the C-E-SE 1/64 sec. cor. of sec. 13.</p> <p>N. 0°06'40" E., on the N-S center line of the NE1/4SE1/4 of sec. 13.</p> <p>Across nearly level land covered with shadescale, cheat and bunchgrass.</p>
20.018	The C-E-E 1/64 sec. cor. of sec. 13.
	<hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 17, T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 8 and 17.</p> <p>S. 0°25'30" W., on the N-S center line of sec. 17, determined on a bearing parallel with a weighted average of the E. bdy. of sec. 17.</p> <p>Across mountainous land, covered with pinon pine, sagebrush, cheat and bunchgrass, posting the boundary of the Walker River Indian Reservation with steel sign posts.</p>
4.00	Spur, slopes SW.
26.00	Ravine, drains SW.
38.774	Point for the center 1/4 sec. cor. of sec. 17, at intersection with the E-W center line.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T12N R28E C 1/4 S17</p> <p style="text-align: center;">2012</p> <p>From this point, a squared wood post set by person(s) unknown, 3x3x42 ins., no marks visible, laying over a mound of stone, 3 ft. base 1 ft. high, bears N. 61°39' E., 1.046 chs. dist., not utilized in the course of this survey.</p> <p>Discontinue posting the boundary of the Walker River Indian Reservation with steel sign posts.</p>
46.50	Divide of mountains, bears NW. and SE.
81.294	Point for the 1/4 sec. cor. of sec. 17 only, on the S. bdy. of sec. 17.
	<hr/>

SUBDIVISION OF SECTION 17,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the 1/4 sec. cor. of secs. 16 and 17.</p> <p>N. 89°31'10" W., on the E-W center line of sec. 17, determined on a bearing parallel with a weighted mean average of the N. bdy. of sec. 17.</p> <p>Across mountainous land, covered with pinon pine, sagebrush, cheat and bunchgrass, posting the boundary of the Walker River Indian Reservation with steel sign posts.</p>
14.00	Spur, bears N. and summit of line.
29.00	Divide of mountains, bears NW. and SE.
42.850	The center 1/4 sec. cor. of sec. 17.
82.734	Point for the 1/4 sec. cor. of sec. 17 only, on the W. bdy. of sec. 17.
<p style="text-align: center;">SUBDIVISION OF SECTION 21, T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA</p>	
	<p>From the 1/4 sec. cor. of secs. 21 and 28.</p> <p>N. 1°36'10" W., on the N-S center line of sec. 21.</p> <p>Across mountainous land, covered with pinon pine, sagebrush, cheat and bunchgrass, posting the boundary of the Walker River Indian Reservation with steel sign posts.</p>
39.00	Spur and divide of mountain range, slopes NW.
40.020	<p>Point for the center 1/4 sec. cor. of sec. 21, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T12N R28E C 1/4 S21 2012</p> <p>From this cor., an unrecorded squared wood post set by person(s) unknown, 2 ins. square, firmly set, projecting 16 ins. above a mound of stone, 4 ft. base, 1 ft. high, mkd. 1/4 S21 on four sides, bears S. 33°36' W., 1.613 chs. dist., not utilized in the course of this survey.</p> <p>Discontinue posting the boundary of the Walker River Indian Reservation with steel sign posts.</p>
80.582	The 1/4 sec. cor. of secs. 16 and 21.

SUBDIVISION OF SECTION 21,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the 1/4 sec. cor. of secs. 21 and 22.</p> <p>S. 89°47'50" W., on the E-W center line of sec. 21, determined on a bearing parallel with a weighted mean average of the N. boundary and W 1/2 of the S. boundary of sec. 21.</p> <p>Across mountainous land, covered with sagebrush, cheat and bunchgrass.</p>
39.848	The center 1/4 sec. cor. of sec. 21.
41.50	Spur and divide of mountain range, slopes NW.
81.032	Point for the 1/4 sec. cor. of sec. 21 only, on the W. bdy. of sec. 21.
<p style="text-align: center;">SUBDIVISION OF SECTION 27, T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA</p>	
	<p>From the 1/4 sec. cor. of secs. 26 and 27.</p> <p>N. 89°25'10" W., on the E-W center line of sec. 27.</p> <p>Across mountainous land, covered with pinon pine, sagebrush, cheat and bunchgrass, posting the boundary of the Walker River Indian Reservation with steel sign posts.</p>
49.50	Summit of line and divide of mountains, bears NNW. and SSE.
80.424	The 1/4 sec. cor. of secs. 27 and 28.
<p style="text-align: center;">SUBDIVISION OF SECTION 36, T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA</p>	
	<p>The 1/4 sec. cor. of secs. 25 and 36, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above a mound of stone, 4 ft. base, 2 ft. high, with brass cap mkd. as described in the dependent resurvey of a portion of subdivisional lines, T.12 N., R. 28 E., executed under Group No. 497, with a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>S. 0°08'00" W., on the N-S center line of sec. 36.</p>
39.930	<p>Point for the center 1/4 sec. cor. of sec. 36, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to bottom of crevice, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p>

SUBDIVISION OF SECTION 36,
T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T12N R28E C 1/4 S36 2011</p>
79.843	<p>The 1/4 sec. cor. of sec. 36, on the S. bdy. of the Tp.</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 31 and 36, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the dependent resurvey of a portion of the east boundary, T. 12 N., R. 28 E., executed under Group No. 497, with a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>S. 89°56'20" W., on the E-W center line of sec. 36.</p> <p>Across gradual E. slope, covered with, shadescale, cheat and bunchgrass.</p>
14.00	<p>Base of mountains, continue across mountainous land, through sagebrush.</p>
20.150	<p>Point for the C-E 1/16 sec. cor. of sec. 36.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">E 1/16 C——C S36 2011</p>
40.300	<p>The center 1/4 sec. cor. of sec. 36.</p>
63.40	<p>Spur, slopes ENE.</p>
80.404	<p>The 1/4 sec. cor. of secs. 35 and 36.</p> <hr/>
	<p>From the C-E 1/16 sec. cor. of sec. 36.</p> <p>N. 0°11'30" E., on the N-S center line of the NE1/4 of sec. 36.</p> <p>Across mountainous land, covered with sagebrush, cheat and bunchgrass, posting the boundary of the Walker River Indian Reservation with steel sign posts.</p>
39.859	<p>The E 1/16 sec. cor. of secs. 25 and 36.</p> <hr/>

REMONUMENTATION OF CERTAIN CORNERS ON THE EAST BOUNDARY OF
T. 12 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The 1/4 sec. cor. of sec. 36, on the E. bdy. of T. 12 N., R 27 E., monumented with a granite stone, 12x10x15 ins. high, firmly set in a mound of stone, 3 ft. base, 1 ft. high, mkd. 1/4 on W. face.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

T12N
R27E R28E
1/4 |
S36 |

2011

Bury mkd. stone alongside and rebuild mound of stone around stainless steel post, 3 ft. base to top.

From this cor., the cor. of Tps. 11 and 12 N., Rs. 27 and 28 E., hereinbefore described, bears S. 1°36'00" W., 40.697 chs. dist.

The cor. of secs. 25 and 36, on the E. bdy. of T. 12 N., R 27 E., monumented with a trap stone, 8x7x13 ins. high, firmly set in a mound of stone, 3 ft. base, 1 ft. high, mkd. with 1 notch on the S. edge and 6 notches on W. edge.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

T12N
R27E R28E
S25 |
— |
S36 |

2011

Bury mkd. stone alongside and rebuild mound of stone around stainless steel post, 3 ft. base to top.

From this cor., the cor. of Tps. 11 and 12 N., Rs. 27 and 28 E., hereinbefore described, bears S. 0°00'10" W., 81.106 chs. dist.

T. 12 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

General Description

The area encompassed in this survey is high mountains covered with pinon pine, with Section 6 being on the southern ramparts of Black Mountain, a basalt capped mountain peak. The crest of the northern Wassuck Range runs from section 6, through Sections 7, 8, 17, 21 and 27, to the south boundary of the township, rising to an approximate elevation of 8000 feet above sea level, in section 21, descending down the steep and rugged east side of the Wassuck Range to an approximate elevation of 4000 feet above sea level at the river bottom lands along the Walker River in section 1 and the old meanders along the much receded Walker Lake in section 36.

Vegetation consist of primarily shadescale at the lower elevations, transitioning to sagebrush at the higher elevations with pinon pine at the highest elevations descending the N. slopes. Cheat and bunchgrass throughout.

Soil consists of loam deposits from the rocky upper slopes of the northern Wassuck Mountain Range descending to the sandy deposits of the Walker River and receded Walker Lake along the base.

Activity consist of many staked mining claims in the NW portion of this area with evidence of being a very active mining area in the past, although no current active mining was witnessed during the course of this survey. In the NE1/4 of section 1, there is cultivated lands which are restricted to the individual Indian allotments defined by the subdivision of that section. The west half of section 1 and the NE1/4NE1/4 of sec. 2 contain the southernmost portion of the development of the town of Schurz, along the Nevada State Highway No. 95 corridor, containing a store and fuel stop, a motel, and school for the local community.

The area surveyed is accessed in the east from Nevada State Highway No. 95 and Alternate Nevada State Highway No. 95 south of the Town of Schurz, Nevada, approximately 25 miles east of the Town of Yerington, Nevada, and from the west, access is gained from Nevada State Highway No. 208, running south from the town of Yerington, Nevada to Bureau of Land Management Route No. 3020.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Lance A. Barney	Cadastral Surveyor
Joseph J. Johnson	Cadastral Surveyor
Michelle E. Martin	Supervisory Range Technician
Anthony A. Beliew	Surveying Technician
Cathy M. Schmursal	Survey Aid
Anthony Swope	Survey Aid
Mark N. Temen	Survey Aid

CERTIFICATE OF SURVEY

We, Michael O. Harmening, Cadastral Surveyor, and Mark G. Petrosine, Surveying Technician, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 24th day of May, 2011, and the Supplemental Special Instructions bearing date of the 10th day of August, 2012, we have dependently resurveyed a portions of the south, west and north boundaries and portions of the subdivisional lines, surveyed a portion of the south boundary, and a portion of the subdivisional lines, subdivided certain sections of Township 12 North, Range 28 East and remonumented certain corners on the east boundary of Township 12 North, Range 27 East of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

April 10, 2013

(Date)

Michael O. Harmening
(Cadastral Surveyor)April 10, 2013

(Date)

Mark Petrosine
(Surveying Technician)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of the dependent resurvey of portions of the south, west and north boundaries and portions of the subdivisional lines, the survey of a portion of the south boundary, and a portion of the subdivisional lines, the subdivision of certain sections of Township 12 North, Range 28 East and the remonumentation of certain corners on the east boundary of Township 12 North, Range 27 East, Mount Diablo Meridian, Nevada, executed by Michael O. Harmening, Cadastral Surveyor, and Mark G. Petrosine, Surveying Technician, having been critically examined and found correct, are hereby approved.

April 16, 2013

(Date)

David D. [Signature]
(Chief Cadastral Surveyor, Nevada)~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above described surveys in T. 12 N., R. 28 E., Mount Diablo Meridian, Nevada, is a true copy of the original field notes.~~

~~(Date)~~~~(Chief Cadastral Surveyor, Nevada)~~