UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

A PORTION OF THE SOUTH BOUNDARY OF TOWNSHIP 14 NORTH, RANGE 55 EAST,

AND

THE SURVEY OF THE EAST BOUNDARY

AND A PORTION OF THE SUBDIVISIONAL LINES,

TOWNSHIP 13 1/2 NORTH, RANGE 55 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATE OF NEVADA

EXECUTED BY

Brandon G. Courtright, Cadastral Surveyor

Under Special Instructions dated, July 25, 2017

and approved, July 25, 2017

and Amended Special Instructions dated, October 3, 2019

and approved, October 3, 2019

which provided for the surveys included under Group No. 974,

and Assignment Instructions dated, July 25, 2017.

Survey commenced July 28, 2017

Survey completed October 4, 2019

INDEX DIAGRAM

TOWNSHIP 13 1/2 NORTH, RANGE 55 EAST, MOUNT DIABLO MERIDIAN, NEVADA

	31	32		33		34			35	
		. 2	1	2		3			3	
19	20	21	14	22	11	23	8	24	5	
				14		11		8		
30	29	28	13	27	10	26	7	25	5	
				13		10		7		
31	32	33	12	34	9	35	6	36	4	

### TOWNSHIP 13 1/2 NORTH, RANGE 55 EAST, MOUNT DIABLO MERIDIAN, NEVADA

### CHAINS

The following field notes are those providing for the dependent resurvey of a portion of the south boundary of Township 14 North, Range 55 East, and the survey of the east boundary and a portion of the subdivisional lines, Township 13 1/2 North, Range 55 East, Mount Diablo Meridian, Nevada.

The south boundary of Township 14 North, Range 55 East was surveyed by Cadastral Surveyor R.A. Pratt in 1969 under Group No. 461. Nevada Protraction Diagram No. 125, Unit No. 61 & 62, for Townships 14 and 15 North, Ranges 55 and 56 East was approved February 1, 1963. Nevada Protraction Diagram No. 123, Unit No. 61, for Townships 11, 12, 13 and 13 1/2 North, Ranges 55 and 55 1/2 East was approved February 1, 1963.

The survey of a portion of the north boundary of Township 13 North; Range 55 East, was executed concurrently under this same Group.

Before restoring the corners, the lines of the original surveys were retraced and a diligent search made for any evidence of the original corners and other calls of the original field note record.

In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications set forth in the <u>Manual of Surveying Instructions</u>, 2009, and the Special Instructions for Group No. 974, dated July 25, 2017, and the Amended Special Instructions dated October 3, 2019.

Measurements were made with Trimble R8 and R10 Global Positioning System (GPS) receivers using the real-time kinematic method and refer to the true meridian based on geodetic methods. The mean bearings of the lines and horizontal equivalents of ground distances only are entered into the field notes.

The NAD 1983 (2011) (Epoch:2010.0000) geographic position, of the following corners were determined from GPS static observations processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuous Operating Reference Stations (CORS), DP2878 TONO TONO\_BRGN\_NV1999 CORS ARP, DL6904 NVSV SPRING VALLEY CORS ARP, and AI8817 ECHO ECHO\_BRGN\_NV1999 CORS ARP, and carried forward by RTK observations is as follows:

The corner of sections 3, 4, 33 and 34, on the S. bdy. of the Tp., is as follows:

Latitude: 38°59'56.858" N. Longitude: 115°48'01.538" W.

The corner of sections 35 and 36, T. 14 N., R. 55 E., is as follows:

Latitude: 39°02'02.708" N. Longitude: 115°44'28.359" W.

TOWNSHIP 13 1/2 NORTH, RANGE 55 EAST, MOUNT DIABLO MERIDIAN, NEVADA

### CHAINS

The July 28, 2017 mean magnetic declination was determined to be 12°22'E., as obtained from the National Oceanic and Atmospheric Administration's National Centers for Environmental Information declination calculator.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY, T. 14 N., R. 55 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of a Portion of the Survey Executed by Cadastral Surveyor R.A. Pratt in 1969

Beginning at the 1/4 sec. cor. of sec. 32, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above a mound of stone, 2 ft. diam., 1 ft. high, with brass cap mkd. as described in the field notes of the survey of the S. bdy. of T. 14 N., R. 55 E., executed under Group No. 461.

N. 89°59'20" E., on the S. bdy. of sec. 32.

- 25.065 Closing cor. of secs. 21 and 22, T. 13 1/2 N., R. 55 E., hereinafter described.
- 31.05 Dirt road, 30 lks. wide, bears N. 35° E. and S. 35° W.
- The cor. of secs. 32 and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above a mound of stone, 3 ft. diam., 1 ft. high, with brass cap mkd. as described in the field notes of the survey of the S. bdy. of T. 14 N., R. 55 E., executed under Group No. 461.

N. 89°59'50" E., on the S. bdy. of sec. 33.

- 3.45 Trail road, 10 lks. wide, bears N. 5° E. and S. 20° W.
- 25.044 The 1/4 sec. cor. of sec. 22, T. 13 1/2 N., R. 55 E., hereinafter described.
- 32.45 | Wash, 10 lks. wide, drains S. 30° E.
- The 1/4 sec. cor. of sec. 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 16 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of the S. bdy. of T. 14 N., R. 55 E., executed under Group No. 461, with a mound of stone, 1 ft. diam., 1 ft. high, N. of cor.

N. 89°58'50" E., beginning new measurement.

## DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY, T. 14 N., R. 55 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
25.042	The closing cor. of secs. 22 and 23, T. 13 1/2 N., R. 55 E., hereinafter described.
40.022	The cor. of secs. 33 and 34, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of the S. bdy. of T. 14 N., R. 55 E., executed under Group No. 461, with a mound of stone, 1 ft. diam., 1 ft. high, N. of cor.
05.000	N. 89°59'50" E., on the S. bdy. of sec. 34.
25.020	The 1/4 sec. cor. of sec. 23, T. 13 1/2 N., R. 55 E., hereinafter described.
40.023	The 1/4 sec. cor. of sec. 34, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above a mound of stone, 2 ft. diam., 1/2 ft. high, with brass cap mkd. as described in the field notes of the survey of the S. bdy. of T. 14 N., R. 55 E., executed under Group No. 461.
	N. 89°59'10" E., beginning new measurement.
24.997	The closing cor. of secs. 23 and 24, T. 13 1/2 N., R. 55 E., hereinafter described.
40.025	The cor. of secs. 34 and 35, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of the S. bdy. of T. 14 N., R. 55 E., executed under Group No. 461, with a mound of stone, 2 ft. diam., 2 ft. high, N. of cor.
	N. 89°59'20" E., on the S. bdy. of sec. 35.
24.972	The 1/4 sec. cor. of sec. 24, T. 13 1/2 N., R. 55 E., hereinafter described.
40.019	The 1/4 sec. cor. of sec. 35, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of the S. bdy. of T. 14 N., R. 55 E., executed under Group No. 461, with a mound of stone, 2 ft. diam., 1 ft. high, N. of cor.
	N. 89°59'10" E., beginning new measurement.

## DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY, T. 14 N., R. 55 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
19.55	Overgrown trail road, 10 lks. wide, bears S. 25° E. and N. 25° W.
24.953	The closing cor. of Tps. 13 1/2 N., Rs. 55 and 55 1/2 E., hereinafter described.
38.95	Trail road, 10 lks. wide, bears S. 30° E. and N. 30° W.
40.017	The cor. of secs. 35 and 36, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of the S. bdy. of T. 14 N., R. 55 E., executed under Group No. 461, with a mound of stone, 3 ft. diam., 1 ft. high, N. of cor.
	SURVEY OF THE EAST BOUNDARY, T. 13 1/2 N., R. 55 E., MOUNT DIABLO MERIDIAN, NEVADA
	From the cor. of Tps. 13 and 13 1/2 N., Rs. 55 and 55 1/2 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 in. above the ground, with brass cap mkd. as described in the field notes of the survey of the E. bdy. of T. 13 N., R. 55 E., executed concurrently under this same Group.
	NORTH, bet. secs. 31 and 36.
40.000	Point for the 1/4 sec. cor. of secs. 31 and 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T13½N
	1/4
	R55E   R55½E S36   S31
	2017
80.000	Point for the cor. of secs. 25, 30, 31 and 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

## SURVEY OF THE EAST BOUNDARY, T. 13 1/2 N., R. 55 E., MOUNT DIABLO MERIDIAN, NEVADA

	T. 13 1/2 N., R. 33 H., ROOM DIEDE MANDEM, NEVADA
CHAINS	
1	T13½N
	R55E R55½E
	S25 S30
	226 222
	S36 S31
	2017
	NORTH, bet. secs. 25 and 30.
40.000	Doint for the 1/4 man are of room 25 and 20
40.000	Point for the 1/4 sec. cor. of secs. 25 and 30.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
	27 ins. in the ground, over a plastic-encased magnet, with brass
	cap mkd.
	T13½N
	1/4 R55E R55½E
	S25 S30
	525,550
	2017
80.000	Point for the cor. of secs. 19, 24, 25 and 30.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
	27 ins. in the ground, over a plastic-encased magnet, with brass
	cap mkd.
	T13½N
	R55E R55½E
	S24 S19
	S25 S30
	5231530
	2017
	NORTH bot goes 10 and 24
	NORTH, bet. secs. 19 and 24.
32.970	Intersect the S. bdy. of T. 14 N., R. 55 E.
	Point for the closing cor. of T. 13 1/2 N., Rs. 55 and 55 1/2 E.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass
	cap mkd.
	<u>F</u>

## SURVEY OF THE EAST BOUNDARY, T. 13 1/2 N., R. 55 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T14N R55E
	S35
	S24 S19
	CC
	R55E R55½E
	T13½N
	2017
	From this point, the cor. of secs. 35 and 36, T. 14 N., R 55 E., hereinbefore described, bears N. 89°59'10" E., 15.064 chs. dist.
	SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 13 1/2 N., R. 55 E., MOUNT DIABLO MERIDIAN, NEVADA
	From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of a portion of the N. bdy. of T. 13 N., R. 55 E., executed concurrently under this same Group.
	N. 0°00'40" W., bet. secs. 35 and 36.
40.000	Point for the 1/4 sec. cor. of secs. 35 and 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush in the ground, over a plastic-encased magnet, with brass cap mkd.
	T13½N R55E
	1/4
	S35 S36
	2017
80.000	Point for the cor. of secs. 25, 26, 35 and 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	·

CHAINS	
	T13½N R55E
	S26 S25
	S35 S36
	555   555
	2017
	From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., hereinbefore described.
	WEST, bet. secs. 25 and 36.
40.000	Point for the 1/4 sec. cor. of secs. 25 and 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T13½N R55E
	\$25
	1/4 —
	S36
	2017
80.000	The cor. of secs. 25, 26, 35 and 36.
	N. 0°00'40" W., bet. secs. 25 and 26.
40.000	Point for the 1/4 sec. cor. of secs. 25 and 26.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	TI SIAT DEED
	T13½N R55E 1/4
	\$26   \$25
	2017
80.000	Point for the cor. of secs. 23, 24, 25 and 26.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush in the ground, over a plastic-encased magnet, with brass cap mkd.

CHAINS	
	T13½N R55E
	S23   S24
	S26 S25
	525   525
	2017
	From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., hereinbefore described.
	WEST, bet. secs. 24 and 25.
40.000	Point for the 1/4 sec. cor. of secs. 24 and 25.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush in the ground, over a plastic-encased magnet, with brass cap mkd.
	T13½N R55E
	S24
	1/4 ————————————————————————————————————
	525
	2017
80.000	The cor. of secs. 23, 24, 25 and 26.
	N. 0°00'40" W., bet. secs. 23 and 24.
32.954	Intersect the S. bdy. of T. 14 N., R. 55 E.
	Point for the closing cor. of secs. 23 and 24.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush in the ground, over a plastic-encased magnet, with brass cap mkd.
	T14N R55E S34
	<del></del>
	S23   S24
	c'c
	T13½N R55E
	2017

### CHAINS

From this point, the cor. of secs. 34 and 35, T. 14 N., R. 55 E., hereinbefore described, bears N. 89°59'10" E., 15.028 chs. dist.

The point for the 1/4 sec. cor. of sec. 24, on the S. bdy. of T. 14 N., R. 55 E., and at midpoint in departure on the N. bdy. of sec. 24.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

T14N R55E

1/4 S24 T13½N R55E

2017

From this point, the 1/4 sec. cor. of sec. 35, T. 14 N., R. 55 E., hereinbefore described, bears N.  $89^{\circ}59'20"$  E., 15.047 chs. dist.

From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 in. above the ground, with brass cap mkd. as described in the field notes of the survey of a portion of the N. bdy. of T. 13 N., R. 55 E., executed concurrently under this same Group.

N. 0°01'20" W., bet. secs. 34 and 35.

40.000 | Point for the 1/4 sec. cor. of secs. 34 and 35.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

T13½N R55E 1/4 S34|S35

2017

80.000 | Point for the cor. of secs. 26, 27, 34 and 35.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

CHAINS	
CIPATINO	T13½N R55E
	S27 S26
	S34 S35
	2017
·	From the cor. of secs. 25, 26, 35 and 36.
	WEST, bet. secs. 26 and 35.
40.000	Point for the 1/4 sec. cor. of secs. 26 and 35.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T13%N R55E
	\$26
	1/4 ——
	S35
	2017
80.000	The cor. of secs. 26, 27, 34 and 35.
	N. 0°01'20" W., bet. secs. 26 and 27.
40.000	Point for the 1/4 sec. cor. of secs. 26 and 27.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T13½N R55E
	1/4
	S27 S26
	2017
80.000	Point for the cor. of secs. 22, 23, 26 and 27.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<u> </u>

CHAINS	
	T13½N R55E
	S22   S23
	S27   S26
	2017
	2017
	From the cor. of secs. 23, 24, 25 and 26.
	WEST, bet. secs. 23 and 26.
40.000	Point for the 1/4 sec. cor. of secs. 23 and 26.
40.000	Total for the 1/4 see. cor. or sees. 23 and 20.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush in the ground, over a plastic-encased magnet, with brass cap mkd.
	T13½N R55E
	S23
	1/4 —
	S26
	2017
80.000	The cor. of secs. 22, 23, 26 and 27.
00.000	ine cor. or bees. 22, 25, 20 and 27.
	N. 0°01'20" W., bet. secs. 22 and 23.
32.941	Intersect the S. bdy. of T. 14 N., R. 55 E.
32.312	anserbees one by buy, or it is in, in so it
	Point for the closing cor. of secs. 22 and 23.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
	27 ins. in the ground, over a plastic-encased magnet, with brass
	cap mkd.
	T14N R55E
	S33
	<del></del>
	S22 S23
	l cc
	T13½N R55E
	2017
	From this point, the cor. of secs. 33 and 34, T. 14 N., R. 55 E., hereinbefore described, bears N. 89°58'50" E.,
	14.980 chs. dist.
	TI. JOG CIID. GIDG.
I	

### CHAINS

The point for the 1/4 sec. cor. of sec. 23, on the S. bdy. of T. 14 N., R. 55 E., and at midpoint in departure on the N. bdy. of sec. 23.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

T14N R55E

1/4 S23 T13½N R55E

2017

From this point, the 1/4 sec. cor. of sec. 34, T. 14 N., R. 55 E., hereinbefore described, bears N. 89°59'50" E., 15.003 chs. dist.

From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of a portion of the N. bdy. of T. 13 N., R. 55 E., executed concurrently under this same Group.

N. 0°02'10" W., bet. secs. 33 and 34.

40.000

Point for the 1/4 sec. cor. of secs. 33 and 34.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

T13½N R55E 1/4 S33|S34

2017

80.000

Point for the cor. of secs. 27, 28, 33 and 34.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

	The state of the s
CHAINS	
	T13½N R55E
	S28 S27
	S33 S34
	2017
	From the cor. of secs. 26, 27, 34 and 35.
	WEST, bet. secs. 27 and 34.
40.000	Point for the 1/4 sec. cor. of secs. 27 and 34.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.
	T13½N R55E
	\$27
	1/4 —
	S34
	2017
80.000	The ger of gogg 27 20 22 and 24
80.000	The cor. of secs. 27, 28, 33 and 34.
	N. 0°02'10" W., bet. secs. 27 and 28.
40.000	Point for the 1/4 sec. cor. of secs. 27 and 28.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T13½N R55E
	1/4
	S28   S27
	2017
80.000	Point for the cor. of secs. 21, 22, 27 and 28.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

	1. 13 1/2 N., R. 35 E., MOUNT DIABLO MERIDIAN, NEVADA
CHAINS	
	T13½N R55E
	S21 S22
	S28 S27
	520   527
	2017
	From the cor. of secs. 22, 23, 26 and 27.
	WEST, bet. secs. 22 and 27.
40.000	Point for the 1/4 sec. cor. of secs. 22 and 27.
. •	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T13½N R55E
	1/4 ——
	\$27
	2017
80.000	The cor. of secs. 21, 22, 27 and 28.
	N. 0°02'10" W., bet. secs. 21 and 22.
25.50	Dirt road, 30 lks. wide, bears N. 45° E. and S. 45° W.
32.928	Intersect the S. bdy. of T. 14 N., R. 55 E.
	Point for the closing cor. of secs. 21 and 22.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

CHAINS

T14N R55E

S32

S21 S22

CC

T13½N R55E

2017

From this point, the cor. of secs. 32 and 33, T. 14 N., R. 55 E., hereinbefore described, bears N. 89°59'20" E., 14.956 chs. dist.

The point for the 1/4 sec. cor. of sec. 22, on the S. bdy. of T. 14 N., R. 55 E., and at midpoint in departure on the N. bdy. of sec. 22.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

T14N R55E

1/4 S22 T13½N R55E

2017

From this point, the 1/4 sec. cor. of sec. 33, T. 14 N., R. 55 E., hereinbefore described, bears N.  $89^{\circ}59'50"$  E., 14.958 chs. dist.

### GENERAL DESCRIPTION

The lands included in the survey are located in Nye County, Nevada, on the westerly edge of the community of Duckwater, Nevada. Access is gained by way of Nevada State Highway No. 379 and various dirt roads. The average elevation of the area is 5950 feet.

The area consists of a gentle east facing slope to the bottom of Duckwater Valley. Vegetation includes juniper, sage brush, various grasses and sparse cacti of varying species.

### UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

### FIELD ASSISTANTS

Matthew E. Campos Sup. Cadastral Surveyor Brandon K. Grace

Cadastral Surveyor

Justin V. Haddon Cadastral Surveyor

Griffin B. Dekker Student Trainee

Kenneth W. Tynan Student Trainee

### CERTIFICATE OF SURVEY

I, Brandon G. Courtright, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 25th day of July 2017, and amended special instructions bearing date of the 3rd day of October, 2019, I have dependently resurveyed a portion of the south boundary of Township 14 North, Range 55 East, and surveyed the east boundary and a portion of the subdivisional lines of Township 13 1/2 North, Range 55 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

DEC 0 3 2019

(Date)

ultud o Hummy /For Brandon G. Courtright

(Cadastral Surveyor)

#### CERTIFICATE OF APPROVAL

### BUREAU OF LAND MANAGEMENT Reno, Nevada

The foregoing field notes of the dependent resurvey of a portion of the south boundary of Township 14 North, Range 55 East, and the survey of the east boundary and a portion of the subdivisional lines of Township 13 1/2 North, Range 55 East, Mount Diablo Meridian, Nevada, executed by Brandon G. Courtright, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

DEC 0 3 2019

(Date)

(Chief Cadastral Surveyor for Nevada)

### CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above described surveys in Township 13 1/2 North, Range 55 East, Mount Diablo Meridian, Nevada, is a true copy of the original field notes.

(Date)

(Chief Cadastral Surveyor for Nevada)