

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF

A PORTION OF THE SOUTH BOUNDARY,  
A PORTION OF THE SUBDIVISIONAL LINES,  
AND PORTIONS OF MINERAL SURVEY NOS. 4892 AND 4893,  
AND A METES-AND-BOUNDS SURVEY IN SECTIONS 35 AND 36  
TOWNSHIP 13 NORTH, RANGE 26 EAST,  
OF THE MOUNT DIABLO MERIDIAN,  
IN THE STATE OF NEVADA

EXECUTED BY

Brandon K. Grace, Cadastral Surveyor

Under Special Instructions dated February 24, 2015,  
and approved February 24, 2015,  
and Supplemental Special Instructions dated February 27, 2015,  
and approved February 27, 2015,  
and Supplemental Special Instructions dated March 24, 2015,  
and approved March 24, 2015,  
which provided for the surveys included under Group No. 941,  
and Assignment Instructions dated February 27, 2015.

Survey commenced March 1, 2015

Survey completed March 27, 2015

INDEX DIAGRAM

TOWNSHIP 13 NORTH, RANGE 26 EAST, MOUNT DIABLO MERIDIAN, NEVADA

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	14 33	13 34	11 35	9 36
		7	5	3	2

M.S. No. 4892.....pp. 16-17.  
M.S. No. 4893.....pp. 17-19.  
Metes-and-Bounds Survey in Secs. 35 and 36.....pp. 19-23.

## TOWNSHIP 13 NORTH, RANGE 26 EAST, MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

The following field notes are those of the dependent resurvey of a portion of the south boundary, a portion of the subdivisional lines, and portions of Mineral Survey Nos. 4892 and 4893 and a metes-and-bounds survey in section 35 and 36, Township 13 North, Range 26 East, Mount Diablo Meridian, Nevada.

The exterior township boundaries were surveyed by U.S. Deputy Surveyors R.A. Chase and A. Lash, Jr. in 1868 under Contract No. 8. A portion of the subdivisional lines were surveyed by U.S. Deputy Surveyor R.A. Chase in 1869 under Contract No. 24. A portion of the subdivisional lines were surveyed by U.S. Transitman H.W. Reppert in 1913-1915 under Group No. 22. A portion of the north boundary and a portion of the subdivisional lines were dependently resurveyed by U.S. Transitman H.W. Reppert in 1913-1915 under Group No. 22. The east boundary, a portion of the south boundary and a portion of the subdivisional lines were retraced by U.S. Transitman H.W. Reppert in 1913-1915 under Group No. 22. A portion of the east boundary was resurveyed concurrently under this same Group. Mineral Survey Nos. 4892 and 4893 were surveyed by U.S. Mineral Surveyor Bill Harris in 1969.

Refer to the field notes of T. 13 N., R. 27 E., surveyed concurrently under this same Group, for a portion of the E. bdy. of T. 13 N., R. 26 E.

Before restoring the corners, the lines of the original surveys were retraced and a diligent search made for any evidence of the original corners and other calls of the field note records.

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions (2009), the Special Instructions for Group No. 941, dated February 24, 2015, Supplemental Special Instructions dated February 27, 2015 and Supplemental Special Instructions dated March 24, 2015.

Measurements were made with Trimble R8 Global Positioning System (GPS) receivers using the real-time kinematic method. The direction of each line is with reference to the true meridian. All bearings are mean bearings and the distances are reported as horizontal measurement at a mean ground elevation of 4,850 feet above sea level.

The NAD 83 (2011) (Epoch 2010.0000) geographic positions of the corners below were determined from GPS static observations processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuous Operating Reference Stations (CORS) DOT1 CARSON CITY COOP CORS ARP, UPSA UPSAL HOGBACK CORS ARP, P143 INDIANCRK\_CN2007 CORS ARP, and carried forward by RTK observations.

## TOWNSHIP 13 NORTH, RANGE 26 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>The corner of Tps. 12 and 13 N., Rs. 26 and 27 E., is as follows:</p> <p style="padding-left: 40px;">Latitude 38°56'22.992" N.      Longitude 119°00'53.610" W.</p> <p>The corner of sections 28, 29, 32 and 33 is as follows:</p> <p style="padding-left: 40px;">Latitude 38°57'14.952" N.      Longitude 119°05'20.666" W.</p> <p>The March 23, 2015 mean magnetic declination was determined to be 13°24' E., as obtained from the National Oceanic and Atmospheric Administration's National Geophysical Data Center declination calculator.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY, T. 13 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyors R.A. Chase and A. Lash, Jr. in 1868 and a Portion of the Retracement Executed by U.S. Transitman H.W. Reppert in 1913.</p> <hr/> <p>Beginning at the cor. of Tps. 12 and 13 N., Rs. 26 and 27 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set in a mound of stone, 2 1/2 ft. base., 1/2 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of the N. bdy., T. 12 N, R. 27 E., executed concurrently under this same Group.</p> <p>S. 89°33'50" W., bet. secs. 1 and 36.</p> <p>Over rocky hills, covered with shadscale.</p> <p>10.90      Trail road, 15 lks. wide bears SE. and NW.</p> <p>14.90      Trail Road, 15 lks. wide bears N. and S.</p> <p>17.40      Barbed wire fence, 4 strands, bears SSE. and NNW.</p> <p>35.20      Ridge, bears SE. and NW.</p> <p>39.317      The 1/4 sec. cor. of secs. 1 and 36, monumented with a granite stone, 14x8x6 ins., loosely set in a mound of stone, 3 ft. diam., 1 ft. high, mkd. 1/4 on N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 6 ft. base, to top, with brass cap mkd.</p>
--------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 13 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T13N R26E S36 1/4 — S 1 T12N  2015</p> <p>Bury mkd. stone alongside the stainless steel post.</p> <hr/> <p>S. 89°46'40" W., beginning new measurement.</p>
8.70	Trail road, 15 lks. wide, bears S. 15° E. and N. 15° W., in the bottom of a ravine, drains S.
13.45	Ridge, bears SSE. and NNW.
27.40	Small spur, (Record: Ridge) slopes SW.
37.30	Power transmission line, bears S. 17° E. and N. 17° W.
38.892	The witness point at the intersection with the westerly right-of-way line of the Sylmar-Oregon H.V.D.C. Transmission Line, hereinafter described.
39.701	<p>The cor. of secs. 1, 2, 35 and 36, perpetuated by person(s) unknown, monumented with a rebar, 1/2 in. diam., 12 ins. long, firmly set flush with a mound of stone, 4 ft. diam., 1 ft. high, with a trap stone, 15x12x5 ins., firmly set in the base of a mound of stone, mkd. with 5 notches on an edge and 1 notch on the opposite edge. This rebar is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T13N R26E S35   S36 —   — S 2   S 1 T12N  2015</p> <p>Insert rebar inside and bury mkd. stone alongside the stainless steel post.</p> <hr/> <p>S. 89°46'10" W., bet. secs. 2 and 35.</p> <p>Over a gentle westerly slope, covered with shadscale.</p>
4.20	Trail road, 15 lks. wide, bears NNE. and SSW.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 13 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
14.70	Closed extension of E. Pursel Lane, dirt road, 15 lks. wide, bears ENE. and WSW.
21.60	Ravine, drains WNW.
25.524	Intersect line 3-4, Mineral Survey No. 4893, Lyon No. 136 lode, identical with line 2-3, Mineral Survey No. 4893, Lyon No. 137 lode, at a point from which Cor. No. 4, Mineral Survey No. 4893, Lyon No. 136 lode, identical with Cor. No. 2, Mineral Survey No. 4893, Lyon No. 137 lode, Cor. No. 4, Mineral Survey No. 4893, Lyon No. 8 lode and Cor. No. 2, Mineral Survey No. 4893, Lyon No. 7 lode, hereinafter described, bears S. 0°04'40" E., 0.147 chs. dist.
25.60	Wire fence, bears N. and S.; enter active Pumpkin Hollow mining area.
40.153	Point for the 1/4 sec. cor. of secs. 2 and 35, at proportionate distance; there is no remaining evidence of the position of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.
	<p>T13N R26E S35 1/4 — S 2 T12N  2015</p>
	Cor. is located at the N. edge of E. Pursel Lane.
57.05	E. Pursel Lane, an improved dirt road, 30 lks. wide, bears E. and W.
68.60	S. edge of E. Pursel Lane, an improved dirt road, 30 lks. wide, bears E. and W.
70.40	Wire fence, bears N. and S.; leave active Pumpkin Hollow mining area.
70.427	Intersect line 2-3, Mineral Survey No. 4893, Lyon No. 135 lode, at a point from which Cor. No. 2, Mineral Survey No. 4893, Lyon No. 135 lode, identical with Cor. No. 4, Mineral Survey No. 4893, Lyon No. 6 lode, hereinafter described, bears S. 0°04'20" E., 0.033 chs. dist.
80.306	The cor. of secs. 2, 3, 34 and 35, reestablished by Richard B. Byrem, Nevada Professional Land Surveyor No. 18297, in 2014, monumented with a rebar, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with plastic cap mkd. R. BYREM PLS 18297, as recorded in Lyon County, Nevada, Corner Record, Document No. 535041. This is accepted as a careful and faithful reestablishment of the position of the original corner.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 13 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS											
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1" style="margin: auto;"> <tr><td colspan="2">T13N R26E</td></tr> <tr><td>S34</td><td>S35</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 3</td><td>S 2</td></tr> <tr><td colspan="2">T12N</td></tr> </table> <p>2015</p> </div> <p>Insert rebar inside stainless steel post.</p> <p>From this cor., a rebar, no record found, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with plastic cap mkd. R. BYREM PLS 18297, bears N. 0°15'50" W., 0.908 chs. dist., not utilized during the course of this survey.</p> <hr/> <p>S. 89°45'20" W., bet. secs. 3 and 34.</p> <p>Over a gentle westerly slope.</p>	T13N R26E		S34	S35	<hr/>		S 3	S 2	T12N	
T13N R26E											
S34	S35										
<hr/>											
S 3	S 2										
T12N											
20.078	<p>A rebar, no record found, 5/8 in. diam., firmly set flush with the ground, with plastic cap mkd. R. BYREM PLS 18297, not utilized during the course of this survey.</p>										
40.156	<p>The 1/4 sec. cor. of secs. 3 and 34, determined by person(s) unknown, monumented with a galvanized post, 2 1/2 ins. diam., projecting 6 ft. above the ground, with welded threading on top of post, firmly set over a rusted post, 2 ins. diam., firmly set in concrete. This post correlates well with other existing corners and is accepted as a careful and faithful determination of the position of the original corner.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 27 ins. in the ground for a reference monument, bears N. 42°41'20" E., 157.0 lks. dist., with brass cap mkd. RM 1/4 S34 103.6 FT. TO COR 2015 and an arrow pointing to the corner.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground for a reference monument, bears N. 55°12'20" W., 232.4 lks. dist., with brass cap mkd. RM 1/4 S34 153.4 FT. TO COR 2015 and an arrow pointing to the corner.</p> <p>From this cor., Cor. No. 1, Mineral Survey No. 4892, Lyon No. 4 lode, identical with Cor. No. 1, Mineral Survey No. 4892, Lyon No. 15 lode, monumented with an iron pipe, 1 in. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. L4-1 L15-1 4892 as described in the field notes of Mineral Survey No. 4892, bears S. 71°57'50" E., 29.012 chs. dist.</p>										

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 13 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p>	<p>From this same cor., Cor. No. 1, Mineral Survey No. 4892, Lyon No. 22 lode, monumented with an iron pipe, 1 in. diam., firmly set flush in a collar of stone, with brass cap mkd. L22-1 4892 as described in the field notes of Mineral Survey No. 4892, bears S. 45°46'50" E., 38.538 chs. dist.</p> <p>From this same cor., a rebar, no record found, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with plastic cap mkd. R. BYREM PLS 18297, bears N. 0°13'20" W., 0.911 chs. dist.</p> <hr/> <p>S. 89°44'50" W., beginning new measurement.</p> <p>20.028 A rebar, no record found, 5/8 in. diam., firmly set, flush with the ground, with plastic cap mkd. R. BYREM PLS 18297, not utilized during the course of this survey.</p> <p>20.90 Ravine, drains NW.</p> <p>40.052 The cor. of secs. 3, 4, 33 and 34, identical with Cor. No 3, Mineral Survey No. 4892, Lyon No 1 lode and Cor. No. 3, Mineral Survey No. 4892, Lyon No 2 lode, perpetuated by person(s) unknown, monumented with a galvanized post, 2 1/2 ins. diam., projecting 6 ft. above the ground, firmly set over a rusted post, 2 ins. diam., firmly set in concrete, with a wood post, 2x2 ins., 4 ft. long, with attached aluminum tag mkd. 1 2 SE COR BZC1 SW COR BZC-2 wired to the galvanized post. A stone, no mks. visible, 15x9x8 ins., was found buried alongside concrete base. An impression in the concrete appears to be that of the stone's triangular base where the stone was once set. This matches the description by George H. Denson, Nevada Professional Land Surveyor No. 4045, in 1994, as recorded in Lyon County, Nevada, Record Of Survey For Boundary Line Adjustment, Document No. 178237. This post correlates well with other existing corners and has been adopted by various other professional land surveyors and is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground for a reference monument, bears N. 40°46'20" E., 138.0 lks. dist., with brass cap mkd. RM T13N R26E S34 91.1 FT. TO COR 2015 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground for a reference monument, bears N. 39°20'20" W., 144.5 lks. dist., with brass cap mkd. RM T13N R26E S33 95.4 FT. TO COR 2015 and an arrow pointing to the corner.</p> <p>From this cor., Cor. No. 4, Mineral Survey No. 4892, Lyon No. 2 lode, identical with Cor. No 2, Mineral Survey No. 4892, Lyon No. 3 lode, monumented with an iron pipe, 1 in. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. L2-4 L3-2 4892 as described in the field notes of Mineral Survey No. 4892, bears N. 89°53'40" E., 22.507 chs. dist.</p>
---------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 13 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From this same cor., Cor. No. 4, Mineral Survey No. 4892, Lyon No. 1 lode, identical with Cor. No 2, Mineral Survey No. 4892, Lyon No. 2 lode, and Cor. No. 4, Mineral Survey No. 4879, Lyon No. 17 lode, and Cor. No. 2, Mineral Survey No. 4892, Lyon No. 18 lode, monumented with an iron pipe, 1 in. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. 4892 L1-4 L2-2 L18-2 4892 L17-4 4879 as described in the field notes of Mineral Survey No. 4892, bears S. 0°02'30" E., 8.906 chs. dist.</p> <p>From this same cor., Cor. No. 1, Mineral Survey No. 4892, Lyon No. 1 lode, identical with Cor. No. 1, Mineral Survey No. 4892, Lyon No. 18 lode, hereinafter described, bears S. 68°14'30" W., 24.155 chs. dist.</p> <p>From this same cor., a rebar, no record found, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with plastic cap mkd. R. BYREM PLS 18297, bears N. 0°14'21" W., 0.911 chs. dist., not utilized during the course of this survey.</p> <hr/> <p>S. 89°44'20" W., bet. secs. 4 and 33.</p> <p>Over a gentle westerly slope, along the southerly edge of E. Pursel Lane.</p> <p>9.30 E. Pursel Lane, an improved road, 28 lks. wide, bears E. and W.</p> <p>14.20 Ravine, at intersection with E. Pursel Lane, course NW.</p> <p>22.449 Intersect line 1-2, Mineral Survey No. 4892, Lyon No. 1 lode, at a point from which the true point for Cor. No. 2, Mineral Survey No. 4892, Lyon No. 1 lode, hereinafter described, bears N. 0°06'00" W., 0.061 chs. dist.</p> <p>40.121 The 1/4 sec. cor. of secs. 4 and 33, reestablished by Richard B. Byrem, Nevada Professional Land Surveyor No. 18297, in 2014, monumented with a rebar, 5/8 in. diam., 10 ins. long, firmly set 4 ins. below the surface of E. Pursel Lane, with aluminum cap faintly mkd. 4 33 18297, as recorded in Lyon County, Nevada, Corner Record, Document No. 535040. This is accepted as a careful and faithful reestablishment of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. below the surface of E. Pursel Lane, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T13N R26E S33 1/4 — S 4 T12N  2015</p> <p>Insert rebar inside stainless steel post.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 13 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>from which</p> <p>A pk nail, set in the side of a power pole for a reference monument, bears S. 73°29'10" W., 84.7 lks. dist.</p> <p>From this cor., a rebar, no record found, 1/2 in. diam., firmly set, projecting 4 ins. above the ground, bears S. 40°53'10" W., 0.484 chs. dist., not utilized during the course of this survey.</p> <p>From this same cor., a rebar, no record found, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with plastic cap mkd. R. BYREM PLS 18297, bears N. 0°05'50" W., 0.910 chs. dist., not utilized during the course of this survey.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°43'50" W., beginning new measurement.</p>								
40.118	<p>The cor. of secs. 4, 5, 32 and 33, reestablished by Richard B. Byrem, Nevada Professional Land Surveyor No. 18297, in 2014, monumented with a rebar, 5/8 in. diam., 12 ins. long, firmly set 4 ins. below the surface of E. Pursel Lane, with aluminum cap faintly mkd. 4 5 32 33 18297, as recorded in Lyon County, Nevada, Corner Record, Document No. 535039. This is accepted as a careful and faithful reestablishment of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 9 ins. below the surface of E. Pursell Lane, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T13N</td> <td style="padding: 0 5px;">R26E</td> </tr> <tr> <td style="padding: 0 5px;">S32</td> <td style="padding: 0 5px;">S33</td> </tr> <tr> <td style="border-top: 1px solid black; padding: 0 5px;">S 5</td> <td style="border-top: 1px solid black; padding: 0 5px;">S 4</td> </tr> <tr> <td style="padding: 0 5px;">T12N</td> <td></td> </tr> </table> <p style="margin-top: 5px;">2015</p> </div> <p>Insert rebar inside stainless steel post.</p> <p>from which</p> <p>A pk nail, set in the side of a power pole for a reference monument, bears N. 62°06'00" W., 98.9 lks. dist.</p> <p>From this cor., a galvanized post, 2 1/2 ins. diam., projecting 6 ft. above the ground, firmly set over a rusted post, 2 ins. diam., firmly set in concrete, bears S. 88°49'30" W., 39.621 chs. dist., not utilized during the course of this survey.</p>	T13N	R26E	S32	S33	S 5	S 4	T12N	
T13N	R26E								
S32	S33								
S 5	S 4								
T12N									

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 13 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From this same cor., the cor. of secs. 5, 6, 31 and 32, monumented with a Nevada Department of Transportation monument, an aluminum cap in a monument well, set in asphalt in E. Pursel Lane, with aluminum cap mkd. 5 6 31 32, as shown on Corner Record, Document No. 187749, recorded by Donald B. Goodman, Nevada Professional Land Surveyor, No. 6222, in 1995, in Lyon County, Nevada, bears S. 89°43'30" W., 80.239 chs. dist. This position has been adopted and recorded by various professional land surveyors and is accepted as the best available evidence of the position of the original corner.</p> <p>From this same cor., a rebar, no record found, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with plastic cap mkd. R. BYREM PLS 18297, bears N. 0°15'20" W., 0.910 chs. dist., not utilized during the course of this survey.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 13 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor R.A. Chase in 1869 and a Portion of the Dependent Resurvey and Retracement Executed by U.S. Transitman H.W. Reppert in 1913-1915.</p> <hr/> <p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°13'40" W., bet. secs. 35 and 36.</p> <p>Over uneven ground and westerly draining draws.</p> <p>1.20 Trail road, 15 lks. wide, bears E. and W.</p> <p>2.748 The witness point at the intersection of the westerly right-of-way line of the Sylmar-Oregon H.V.D.C. Transmission Line, hereinafter described.</p> <p>8.10 The Sylmar-Oregon H.V.D.C. Transmission Line, bears S. 17° E. and N. 17° W.</p> <p>8.90 Trail road, 20 lks. wide, curves N. and bears SW.</p> <p>10.10 Trail road, 20 lks. wide, curves S. and bears NW.</p> <p>40.391 The 1/4 sec. cor. of secs. 35 and 36, monumented with a trap stone, 14x8x4 ins., loosely set in a mound of stone, 3 ft. diam., 1 ft. high, mkd. 1/4 on W. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
--------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T13N R26E 1/4 S35 S36  2015
	Bury the mkd. stone alongside the stainless steel post.
	_____
	N. 0°06'10" W., beginning new measurement.
4.192	The witness point at the intersection with a metes-and-bounds survey, hereinafter described.
7.50	Dirt road, 30 lks. wide, bears E. and W.
16.320	The witness point at the intersection with a metes-and-bounds survey, hereinafter described.
40.229	The cor. of secs. 25, 26, 35 and 36, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above a mound of stone, 3 ft. diam., 1 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines, T. 13 N., R. 26 E., executed under Group No. 22.
	_____
	From the cor. of secs. 25 and 36, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set in a mound of stone, 3 ft. diam., 1/2 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of the E. bdy., T. 13 N., R. 26 E., executed concurrently under this same Group.
	N. 89°41'20" W., bet. secs. 25 and 36.
	Over rocky hills, covered with shadscale.
34.60	Barbed wire fence, 4 strands, bears SSE. and NNW.
35.60	Trail road, 15 lks. wide, bears S. 30° E. and N. 30° W.
39.741	The 1/4 sec. cor. of secs. 25 and 36, monumented with an iron post, 1 in. diam., firmly set, projecting 3 ins. above a mound of stone, 4 ft. diam., 3 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines, T. 13 N., R. 26 E., executed under Group No. 22, with a witness mound of stone, 2 ft. diam., 2 ft. high, N. of cor. Remark the brass cap to read as follows:
	T13N R26E S25 1/4 _____ S36  2015 1913
	_____

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 89°58'30" W., beginning new measurement.
39.923	The cor. of secs. 25, 26, 35 and 36.
	<hr/> From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., hereinbefore described. N. 0°04'30" W., bet. secs. 34 and 35. Over gentle westerly sloping ground covered with shadscale.
0.60	E. Pursel Lane, an improved dirt road, 26 lks. wide, bears E. and W.
41.197	The 1/4 sec. cor. of secs. 34 and 35, monumented with a trap stone, 8x6x4 ins. (Record: 16x10x4 ins.), firmly set, projecting 4 ins. above an embedded mound of stone, 3 ft. diam., mkd. 1/4 on W. face.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.
	T13N R26E 1/4 S34 S35  2015
	Bury the mkd. stone alongside the stainless steel post.
	<hr/> N. 0°04'10" E., beginning new measurement.
5.75	Dirt road, 38 lks. wide, bears E. and W.
23.10	Trail road, 15 lks. wide, bears ENE. and WSW.
29.853	Point for the N-N 1/64 sec. cor. of secs. 34 and 35.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.
	N-N 1/64 S34 S35  2015
35.40	Trail road, 15 lks. wide, bears NNE. and SSW.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.804	<p>The cor. of secs. 26, 27, 34 and 35, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines, T. 13 N., R. 26 E., executed under Group No. 22.</p> <hr/>
	<p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>N. 89°51'30" W., bet. secs. 26 and 35.</p> <p>Over uneven ground covered with shadscale.</p>
19.00	<p>The Sylmar-Oregon H.V.D.C. Transmission Line, bears S. 15° E. and N. 15° W.</p>
21.70	<p>Trail road, 15 lks. wide, bears NNE. and SSW.</p>
29.389	<p>The witness point at the intersection with a metes-and-bounds survey, hereinafter described.</p>
31.50	<p>Trail road, 15 lks. wide, bears NNE. and SSW.</p>
39.948	<p>The 1/4 sec. cor. of secs. 26 and 35, monumented with a granite stone, 14x10x8 ins. (Record: 12x9x8 ins.), loosely set, projecting 9 ins. above an embedded mound of stone, 2 ft. diam., mkd. 1/4 on S. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T13N R26E S26 1/4 — S35</p> <p style="text-align: center;">2015</p> <p>Bury the mkd. stone alongside the stainless steel post.</p> <hr/> <p>S. 89°56'20" W., beginning new measurement.</p>
25.070	<p>Point for the E-W-W 1/256 sec. cor. of secs. 26 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	S26 E-W-W 1/256 S35
	2015
39.10	Trail road, 15 lks. wide, bears NNE. and SSW.
40.112	The cor. of secs. 26, 27, 34 and 35.
	From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., hereinbefore described.
	N. 0°05'50" W., bet. secs. 33 and 34.
	Over gentle westerly sloping ground covered with shadscale.
0.20	E. Pursel Lane, an improved dirt road, 38 lks. wide, bears E. and W.
18.00	Trail road, 15 lks. wide, bears N. and S.
19.10	Trail road, 15 lks. wide, bears N. and S.
35.40	Dirt road, 22 lks. wide, bears NE. and SW.
40.536	Point for the 1/4 sec. cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the position of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T13N R26E 1/4 S33   S34
	2015
54.95	Trail road, 15 lks. wide, bears SE. and NW.
76.005	Point for the N-N-N 1/256 sec. cor. of secs. 33 and 34.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush in the ground, over a plastic-encased magnet, with brass cap mkd.
	N-N-N 1/256 S33   S34
	2015

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
81.072	<p>The cor. of secs. 27, 28, 33 and 34, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines, T. 13 N., R. 26 E., executed under Group No. 22.</p> <hr/>
	<p>From the cor. of secs. 26, 27, 34 and 35.</p>
	<p>N. 89°32'10" W., bet. secs. 27 and 34.</p>
	<p>Over sandy ground covered with scattered shadscale.</p>
13.70	<p>Trail road, 15 lks. wide, bears NNE. and SSW.</p>
24.50	<p>Trail road, 15 lks. wide, bears NNE. and SSW.</p>
37.00	<p>Trail road, 15 lks. wide, bears NE. and SW.</p>
40.193	<p>The 1/4 sec. cor. of secs. 27 and 34, monumented with a granite stone, 8x5x3 ins., lying loose in a scattered mound of stone, mkd. 1/4 on a face.</p>
	<p>At the corner point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T13N R26E S27 1/4 — S34</p>
	<p style="text-align: center;">2015</p>
	<p>Bury the mkd. stone alongside the stainless steel post and raise a mound of stone N. of cor.</p> <hr/>
	<p>S. 89°07'40" W., beginning new measurement.</p>
21.80	<p>Trail road, 20 lks. wide, bears NNE. and SSW.</p>
40.133	<p>The cor. of secs. 27, 28, 33 and 34.</p> <hr/>
	<p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., hereinbefore described.</p>
	<p>N. 0°00'50" W., bet. secs. 32 and 33.</p>
	<p>Over sandy ground covered with scattered shadscale.</p>
0.05	<p>E. Pursel Lane, an improved dirt road, 35 lks. wide, bears E. and W.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
1.50	Dirt road, 27 lks. wide, bears ENE. and WSW.
21.60	Trail road, 15 lks. wide, ESE. and WNW.
40.582	Point for the 1/4 sec. cor. of secs. 32 and 33, at proportionate distance; there is no remaining evidence of the position of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T13N R26E 1/4 S32 S33  2015
69.60	Trail road, 15 lks. wide, bears NE. and SW.
72.20	Trail road, 15 lks. wide, bears SE. and NW.
81.164	The cor. of secs. 28, 29, 32 and 33, monumented with an iron post, 2 ins. diam., firmly set, projecting 11 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines, T. 13 N., R. 26 E., executed under Group No. 22.
	<hr/> From the cor. of secs. 27, 28, 33 and 34. S. 89°45'00" W., bet. secs. 28 and 33. Over sandy ground covered with scattered shadscale.
0.20	Trail road, 15 lks. wide, bears N. and S.
15.80	Trail road, 15 lks. wide, bears SE. and NW.
40.005	The 1/4 sec. cor. of secs. 28 and 33, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines, T. 13 N., R. 26 E., executed under Group No. 22. Remark the brass cap to read as follows:
	T13N R26E S28 1/4 <hr style="width: 10%; margin: 0 auto;"/> S33  2015 1913 <hr style="width: 30%; margin: 0 auto;"/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	S. 89°51'40" W., beginning new measurement.
10.025	Point for the E-W 1/64 sec. cor. of secs. 28 and 33.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.  S28 E-W 1/64 S33  2015
31.90	Trail road, 15 lks. wide, bears NE. and SW.
40.100	The cor. of secs. 28, 29, 32 and 33.
<hr/> <p>DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4892, T. 13 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of a Portion of the Survey Executed by U.S. Mineral Surveyor Bill Harris in 1969</p> <hr/> <p><u>Lyon No. 1 lode</u></p> <p>From Cor. No. 1, Mineral Survey No. 4892, Lyon No. 1 lode, identical with Cor. No. 1, Mineral Survey No. 4892, Lyon No. 18 lode, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of Mineral Survey No. 4892.</p> <p>N. 0°06'00" W., on line 1-2, Mineral Survey No. 4892, Lyon No. 1 lode.</p>	
8.610	Witness corner for Cor. No. 2, Mineral Survey No. 4892, Lyon No. 1 lode, monumented with an iron post, 1 in. diam., firmly set, bent towards the SE., with brass cap mkd. as described in the field notes of Mineral Survey No. 4892. The bend in the iron post is accepted as the best available evidence of the position of the original corner.
0.242	N. 0°06'00" W., beginning new measurement.  Intersect the line bet. secs. 4 and 33, on the S. bdy. of the TP., at a point from which the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., hereinbefore described, bears N. 89°44'20" E., 22.449 chs. dist.

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4892,  
T. 13 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
0.303	<p>Point for the true point for Cor. No. 2, Mineral Survey No. 4892, Lyon No. 1 lode, determined by projected bearing and record distance; point falls in E. Pursel Lane, where it is impractical to establish a permanent monument.</p> <hr/> <p>N. 89°53'50" E., on line 2-3, Mineral Survey No. 4892, Lyon No. 1 lode.</p>
22.449	<p>Cor. No. 3, Mineral Survey No. 4892, Lyon No. 1 lode, identical with Cor. No. 3, Mineral Survey No. 4892, Lyon No. 2 lode, and the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4893, T. 13 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of a Portion of the Survey Executed by U.S. Mineral Surveyor, Bill Harris, in 1969</p> <hr/> <p style="text-align: center;"><u>Lyon No. 135 lode</u></p> <p>From Cor. No. 2, Mineral Survey No. 4893, Lyon No. 135 lode, identical with Cor. No. 4, Mineral Survey No. 4893, Lyon No. 6 lode, monumented with an iron post, 1 in. diam., firmly set, projecting 5 ins. above a collar of stone, with brass cap mkd. as described in the field notes of Mineral Survey No. 4893.</p> <p>N. 0°04'20" W., on line 2-3, Mineral Survey No. 4893, Lyon No. 135 lode.</p>
0.033	<p>Intersect the line bet. secs. 2 and 35, on the S. bdy. of the Tp., at a point from which the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., hereinbefore described, bears S. 89°46'10" W., 9.879 chs. dist.</p>
0.20	<p>E. Pursel Lane, an improved dirt road, 30 lks. wide, bears E. and W.</p>
8.778	<p>Cor. No. 3, Mineral Survey No. 4893, Lyon No. 135 lode, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above a collar of stone, with brass cap mkd. as described in the field notes of Mineral Survey No. 4893.</p> <p>From this cor., a corner of a 3 strand wire fence bears S. 36°05'20" E., 0.032 chs. dist., from which fences extend S. and E.</p> <p>From this same cor., a wood post, 4x4 ins., firmly set, projecting 4 ft. above the ground, with 4 tags mkd.; SW COR LYON 151, NW COR LYON 135, NE COR 130, SE COR LYON 129, bears S. 39°36'30" W., 0.063 chs. dist.</p> <hr/>

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4893,  
T. 13 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 89°55'20" E., on line 3-4, Mineral Survey No. 4893, Lyon No. 135 lode.
22.450	<p>Cor. No. 4, Mineral Survey No. 4893, Lyon No. 135 lode, identical with Cor. No. 2, Mineral Survey No. 4893, Lyon No. 136 lode, monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above a collar of stone, with brass cap mkd. as described in the field notes of Mineral Survey No. 4893.</p> <p>From this cor., a wood post, 4x4 ins, firmly set, projecting 3 ft. above the ground, with 4 tags mkd.; SW COR LYON NO. 152, NW COR LYON NO. 136, NE COR LYON NO. 135, SE COR LYON NO. 151, bears N. 51°36'20" E., 0.250 chs. dist.</p> <p>From this same cor., a 3 strand wire fence bears South, 0.181 chs. dist., with fences extending E. and W.</p> <hr/> <p style="text-align: center;"><u>Lyon No. 136 lode</u></p> <p>From Cor. No. 2, Mineral Survey No. 4893, Lyon No. 136 lode, identical with Cor. No. 4, Mineral Survey No. 4893, Lyon No. 135 lode, hereinbefore described.</p> <p>From this cor., the 1/4 sec. cor. of secs. 2 and 35, on the S. bdy. of the Tp., hereinbefore described, bears S. 42°09'30" E., 11.673 chs. dist.</p> <p>N. 89°53'50" E., on line 2-3, Mineral Survey No. 4893, Lyon No. 136 lode.</p>
22.451	<p>Cor. No. 3, Mineral Survey No. 4893, Lyon No. 136 lode, identical with Cor. No. 3, Mineral Survey No. 4893, Lyon No. 137 lode, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above a collar of stone, with brass cap mkd. as described in the field notes of Mineral Survey No. 4893.</p> <p>From this cor., a corner of a 3 strand wire fence, bears S. 44°23'30" W., 0.050 chs. dist., from which fences extend S. and W.</p> <p>From this same cor., a wood post, 4x4 ins, firmly set, projecting 4 ft. above the ground, with 4 tags mkd.; LYON 153 S.W. COR., LYON 137 N.W. COR., LYON 136 N.E. COR., LYON 152 S.E. COR., bears S. 77°00'20" W., 0.192 chs. dist.</p> <hr/> <p>S. 0°04'40" E., on line 3-4, Mineral Survey No. 4893, Lyon No. 135 lode.</p>
8.635	Intersect the line bet. secs. 2 and 35, on the S. bdy. of the Tp., at a point from which the 1/4 sec. cor. of secs. 2 and 35, on the S. bdy. of the Tp., hereinbefore described, bears S. 89°46'10" W., 14.629 chs. dist.
8.782	Cor. No. 4, Mineral Survey No. 4893, Lyon No. 136 lode, identical with Cor. No. 2, Mineral Survey No. 4893, Lyon No. 137 lode, Cor. No. 4, Mineral Survey No. 4893, Lyon No. 8 lode and Cor. No. 2, Mineral Survey No. 4893, Lyon No. 7 lode, monumented

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4893,  
T. 13 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

with an iron post, 1 in. diam., firmly set, projecting 5 ins. above a collar of stone, with brass cap mkd. as described in the field notes of Mineral Survey No. 4893.

From this cor., a corner of a 3 strand wire fence bears S. 42°10'20" W., 0.051 chs. dist., from which fences extend N. and E.

---

METES-AND-BOUNDS SURVEY IN SECTIONS 35 AND 36,  
T. 13 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

---

MEMORANDUM

The following metes-and-bounds survey is executed to identify certain lands to be conveyed to the City of Yerington, Nevada, pursuant to the National Defense Authorization Act for fiscal Year 2015 (P.L. 113-291).

From the point for the witness point, at the intersection of the line bet. secs. 1 and 36, on the S. bdy. of the Tp., with the westerly right-of-way line of the Sylmar-Oregon H.V.D.C. Transmission Line.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

WP  
T13N R26E  
S \ 36  
-----  
S 1  
T12N

2015

From this point, an angle point of the Sylmar-Oregon H.V.D.C. Transmission Line, established by Walter H. Georg, Nevada Professional Land Surveyor No. 2142, in 1966, monumented with an iron post, 2 ins. diam., filled with concrete, firmly set, projecting 1 in. above the ground, with tag mkd. with a legible 9, as shown on the Sylmar-Oregon H.V.D.C. Transmission Line Of The City Of Los Angeles map, recorded in Lyon County, Nevada, as Document No. 99950, bears S. 16°43'00" E., 752.709 chs. dist.

From this same point, the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., hereinbefore described, bears S. 89°46'40" W., 0.809 chs. dist.

N. 16°37'10" W., on the westerly right-of-way line of the Sylmar-Oregon H.V.D.C. Transmission Line.

2.864

Point for a witness point, at the intersection of the line bet. secs. 35 and 36, with the westerly right-of-way line of the Sylmar-Oregon H.V.D.C. Transmission Line.

METES-AND-BOUNDS SURVEY IN SECTIONS 35 AND 36,  
T. 13 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">           WP            T13N R26E            S35 \ S36            2015         </p> <p>From this point, the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., hereinbefore described, bears S. 0°13'40" E., 2.748 chs. dist.</p>
<p>6.544</p>	<p>N. 16°37'10" W., on the westerly right-of-way line of the Sylmar-Oregon H.V.D.C. Transmission Line.</p> <p>Point for Angle Point No. 1, in sec. 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">           T13N R26E            S35 \ AP1            2015         </p> <p>From this point, an angle point of the Sylmar-Oregon H.V.D.C. Transmission Line, established by Walter H. Georg, Nevada Professional Land Surveyor No. 2142, in 1966, monumented with an iron post, 2 ins. diam., filled with concrete, firmly set, projecting 2 ins. above the ground, with tag mkd. P.I. 10, as shown on the Sylmar-Oregon H.V.D.C. Transmission Line Of The City Of Los Angeles map, recorded in Lyon County, Nevada, as Document No. 99951, bears N. 74°16'50" E., 1.515 chs. dist.</p>
<p>36.393</p>	<p>N. 14°49'20" W., on line 1-2, identical with the westerly right-of-way line of the Sylmar-Oregon H.V.D.C. Transmission Line.</p> <p>Point for Angle Point No. 2, in sec. 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">           T13N R26E            S35 \ AP2            2015         </p>

METES-AND-BOUNDS SURVEY IN SECTIONS 35 AND 36,  
T. 13 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS							
	<p>From this point, an angle point of the Sylmar-Oregon H.V.D.C. Transmission Line, established by Walter H. Georg, Nevada Professional Land Surveyor No. 2142, in 1966, monumented with an iron post, 2 ins. diam., filled with concrete, firmly set, projecting 3 ins. above the ground, with tag mkd. P.I. 11, as shown on the Sylmar-Oregon H.V.D.C Transmission Line Of The City Of Los Angeles map, recorded in Lyon County, Nevada, as Document No. 99951, bears N. 14°28'00" W., 239.562 chs. dist.</p>						
	<hr/> <p>N. 88°01'00" E., in sec. 35.</p>						
1.55	<p>The Sylmar-Oregon H.V.D.C. Transmission Line, bears S. 15° E. and N. 15° W.</p>						
11.031	<p>Point for a witness point at the intersection with the line bet. secs. 35 and 36.</p>						
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p>						
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>WP</td></tr> <tr><td>T13N R26E</td></tr> <tr><td>S   S</td></tr> <tr><td>— —</td></tr> <tr><td>35   36</td></tr> <tr><td>2015</td></tr> </table>	WP	T13N R26E	S   S	— —	35   36	2015
WP							
T13N R26E							
S   S							
— —							
35   36							
2015							
	<p>From this point, the 1/4 sec. cor. of secs. 35 and 36, hereinbefore described, bears S. 0°06'10" E., 4.192 chs. dist.</p>						
	<hr/> <p>N. 88°01'00" E., in sec. 36.</p>						
34.471	<p>Point for a witness point.</p>						
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p>						
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>WP</td></tr> <tr><td>T13N R26E</td></tr> <tr><td>S</td></tr> <tr><td>—</td></tr> <tr><td>36</td></tr> <tr><td>2015</td></tr> </table>	WP	T13N R26E	S	—	36	2015
WP							
T13N R26E							
S							
—							
36							
2015							
79.471	<p>The witness point, at the intersection of a line bet. Angle Point No. 2, in sec. 35, of this metes-and-bounds survey and Angle Point No. 1, in sec. 31, T. 13 N., R. 27 E., of a metes-and-bounds survey executed concurrently under this same Group with the E. bdy. of T. 13 N., R. 26 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. as described in the field notes of the metes-and-bounds survey in secs. 28, 29, 30</p>						

METES-AND-BOUNDS SURVEY IN SECTIONS 35 AND 36,  
T. 13 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS							
	<p>and 31, T. 13 N., R. 27 E., executed concurrently under this same Group.</p> <p>From this point, the 1/4 sec. cor. of sec. 36, on the E. bdy. of the Tp., bears S. 0°19'00" W., 6.787 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set 2 ins. below the surface of a dirt road, 12 lks. wide, bears S. 30° E. and N. 30° W., as described in the field notes of the dependent resurvey of a portion of the E. bdy of T. 13 N., R. 26 E., executed concurrently under this same Group.</p> <hr/> <p>From the witness point, at the intersection of a line bet. Angle Point No. 3, in sec. 31, T. 13 N., R. 27 E., of a metes-and-bounds survey executed concurrently under this same Group and Angle Point No. 3, in sec. 35, T. 13 N., R. 26 E., of this metes-and-bounds survey with the E. bdy. of T. 13 N., R. 26 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. as described in the field notes of the metes-and-bounds survey in secs. 28, 29, 30 and 31, T. 13 N., R. 27 E., executed concurrently under this same Group.</p> <p>From this point, the cor. of secs. 25 and 36, T. 13 N., R. 26 E., hereinbefore described, bears N. 0°19'00" E., 20.925 chs. dist.</p> <p>S. 88°01'00" W., in sec. 36.</p>						
38.604	<p>Point for a witness point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>WP</p> <p>T13N R26E</p> <p>S</p> <hr style="width: 50px; margin: 0 auto;"/> <p>36</p> <p>2015</p> </div>						
79.557	<p>Point for a witness point, at the intersection with the line bet. secs. 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>WP</p> <p>T13N R26E</p> <table border="1" style="margin: 0 auto; border-collapse: collapse;"> <tr> <td style="padding: 2px 5px;">S</td> <td style="padding: 2px 5px;">S</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black; border-bottom: 1px solid black;"></td> </tr> <tr> <td style="padding: 2px 5px;">35</td> <td style="padding: 2px 5px;">36</td> </tr> </table> <p>2015</p> </div>	S	S			35	36
S	S						
35	36						

METES-AND-BOUNDS SURVEY IN SECTIONS 35 AND 36,  
T. 13 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From this cor., the cor. of secs. 25, 26, 35 and 36, hereinbefore described, bears N. 0°06'10" W., 23.909 chs. dist.</p> <hr/>
	<p>S. 88°01'00" W., in sec. 35.</p>
12.60	<p>The Sylmar-Oregon H.V.D.C. Transmission Line, bears S. 15° E. and N. 15° W.</p>
28.897	<p>Point for Angle Point No. 3, in sec. 35.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T13N R26E S35   AP3 2015</p> <hr/>
	<p>N. 1°16'10" W., in sec. 35.</p>
24.988	<p>Point for a witness point, at the intersection of the last course of this metes-and-bounds survey with the line bet. secs. 26 and 35.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">WP T13N R26E S26 S   35 2015</p>
	<p>From this point, the 1/4 sec. cor. of secs. 26 and 35, hereinbefore described, bears N. 89°51'30" W., 10.559 chs. dist.</p> <hr/>

METES-AND-BOUNDS SURVEY IN SECTIONS 35 AND 36,  
T. 13 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<u>GENERAL DESCRIPTION</u>
	<p>The lands located within Township 13 North, Range 26 East, are located in Lyon County, Nevada, situated southeast of Yerington, Nevada. Access is gained by way of E. Pursel Lane and numerous secondary desert trail roads. The terrain varies from rocky hills in the east portion to gently westerly sloping lands in the west portion. The average elevation of the area is approximately 4,850 feet above sea level. Vegetation consists primarily of shadscale covering the mostly sandy ground.</p> <p>The Pumpkin Hollow mining operation is situated in section 35. Currently, E. Pursel Lane is the main access road to the active mine site. A LADWP power transmission line crosses sections 35 and 36.</p>

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Brock R. Clifford	Cadastral Surveyor
Brandon G. Courtright	Cadastral Surveyor
Michael E. Swope	Cadastral Surveyor
Mark G. Petrosine	Surveying Technician

## CERTIFICATE OF SURVEY

I, Brandon K. Grace, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 24th day of February, 2015, supplemental special instructions bearing date of the 27th day of February, 2015 and supplemental special instructions bearing date of the 24th day of March, 2015, I have dependently resurveyed a portion of the south boundary, a portion of the subdivisional lines and portions of Mineral Survey Nos. 4892 and 4893 and executed a metes-and-bounds survey in sections 35 and 36, Township 13 North, Range 26 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

**JUN 12 2015**

(Date)

*Brandon K. Grace*

(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Reno, Nevada

The foregoing field notes of the dependent resurvey of a portion of the south boundary, a portion of the subdivisional lines and portions of Mineral Survey Nos. 4892 and 4893 and a metes-and-bounds survey in sections 35 and 36, Township 13 North, Range 26 East, Mount Diablo Meridian, Nevada, executed by Brandon K. Grace, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

**JUN 12 2015**

(Date)

*Michael C. Hammon*

(Chief Cadastral Surveyor for Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above described surveys in T. 13 N., R. 26 E., Mount Diablo Meridian, Nevada, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor for Nevada)~~