

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

A PORTION OF THE NORTH BOUNDARY

OF

TOWNSHIP 12 NORTH, RANGE 27 EAST;

THE WEST BOUNDARY

OF

TOWNSHIP 13 NORTH, RANGE 28 EAST;

A PORTION OF THE SUBDIVISIONAL LINES

OF

TOWNSHIP 13 NORTH, RANGE 27 EAST;

AND

PORTIONS OF CERTAIN MINERAL SURVEYS

IN

TOWNSHIPS 13 NORTH, RANGES 27 AND 28 EAST;

AND,

THE SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF CERTAIN SECTIONS,

TOWNSHIP 13 NORTH, RANGE 27 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATE OF NEVADA

EXECUTED BY

David J. Clark, Cadastral Surveyor  
Mark G. Petrosine, Surveying Technician

Under Special Instructions dated August 16, 2007,  
and approved August 16, 2007,  
and Supplemental Special Instructions dated, March 26, 2009,  
and approved March 26, 2009,  
which provided for the surveys included under Group No. 855,  
and Assignment Instructions dated January 16, 2008.

Survey commenced February 9, 2008

Survey completed March 28, 2009

## INDEX DIAGRAM

TOWNSHIP 13 NORTH, RANGE 27 EAST, MOUNT DIABLO MERIDIAN, NEVADA

6	5	4	3	2	12 1	11
					13	
7	8	9	10	11	12	9
				19		
18	17	16	15	42 14	15 13	8
				42 20	16	
19	20	21	22	43 23	17 24	7
				43	37 37 18	
30	29	28	27	44 26	38 25	6
				45	39	
31	32	33	34	35	41 36	4

2

Dependent Resurvey of a Portion of Mineral Survey No. 3981.. pp. 21 - 23  
 Dependent Resurvey of a Portion of Mineral Survey No. 4107.. pp. 23 - 24  
 Dependent Resurvey of a Portion of Mineral Survey No. 4344.. pp. 24 - 27  
 Dependent Resurvey of Mineral Survey No. 4447..... pp. 27 - 29  
 Dependent Resurvey of Mineral Survey No. 4526..... pp. 29 - 32  
 Dependent Resurvey of a Portion of Mineral Survey No. 4542.. pp. 32 - 37  
 Subdivision of Section 1 ..... pp. 45 - 46  
 Subdivision of Section 23 ..... pp. 46 - 47  
 Subdivision of Section 24 ..... pp. 48 - 49  
 Subdivision of Section 26 ..... pp. 49 - 50  
 Subdivision of Section 36 ..... p. 50

## TOWNSHIP 13 NORTH, RANGE 27 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>The following field notes are those of the dependent resurvey of a portion of the north boundary of Township 12 North, Range 27 East; the west boundary of Township 13 North, Range 28 East; a portion of the subdivisional lines of Township 13 North, Range 27 East; and portions of certain Mineral Surveys in Townships 13 North, Ranges 27 and 28 East; and, the survey of a portion of the subdivisional lines, and the subdivision of certain sections, Township 13 North, Range 27 East, Mount Diablo Meridian, Nevada.</p> <p>The south boundary was surveyed by U.S. Deputy Surveyor R.A. Chase in 1869-70 under Contract No. 29. A portion of the south boundary was retraced and the east boundary and a portion of the north boundary were surveyed by U.S. Deputy Surveyors H.E. Franks and J.S. Mullen in 1904 under Contract No. 237. A portion of the subdivisional lines was surveyed by U.S. Deputy Surveyors H. Thurtell and W. Kearney in 1908 under Contract No. 257. A portion of the north boundary was dependently resurveyed by Cadastral Surveyor D.A. Potts and Surveying Technician M.G. Petrosine in 2006-08 under Group No. 837. Mineral Survey No. 3981, Capatola lode, was surveyed in 1911 by U.S. Mineral Surveyor G.W. Lloyd, and amended in 1913 by the same surveyor. Mineral Survey No. 4107, Wadloux and Calaverite lodes, were surveyed by U.S. Mineral Surveyor L.G.B. MacDowell in 1912. Mineral Survey No. 4206 was surveyed by U.S. Mineral Surveyor J.H. Tate in 1914 and cancelled July 6, 1995. Mineral Survey No. 4344, Golden Fleece, Colchise, Argo (Cancelled July 6, 1995), Jason, Argonaut, Argonaut No. 2 and Argonaut No. 3 lodes, were surveyed by U.S. Mineral Surveyor W.A. Pray in 1917. Mineral Survey No. 4447, Climax lode, was surveyed by U.S. Mineral Surveyor G.W. Malone in 1920. Mineral Survey No. 4526, Mountain View lode, was surveyed by U.S. Mineral Surveyor G.W. Malone in 1921-22. Mineral Survey No. 4542, Mohawk and Boston lodes, were surveyed by U.S. Mineral Surveyor R.M. Stewart in 1922. Other official surveys remote to this area are not included.</p> <p>Before restoring the corners, the lines of the original surveys were retraced and diligent search made for any evidence of the original corners and other calls of the original field note record.</p> <p>Lost corner(s) were reestablished at position(s) based on the official record, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.</p> <p>The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, the Special Instructions dated August 16, 2007 and the Supplemental Special Instructions dated March 26, 2009, for Group No. 855.</p> <p>Measurements were made with Trimble 4700, 5700, and 5800 Global Positioning System (GPS) receivers using static and real-time kinematic methods and refer to the true meridian based on geodetic methods. The mean bearings of the lines and horizontal equivalents of ground distances only are entered in the field notes.</p> <p>The NAD 1983 (CORS 96) geographic position of the corner of Townships 12 and 13 North, Ranges 27 and 28 East, determined from GPS static observations post processed by the National</p>
--------	--

## TOWNSHIP 13 NORTH, RANGE 27 EAST, MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

Geodetic Survey, Online Positioning User(OPUS), utilizing Continuously Operating Reference Stations(CORS) UPSAL HOGBACK CORS ARP, GABBS CORS ARP AND AUSTIN 1 CORS ARP, in 2008, and carried forward by additional static observation is as follows:

Latitude: 38°56'20.645" N. Longitude: 118°54'11.491" W.

The mean magnetic declination is 15°30' E., as shown on U.S.G.S. 7 1/2 minute quadrangle map "HUSSMAN SPRING, NEVADA", provisional edition dated 1988.

---

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
T. 12 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

---

Reestablishment of a Portion of the Survey Executed by  
U.S. Deputy Surveyor R.A. Chase in 1869-70  
and Retraced by U.S. Deputy Surveyors H.E. Franks  
and J.S. Mullen in 1904

---

Beginning at the cor. of Tps. 12 and 13 N., Rs. 27 and 28 E., monumented with a granite stone, 16x10x8 ins., firmly set, projecting 8 ins. above the ground, mkd. with 7 notches on the NE., SE., SW. and NW. edges, and in a mound of stone, 2 ft. base, 1/2 ft. high, from which the original bearing trees

A pinon pine, 8 ins. diam., bears N. 42° E., 19 lks. dist., with scribe mks. T12N R 9 S1 BT visible on partially healed blaze. (Record: N. 40° E., 80 lks.)

A down pinon pine, 10 ins. diam., on E. fork, bears S. 36° E., 43 lks. dist., with illegible scribe mks. visible on partially healed blaze. (Record: S. 60° E., 20 lks.)

A down pinon pine, 14 ins. diam., bears S. 68° W., 60 lks. dist., with scribe mks. T12R N9E BT visible on weathered blaze. (Record: S. 50° W., 70 lks.)

A dead standing pinon pine, 10 ins. diam., bears N. 37 1/4° W., 39 1/2 lks. dist., with illegible scribe mks. visible on upper blaze and T13N R27E on lower blaze. (Record: N. 4° W., 45 lks.)

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

T13N	
R27E	R28E
S36	S31
S 1	S 6
T12N	

2008

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
T. 12 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>from which</p> <p>A chiseled X followed by the letters BO, bears S. 66°52' E., 158.7 lks. dist., mkd. on the top of a granite boulder, 2x2x1 ft. high.</p> <p>A chiseled X followed by the letters BO, bears S. 62°54' W., 90.8 lks. dist., mkd. on the top of an igneous outcrop, 4x2x2 1/2 ft. high.</p> <p>A chiseled X followed by the letters BO, bears N. 12°22' W., 90.4 lks. dist., mkd. on the top of a granite boulder, 2x1 1/2x1 ft. high.</p> <p>Rebuild mound around stainless steel post, 3 ft. base, to top.</p> <p>Deposit original stone alongside stainless steel post.</p> <p>S. 89°39'50" W., on the N. bdy. of sec. 1.</p> <p>Over mountainous terrain, through pinon pine, sagebrush, cheat and bunchgrass.</p> <p>30.00 Top steep ascent of divide.</p> <p>32.00 Descend W. slope of divide.</p> <p>39.930 The 1/4 sec. cor. of sec. 36 only, T. 13 N., R. 27 E., hereinafter described.</p> <p>40.415 The 1/4 sec. cor. of secs. 1 and 36, determined at the center of a mound of stone, 2 ft. base, 1/2 ft. high, with a weathered squared pine branch, 2 ins. diam., 3 ft. long, mkd. 1/4 S, lying alongside, from which the original bearing trees</p> <p>A pinon pine, 12 ins. diam., bears N. 83 1/4° E., 26 1/2 lks. dist., with scribe mks. 1/4 S BT visible on a partially healed blaze. (Record: N. 16° E., 50 lks.) Remove the mks. 1/4 S and add the mark X</p> <p>A pinon pine, 12 ins. diam., bears S. 19 1/4° W., 28.5 lks. dist., with scribe mks. 1/4 S BT visible on a partially healed blaze. (Record: S. 2° W., 70 lks.)</p> <p>This cor. will now refer to sec. 1 only.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to bedrock, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13N R27E</p> <hr style="width: 50%; margin: 0 auto;"/> <p>1/4 S 1</p> <p>T12N R27E</p> <p>2008</p> </div> <p>Rebuild mound around stainless steel post, 3 ft. base, to top.</p>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
T. 12 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Deposit original wood post remains alongside stainless steel post.</p> <hr/> <p>N. 88°16'40" W., beginning new measurement.</p>								
39.533	<p>The cor. of secs. 1, 2, 35 and 36, determined at the center of a mound of stone, 3 ft. base, 1/2 ft. high, with a weathered squared wood post, 3 ins. diam., 2 ft. long, no mks. visible lying alongside.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr> <td>T13N</td><td>R27E</td></tr> <tr> <td>S35</td><td>S36</td></tr> <tr> <td>S 2</td><td>S 1</td></tr> <tr> <td>T12N</td><td></td></tr> </table> <p>2008</p> </div> <p>Rebuild mound around stainless steel post, 3 ft. base, to top.</p> <p>Deposit original wood post alongside stainless steel post and below mound.</p> <p>Corner is located at westerly edge of pinon pines, bears NW. and SE.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF THE WEST BOUNDARY, T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of the Survey Executed by U.S. Deputy Surveyors H.E. Franks and J.S. Mullen in 1904</p> <hr/> <p>From the cor. of Tps. 12 and 13 N., Rs. 27 and 28 E., hereinbefore described.</p> <p>N. 0°57'40" W., on the W. bdy. of sec. 31.</p> <p>Across mountainous terrain, through pinon pine, sagebrush, cheat and bunchgrass.</p>	T13N	R27E	S35	S36	S 2	S 1	T12N	
T13N	R27E								
S35	S36								
S 2	S 1								
T12N									
12.20	Spur, slopes E.								
38.289	The 1/4 sec. cor. of sec. 36 only, T. 13 N., R. 27 E., hereinafter described.								
39.579	<p>The 1/4 sec. cor. of secs. 31 and 36, monumented with a granite stone, 18x6x6 ins., lying on side, mkd. 1/4 on side facing up, from which the original bearing trees</p> <p style="padding-left: 40px;">A dead standing pinon pine, 14 ins. diam., bears N. 65° E., 15 lks. dist., with scribe mks. 1/4 S31 visible on weathered blaze. (Record: N. 80° E.)</p>								

DEPENDENT RESURVEY OF THE WEST BOUNDARY,  
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>A pinon pine, 14 ins. diam., bears W., 5 lks. dist., with scribe mks. 1/4 S36 BT visible on partially healed blaze. Remove the mks. 1/4 S36 and add the mark X</p> <p>This cor. will now refer to sec. 31 only.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13N R27E R28E   1/4   S31</p> <p>2008</p> </div> <p>Deposit original stone alongside stainless steel post and at base of mound.</p> <hr/> <p>N. 0°59'00" E., beginning new measurement.</p>
0.50	Ravine, drains E.
9.30	Top of steep S. slope.
34.40	Top of steep N. slope.
38.40	Ravine, drains NE.
38.716	The cor. of secs. 25 and 36, T. 13 N., R. 27 E., hereinafter described.
39.792	<p>The cor. of secs. 25, 30, 31 and 36, monumented with a granite stone, 18x8x7 ins., firmly set, projecting 13 ins. above the ground, mkd. with 5 partially destroyed grooves on the E. and S. faces, and with 5 grooves on the N. face and 1 groove on the S. face, from which the original bearing trees</p> <p>A dead standing pinon pine, 10 ins. diam., bears S. 16 1/4° W., 15 1/2 lks. dist., with scribe mks. T13N R27E S36 BT visible on weathered blaze. (Record: S. 20° W., 11 lks.) Remove the mks. T13N R27E S36 and add the mark X.</p> <p>The rotted remains of the NW. bearing tree, 9 ins. diam., bears N. 79° W., 25 lks. dist., with scribe mks. T13N R remaining, original position indeterminate. (Record: N. 73° W., 39 lks.)</p> <p>This cor. will now refer to secs. 30 and 31 only.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

DEPENDENT RESURVEY OF THE WEST BOUNDARY,  
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<div style="display: flex; justify-content: center; align-items: center;"> <div style="text-align: center; margin-right: 10px;"> T13N R27E S25 </div> <div style="border-left: 1px solid black; padding-left: 10px; text-align: center;"> T13N S30 S31 R28E </div> </div> <div style="text-align: center; margin-top: 10px;">2008</div>
	<p>from which</p> <p style="margin-left: 40px;">A chiseled X followed by the letters BO, bears S. 79°04' E., 38.1 lks. dist., mkd. on the top of an igneous outcrop, 6x5x2 ft. high, 1 ft. from NW. end.</p> <p style="margin-left: 40px;">A chiseled X followed by the letters BO, bears N. 48°42' W., 9.2 lks. dist., mkd. on a rock face, 2 1/2x3 1/2, 1 ft. from W. end.</p>
	<hr/> <p>N. 0°00'50" W., on the W. bdy. of sec. 30.</p> <p>Across mountainous terrain, through pinon pine, sagebrush, cheat and bunchgrass.</p>
12.05	Graded dirt road, 15 lks. wide, bears N. 40° E. and S. 40° W.
14.70	Top of steep descent to the N., bears ENE. and WSW.
17.60	Ravine, drains E.
23.80	Spur, slopes ESE.
36.94	From this point, a mound of stone, 3 ft. base, 1 ft. high, bears E., 0.10 chs. dist., located on top of ridge, bears NE. and SW.
38.924	The 1/4 sec. cor. of sec. 25 only, T. 13 N., R. 27 E., hereinafter described.
39.760	<p>The 1/4 sec. cor. of secs. 25 and 30, monumented with a granite stone, 18x6x6 ins., mkd. 1/4 on a face, lying alongside the E. side of a scattered mound of stone, 4 ft. base, 1 ft. high, and an old wood stake, 1 in. square, 31 ins. long, also lying alongside. This cor. will now refer to sec. 30 only.</p> <p>At the corner point, base of mkd. stone</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin-top: 20px;"> T13N R27E R28E 1/4 S30 </div> <div style="text-align: center; margin-top: 10px;">2008</div> <p>Deposit original stone alongside stainless steel post and the wood stake in the mound.</p>
	<hr/> <p>N. 0°01'40" E., beginning new measurement.</p>



DEPENDENT RESURVEY OF THE WEST BOUNDARY,  
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS									
39.833	<p>The cor. of secs. 19, 24, 25 and 30, monumented with a granite stone, 18x6x5 ins., lying alongside the E. side of a mound of stone, 3 ft. base, 1 ft. high, mkd. with 3 notches on an edge and 3 notches on the opposite edge.</p> <p>At the corner point, base of mkd. stone</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T13N</td><td></td></tr> <tr><td>R27E</td><td>R28E</td></tr> <tr><td>S24</td><td>S19</td></tr> <tr><td>S25</td><td>S30</td></tr> </table> <p>2008</p> </div> <p>Deposit original stone alongside stainless steel post and below mound.</p>	T13N		R27E	R28E	S24	S19	S25	S30
T13N									
R27E	R28E								
S24	S19								
S25	S30								
	<hr/> <p>N. 0°02'40" W., bet. secs. 19 and 24.</p>								
	<p>Across mountainous terrain, through sagebrush, cheat and bunchgrass.</p>								
1.00	<p>Spur and top of steep descent to the N.</p>								
35.90	<p>Ridge, bears NE. and SW.</p>								
39.778	<p>The 1/4 sec. cor. of secs. 19 and 24, monumented with a granite stone, 20x7x5 ins., firmly set, projecting 13 ins. above the ground, mkd. 1/4 on the E. face, with a mound of stone, 3 ft. base, 1 ft. high, W. of cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T13N</td><td></td></tr> <tr><td>1/4</td><td></td></tr> <tr><td>R27E</td><td>R28E</td></tr> <tr><td>S24</td><td>S19</td></tr> </table> <p>2008</p> </div> <p>from which</p> <p>A chiseled X followed by the letters BO, bears S. 67°08' E., 77.7 lks. dist., mkd. on the top of an igneous outcrop, 3x2x1 ft. high.</p> <p>A chiseled X followed by the letters BO, bears N. 16°38' W., 108.9 lks. dist., mkd. on the top of an igneous outcrop, 3x2x1 ft. high.</p>	T13N		1/4		R27E	R28E	S24	S19
T13N									
1/4									
R27E	R28E								
S24	S19								

DEPENDENT RESURVEY OF THE WEST BOUNDARY,  
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Deposit original stone alongside stainless steel post and below mound.</p> <hr/> <p>N. 0°07'20" W., beginning new measurement.</p>								
0.30	Spur, slopes NW.								
9.60	Ravine, drains NW.								
12.50	Spur, slopes NW.								
31.15	Dirt road, 15 lks. wide, in center of ravine, bears NE. and SW.; ravine drains NE.								
39.760	<p>The cor. of secs. 13, 18, 19 and 24, monumented with a granite stone, 19x8x8 ins., lying on its side at E. side of scattered mound of stone, 3 ft. base, 1/2 ft. high, mkd. with 3 notches on an edge and 3 notches on the opposite edge.</p> <p>At the corner point, base of mkd. stone</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td colspan="2">T13N</td></tr> <tr><td>R27E</td><td>R28E</td></tr> <tr><td>S13</td><td>S18</td></tr> <tr><td>S24</td><td>S19</td></tr> </table> <p>2008</p> </div> <p>Rebuild mound around stainless steel post, 3 ft. base to top.</p> <p>Deposit original stone alongside stainless steel post and below mound.</p> <hr/> <p>N. 0°57'20" W., bet. secs. 13 and 18.</p> <p>Across mountainous terrain, through sagebrush, shadscale, cheat and bunchgrass, posting the boundary of the Walker River Indian Reservation with steel sign posts.</p>	T13N		R27E	R28E	S13	S18	S24	S19
T13N									
R27E	R28E								
S13	S18								
S24	S19								
3.10	Ravine, drains SE., soon E.								
7.30	Spur, slopes SE.								
11.00	Head of ravine, drains SE.								
17.00	Spur, slopes NE.								
39.90	Graded dirt road, 15 lks. wide, bears N. 20° E. and S. 20° W.								
40.316	<p>The 1/4 sec. cor. of secs. 13 and 18, monumented with a granite stone, 18x8x5 ins., firmly set, projecting 7 ins. above the ground, the mks. /4 visible on the W. face, with a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.</p> <p>At the corner point</p>								

DEPENDENT RESURVEY OF THE WEST BOUNDARY,  
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13N 1/4 R27E   R28E S13   S18</p> <p>2008</p> </div> <p>Deposit original stone alongside stainless steel post, and below mound.</p> <p>Discontinue posting north of this cor.</p> <p>From this corner, Cor. No. 3, Mineral Survey No. 4447, Climax lode, hereinafter described, bears N. 36°24'00" W., 16.333 chs. dist.</p> <hr/> <p>N. 1°05'40" E., beginning new measurement.</p> <p>6.70      Ravine, 25 lks. wide, drains NNE.</p> <p>13.60      Dirt road, 15 lks. wide, bears N. 20° E. and S. 20° W.</p> <p>27.35      Dirt road, 15 lks. wide, bears N. 40° W. and S. 40° E.</p> <p>30.80      Dirt road, 15 lks. wide, bears N. 40° E. and S. 40° W.</p> <p>40.133      The cor. of secs. 7, 12, 13 and 18, monumented with a granite stone, 18x8x5 ins., firmly set, projecting 12 ins. above the ground, mkd. with 2 notches on the N. edge and 4 notches on the S. edge, with a mound of stone, 2 ft. base, 2 ft. high, W. of cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13N R27E   R28E S12   S 7 S13   S18</p> <p>2008</p> </div> <p>Rebuild mound around stainless steel post, 3 ft. base, to top, and deposit original stone alongside stainless steel post and below mound.</p> <p>From this corner, Cor. No. 2, Mineral Survey No. 4447, Climax lode, hereinafter described, bears S. 30°00'50" W., 20.660 chs. dist.</p> <hr/> <p>N. 0°02'00" E., bet. secs. 7 and 12.</p> <p>Across mountainous terrain, through shadscale, cheat and bunchgrass.</p>
--------	--

DEPENDENT RESURVEY OF THE WEST BOUNDARY,  
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
5.00	Top left bank of ravine, bears NNE. and SSW.
21.00	Top right bank of another ravine, bears NNE. and SSW.
29.70	Graded dirt road, 15 lks. wide, in ravine, bears N. 60° E. and S. 70° W.; ravine drains N. 60° E.
39.982	<p>The 1/4 sec. cor. of secs. 7 and 12, monumented with a granite stone, 21x8x3 ins., firmly set, projecting 18 ins. above the ground, mkd. 1/4 on the W. face, in a collar of stone, with a mound of stone, 2 ft. base, 2 ft. high, W. of cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 3 ins. in the ground, to bedrock, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13N 1/4 R27E   R28E S12   S 7</p> <p>2008</p> </div> <p>Rebuild mound around stainless steel post, 4 ft. base, to top.</p> <p>Deposit original stone alongside stainless steel post and below mound.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°02'20" W., beginning new measurement.</p>
5.30	Spur, slopes ENE.
9.112	Intersect line 2-3, Mineral Survey No. 3981, Capatola lode, and point for a closing corner, hereinafter described, at a point from which Cor. No. 3, hereinafter described, bears S. 54°35'30" E., 3.131 chs. dist.
21.20	Spur, slopes E.
22.17	Barbed wire fence, wood posts, bears N. 70° E. and S. 70° W.
40.534	<p>The cor. of secs. 1, 6, 7, and 12, monumented with a granite stone, 22x9x6 ins., firmly set, projecting 7 ins. above a scattered mound of stone, 3 ft. base, 1 ft. high, mkd. with 1 notch on the N. edge and 5 notches on the S. edge.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13N R27E   R28E S 1   S 6 <hr style="width: 50%; margin: 0 auto;"/>S12   S 7</p> <p>2008</p> </div>

DEPENDENT RESURVEY OF THE WEST BOUNDARY,  
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Rebuild mound around stainless steel post, 3 ft. base, to top.</p> <p>Deposit original stone alongside stainless steel post and below mound.</p> <hr/> <p>N. 0°05'30" W., bet. secs. 1 and 6.</p> <p>Across mountainous terrain, through shadscale, cheat and bunchgrass.</p> <p>0.455 Intersect line 4-1, Mineral Survey No. 4542, Boston lode, at a point from which Cor. No. 1, hereinafter described, bears S. 72°27'20" E., 1.157 chs. dist.</p> <p>1.092 Intersect line 1-2, Mineral Survey No. 4542, Mohawk lode, at a point from which Cor. No. 1, hereinafter described, bears N. 80°16'20" W., 3.042 chs. dist.</p> <p>6.40 Ravine, drains NW.</p> <p>13.00 Foot of mountains, bears E. and W., continue descent over gentle N. slope.</p> <p>40.256 The 1/4 sec. cor. of secs. 1 and 6, monumented with a quartz stone, 24x6x4 ins., firmly set, projecting 6 ins. above the ground, mkd. 1/4 on the W. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13N 1/4 R27E   R28E S 1   S 6</p> <p>2008</p> </div> <p>Deposit original stone alongside stainless steel post and below collar.</p> <hr/> <p>N. 0°19'20" E., beginning new measurement.</p> <p>9.71 Powerline, wood poles, bears N. 55° W. and S. 55° E.</p> <p>18.62 Asphalt remains of old U.S. Alternate Highway No. 95, 18 lks. wide, bears NW. and SE.</p> <p>25.78 Center of pavement, U.S. Alternate Highway No. 95, 50 lks. wide, bears N. 56 3/4° W. and S. 56 3/4° E.</p> <p>27.62 Barbed wire fence, wood and steel posts, parallels U.S. Alternate Highway No. 95.</p>
--------	--

DEPENDENT RESURVEY OF THE WEST BOUNDARY,  
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.940	<p>The cor. of Tps. 13 and 14 N., Rs. 27 and 28 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, and in an embedded collar of stone, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 14 N., R. 27 E., executed under Group No. 837.</p>
	<hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 13 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>
	<p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyors H. Thurtell and W. Kearney in 1908</p> <hr/>
	<p>From the cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, set flush with the top of a mound of stone, 3 ft. base, 1/2 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 14 N., R. 27 E., executed under Group No. 837.</p>
	<p>S. 0°04'10" W., bet. secs. 1 and 2, posting the boundary of the Walker River Indian Reservation with steel sign posts.</p>
	<p>Along W. side of fence, across mountainous terrain, through shadscale, cheat and bunchgrass.</p>
16.70	<p>Intersect 2 track road, 10 lks. wide, bears N. and SW.</p>
18.51	<p>From this point, a well embedded mound of stone, of unknown origin, 3 ft. base, 2 1/2 ft. high, bears W., 0.14 chs. dist.</p>
37.30	<p>Ravine, drains NE.</p>
40.290	<p>The 1/4 sec. cor. of secs. 1 and 2, monumented with an andesite stone, 20x18x8 ins., firmly set, projecting 8 ins. above the ground, mkd. 1/4 on the W. face, with a mound of stone, 4 ft. base, 1 ft. high, W. of cor.</p>
	<p>At the corner point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p>T13N R27E</p>
	<p>1/4</p>
	<p>S 2   S 1</p>
	<p>2008</p>
	<p>Rebuild mound around stainless steel post, 3 ft. base, to top.</p>
	<p>Deposit original stone alongside stainless steel post and below mound.</p>
	<p>Discontinue posting south of this cor.</p> <hr/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	S. 0°01'10" E., beginning new measurement.						
2.13	From this point, a corner of barbed wire fences bears E., 0.20 chs. dist., from which fences extend N. and S. 60° E.						
4.90	Single track trail, bears NW. and SE.						
24.50	Bottom of deep ravine, drains NE.						
28.10	From this point, a rock cairn, 2 ft. base, 2 ft. high, bears W., 0.55 chs. dist.						
32.60	Spur, slopes ESE.						
34.30	Ravine, drains SE.						
35.60	Spur, slopes ESE.						
36.50	Ravine, drains ESE.						
40.059	The cor. of secs. 1, 2, 11 and 12, monumented with a basalt stone, 18x8x5 ins., firmly set, projecting 5 ins. above the ground, mkd. with 3 grooves on the S. face and 2 grooves on the E. face, with a scattered mound of stone, W. and also settling around mkd. stone.						
	At the corner point						
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.						
	<table> <tr> <td>T13N</td><td>R27E</td></tr> <tr> <td>S 2</td><td>S 1</td></tr> <tr> <td>S11</td><td>S12</td></tr> </table>	T13N	R27E	S 2	S 1	S11	S12
T13N	R27E						
S 2	S 1						
S11	S12						
	2008						
	from which						
	A chiseled X followed by the letters BO, bears N. 60°58' E., 446.6 lks. dist., mkd. on top of the SW. corner of a concrete water trough, 16x11x2 ft. high.						
	A chiseled X followed by the letters BO, bears S. 2°54' W., 73.7 lks. dist., mkd. on the top of an igneous outcrop, 6x3x3 ft. high.						
	Deposit original stone alongside stainless steel post and below mound.						
	From this cor., the SW. corner of a concrete water trough, 16x11x2 ft. high, bears N. 60°58' E., 4.47 chs. dist., fed by an iron pipe, 2 ins. diam., projecting horizontally from the ground at the NE. cor. of the trough.						
	From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., hereinbefore described.						
	N. 89°56'30" W., bet. secs. 1 and 12.						

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Across mountainous terrain, through shadscale, cheat and bunchgrass.
3.146	Intersect line 4-1, Mineral Survey No. 4542, Mohawk lode, at a point from which Cor. No. 1, hereinafter described, bears N. 5°10'10" E., 1.609 chs. dist.
5.10	Ravine, drains NE.
7.716	Intersect line 3-4, Mineral Survey No. 4542, Boston lode, and point for a closing corner, hereinafter described, at a point from which Cor. No. 4, hereinafter described, bears N. 6°36'00" E., 2.803 chs. dist.
	Begin posting the boundary of the Walker River Indian Reservation with steel sign posts.
11.00	Spur, slopes N.
20.50	Ravine, drains ENE.
25.10	Spur, slopes NE.
35.70	Ravine, drains NNE.
40.125	The 1/4 sec. cor. of secs. 1 and 12, monumented with a basalt stone, 15x10x8 ins., firmly set, projecting 9 ins. above the ground, mkd. 1/4 on N. face, with a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	T13N R27E S 1 1/4 $\frac{\quad}{S12}$
	2008
	Deposit original stone alongside stainless steel post and below mound.
	Discontinue posting west of this cor.
	<hr/> S. 89°47'00" W., beginning new measurement.
5.00	Broad ridge, 1 ch. wide, bears NW. and SE.
14.70	Ravine, drains NW.
37.50	Ravine, drains NNE.
40.023	The cor. of secs. 1, 2, 11 and 12.
	<hr/>



DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS					
	<p>From the cor. of secs. 11, 12, 13 and 14, monumented with an andesite stone, 20x12x6 ins., firmly set, projecting 6 ins. above the ground, mkd. with 1 notch on the E. edge and 5 notches on the S. edge, with a mound of stone, 2 ft. base, 1 ft. high, SW. of cor., and another mound of stone, 2 ft. base, 1 ft. high, S.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13N R27E</p> <table> <tr><td>S11</td><td>S12</td></tr> <tr><td>S14</td><td>S13</td></tr> </table> <p>2008</p> </div> <p>Deposit original stone alongside stainless steel post and below the mound.</p> <p>From this cor., Paiute Spring bears N. 80 3/4° E., 35.35 chs. dist.</p> <p>S. 0°02'50" E., bet. secs. 13 and 14.</p> <p>Across mountainous terrain, through sagebrush and bunchgrass.</p>	S11	S12	S14	S13
S11	S12				
S14	S13				
22.70	Graded dirt road, 15 lks. wide, bears E. and W.				
23.70	Ravine, drains NE., soon E.				
40.493	<p>The 1/4 sec. cor. of secs. 13 and 14, monumented with an andesite stone, 14x10x6 ins., firmly set, projecting 2 ins. above the ground, mkd. 1/4 on the W. face, with a scattered mound of stone, 2 ft. base, 1/2 ft. high, W. of cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13N R27E</p> <table> <tr><td>1/4</td><td></td></tr> <tr><td>S14</td><td>S13</td></tr> </table> <p>2008</p> </div> <p>Deposit original stone alongside stainless steel post and below mound.</p> <p>Set steel sign post alongside stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 0°07'20" E., beginning new measurement.</p>	1/4		S14	S13
1/4					
S14	S13				
4.20	From this point, the top of a conical shaped peak bears W., 3.5 chs. dist.				
19.60	Ravine, drains NNE., soon E.				

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS							
22.80	From this point, a mound of stone, 2 ft. base, 1 ft. high, bears E., 0.67 chs. dist., set on top of small hill.						
40.183	<p>The cor. of secs. 13, 14, 23 and 24, monumented with an igneous stone, 15x8x6 ins., firmly set, projecting 10 ins. above the ground, mkd. with 1 notch on the E. edge and 3 notches on the S. edge, with a scattered mound of stone, 3 ft. base, 1/2 ft. high, S. of cor. (Record: limestone)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td>T13N</td><td>R27E</td></tr> <tr><td>S14</td><td>S13</td></tr> <tr><td>S23</td><td>S24</td></tr> </table> <p>2008</p> </div> <p>Deposit original stone alongside stainless steel post and below mound.</p> <hr/> <p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°55'50" W., bet. secs. 13 and 24.</p> <p>Across mountainous terrain, through sagebrush and bunchgrass posting the boundary of the Walker River Indian Reservation with steel sign posts.</p>	T13N	R27E	S14	S13	S23	S24
T13N	R27E						
S14	S13						
S23	S24						
5.40	Ridge, bears NE. and SE.						
9.90	Ravine, drains N.						
10.95	Single track trail, bears NNE. and SSW.						
14.20	Spur, slopes N.						
18.40	Spur, slopes NNE.						
23.10	Ravine, drains NNE.						
24.20	Spur, slopes NE.						
26.00	Ravine, drains NNE.						
29.80	Ravine, drains NE.						
34.70	Spur, slopes NE.						
37.567	<p>Intersect line 4-1, Mineral Survey No. 4344, Golden Fleece lode, and point for a closing corner, hereinafter described, at a point from which Cor. No. 1, hereinafter described, bears S. 27°22'30" W., 6.720 chs. dist.</p> <p>Discontinue posting west of this intersection.</p>						

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
37.70	Ravine, drains NE.
40.113	The 1/4 sec. cor. of secs. 13 and 24, monumented with an igneous stone, 18x14x6 ins., firmly set, projecting 8 ins. above the ground, mkd. 1/4 on the N. face, with a mound of stone, 2 1/2 ft. base, 1 ft. high, N. of cor. (Record: limestone)
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	<div style="text-align: center;">           T13N R27E            S13            1/4 <math>\frac{\quad}{\quad}</math>            S24              2008         </div>
	Deposit original stone alongside stainless steel post and below mound.
	<hr/>
	S. 89°50'10" W., beginning new measurement.
5.10	Ridge, bears NE. and SW.
8.20	Ravine, drains NE.
16.40	Spur, slopes NE.
23.40	Spur, slopes NNE.
27.69	Intersect mound of stone, of unknown origin, 3 ft. base, 1 ft. high, on spur, slopes NNE.
31.60	Convergence of two ravines draining NE.
39.246	Intersect line 3-4, Mineral Survey No. 4344, Argonaut lode, at a point from which Cor. No. 3, hereinafter described, bears S. 29°32'30" W., 0.117 chs. dist.
39.50	Saddle on ridge, bears NE. and SW.
39.952	The cor. of secs. 13, 14, 23 and 24.
	<hr/>
	S. 0°20'10" E., bet. secs. 23 and 24.
	Across mountainous terrain, through scattered pinon pine, sagebrush and bunchgrass.
1.00	Ridge, bears NE. and SW.
4.50	Spur, slopes NE.
8.80	Ravine, drains NE.
12.00	Spur, slopes ENE.
17.00	Ravine, drains E.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.10	Spur, slopes ENE.
25.00	Ravine, drains ENE.
26.20	Spur, slopes ENE.
31.30	Ravine, drains ENE.
33.10	From this point, the NE. corner of a collapsed wood building, 14 ft. square, sides bear N. 75° W. and S. 15° W., bears W., 2.05 chs. dist.
40.040	<p>The 1/4 sec. cor. of secs. 23 and 24, monumented with an andesite stone, 14x8x6 ins., firmly set, projecting 8 ins. above the ground, mkd. 1/4 on the W. face, with a mound of stone, 2 ft. base, 1 ft. high, SW. of cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T13N R27E 1/4 S23 S24 2008</p> <p>Deposit original stone alongside stainless steel post and below mound.</p> <hr/> <p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 24 and 25.</p> <p>Over mountainous terrain, through sagebrush cheat and bunchgrass.</p>
3.00	Spur, slopes NNW.
14.60	Ravine, drains NW.
17.70	End of spur, slopes N.
33.20	Head of ravine, drains N.
35.90	Spur, slopes N.
40.000	<p>The 1/4 sec. cor. of secs. 24 and 25, determined at record bearing and distance from the cor. of secs. 19, 24, 25 and 30; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<div style="text-align: right;">T13N R27E</div> <div style="text-align: right;">S24</div> <div style="text-align: right;">1/4 <u>      </u></div> <div style="text-align: right;">S25</div> <div style="text-align: right;">2008</div> <hr/> <p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>S. 89°47'40" W., bet. secs. 11 and 14.</p> <p>Over rolling land, through sagebrush, shadscale, cheat and bunchgrass.</p>
4.00	Broad spur, slopes N.
40.187	<p>The 1/4 sec. cor. of secs. 11 and 14, monumented with a basalt stone, 16x14x8 ins., firmly set, projecting 6 ins. above the ground, mkd. 1/4 on the N. face, with a mound of stone, 2 ft. base, 1 ft. high, N. of cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: right;">T13N R27E</div> <div style="text-align: right;">S11</div> <div style="text-align: right;">1/4 <u>      </u></div> <div style="text-align: right;">S14</div> <div style="text-align: right;">2008</div> <p>A chiseled X followed by the letters BO, bears S. 34°03' W., 43.2 lks. dist., mkd. on the top of an igneous outcrop, 18x15x3 ft. high.</p> <p>A chiseled X followed by the letters BO, bears N. 23°24' W., 103.4 lks. dist., mkd. on the top of an igneous outcrop, 23x11x4 ft. high, 2 ft. from SE. end.</p> <p>Rebuild mound around stainless steel post, 4 ft. base, to top.</p> <p>Deposit original stone alongside stainless steel post and below mound.</p> <hr/> <p>S. 89°43'30" W., beginning new measurement.</p>
5.00	Wash, 1 ch. wide, drains NW.
36.00	Ravine, drains NNW.
40.096	<p>The cor. of secs. 10, 11, 14 and 15, monumented with an igneous stone, 19x10x8 ins., firmly set, projecting 8 ins. above the ground, mkd. with 4 notches on the S. edge, and 2 notches on the E. edge. (Record: limestone 15x8x6 ins.)</p> <p>At the corner point</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13N R27E</p> <table> <tr> <td>S10</td><td>S11</td></tr> <tr> <td>S15</td><td>S14</td></tr> </table> <p>2008</p> </div> <p>from which</p> <p style="padding-left: 40px;">A chiseled X followed by the letters BO, bears S. 3°10' E., 37.2 lks. dist., mkd. on the top of an igneous outcrop, 6x4x1 ft. high.</p> <p>Deposit original stone alongside stainless steel post and below mound.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>S. 89°47'50" W., bet. secs. 14 and 23.</p> <p>Over mountainous terrain, through sagebrush, cheat and bunchgrass.</p> <p>4.00 Spur, slopes NE.</p> <p>5.70 Ravine, drains NE.</p> <p>7.70 Spur, slopes NE.</p> <p>10.90 Ravine, drains NE.</p> <p>14.70 Spur, slopes NE.</p> <p>17.50 Spur, slopes NNE.</p> <p>21.50 From this point, the mouth of a tunnel, bearing SE., bears S., 5.20 chs. dist.</p> <p>22.05 Graded dirt road, 15 lks. wide, bears NE. and SSW.</p> <p>23.25 From this point, a vertical shaft, bears S., 2.90 chs. dist.</p> <p>26.00 From this point, a pit, 1/2 ch. wide, 4 ft. deep, bears S., 0.80 chs. dist.</p> <p>37.20 Ridge and crest of divide, bears NW. and S.</p> <p>40.294 The 1/4 sec. cor. of secs. 14 and 23, monumented with a basalt stone, 18x18x12 ins., firmly set, projecting 12 ins. from a talus slide, mkd. 1/4 on the N. face, with a mound of stone, 3 ft. base, 1 ft. high, NW. of cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>	S10	S11	S15	S14
S10	S11				
S15	S14				

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

T13N R27E

$$1/4 \frac{S14}{S23}$$

2008

from which

A chiseled X followed by the letters BO, bears  
S. 3°58' E., 66.4 lks. dist., mkd. on the top of an  
igneous outcrop, 2x1x2 ft. high.

A chiseled X followed by the letters BO, bears  
S. 47°20' W., 117.4 lks. dist., mkd. on the top of an  
igneous outcrop, 2x3x2 ft. high.

Deposit original stone alongside stainless steel post and below  
mound.

From this corner, plate boundary observatory GPS station, P134,  
"Miners Ridge NV2006", a continuously operating reference  
station, bears S. 23°31'00" E., 8.095 chs. dist., to base of  
antenna.

---

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 3981,  
TPS. 13 N., RS. 27 AND 28 E., MOUNT DIABLO MERIDIAN, NEVADA

---

Reestablishment of the Survey Executed by  
U.S. Mineral Surveyor G.W. Lloyd in 1911 and Amended in 1913

---

CAPATOLA LODE

From the point for Cor. No. 1, Mineral Survey No. 3981, Capatola  
lode, identical with Cor. No. 1, Mineral Survey No. 4107,  
Calaverite lode, determined by the method of parallel end and  
side lines. There is no remaining evidence of the original  
corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,  
21 ins. in the ground, over a plastic-encased magnet, and in a  
mound of stone, 3 ft. base, to top, with brass cap mkd.

COR 1 MS 4107 CAL

MS 4542 BOS

COR 1 MS 3981 CAP

2009

From this corner, Cor. No. 4, Mineral Survey No. 3981, Capatola  
lode, hereinafter described, bears S. 54°35'30" E. 22.562 chs.  
dist.

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 3981,  
TPS. 13 N., RS. 27 AND 28 E., MOUNT DIABLO MERIDIAN, NEVADA


CHAINS	<p>Thence S. 56°12'50" W., on line 1-2, Mineral Survey No. 3981 Capatola lode, identical with line 1-2, Mineral Survey No. 4107, Calaverite lode.</p>
0.995	<p>Intersect line 3-4, Mineral Survey No. 4542, Boston lode, at a point from which Cor. No. 3, hereinafter described, bears S. 6°36'00" W., 3.365 chs. dist.</p>
8.513	<p>Cor. No. 2, Mineral Survey No. 3981, Capatola lode, identical with Cor. No. 2, Mineral Survey No. 4107, Calaverite lode, on line 4-1, Mineral Survey No. 4107, Wadloux lode, monumented with a wood post, 4 ins. square, firmly set, projecting 3 ft. above the ground, mkd. with illegible scribe mks. on the SE. side, with a mound of stone, 3 ft. base, 1 ft. high, SE. of cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a collar of stone, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="792 835 1166 1077" data-label="Diagram"> <p>The diagram shows a corner point labeled '2008'. A line from the top left is labeled 'MS 4107' and 'WAD'. Another line from the top left is labeled 'MS 4107' and 'CAL'. A line from the top right is labeled 'MS 3981' and 'CAP'. A line from the bottom right is labeled 'S12'. A central point is labeled 'COR 2'.</p> </div> <p>Deposit original wood post alongside stainless steel post.</p> <p>Thence S. 54°35'30" E., on line 2-3, Mineral Survey No. 3981, Capatola lode.</p>
19.431	<p>Intersect the line bet. secs. 7 and 12, on the E. bdy. of the Tp., and point for a closing corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="824 1451 1101 1713" data-label="Diagram"> <p>The diagram shows a corner point labeled '2009'. A line from the top left is labeled 'MS 3981' and 'CA'. A line from the top right is labeled 'MS 3981' and 'CA'. A line from the bottom left is labeled 'S12' and 'R27E'. A line from the bottom right is labeled 'S 7' and 'R28E'. A central point is labeled 'C' and 'T13N'.</p> </div>
22.562	<p>Cor. No. 3, Mineral Survey No. 3981, Capatola lode, monumented with a wood post, 4 ins. square, 4 ft. long, firmly set, projecting 3 ft. above a mound of stone, 3 1/2 ft. base, 1 ft. high, mkd. 3 3981 C.</p> <p>At the corner point</p>



DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 3981,  
TPS. 13 N., RS. 27 AND 28 E., MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.




Rebuild mound around stainless steel post, 3 1/2 ft. base, to top.

Deposit original wood post alongside stainless steel post and below mound.

From this corner, Cor. No. 4, Mineral Survey No. 3981, Capatola lode, bears N. 56°12'50" E. 8.513 chs. dist., monumented with a wood post, 4 ins. square, 4 ft. long, projecting 2 1/2 ft. above a scattered mound of earth and stone, 3 ft. base, 1 ft. high, mkd. 4 3981 CAPATOLA ON NW. face, with an iron pin, 3/4 diam., projecting 1 in. above ground, set against NE. side of wood post.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.



Rebuild mound around stainless steel post, 3 ft. base, to top.

Deposit original wood post alongside stainless steel post and below mound.

---

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4107,  
T. 13 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

---

Reestablishment of the Survey Executed by  
L.G.B. MacDowell in 1912

---


CALAVERITE LODGE

From Cor. No. 5, Mineral Survey No. 4107, Calaverite lode, monumented with a wood post, 4 ins. square, 5 ft. long, loosely set in a mound of stone, 3 ft. base, 1 ft. high, mkd. W 4107,

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to bedrock, over a plastic-encased magnet, with brass cap mkd.



DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4107,  
T. 13 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div data-bbox="860 273 1055 493"> <p>T13N R27E S12 COR 5 MS 4107 CAL 2009</p>  </div> <p>Rebuild mound around stainless steel post, 5 ft. base, to top. Deposit original wood post alongside stainless steel post and below mound.</p> <p>Thence S. 47°18'40" E., on line 5-1, Mineral Survey No. 4107, Calaverite lode.</p> <p>9.960 Intersect line 3-4, Mineral Survey No. 4542, Boston lode, at a point from which Cor. No. 3, hereinafter described, bears S. 6°36'00" E., 4.562 chs. dist.</p> <p>10.898 Cor. No. 1, Mineral Survey No. 4107, Calaverite lode, identical with Cor. No. 1, Mineral Survey No. 3981, Capatola lode, hereinbefore described.</p> <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4344, T. 13 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of the Survey Executed by W.A. Pray in 1917</p> <hr/> <p>GOLDEN FLEECE LODGE</p> <p>From Cor. No. 4, Mineral Survey No. 4344, Golden Fleece lode, monumented with the original eruptive stone, 13x6 ins., firmly set, projecting 12 ins. above ground, mkd. G F 4 4344 on the NW. face and X on top, with a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>CORNER POINT NOT REMONUMENTED</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, over a plastic-encased magnet, and in a collar of stone, bears S. 2°26' E., 62.7 lks. dist., with brass cap mkd. RM MS 4344 GF COR 4 S13 2008 41.4 FT TO COR and an arrow pointing to the cor.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, over a plastic-encased magnet, and in a collar of stone, bears S. 34°26' W., 54.7 lks. dist., with brass cap mkd. RM MS 4344 GF COR 4 S13 2008 36.1 FT TO COR and an arrow pointing to the cor.</p> <p>Thence S. 27°22'30" W., on line 4-1, Mineral Survey No. 4344, Golden Fleece lode.</p>
--------	---

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4344,  
T. 13 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
16.065	<p>Intersect the line bet. secs. 13 and 24 and point for a closing corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 1 in. in the ground, to bedrock, over a plastic-encased magnet, in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <div data-bbox="812 483 1136 682"> <p>MS 4344 G F C C S13 T13N S24 R27E MS4344 G F</p> </div> <p>2008</p> <p>From this point, the 1/4 sec. cor. of secs. 13 and 24, hereinbefore described, bears S. 89°55'50" W., 2.546 chs. dist.</p> <p>Begin posting the boundary of the Walker River Indian Reservation with steel sign posts.</p>
21.570	<p>Intersect the N-S center line of sec. 24 and point for a closing corner, hereinafter described, at a point from which the 1/4 sec. cor. of secs. 13 and 24, hereinbefore described, bears N. 0°10'10" W., 4.886 chs. dist.</p> <p>Discontinue posting north of this intersection.</p>
22.785	<p>Cor. No. 1, Mineral Survey No. 4344, Golden Fleece lode, monumented with an eruptive stone, 24x12x7 ins., firmly set, projecting 12 ins. above ground, mkd. G F 1 4344 on the NW. face and an X on top, with a mound stone, 3 ft. base, 2 ft. high, W. of the cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div data-bbox="812 1428 1055 1606"> <p>MS 4344 G F COR 1 T13N R27E S24</p> </div> <p>2008</p> <p>Deposit original stone alongside stainless steel post and below mound.</p> <hr/> <p>Thence N. 47°15'40" W., on a portion of line 1-2, Mineral Survey No. 4344, Golden Fleece lode.</p>

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4344,  
T. 13 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>0.608 Cor. No. 1, Mineral Survey No. 4344, Jason lode, monumented with an eruptive stone, 24x11x5 ins., firmly set, projecting 8 ins. above the ground, mkd. J1 4344 on the W. face and an X on top, with a mound stone, 3 ft. base, 2 ft. high, SE. of the cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>  <p>2008</p> <p>Deposit original stone alongside stainless steel post and below mound.</p>
	<p>ARGONAUT LODE</p>
	<p>From Cor. No. 3, Mineral Survey No. 4344, Argonaut lode, monumented with an eruptive stone, 26x10x8 ins., firmly set, projecting 9 ins. above ground, and in a collar of stone, mkd. A 3 4344 on the E. face and X on top.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>  <p>2008</p> <p>Deposit original stone alongside stainless steel post and below mound.</p> <p>Thence N. 29°32'30" E., on line 3-4, Mineral Survey No. 4344, Argonaut lode.</p>
0.117	<p>Intersect the line bet. secs. 13 and 24, at a point from which the cor. of secs. 13, 14, 23 and 24, hereinbefore described, bears S. 89°50'10" W., 0.706 chs. dist.</p>
18.454	<p>Cor. No. 4, Mineral Survey No. 4344, Argonaut lode, monumented with an eruptive stone, 17x8x6 ins., lying loose in a mound of stone, 3 ft. base, 1 ft. high, mkd. 4 4344 with an X on top.</p>

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4344,  
T. 13 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

At the corner point

Set a brass tablet 3 1/4 in. diam., 3 1/2-in. stem, in drill hole, 1 in. diam., in bedrock, with top mkd.

T13N R27E  
S13  
COR 4  
MS 4344  
ARG

2008

Rebuild mound around tablet, 3 ft. base, 6 ins. above tablet and deposit original stone at base of mound.

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 4447,  
T. 13 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by  
G.W. Malone in 1920

CLIMAX LODGE

From the point for Cor. No. 1, Mineral Survey No. 4447, Climax lode, determined at right angle measurement to line 3-4 and record distance from Cor. No. 4. The remains of the original wood post, 4 ins. square, 2 1/2 ft. long, lying loose, mkd. 1 N 4447, original position indeterminate, bears NW., 0.10 chs. dist.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

T13N R27E  
S13  
COR 1  
MS 4447  
CLI

2009

Deposit wood post alongside stainless steel post and below surface of the ground.

Thence S. 89°13'30" E., on line 1-2, Mineral Survey No. 4447, Climax lode.

11.42

Intersect a scattered mound of stone, 2 ft. base, 1/2 ft. high, with a weathered wood post, 4 ins. square, 4 ft. long, the marks NS remaining, lying alongside.

From this mound, a tunnel, 4 ft. wide, bears S. 46°50' E., 4.70 chs. dist., the course of which bears SW.

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 4447,  
T. 13 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

22.750

Point for Cor. No. 2, Mineral Survey No. 4447, Climax lode, determined at right angle measurement to line 3-4 and record distance from Cor. No. 3. The original wood post, 4 ins. square, 4 ft. long, lying loose, mkd. NE COR, original position indeterminate, bears NE., 0.05 chs. dist.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.

T13N R27E  
S13

COR 2  
MS 4447  
CLI

2009

Deposit wood post alongside stainless steel post and below surface of the ground.

Thence S. 0°46'30" W., on line 2-3, Mineral Survey No. 4447, Climax lode.

9.091

Cor. No. 3, Mineral Survey No. 4447, Climax lode, determined at the center of a scattered mound of stone, 3 ft. base, 1/2 ft. high, with a weathered wood post, 4 ins. square, 4 ft. long, mkd. N 4447, lying loose alongside mound.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

MS 4447  
CLI  
COR 1

T13N  
R27E  
S13

2009

Rebuild mound of stone around stainless steel post, 4 1/2 ft. base to top.

Deposit original wood post alongside stainless steel post and below mound.

Thence N. 89°13'30" W., on line 3-4, Mineral Survey No. 4447, Climax lode.

11.34

Intersect a scattered mound of stone, 3 ft. base, 1 ft. high, with a weathered wood post, 4 ins. square, 4 ft. long, mkd. N 4447 on a side and CLIMAX on the opposite side, lying alongside.

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 4447,  
T. 13 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

22.750

Cor. No. 4, Mineral Survey No. 4447, Climax lode, determined at the center of a mound of stone, 3 ft. base, 1 ft. high, with a weathered wood post, 4 ins. square, 4 ft. long, lying loose across mound mkd. N 4447 SW COR.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to bedrock, over a plastic-encased magnet, with brass cap mkd.

T13N	MS 4447
R27E	CLI
S13	COR 4

2009

Rebuild mound around stainless steel post, 4 ft. base to top.

Deposit original wood post alongside stainless steel post and below mound.

Thence N. 0°46'30" E., on line 4-1, Mineral Survey No. 4447, Climax lode

9.091

Cor. No. 1, Mineral Survey No. 4447, Climax lode, and the place of beginning.

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 4526,  
T. 13 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by  
G.W. Malone in 1922

## MOUNTAIN VIEW LODE



From the point for Cor. No. 1, Mineral Survey No. 4526, Mountain View lode, determined parallel with and at equal length to line between the south side center and Cor. No. 4, from the north side center; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T13N R27E
COR 1 S 23
MS 4526
M V

2009

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 4526,  
T. 13 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Thence S. 80°50'10" W., on line 1-2, Mineral Survey No. 4526, Mountain View lode.</p>
10.324	<p>North side center, Mineral Survey No. 4526, Mountain View lode, monumented with a weathered wood post 4 ins. square, firmly set, projecting 3 ft. above a mound of stone, 3 ft. base, 1 ft. high, mkd. NSC M V on the south face and SSC V on the north face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="889 657 1036 892" style="text-align: center;"> <p>T13N R27E S 23</p>  <p>NSC MS 4526 M V</p> <p>2009</p> </div> <p>Rebuild mound around stainless steel post, 3 ft. base, to top.</p> <p>Deposit original wood post alongside stainless steel post and below mound of stone.</p> <hr/> <p>Continue on line 1-2, Mineral Survey No. 4526, Mountain View lode, S. 82°05'00" W., beginning new measurement.</p>
11.944	<p>Point for Cor. No. 2, Mineral Survey No. 4526, Mountain View lode, determined parallel with and at equal length to the line between Cor. No. 3 and the south side center, from the north side center. The original wood post, 4 ins. square, 4 ft. long, mkd. M V NW COR found lying loose, original position indeterminate, bears S. 14° E., 4.10 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div data-bbox="878 1476 1044 1711" style="text-align: center;"> <p>T13N R27E S 23</p>  <p>COR 2 MS 4526 M V</p> <p>2009</p> </div> <p>From this corner, an igneous stone, 12x8x7 ft., mkd. M V 4 on a face and I M 1 on an adjacent face, lying loose in a scattered mound of stone, 3 ft. base, 1 ft. high, bears S. 4°37' E., 1.014 chs. dist., not utilized in the course of this survey.</p> <p>From this same corner, a tunnel, 5x7 ft., bears S. 53°57' E., 7.19 chs. dist., the course of which bears N. 60° E.</p>



DEPENDENT RESURVEY OF MINERAL SURVEY NO. 4526,  
T. 13 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From this corner, a tunnel, 5x7 ft., bears S. 27°26' E., 5.31 chs. dist., the course of which bears N. 60° E.</p>
	<p>Thence S. 29°36'40" E., on line 2-3, Mineral Survey No. 4526, Mountain View lode.</p> <p>9.762 Cor. No. 3, Mineral Survey No. 4526, Mountain View lode, determined at the center of a scattered mound of earth and stone, 4 ft. base, 1 ft. high. This mound correlates well with other existing corners and is accepted as the best available evidence of the original corner position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="812 787 1104 976"> <p>A diagram showing a corner point labeled 'COR 3'. To the left, a line segment is labeled 'T13N R27E S 23'. To the right, a line segment is labeled 'MS 4526 M V'. The corner point is marked with a line segment labeled '2009'.</p> </div> <p>Rebuild mound around stainless steel post, 4 ft. base, to top.</p>
11.944	<p>Thence N. 82°05'00" E., on line 3-4, Mineral Survey No. 4526, Mountain View lode.</p> <p>South side center, Mineral Survey No. 4526, Mountain View lode, monumented with a weathered wood post, 4 ins. square, firmly set, projecting 3 ft. above a mound of stone, 3 ft. base, 1 ft. high, mkd. SSC MV on the north face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to bedrock, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="868 1459 1039 1701"> <p>A diagram showing a corner point labeled 'SSC'. Above it, a line segment is labeled 'M V MS 4526'. Below it, a line segment is labeled 'S 23 T13N R27E'. The corner point is marked with a line segment labeled '2009'.</p> </div> <p>Rebuild mound around stainless steel post, 5 ft. base, to top. Deposit original wood post alongside stainless steel post and below mound of stone.</p> <p>Continue on line 3-4, Mineral Survey No. 4526, Mountain View lode, N. 80°50'10" E., beginning new measurement.</p>

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 4526,  
T. 13 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

10.324

Cor. No. 4, Mineral Survey No. 4526, Mountain View lode, determined at the center of a scattered mound of earth and stone, 4 ft. base, 1 ft. high with the remains of a wood post, 4 ins. square, 2 ft. long, lying loose alongside. This mound correlates well with other existing corners and is accepted as the best available evidence of the original corner position.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

M V	T13N
COR 4	R27E
MS 4526	S 23

2009

Rebuild mound around stainless steel post, 4 ft. base, to top.

Deposit original wood post alongside stainless steel post and below mound of stone.

---

Thence N. 29°36'40" W., on line 4-1, Mineral Survey No. 4526, Mountain View lode.

9.762

Cor. No. 1, Mineral Survey No. 4526, Mountain View lode, and the place of beginning.

---

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 4542,  
TPS. 13 N., RS. 27 AND 28 E., MOUNT DIABLO MERIDIAN, NEVADA

---

Reestablishment of the Survey Executed by  
U.S. Mineral Surveyor R.M. Stewart in 1922

---

MOHAWK LODE

From Cor. No. 4, Mineral Survey No. 4542, Mohawk lode, monumented with a weathered wood post, 4 ins. square, 3 1/2 ft. long, firmly set, projecting 2 ft. above a mound of stone, 4 ft. base, 2 ft. high, mkd. 4 4542.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4542,  
TPS. 13 N., RS. 27 AND 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<div data-bbox="885 275 1101 451"> <p>MS 4542 MOH COR 4 MS 3981 CAP</p> </div> <p>2009</p> <p>Rebuild mound around stainless steel post, 3 ft. base, to top.</p> <p>Deposit wood post, alongside stainless steel post and below mound.</p> <p>Thence N. 5°10'10" E., on line 4-1, Mineral Survey No. 4542, Mohawk lode.</p> <p>21.700 Intersect the line bet. secs. 1 and 12, at a point from which the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., hereinbefore described, bears S. 89°56'30" E., 3.146 chains dist.</p> <p>23.112 Intersect line 4-1, Mineral Survey No. 4542, Boston lode, and point for a closing corner, hereinafter described, at a point from which Cor. No. 1, hereinafter described, bears S. 72°27'20" E., 4.321 chs. dist.</p> <p>Begin posting the boundary of the Walker River Indian Reservation with steel sign posts.</p> <p>23.309 Cor. No. 1, Mineral Survey No. 4542, Mohawk lode, determined at the center of a mound of earth and stone, 3 ft. base, 1 ft. high, with a weathered redwood post, 4x3 ins., 3 1/2 ft. long, lying loose across mound, no marks visible, and a broken weathered redwood post, 4 ins. square, no marks visible, also lying atop mound.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="857 1446 1076 1606"> <p>T13N R27E S1 COR 1 MS 4542 MOH</p> </div> <p>2008</p> <p>Rebuild mound of stone around stainless steel post, 3 ft. base to top.</p> <p>Deposit original redwood post and the other wood post alongside stainless steel post and below mound.</p>



DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4542,  
TPS. 13 N., RS. 27 AND 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Thence S. 80°16'20" E., on line 1-2, Mineral Survey No. 4542, Mohawk lode, posting the boundary of the Walker River Indian Reservation with steel sign posts.</p> <p>3.042 Intersect the line bet. secs. 1 and 6, on the E. bdy. of the Tp., at a point from which the cor. of secs. 1, 6, 7 and 12, hereinbefore described, bears S. 0°05'30" E., 1.092 chs. dist.</p> <p>Discontinue posting east of this intersection.</p> <p>9.002 Cor. No. 2, Mineral Survey No. 4542, Mohawk lode, determined at the center of a mound of earth and stone, 3 ft. base, 1 ft. high, with a weathered redwood post, 4x3 ins., 3 ft. long, lying loose alongside, mkd. 2 4542M.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="812 835 1047 1003"> <p>T13N R28E S6 COR 2 MS 4542 MOH</p> </div> <p>2008</p> <p>Rebuild mound of stone around stainless steel post, 3 ft. base, to top.</p> <p>Deposit original redwood post alongside stainless steel post and below mound.</p> <hr/> <p>BOSTON LODGE</p> <p>From Cor. No. 3, Mineral Survey No. 4542, Boston lode, monumented with a weathered wood post, 3x3 ins. remaining, firmly set, projecting 2 1/2 ft. above a mound of earth and stone, 3 ft. base, 1 ft. high, mkd. 3 4542B, with an iron pin, 3/4 in. diam., firmly set against S. side of wood post, projecting 5 ins. above mound.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to bedrock, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="876 1696 1079 1879"> <p>MS4542 BOS COR 3 MS 3981 CAP</p> </div> <p>2009</p>
--------	---

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4542,  
TPS. 13 N., RS. 27 AND 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Rebuild mound of stone around stainless steel post, 4 ft. base, to top.</p> <p>Deposit original wood post alongside stainless steel and below mound.</p> <p>Thence N. 6°36'00" E., on line 3-4, Mineral Survey No. 4542, Boston lode.</p>										
0.03	Barbed wire fence, wood posts, bears E. and W.										
3.365	Intersect line 1-2, Mineral Survey No. 3981, Capatola lode, identical with line 1-2, Mineral Survey No. 4107, Calaverite lode, at a point from which Cor. No. 1 Capatola lode, identical with Cor. No. 1, Calaverite lode, hereinbefore described, bears N. 56°12'50" E., 0.995 chs. dist.										
4.562	Intersect line 5-1, Mineral Survey No. 4107, Calaverite lode, at a point from which Cor. No. 1, Mineral Survey No. 3981, Capatola lode, identical with Cor. No. 1, Calaverite lode, hereinbefore described, bears S. 47°18'40" E., 0.938 chs. dist.										
19.462	<p>Intersect the line between secs. 1 and 12 and point for a closing corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr> <td>S 1</td><td>MS 4542</td></tr> <tr> <td>T13N</td><td>BOS</td></tr> <tr> <td>R27E</td><td>C C</td></tr> <tr> <td>S12</td><td>MS 4542</td></tr> <tr> <td></td><td>BOS</td></tr> </table> <p>2008</p> </div> <p>From this corner, the corner of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., hereinbefore described, bears S. 89°56'30" E., 7.716 chs. dist.</p> <p>Begin posting the boundary of the Walker River Indian Reservation with steel sign posts.</p>	S 1	MS 4542	T13N	BOS	R27E	C C	S12	MS 4542		BOS
S 1	MS 4542										
T13N	BOS										
R27E	C C										
S12	MS 4542										
	BOS										
22.265	<p>Cor. No. 4, Mineral Survey No. 4542, Boston lode, monumented with a wood post, 4 ins. square, 4 ft. long, firmly set, projecting 3 ft. above a mound of earth and stone, 3 ft. base, 1 ft. high, mkd. with illegible scribe marks.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>										

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4542,  
TPS. 13 N., RS. 27 AND 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T13N R27E</p> <div style="text-align: center;">  </div> <p style="text-align: center;">2008</p> <p>Rebuild mound, 3 1/2 ft. diam., to top.</p> <p>Deposit original wood post alongside stainless steel post and below mound.</p> <p>From this corner a mound of stone, 4 ft. base, 3 ft. high, bears N., 12 lks. dist.</p> <hr style="width: 30%; margin: 20px auto;"/> <p>Thence S. 72°27'20" E., on line 4-1, Mineral Survey No. 4542, Boston lode, posting the boundary of the Walker River Indian Reservation with steel fence posts.</p>
4.590	<p>Intersect line 4-1, Mineral Survey No. 4542, Mohawk lode and point for a closing corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;">  </div> <p style="text-align: center;">2008</p> <p>Discontinue posting east of this intersection.</p> <p>From this corner, Cor. No. 1, Mineral Survey No. 4542, Mohawk lode, hereinbefore described, bears N. 5°10'10" E., 0.197 chs. dist.</p>
7.754	<p>Intersect the line between secs. 1 and 6, on the E. bdy. of the Tp., at a point from which the cor. of secs. 1, 6, 7 and 12, hereinbefore described, bears S. 0°05'30" E., 0.455 chs. dist.</p>
8.911	<p>Cor. No. 1, Mineral Survey No. 4542, Boston lode, monumented with a wood post, 4 ins. square, 2 1/2 ft. long, firmly set, projecting 2 ft. above ground, mkd. 1 4542 B on SW. face, with a mound of earth and stone 3 ft. base, 1 ft. high, E. of cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4542,  
TPS. 13 N., RS. 27 AND 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS							
	<div data-bbox="824 289 1047 451"> </div> <p data-bbox="933 472 998 493">2009</p> <p data-bbox="446 525 1437 556">Rebuild mound around stainless steel post, 3 ft. base, to top.</p> <p data-bbox="446 577 1437 630">Deposit original wood post alongside stainless steel post and below mound.</p> <hr/> <p data-bbox="568 682 1356 745">SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 13 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p data-bbox="446 798 1323 850">From the 1/4 sec. cor. of secs. 23 and 24, hereinbefore described.</p> <p data-bbox="446 871 1031 903">S. 0°00'30" W., bet. secs. 23 and 24.</p> <p data-bbox="446 924 1307 976">Across mountainous land, through scattered pinon pine, sagebrush, cheat and bunchgrass.</p> <p data-bbox="300 1008 1193 1039">11.15 Graded dirt road, 15 lks. wide, bears E. and W.</p> <p data-bbox="300 1060 747 1092">18.20 Ravine, drains ENE.</p> <p data-bbox="300 1113 730 1144">37.90 Ravine drains ESE.</p> <p data-bbox="300 1165 1177 1197">40.000 Point for the cor. of secs. 23, 24, 25 and 26.</p> <p data-bbox="446 1218 1437 1302">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div data-bbox="876 1323 1031 1417"> <table> <tr> <td>T13N</td><td>R27E</td></tr> <tr> <td>S23</td><td>S24</td></tr> <tr> <td>S26</td><td>S25</td></tr> </table> </div> <p data-bbox="917 1438 982 1459">2008</p> <p data-bbox="446 1491 1307 1596">Land, steep mountainous. Soil, rocky loam. Vegetation, scattered pinon pine, sagebrush, cheat and bunchgrass.</p> <hr/> <p data-bbox="446 1659 1323 1711">From the 1/4 sec. cor. of secs. 24 and 25, hereinbefore described.</p> <p data-bbox="446 1732 1047 1764">S. 89°02'40" W., bet. secs. 24 and 25.</p> <p data-bbox="446 1785 1307 1837">Across mountainous land, through scattered pinon pine, sagebrush, cheat and bunchgrass.</p> <p data-bbox="300 1869 1015 1900">11.70 Saddle on ridge, bears NNW. and SSE.</p> <p data-bbox="300 1921 722 1953">30.30 Ravine, drains NE.</p>	T13N	R27E	S23	S24	S26	S25
T13N	R27E						
S23	S24						
S26	S25						

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
31.90	Graded dirt road, 15 lks. wide, bears N. and S. 10° E.
39.972	The cor. of secs. 23, 24, 25 and 26.  Land, steep mountainous. Soil, rocky loam. Vegetation, scattered pinon pine, sagebrush, cheat and bunchgrass.
	<hr/>
	S. 0°00'30" W., bet. secs. 25 and 26.  Across mountainous land, through scattered pinon pine, sagebrush, cheat and bunchgrass.
40.000	Point for the 1/4 sec. cor. of secs. 25 and 26.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.  <div style="text-align: center;"> T13N R27E  1/4  S26 S25    2008 </div>
	Corner is located in the center of a steep draw, 1 ch. wide, drains E.  Begin posting the boundary of the Walker River Indian Reservation with steel sign posts.
54.60	Four-wheel drive trail, 15 lks. wide, bears N. 60° E. and S. 60° W.
60.80	Ravine, drains NE.
80.000	Point for the cor. of secs. 25, 26, 35 and 36.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.  <div style="text-align: center;"> T13N R27E  S26 S25  <hr/> S35 S36    2008 </div>
	from which  A chiseled X followed by the letters BO, bears S. 65°51' E., 33.5 lks. dist., mkd. on the top of an igneous boulder, 2x2x2 ft. high.  A chiseled X followed by the letters BO, bears S. 11°03' W., 51.1 lks. dist., mkd. on the top of an igneous boulder, 4x3x2 ft. high.



SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Land, steep mountainous. Soil, rocky loam. Vegetation, scattered pinon pine, sagebrush, cheat and bunchgrass.</p> <hr/> <p>East, bet. secs. 25 and 36.</p> <p>Across mountainous land, through pinon pine, sagebrush, cheat and bunchgrass, posting the boundary of the Walker River Indian Reservation with steel sign posts.</p>
12.10	Top of left lateral moraine, bears NE., enter flat.
15.80	Graded dirt road, 15 lks. wide, bears N. 60° E. and S. 70° W., ascend from flat.
21.10	Foot trail, 2 ft. wide, bears NW. and SE.
21.50	Top of easterly lateral moraine, bears NNW.
28.70	Graded dirt road, 15 lks. wide, bears N. 70° W. and S. 70° E.
40.000	<p>Point for the 1/4 sec. cor. of secs. 25 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13N R27E</p> <p>S25</p> <p>1/4 <u>        </u></p> <p>S36</p> <p>2008</p> </div> <p>from which</p> <p style="padding-left: 40px;">A chiseled X followed by the letters BO, bears S. 40°56' W., 68.2 lks. dist., mkd. on the top of an igneous outcrop, 10x5x4 ft. high.</p> <p style="padding-left: 40px;">A chiseled X followed by the letters BO, bears N. 47°52' W., 43.6 lks. dist., mkd. on the top of an igneous boulder, 2x1 1/2x1 ft. high.</p> <p>Discontinue posting east of this cor.</p>
45.20	Graded dirt road, 15 lks. wide, bears N. 20° W. and S. 10° E.
54.51	From this point, a mound of stone, 5 ft. base, 1 1/2 ft. high, with the broken remains of a wood post, 4x4x12 ins. long, mkd. IR 4206, bears S., 1.19 chs. dist.
55.30	Crest of divide, bears N. and S.
79.970	<p>Intersect the W. bdy. of sec. 31, T. 13 N., R. 28 E.</p> <p>Point for the closing cor. of secs. 25 and 36</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

T13N	T13N
R27E	R28E
C S25	S31
C S36	

2008

from which

A chiseled X above the letters BO, bears S. 4°02' E.,  
62.1 lks. dist., mkd. near the top of the N. face of  
an igneous outcrop, 10x6x9 ft. high.

From this point, the cor. of secs. 30 and 31, T. 13 N.,  
R. 28 E., hereinbefore described, bears N. 0°59'00" E., 1.076  
chs. dist.

Land, steep mountainous.

Soil, rocky loam.

Vegetation, pinon pine, sagebrush, cheat and bunchgrass.

The point for the 1/4 sec. cor. of sec. 25 only, T. 13 N.,  
R. 27 E., is at 40 chs. in latitude from the closing cor. of  
secs. 25 and 36, and on the E. bdy. of sec. 25.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,  
20 ins. in the ground, over a plastic-encased magnet, and in a  
mound of stone, 3 ft. base, to top, with brass cap mkd.

T13N	
1/4	
R27E	R28E
1/4 S25	

2008

From this point, the 1/4 sec. cor. of sec. 30, T. 13 N.,  
R. 28 E., hereinbefore described, bears N. 0°00'50" W., 0.836  
chs. dist.

The point for the 1/4 sec. cor. of sec. 36 only, T. 13 N.,  
R. 27 E., is at 40 chs. in latitude from the closing cor. of  
secs. 25 and 36, and on the E. bdy. of sec. 36.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,  
18 ins. in the ground, over a plastic-encased magnet, and in a  
mound of stone, 3 ft. base, to top, with brass cap mkd.

T13N	
1/4	
R27E	R28E
1/4 S36	

2008

From this point, the 1/4 sec. cor. of sec. 31, T. 13 N.,  
R. 28 E., hereinbefore described, bears N. 0°57'40" W., 1.290  
chs. dist.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>S. 0°02'40" E., bet. secs. 35 and 36.</p> <p>Across mountainous land, through pinon pine, sagebrush, cheat and bunchgrass.</p>
3.80	Graded dirt road, 15 lks. wide, bears N. 80° E. and S. 80° W.
11.90	Spur, slopes NW.
36.00	Top, ascent of NW. slope, Black Mountain.
40.000	<p>Point for the 1/4 sec. cor. of secs. 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T13N R27E 1/4 S35 S36  2008</p>
42.70	Graded dirt road, 15 lks. wide, bears W. and SSE.
77.334	<p>The cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., hereinbefore described.</p> <p>Land, steep mountainous. Soil, rocky loam. Vegetation, pinon pine, sagebrush, cheat and bunchgrass.</p> <hr/> <p>The point for the 1/4 sec. cor. of sec. 36 only, T. 13 N., R. 27 E., is at 40 chs. in departure from the cor. of secs. 1, 2, 35 and 36, and on the S. bdy. of sec. 36.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, in a 3/4-in. drill hole, on top of an igneous boulder 4x2x3 ft. high, mkd.</p> <p style="text-align: center;">T13N R27E 1/4 S36 T12N R27E  2008</p> <p>from which</p> <p style="margin-left: 40px;">A chiseled X followed by the letters BO, bears N. 24°16' E., 42.0 lks. dist., mkd. on the top of an igneous rock face, 2x2 ft., embedded in talus.</p> <p style="margin-left: 40px;">A chiseled X followed by the letters BO, bears N. 44°43' W., 80.3 lks. dist., mkd. on the top of an igneous outcrop, 9x4x7 ft. high.</p>

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From this point, U.S.G.S. station "BLACK", located on the summit of Black Mountain, bears N. 1°13'00" E., 28.714 chs. dist., monumented with a U.S.G.S. standard brass disk, 4 ins. diam., mkd. BLACK 1963, set in cement and at the surface of the ground, encircled with a mound of stone, 3 ft. base, 1 1/2 ft. high.</p> <hr/> <p>From the cor. of secs. 10, 11, 14 and 15, hereinbefore described.</p> <p>S. 0°00'10" E., bet. secs. 14 and 15.</p> <p>Along the toe of slope of E. facing mountain peaks.</p>
40.000	<p>Point for the 1/4 sec. cor. of secs. 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13N R27E 1/4 S15 S14</p> <p>2008</p> </div>
40.70	Ravine, drains ESE.
71.30	Ravine, parallels dirt road.
73.40	Graded dirt road, 15 lks. wide, bears N. 40° E. and S. 40° W.
80.000	<p>Point for the cor. of secs. 14, 15, 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13N R27E S15 S14 S22 S23</p> <p>2008</p> </div> <p>Land, rolling. Soil, rocky loam. Vegetation, sagebrush, shadscale, cheat and bunchgrass.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 14 and 23, hereinbefore described.</p> <p>N. 89°19'00" W., bet. secs. 14 and 23.</p> <p>Across mountainous terrain, through sagebrush, shadscale, cheat and bunch grass.</p>
40.122	The cor. of secs. 14, 15, 22 and 23.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Land, steep mountainous. Soil, rocky loam. Vegetation, sagebrush, shadscale, cheat and bunchgrass.</p> <hr/> <p>S. 0°00'10" E., bet. secs. 22 and 23.</p> <p>Along base of W. slope of mountains, through sagebrush, shadscale, cheat and bunch grass.</p> <p>7.90 Graded dirt road, 15 lks. wide, bears N. 50° W. and S. 50° E.</p> <p>27.00 Graded dirt road, 15 lks. wide, bears N. 70° W. and S. 70° E.</p> <p>34.80 Graded dirt road, 15 lks. wide, bears E. and W.</p> <p>40.000 Point for the 1/4 sec. cor. of secs. 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13N R27E 1/4 S22 S23</p> <p>2008</p> </div> <p>51.95 Graded dirt road, 15 lks. wide, bears N. 30° W. and S. 20° E.</p> <p>63.35 Graded dirt road, 15 lks. wide, bears N. 70° E. and S. 60° W.</p> <p>75.80 Ravine, drains WSW.</p> <p>80.000 Point for the cor. of secs. 22, 23, 26 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13N R27E S22 S23 S27 S26</p> <p>2008</p> </div> <p>Land, broken hills. Soil, rocky loam. Vegetation, sagebrush, shadscale, cheat and bunchgrass.</p> <hr/> <p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>N. 89°43'50" W., bet. secs. 23 and 26.</p> <p>Across mountainous land, through scattered pinon pine, sagebrush cheat and bunchgrass.</p> <p>15.20 Spur, slopes NE.</p> <p>40.655 Point for the 1/4 sec. cor. of secs. 23 and 26, at 40 chs. distance from the cor. of secs. 22, 23, 26 and 27.</p>
--------	---

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T13N R27E S23 1/4 <u>      </u> S26</p> <p style="text-align: center;">2008</p> <p>Corner is located at the head of a ravine, drains NE., soon E.</p> <p>From this corner, Cor. No. 4, Mineral Survey No. 4526, Mountain View lode, hereinbefore described, bears N. 0°38'40" W., 18.709 chs. dist.</p>
44.40	Single track trail, bears N. 20° W. and S. 20° E.
44.80	Crest of divide, bears NNW. and SSE.
80.655	<p>The cor. of secs. 22, 23, 26 and 27.</p> <p>Land, steep mountainous. Soil, rocky loam. Vegetation, scattered pinon pine, sagebrush, cheat and bunchgrass.</p> <hr/> <p>S. 0°00'10" E., bet. secs. 26 and 27.</p> <p>Along base of W. slope of mountains, through sagebrush, shadscale, cheat and bunch grass.</p>
2.60	Ravine, drains WNW.
5.00	Ravine, drains NW.
40.000	<p>Point for the 1/4 sec. cor. of secs. 26 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T13N R27E 1/4 S27 S26</p> <p style="text-align: center;">2008</p>
46.10	Ravine, drains WNW.
46.65	Graded dirt road, 15 lks. wide, bears N. 70° W. and S. 60° E.
55.70	Graded dirt road, 15 lks. wide, bears N. 30° E. and S. 30° W.
80.000	<p>Point for the cor. of secs. 26, 27, 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<div style="text-align: center;">           T13N R27E            S27 S26            S34 S35              2008         </div> <p>Corner is located 20 lks. N. of a ravine, drains NW.</p> <p>Land, broken hills. Soil, rocky loam. Vegetation, sagebrush, shadscale, cheat and bunchgrass.</p> <hr/> <p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>N. 89°43'50" W., bet. secs. 26 and 35.</p> <p>Across mountainous land, through pinon pine, sagebrush, cheat and bunchgrass.</p> <p>3.80 Crest of westerly divide, bears NW. and SE.</p> <p>22.45 Graded dirt road, 15 lks. wide, bears N. 70° W. and S. 70° E.</p> <p>24.70 Ravine, drains NW.</p> <p>26.65 Graded dirt road, 15 lks. wide, bears N. 40° W. and S. 20° E.</p> <p>40.657 Point for the 1/4 sec. cor. of secs. 26 and 35, at 40.000 chs. distance from the cor. of secs. 26, 27, 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;">           T13N R27E            S26            1/4 ———            S35              2008         </div> <p>53.65 Graded dirt road, 15 lks. wide, bears N. 10° W. and S. 10° E.</p> <p>80.657 The cor. of secs. 26, 27, 34 and 35.</p> <p>Land, steep mountainous. Soil, rocky loam. Vegetation, pinon pine, sagebrush, cheat and bunchgrass.</p> <hr/> <div style="text-align: center;">           SUBDIVISION OF SECTION 1,            T. 13 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA         </div> <hr/> <p>From the 1/4 sec. cor. of secs. 1 and 12.</p> <p>N. 0°06'20" E., on the N-S center line of sec. 1.</p> <p>Across mountainous land, through sagebrush, shadscale, cheat and bunchgrass, posting the boundary of the Walker River Indian Reservation with steel sign posts.</p>

SUBDIVISION OF SECTION 1,  
T. 13 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA


CHAINS	
12.00	Base of mountain, continue descent over gentle NE. slope.
40.065	Point for the center 1/4 sec. cor. of sec. 1, at intersection with the E-W center line.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.  T13N R27E C 1/4 S 1  2008  Set a steel sign post alongside cor.  Discontinue posting north of this corner.
64.90	Dirt road, 15 lks. wide, bears N. 50° E. and S. 50° W.
77.90	Powerline, wood poles, bears N. 55° W. and S. 55° E.
80.178	The 1/4 sec. cor. of secs. 1 and 36, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., set flush with the top of a mound of stone, 3 ft. base, 1/2 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 14 N., R. 27 E., executed under Group No. 837.  <hr/> From the 1/4 sec. cor. of secs. 1 and 6 on the E. bdy. of the Tp. S. 89°46'50" W., on the E-W center line of sec. 1.  Over rolling land, through sagebrush, shadscale, cheat and bunchgrass.
39.982	The center 1/4 sec. cor. of sec. 1.  Begin posting the boundary of the Walker River Indian Reservation with steel sign posts.
65.20	Dirt road, 15 lks. wide, bears S. 20° E. and N. 20° W.
79.88	Barbed wire fence, wood posts, bears N. and S.
80.088	The 1/4 sec. cor. of secs. 1 and 2.  <hr/> SUBDIVISION OF SECTION 23, T. 13 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA  <hr/> From the 1/4 sec. cor. of secs. 23 and 26.  N. 0°05'20" E., on the N-S center line of sec. 23.  Across mountainous terrain, through scattered pinon pine, sagebrush, cheat and bunch grass, posting the boundary of the Walker River Indian Reservation with steel sign posts.



SUBDIVISION OF SECTION 23,  
T. 13 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
24.10	Intersection of graded dirt roads, bears NE., E., SW. and NW., located in saddle on crest of divide, bears N. and S.
30.15	Graded dirt road, 15 lks. wide, bears N. 40° E. and S. 40° W.
40.000	Point for the center 1/4 sec. cor. of sec. 23, at intersection with the E-W center line.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.  T13N R27E C 1/4 S23  2008  Discontinue posting north of this cor.  From this corner, Cor. No. 1, Mineral Survey No. 4526, Mountain View lode, hereinbefore described, bears S. 21°41'20" W., 13.785 chs. dist.
40.80	Graded dirt road, 15 lks. wide, bears N. 35° W. and S. 35° E.
47.30	Crest of divide, bears NNW. and SSE.
48.40	Graded dirt road, 15 lks. wide, bears N. 60° W. and S. 50° E.
79.706	The 1/4 sec. cor. of secs. 14 and 23. <hr/> From the 1/4 sec. cor. of secs. 23 and 24.  N. 89°44'00" W., on the E-W center line of sec. 23.  Across mountainous terrain, through scattered pinon pine, sagebrush, cheat and bunch grass, posting the boundary of the Walker River Indian Reservation with steel sign posts.
21.50	Ravine, drains NE.
36.00	Crest of divide, bears NNW. and S.
40.10	Graded dirt road, 15 lks. wide, bears N. 35° W. and S. 35° E.
40.595	The center 1/4 sec. cor. of sec. 23.  Discontinue posting west of this cor.
49.00	Graded dirt road, 15 lks. wide, bears N. 35° W. and S. 35° E.
57.50	Intersection of graded dirt roads, 15 lks. wide, bears NNW., ESE. and SSE.
65.75	Graded dirt road, 15 lks. wide, bears N. 60° W. and S. 60° E.
80.654	The 1/4 sec. cor. of secs. 22 and 23. <hr/>

SUBDIVISION OF SECTION 24,  
T. 13 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the 1/4 sec. cor. of secs. 24 and 25.</p> <p>N. 0°10'10" W., on the N-S center line of sec. 24.</p> <p>Across mountainous terrain, through scattered pinon pine, sagebrush, cheat and bunchgrass.</p>
36.60	Spur, slopes NE.
39.558	<p>Point for the center 1/4 sec. cor. of sec. 24, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T13N R27E C 1/4 S24</p> <p style="text-align: center;">2008</p> <p>Set a steel sign post alongside cor.</p> <p>Begin posting the boundary of the Walker River Indian Reservation with steel sign posts.</p>
44.80	Graded dirt road, 15 lks. wide, bears N. 60° E. and S. 60° W., leave pinon pines.
57.90	Saddle on spur, bears NE. and SW.
65.20	Ravine, drains NE.
69.30	Ridge, bears NE. and SW.
74.604	<p>Intersect line 4-1, Mineral Survey No. 4344, Golden Fleece lode, and point for a closing cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a mound of stone, 3 ft. base, to top, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>MS 4344 G F</p>  <p style="text-align: center;">2008</p> </div> <p>Discontinue posting north of this cor.</p> <p>From this corner, Cor. No. 1, Mineral Survey No. 4344, Golden Fleece lode, hereinbefore described, bears S. 27°22'30" W., 1.215 chs. dist.</p>
76.70	Single track trail, 5 lks. wide, bears NNE. and SSW., in bottom of ravine, drains NE.

SUBDIVISION OF SECTION 24,  
T. 13 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
79.490	The 1/4 sec. cor. of secs. 13 and 24.
	<hr/> <p>From the 1/4 sec. cor. of secs. 19 and 24, on the E. bdy. of the Tp.</p> <p>S. 89°41'00" W., on the E-W center line of sec. 24.</p> <p>Across mountainous terrain, through sagebrush, cheat and bunch grass.</p>
32.30	Ravine, drains NE.
40.084	The center 1/4 sec. cor. of sec. 24.
	<p>Begin posting the boundary of the Walker River Indian Reservation with steel sign posts.</p>
48.90	Graded dirt road, 15 lks. wide, bears NE. and SW., in center of ravine, drains NE.
79.925	The 1/4 sec. cor. of secs. 23 and 24.
	<hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 26, T. 13 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 26 and 35.</p> <p>N. 0°00'10" E., on the N-S center line of sec. 26.</p> <p>Across mountainous terrain, through scattered pinon pine, sagebrush, cheat and bunchgrass.</p>
4.80	Graded dirt road, 15 lks. wide, bears E. and W.
5.00	Ravine, drains NW.
40.000	Point for the center 1/4 sec. cor. of sec. 26, at intersection with the E-W center line.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T13N R27E C 1/4 S26</p>
	<p style="text-align: center;">2008</p>
	from which
	<p>A chiseled X followed by the letters BO, bears N. 78°31' E., 106.9 lks. dist., mkd. on the top of a igneous outcrop, 15x10x7 ft. high.</p>
	<p>A chiseled X followed by the letters BO, bears S. 60°48' E., 64.1 lks. dist., mkd. on the top of an igneous boulder 2x1 1/2x1 ft. high.</p>

SUBDIVISION OF SECTION 26,  
T. 13 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Begin posting the boundary of the Walker River Indian Reservation with steel sign posts.
74.60	Single track trail running along with top of crest of divide, bears N. 50° W. and S. 50° E.
80.000	The 1/4 sec. cor. of secs. 23 and 26.
	From the 1/4 sec. cor. of secs. 25 and 26.
	N. 89°43'50" W., on the E-W center line of sec. 26.
	Across mountainous terrain, through scattered pinon pine, sagebrush, cheat and bunchgrass, posting the boundary of the Walker River Indian Reservation with steel sign posts.
27.00	Four-wheel drive road, 15 lks. wide, bears S. 30° E. and N. 10° W. and crest of divide, bears NW. and SSE.
40.656	The center 1/4 sec. cor. of sec. 26.
	Discontinue posting west of this cor.
80.656	The 1/4 sec. cor. of secs. 26 and 27.
	SUBDIVISION OF SECTION 36, T. 13 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA
	From the 1/4 sec. cor. of secs. 25 and 36.
	S. 0°02'20" E., on the N-S center line of sec. 36.
	Across mountainous terrain, through pinon pines, scattered junipers, sagebrush, cheat and bunchgrass, posting the boundary of the Walker River Indian Reservation with steel sign posts.
4.05	Graded dirt road, 15 lks. wide, bears NNW. and SSE.
7.20	Intersection of graded dirt roads, bears N., SE., S. and NW.
13.90	Graded dirt road, 15 lks. wide, bears NNW. and SSE.
50.00	Summit of Black Mountain, bears SE. and NW.
78.519	The 1/4 sec. cor. of sec. 36 only, on the S. bdy. of the Tp.

## TOWNSHIP 13 NORTH, RANGE 27 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	GENERAL DESCRIPTION
	<p>The area encompassed in this survey is mostly mountainous, the high point being Black Mountain with an approximate elevation of 8100 feet above sea level in section 36, descending to the low point of approximately 4400 feet above sea level at the corner of Townships 13 and 14 North, Ranges 27 and 28 East. Two main spur ridges running from the N. slope of Black Mountain form two main divides of the Wassuck Mountains north of Black Mountain, creating a narrow central valley draining the north slope of Black Mountain, the easterly spur runs approximately two miles to the N. and the westerly spur runs approximately three miles to the NNW. Sections 1 and 12 are separated by a lower set of rugged igneous mountains with an approximate elevation of 5400 ft. above sea level.</p> <p>Vegetation consists of pinon pine in the upper elevations and on the northerly slopes with some sparse juniper on the summit of Black Mountain, with sagebrush transitioning to shadscale at the lower elevations. Grasses are bunchgrass throughout with cheat grass invading the E. and W. slopes, being somewhat limited on the upper N. slopes.</p> <p>Evidence of mining activity and abandoned mining claims exist throughout the lands surveyed with most access being on roads apparently created for those activities.</p> <p>The soil consists of loam deposits generated from the many igneous formations throughout the surveyed area, the summit of Black Mountain being capped with basalt.</p> <p>The surveyed area is located approximately 6 miles west of the town of Schurz, Nevada, traveling on U.S. Alternate Highway No. 95 towards the town of Yerington, Nevada.</p> <hr/>

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Don R. Aschenbach	Cadastral Surveyor
Steven E. Dagitz	Land Surveyor (Student Trainee)
Phillip D. Van Buren	Surveying Technician
Michelle E. Martin	Supervisory Range Technician
Derrick J. Rader	Supervisory Range Technician
Mathew J. White	Lead Range Technician

## CERTIFICATE OF SURVEY

We, David J. Clark, Cadastral Surveyor, and Mark G. Petrosine, Surveying Technician, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 16th day of August, 2007, and Supplemental Special Instructions bearing date of the 26th day of March, 2009, we have dependently resurveyed a portion of the north boundary of Township 12 North, Range 27 East; the west boundary of Township 13 North, Range 28 East; a portion of the subdivisional lines of Township 13 North, Range 27 East; and portions of certain Mineral Surveys in Townships 13 North, Ranges 27 and 28 East; and, surveyed a portion of the subdivisional lines, and subdivided certain sections, Township 13 North, Range 27 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special and supplemental special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

July 13, 2009

(Date)

David J. Clark

(Cadastral Surveyor)

July 8, 2009

(Date)

Mark G. Petrosine

(Surveying Technician)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Reno, Nevada

The foregoing field notes of the dependent resurvey of a portion of the north boundary of Township 12 North, Range 27 East; the west boundary of Township 13 North, Range 28 East; a portion of the subdivisional lines of Township 13 North, Range 27 East; and portions of certain Mineral Surveys in Townships 13 North, Ranges 27 and 28 East; and, the survey of a portion of the subdivisional lines, and the subdivision of certain sections, Township 13 North, Range 27 East, Mount Diablo Meridian, Nevada, executed by David J. Clark, Cadastral Surveyor, and Mark G. Petrosine, Surveying Technician, having been critically examined and found correct, are hereby approved.

July 14, 2009

(Date)

David D. Morlan

(Chief Cadastral Surveyor, Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above described surveys in T. 13 N., R. 27 E., Mount Diablo Meridian, Nevada, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor, Nevada)~~