

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

PORTIONS OF THE SOUTH, EAST AND NORTH BOUNDARIES,

A PORTION OF THE SUBDIVISIONAL LINES,

PORTIONS OF THE SUBDIVISION-OF-SECTION LINES

OF CERTAIN SECTIONS,

INDIAN ALLOTMENT NO. 108,

A PORTION OF INDIAN ALLOTMENT NO. 493,

AND A PORTION OF MINERAL SURVEY NO. 4542,

THE SUBDIVISION OF CERTAIN SECTIONS,

AND THE FURTHER SUBDIVISION OF CERTAIN SECTIONS,

TOWNSHIP 13 NORTH, RANGE 28 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATE OF NEVADA

EXECUTED BY

Lance A. Barney, Cadastral Surveyor

Mark G. Petrosine, Surveying Technician

Under Special Instructions dated July 7, 2009,

and approved July 7, 2009,

which provided for the surveys included under Group No. 878,

and Assignment Instructions dated July 7, 2009.

Survey commenced July 8, 2009

Survey completed November 30, 2010

INDEX DIAGRAM

TOWNSHIP 13 NORTH, RANGE 28 EAST, MOUNT DIABLO MERIDIAN, NEVADA

12		12	11	10	9
6	5	46 4	40 3	31 2	23 1
57		45	40	30	22
7	8	9	38 10	30 11	22 12
56	57 56	44	36	29	21
18	55 17	16	35 15	28 14	20 13
54	54		34 33	27	19
19	53 20	21	32 22	26 23	18 24
52	52	44 44		25 23	17
30	50 29	43 28	27	26	16 25
49	49	42			13
31	48 32	41 33	31 34	35	36
6	5	4	3		8 2

- Continued on Next Page -

Dep. Resurvey of the Subdivision-of-Section Lines of Sec. 21 ..	pp. 58-60
Dep. Resurvey of the Subdivision-of-Section Lines of Sec. 22 ..	pp. 60-64
Dep. Resurvey of the Subdivision-of-Section Lines of Sec. 26 ..	pp. 64-65
Dep. Resurvey of the Subdivision-of-Section Lines of Sec. 27 ..	pp. 65-68
Dep. Resurvey of the Subdivision-of-Section Lines of Sec. 36 ..	pp. 68-71
Dep. Resurvey of Indian Allotment No. 108	pp. 71-72
Dep. Resurvey of a Portion of Indian Allotment No. 493	pp. 72-73
Dep. Resurvey of a Portion of Mineral Survey No. 4542	pp. 73-74
Subdivision of Section 4	pp. 74-82
Subdivision of Section 7	p. 82
Subdivision of Section 9	pp. 83-90
Subdivision of Section 10	pp. 90-92
Subdivision of Section 14	pp. 93-96
Subdivision of Section 15	pp. 97-116
Subdivision of Section 18	pp. 116-117
Subdivision of Section 23	pp. 117-128
Subdivision of Section 25	pp. 128-134
Further Subdivision of Section 21	pp. 134-136
Further Subdivision of Section 22	pp. 136-152
Further Subdivision of Section 26	pp. 152-160
Further Subdivision of Section 27	pp. 160-163
Further Subdivision of Section 35	pp. 163-166
Further Subdivision of Section 36	pp. 166-172

TOWNSHIP 13 NORTH, RANGE 28 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The following field notes are those of the dependent resurvey of portions of the south, east and north boundaries, a portion of the subdivisional lines, portions of the subdivision-of-section lines of certain sections, Indian Allotment No. 108, a portion of Indian Allotment No. 493, and a portion of Mineral Survey No. 4542, the subdivision of certain sections, and the further subdivision of certain sections, Township 13 North, Range 28 East, Mount Diablo Meridian, Nevada.

The south, east, west and north boundaries and the subdivisional lines surveyed by U.S. Deputy Surveyors H.E. Franks and J.S. Mullen in 1904 under Contract No. 237. Portions of the south and east boundaries, and a portion of the subdivisional lines were dependently resurveyed and Allotment Nos. 106, 108 and 493 and the Allotment for the Methodist Episcopal Church were surveyed by U.S. Cadastral Engineer E. Voight in 1922 under Group No. 66. Mineral Survey No. 4542, Mohawk and Boston Lodes, were surveyed by U.S. Mineral Surveyor R.M. Stewart in 1922. A portion of the east boundary was dependently resurveyed by U.S. Cadastral Engineer C.S. Swanholm in 1936 under Group No. 181. Portions of the south and east boundaries, a portion of the subdivisional lines, Allotment No. 493 in section 26 and Allotment No. 106 in section 36 were dependently resurveyed and the subdivision of sections 21, 22, 26, 27 and 36 were surveyed by Cadastral Surveyor J.A. Mack in 1986 under Group No. 635. A portion of the north and south boundaries, a portion of the subdivisional lines and a portion of the subdivision of section 35, were dependently resurveyed and the subdivision of section 8 and a portion of section 35 were surveyed by R.A. Pratt in 1989 under Group No. 670. The northwest corner of the township was perpetuated by Cadastral Surveyor D.A. Potts and Surveying Technician M.G. Petrosine in 2006-08, under Group No. 837. The west boundary and portions of Mineral Survey Nos. 3981 and 4542 were dependently resurveyed by Cadastral Surveyor D.J. Clark and Surveying Technician M.G. Petrosine in 2008-09, under Group No. 855.

Before restoring the corners, the lines of the original surveys and resurveys were retraced and a diligent search made for any evidence of the original and resurvey corners and other calls of the field note records.

The rules of proportionate measurements were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 878, dated July 7, 2009.

Measurements were made with Trimble 4700, 5700, 5800 and R8 Global Positioning System (GPS) receivers using the real-time kinematic (RTK) and static methods and refer to the true meridian based on geodetic methods. The mean bearings of the lines and horizontal equivalents of ground distances only are entered in the field notes.

TOWNSHIP 13 NORTH, RANGE 28 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>The NAD 1983 (CORS 96) geographic position of the E-E 1/64 sec. cor. of secs. 1 and 36, on the south boundary of the township, as determined from GPS static observations processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuous Operating Reference Stations (CORS) FERNLEY COOP CORS ARP, GABB GABBS CORS ARP and UPSAL HOGBACK CORS ARP, in 2009, and carried forward by RTK observations is as follows:</p> <p>Latitude: 38°56'20.368" N. Longitude: 118°47'39.491" W.</p> <p>The 1988 mean magnetic declination is 15°30' E., as shown on 7 1/2 minute U.S.G.S. quadrangle map "SCHURZ, NEVADA", provisional edition dated 1988.</p> <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY, T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of a Portion of the Survey Executed by H.E. Franks and J.S. Mullen, U.S. Deputy Surveyors, in 1905, a Portion of the Dependent Resurvey Executed by E. Voight, Cadastral Engineer, in 1922 and a Portion of the Dependent Resurvey Executed by J.A. Mack, in 1987</p> <hr/> <p>Beginning at the E-E 1/64 sec. cor. of secs. 1 and 36, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of the south boundary, T. 13 N., R. 28 E., executed under Group No. 635.</p> <p>Cor. is located in a fence, bears E. and W.</p> <p>N. 89°57'50" W., bet. secs. 1 and 36.</p> <p>Over nearly level land, covered with scattered cottonwoods, shadscale, cheat and bunch grass, along fence.</p> <p>6.2519 Point for the 1/4096 sec. cor. of secs. 1 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\frac{1}{4096}$ <p>2010</p> </div> <p>9.03 Cor. of barbed wire fences, extending E. and SW.</p> <p>9.055 Point selected for the witness E 1/16 sec. cor. of secs. 1 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
--------	---

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<div style="text-align: center;"> WC S36 E 1/16 ← S 1 2010 </div>
9.20	Left bank of the Walker River, bears NNW. and SSE., thence across river, course SSE.
9.330	Point for the 1986 witness E 1/16 sec. cor. of secs. 1 and 36, at record distance; there is no remaining evidence of the corner. This point now serves no further function.
10.003	True point for the E 1/16 sec. cor. of secs. 1 and 36, falls in river where it is impractical to establish a permanent monument.
10.50	Right bank of the Walker River, bears NNW. and SSE., thence across rolling land.
12.50	Cor. of barbed wire fences, extending W. and SSE., thence along fence.
20.006	<p>The W-E 1/64 sec. cor. of secs. 1 and 36, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of the south boundary, T. 13 N., R. 28 E., executed under Group No. 635.</p> <p>Cor. is located on the N. side of a fence cor., from which barbed wire fences extend S., E. and W.</p>
	<hr/> <p>From the cor. of secs. 2, 3, 34 and 35, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the south boundary, T. 13 N., R. 28 E., executed under Group No. 670, with a redwood post set alongside, and a scattered mound of stone W. of cor.</p> <p>Rebuild the mound of stone, 3 ft. base, 1 ft. high, W. of cor.</p> <p>N. 89°56'50" W., bet. secs. 3 and 34.</p> <p>Over nearly level land, covered with low brush, cheat and bunch grass.</p>
6.40	Ravine, drains. NE.
40.402	<p>The 1/4 sec. cor. of secs. 3 and 34, monumented with a redwood post, 4x3x36 ins. long, firmly set, projecting 14 ins. above the ground, mkd. 4 S4 on the N. side, with a stone, 5x3x1 ins., mkd. with an X, recovered below the wood post.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div data-bbox="862 264 1024 401"> <p>T13N R28E S34 1/4 — S 3 T12N</p> </div> <div data-bbox="919 422 984 449">2009</div> <div data-bbox="435 474 1398 531">Bury the mkd. stone and redwood post alongside the stainless steel post.</div> <hr/> <div data-bbox="435 590 1122 617">N. 89°56'40" W., beginning new measurement.</div> <div data-bbox="289 642 391 669">40.142</div> <div data-bbox="435 642 1430 800"> <p>The cor. of secs. 3, 4, 33 and 34, monumented with a basalt stone, 24x8x6 ins., firmly set, projecting 10 ins. above the ground, mkd. with 5 partial grooves on SE. face, 4 partial grooves on SW. face, 3 notches on E. edge and 3 notches on W. edge, with a mound of stone, 2 1/2 ft. base, 1 ft. high, N. of cor.</p> </div> <div data-bbox="435 825 740 852">At the corner point</div> <div data-bbox="435 877 1458 961"> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> </div> <div data-bbox="873 982 1024 1119"> <p>T13N R28E S33 S34 — — S 4 S 3 T12N</p> </div> <div data-bbox="919 1140 984 1167">2009</div> <div data-bbox="435 1192 1312 1220">Bury the mkd. stone alongside the stainless steel post.</div> <hr/> <div data-bbox="435 1283 1024 1310">N. 89°54'30" W., bet. secs. 4 and 33.</div> <div data-bbox="435 1335 1398 1392">Over mountainous terrain, covered with shadescale, cheat and bunch grass.</div> <div data-bbox="289 1413 375 1440">36.50</div> <div data-bbox="435 1413 1312 1440">Four-wheel drive trail, 10 lks. wide, bears NE. and SW.</div> <div data-bbox="289 1465 391 1493">39.936</div> <div data-bbox="435 1465 1458 1602"> <p>The 1/4 sec. cor. of secs. 4 and 33, determined at the base of a granite stone, 6x6x15 ins., lying on side, mkd. 1/4 on one face, with a mound of stone, 3 ft. base, 1 ft. high, N. of cor. Accepted base of stone as the best available evidence of the position of the original corner.</p> </div> <div data-bbox="435 1623 740 1650">At the corner point</div> <div data-bbox="435 1675 1425 1759"> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> </div>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div data-bbox="862 264 1024 401"> <p>T13N R28E S33 1/4 — S 4 T12N</p> </div> <div data-bbox="919 422 984 449">2009</div> <div data-bbox="436 478 1248 506">Bury mkd. stone alongside the stainless steel post.</div> <hr/> <div data-bbox="436 562 1118 590">N. 89°59'30" W., beginning new measurement.</div> <div data-bbox="290 617 1455 722"> <p>39.871 The cor. of secs. 4, 5, 32 and 33, monumented with a granite stone, 17x6x7 ins., firmly set, projecting 6 ins. above the ground, mkd. with 4 notches on E. edge and 2 notches on W. edge, with a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> </div> <div data-bbox="436 749 740 777">At the corner point</div> <div data-bbox="436 804 1455 882"> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> </div> <div data-bbox="878 909 1024 1037"> <p>T13N R28E S32 S33 —+— S 5 S 4 T12N</p> </div> <div data-bbox="911 1064 976 1092">2009</div> <div data-bbox="436 1119 1248 1146">Bury mkd. stone alongside the stainless steel post.</div> <hr/> <div data-bbox="436 1203 1021 1230">S. 89°43'10" W., bet. secs. 5 and 32.</div> <div data-bbox="436 1257 1406 1312"> <p>Over mountainous terrain, covered with scattered pinyon pine, sagebrush, cheat and bunch grass.</p> </div> <div data-bbox="290 1339 704 1367"> <p>14.20 Spur, slopes SSE.</p> </div> <div data-bbox="290 1394 1373 1472"> <p>40.064 The 1/4 sec. cor. of secs. 5 and 32, monumented with a decomposed granite stone, 4x7x19 ins., loosely set, no mks. visible, with a scattered mound of stone N. of cor.</p> </div> <div data-bbox="436 1499 740 1526">At the corner point</div> <div data-bbox="436 1554 1455 1631"> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 2 ins. in the ground to bedrock, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> </div> <div data-bbox="850 1659 1013 1787"> <p>T13N R28E S32 1/4 — S 5 T12N</p> </div> <div data-bbox="911 1814 976 1841">2009</div>
--------	---

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Bury unmkd. stone alongside the stainless steel post.
	N. 89°36'50" W., beginning new measurement.
40.046	The cor. of secs. 5, 6, 31 and 32, monumented with a granite stone, 16x8x6 ins., firmly set, projecting 5 ins. above the ground, mkd. with 5 notches on E. edge and 1 notch on W. edge, from which the remaining original bearing trees
	A pinyon pine, 15 ins. diam., bears S. 25° E., 23 lks. dist., with illegible scribe mks. on a partially healed blaze.
	A pinyon pine, 12 ins. diam., bears S. 76° W., 24 lks. dist., mkd. with a healed blaze. (Record, 19 lks.)
	A pinyon pine, 11 ins. diam., bears N. 16 1/2° W., 55 lks. dist., mkd. BT and with other illegible scribe mks. visible on a partially healed blaze. (Record, N. 15° W., 59 lks.)
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	<div style="text-align: center;"> T13N R28E S31 S32 <hr style="width: 50%; margin: 0 auto;"/> S 6 S 5 T12N 2009 </div>
	from which new bearing objects
	A chiseled X followed by the letters BO, bears N. 57°21' E., 91.1 lks. dist., mkd. on the top of a granite boulder, 6 1/2x6x2 1/2 ft. high.
	A chiseled X followed by the letters BO, bears S. 75°34' W., 24.2 lks. dist., mkd. on the top of a granite boulder, 1 1/2x1 1/2x1 ft. high.
	Bury mkd. stone alongside the stainless steel post.
	S. 89°56'50" W., bet. secs. 6 and 31.
	Over mountainous terrain, covered with pinyon pine, sagebrush, cheat and bunch grass.
40.366	The 1/4 sec. cor. of secs. 6 and 31, determined at the S. side of a mound of stone, 3 ft. base, 1 ft. high, with a granite stone, 6x8x18 ins., lying loose downhill, mkd. 1/4 on one face.
	At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd.</p> <p style="text-align: center;">T13N R28E S31 1/4 — S 6 T12N 2009</p> <p>Deposit mkd. stone alongside the stainless steel post.</p> <hr/> <p>N. 89°56'20" W., beginning new measurement.</p>
38.491	<p>The cor. of Tps. 12 and 13 N., Rs. 27 and 28 E., monumented with a stainless steel post, 2 1/2 ins. diam., set flush with a mound of stone, 3 ft. base, 1/2 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of the north boundary, T. 12 N., R. 27 E., executed under Group No. 855, from which the original bearing trees</p> <p style="padding-left: 40px;">A pinyon pine, 8 ins. diam., bears N. 42° E., 19 lks. dist., mkd. T12N R 9 S1 BT visible on partially healed blaze. (Record, N. 40° E., 80 lks.)</p> <p style="padding-left: 40px;">A down pinyon pine, 10 ins. diam. on E. fork, bears S. 36° E., 43 lks. dist., with illegible scribe mks. visible on partially healed blaze. (Record, S. 60° E., 20 lks.)</p> <p style="padding-left: 40px;">A down pinyon pine, 14 ins. diam., bears S. 68° W., 60 lks. dist., with scribe mks. T12R N9E BT visible on weathered blaze. (Record, S. 50° W., 70 lks.)</p> <p style="padding-left: 40px;">A dead standing pinyon pine, 10 ins. diam., bears N. 37 1/4° W., 39 1/2 lks. dist., with illegible scribe mks. visible on upper blaze and T13N R27E on lower blaze. (Record, N. 4° W., 45 lks.)</p> <p>and the 2008 bearing objects</p> <p style="padding-left: 40px;">A chiseled X followed by the letters BO, bears S. 66°52' E., 158.7 lks. dist., mkd. on the top of a granite boulder, 2x2x1 ft. high.</p> <p style="padding-left: 40px;">A chiseled X followed by the letters BO, bears S. 62°54' W., 90.8 lks. dist., mkd. on the top of an igneous outcrop, 4x2x2 1/2 ft. high.</p> <p style="padding-left: 40px;">A chiseled X followed by the letters BO, bears N. 12°22' W., 90.4 lks. dist., mkd. on the top of a granite boulder, 2x1 1/2x1 ft. high.</p> <hr/>

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Reestablishment of a Portion of the Survey Executed by H.E. Franks and J.S. Mullen, U.S. Deputy Surveyors, in 1904 and a Portion of the Dependent Resurvey Executed by E. Voigt, Cadastral Engineer, in 1922</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 31 and 36, monumented with an iron post, 2 1/2 ins. diam., recovered 6 ins. below the surface of the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the east boundary, T. 13 N., R. 28 E., executed under Group No. 635.</p> <p>N. 0°03'20" W., bet. secs. 31 and 36.</p> <p>Across cultivated land, and along fence.</p>
0.10	Cor. of barbed wire fences, extending N., S. and W.
12.323	<p>An unrecorded rebar, 5/8 in. diam., projecting 4 ins. above ground, with plastic cap mkd. PLS 9607.</p> <p>Cor. is located at N. end of fence, extends S.</p>
12.60	Concrete lined irrigation ditch, 20 lks. wide, drains S. 45° E.
13.20	<p>Heart Falls Road, asphalt surfaced, 38 lks. wide, parallels irrigation ditch.</p> <p>Thence across rolling land, covered with shadscale, cheat and bunch grass.</p>
13.794	An unrecorded rebar, 5/8 in. diam., projecting 1 in. above the ground, with plastic cap mkd. PLS 9607.
19.947	<p>Point for the N 1/16 sec. cor. of secs. 31 and 36, falls on NW. side of wood post, 6x8 ins., projecting 6 ft. above ground, with the remains of a redwood post, 3 ins. square lying loose alongside, the original position indeterminate.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S36 S31 2010</p>
21.60	Double Springs road, improved dirt surface, 50 lks. wide, bears N. 85° E. and S. 85° W.
39.894	<p>The cor. of secs. 25, 30, 31 and 36, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 13 N., R. 28 E., executed under Group No. 66.</p> <hr/>

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Restoring a Portion of the Survey Executed by H.E. Franks and J.S. Mullen, U.S. Deputy Surveyors, in 1904, a Portion of the Resurvey Executed by C.S. Swanholm, Cadastral Engineer and R.F. Guinn, C. Pettengill and H. Westfall, Transitmen, P.W., in 1936 and a Portion of the Resurvey Executed by R.A. Pratt, Cadastral Surveyor, in 1989</p> <hr/> <p>From the cor. of Tps. 13 and 14 N., Rs. 28 and 29 E., monumented with a granite stone, 15x15 ins., firmly set, projecting 16 ins. above the ground, mkd. with 6 notches on the N., E., S. and W. edges, with an iron post, 3 ins. diam., firmly set E. of cor., projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the west boundary, T. 13 N., R. 29 E., executed under Group No. 181, and a mound of stone, 3 ft. base, 2 1/2 ft. high, S. of cor.</p> <p>At the corner point</p> <p>Chisel an X on the top of the mkd. stone and invert the iron post alongside.</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 45°26' E., 22.7 lks. dist., with brass cap mkd. RM T13N R29E S6 15.0 FT TO COR 2010 and an arrow pointing to the cor.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 44°37' W., 22.9 lks. dist., with brass cap mkd. RM T13N R28E S1 15.1 FT TO COR 2010 and an arrow pointing to the cor.</p> <p>N. 89°49'30" W., bet. secs. 1 and 36.</p> <p>Across rolling land, covered with shadescale, cheat and bunch grass.</p> <p>34.00 U.S. Highway No. 95, asphalt surfaced, 50 lks. wide, bears N. 7° E. and S. 7° W.</p> <p>40.088 The 1/4 sec. cor. of secs. 1 and 36, monumented with a redwood post, 4 ins. square, 36 ins. long, loosely set, projecting 24 ins. above the ground, with illegible scribe mks. visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
--------	---

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div data-bbox="857 262 1019 394" data-label="Text"> <p>T14N R28E S36 1/4 — S 1 T13N</p> </div> <div data-bbox="911 422 976 447" data-label="Text"> <p>2009</p> </div> <div data-bbox="436 474 1281 501" data-label="Text"> <p>Bury redwood post alongside the stainless steel post.</p> </div> <hr/> <div data-bbox="436 560 1122 588" data-label="Text"> <p>S. 89°58'40" W., beginning new measurement.</p> </div> <div data-bbox="289 615 1409 693" data-label="Text"> <p>40.057 The cor. of secs. 1, 2, 35 and 36, monumented with a redwood post, 4 ins. square, 30 ins. long, loosely set, projecting 24 ins. above the ground, with illegible scribe mks. visible.</p> </div> <div data-bbox="436 720 742 747" data-label="Text"> <p>At the corner point</p> </div> <div data-bbox="436 772 1458 850" data-label="Text"> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> </div> <div data-bbox="878 877 1024 1010" data-label="Text"> <p>T14N R28E S35 S36 —+— S 2 S 1 T13N</p> </div> <div data-bbox="919 1037 984 1062" data-label="Text"> <p>2009</p> </div> <div data-bbox="436 1089 1281 1117" data-label="Text"> <p>Bury redwood post alongside the stainless steel post.</p> </div> <hr/> <div data-bbox="436 1176 1024 1203" data-label="Text"> <p>N. 89°54'00" W., bet. secs. 2 and 35.</p> </div> <div data-bbox="436 1230 1409 1283" data-label="Text"> <p>Across rolling land, covered with shadescale, cheat and bunch grass.</p> </div> <div data-bbox="289 1310 846 1337" data-label="Text"> <p>3.90 Low ridge, bears N. and S.</p> </div> <div data-bbox="289 1362 735 1390" data-label="Text"> <p>12.80 Ravine, drains SSW.</p> </div> <div data-bbox="289 1415 1458 1547" data-label="Text"> <p>39.965 The 1/4 sec. cor. of secs. 2 and 35, perpetuated with an unrecorded iron post, 1 in. diam., firmly set, projecting 8 ins. above the ground, with the remains of a wood post, 4 ins. square, 14 ins. long, lying loose alongside, with a General Land Office regulation brass cap mkd.</p> </div> <div data-bbox="867 1575 1024 1732" data-label="Text"> <p>T14N R28E S35 1/4 — S 2 1937</p> </div> <hr/>
--------	---

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 89°49'40" W., beginning new measurement.																														
40.034	<p>The cor. of secs. 2, 3, 34 and 35, perpetuated with an unrecorded iron pipe, 2 ins. diam., firmly set, projecting 8 ins. above the ground, with the remains of a wood post, 4 ins. square, 24 ins. long, lying loose alongside, with a General Land Office regulation brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td>T14N</td><td>R28E</td></tr> <tr><td>S34</td><td>S35</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 3</td><td>S 2</td></tr> <tr><td colspan="2">T13N</td></tr> </table> <p>1937</p> </div> <hr/> <p>S. 89°55'50" W., bet. secs. 3 and 34.</p> <p>Across rolling land, covered with shadescale, cheat and bunch grass.</p> <p>40.088 Point for the 1/4 cor. of secs. 3 and 34, at proportionate dist.; there is no remaining evidence of the position of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td>T14N</td><td>R28E</td></tr> <tr><td>S34</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 3</td><td></td></tr> <tr><td colspan="2">T13N</td></tr> </table> <p>2009</p> </div> <p>80.176 The cor. of secs. 3, 4, 33 and 34, monumented with a redwood post, 4 ins. square, loosely set, projecting 24 ins. above the ground, with illegible scribe mks. visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td>T14N</td><td>R28E</td></tr> <tr><td>S33</td><td>S34</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 4</td><td>S 3</td></tr> <tr><td colspan="2">T13N</td></tr> </table> <p>2009</p> </div> <p>Bury redwood post alongside the stainless steel post.</p> <hr/>	T14N	R28E	S34	S35	<hr/>		S 3	S 2	T13N		T14N	R28E	S34		1/4	—	S 3		T13N		T14N	R28E	S33	S34	<hr/>		S 4	S 3	T13N	
T14N	R28E																														
S34	S35																														
<hr/>																															
S 3	S 2																														
T13N																															
T14N	R28E																														
S34																															
1/4	—																														
S 3																															
T13N																															
T14N	R28E																														
S33	S34																														
<hr/>																															
S 4	S 3																														
T13N																															

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 89°49'00" W., bet. secs. 4 and 33.
	Across rolling land, covered with shadescale, cheat and bunch grass.
14.50	Graded dirt road, 40 lks. wide, bears N. 10° W. and S. 10° E.
40.000	The 1/4 sec. cor. of secs. 4 and 33, monumented with a redwood post, 4 ins. square, loosely set, projecting 20 ins. above the ground, with illegible scribe mks. visible.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<div style="text-align: center;"> T14N R28E S33 1/4 — S 4 T13N 2009 </div>
	Bury redwood post alongside the stainless steel post.
	<hr/>
	N. 89°50'20" W., beginning new measurement.
10.086	Point for the E-W 1/64 sec. cor. of secs. 4 and 33.
	POINT NOT MONUMENTED
18.00	Rim, bears N. and S., descend into river canyon.
20.172	Point for the W 1/16 sec. cor. of secs. 4 and 33.
	POINT NOT MONUMENTED
24.00	Left bank, Walker River, bears NNE. and SSW., thence across river, course SSW.
24.20	Right bank, Walker River, bears NNE. and SSW.
35.70	Graded dirt road, 25 lks. wide, bears N. and SSE.
40.344	The cor. of secs. 4, 5, 32 and 33, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the north boundary, T. 13 N., R. 28 E., executed under Group No. 670.
	<hr/>
	From the cor. of secs. 5, 6, 31 and 32, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above the ground, the remains of a cottonwood post, 4 ins. square, 12 ins. long, no mks. visible, lying loose alongside, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the north boundary, T. 13 N., R. 28 E., executed under Group No. 670.

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	S. 89°58'40" W., bet. secs. 6 and 31. Across rolling land, covered with shadescale, cheat and bunch grass.
36.80	Center of Southern Pacific railroad tracks, bears N. 28° W. and S. 28° E.
39.796	Point for the 1/4 sec. cor. of secs. 6 and 31, at proportionate dist.; there is no remaining evidence of the position of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;"> T14N R28E S31 1/4 ——— S 6 T13N 2009 </div>
47.10	Graded dirt road, 40 lks. wide, bears N. 20° W. and S. 20° E.
78.001	The cor. of Tps. 13 and 14 N., Rs. 27 and 28 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set flush with the top of a collar of stone, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the south boundary, T. 14 N., R. 27 E., executed under Group No. 837.
<hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of a Portion of the Survey Executed by H.E. Franks and J.S. Mullen in 1905, A Portion of the Dependent Resurvey Executed by E. Voigt in 1922, A Portion of the Dependent Resurvey Executed by J.A. Mack in 1986 and a Portion of the Dependent Resurvey Executed by R.A. Pratt in 1989</p> <hr/> <p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°58'10" W., bet. secs. 25 and 36.</p> <p>Over rolling land, covered with shadescale, cheat and bunch grass.</p>	
3.40	Graded dirt road, 90 lks. wide, bears NW. and SE.
9.20	Dirt road, 90 lks. wide, bears NW. and SE.
9.981	The E-E 1/64 sec. cor. of secs. 25 and 36, determined by person(s) unknown, monumented with a rebar, 5/8 in. diam, 24 ins. long, firmly set flush with the surface of the ground, and

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S25 E-E 1/64 S36</p> <p style="text-align: center;">2009</p> <p>Deposit rebar inside the stainless steel post.</p> <hr/> <p>S. 89°54'10" W., beginning new measurement.</p> <p>9.951 Point for the E 1/16 sec. cor. of secs. 25 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S25 E 1/16 <u> </u> S36</p> <p style="text-align: center;">2009</p> <p>15.40 Irrigation ditch, 23 lks. wide, drains S. 45° E.</p> <p>Thence across nearly level land.</p> <p>19.902 The W-E 1/64 sec. cor. of secs. 25 and 36, determined by person(s) unknown, monumented with a rebar, 1/2 in. diam., 12 ins. long, firmly set 3 ins. below the surface of the ground, alongside of which is the remains of a rusted bolt, 1/2 in. diam., with round head, 1 1/2 ins. diam., too corroded to determine length. This corner is harmoniously related to local improvements and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S25 W-E 1/64 S36</p> <p style="text-align: center;">2009</p> <p>Deposit rebar and bolt inside the stainless steel post.</p> <hr/>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 89°43'40" W., beginning new measurement.
2.00	Barbed wire fence, bears N. 75° W. and S. 75° E., thence across cultivated field.
10.00	Barbed wire fence, bears N. and S., 0.02 chs. dist. to cor. of barbed wired fences, extending N., S. and W. Thence across nearly level land, along fence.
10.072	The 1/4 sec. cor. of secs. 25 and 36, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 1 in. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 13 N., R. 28 E., executed under Group No. 635. S. 89°54'50" W., beginning new measurement.
0.60	Irrigation ditch, 30 lks. wide, 5 ft. deep, drains S.
0.90	Intersection of Milton Road, a graded dirt road, 20 lks. wide, extends N. and S., and the N. side of a graded dirt road, 15 lks. wide, extends W. Thence along N. side of graded dirt road and along barbed wire fence.
9.93	Barbed wire fence, bears N. and S., 0.02 chs. dist. of the cor. of fences, extending E., W. and S.
9.978	Point for the E-W 1/64 sec. cor. of secs. 25 and 36, at proportionate distance; there is no remaining evidence of the position of the 1986 corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. S25 E-W 1/64 S36 2009
19.85	Concrete lined irrigation ditch, 10 lks. wide, 4 ft. deep, drains S., 10 lks. dist. N. of the cor. of concrete lined irrigation ditches, extending N. and W., thence along concrete lined irrigation ditch.
19.956	The W 1/16 sec. cor. of secs. 25 and 36, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, in a collar of broken concrete, with aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 13 N., R. 28 E., executed under Group No. 635.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	S. 89°54'50" W., beginning new measurement.
7.485	Point for the 1/1024 sec. cor. of secs. 25 and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. 1/1024 2009 Point is located 1.5 lks. N. of concrete lined irrigation ditch, bears E. and W. and on S. edge of dirt road, 15 lks. wide, bears E. and W.
9.980	The W-W 1/64 sec. cor. of secs. 25 and 36, monumented with a railroad spike, firmly set flush with the surface of dirt road, from which the 1986 reference monuments An aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, in a collar of stone, bears S. 55 1/4° E., 36.4 lks. dist., with aluminum cap mkd. RM W-W 1/64 S36 24 FT 1986 and an arrow pointing to the cor. An aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, in a collar of stone, bears N. 56° W., 37.9 lks. dist., with aluminum cap mkd. RM W-W 1/64 S25 25 FT 1986 and an arrow pointing to the cor. Cor. is located in a dirt road, 25 lks. wide, bears E. and W. <hr/> From the S 1/16 sec. cor. of secs. 25 and 26, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 13 N., R. 28 E., executed under Group No. 635. N. 0°10'30" W., bet. secs. 25 and 26. Across nearly level, developed land.
0.03	Barbed wire fence, bears E. and W.
4.20	Barbed wire fence, bears E. and W.
9.90	Cor. of barbed wire fences, extending NW., SE. and W.
9.928	The N-S 1/64 sec. cor. of secs. 25 and 26, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 13 N., R. 28 E., executed under Group No. 635, with a mound of stone, 2 ft. base, 1 ft. high, W. of cor. <hr/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°10'00" W., beginning new measurement.						
0.50	Graded dirt road, 30 lks. wide, bears NW. and SE.						
2.00	Concrete lined irrigation ditch, 25 lks. wide, 5 ft. deep, drains S. 40° E.						
6.90	Dirt road, 30 lks. wide, bears NW. and SE.						
9.979	The 1/4 sec. cor. of secs. 25 and 26, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 13 N., R. 28 E., executed under Group No. 635, with a weathered redwood post, 4 ins. square, projecting 10 ins. above ground, set on E. side of aluminum post, and a wood post, 6x8 ins., projecting 6 ft. above ground, set on N. side of aluminum post.						
	Cor. is located on W. edge of dirt road, bears SSE. and NNW.						
	N. 0°06'50" W., beginning new measurement.						
0.70	Dirt road, 30 lks. wide, bears SSE. and N.						
20.019	Point for the N 1/16 sec. cor. of secs. 25 and 26.						
	POINT NOT MONUMENTED						
32.00	Little Dam Road, asphalt surfaced, 40 lks. wide, bears N. 50° W. and S. 50° E.						
40.038	The cor. of secs. 23, 24, 25 and 26, monumented with a redwood post, 4 ins. square, 36 ins. long, firmly set, projecting 12 ins. above the ground, with illegible scribe mks. visible.						
	At the corner point						
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.						
	<table> <tr> <td>T13N</td><td>R28E</td></tr> <tr> <td>S23</td><td>S24</td></tr> <tr> <td>S26</td><td>S25</td></tr> </table>	T13N	R28E	S23	S24	S26	S25
T13N	R28E						
S23	S24						
S26	S25						
	2009						
	Bury redwood post alongside the stainless steel post.						
	From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the west boundary, T. 13 N., R. 29 E., executed under Group No. 181.						

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>N. 89°56'10" W., bet. secs. 24 and 25.</p> <p>Over rolling land covered with shadescale, cheat and bunch grass.</p>
40.677	<p>The 1/4 sec. cor. of secs. 24 and 25, monumented with a redwood post, 4 ins. square, 36 ins. long, loosely set, with illegible scribe mks. visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13N R28E</p> <p>S24</p> <p>1/4 —</p> <p>S25</p> <p>2009</p> </div> <p>Bury redwood post alongside the stainless steel post.</p> <hr/> <p>S. 89°38'10" W., beginning new measurement.</p>
15.10	Graded dirt road, 15 lks. wide, bears NE. and SW.
31.246	From this point, a Nevada State Highway right-of-way monument; a concrete block, 6 ins. square, firmly set, projecting 6 ins. above the ground, with the letter N cast into the westerly side and a brass wire in top center, bears SOUTH, 0.031 chs. dist.
34.60	U.S. Highway No. 95, asphalt surfaced, 50 lks. wide, bears N. 8° E. and S. 8° W.
37.369	From this point, a Nevada State Highway monument; a concrete block, 6 ins. square, firmly set, projecting 6 ins. above the ground, with the letter N cast into the easterly side and a brass wire in top center, bears SOUTH, 0.008 chs. dist.
39.323	<p>The cor. of secs. 23, 24, 25 and 26.</p> <hr/> <p>N. 0°03'00" E., bet. secs. 23 and 24.</p> <p>Over rolling land covered with shadescale, cheat and bunch grass.</p>
39.952	<p>Point for the 1/4 sec. cor. of secs. 23 and 24, determined by the method of irregular boundary adjustment; a weathered cottonwood post, 3 ins. diam., 14 ins. long, no mks. visible, was found lying loose nearby, original position indeterminate.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div data-bbox="873 262 1019 346"> T13N R28E 1/4 S23 S24 </div> <div data-bbox="911 367 976 394">2009</div> <hr/> <div data-bbox="435 457 1105 485">N. 0°07'00" W., beginning new measurement.</div> <div data-bbox="293 510 1425 642"> 40.163 The cor. of secs. 13, 14, 23, and 24, perpetuated with an unrecorded rebar, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with plastic cap mkd. PLS 5194, with the remains of a cottonwood post, 2 1/2 ins. diam., 8 ins. long, lying loose alongside. </div> <div data-bbox="435 667 740 695">At the corner point</div> <div data-bbox="435 720 1458 800">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</div> <div data-bbox="873 829 1019 934"> T13N R28E S14 S13 <hr/> S23 S24 </div> <div data-bbox="911 961 976 989">2009</div> <div data-bbox="435 1014 1445 1068">Deposit the rebar inside stainless steel post and bury the wood post alongside.</div> <hr/> <div data-bbox="435 1129 1458 1314">From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., monumented with a redwood post, 4 ins. square, firmly set, projecting 12 ins. above the ground, with illegible scribe mks. visible, with an iron post, 2 ins. diam., firmly set on the E. side of the wood post, with brass mkd. as described in the field notes of the dependent resurvey of a portion of the west boundary of T. 13 N., R. 29 E., executed under Group No. 181.</div> <div data-bbox="435 1339 740 1367">At the corner point</div> <div data-bbox="435 1392 1458 1472">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</div> <div data-bbox="873 1501 1019 1627"> T13N R28E R29E S13 S18 <hr/> S24 S19 </div> <div data-bbox="911 1654 976 1682">2010</div> <div data-bbox="435 1707 1344 1764">Bury the iron post, inverted, and wood post alongside the stainless steel post.</div> <div data-bbox="435 1789 1036 1816">N. 89°51'40" W., bet. secs. 13 and 24.</div> <div data-bbox="435 1841 1377 1896">Over rolling land, covered with shadescale, cheat and bunch grass.</div>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.048	<p>Point for the 1/4 sec. cor. of secs. 13 and 24, at proportionate dist.; there is no remaining evidence of the position of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> T13N R28E S13 1/4 <u> </u> S24 2009 </div>
64.80	U.S. Highway No. 95, asphalt surfaced, 50 lks. wide, bears N. 8° E. and S. 8° W.
80.096	<p>The cor. of secs. 13, 14, 23 and 24.</p> <hr/> <p>N. 0°07'20" W., bet. secs. 13 and 14.</p> <p>Over rolling land, covered with shadescale, cheat and bunch grass.</p>
39.907	<p>Point for the 1/4 sec. cor. of secs. 13 and 14, at proportionate dist.; there is no remaining evidence of the position of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> T13N R28E 1/4 S14 S13 2009 </div>
79.814	<p>Point for the cor. of secs. 11, 12, 13 and 14, at proportionate dist.; there is no remaining evidence of the position of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> T13N R28E S11 S12 <u> </u> S14 S13 2009 </div> <hr/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., monumented with a redwood post, 4 ins. square, 30 ins. long, firmly set, with an unmkd. memorial stone, 7x5x4 ins., recovered beneath the wood post, and with an iron post, 2 ins. diam., 36 ins. long, firmly set on the E. side of wood post, with brass mkd. as described in the field notes of the dependent resurvey of a portion of the west boundary, T. 13 N., R. 29 E., executed under Group No. 181.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td colspan="2">T13N</td></tr> <tr><td>R28E</td><td>R29E</td></tr> <tr><td>S12</td><td>S 7</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S13</td><td>S18</td></tr> </table> <p>2010</p> </div> <p>Bury iron post, inverted, wood post and stone alongside the stainless steel post.</p> <p>S. 89°45'20" W., bet. secs. 12 and 13</p> <p>Over rolling land, covered with shadescale, cheat and bunch grass.</p> <p>40.167 The 1/4 sec. cor. of secs. 12 and 13, monumented with a redwood post, 4 ins. square, 36 ins. long, loosely set, with illegible scribe mks. visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td colspan="2">T13N R28E</td></tr> <tr><td colspan="2">S12</td></tr> <tr><td>1/4</td><td><hr/></td></tr> <tr><td colspan="2">S13</td></tr> </table> <p>2009</p> </div> <p>Bury redwood post alongside the stainless steel post.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 89°32'10" W., beginning new measurement.</p> <p>14.60 U.S. Highway No. 95, asphalt surfaced, 50 lks. wide, bears N. 8° E. and S. 8° W.</p> <p>40.133 The cor. of secs. 11, 12, 13 and 14.</p> <hr style="width: 60%; margin: 10px auto;"/>	T13N		R28E	R29E	S12	S 7	<hr/>		S13	S18	T13N R28E		S12		1/4	<hr/>	S13	
T13N																			
R28E	R29E																		
S12	S 7																		
<hr/>																			
S13	S18																		
T13N R28E																			
S12																			
1/4	<hr/>																		
S13																			

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°27'40" E., bet. secs. 11 and 12.
	Over rolling land, covered with shadescale, cheat and bunch grass.
39.907	The 1/4 sec. cor. of secs. 11 and 12, monumented with a redwood post, 4 ins. square, 36 ins. long, firmly set, projecting 18 ins. above the ground, with illegible scribe mks. visible.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<div style="text-align: center;"> T13N R28E 1/4 S11 S12 2009 </div>
	Bury redwood post alongside the stainless steel post.
	<hr/> N. 0°34'00" W., beginning new measurement.
40.049	The cor. of secs. 1, 2, 11 and 12, at proportionate dist.; remnants of wood post was found lying loose nearby, the original position indeterminate.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<div style="text-align: center;"> T13N R28E S 2 S 1 <hr/> S11 S12 2009 </div>
	Bury the remnants of wood post alongside stainless steel post.
	<hr/> From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in field notes of the dependent resurvey of a portion of the west boundary, T. 13 N., R. 29 E., executed under Group No. 181.
	S. 89°54'50" W., bet. secs. 1 and 12.
	Over rolling land, covered with shadescale, cheat and bunch grass.
40.259	The 1/4 sec. cor. of secs. 1 and 12, monumented with a redwood post, 4 ins. square, 36 ins. long, loosely set, projecting 18 ins. above the ground, with illegible scribe mks. visible.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T13N R28E S 1 1/4 — S12 2009</p> <p>Bury redwood post alongside the stainless steel post.</p> <hr/> <p>N. 89°46'50" W., beginning new measurement.</p>
4.00	U.S. Highway No. 95, asphalt surfaced, 50 lks. wide, bears N. 8° E. and S. 8° W.
40.016	The cor. of secs. 1, 2, 11 and 12.
	<hr/> <p>N. 0°03'30" E., bet. secs. 1 and 2.</p> <p>Over rolling land, covered with shadescale, cheat and bunch grass.</p>
40.047	<p>Point for the 1/4 sec. cor. of secs. 1 and 2, at proportionate dist.; there is no remaining evidence of the position of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T13N R28E 1/4 S 2 S 1 2009</p>
80.003	<p>The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>N. 89°48'20" W., bet. secs. 23 and 26.</p> <p>Over rolling land, covered with shadescale, cheat and bunch grass.</p>
3.50	Little Dam Road, asphalt surfaced, 30 lks. wide, curves left to the NW. and curves right to the SE.
16.00	Sunset Drive, asphalt surfaced, 30 lks. wide, bears N. 30° W. and S. 30° E.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
30.117	<p>The W-E 1/64 sec. cor. of secs. 23 and 26, monumented with an unrecorded rebar, 5/8 in. diam., firmly set flush with the surface of the ground, with plastic cap mkd. PLS 5198. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>S23 W-E 1/64 S26</p> <p>2009</p> </div> <p>Deposit rebar inside stainless steel post.</p> <hr/> <p>N. 89°48'20" W., beginning new measurement.</p>
10.039	<p>The 1/4 sec. cor. of secs. 23 and 26, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 13 N., R. 28 E., executed under Group No. 670.</p> <hr/> <p>N. 89°44'50" W., beginning new measurement.</p>
10.030	<p>Point for the E-W 1/64 sec. cor. of secs. 23 and 26.</p> <p>POINT NOT MONUMENTED</p>
20.00	<p>E. edge of graded dirt road, 25 lks. wide, bears S. and N. for 25 lks., thence W.</p>
20.060	<p>Point for the W 1/16 sec. cor. of secs. 23 and 26.</p> <p>Set a copper coated steel rod, 1/2 in. diam., 12 ins. long, with brass cap, 1 1/2 ins. diam., mkd.</p> <div style="text-align: center;"> <p>BLM S23 W 1/16 <hr/>S26</p> <p>2009</p> </div> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 53°20' E., 17.0 lks. dist., with brass cap mkd. RM W 1/16 S23 11.2 FT TO COR 2010 and an arrow pointing to the cor.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 68°41' E., 14.1 lks. dist., with brass cap mkd. RM W 1/16 S26 9.3 FT TO COR 2010 and an arrow pointing to the cor.</p> <p>Point is located in graded dirt road, over buried steel culvert.</p>				
40.120	<p>The cor. of secs. 22, 23, 26 and 27, determined by person(s) unknown, monumented with a 20D nail, set flush with the asphalt surface, from which the 1986 reference monuments</p> <p>An aluminum post, 2 1/2 ins. diam., firmly set in a collar of stone, bears S. 69° E., 45.5 lks. dist., with aluminum cap mkd. RM T13N R28E S26 30 FT 1986 and an arrow pointing to the cor.</p> <p>An aluminum post, 2 1/2 ins. diam., firmly set in a collar of stone, bears S. 64 1/2° W., 62.1 lks. dist., with aluminum cap mkd. RM T13N R28E S27 41 FT 1986 and an arrow pointing to the cor.</p> <p>At the corner point</p> <p>Set a copper coated steel rod, 1/2 in. diam., 6 ins. long, 1/2 in. below the asphalt surface, with with brass cap, 1 1/2 ins. diam., mkd.</p> <div style="text-align: center;"> <p>BLM</p> <p>T13N R28E</p> <table border="1" style="margin: auto;"> <tr> <td>S22</td><td>S23</td></tr> <tr> <td>S27</td><td>S26</td></tr> </table> <p>2010</p> </div> <p>Remove and dispose of the 20d nail.</p> <p>Cor. is located in Farm Road, asphalt surfaced, 35 lks. wide, extending S. and W.</p>	S22	S23	S27	S26
S22	S23				
S27	S26				
9.975	<p>N. 0°05'10" W., bet. secs. 22 and 23.</p> <p>Leave asphalt surface, thence along graded dirt road.</p> <p>Point for the S-S 1/64 sec. cor. of secs. 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>S-S</p> <p>1/64</p> <table border="1" style="margin: auto;"> <tr> <td>S22</td><td>S23</td></tr> </table> <p>2009</p> </div> <p>Cor. is located on W. edge of graded dirt road.</p>	S22	S23		
S22	S23				

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
19.950	<p>The S 1/16 sec. cor. of secs. 22 and 23, monumented with an aluminum post, 2 1/2 ins. diam., recovered 4 ins. below the surface of a graded dirt road, with corroded aluminum cap unreadable.</p> <p>from which new bearing objects</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 43°56' E., 26.2 lks. dist., with brass cap mkd. RM S1/16 S23 17.3 FT TO COR 2010 and an arrow pointing to the cor.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 51°54' E., 27.0 lks. dist., with brass cap mkd. RM S1/16 S23 17.8 FT TO COR 2010 and an arrow pointing to the cor.</p> <p>Deposit plastic-encased magnet inside aluminum post.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 22 and 23, monumented with an iron post, 1 in. diam., recovered 3 ins. below the surface of the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 13 N., R. 28 E., executed under Group No. 635.</p> <p>N. 0°24'40" W., bet. secs. 22 and 23.</p> <p>Across river bottom lands, covered with scattered cottonwoods, willows, cheat and bunch grass.</p>
10.013	<p>Point for the S-N 1/64 sec. cor. of secs. 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S-N 1/64 S22 S23 2009</p>
20.026	<p>Point for the N 1/16 sec. cor. of secs. 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S22 S23 2009</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
30.039	<p>Point for the N-N 1/64 sec. cor. of secs. 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">N-N 1/64 S22 S23 2009</p>
40.052	<p>The cor. of secs. 14, 15, 22 and 23, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 13 N., R. 28 E., executed under Group No. 66.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>N. 89°55'10" W., bet. secs. 14 and 23.</p> <p>Across rolling land, covered with shadescale, cheat and bunch grass.</p>
39.960	<p>The 1/4 sec. cor. of secs. 14 and 23, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 13 N., R. 28 E., executed under Group No. 66.</p> <hr/> <p>N. 89°52'00" W., beginning new measurement.</p> <p>Across rolling land, covered with shadescale, cheat and bunch grass.</p>
10.147	<p>Point for the E-W 1/64 sec. cor. of secs. 14 and 23.</p> <p>POINT NOT MONUMENTED</p>
14.40	<p>Graded dirt road, 50 lks. wide, bears N. 30° W. and S. 30° E.</p>
20.294	<p>Point for the W 1/16 sec. cor. of secs. 14 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S14 W 1/16 — S23 2009</p>
20.50	<p>Descend into river bottom lands, through scattered cottonwoods and willows.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
21.80	Concrete lined irrigation ditch, 20 lks. wide, 5 ft. deep, drains SSW.
30.441	Point for the W-W 1/64 sec. cor. of secs. 14 and 23. POINT NOT MONUMENTED
40.588	The cor. of secs. 14, 15, 22 and 23. <hr/> N. 0°11'40" E., bet. secs. 14 and 15. Across river bottom lands, covered with scattered cottonwoods, willows, cheat and bunch grass.
9.950	Point for the S-S 1/64 sec. cor. of secs. 14 and 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;">S-S 1/64 S15 S14 2009</div>
19.900	Point for the S 1/16 sec. cor. of secs. 14 and 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;">S 1/16 S15 S14 2009</div> From this point, the cor. of barbed wire fences, extending NNE. and W., bears S. 4° W., 0.14 chs. dist. Thence across cultivated land.
29.850	Point for the N-S 1/64 sec. cor. of secs. 14 and 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;">N-S 1/64 S15 S14 2009</div>
39.800	Point for the 1/4 sec. cor. of secs. 14 and 15, at proportionate dist.; there is no remaining evidence of the position of the original corner. Chisel an X in concrete lined irrigation ditch.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 32°42' W., 13.5 lks. dist., with brass cap mkd. RM 1/4 S15 8.9 FT TO COR 2009 and arrow pointing to the cor.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 78°24' W., 19.8 lks. dist., with brass cap mkd. RM 1/4 S15 13.1 FT TO COR 2009 and arrow pointing to the cor.</p> <p>Cor. falls in a concrete lined irrigation ditch, 10 lks. wide, 2 ft. deep, drains SE.</p>
40.85	<p>Concrete lined irrigation ditch, 25 lks. wide, 5 ft. deep, drains SE.</p> <p>Thence across nearly level land covered with shadscale, cheat and bunch grass.</p>
49.750	<p>Point for the S-N 1/64 sec. cor. of secs. 14 and 15.</p> <p>POINT NOT MONUMENTED</p>
59.700	<p>Point for the N 1/16 sec. cor. of secs. 14 and 15.</p> <p>POINT NOT MONUMENTED</p>
79.600	<p>The cor. of secs. 10, 11, 14 and 15, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 13 N., R. 28 E., executed under Group No. 635.</p> <hr/> <p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>S. 89°57'10" W., bet. secs. 11 and 14.</p> <p>Across rolling land covered with shadscale, cheat and bunch grass.</p>
40.046	<p>Point for the 1/4 sec. cor. of secs. 11 and 14, at proportionate dist.; there is no remaining evidence of the position of the position of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>T13N R28E S11 1/4 <u> </u> S14 2009</p>
80.092	<p>The cor. of secs. 10, 11, 14 and 15.</p> <hr/> <p>N. 0°01'30" W., bet. secs. 10 and 11.</p> <p>Across rolling land covered with shadescall, cheat and bunch grass.</p>
40.065	<p>Point for the 1/4 sec. cor. of secs. 10 and 11, at proportionate dist.; there is no remaining evidence of the position of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p>T13N R28E 1/4 S10 S11 2009</p>
41.60	<p>Four-wheel drive trail, 10 lks. wide, bears NNE. and SSW.</p>
80.130	<p>The cor. of secs. 2, 3, 10 and 11, monumented with a redwood post, 4 ins. square, 36 ins. long, firmly set, projecting 18 ins. above the ground, with illegible scribe mks. visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p>T13N R28E S 3 S 2 <u> </u> S10 S11 2009</p> <p>Bury redwood post alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>N. 89°55'40" W., bet. secs. 2 and 11.</p> <p>Across rolling land covered with shadescall, cheat and bunch grass.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.946	<p>The 1/4 sec. cor. of secs. 2 and 11, monumented with a redwood post, 4 ins. square, 36 ins. long, firmly set, projecting 14 ins. above the ground, with illegible scribe mks. visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T13N R28E S 2 1/4 — S11</p> <p style="text-align: center;">2009</p> <p>Bury redwood post alongside the stainless steel post.</p> <hr/> <p>N. 89°54'50" W., beginning new measurement.</p>
40.089	<p>The cor. of secs. 2, 3, 10 and 11.</p> <hr/> <p>N. 0°04'30" E., bet. secs. 2 and 3.</p> <p>Across rolling land covered with shadescall, cheat and bunch grass.</p>
40.088	<p>Point for the 1/4 sec. cor. of secs. 2 and 3, at proportionate dist.; the remnants of a wood post was found lying loose nearby, the original position indeterminate.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T13N R28E 1/4 S 3 S 2</p> <p style="text-align: center;">2009</p> <p>Bury remnants of wood post alongside the stainless steel post.</p>
80.086	<p>The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°01'50" E., bet. secs. 33 and 34.</p> <p>Over mountainous terrain covered with sagebrush, shadescall, cheat and bunch grass.</p>
1.20	<p>Top of ravine, bears NNE. and NNW.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
2.10	Bottom of ravine, drains ENE.
2.50	Four-wheel drive trail, 19 lks wide, follows bottom of ravine.
11.80	Foot trail, 5 lks. wide, bears NW. and SE.
12.50	Top of ascent, bears NW. and SE.
35.80	Ravine, drains NE.
36.10	From this point, the confluence of ravines bears E., 0.70 chs. dist., drains NE.
39.747	<p>The 1/4 sec. cor. of secs. 33 and 34, monumented with a granite stone, 18x8x6 ins., firmly set, projecting 10 ins. above the ground, mkd. 1/4 on W. face, with a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 13 ins. in the ground to bedrock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T13N R28E 1/4 S33 S34 2009</p> <p>Bury mkd. stone alongside the stainless steel post.</p> <hr/> <p>N. 0°00'20" W., beginning new measurement.</p>
36.80	Ravine, drains ENE.
39.872	<p>The cor. of secs. 27, 28, 33 and 34, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 13 N., R. 28 E., executed under Group No. 635.</p> <p>from which new bearing objects</p> <p style="padding-left: 40px;">A chiseled X followed by the letters B0, bears N. 36°48' E., 52.6 lks. dist., mkd. on the top of a granite boulder, 5X2 1/2X1 ft. high.</p> <p style="padding-left: 40px;">A chiseled X followed by the letters B0, bears S. 81°39' W., 16.6 lks. dist., mkd. on the top of a granite boulder, 8x8x3 ft. high.</p> <hr/> <p>From the N-S 1/64 sec. cor. of secs. 21 and 22, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 13 N., R. 28 E., executed under Group No. 635.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Cor. is located in barbed wire fence, bears N. and S.
	N. 0°28'40" W., bet. secs. 21 and 22.
	Across level farmland, along W. side of fence.
10.010	Point for the 1/4 sec. cor. of secs. 21 and 22, determined by
	the method of irregular boundary adjustment; the 1986 aluminum
	post, 2 1/2 ins. diam., 28 ins. long, with aluminum cap mkd. as
	described in the field notes of the dependent resurvey of a
	portion of the subdivisional lines, T. 13 N., R. 28 E., executed
	under Group No. 635, was found in a disturbed position, with cap
	rotated 90 degrees from north, bears N. 73°07'30" E., 0.071 chs.
	dist.
	Reset aluminum post at the corner point, 24 ins. in the ground,
	over a plastic-encased magnet and add the marks 2010.
	Point is located in a barbed wire fence, bears W., and E. for
	0.06 chs. dist to cor. of fences, extending S. and W.
	N. 0°11'50" E., beginning new measurement.
10.010	The S-N 1/64 sec. cor. of secs. 21 and 22, monumented with the
	lower portion of an aluminum post, 2 1/2 ins. diam., recovered
	20 ins. below the surface of the ground in an upright position,
	the upper portion sheared off and not found.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
	24 ins. in the ground, over a plastic-encased magnet, with brass
	cap mkd.
	S-N
	1/64
	S21 S22
	2009
	Bury remains of aluminum post alongside the stainless steel
	post.
	From the E 1/16 sec. cor. of secs. 15 and 22, monumented with a
	chiseled X in a concrete irrigation ditch, from which the 1986
	reference monuments
	An aluminum post, 2 1/2 ins. diam., firmly set flush
	with the ground, bears N. 52°06' E., 15 lks. dist.,
	with aluminum cap mkd. RM E 1/16 S15 10 FT 1986 and an
	arrow pointing to the cor. (Record, N. 50 1/4° E.)
	An aluminum post, 2 1/2 ins. diam., firmly set,
	projecting 8 ins. above the ground, bears
	S. 34°14' E., 22.7 lks. dist., with aluminum cap mkd.
	RM E 1/16 S22 15 FT 1986 and an arrow pointing to the
	cor. (Record, S. 33 1/2° E.)
	N. 89°59'20" W., bet. secs. 15 and 22.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Across cultivated land and along concrete irrigation ditch.
10.000	<p>The W-E 1/64 sec. cor. of secs. 15 and 22, monumented with a chiseled X in a concrete irrigation ditch, from which the 1986 reference monuments</p> <p>An aluminum post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, in a collar of stone, bears S. 39° W., 19.7 lks. dist., with aluminum cap mkd. RM W-E 1/64 S22 13 FT 1986 and an arrow pointing to the cor.</p> <p>An aluminum post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, bears N. 32 1/4° W., 27.3 lks. dist., with aluminum cap mkd. RM W-E 1/64 S15 18 FT 1986 and an arrow pointing to the cor.</p> <hr/> <p>From the W 1/16 sec. cor. of secs. 15 and 22, monumented with a chiseled square mkd. on a wooden plank, on the east side of a bridge over a concrete lined irrigation ditch, from which the 1986 reference monuments</p> <p>An aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, in a collar of stone, bears S. 37 1/2° W., 62.1 lks. dist., with aluminum cap mkd. RM W1/16 S22 41 FT 1986 and an arrow pointing to the cor.</p> <p>An aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, bears N. 46 1/2° W., 53.0 lks. dist., with aluminum cap mkd. mkd. RM W1/16 S15 35 FT 1986 and an arrow pointing to the cor.</p> <p>At the corner point</p> <p>Set a PK nail flush with the surface of wood plank.</p> <p>N. 89°55'50" W., continuing bet. secs. 15 and 22.</p> <p>Across rolling land covered with shadecale, cheat and bunch grass.</p>
10.000	<p>Point for the W-W 1/64 sec. cor. of secs. 15 and 22, at proportionate dist.; an aluminum post, 2 1/2 ins. diam., 30 ins. long, with cap mkd. as described the field notes of the 1986 dependent resurvey of a portion of the subdivisional lines, T. 13 N., R. 28 E., executed under Group No. 635, was found lying loose nearby, the original position indeterminate.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: right; margin-right: 100px;"> <p>S15</p> <p>W-W 1/64 —</p> <p>S22</p> <p>2009</p> </div>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Bury aluminum post alongside the stainless steel post. Thence along fallen fence line, between cultivated fields.
20.000	The cor. of secs. 15, 16, 21 and 22, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 13 N., R. 28 E., executed under Group No. 635.
	N. 0°09'10" W., bet. secs. 15 and 16. Across cultivated land.
7.00	Irrigation ditch, drains SW. Thence across level land, covered with shadecale, cheat and bunch grass.
17.40	West Loop Road, asphalt surfaced, 30 lks. wide, curves right to the NE. and curves left to the SW.
19.977	The S 1/16 sec. cor. of secs. 15 and 16, monumented with an unrecorded rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 4 ins. above the ground, with plastic cap illegibly mkd. This is accepted as a careful and faithful determination of the position of the corner. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. S 1/16 S16 S15 2009 Insert rebar inside the stainless steel post. Cor. is located at fence cor., extending S. and E.
	N. 0°09'10" W., beginning new measurement.
19.977	The 1/4 sec. cor. of secs. 15 and 16, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set flush with the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 13 N., R. 28 E., executed under Group No. 670.
	N. 0°15'10" E., beginning new measurement.
6.40	Road, asphalt surfaced, 30 lks. wide, bears N. 40° W. and S. 40° E.
19.971	Point for the N 1/16 sec. cor. of secs. 15 and 16.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S16 S15</p> <p style="text-align: center;">2009</p>
25.05	<p>Concrete lined irrigation ditch, 25 lks. wide, 5 ft. deep, drains S. 70° E.</p> <p>Thence across level land, through scattered cottonwood trees.</p>
29.00	<p>Right bank of the Walker River, bears NNW. and SSE., thence across river, course SSE.</p>
29.9565	<p>Point for the N-N 1/64 sec. cor. of secs. 15 and 16, falls in the Walker River where it is impractical to establish a permanent monument.</p> <p>POINT NOT MONUMENTED</p>
30.50	<p>Right bank of the Walker River, bears NNE. and SSW., leave river.</p>
33.00	<p>Right bank of the Walker River, bears NNW. and SSE., thence across river, course SSE.</p>
34.50	<p>Left bank of the Walker River, bears NNW. and SSE., leave river.</p>
38.50	<p>Left bank of the Walker River, bears NE. and SW., thence across river, course SW.</p>
39.00	<p>Right bank of the Walker River, bears NE. and SW.</p>
39.942	<p>Point for the cor. of secs. 9, 10, 15 and 16, determined on the extension of the line bet. secs. 9 and 16, at record distance from the 1989 witness corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T13N R28E S 9 S10 ----- S16 S15</p> <p style="text-align: center;">2010</p> <p>Point is located on accreted right bank of Walker River.</p> <hr/> <p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>N. 89°43'00" W., bet. secs. 10 and 15.</p> <p>Across rolling land covered with shadecale, cheat and bunch grass.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.042	Point for the E 1/16 sec. cor. of secs. 10 and 15. POINT NOT MONUMENTED
30.063	Point for the W-E 1/64 sec. cor. of secs. 10 and 15. POINT NOT MONUMENTED
40.084	The 1/4 sec. cor. of secs. 10 and 15, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 13 N., R. 28 E., executed under Group No. 670. <hr/>
	N. 89°43'00" W., beginning new measurement.
0.50	Concrete lined irrigation ditch, 25 lks. wide, 5 ft. deep, drains S. 30° E. Thence across level, cultivated land.
9.80	Concrete lined irrigation ditch, 25 lks. wide, 5 ft. deep, drains N. 50° E.
10.021	Point for the E-W 1/64 sec. cor. of secs. 10 and 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;"> $\begin{array}{r} \text{S10} \\ \text{E-W 1/64 } \frac{\quad}{\quad} \\ \text{S15} \\ \hline 2009 \end{array}$ </div>
13.55	Concrete lined irrigation ditch, 27 lks. wide, 5 ft. deep, drains S. 50° E.
14.75	Concrete lined irrigation ditch, 5 lks. wide, 3 ft. deep, drains S. 65° E.
20.042	Point for the W 1/16 sec. cor. of secs. 10 and 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;"> $\begin{array}{r} \text{S10} \\ \text{W 1/16 } \frac{\quad}{\quad} \\ \text{S15} \\ \hline 2009 \end{array}$ </div>
30.063	Point for the W-W 1/64 sec. cor. of secs. 10 and 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>S10 W-W 1/64 — S15 2009</p>
30.40	<p>Barbed wire fence, bears N. and S. for 0.015 chs. to cor. of fences, extending N. and W. Thence along fence, through scattered cottonwoods and willows.</p>
37.60	Left bank of the Walker River, bears NNE. and SSW, thence across river, course SSW.
38.70	Right bank of the Walker River, bears NE. and SW., leave river.
40.084	The cor. of secs. 9, 10, 15 and 16.
	<hr/> <p>N. 0°01'50" E., bet secs. 9 and 10. Across river bottom land, covered with scattered cottonwoods, willows, shadescale, cheat and bunch grass.</p>
3.30	Right bank of the Walker River, bears WSW. and ENE., thence across river, course ENE.
4.00	Left bank of the Walker River, bears ENE. and WSW.
9.986	<p>Point for the S-S 1/64 sec. cor. of secs. 9 and 10. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p>S-S 1/64 S 9 S10 2009</p>
19.972	<p>Point for the S 1/16 sec. cor. of secs. 9 and 10. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p>S 1/16 S 9 S10 2009</p>
20.05	Concrete lined irrigation ditch, 11 lks. wide, 2 ft. deep, drains S. 68° W.
22.60	Left bank of the Walker River, bears NE. and SW., thence along river, course S.
24.10	Left bank of the Walker River, bears NW. and SE., leave river.
29.958	Point for the N-S 1/64 sec. cor. of secs. 9 and 10.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">N-S 1/64 S 9 S10 2009</p> <p>From this point, the cor. of barbed wire fences, extending S. and W., bears N. 75° W., 0.04 chs. dist.</p> <p>Thence along E. side of barbed wire fence.</p>
33.80	<p>Concrete lined irrigation ditch, 30 lks. wide, 5 ft. deep, drains S. 40° E.</p> <p>Thence across rolling land, covered with shadescale, cheat and bunch grass.</p>
39.944	<p>The 1/4 sec. cor. of secs. 9 and 10, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 13 N., R. 28 E., executed under Group No. 670.</p> <hr/> <p>N. 0°06'00" E., beginning new measurement.</p>
3.50	Graded dirt road, 50 lks. wide, bears NW. and SE.
9.968	<p>Point for the S-N 1/64 sec. cor. of secs. 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S-N 1/64 S 9 S10 2009</p>
10.05	Barbed wire fence, steel posts, bears N. 43° W. and S. 43° E.
19.936	<p>Point for the N 1/16 sec. cor. of secs. 9 and 10.</p> <p>POINT NOT MONUMENTED</p>
39.872	<p>The cor. of secs. 3, 4, 9 and 10, monumented with a redwood post, 4 ins. square, 36 ins. long, firmly set, projecting 12 ins. above the ground, with illegible scribe mks. visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div data-bbox="873 264 1016 369"> <p>T13N R28E S 4 S 3 ----- S 9 S10</p> </div> <div data-bbox="911 396 976 420">2009</div> <div data-bbox="438 451 1281 476">Bury redwood post alongside the stainless steel post.</div> <hr/> <div data-bbox="438 537 1057 562">From the cor. of secs. 2, 3, 10 and 11.</div> <div data-bbox="438 590 1024 615">N. 89°56'10" W., bet. secs. 3 and 10.</div> <div data-bbox="438 642 1411 695">Across rolling land, covered with shadescale, cheat and bunch grass.</div> <div data-bbox="289 722 1446 800"> <p>40.012 Point for the 1/4 sec. cor. of secs. 3 and 10, at proportionate dist.; the remains of a wooden post was found lying loose, the original position indeterminate.</p> </div> <div data-bbox="438 827 1458 905"> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> </div> <div data-bbox="854 932 1016 1037"> <p>T13N R28E S 3 1/4 ----- S10</p> </div> <div data-bbox="911 1064 976 1087">2009</div> <div data-bbox="289 1117 1406 1142"> <p>73.60 Graded dirt road, 40 lks. wide, bears N. 10° W. and S. 10° E.</p> </div> <div data-bbox="289 1169 959 1194"> <p>80.024 The cor. of secs. 3, 4, 9 and 10.</p> </div> <hr/> <div data-bbox="438 1255 992 1281">N. 0°02'50" W., bet. secs. 3 and 4.</div> <div data-bbox="438 1308 1411 1360">Across rolling land, covered with shadescale, cheat and bunch grass.</div> <div data-bbox="289 1388 1406 1413"> <p>24.70 Graded dirt road, 40 lks. wide, bears N. 20° W. and S. 20° E.</p> </div> <div data-bbox="289 1440 1425 1518"> <p>39.944 Point for the 1/4 sec. cor. of secs. 3 and 4, at proportionate dist.; there is remaining evidence of the position of the original corner.</p> </div> <div data-bbox="438 1545 1458 1623"> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> </div> <div data-bbox="867 1650 1016 1734"> <p>T13N R28E 1/4 S 4 S 3</p> </div> <div data-bbox="911 1761 976 1785">2010</div> <div data-bbox="289 1812 1403 1864"> <p>79.898 The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., hereinbefore described.</p> </div> <hr/>
--------	---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°20'40" E., bet. secs. 32 and 33.</p> <p>Over mountainous terrain, covered with scattered pinyon pine, sagebrush, shadescale, cheat and bunch grass.</p>
12.60	Saddle in ridge, bears ENE. and WSW.
30.80	Ravine, drains NNE.
40.237	<p>The 1/4 sec. cor. of secs. 32 and 33, determined NORTH at 3 lks. dist. from the N. edge of a granite boulder, 6x4x8 ft. high, as described in the field note record of the original survey, falls at a position where it is impractical to establish a permanent monument.</p> <p>From this point, the point selected for the witness 1/4 sec. cor. of secs. 32 and 33, bears N. 72°50' W., 0.129 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC T13N R28E 1/4 S32 S33 2009 ↘</p> </div> <p>from which</p> <p>A chiseled X followed by the letters BO, bears S. 60°20' E., 17.3 lks. dist., mkd. on the top of a granite boulder, 6X4X8 ft. high, 1 ft. from E. edge.</p> <p>A chiseled X followed by the letters BO, bears S. 77°01' W., 31.2 lks. dist., mkd. on an exposed rock spine of a spur, slopes SE.</p> <hr/> <p>N. 0°05'20" E., beginning new measurement.</p>
40.047	<p>Point for the cor. of secs. 28, 29, 32 and 33, at proportionate dist.; there is no remaining evidence of the position of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13N R28E S29 S28 S32 S33 2009</p> </div>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>from which</p> <p>A chiseled X followed by the letters BO, bears S. 57°06' E., 15.0 lks. dist., mkd. on the W. face of a granite boulder, 2x3x4 ft. high, 1 ft. below the top.</p> <p>A chiseled X followed by the letters BO, bears S. 47°47' W., 50.8 lks. dist., mkd. on the NE. face of a granite boulder, 5x3x4 ft. high, 1 1/2 ft. below top.</p> <p>From this point, a wood post of unknown origin, 4 ins. square, projecting 3 ft. above a mound of stone, 2 ft. base, 1 ft. high, bears N. 60°05'50" E., 1.613 chs. dist. This position does not correlate well with surrounding corners and other calls of record and is not utilized in the course of this survey.</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>S. 89°58'10" W., bet. secs. 28 and 33.</p> <p>Over mountainous terrain covered with sagebrush, shadscale, cheat and bunch grass.</p> <p>39.10 Ravine, drains. NE.</p> <p>39.820 The 1/4 sec. cor. of secs. 28 and 33, monumented with a granite stone, 19x10x7 ins., firmly set, projecting 10 ins. above the ground, mkd. 1/4 on N. face, with a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T13N R28E S28 1/4 ——— S33 2009</p> <p>Bury mkd. stone alongside the stainless steel post.</p> <hr/> <p>N. 88°54'40" W., beginning new measurement.</p> <p>33.70 Spur, slopes NNE.</p> <p>37.20 Ravine, drains N.</p> <p>39.691 The cor. of secs. 28, 29, 32 and 33.</p> <hr/>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>N. 0°30'50" E., bet. secs. 28 and 29.</p> <p>Over mountainous terrain covered with sagebrush, shadescale, cheat and bunch grass.</p>
15.90	Ravine, drains E.
27.60	Ridge, bears ENE. and WSW.
40.049	<p>Point for the 1/4 sec. cor. of secs. 28 and 29, at proportionate dist.; there is no remaining evidence of the position of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13N R28E 1/4 S29 S28</p> <p>2009</p> </div> <p>from which</p> <p>A chiseled X between the letters BO, bears N. 20°58' E., 64.7 lks. dist., mkd. on the top of a granite boulder, 1 1/2x1 1/2X1/2 ft. high.</p> <p>A chiseled X above the letters BO, bears N. 74°28' W., 77.3 lks. dist., mkd. on the W. face of a granite boulder, 2 1/2x2x2 ft. high, 1/2 ft. above the ground.</p> <p>Point is located on S. edge of graded dirt road, 10 lks. wide, bears N. 60° E. and S. 60° W.</p>
44.20	S. rim of ravine, bears NE. and SW.
46.50	Ravine, drains NE.
80.098	<p>The cor. of secs. 20, 21, 28 and 29, determined on the E. side of a mound of stone, 2 ft. base, 1 ft. high.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13N R28E S20 S21 S29 S28</p> <p>2009</p> </div>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the 1/4 sec. cor. of secs. 21 and 28, monumented with an aluminum post, 2 1/2 ins. diam., firmly set flush with the top of a collar of stone, with aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 13 N., R. 28 E., executed under Group No. 635.</p> <p>N. 89°09'50" W., bet. secs. 21 and 28.</p> <p>Over rolling land, covered with shadescall, cheat and bunch grass.</p>
38.722	<p>The cor. of secs. 20, 21, 28 and 29.</p> <hr/> <p>N. 2°23'40" W., bet. secs. 20 and 21.</p> <p>Over rolling land, covered with shadescall, cheat and bunch grass.</p>
28.40	Power line, bears N. 75° E. and S. 75° W.
30.00	Graded dirt road, 15 lks. wide, bears N. 65° E. and S. 65° W., to communications site located in the NE1/4NE1/4 sec. 30.
39.558	<p>The 1/4 sec. cor. of secs. 20 and 21, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with aluminum cap mkd. as described in the field notes of the subdivision of section 21, T. 13 N., R. 28 E., executed under Group No. 635, with mound of stone, 3 ft. base, 1 1/2 ft. high, W. of cor.</p> <hr/> <p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>N. 89°50'10" W., bet. secs. 9 and 16.</p> <p>Across river bottom land, covered with scattered cottonwood trees, shadescall, cheat and bunch grass.</p>
0.690	<p>The witness cor. to secs. 9, 10, 15 and 16, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 13 N., R. 28 E., executed under Group No. 670.</p> <hr/> <p>N. 89°50'10" W., beginning new measurement.</p>
10.20	<p>Concrete lined irrigation ditch, 30 lks. wide, 5 ft. deep, drains S. 5° E.</p> <p>Leave scattered cottonwood trees.</p>
19.402	<p>Point for the E 1/16 sec. cor. of secs. 9 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">S 9 E 1/16 — S16 2009</p> <p>From this point, an unrecorded wood post, 2x3 ins., firmly set, projecting 3 ins. above the ground, with an iron pipe, 1/2 in. diam., projecting 17 ins. above the ground, set alongside, bears N. 67° W., 0.128 chs. dist. This position is not harmoniously related to surrounding corners and is not utilized in the course of this survey.</p>
19.90	Graded dirt road, 50 lks. wide, bears N. 30° W. and S. 30° E.
39.494	<p>The 1/4 sec. cor. of secs. 9 and 16, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 13 N., R. 28 E., executed under Group No. 670, with an iron pipe, 1 in. diam., set alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 3, 4, 9 and 10. N. 89°49'00" W., bet. secs. 4 and 9. Across broken land, covered with shadescale, cheat and bunch grass.</p>
20.108	<p>Point for the E 1/16 sec. cor. of secs. 4 and 9. POINT NOT MONUMENTED</p>
28.90	Barbed wire fence, steel posts, bears N. 40° W. and S. 40° E.
31.90	Graded dirt road, 50 lks. wide, bears N. 35° W. and S. 40° E.
34.80	Concrete lined irrigation ditch, 30 lks. wide, 5 ft. deep, drains S. 40° E.
	Thence continue across river bottom lands, through scattered cottonwoods and willows.
40.216	<p>The 1/4 sec. cor. of secs. 4 and 9, determined by person(s) unknown, monumented with an iron pipe, 1 in. diam., 30 ins. long, firmly set, projecting 10 ins. above the ground, with iron plumbing cap, no mks. visible. This position is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>T13N R28E S 4 1/4 <u> </u> S 9</p> <p>2009</p> <p>Bury iron pipe alongside the stainless steel post.</p> <hr/> <p>N. 89°46'40" W., beginning new measurement.</p>
8.80	Left bank of the Walker River, bears NE. and SW., thence across river, course SW.
9.90	Right bank of the Walker River, bears NE. and SW., leave river.
11.20	Graded dirt road, 25 lks. wide, parallels irrigation ditch.
11.50	Concrete lined irrigation ditch, 15 lks. wide, drains S. 25° E.
16.30	Graded dirt road, 25 lks. wide, bears N. and S.
20.045	Point for the W 1/16 sec. cor. of secs. 4 and 9.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p>S 4 W 1/16 <u> </u> S 9</p> <p>2009</p> <p>Cor. falls in center of a four-wheel drive trail, 10 lks. wide, bears NE. and SW.</p>
24.60	Graded dirt road, 25 lks. wide, bears N. 40° W. and S. 40° E.
35.50	Graded dirt road, 40 lks. wide, bears N. 10° W. and S. 10° E.
40.090	<p>The cor. of secs. 4, 5, 8 and 9, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 13 N., R. 28 E., executed under Group No. 670.</p> <hr/> <p>N. 0°05'40" W., bet. secs. 4 and 5.</p> <p>Across broken land, covered with shadecale, cheat and bunch grass.</p>
15.10	Barbed wire fence, wood and steel posts, bears N. 75° E. and S. 75° W.
19.10	Graded dirt road, 40 lks. wide, bears N. 50° W. and S. 50° E.
19.934	Point for the S 1/6 sec. cor. of secs. 4 and 5.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	POINT NOT MONUMENTED
22.60	Rim, bears NW. and SE., descend into River Canyon.
27.00	Right bank of the Walker River, bears NNW. and SE., thence across river, course SW.
27.629	Point for the original witness cor. for the 1/4 sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the position of the original corner. The witness corner serves no further function.
32.50	Right bank of the Walker River, bears NNE. and SSW., leave river, enter scattered cottonwoods and willows.
29.901	Point for the N-S 1/64 sec. cor. of secs. 4 and 5.
	POINT NOT MONUMENTED
39.868	The 1/4 sec. cor. of secs. 4 and 5, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, in a collar of stone, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 13 N., R. 28 E., executed under Group No. 670.
	<hr/>
	N. 0°05'40" W., beginning new measurement.
1.90	Right bank of the Walker River, bears NNW. and SSE., thence along river, course SSE.
4.00	Right bank of the Walker River, bears NNE. and SSW., leave river.
9.970	Point for the S-N 1/64 sec. cor. of secs. 4 and 5.
	POINT NOT MONUMENTED
13.00	Right bank of the Walker River, bears NW. and SE., thence along river, course SE.
19.940	Point for the N 1/16 sec. cor. of secs 4 and 5.
	POINT NOT MONUMENTED
23.70	Right bank of the Walker River, bears E. and SW., leave river.
27.20	Dirt road, 10 lks. wide, bears ENE. and WSW.
28.70	Graded dirt road, 15 lks. wide, bears N. 50° E. and S. 50° W.
39.989	The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., hereinbefore described.
	<hr/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°00'20" E., bet. secs. 31 and 32.</p> <p>Over mountainous terrain, covered with pinyon pine, sagebrush, cheat and bunch grass.</p>
14.20	Spur, slopes NE.
39.042	<p>The 1/4 sec. cor. of secs. 31 and 32, monumented with a granite stone, 21x7x6 ins., firmly set, projecting 10 ins. above the ground, mkd. 1/4 on the W. face, with a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13N R28E</p> <p>1/4</p> <p>S31 S32</p> <p>2009</p> </div> <p>Bury mkd. stone alongside the stainless steel post.</p> <hr/> <p>N. 0°08'10" E., beginning new measurement.</p>
19.70	Ravine, drains. NE.
25.40	Foot trail, 5 lks. wide, bears NE. and SW.
35.60	Foot trail, 5 lks. wide, bears NE. and SW.
40.332	<p>The cor. of secs. 29, 30, 31 and 32, determined on the E. side of a scattered mound of stone, 3 ft. base, 1/2 ft. high, with a granite stone, 18x8x6 ins., mkd. with 5 notches on one edge and 1 notch on an adjacent edge, lying loose on the downhill side of the mound.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13N R28E</p> <p>S30 S29</p> <hr/> <p>S31 S32</p> <p>2009</p> </div> <p>Bury mkd. stone alongside the stainless steel post.</p> <hr/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>S. 89°10'00" W., bet. secs. 29 and 32.</p> <p>Across mountainous terrain, covered with pinyon pine, sagebrush, shadescale, cheat and bunch grass.</p>
4.60	Spur, slopes NNE.
8.60	Ravine, drains. N.
20.50	Ravine, drains NE.
39.530	<p>The 1/4 sec. cor. of secs. 29 and 32, monumented with a granite stone, 16x6x6 ins., firmly set, projecting 6 ins. above the ground, with a mound of stone, 3 ft. base, 1 1/2 ft. high, N. of cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13N R28E</p> <p>S29</p> <p>1/4 ———</p> <p>S32</p> <p>2009</p> </div> <p>Bury mkd. stone alongside the stainless steel post.</p> <hr/> <p>S. 89°37'50" W., beginning new measurement.</p>
3.30	Spur, slopes NE.
23.90	Ravine, drains NE.
30.00	Graded dirt road, 10 lks. wide, bears N. and SSE.
39.00	Foot trail, 5 lks. wide, bears N. and S.
40.769	<p>The cor. of secs. 29, 30, 31 and 32.</p> <hr/> <p>N. 89°43'30" W., bet. secs. 30 and 31.</p> <p>Across mountainous terrain, covered with pinyon pine, sagebrush, cheat and bunch grass.</p>
0.90	Descend into deep ravine, NNE. and SSW.
4.40	Ravine, drains N.
39.10	Spur, slopes SE.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.973	<p>The 1/4 sec. cor. of secs. 30 and 31, monumented with a granite stone, 24x7x6 ins., firmly set, projecting 10 ins. above the ground, mkd. 1/4 on the N. face, with a mound, 3 ft. base, 2 ft. high, N. of cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13N R28E</p> <p>S30</p> <p>1/4 ———</p> <p>S31</p> <p>2009</p> </div> <p>Bury mkd. stone alongside the stainless steel post.</p> <hr/> <p>S. 89°41'40" W., beginning new measurement.</p>
38.947	<p>The cor. of secs. 30 and 31 only, on the W. bdy. of the Tp., monumented with stainless steel post, 2 1/2 ins. diam., firmly set flush with the top of a mound of stone, 3 ft. base, 1/2 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of the W. bdy. of T. 13 N., R. 28 E., executed under Group No. 855, from which the remaining original bearing trees</p> <p style="padding-left: 40px;">A dead standing pinyon pine, 10 ins. diam., bears S. 16 1/4° W., 15 1/2 lks. dist., with the 2008 scribe mk. X visible on an open blaze. (Record, S. 20° W., 11 lks.)</p> <p style="padding-left: 40px;">The rotted remains of the a tree, 9 ins. diam., bears N. 79° W., 25 lks. dist., with scribe mks. T13N R visible, the original position indeterminable. (Record, N. 73° W., 39 lks.)</p> <p>and the 2008 bearing objects</p> <p style="padding-left: 40px;">A chiseled X followed by the letters BO, bears S. 79°04' E., 38.1 lks. dist., mkd. on the top of an igneous outcrop, 6x5x2 ft. high, 1 ft. from NW. end.</p> <p style="padding-left: 40px;">A chiseled X followed by the letters BO, bears N. 48°42' W., 9.2 lks. dist., mkd. on a rock face, 2 1/2x3 1/2 ft., 1 ft. from W. end.</p> <hr/> <p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0°23'10" W., bet. secs. 29 and 30.</p> <p>Across mountainous terrain, covered with pinyon pine, sagebrush, cheat and bunch grass.</p>
1.50	<p>Descend into ravine, bears E. and SW.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
9.70	Graded dirt road, 10 lks. wide, bears ESE. and W.
11.80	Graded dirt road, 10 lks. wide, bears ENE. and SW., located in ravine, drains ENE.
38.60	Spur, slopes NE.
39.422	<p>The 1/4 sec. cor. of secs. 29 and 30, determined on the E. side of a mound of stone, 3 ft. base, 1 ft. high, with a granite stone, 24x8x5 ins., mkd. with a faint 1/4 on one face, lying loose on the downhill side of the mound.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13N R28E 1/4 S30 S29</p> <p>2009</p> </div> <p>Bury mkd. stone alongside the stainless steel.</p> <hr/> <p>N. 0°02'20" W., beginning new measurement.</p>
11.00	Ravine, drains NE.
12.10	Graded dirt road, 20 lks. wide, bears ENE. and SW.
13.10	Graded dirt road, 20 lks. wide, bears NE. and SW.
17.40	Power line, bears N. 87° W., and S. 87° E.
19.10	Graded dirt road, 20 lks. wide, bears NE. and SW.
39.828	<p>The cor. of secs. 19, 20, 29 and 30, determined on the E. side of mound of stone, 2 ft. base, 1 ft. high, with a granite stone, 20x8x6 ins., mkd. with 5 notches on one edge, and 2 notches on adjacent edge, lying loose on the downhill side of the mound.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13N R28E S19 S20 S30 S29</p> <p>2009</p> </div> <p>Bury mkd. stone alongside the stainless steel post.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From this cor., wood posts, each 6 ins. diam., projecting 6 ft. above ground, marking the perimeter of a communication site, bear S. 50°48'40" W., 19.580 chs. dist., S. 55°56'10" W., 25.204 chs. dist., S. 63°37'40" W., 18.369 chs. dist. and S. 65°56'10" W., 24.275 chs. dist.</p> <p>From this same cor., the NE cor. of a brick building, 8 ft. square, with cell phone tower, bears S. 76°21'30" W., 23.60 chs. dist., easterly side bears N. 15° E.</p> <hr/> <p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>S. 87°33'40" W., bet. secs. 20 and 29.</p> <p>Across mountainous terrain, covered with sagebrush, shadescale cheat and bunch grass.</p>
40.880	<p>The 1/4 sec. cor. of secs. 20 and 29, determined on the S. side of a mound of stone, 2 ft. base, 1/2 ft. high, with a granite stone, 17x7x6 ins., lying loose nearby, mkd. with a faint 1/4 on one face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13N R28E</p> <p>S20</p> <p>1/4 ———</p> <p>S29</p> <p>2009</p> </div> <p>Bury mkd. stone alongside the stainless steel post.</p> <hr/> <p>N. 89°55'40" W., beginning new measurement.</p>
10.30	Ravine, drains NNE.
12.70	Graded dirt road to communications site, 20 lks. wide, bears NNE. and SSW.
14.30	Power line, bears N. 27° E. and S. 27° W.
40.445	The cor. of secs. 19, 20, 29 and 30.
	<hr/> <p>S. 89°13'40" W., bet. secs. 19 and 30.</p> <p>Across mountainous terrain, covered with scattered pinyon pine, sagebrush, cheat and bunch grass.</p>
24.60	Spur, slopes NNW.
38.682	The 1/4 sec. cor. of secs. 19 and 30, monumented with a pinyon pine, 20 ins. diam., mkd. 1/4 S on partially healed blaze on N. face and a healed blaze on S. face.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>from which new bearing objects</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 70°51' E., 35.1 lks. dist., with brass cap mkd. RM 1/4 S19 23.2 FT TO COR 2009 and arrow pointing to the cor.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 0°03' E., 59.4 lks. dist., with brass cap mkd. RM 1/4 S30 39.2 FT TO COR 2009 and arrow pointing to the cor.</p> <hr/> <p>S. 88°47'10" W., beginning new measurement.</p>
1.60	Ravine, drains NNE.
17.80	Ravine, drains NE.
39.929	<p>The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set flush with the top of a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of the west boundary, T. 13 N., R. 28 E., executed under Group No. 855.</p> <hr/> <p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0°06'40" W., bet. secs. 19 and 20.</p>
26.90	Ravine, drains NE.
40.315	<p>The 1/4 sec. cor. of secs. 19 and 20, monumented with a granite stone, 22x6x5 ins., firmly set, projecting 10 ins. above the ground, mkd. with a faint 1/4 on W. face, with a mound of stone, 2 1/2 ft. base, 1 ft. high, W. of cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T13N R28E 1/4 S19 S20 2009</p> <p>Bury mkd. stone alongside the stainless steel post.</p> <hr/> <p>N. 0°11'20" W., beginning new measurement.</p>
0.30	Ravine, drains NE.
2.10	Ravine, drains NE.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS							
40.098	<p>The cor. of secs. 17, 18, 19 and 20, monumented with a granite stone, 18x6x5 ins., firmly set, projecting 7 ins. above the ground, mkd. with 5 notches on E. edge and 3 notches on S. edge, with a mound of stone, 2 ft. base, 1 ft. high, W. of cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T13N</td><td>R28E</td></tr> <tr> <td>S18</td><td>S17</td></tr> <tr> <td>S19</td><td>S20</td></tr> </table> <p>2009</p> </div> <p>Bury mkd. stone alongside the stainless steel post.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 17 and 20, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 13 N., R. 28 E., executed under Group No. 670, with a weathered redwood post, 4 ins. square, projecting 24 ins. above the ground, and a mound of stone, 2 ft. base, 1 ft. high, both on the N. side of cor.</p> <p>S. 89°04'30" W., bet. secs. 17 and 20.</p> <p>Across rolling land, covered with sagebrush, shadescale, cheat and bunch grass.</p>	T13N	R28E	S18	S17	S19	S20
T13N	R28E						
S18	S17						
S19	S20						
39.762	<p>The cor. of secs. 17, 18, 19 and 20.</p> <hr/> <p>S. 89°47'50" W., bet. secs. 18 and 19.</p> <p>Across broken land, covered with sagebrush, shadescale, cheat and bunch grass.</p>						
35.80	<p>Summit of line, falls on N. side of rock outcrop.</p>						
39.812	<p>The 1/4 sec. cor. of secs. 18 and 19, determined on the S. side of a mound of stone, 3 ft. base, 1 ft. high, with a basalt stone, 18x7x6 ins., mkd. 1/4 on one face, lying on top of the mound of stone.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>						

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>T13N R28E S18 1/4 — S19 2009</p> <p>Bury mkd. stone alongside the stainless steel.</p> <p>From this cor., a mineshaft, 10x10 ft. opening, bears N. 62° E., 1.35 chs. dist.</p> <hr/> <p>S. 89°23'20" W., beginning new measurement.</p> <p>0.50 Ravine, drains SW.</p> <p>2.50 Ravine, drains SW.</p> <p>30.55 Graded dirt road, 20 lks. wide, bears NE. and SW.</p> <p>38.676 The cor. of secs. 13, 18, 19 and 24, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set flush with the top of a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of the west boundary, T. 13 N., R. 28 E., executed under Group No. 855.</p> <hr/> <p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 0°02'00" E., bet. secs. 17 and 18.</p> <p>Across broken land, covered with sagebrush, shadescale, cheat and bunch grass.</p> <p>28.80 Graded dirt road, 15 lks. wide, bears WNW. and ESE.</p> <p>34.80 Dirt road, 10 lks. wide, bears NW. and SE., in wash, drains SE.</p> <p>40.112 The 1/4 sec. cor. of secs. 17 and 18, monumented with a granite stone, 18x6x5 ins., firmly set, projecting 7 ins. above the ground, mkd. 1/4 on W. face, with a mound of stone, 3 ft. base, 1 ft. high, W. of cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p>T13N R28E 1/4 S18 S17 2009</p> <p>Bury mkd. stone alongside the stainless steel.</p> <hr/>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°03'50" W., beginning new measurement.						
40.275	<p>The cor. of secs. 7, 8, 17 and 18, monumented with a granite stone, 24x12x8 ins., firmly set, projecting 8 ins. above the ground, mkd. with 5 notches on E. edge and 2 notches on N. edge. (Record, 4 notches on S. edge)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td>T13N</td><td>R28E</td></tr> <tr><td>S 7</td><td>S 8</td></tr> <tr><td>S18</td><td>S17</td></tr> </table> <p>2009</p> </div> <p>Bury mkd. stone alongside the stainless steel.</p> <p>Cor. is located on the crest of White Mountain.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 8 and 17, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 13 N., R. 28 E., executed under Group No. 670.</p> <p>S. 89°25'10" W., bet. secs. 8 and 17.</p> <p>Across broken land, covered with shadescale, cheat and bunchgrass.</p>	T13N	R28E	S 7	S 8	S18	S17
T13N	R28E						
S 7	S 8						
S18	S17						
39.946	<p>The cor. of secs. 7, 8, 17 and 18.</p> <hr/> <p>S. 89°37'50" W., bet. secs. 7 and 18.</p> <p>Across broken land, covered with shadescale, cheat and bunch grass.</p>						
12.60	Spur slopes SSW.						
38.40	Ravine, drains SSE.						
39.984	<p>Point for the 1/4 sec. cor. of secs. 7 and 18, at proportionate dist.; there is no remaining evidence of the position of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>						

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>T13N R28E S 7 1/4 — S18</p> <p>2009</p>
76.20	Dirt road, 15 lks. wide, bears N. and S.
78.359	<p>The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set flush with the top of a mound of stone, 3 ft. base, 1/2 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of the west boundary, T. 13 N., R. 28 E., executed under Group No. 855.</p> <hr/> <p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 0°13'40" E., bet. secs. 7 and 8.</p> <p>Across mountainous terrain, covered with sagebrush, shadescale, cheat and bunch grass.</p>
40.286	<p>The 1/4 sec. cor. of secs. 7 and 8, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set flush with the top of a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 13 N., R. 28 E., executed under Group No. 670.</p> <hr/> <p>From the cor. of secs. 5, 6, 7 and 8, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 13 N., R. 28 E., executed under Group No. 670, with a mound of stone, 2 ft. base, 1 ft. high, W. of cor.</p> <p>S. 89°45'00" W., bet. secs. 6 and 7.</p> <p>Across rolling land, covered with sagebrush, shadescale, cheat and bunch grass.</p>
8.50	Asphalt remains of old U.S. Highway No. 95 Alternate, 30 lks. wide, bears N. 43° W. and S. 43° E.
14.70	Powerline, parallels old U.S. Highway No. 95 Alternate.
39.985	<p>The 1/4 sec. cor. of secs. 6 and 7, monumented with a granite stone, 16x10x5 ins., firmly set, projecting 9 ins. above the ground, mkd. 1/4 on N. face, with a scattered mound of stone, 3 1/2 ft. base, 1 ft. high, N. of cor.</p> <p>At the corner point</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T13N R28E S 6 1/4 — S 7</p> <p style="text-align: center;">2009</p> <p>Bury mkd. stone alongside the stainless steel.</p> <hr/> <p>S. 89°52'20" W., beginning new measurement.</p> <p>Begin posting the boundary of the Walker River Indian Reservation with steel sign posts.</p> <p>10.60 Graded dirt road, 20 lks. wide, bears NE. and SW.</p> <p>13.20 Braided wash, 2 chs. wide, drains NE.</p> <p>32.452 Intersect line 2-3, Mineral Survey No. 4542, Mohawk lode and point for a closing cor., hereinafter described, at a point from which Cor. No. 2, Mineral Survey No. 4542, hereinafter described, bears N. 5°02'20" E., 0.073 chs. dist.</p> <p>Discontinue posting west of this intersection.</p> <p>38.317 The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set flush with the top of a mound of stone, 3 ft. base, 1/2 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of the west boundary, T. 13 N., R. 28 E., executed under Group No. 855.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISION-OF-SECTION LINES OF SECTION 21, T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Restoring a Portion of the Survey Executed by J.A. Mack, Cadastral Surveyor, in 1986-87</p> <hr/> <p>From the point for the C-N 1/16 sec. cor. of sec. 21, at proportionate dist.; there is no remaining evidence of the position of the 1986 corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 21,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div style="text-align: center;"> $\begin{array}{c} C \\ N \ 1/16 \quad \quad S21 \\ C \end{array}$ </div> <div style="text-align: center;">2009</div> <p>From this point, the center 1/4 sec. cor. of sec. 21, bears S. 0°09'20" E., 19.927 chs. dist., monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above a collar of stone, with aluminum cap mkd. as described in the field notes of the dependent resurvey of the subdivision of section 21, T. 13 N., R. 28 E., executed under Group No. 635.</p> <p>N. 0°09'20" W., on a portion of the N-S center line of sec. 21.</p> <p>Across rolling land, covered with shadescale, cheat and bunch grass.</p> <p>19.927 The 1/4 sec. cor. of secs. 16 and 21, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines, T. 13 N., R. 28 E., executed under Group No. 635.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 21 and 22.</p> <p>N. 89°54'10" W., on a portion of the E-W center line of sec. 21.</p> <p>Across level farmland, along barbed wire fence.</p> <p>9.981 Point for the C-E-E 1/64 sec. cor. of sec. 21, at proportionate dist.; there is no remaining evidence of the position of the 1986 corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} E-E \ 1/64 \\ C \text{---} C \\ S21 \end{array}$ </div> <div style="text-align: center;">2009</div> <p>Cor. is located on S. side of barbed wire fence, bears E. and W.</p> <p>19.962 The C-E 1/16 sec. cor. of sec. 21, monumented with an aluminum post, 2 1/2 ins. diam., recovered 10 ins. below the surface of the ground, with corroded aluminum cap illegibly mkd., encircled in a buried mound of stone.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 21,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>E 1/16 C—C S21 2010</p> <p>Bury the aluminum post alongside the stainless steel post.</p> <p>Cor. is located on E. side of the cor. of fences, extending N., S. and E.</p> <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISION-OF-SECTION LINES OF SECTION 22, T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Restoring a Portion of the Survey Executed by J.A. Mack, Cadastral Surveyor, in 1986-87</p> <hr/> <p>From the C-S-S 1/64 sec. cor. of sec. 22, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. as described in the field notes of the subdivision of section 22, T. 13 N., R. 28 E., executed under Group No. 635.</p> <p>Cor. is located in fence, bears E. and W.</p> <p>N. 0°11'10" W., on a portion of the N-S center line of sec. 22.</p> <p>Across cultivated land.</p> <p>9.991 Point for the C-S 1/16 sec. cor. of sec. 22, at proportionate dist.; there is no remaining evidence of the position of the 1986 corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;"> C S 1/16 S22 C </p> <p style="text-align: center;">2009</p> <p>19.982 Point for the C-N-S 1/64 sec. cor. of sec. 22, at proportionate dist.; there is no remaining evidence of the position of the 1986 corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
--------	---

DEPENDENT RESURVEY OF A PORTION OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 22,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div style="text-align: center;"> $\begin{array}{c} \text{C} \\ \text{N-S } 1/64 \quad \quad \text{S22} \\ \text{C} \end{array}$ <p>2009</p> </div>
29.973	<p>The center 1/4 sec. cor. of sec. 22, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. as described in the field notes of the subdivision of section 22, T. 13 N., R. 28 E., executed under Group No. 635.</p>
	<hr/> <p>From the C-S-N 1/64 sec. cor. of sec. 22, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. as described in the field notes of the subdivision of section 22, T. 13 N., R. 28 E., executed under Group No. 635.</p> <p>N. 0°11'50" W., continuing on a portion of the N-S center line of sec. 22.</p> <p>Across level cultivated land.</p>
10.028	<p>The C-N 1/16 sec. cor. of sec. 22, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. as described in the field notes of the subdivision of section 22, T. 13 N., R. 28 E., executed under Group No. 635.</p>
	<hr/> <p>N. 0°10'50" W., beginning new measurement.</p>
10.001	<p>The C-N-N 1/64 sec. cor. of sec. 22, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. as described in the field notes of the subdivision of section 22, T. 13 N., R. 28 E., executed under Group No. 635.</p>
	<hr/> <p>From the C-E-E 1/64 sec. cor. of sec. 22, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. as described in the field notes of the subdivision of section 22, T. 13 N., R. 28 E., executed under Group No. 635.</p> <p>N. 89°51'40" W., on a portion of the E-W center line of sec. 22.</p> <p>Across level cultivated land.</p>
9.70	<p>Barbed wire fence, bears N. and S.</p>
9.80	<p>Graded dirt road, 25 lks. wide, bears N. and S.</p>
10.044	<p>The C-E 1/16 sec. cor. of sec. 22, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. as described in the field notes of the subdivision of section 22, T. 13 N., R. 28 E., executed under Group No. 635.</p>

DEPENDENT RESURVEY OF A PORTION OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 22,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the C-W-E 1/64 sec. cor. of sec. 22, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with aluminum cap mkd. as described in the field notes of the subdivision of section 22, T. 13 N., R. 28 E., executed under Group No. 635.</p> <p>N. 89°52'00" W., on a portion of the E-W center line of sec. 22.</p> <p>Across level cultivated land.</p>
10.041	<p>The center 1/4 sec. cor. of sec. 22.</p> <hr/> <p>From the C-S-SW 1/64 sec. cor. of sec. 22, monumented with an unrecorded rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 2 ins. above the ground, with plastic cap mkd. OWENS ENG PLS 3090, and is accepted as a careful and faithful reestablishment of the 1986 position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>S22 C-S-SW 1/64</p> <p>2009</p> </div> <p>Deposit the rebar inside the stainless steel post.</p> <p>From this point, the W 1/16 sec. cor. of secs. 22 and 27, bears S. 0°20'10" E., 10.001 chs. dist., monumented with a faint X chiseled on the E. sidewall of a concrete lined irrigation ditch, 1 ft. above the bottom, from which the remaining 1986 reference monument</p> <div style="margin-left: 40px;"> <p>An aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, bears N. 68 3/4° W., 45.5 lks. dist., with aluminum cap mkd. RM W1/16 S22 30 FT 1986 and an arrow pointing to the cor.</p> </div> <p>and a new bearing object</p> <div style="margin-left: 40px;"> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 30°09' W., 58.9 lks. dist., with brass cap mkd. RM W1/16 S27 38.9 FT TO COR 2010 and an arrow pointing to the cor.</p> </div> <p>Cor. is located on the E. sidewall of a concrete lined irrigation ditch, 20 lks. wide, 4 ft. deep, drains S. 15° E.</p> <p>N. 0°20'10" W., on a portion of the N-S center line of the SW1/4 of sec. 22.</p> <p>Across cultivated land.</p>

DEPENDENT RESURVEY OF A PORTION OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 22,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
9.95	Concrete lined irrigation ditch, 10 lks. wide, 3 ft. deep, drains E.
10.001	Point for the SW 1/16 sec. cor. of sec. 22, at intersection with the E-W center line of the SW1/4; there is no remaining evidence of the position of the 1986 corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. SW 1/16 S22 2009
20.001	Point for the C-N-SW 1/64 sec. cor. of sec. 22, at proportionate dist.; there is no remaining evidence of the position of the 1986 corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. S22 C-N-SW 1/64 2009
21.00	The SE. cor. of a cemetery, thence along E. side.
27.30	Leave cemetery, across cultivated land.
30.001	The C-W 1/16 sec. cor. of sec. 22, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. as described in the field notes of the subdivision of section 22, T. 13 N., R. 28 E., executed under Group No. 635. Cor. is located 0.15 chs. W. of a fence, bears N. and S. <hr/> From the C-S 1/16 sec. cor. of sec. 22. N. 89°58'50" W., on a portion of the E-W center line of the SW1/4 of sec. 22. Across cultivated land, along N. side of concrete lined irrigation ditch.
10.046	Point for the C-E-SW 1/64 sec. cor. of sec. 22, at proportionate distance; there is no remaining evidence of the position of the 1986 corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

DEPENDENT RESURVEY OF A PORTION OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 22,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>S22 C-E-SW 1/64</p> <p>2009</p>
20.092	The SW 1/16 sec. cor. of sec. 22.
30.138	<p>The C-W-SW 1/64 sec. cor. of sec. 22, monumented with a railroad spike, set flush with the asphalt surface, from which the 1986 reference monuments</p> <p>An aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, bears S. 44 1/2° E., 81.8 lks. dist., with aluminum cap mkd. RM C-W-SW 1/64 S22 54 FT 1986 and an arrow pointing to the cor.</p> <p>An aluminum post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above the ground, bears N. 44 1/2° W., 81.8 lks. dist., with aluminum cap mkd. XRM 1986. Add the mks. 54.0 FT and an arrow pointing to cor. on the aluminum cap.</p> <p>Cor. falls in the asphalt surface of Vista Drive, 35 lks. wide, bears N. and S.</p> <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISION-OF-SECTION LINES OF SECTION 26, T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Restoring a Portion of the Survey Executed by J.A. Mack, Cadastral Surveyor, in 1986-87</p> <hr/> <p>From the witness C-E 1/16 sec. cor. of sec. 26, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with aluminum cap mkd. as described in the field notes of the subdivision of section 26, T. 13 N., R. 28 E., executed under Group No. 635.</p> <p>N. 89°48'20" W., on the E-W center line of sec. 26.</p> <p>Across river bottom land, covered with cottonwood trees, willows and grass.</p>
1.078	<p>True point for the C-E 1/16 sec. cor. of sec. 26, determined at proportionate dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p>E 1/16 C——C S26</p> <p>2010</p> <p>Point falls on the accreted left bank of Walker River.</p>

DEPENDENT RESURVEY OF A PORTION OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 26,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
2.00	Left bank of the Walker River, bears NNW. and SE., thence across river, course SE.
4.40	Right bank of the Walker River, bears NNW. and SE.
21.164	<p>The center 1/4 sec. cor. of sec. 26, monumented with a railroad spike, loosely set, projecting 4 ins. above the asphalt surface, from which the 1986 reference monuments</p> <p>An aluminum post, 2 1/2 ins. diam., firmly set in a collar of stone, bears S. 45° E., 40.9 lks. dist., with aluminum cap mkd. RM C1/4 S26 27 FT 1986 and an arrow pointing to the cor.</p> <p>An aluminum post, 2 1/2 ins. diam., firmly set in a collar of stone, bears S. 45° W., 25.8 lks. dist., with aluminum cap mkd. XRM 1986. Add the mks. 17.0 FT and an arrow pointing to the cor. on the aluminum cap.</p> <p>At the corner point</p> <p>Set a copper coated steel rod, 1/2 in. diam., 6 ins. long, flush with the asphalt surface, with brass cap, 1 1/2 ins. diam., mkd.</p> <p>BLM T13N R28E C 1/4 S26</p> <p>2010</p> <p>Cor. is located in Mesquite Drive, asphalt-surfaced, 35 lks. wide, bears N. and S.</p> <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISION-OF-SECTION LINES OF SECTION 27, T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Restoring a Portion of the Survey Executed by J.A. Mack, Cadastral Surveyor, in 1986-87</p> <hr/> <p>From the center 1/4 sec. cor. of sec. 27, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with aluminum cap mkd. as described in the field notes of the subdivision of section 27, T. 13 N., R. 28 E., executed under Group No. 635.</p> <p>From this cor., the cor. of barbed wire fences, extending S. and WNW., bears NW., 0.02 chs. dist.</p> <p>N. 0°03'50" W., on a portion of the N-S center line of sec. 27.</p> <p>Across level farmland, along E. side of barbed wire fence.</p>


DEPENDENT RESURVEY OF A PORTION OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 27,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.044	<p>Point for the C-N 1/16 sec. cor. of sec. 27, at proportionate dist.; the 1986 aluminum post was found lying horizontal, 30 ins. below the surface of the ground, original position indeterminate.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \text{C} \\ \text{N } 1/16 \quad \quad \text{S } 27 \\ \text{C} \end{array}$ <p>2009</p> </div> <p>Bury aluminum post alongside the stainless steel post.</p> <p>From this point, the 1/4 sec. cor. of secs. 22 and 27 bears N. 0°03'50" W., 20.044 chs. dist., monumented with a railroad spike, set flush with the asphalt surface; the 1986 aluminum posts set for reference monuments were found lying loose along roadside, original positions indeterminate.</p> <p>from which new bearing objects</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 52°20' W., 77.6 lks. dist., with brass cap mkd. RM 1/4 S27 51.2 FT TO COR 2009 and arrow pointing to the cor. Reference is located in barbed wire fence, bears E. and W.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 51°04' W., 68.3 lks. dist., with brass cap mkd. RM 1/4 S22 45.1 FT TO COR 2009 and arrow pointing to the cor. Reference is located in barbed wire fence, bears E. and W.</p> <p>Cor. is located in the asphalt surface of Farm Road, 35 lks. wide, bears E. and W.</p>
10.096	<p>From the center 1/4 sec. cor. of sec. 27.</p> <p>S. 89°57'30" W., on a portion of the E-W center line of sec. 27.</p> <p>Along N. side of irrigation ditch, 10 lks. wide, 3 ft. deep, drains E.</p> <p>Point for the C-E-W 1/64 sec. cor. of sec. 27, at proportionate dist.; the 1986 aluminum post, 2 1/2 ins. diam., 30 ins. long, with aluminum cap mkd. as described in the field notes of the subdivision of section 27, T. 13 N., R. 28 E., executed under Group No. 635, was found in a disturbed position, projecting at an angle from the N. embankment of irrigation ditch, original position indeterminate.</p>

DEPENDENT RESURVEY OF A PORTION OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 27,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Reset aluminum post, 20 ins. in the ground, over a plastic-encased magnet, and in a collar of stone. Add the marks 2009 to the aluminum cap.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 40°55' E., 24.3 lks. dist., with brass cap mkd. RM C-E-W 1/64 S27 16.0 FT TO COR 2009 and arrow pointing to the cor.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 46°07' E., 80.9 lks. dist., with brass cap mkd. RM C-E-W 1/64 S27 53.4 FT TO COR 2009 and arrow pointing to the cor.</p> <p>11.05 U.S. Highway No. 95 Alternate, asphalt surfaced, 50 lks. wide, bears N. 40° W. and S. 40° E.</p> <p>11.90 Barbed wire fence, parallels highway, thence along irrigation ditch 8 lks. wide, 3 ft. deep.</p> <p>16.15 Floodgate, between an irrigation ditch, 8 lks. wide, 3 ft. deep drains E., and an irrigation ditch, 12 lks. wide, 5 ft. deep, drains SSW.</p> <p>19.00 Graded dirt road, 10 lks. wide, bears NNW. and SSE.</p> <p>20.192 The C-W 1/16 sec. cor. of sec. 27, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with aluminum cap mkd. as described in the field notes of the subdivision of section 27, T. 13 N., R. 28 E., executed under Group No. 635.</p> <p>Cor. is located on E. side of graded dirt road, 25 lks. wide, bears N. and S.</p> <hr/> <p>From the C-N 1/16 sec. cor. of sec. 27.</p> <p>S. 89°57'30" W., on a portion of the E-W center line of the NW1/4 sec. 27.</p> <p>Across level farmland, along barbed wire fence and irrigation ditch.</p> <p>9.906 Point selected for the witness C-E-NW 1/64 sec. cor. of sec. 27; the 1986 aluminum post for the true point was found laying loose, original position indeterminate.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
--------	---

DEPENDENT RESURVEY OF A PORTION OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 27,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div style="text-align: center;"> WC C-E-NW 1/64  S27 2009 </div> <p>Bury the aluminum post alongside the stainless steel post.</p> <p>10.059 True point for the C-E-NW 1/64 sec. cor. of sec. 27, falls on N. embankment of irrigation ditch, 10 lks. wide, 4 ft. deep, drains E., where it is impractical to establish a permanent monument.</p> <p>14.25 Concrete lined irrigation ditch, 20 lks. wide, 4 ft. deep, drains S., thence across nearly level land, covered with shadescale, cheat and bunch grass.</p> <p>20.118 The NW 1/16 sec. cor. of sec. 27, monumented with an aluminum post, 2 1/2 ins. diam., firmly set flush with the ground, with aluminum cap mkd. as described in the field notes of the subdivision of the northwest 1/4 of section 27, T. 13 N., R. 28 E., executed under Group No. 635.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISION-OF-SECTION LINES OF SECTION 36, T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Restoring a Portion of the Survey Executed by J.A. Mack, Cadastral Surveyor, in 1986-87</p> <hr/> <p>From the true point for the E 1/16 sec. cor. of secs. 1 and 36, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°06'40" E., on the N-S center line of the SE1/4 of sec. 36.</p> <p>Across the Walker River.</p> <p>1.80 Left bank of the Walker River, bears NW. and SSE.</p> <p>Thence across nearly level land, covered with scattered cottonwoods, shadescale, cheat and bunch grass and along barbed wire fence.</p> <p>19.438 Intersect the southwesterly right-of-way line of the Southern Pacific Railroad, bears N. 54°37.9' W. and S. 54°37.9' E.</p> <p>20.016 Point for the SE 1/16 sec. cor. of sec. 36, at intersection with the E-W center line of the SE1/4; there is no remaining evidence of the position of the 1986 corner.</p> <p>Set a copper coated steel rod, 1/2 in. diam., 24 ins. long, flush with the surface of the ground, at SW edge of asphalt surface, with with brass cap, 1 1/2 ins. diam., mkd.</p>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 36,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>BLM SE 1/16 S36</p>
	<p>2009</p>
	<p>from which</p>
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 44°25' E., 77.7 lks. dist., with brass cap mkd. RM SE1/16 S36 51.3 FT TO COR 2009 and arrow pointing to the cor.</p>
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 41°54' E., 62.5 lks. dist., with brass cap mkd. RM SE1/16 S36 41.2 FT TO COR 2009 and arrow pointing to the cor.</p>
20.35	<p>Lake Pasture Road, asphalt surfaced, 30 lks. wide, bears N. 55° W. and S. 55° E.</p>
21.294	<p>Center line of the Southern Pacific Railroad track, bears N. 54°37.9' W. and S. 54°37.9' E.</p>
23.150	<p>Intersect the northeasterly right-of-way line of the Southern Pacific Railroad, bears N. 54°37.9' W. and S. 54°37.9' E.</p>
40.028	<p>The C-E 1/16 sec. cor. of sec. 36, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. as described in the field notes of the subdivision of section 36, T. 13 N., R. 28 E., executed under Group No. 635.</p>
	<p>From the C-E-SE 1/64 sec. cor. of sec. 36, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. as described in the field notes of the subdivision of the southeast 1/4 of section 36, T. 13 N., R. 28 E., executed under Group No. 635.</p>
	<p>From this cor., the cor. of barbed wire fences, extending N. and E., bears N. 50° W., 0.38 chs. dist.</p>
	<p>S. 89°58'50" W., on a portion of the E-W center line of the SE1/4 of sec. 36.</p>
	<p>Along graded dirt, 30 lks. wide, bears E. and W.</p>
5.590	<p>Intersect the northeasterly right-of-way line of the Southern Pacific Railroad, bears N. 54°37.9' W. and S. 54°37.9' E.</p>
6.255	<p>Point for the 1/4096 sec. cor. of sec. 36, on the E-W center line of the SE1/4.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of a dirt road, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 36,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	1/4096
	2009
8.206	Center line of the Southern Pacific Railroad track, bears N. 54°37.9' W. and S. 54°37.9' E.
9.50	Lake Pasture Road, asphalt surfaced, 30 lks. wide, bears N. 55° W. and S. 55° E.
10.008	The SE 1/16 sec. cor. of sec. 36.
10.822	Intersect the southwesterly right-of-way line of the Southern Pacific Railroad, bears N. 54°37.9' W. and S. 54°37.9' E.
20.018	The C-W-SE 1/64 sec. cor. of sec. 36, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with aluminum cap mkd. as described in the field notes of the subdivision of the southeast 1/4 of section 36, T. 13 N., R. 28 E., executed under Group No. 635.
	<p>From the SW 1/16 sec. cor. of sec. 36, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with aluminum cap mkd. as described in the field notes of the subdivision of the southwest 1/4 of section 36, T. 13 N., R. 28 E., executed under Group No. 635.</p> <p>S. 89°59'50" W., on a portion of the E-W center line of the SW 1/4 of sec. 36.</p> <p>Across river bottom lands, covered with scattered cottonwoods, shadescale, cheat and bunch grass.</p>
5.70	Leave river bottom lands, thence across nearly level land covered through shadescale.
9.949	The C-W-SW 1/64 sec. cor. of sec. 36, monumented with an unrecorded aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with a mound of stone, 2 ft. base, 1 ft. high, W. of cor., with a standard Bureau of Land Management aluminum cap mkd.
	<p style="text-align: center;">C-W-SW 1/64 S36 1986</p>
	S. 89°58'10" W., beginning new measurement.
9.961	The S 1/16 sec. cor. of secs. 35 and 36, determined at the intersection of record distances from the 1986 reference monuments
	<p>An aluminum post, 2 1/2 ins. diam., firmly set in a collar of stone, bears N. 51 1/2° E., 90.9 lks. dist., with aluminum cap mkd. RM S 1/16 S36 60 FT 1986 and an arrow pointing to the cor.</p>

DEPENDENT RESURVEY OF A PORTION OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 36,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>An aluminum post, 2 1/2 ins. diam., firmly set in a collar of stone, bears N. 48 1/4° W., 66.7 lks. dist., with aluminum cap mkd. RM S 1/16 S35 44 FT 1986 and an arrow pointing to the cor.</p> <p>At the corner point</p> <p>Set a PK nail flush with asphalt surface.</p> <p>Cor. is located in U.S. Highway No. 95, asphalt surfaced, 50 lks. wide, bears N. and S.</p> <hr/> <p>DEPENDENT RESURVEY OF INDIAN ALLOTMENT NO. 108, IDENTICAL WITH THE SW1/4NE1/4SW1/4 AND NW1/4SE1/4SW1/4 OF SECTION 23, T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Restoring a Portion of the Survey Executed by E. Voight, U.S. Cadastral Engineer, in 1922</p> <hr/> <p>From the point for the NE. cor. of Indian Allotment No. 108, identical with the NE-SW 1/64 sec. cor. of sec. 23, hereinafter described.</p> <p>Thence N. 89°48'00" W., on the N. bdy. of Indian Allotment No. 108, identical with the W 1/2 of the E-W center line of the NE1/4SW1/4 of sec. 23.</p> <p>10.051 Point for the NW. cor. of Indian Allotment No. 108, identical with C-N-SW 1/64 sec. cor. of sec. 23, hereinafter described.</p> <hr/> <p>Thence S. 0°00'40" W., on the W. bdy. of Indian Allotment No. 108, identical with a portion of the N-S center line of the SW1/4 of sec. 23.</p> <p>9.980 The point for the SW 1/16 sec. cor. of sec. 23, hereinafter described.</p> <p>19.960 The point for the SW. cor. of Indian Allotment No. 108, identical with C-S-SW 1/64 sec. cor. of sec. 23, hereinafter described.</p> <hr/> <p>Thence S. 89°45'50" E., on the S. bdy. of Indian Allotment No. 108, identical with the W 1/2 of the E-W center line of the SE1/4SW1/4 of sec. 23.</p> <p>10.036 The SE. cor. of Indian Allotment No. 108, identical with the SE-SW 1/64 sec. cor. of sec. 23, hereinafter described.</p> <hr/> <p>Thence N. 0°03'20" E., on the E. bdy. of Indian Allotment No. 108, identical with the N 1/2 of the N-S center of the SE1/4SW1/4 of sec. 23.</p>
--------	--

DEPENDENT RESURVEY OF INDIAN ALLOTMENT NO. 108,
IDENTICAL WITH THE SW1/4NE1/4SW1/4 AND NW1/4SE1/4SW1/4 OF
SECTION 23, T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
9.983	Point for the C-E-SW 1/64 sec. cor. of sec. 23, hereinafter described.
	<hr/> <p>Thence N. 0°03'20" E., continuing on the E. bdy. of Indian Allotment No. 108, identical with the S 1/2 of the NE1/4SW1/4 of sec. 23.</p>
9.983	The NE. cor. of Indian Allotment No. 108, identical with the NE-SW 1/64 sec. cor. of sec. 23, and point of beginning.
	<hr/> <p>DEPENDENT RESURVEY OF A PORTION OF INDIAN ALLOTMENT NO. 493, IDENTICAL WITH THE N 1/2SW1/4NE1/4 OF SECTION 26, T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>
	<p>Restoring a Portion of the Survey Executed by E. Voight, U.S. Cadastral Engineer, in 1922 and a Portion of the Resurvey Executed by J.A. Mack, in 1986-87</p> <hr/>
	<p>From the NE. cor. of Indian Allotment No. 493, identical with the NE 1/16 sec. cor. of sec. 26, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of the N1/2SW1/4NE1/4 of section 26, identical with Indian Allotment No. 493, T. 13 N., R. 28 E., executed under Group No. 635.</p>
	<p>Thence N. 89°46'50" W., on the N. bdy. of Indian Allotment No. 493, identical with the W 1/2 of the E-W center line of the NE1/4 of sec. 26.</p>
0.50	Dirt road, parallels concrete irrigation ditch.
1.44	Barbed wire fence, bears NW. and SE.
3.50	Leave broken land, thence across level land and along N. side of cultivated field and barbed wire fence.
9.939	<p>Point for the C-W-NE 1/64 sec. cor. of sec. 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">S26 C-W-NE 1/64 2009</p>
19.878	The NW. cor. of Indian Allotment No. 493, identical with the C-N 1/16 sec. cor. of sec. 26, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of the N1/2SW1/4NE1/4 of section 26,

DEPENDENT RESURVEY OF A PORTION OF INDIAN ALLOTMENT NO. 493,
 IDENTICAL WITH THE N 1/2SW1/4NE1/4 OF SECTION 26,
 T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>identical with Indian Allotment No. 493, T. 13 N., R. 28 E., executed under Group No. 635.</p> <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4542, TPS. 13 N., RS. 27 AND 28 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Restoring a Portion of the Survey Executed by R.A. Stewart, U.S. Mineral Surveyor, in 1922</p> <hr/> <p>MOHAWK LODGE</p> <p>From Cor. No. 2, Mineral Survey No. 4542, Mohawk lode, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set flush with the top of a mound of stone, 3 ft. base, 1/2 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of Mineral Survey No. 4542, Tps. 13 N., Rs. 27 and 28 E., executed under Group No. 855.</p> <p>Thence S. 5°02'20" W., on line 2-3, Mineral Survey No. 4542, Mohawk lode.</p> <p>0.073 Intersect the line bet. secs. 6 and 7.</p> <p>Point for a closing cor. of secs. 6 and 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13N R28E</p> <p>MS4542 C / C S 6</p> <hr style="width: 50%; margin: auto;"/> <p>MOH / S 7</p> <p>2009</p> </div> <p>From this point, the cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., bears S. 89°52'20" W., 5.865 chs. dist., hereinbefore described.</p> <p>22.726 Cor. No. 3, Mineral Survey No. 4542, Mohawk lode, monumented with a weathered redwood post, 4 ins. square, 5 1/2 ft. long, loosely set, projecting 4 1/2 ft. above the ground, mkd. 3 4542 M visible, with a scattered mound of stone, 3 ft. base, 1/2 ft. high, N. of cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
--------	---

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4542,
TPS. 13 N., RS. 27 AND 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<div data-bbox="841 289 1076 449"> <p>4542 MOH 3</p> <p>T13N R28E S 7</p> <p>2009</p> </div> <p>Bury wood post alongside the stainless steel post.</p> <hr/> <p>SUBDIVISION OF SECTION 4, T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 4 and 9. N. 0°06'10" E., on the N-S center line of sec. 4. Across river bottom lands, covered with scattered cottonwoods, shadescale, cheat and bunch grass.</p> <p>5.20 Concrete lined irrigation ditch, 20 lks. wide, 4 ft. deep, drains S. 45° E.</p> <p>8.20 Graded dirt road, 20 lks. wide, bears N. 70° W. and S. 60° E., leave scattered cottonwood trees.</p> <p>9.980 Point for the C-S-S 1/64 sec. cor. of sec. 4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="792 1182 1011 1308"> <p>S-S 1/64 $\begin{array}{c} C \\ \\ C \end{array}$ S 4</p> <p>2009</p> </div> <p>10.20 Graded dirt road, 30 lks. wide, bears N. 30° W. and S. 30° E.</p> <p>14.10 Barbed wire fence, bears N. 30° W. and S. 30° E.</p> <p>16.50 Leave river bottom lands, thence across broken lands.</p> <p>19.960 Point for the C-S 1/16 sec. cor. of sec. 4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="821 1654 1011 1780"> <p>S 1/16 $\begin{array}{c} C \\ \\ C \end{array}$ S 4</p> <p>2009</p> </div> <p>29.00 Thence across rolling lands.</p> <p>29.940 Point for the C-N-S 1/16 sec. cor. of sec. 4.</p>

SUBDIVISION OF SECTION 4,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	POINT NOT MONUMENTED
39.920	Point for the center 1/4 sec. cor. of sec. 4, at intersection with the E-W center line. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T13N R28E C 1/4 S 4 2009
59.878	Point for the C-N 1/16 sec. cor. of sec. 4. POINT NOT MONUMENTED
69.857	Point for the C-N-N 1/64 sec. cor. of sec. 4. POINT NOT MONUMENTED
79.896	The 1/4 sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp. <hr/> From the 1/4 sec. cor. of secs. 3 and 4. N. 89°51'10" W., on the E-W center line of sec. 4. Across rolling land, covered with shadescale, cheat and bunch grass.
1.60	Graded dirt road, 50 lks. wide, bears N. 20° W. and S. 20° E.
40.107	The center 1/4 sec. cor. of sec. 4.
50.162	Point for the C-E-W 1/64 sec. cor. of sec. 4. POINT NOT MONUMENTED
60.217	Point for the C-W 1/16 sec. cor. of sec. 4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. W 1/16 C ——— C S 4 2009
64.30	Descend into river bottom lands, bears NW. and SE.
70.272	Point for the C-W-W 1/64 sec. cor. of sec. 4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

SUBDIVISION OF SECTION 4,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">W-W 1/64 C——C S 4</p> <p style="text-align: center;">2009</p>
72.80	Left bank of the Walker River, bears NNW. and SSE., thence across river, course SSE.
73.60	Right bank of the Walker River, bears NW. and SSE.
80.327	The 1/4 sec. cor. of secs. 4 and 5.
	<hr/> <p>From the W 1/16 sec. cor. of secs. 4 and 9.</p> <p>N. 0°00'30" E., on the N-S center line of the SW1/4 of sec. 4.</p> <p>Across broken land, covered with shadescall, cheat and bunch grass.</p>
7.50	Graded dirt road, 15 lks. wide, bears NW. and SE., thence across river bottom lands, covered with scattered cottonwoods, willows, shadescall, cheat and bunch grass.
9.974	Point for the C-S-SW 1/64 sec. cor. of sec. 4.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 4 C-S-SW 1/64</p> <p style="text-align: center;">2009</p>
10.70	Right bank of the Walker River, bears NW. and SE., thence across river, course SE.
12.40	Left bank of the Walker River, bears NW. and SE.
19.948	Point for the SW 1/16 sec. cor. of sec. 4, at intersection with the E-W center line of the SW1/4.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SW 1/16 S 4</p> <p style="text-align: center;">2009</p>
	Cor. is located on a dirt levy, 50 lks. wide, 4 ft. high, bears NW. and SE.
29.921	Point for the C-N-SW 1/64 sec. cor. of sec. 4.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

SUBDIVISION OF SECTION 4,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">S 4 C-N-SW 1/64 2009</p>
30.00	Barbed wire fence, bears E. and W.
39.894	The C-W 1/16 sec. cor. of sec. 4.
	<hr/> <p>From the C-S 1/16 sec. cor. of sec. 4. N. 89°49'00" W., on the E-W center line of the SW1/4 of sec. 4. Across river bottom land, covered with shadescall, cheat and bunch grass.</p>
3.60	Barbed wire fence, steel posts, bears N. 30° W. and S. 30° E.
5.30	Fork in graded dirt roads, 50 lks. wide, bears WNW., NW. and SE., thence through scattered cottonwoods.
9.00	Dirt road, 15 lks. wide, bears NE. and SE.
10.039	Point for the C-E-SW 1/64 sec. cor. of sec. 4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<p style="text-align: center;">S 4 C-E-SW 1/64 2009</p>
20.078	The SW 1/16 sec. cor. of sec. 4.
29.70	Left bank of the Walker River, bears N. and SE., thence across river, course SE.
30.117	Point for the C-W-SW 1/64 sec. cor. of sec. 4, falls in river where it is impractical to establish a permanent monument.
30.70	Right bank of the Walker River, bears N. and SE.
40.156	The point for the S 1/16 sec. cor. of secs. 4 and 5.
	<hr/> <p>From the C-E-SW 1/64 sec. cor. of sec. 4. N. 0°03'20" E., on the N-S center line of the NE1/4SW1/4 of sec. 4. Across river bottom lands, covered with scattered cottonwood trees, shadescall, cheat and bunch grass.</p>
7.10	Dirt road, 15 lks. wide, bears NW. and SE.

SUBDIVISION OF SECTION 4,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
9.977	Point for the NE-SW 1/64 sec. cor. of sec. 4, at intersection with the E-W center line of the NE1/4SW1/4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;">S 4 NE-SW 1/64 2009</div> From this point, the cor. of barbed wire fences, extending W. and SE., bears N. 64° E., 0.32 chs. dist.
10.40	Leave river bottom lands, thence across rolling lands, covered with shadescall, cheat and bunch grass.
19.954	The point for the C-E-W 1/64 sec. cor. of sec. 4. <hr/>
	From the point for the C-N-S 1/64 sec. cor. of sec. 4. N. 89°50'10" W., on the E-W center line of the NE1/4SW1/4 of sec. 4. Across rolling land, covered with shadescall, cheat and bunch grass.
2.40	Easterly rim of Walker River, bears NW. and SE., descend into river bottom lands.
9.67	Barbed wire fence, bears S. 30° E., and N. 30° W. for 0.17 chs., to cor. of fences, extending S. 30° E. and W.
10.047	The NE-SW 1/64 sec. cor. of sec. 4. Thence across river bottom lands, covered with shadescall, cheat and bunch grass and along barbed wire fence.
13.75	Dirt road, 15 lks. wide, bears NW. and SE., thence through scattered cottonwoods.
20.094	The C-N-SW 1/64 sec. cor. of sec. 4. <hr/>
	From the C-S-S 1/64 sec. cor. of sec. 4. N. 89°47'50" W., on the E-W center line of SE1/4SW1/4 of sec. 4. Across river bottom lands, covered with scattered cottonwood trees, shadescall, cheat and bunch grass.
5.00	Concrete lined irrigation ditch, 30 lks. wide, 5 ft. deep, drains S. 45° E.
19.50	Left bank of the Walker River, bears NNE. and SSW., thence across river, course S.

SUBDIVISION OF SECTION 4,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.061	The C-S-SW 1/64 sec. cor. of sec. 4.
	<hr/> <p>From the point for the C-W-SW 1/64 sec. cor. of sec. 4.</p> <p>N. 0°02'20" W., on the N-S center line of the NW1/4SW1/4 of sec. 4</p> <p>Across the Walker River, course S.</p>
3.90	Left bank of the Walker River, bears NW. and SE.
9.970	Point for the NW-SW 1/64 sec. cor. of sec. 4, at intersection with the E-W center line of the NW1/4SW1/4.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 4 NW-SW 1/64 2009</p> <p>From this point, the cor. of barbed wire fences, wood posts, extending E. and S., bears N. 85° W., 0.57 chs. dist.</p>
10.02	Barbed wire fence, bears E. and W.
15.50	Dirt road, 15 lks. wide, bears SE. and SW.
19.940	The C-W-W 1/64 sec. cor. of sec. 4.
	<hr/> <p>From the C-N-SW 1/64 sec. cor. of sec. 4.</p> <p>N. 89°50'20" W., on the E-W center line of the NW1/4SW1/4 of sec. 4.</p> <p>Across river bottom lands, covered with scattered cottonwoods, shadescall, cheat and bunch grass.</p>
10.047	The NW-SW 1/64 sec. cor. of sec. 4.
10.60	Barbed wire fence, wood posts, bears N. for 0.04 chs. dist., to cor. fences, extending E. and S.
19.60	Left bank of the Walker River, bears NNE. and S., thence across river, course S.
20.094	The point for the N-S 1/64 sec. cor. of secs. 4 and 5.
	<hr/> <p>From the C-W 1/16 sec. cor. of sec. 4.</p> <p>N. 0°00'30" E., on the N-S center line of the NW1/4 of sec. 4.</p> <p>Across rolling land, covered with shadescall, cheat and bunch grass.</p>

SUBDIVISION OF SECTION 4,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
9.974	<p>Point for the C-S-NW 1/64 sec. cor. of sec. 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 4 C-S-NW 1/64</p> <p style="text-align: center;">2009</p>
19.948	<p>Point for the NW 1/16 sec. cor. of sec. 4, at intersection with the E-W center line of the NW1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S 4</p> <p style="text-align: center;">2009</p>
25.20	Descend into river bottom lands, across steep W. slope.
29.922	<p>Point for the C-N-NW 1/64 sec. cor. of sec. 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">S 4 C-N-NW 1/64</p> <p style="text-align: center;">2009</p>
39.981	<p>The W 1/16 sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp.</p> <hr/> <p>From the point for the C-N 1/16 sec. cor. of sec. 4.</p> <p>N. 89°53'00" W., on the E-W center line of the NW1/4 of sec. 4.</p> <p>Across rolling land, covered with shadescale, cheat and bunch grass.</p>
10.070	<p>Point for the C-E-NW 1/64 sec. cor. of sec. 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 4 C-E-NW 1/64</p> <p style="text-align: center;">2009</p>

SUBDIVISION OF SECTION 4,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.140	The NW 1/16 sec. cor. of sec. 4.
25.20	Descend into river bottom lands, thence through scattered cottonwoods and willows.
29.70	Left bank of the Walker River, bears NE. and SW., thence across river, course SW.
30.210	Point for the C-W-NW 1/64 sec. cor. of sec. 4, falls in river where it is impractical to establish a permanent monument.
30.90	Right bank of the Walker River, bears NE. and SW.
40.280	The N 1/16 sec. cor. of secs. 4 and 5.
	<hr/>
	From the C-E-NW 1/64 sec. cor. of sec. 4.
	N. 0°03'20" E., on the N-S center line of the NE1/4NW1/4 of sec. 4.
	Across rolling land, covered with shadescale, cheat and bunch grass.
9.978	Point for the NE-NW 1/64 sec. cor. of sec. 4, at intersection with the E-W center line of the NE1/4NW1/4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	S 4 NE-NW 1/64 2009
20.026	The point for the E-W 1/64 sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp.
	<hr/>
	From the point for the C-N-N 1/64 sec. cor. of sec. 4.
	N. 89°53'20" W., on the E-W center line of the NE1/4NW1/4 of sec. 4.
	Across rolling land, covered with shadescale, cheat and bunch grass.
10.078	The NE-NW 1/64 sec. cor. of sec. 4.
18.60	Descend into river bottom lands.
20.156	The C-N-NW 1/64 sec. cor. of sec. 4.
	<hr/>
	From the C-W-W 1/64 sec. cor. of sec. 4.
	N. 0°02'20" W., on the N-S center line of the SW1/4NW1/4 of sec. 4.

SUBDIVISION OF SECTION 4,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Across river bottom lands, covered with scattered cottonwoods, willows, shadescala, cheat and bunch grass.
9.972	Point for the SW-NW 1/64 sec. cor. of sec 4, at intersection with the E-W center line of the SW1/4NW1/4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. S 4 SW-NW 1/64 2009
19.944	The point for the C-W-NW 1/64 sec. cor. of sec. 4. <hr/> From the C-S-NW 1/64 sec. cor. of sec. 4. N. 89°52'10" W., on the E-W center line of the SW1/4NW1/4 of sec. 4. Across rolling land, covered with shadescala, cheat and bunch grass.
7.00	Descend into river bottom lands, thence through scattered cottonwoods and willows.
10.062	The SW-NW 1/64 sec. cor. of sec. 4.
15.80	Left bank of the Walker River, bears NW. and SE., thence across river, course SE.
17.70	Right bank of the Walker River, bears NW. and SE.
20.124	The point for the S-N 1/64 sec. cor. of secs. 4 and 5. <hr/> SUBDIVISION OF SECTION 7, T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA <hr/> From the 1/4 sec. cor. of secs. 7 and 18. N. 0°02'10" W., on the N-S center line of sec. 7. Across mountainous terrain, covered with sagebrush, shadescala, cheat and bunch grass, posting the boundary of the Walker River Indian Reservation with steel sign posts.
31.20	Summit of line, on westerly shoulder of White Mountain.
80.354	The 1/4 sec. cor. of secs. 6 and 7. <hr/>

SUBDIVISION OF SECTION 9,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the 1/4 sec. cor. of secs. 9 and 16.</p> <p>N. 0°03'50" E., on the N-S center line of sec. 9.</p> <p>Across rolling land, covered with shadecale, cheat and bunch grass.</p>
19.960	<p>Point for the C-S 1/16 sec. cor. of sec. 9.</p> <p>POINT NOT MONUMENTED</p>
29.940	<p>The C-N-S 1/64 sec. cor. of sec. 9, determined by person(s) unknown, monumented with an iron pipe, 1 1/2 ins. diam., 36 ins. long, firmly set, projecting 2 ins. above the ground, no mks. visible. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \text{C} \\ \text{N-S } 1/64 \quad \quad \text{S } 9 \\ \text{C} \end{array}$ <p>2009</p> </div> <p>Bury inverted pipe alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°01'40" E., beginning new measurement.</p>
9.996	<p>The center 1/4 sec. cor. of sec. 9, determined by person(s) unknown, monumented with an iron pipe, 1 1/2 ins. diam., 36 ins. long, firmly set, projecting 8 ins. above the ground, with iron cap mkd. T13N R28E C1/4 S9. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \text{T13N R28E} \\ \text{C } 1/4 \text{ S } 9 \end{array}$ <p>2009</p> </div> <p>Bury inverted pipe alongside stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°01'40" E., beginning new measurement.</p>
1.40	Graded dirt road, 25 lks. wide, bears N. 20° W. and S. 20° E.
9.974	Point for the C-S-N 1/64 sec. cor. of sec. 9.

SUBDIVISION OF SECTION 9,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;"> $\begin{array}{c} C \\ S-N \frac{1}{64} \quad \quad S \ 9 \\ C \end{array}$ </p> <p style="text-align: center;">2009</p>
13.40	Concrete lined irrigation ditch, 30 lks. wide, 5 ft. deep, drains S. 50° E., thence across river bottom lands, through scattered cottonwood trees.
19.948	<p>Point for the C-N 1/16 sec. cor. of sec. 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;"> $\begin{array}{c} C \\ N \frac{1}{16} \quad \quad S \ 9 \\ C \end{array}$ </p> <p style="text-align: center;">2009</p>
29.922	<p>Point for the C-N-N 1/64 sec. cor. of sec. 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;"> $\begin{array}{c} C \\ N-N \frac{1}{64} \quad \quad S \ 9 \\ C \end{array}$ </p> <p style="text-align: center;">2009</p>
30.50	Right bank of the Walker River, bears E. and W., thence across river, course E.
31.30	Left bank of the Walker River, bears NE. and W.
39.896	The 1/4 sec. cor. of secs. 4 and 9.
	<hr/> <p>From the 1/4 sec. cor. of secs. 9 and 10.</p> <p>N. 89°51'00" W., on the E-W center line of sec. 9.</p>
3.90	<p>Concrete lined irrigation ditch, 30 lks. wide, 5 ft. deep, drains S. 15° E.</p> <p>Thence across river bottom lands, through scattered cottonwoods and willows.</p>
10.00	Left bank of the Walker River, bears NW. and SE., thence across river, course SE.
11.00	Right bank of the Walker River, bears NW. and SE.

SUBDIVISION OF SECTION 9,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.085	<p>Point for the C-E 1/16 sec. cor. of sec. 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \text{E } 1/16 \\ \text{C} \text{-----} \text{C} \\ \text{S } 9 \end{array}$ </div> <p style="text-align: center;">2009</p>
25.80	<p>Concrete lined irrigation ditch, 30 lks. wide, 5 ft. deep, drains S.</p> <p>Thence across rolling land, covered with shadescale, cheat and bunch grass.</p>
39.60	Graded dirt road, 25 lks. wide, bears N. 25° W. and S. 25° E.
40.170	<p>The C 1/4 sec. cor. of sec. 9.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°52'20" W., beginning new measurement.</p>
40.052	<p>The 1/4 sec. cor. of secs. 8 and 9, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of dependent resurvey of a portion of the subdivisional lines, T. 13 N., R. 28 E., executed under Group No. 670, with a mound of stone, 3 ft. base, 1 ft. high, W. of cor.</p> <hr style="width: 50%; margin: 10px auto;"/> <p>From the C-E 1/16 sec. cor. of sec. 9.</p> <p>N. 0°03'50" E., on the N-S center line of the NE1/4 of sec. 9.</p> <p>Across river bottom lands, covered with scattered cottonwoods, shadescale, cheat and bunch grass.</p>
9.971	<p>Point for the C-S-NE 1/64 sec. cor. of sec. 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \text{S } 9 \\ \text{C-S-NE} \\ 1/64 \end{array}$ </div> <p style="text-align: center;">2009</p>
11.50	Right bank of the Walker River, bears NNW. and SE., thence across river, course SE.
12.80	Left bank of the Walker River, bears NNW. and SE.
15.70	Left bank of the Walker River, bears NNE. and SSW., thence across river, course SSW.

SUBDIVISION OF SECTION 9,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
17.30	Left bank of the Walker River, bears NNW. and SSE.
19.942	Point for the NE 1/16 sec. cor. of sec. 9, at intersection with the E-W center line of the NE 1/4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. NE 1/16 S 9 2009
25.60	Concrete lined irrigation ditch, 30 lks. wide, 5 ft. deep, drains S. 45° E.
29.10	Graded dirt road, 20 lks. wide, bears N. 45° W. and S. 45° E.
29.55	Barbed wire fence, bears N. 45° W. and S. 45° E.
29.913	Point for the C-N-NE 1/64 sec. cor. of sec. 9. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. S 9 C-N-NE 1/64 2009
39.884	The point for the E 1/16 sec. cor. of secs. 4 and 9. <hr/> From the point for the N 1/16 sec. cor. of secs. 9 and 10. N. 89°50'00" W., on the E-W center line of the NE 1/4 of sec. 9. Across rolling land, covered with shadescale, cheat and bunch grass.
10.20	Barbed wire fence, steel posts, bears N. 45° W. and S. 45° E.
12.20	Graded dirt road, 30 lks. wide, bears N. 40° W. and S. 40° E.
14.35	Concrete lined irrigation ditch, 30 lks. wide, 5 ft. deep, drains S. 45° E., thence across river bottom lands, through scattered cottonwoods and willows.
20.096	The NE 1/16 sec. cor. of sec. 9.
23.70	Left bank of the Walker River, bears NW. and SE., thence across river, course SE.
24.30	Right bank of the Walker River, bears NW. and SE.
40.192	The C-N 1/16 sec. cor. of sec. 9. <hr/>

SUBDIVISION OF SECTION 9,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the S-N 1/64 sec. cor. of secs. 9 and 10.</p> <p>N. 89°50'20" W., on the E-W center line of the SE1/4NE1/4 of sec. 9.</p> <p>Across rolling land, covered with shadescall, cheat and bunch grass.</p>
4.40	Graded dirt road, 30 lks. wide, bears N. 30° W. and S. 30° E.
10.20	Concrete lined irrigation ditch, 30 lks. wide, 5 ft. deep, drains S. 45° E.
	Thence across river bottom lands, through scattered cottonwoods and willows.
16.30	Left bank of the Walker River, bears NW. and SE., thence across river, course SE.
17.30	Right bank of the Walker River, bears NW. and SE.
20.091	The C-S-NE 1/64 sec. cor. of sec. 9.
	<hr/> <p>N. 89°50'30" W., on the E-W center line of the SW1/4NE1/4 of sec. 9.</p> <p>Across river bottom lands, covered with scattered cottonwoods, shadescall, cheat and bunch grass.</p>
15.90	Concrete lined irrigation ditch, 30 lks. wide, 5 ft. deep, drains S. 50° E.
20.091	The C-S-N 1/64 sec. cor. of sec. 9.
	<hr/> <p>From the C-N-NE 1/64 sec. cor. of sec. 9.</p> <p>N. 89°49'30" W., on the E-W center line of the NW1/4NE1/4 of sec. 9.</p> <p>Across river bottom lands, covered with scattered cottonwoods, shadescall, cheat and bunch grass.</p>
0.40	Barbed wire fence, steel posts, bears N. 40° W. and S. 40° E.
7.70	Left bank of the Walker River, bears NW. and SE., thence across river, course SE.
8.60	Right bank of the Walker River, bears NW. and SE.
10.40	Right bank of the Walker River, bears NE. and SW., thence across river, course NE.
11.30	Left bank of the Walker River, bears NE. and SW.
13.00	Left bank of the Walker River, bears N. and SE., thence across river, course S.
13.80	Right bank of the Walker River, bears NNE. and SE.

SUBDIVISION OF SECTION 9,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.102	The C-N-N 1/64 sec. cor. of sec. 9.
	<p>From the E 1/16 sec. cor. of secs. 9 and 16.</p> <p>N. 0°02'50" E., on the N-S center line of the SE1/4 of sec. 9.</p> <p>Across rolling land, covered with shadescale, cheat and bunch grass.</p>
9.984	<p>Point for the C-S-SE 1/64 sec. cor. of sec. 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 9 C-S-SE 1/64 2009</p> <p>From this point, a redwood post of unknown origin, 2x3 ins., firmly set, projecting 16 ins. above the ground, no mks. visible, bears N. 64°22' W., 0.10 chs. dist. This position cannot be reconciled with proper procedures, is not harmoniously related to surrounding corners and is not utilized in the course of this survey.</p>
19.95	Center of concrete lined irrigation ditch, 30 lks. wide, 5 ft. deep, drains S. 30° E.
19.968	<p>Point for the SE 1/16 sec. cor. of sec. 9, at intersection with the E-W center line of the SE1/4.</p> <p>Chisel an X on NE embankment of concrete lined irrigation ditch. from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 86°34' E., 12.9 lks. dist., with brass cap mkd. RM SE1/16 S9 8.5 FT TO COR 2009 and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 50°10' W., 15.3 lks. dist., with brass cap mkd. RM SE1/16 S9 10.1 FT TO COR 2009 and an arrow pointing to the cor.</p> <p>Thence across river bottom lands, through scattered cottonwoods and willows.</p>
20.50	<p>From this point, the cor. of barbed wire fences, extending N. and SE., bears E., 0.05 chs. dist.</p> <p>Thence along fence.</p>
29.955	Point for the C-N-SE 1/64 sec. cor. of sec. 9.

SUBDIVISION OF SECTION 9,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 9 C-N-SE 1/64 2009</p> <p>From this point, the cor. of barbed wire fences, extending E. and S., bears N. 44° W., 0.103 chs. dist.</p>
39.942	<p>The C-E 1/16 sec. cor. of sec. 9.</p> <hr/> <p>From the S 1/16 sec. cor. of secs. 9 and 10.</p> <p>N. 89°51'10" W., on the E-W center line of the SE1/4 of sec. 9.</p> <p>Across river bottom lands, covered with scattered cottonwoods, shadescall, cheat and bunch grass.</p>
4.10	Left bank of the Walker River, bears N. and S., thence across river, course S.
4.70	Right bank of the Walker River, bears N. and S., thence along N. side of cultivated field and along barbed wire fence.
19.55	From this point, the cor. of barbed wire fences, extending NW. and E., bears N., 0.07 chs. dist.
20.088	The SE 1/16 sec. cor. of sec. 9.
20.10	Concrete lined irrigation ditch, 30 lks. wide, 5 ft. deep, drains S. 30° E.
40.173	<p>The point for the C-S 1/16 sec. cor. of sec. 9.</p> <hr/> <p>From the N-S 1/64 sec. cor. of secs. 9 and 10.</p> <p>N. 89°51'00" W., on the E-W center line of the NE1/4SE1/4 of sec. 9.</p> <p>Across river bottom lands, covered with scattered cottonwoods, shadescall, cheat and bunch grass.</p>
4.30	Left bank of the Walker River, bears NW. and SE., thence across river, course SE.
7.60	Left bank of the Walker River, bears ENE. and SW.
11.60	Left bank of the Walker River, bears NW. and S., thence across river, course S.
12.20	Right bank of the Walker River, bears NW. and S.
20.087	<p>The C-N-SE 1/64 sec. cor. of sec. 9.</p> <hr/>

SUBDIVISION OF SECTION 9,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the S-S 1/64 sec. cor. of secs. 9 and 10.</p> <p>N. 89°50'30" W., on the E-W center line of the SE1/4SE1/4 of sec. 9.</p> <p>Across river bottom lands, covered with scattered cottonwoods, willows, shadescala, cheat and bunch grass.</p>
7.50	Left bank of the Walker River, bears NE. and SSW., thence across river, course SSW.
8.00	Right bank of the Walker River, bears NE. and SSW.
11.90	Concrete lined irrigation ditch, 30 lks. wide, 5 ft. deep, drains S. 10° E.
	Thence across rolling land, covered with shadescala, cheat and bunch grass.
20.090	The C-S-SE 1/64 sec. cor. of sec. 9.
	<hr/> <p>From the C-N-SE 1/64 sec. cor. of sec. 9.</p> <p>N. 89°52'30" W., on the E-W center line of the NW1/4SE1/4 of sec. 9.</p> <p>Across river bottom lands, covered with scattered cottonwoods, willows, shadescala, cheat and bunch grass.</p>
7.50	Concrete lined irrigation ditch, 30 lks. wide, 5 ft. deep, drains S.
	Thence across rolling land, covered with shadescala, cheat and bunch grass.
20.082	The C-N-S 1/64 sec. cor. of sec. 9.
	<hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 10, T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 10 and 15.</p> <p>N. 0°01'00" E., on the N-S center line of sec. 10.</p> <p>Across rolling land, covered with shadescala, cheat and bunch grass.</p>
3.40	Graded dirt road, 40 lks. wide, bears N. 30° W. and S. 30° E.
7.30	Barbed wire fence, bears N. 43° W. and S. 43° E.
20.002	Point for the C-S 1/16 sec. cor. of sec. 10.
	POINT NOT MONUMENTED
40.004	Point for the center 1/4 sec. cor. of sec. 10, at intersection with the E-W center line.

SUBDIVISION OF SECTION 10,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T13N R28E C 1/4 S10 2009</p>
79.971	<p>The 1/4 sec. cor. of secs. 3 and 10.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 10 and 11.</p> <p>N. 89°48'00" W., on the E-W center line of sec. 10.</p> <p>Across rolling land, covered with shadescale, cheat and bunch grass.</p>
0.30	Four-wheel drive road, 10 lks. wide, bears NNE. and SSW.
40.046	The center 1/4 sec. cor. of sec. 10.
60.082	<p>Point for the C-W 1/16 sec. cor. of sec. 10.</p> <p>POINT NOT MONUMENTED</p>
70.70	Barbed wire fence, bears N. 43° W. and S. 43° E.
75.90	Graded dirt road, 20 lks. wide, bears N. and S.
77.00	Graded dirt road, 40 lks. wide, bears N. 40° W. and S. 40° E.
80.118	<p>The 1/4 sec. cor. of secs. 9 and 10.</p> <hr/> <p>From the W 1/16 sec. cor. of secs. 10 and 15.</p> <p>N. 0°01'50" E., on the N-S center line of the SW1/4 of sec. 10.</p> <p>Across cultivated land.</p>
1.00	Leave cultivated lands, thence across rolling land covered with shadescale, cheat and bunch grass.
2.80	Concrete lined irrigation ditch, 25 lks. wide, 5 ft. deep, drains N. 70° E.
4.00	From this point, the cor. of barbed wire fences, extending N. and S. 70° W., bears W., 0.38 chs. dist., thence along E. side of barbed wire fence.
10.00	From this point, the cor. of barbed wire fences, extending S. and N. 85° W., bears W., 0.38 chs. dist.
19.60	Graded dirt road, 40 lks. wide, bears N. 60° W. and S. 60° E.
19.989	<p>Point for the SW 1/16 sec. cor. of sec. 10, at intersection with the E-W center line of the SW1/4.</p> <p>POINT NOT MONUMENTED</p>

SUBDIVISION OF SECTION 10,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
28.70	Barbed wire fence, bears N. 43° W. and S. 43° E.
39.977	The point for the C-W 1/16 sec. cor. of sec. 10.
	<hr/> <p>From the point for the C-S 1/16 sec. cor. of sec. 10.</p> <p>N. 89°45'40" W., on the E-W center line of the SW1/4 of sec. 10.</p> <p>Across rolling land, covered with shadescall, cheat and bunch grass.</p>
11.90	Barbed wire fence, bears N. 43° W. and S. 43° E.
20.041	The point for the SW 1/16 sec. cor. of sec. 10.
20.60	Graded dirt road, 40 lks. wide, bears N. 40° W. and S. 60° E.
30.062	Point for the C-W-SW 1/64 sec. cor. of sec. 10.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S10 C-W-SW 1/64 2009</p>
33.10	Concrete lined irrigation ditch, 25 lks. wide, 6 ft. deep, drains S. 15° E.
	Thence across river bottom lands, through scattered cottonwoods.
40.083	The S 1/16 sec. cor. of secs. 9 and 10.
	<hr/> <p>From the W-W 1/64 sec. cor. of secs. 10 and 15.</p> <p>N. 0°02'00" E., on the N-S center line of the SW1/4SW1/4 of sec. 10.</p> <p>Along W. side of cultivated land and on E. side of barbed wire fence.</p>
11.30	Concrete lined irrigation ditch, 25 lks. wide, 6 ft. deep, drains S. 25° E., thence across rolling land, covered with shadescall, cheat and bunch grass.
19.981	The C-W-SW 1/64 sec. cor. of sec. 10.
	<hr/>

SUBDIVISION OF SECTION 14,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the 1/4 sec. cor. of secs. 14 and 23.</p> <p>N. 0°11'20" W., on the N-S center line of sec. 14.</p> <p>Across rolling land, covered with shadescale, cheat and bunch grass.</p>
19.937	<p>Point for the C-S 1/16 sec. cor. of sec. 14.</p> <p>POINT NOT MONUMENTED</p>
29.40	Four-wheel drive trail, 10 lks. wide, bears NE. and SW.
39.874	<p>Point for the center 1/4 sec. cor. of sec. 14, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T13N R28E C 1/4 S14 2009</p>
79.724	<p>The 1/4 sec. cor. of secs. 11 and 14.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 13 and 14.</p> <p>N. 89°58'10" W., on the E-W center line of sec. 14.</p> <p>Across rolling land, covered with shadescale, cheat and bunch grass.</p>
40.003	The center 1/4 sec. cor. of sec. 14.
60.161	<p>Point for the C-W 1/16 sec. cor. of sec. 14.</p> <p>POINT NOT MONUMENTED</p>
70.240	<p>Point for the C-W-W 1/64 sec. cor. of sec. 14.</p> <p>POINT NOT MONUMENTED</p>
76.20	Barbed wire fence, bears N. 43° W. and S. 43° E.
76.70	Graded dirt road, 40 lks. wide, bears N. 43° W. and S. 43° E.
77.20	Graded dirt road, 40 lks. wide, bears N. 40° W., 1 ch. dist. to fork in road, and S. 35° E.
79.05	Concrete irrigation ditch, 25 lks. wide, 5 ft. deep, drains SE.
80.319	<p>The 1/4 sec. cor. of secs. 14 and 15.</p> <hr/> <p>From the W 1/16 sec. cor. of secs. 14 and 23.</p> <p>N. 0°00'10" E., on the N-S center line of the SW1/4 of sec. 14.</p>

SUBDIVISION OF SECTION 14,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Across rolling land, covered with shadescale, cheat and bunch grass.
8.90	Graded dirt road, 40 lks. wide, bears N. 35° W. and S. 35° E.
9.959	Point for the C-S-SW 1/64 sec. cor. of sec. 14. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. S14 C-S-SW 1/64 2009
11.00	Barbed wire fence, bears N. 20° W. and S. 20° E.
16.10	Four wheel drive trail, 10 lks. wide, bears NE. and SW.
19.918	Point for the SW 1/16 sec. cor. of sec. 14, at intersection with the E-W center line of the SW1/4. POINT NOT MONUMENTED
29.877	Point for the C-N-SW 1/64 se. cor. of sec. 14. POINT NOT MONUMENTED
39.836	The point for the C-W 1/16 sec. cor. of sec. 14. <hr/> From the point for the C-S 1/16 sec. cor. of sec. 14. N. 89°55'10" W., on the E-W center line of the SW1/4 of sec. 14. Across rolling land, covered with shadescale, cheat and bunch grass.
15.40	Four-wheel drive trail, 10 lks. wide, bears NE. and SW.
20.227	The point for the SW 1/16 sec. cor. of sec. 14.
23.50	Barbed wire fence, bears N. 20° W. and S. 20° E.
24.50	Graded dirt road, 30 lks. wide, bears N. 20° W. and S. 20° E.
28.50	Graded dirt road, 40 lks. wide, bears N. 15° W. and S. 15° E.
30.340	Point for the C-W-SW 1/64 sec. cor. of sec. 14. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

SUBDIVISION OF SECTION 14,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">S14 C-W-SW 1/64 2009</p>
35.50	Concrete lined irrigation ditch, 25 lks. wide, 5 ft. deep, drains S. 45° E.
40.453	The S 1/16 sec. cor. of secs. 14 and 15.
	<hr/> <p>From the point for the W-W 1/64 sec. cor. of secs. 14 and 23. N. 0°06'00" E., on the N-S center line of the SW1/4SW1/4 of sec. 14. Across river bottom lands, covered with scattered cottonwoods, shadescale, cheat and bunch grass.</p>
4.40	Concrete lined irrigation ditch, 25 lks. wide, 5 ft. deep, drains S. 60° E.; leave bottom land, enter rolling hills.
9.954	Point for the SW-SW 1/64 sec. cor. of sec. 14, at intersection with the E-W center line of the SW1/4SW1/4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<p style="text-align: center;">S14 SW-SW 1/64 2009</p>
19.908	The C-W-SW 1/64 sec. cor. of sec. 14.
	<hr/> <p>From the C-S-SW 1/64 sec. cor. of sec. 14. N. 89°53'40" W., on the E-W center line of the SW1/4SW1/4 of sec. 14. Across rolling land, covered with shadescale, cheat and bunch grass.</p>
0.70	Graded dirt road, 40 lks. wide, bears N. 30° W. and S. 30° E.
10.130	The SW-SW 1/64 sec. cor. of sec. 14.
11.25	Concrete lined irrigation ditch, 25 lks. wide, 5 ft. deep, drains S. 35° E.
	Thence across river bottom lands, through scattered cottonwoods.
20.261	The S-S 1/64 sec. cor. of secs. 14 and 15.
	<hr/>

SUBDIVISION OF SECTION 14,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the C-W-SW 1/64 sec. cor. of sec. 14.</p> <p>N. 0°06'00" E., on the N-S center line of the NW1/4SW1/4 of sec. 14.</p> <p>Across rolling land, covered with shadescall, cheat and bunch grass.</p>
3.80	Graded dirt road, 40 lks. wide, bears N. 30° W. and S. 30° E.
9.954	<p>Point for the NW-SW 1/64 sec. cor. of sec. 14, at intersection with the E-W center line of the NW1/4SW1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S14 NW-SW 1/64</p> <p style="text-align: center;">2009</p>
12.80	Graded dirt road, 40 lks. wide, bears N. 40° W. and S. 40° E.
13.60	Barbed wire fence, bears N. 43° W. and S. 43° E.
19.908	The point for the C-W-W 1/64 sec. cor. of sec. 14.
	<hr/> <p>From the point for the C-N-SW 1/64 sec. cor. of sec. 14.</p> <p>N. 89°56'50" W., on the E-W center line of the NW1/4SW1/4 of sec. 14.</p> <p>Across rolling land covered with shadescall, cheat and bunch grass.</p>
6.80	Barbed wire fence, bears N. 43° W. and S. 43° E.
7.90	Graded dirt road, 40 lks. wide, bears N. 35° W. and S. 35° E.
10.096	The NW-SW 1/64 sec. cor. of sec. 14.
14.50	Graded dirt road, 40 lks. wide, bears N. 15° W. and S. 15° E.
18.10	Concrete lined irrigation ditch, 25 lks. wide, 5 ft. deep, drains S. 20° E.
	Thence across cultivated land.
20.192	The N-S 1/64 sec. cor. of secs. 14 and 15.
	<hr/>

SUBDIVISION OF SECTION 15,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the 1/4 sec. cor. of secs. 15 and 22, monumented with an aluminum post, 2 1/2 ins. diam., set flush with the surface of the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 13 N., R. 28 E., executed under Group No. 635.</p> <p>from which new accessories</p> <p>A chiseled X followed by the letters BO, bears S. 11°26' E., 48.6 lks. dist., mkd. on the top center of a concrete headwall, 4 ft. wide, over a culvert, 3 ft. diam., drains E.</p> <p>A stamped X between the letters BO, bears S. 69°14' W., 78.8 lks. dist., mkd. on top of the operating screw for the most westerly of three floodgates.</p> <p>N. 0°08'00" E., on the N-S center line of sec. 15.</p> <p>Across nearly level land, covered with scattered cottonwood trees, shadescale, cheat and bunch grass.</p>
0.015	S. edge of East Loop Road, asphalt surfaced, 40 lks. wide, bears N. 40° W. and S. 40° E.
1.50	Concrete lined irrigation ditch, 12 lks. wide, 5 ft. deep, drains SE.
2.00	<p>From this point, the cor. of barbed wire fences, extending N., and SE. and NW., parallel to concrete ditch, bears E., 0.22 chs. dist.</p> <p>Thence along W. side of barbed wire fence and along W. side of cultivated field.</p>
9.971	<p>Point for the C-S-S 1/64 sec. cor. of sec. 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} C \\ S-S\ 1/64 \quad \quad S15 \\ C \end{array}$ <p>2009</p> </div> <p>From this point, the cor. of barbed wire fences, extending E., S. and W., bears S. 89° E., 0.11 chs. dist.</p>
10.08	Concrete lined irrigation ditch, 10 lks. wide, 3 ft. deep, bears E. and W.
10.20	Graded dirt road, 25 lks. wide, bears E. and W.
10.40	From this point, a cor. of fences, extending N., E. and W., bears E., 0.186 chs. dist.
19.942	Point for the C-S 1/16 sec. cor. of sec. 15.

SUBDIVISION OF SECTION 15,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	POINT NOT MONUMENTED
29.80	Power line, bears E. for 0.01 chs., thence extending S. and W.
29.84	Barbed wire fence, bears E. and W.
29.913	Point for the C-N-S 1/64 sec. cor. of sec. 15. Chiseled an X in S. embankment of concrete lined irrigation ditch. from which A chiseled X followed by the letters BO, mkd. on top of the N. embankment of a concrete irrigation ditch, bears N. 73°50' W., 20.0 lks. dist. A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 12°09' W., 16.1 lks. dist., with brass cap mkd. RM C-N-S 1/64 S15 10.6 FT TO COR 2009 and arrow pointing to the cor. From this point, a power pole bears S. 30° E., 0.03 chs. dist., from which power lines extend S. and W. From this same point, a fence cor. bears S. 15° E., 0.07 chs. dist., from which barbed wire fences, extend NNE., S. and W.
38.50	Right bank of the Walker River, bears NW. and SE., thence across river, course SE.
39.884	Point for the center 1/4 sec. cor. of sec. 15, at intersection with the E-W center line, falls in river where it is impractical to establish a permanent monument.
42.70	Right bank of the Walker River, bears NE. and SW.
49.20	Right bank of the Walker River, bears NW. and SE., thence across river, course SE.
49.851	Point for the C-S-N 1/64 sec. cor. of sec. 15, falls in the river where it is impractical to establish a permanent monument.
50.50	Left bank of the Walker River, bears NW. and SE., thence across cultivated lands and along E. side of barbed wire fence, bears N.
59.818	Point for the C-N 1/16 sec. cor. of sec. 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;"> C N 1/16 S15 C 2009 </div>
69.785	Point for the C-N-N 1/64 sec. cor. of sec. 15

SUBDIVISION OF SECTION 15,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Chisel an X in concrete surface of irrigation ditch.</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 49°38' E., 52.9 lks. dist., with brass cap mkd. RM C-N-N 1/64 S15 34.9 FT TO COR 2010 and arrow pointing to the cor.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 51°18' E., 57.7 lks. dist., with brass cap mkd. RM C-N-N 1/64 S15 38.1 FT TO COR 2010 and arrow pointing to the cor.</p> <p>Point is located on concrete lined irrigation ditch, 25 lks. wide, 5 ft. deep, drains SSE.</p>
78.90	Concrete lined irrigation ditch, 25 lks. wide, 5 ft. deep, drains SSE.
79.752	The 1/4 sec. cor. of secs. 10 and 15.
	<hr/> <p>From the 1/4 sec. cor. of secs. 14 and 15.</p> <p>N. 89°49'00" W., on the E-W center line of sec. 15.</p> <p>Across level cultivated fields.</p>
10.010	<p>Point for the C-E-E 1/64 sec. cor. of sec. 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>E-E 1/64</p> <p>C——C</p> <p>S15</p> <p>2009</p> </div>
20.00	Barbed wire fence, bears N. and S.
20.020	<p>Point for the C-E 1/16 sec. cor. of sec. 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>E 1/16</p> <p>C——C</p> <p>S15</p> <p>2009</p> </div>
30.030	Point for the C-W-E 1/64 sec. cor. of sec. 15.

SUBDIVISION OF SECTION 15,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">W-E 1/64 C——C S15</p> <p style="text-align: center;">2009</p>
39.60	Left bank of the Walker River, thence across river, course SE.
40.040	The point for the center 1/4 sec. cor. of sec. 15.
40.80	Right bank of the Walker River, bears NW. and SE., thence across level farmland, through scattered cottonwoods.
41.85	From this point, the E. end of a barbed wire fence, extending W., bears N., 0.10 chs. dist., thence along S. side of barbed wire fence, and along N. side of graded dirt road, 15 lks. wide, parallels fence.
50.085	<p>Point for the C-E-W 1/64 sec. cor. of sec. 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">E-W 1/64 C——C S15</p> <p style="text-align: center;">2010</p>
60.130	<p>The point for the C-W 1/16 sec. cor. of sec. 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">W 1/16 C——C S15</p> <p style="text-align: center;">2010</p> <p>From this point, the cor. of barbed wire fences, extending N., E. and W., bears N. 82° W., 0.09 chs. dist.</p>
70.175	<p>Point for the C-W-W 1/64 sec. cor. of sec. 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 3 ins. below the surface of graded dirt road, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">W-W 1/64 C——C S15</p> <p style="text-align: center;">2010</p>

SUBDIVISION OF SECTION 15,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Point falls in center of Red Earth Way, a graded dirt road, 15 lks. wide, parallels irrigation ditch.
70.42	Concrete irrigation ditch, 15 lks. wide, 5 ft. deep, drains SSE.
73.70	Power line, bears N. 41° W. and S. 41° E.
74.45	White Mountain Drive, asphalt surfaced, 35 lks. wide, bears N. 40° W. and S. 40° E.
80.220	The 1/4 sec. cor. of secs. 15 and 16.
	<hr/> <p>From the C-E 1/16 sec. cor. of sec. 15.</p> <p>N. 0°09'50" E., on the N-S center line of the NE1/4 of sec. 15.</p> <p>Across level cultivated field, and along barbed wire fence.</p>
9.75	From this point, the cor. of an irrigation ditch bears E., 0.17 chs. dist., from which a concrete lined irrigation ditch bears N. and drains E., thence along W. side of irrigation ditch.
9.958	Point for the C-S-NE 1/64 sec. cor. of sec. 15.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">15 C-S-NE 1/64 2010</p>
16.85	Concrete irrigation ditch, 25 lks. wide, 5 ft. deep, drains SE.
19.916	Point for the NE 1/16 sec. cor. of sec. 15, at intersection with the E-W center line of the NE1/4.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S15 2010</p>
20.90	Graded dirt road, 40 lks. wide, bears N. 45° W. and S. 45° E.
25.80	Barbed wire fence, bears N. 43° W. and S. 43° E.
29.874	Point for the C-N-NE 1/64 sec. cor. of sec. 15.
	POINT NOT MONUMENTED
39.832	The point for the E 1/16 sec. cor. of secs. 10 and 15.
	<hr/>

SUBDIVISION OF SECTION 15,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the point for the N 1/16 sec. cor. of secs. 14 and 15.</p> <p>N. 89°45'40" W., on the E-W center line of the NE 1/4 of sec. 15.</p> <p>Across rolling land, covered with shadescall, cheat and bunch grass.</p>
10.015	<p>Point for the C-E-NE 1/64 sec. cor. of sec. 15.</p> <p>POINT NOT MONUMENTED</p>
14.55	Barbed wire fence, bears N. 43° W. and S. 43° E.
18.90	Graded dirt road, 40 lks. wide, bears N. 45° W. and S. 45° E.
20.030	The NE 1/16 sec. cor. of sec. 15.
24.40	Concrete lined irrigation ditch, 25 lks. wide, 5 ft. deep, drains S. 54° E., thence across level cultivated land.
30.045	<p>Point for the C-W-NE 1/64 sec. cor. of sec. 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S15 C-W-NE 1/64 2010</p>
30.21	Barbed wire fence, bears NNE. and S.
40.060	The C-N 1/64 sec. cor. of sec. 15.
	<hr/> <p>From the C-E-E 1/64 sec. cor. of sec. 15.</p> <p>N. 0°10'50" E., on the N-S center line of the SE1/4NE1/4 of sec. 15.</p> <p>Across level cultivated land.</p>
7.50	Barbed wire fence, bears N. 40° W. and S. 40° E.
8.20	Concrete lined irrigation ditch, 25 lks. wide, 5 ft. deep, drains S. 40° E.
9.954	<p>Point for the SE-NE 1/64 sec. cor. of sec. 15, at intersection with the E-W center line of the SE1/4NE1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

SUBDIVISION OF SECTION 15,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">S15 SE-NE 1/64 2010</p>
12.90	Graded dirt road, 40 lks. wide, bears N. 50° W. and S. 50° E.
15.10	Barbed wire fence, bears N. 43° W. and S. 43° E.
19.908	The point for the C-E-NE 1/64 sec. cor. of sec. 15.
	<hr/> <p>From the point for the S-N 1/64 sec. cor. of secs. 14 and 15. N. 89°47'10" W., on the E-W center line of the SE1/4NE1/4 of sec. 15. Across rolling land, covered with shadescall, cheat and bunch grass.</p>
5.20	Barbed wire fence, bears N. 43° W. and S. 43° E.
6.50	Graded dirt road, 40 lks. wide, bears N. 50° W. and S. 50° E.
10.012	The SE-NE 1/64 sec. cor. of sec. 15.
11.50	Concrete lined irrigation ditch, 25 lks. wide, 5 ft. deep, drains S. 40° E.
12.20	Barbed wire fence, bears N. 40° W. and S. 40° E.
20.025	The C-S-NE 1/64 sec. cor. of sec. 15.
	<hr/> <p>From the C-W-E 1/64 sec. cor. of sec. 15. N. 0°09'00" E., on the N-S center line of the SW1/4NE1/4 of sec. 15. Across level cultivated land, along E. side of barbed wire fence.</p>
9.963	<p>Point for the SW-NE 1/64 sec. cor. of sec. 15, at intersection with the E-W center line of the SW1/4NE1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S15 SW-NE 1/64 2010</p>
19.926	<p>From this point, the cor. of barbed wire fences, extending N., S. and WSW., bears S. 10° W., 0.59 chs. dist.</p> <p>The C-W-NE 1/64 sec. cor. of sec. 15.</p> <hr/>

SUBDIVISION OF SECTION 15,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the C-S-NE 1/64 sec. cor. of sec. 15.</p> <p>N. 89°47'20" W., on the E-W center line of the SW1/4NE1/4 of sec. 15.</p> <p>Across level cultivated land.</p>
10.012	The SW-NE 1/64 sec. cor. of sec. 15.
10.11	Barbed wire fence bears N. and S.
19.45	Left bank of the Walker River, bears NW. and SE., thence across river, course SE.
20.024	The point for the C-S-N 1/64 sec. cor. of sec. 15.
	<hr/> <p>From the C-W-NE 1/64 sec. cor. of sec. 15.</p> <p>N. 0°09'00" E., on the N-S center line of the NW1/4NE1/4 of sec. 15.</p> <p>Across level cultivated land, along E. side of barbed wire fence.</p>
3.50	From this point, the cor. of barbed wire fences, extending NW. and S., bears W., 3.50 chs. dist.
4.20	Concrete lined irrigation ditch, 25 lks. wide, 5 ft. deep, drains S. 55° E., thence across nearly level land, covered with shadescall, and cheat and bunch grass.
9.963	<p>Point for the NW-NE 1/64 sec. cor. of sec. 15, at intersection with the E-W center line of the NW1/4NE1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S15 NW-NE 1/64 2010</p>
10.80	Graded dirt road, 40 lks. wide, bears SE.
16.50	Barbed wire fence, bears N. 43° W. and S. 43° E.
19.926	The point for the W-E 1/64 sec. cor. of secs. 10 and 15.
	<hr/> <p>From the point for the C-N-NE 1/64 sec. cor. of sec. 15.</p> <p>N. 89°44'10" W., on the E-W center line of the NW1/4NE1/4 of sec. 15.</p> <p>Across nearly level land, covered with shadescall, cheat and bunch grass.</p>
3.90	Barbed wire fence, bears N. 43° W. and S. 43° E.

SUBDIVISION OF SECTION 15,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
9.10	Graded dirt road, 40 lks. wide, bears SE.
10.017	The NW-NE 1/64 sec. cor. of sec. 15.
20.034	The C-N-N 1/64 sec. cor. of sec. 15.
	<p>From the E 1/16 sec. cor. of secs. 15 and 22, monumented with a chiseled X on the concrete surface of an irrigation ditch, drains S., from which the 1986 reference monuments</p> <p>An aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, in a collar of stone, bears N. 52°06' E., 15 lks. dist., with aluminum cap mkd. RM E1/16 S15 10 FT 1986 and an arrow pointing to the cor. (Record, N. 50 1/4° E.)</p> <p>An aluminum post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, in a collar of stone, bears S. 34°15' E., 22.7 lks. dist., with aluminum cap mkd. RM E1/16 S22 15 FT 1986 and an arrow pointing to the cor. (Record, S. 33 1/2° E.)</p> <p>N. 0°09'40" E., on the N-S center line of the SE1/4 of sec. 15.</p> <p>Across nearly level land, covered with shadescale, scattered cottonwoods, cheat and bunch grass.</p>
9.958	Point for the C-S-SE 1/64 sec. cor. of sec. 15, falls on right bank of the Walker River, bears NW. and SE., where it is impractical to establish a permanent monument.
	Thence across river, course SE.
16.90	Left bank of the Walker River, bears NW. and SE.
19.916	Point for the SE 1/16 sec. cor. of sec. 15, at intersection with the E-W center line of the SE1/4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	SE 1/16 S15
	2010
29.10	Power line, bears N. 71° E. and S. 71° W.
29.82	Barbed wire fence, bears WSW. and ENE. for 0.12 chs. dist. to the cor. of fences, extending E., WSW. and NNW., thence along W. side of fence.
29.876	Point for the C-N-SE 1/64 sec. cor. of sec. 15.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

SUBDIVISION OF SECTION 15,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">S15 C-N-SE 1/64 2010</p>
39.836	<p>The C-E 1/16 sec. cor. of sec. 15.</p> <hr/> <p>From the S 1/16 sec. cor. of secs. 14 and 15. N. 89°52'20" W., on the E-W center line of the SE1/4 of sec. 15. Across level cultivated land, along N. side of barbed wire fence.</p>
9.87	Barbed wire fence, bears N. and S. 0.17 chs. dist. to cor. of fences, extending N. and E.
10.004	<p>Point for the C-E-SE 1/64 sec. cor. of sec. 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S15 C-E-SE 1/64 2010</p> <p>Thence through scattered cottonwoods and shadescale.</p>
20.008	The SE 1/16 sec. cor. of sec. 15.
21.70	Left bank of the Walker River, bears NW. and SE., thence across river, course SE.
24.00	Right bank of the Walker River, bears NW. and SE.
30.014	<p>Point for the C-W-SE 1/64 sec. cor. of sec. 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S15 C-W-SE 1/64 2010</p> <p>Point falls on the E. edge of a dirt road, 20 lks. wide, bears N. and S. Thence along N. side of cultivated field.</p>
40.020	<p>The point for the C-S 1/16 sec. cor. of sec. 15.</p> <hr/>

SUBDIVISION OF SECTION 15,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the C-E-SE 1/64 sec. cor. of sec. 15.</p> <p>N. 0°10'40" E., on the N-S center line of the NE1/4SE1/4 of sec. 15.</p> <p>Across level land, along W. side of cultivated field.</p>
9.955	<p>Point for the NE-SE 1/64 sec. cor. of sec. 15, at intersection with the E-W center line of the NE1/4SE1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S15 NE-SE 1/64 2010</p>
19.910	<p>From this point, the cor. of barbed wire fences, extending S. and W., bears N. 5° W., 0.10 chs. dist.</p> <p>The C-E-E 1/64 sec. cor. of sec. 15.</p> <hr/> <p>From the N-S 1/64 sec. cor. of secs. 14 and 15.</p> <p>N. 89°50'30" W., on the E-W center line of the NE1/4SE1/4 of sec. 15.</p> <p>Across level cultivated land.</p>
10.007	<p>The NE-SE 1/64 sec. cor. of sec. 15.</p> <p>Thence along fence line and the S. side of cultivated field.</p>
17.70	Power line, bears N. 72° E. and S. 72° W.
19.90	Barbed wire fence, bears N. and S. for 0.04 chs. dist. to cor. of fences, extending N. and E.
20.014	<p>The C-N-SE 1/64 sec. cor. of sec. 15.</p> <hr/> <p>From the E-E 1/64 sec. cor. of secs. 15 and 22, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of subdivision lines, T. 13 N., R. 28 E., executed under Group No. 635.</p> <p>N. 0°10'30" E., on the N-S center line of the SE1/4SE1/4 of sec. 15.</p> <p>Across nearly level land, covered with scattered cottonwood trees, willows and shadescale.</p>
19.911	<p>The C-E-SE 1/64 sec. cor. of sec. 15.</p> <hr/>

SUBDIVISION OF SECTION 15,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the W-E 1/64 sec. cor. of secs. 15 and 22, monumented with an X chiseled on a concrete lined irrigation ditch, drains E., from which the 1986 reference monuments</p> <p>An aluminum post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, in a collar of stone, bears S. 39° W., 19.7 lks. dist., with aluminum cap mkd. RM W-E 1/64 S22 13 FT 1986 and an arrow pointing to the cor.</p> <p>An aluminum post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, in a collar of stone, bears N. 31°33' W., 27.3 lks. dist., with aluminum cap mkd. RM W-E 1/64 S15 18 FT 1986 and an arrow pointing to the cor. (Record, N. 32 1/4° W.)</p> <p>N. 0°08'30" E., on the N-S center line of the SW1/4SE1/4 of sec. 15.</p> <p>Across level cultivated land.</p>
9.971	<p>Point for the SW-SE 1/64 sec. cor. of sec. 15, at intersection with the E-W center line of the SW1/4SE1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S15 SW-SE 1/64 2009</p>
10.02	Barbed wire fence, bears E. and W.
10.06	Concrete irrigation ditch, 10 lks. wide, bears E. and W., thence across level farmland.
19.935	The C-W-SE 1/64 sec. cor. of sec. 15.
	<hr/> <p>From the point for the C-S-SE 1/64 sec. cor. of sec. 15.</p> <p>N. 89°54'40" W., on the E-W center line of the SW1/4SE1/4 of sec. 15.</p> <p>Across level cultivated land, along S. side of fence.</p>
10.003	The SW-SE 1/64 sec. cor. of sec. 15.
20.008	The C-S-S 1/64 sec. cor. of sec. 15.
	<hr/> <p>From the C-W-SE 1/64 sec. cor. of sec. 15.</p> <p>N. 0°08'50" E., on the N-S center line of the NW1/4SE1/4 of sec. 15.</p> <p>Across level farmland.</p>

SUBDIVISION OF SECTION 15,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
9.966	<p>Point for the NW-SE 1/64 sec. cor. of sec. 15, at intersection with the E-W center line of the NW1/4SE1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S15 NW-SE 1/64 2009</p> <p>Thence through scattered cottonwood trees.</p>
14.00	Right bank Walker River bears N. and SE., thence along right bank.
18.00	Leave right bank, bears NW. and S., thence across river, course SSE.
19.932	The C-W-E 1/64 sec. cor. of sec. 15.
	<hr/> <p>From the C-N-SE 1/64 sec. cor. of sec. 15.</p> <p>N. 89°50'40" W., on the E-W center line of the NW1/4SE1/4 of sec. 15.</p> <p>Across nearly level land, covered with scattered cottonwood trees, shadescall, cheat and bunch grass.</p>
5.00	Left bank of the Walker River, bears N. and S., thence across river, course S.
6.00	Right bank of the Walker River, bears N. and S.
10.008	The NW-SE 1/64 sec. cor. of sec. 15.
13.00	Edge of cultivated field, bears W. and S., thence along N. edge of cultivated field.
20.016	The C-N-S 1/64 sec. cor. of sec. 15.
	<hr/> <p>From the W 1/16 sec. cor. of secs. 15 and 22.</p> <p>NORTH, on the N-S center line of the SW1/4 of sec. 15.</p> <p>Across level land, along E. side of irrigation ditch and W. side of graded dirt road.</p>
9.979	<p>Point for the C-S-SW 1/64 sec. cor. of sec. 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

SUBDIVISION OF SECTION 15,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>S15 C-S-SW 1/64 2009</p>
19.958	<p>Point for the SW 1/16 sec. cor. of sec. 15, at intersection with the E-W center line of the SW1/4.</p> <p>Set PK nail flush with asphalt surface.</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 39°21' E., 88.8 lks. dist., with brass cap mkd. RM SW1/16 S15 58.6 FT TO COR 2010 and an arrow pointing to the cor.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 52°15' W., 123.3 lks. dist., with brass cap mkd. RM SW1/16 S15 81.4 FT TO COR 2010 and an arrow pointing to the cor.</p> <p>Point falls in the asphalt surface of West Loop Road, 35 lks. wide, curves left to the NW., and curves right to the SE.</p> <p>Thence across developed land.</p>
24.50	Concrete lined irrigation ditch, 10 lks. wide, 3 ft. deep, drains S. 40° E.
28.20	Enter cultivated field, bears NW. and SE.
29.80	Power line, bears E. and W.
29.938	<p>Point for the C-N-SW 1/64 sec. cor. of sec. 15</p> <p>Chisel an X in concrete lined irrigation ditch.</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 44°06' E., 19.8 lks. dist., with brass cap mkd. RM C-N-SW 1/64 S15 13.1 FT TO COR 2010 and an arrow pointing to the cor.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 31°26' W., 16.8 lks. dist., with brass cap mkd. RM C-N-SW 1/64 S15 11.1 FT TO COR 2010 and an arrow pointing to the cor.</p> <p>Point falls on S. bank of concrete lined irrigation ditch, 8 lks. wide, 3 ft. deep, drains E.</p> <p>Thence across cultivated land.</p>
39.75	Graded dirt road, 15 lks. wide, bears E. and W.

SUBDIVISION OF SECTION 15,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.918	The C-W 1/16 sec. cor. of sec. 15.
	From the point for the C-S 1/16 sec. cor. of sec. 15. N. 89°52'10" W., on the E-W center line of the SW1/4 of sec. 15. Across level cultivated land.
10.023	Point for the C-E-SW 1/64 sec. cor. of sec. 15, falls in cultivated field where it is impractical to establish a permanent monument.
11.20	Leave cultivated land, bears NNW. and SSE., thence through shadescale, cheat and bunch grass.
16.20	Concrete lined irrigation ditch, 10 lks. wide, 3 ft. deep, drains S. 40° E.
20.046	The SW 1/16 sec. cor. of sec. 15. Thence along S. edge of West Loop Road.
28.60	Concrete lined irrigation ditch, 20 lks. wide, 4 ft. deep, drains SSE., 0.40 chs. dist., thence E.
30.068	Point for the C-W-SW 1/64 sec. cor. of sec. 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;">S15 C-W-SW 1/64 2009</div>
	Point falls under power line, bears N. 77° E. and S. 77° W.
34.50	West Loop Road, asphalt surfaced, 35 lks. wide, curves right to the NE. and curves left to the SW.
40.090	The S 1/16 sec. cor. of secs. 15 and 16.
	From the point for the C-E-SW 1/64 sec. cor. of sec. 15. N. 0°04'00" E., on the N-S center line of the NE1/4SW1/4 of sec. 15. Across level cultivated land.
9.85	Power line, bears E. and W.
9.975	Point for the NE-SW 1/64 sec. cor. of sec. 15, at intersection with the E-W center line of the NE1/4SW1/4.

SUBDIVISION OF SECTION 15,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S15 NE-SW 1/64 2010</p>
10.05	Concrete lined irrigation ditch, 8 lks. wide, 3 ft. deep, drains E.
19.950	The C-E-W 1/64 sec. cor. of sec. 15.
	<hr/> <p>From the C-N-S 1/64 sec. cor. of sec. 15.</p> <p>N. 89°50'30" W., on the E-W center line of the NE1/4SW1/4 of sec. 15.</p> <p>Across level cultivated land, along S. side of concrete lined irrigation ditch.</p>
10.034	The NE-SW 1/64 sec. cor. of sec. 15.
20.068	The C-N-SW 1/64 sec. cor. of sec. 15.
	<hr/> <p>From the E-W 1/64 sec. cor. of secs. 15 and 22, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 13 N., R. 28 E., executed under Group No. 635.</p> <p>N. 0°03'50" E., on the N-S center line of the SE1/4SW1/4 of sec. 15.</p> <p>Across nearly level land, covered with shadscale, cheat and bunch grass.</p>
9.974	<p>Point for the SE-SW 1/64 sec. cor. of sec. 15, at intersection with the E-W center line of the SE1/4SW1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S15 SE-SW 1/64 2009</p>
11.50	West Loop Road, asphalt surfaced, 35 lks. wide, bears N. 45° W. and S. 45° E.
12.60	Concrete lined irrigation ditch, 10 lks. wide, 3 ft. deep, drains S. 45° E.

SUBDIVISION OF SECTION 15,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
15.00	Enter cultivated field, bears NW. and SE.
19.949	The point for the C-E-SW 1/64 sec. cor. of sec. 15.
	<hr/>
	From the C-S-S 1/64 sec. cor. of sec. 15.
	N. 89°53'30" W., on the E-W center line of the SE1/4SW1/4 of sec. 15.
	Across level farmland, along S. side of concrete lined irrigation ditch.
7.70	Concrete lined irrigation ditch, 18 lks. wide, 5 ft. deep, drains S. 40° E.
8.65	West Loop Road, asphalt surfaced, 35 lks. wide, parallels ditch, thence through shadescall, cheat and bunch grass.
10.011	The SE-SW 1/64 sec. cor. of sec. 15.
20.023	The C-S-SW 1/64 sec. cor. of sec. 15.
	<hr/>
	From the W-W 1/64 sec. cor. of secs. 15 and 22.
	N. 0°04'10" W., on the N-S center line of the SW1/4SW1/4 of sec. 15.
	Across level cultivated land.
10.80	Irrigation ditch, 10 lks. wide, 3 ft. deep, drains SW., thence through shadescall, cheat and bunch grass.
19.968	The C-W-SW 1/64 sec. cor. of sec. 15.
	<hr/>
	From the C-W 1/16 sec. cor. of sec. 15.
	N. 0°11'40" E., on the N-S center line of the NW 1/4 of sec. 15.
	Across nearly level land, covered with scattered cottonwood trees, shadescall, cheat and bunch grass.
0.01	Barbed wire fence, bears E. and W.
15.70	Right bank of the Walker River, bears NW. and SE., thence across river, course SE. from the N.
19.951	Point for the NW 1/16 sec. cor. of sec. 15, at intersection with the E-W center line, falls in river where it is impractical to establish a permanent monument.
22.40	Right bank of the Walker River, bears NE. and SSW., thence across nearly level land covered with shadescall, cottonwoods cheat and bunch grass.

SUBDIVISION OF SECTION 15,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
27.75	Right bank of the Walker River, bears WSW and ESE., thence across river course ESE.
28.60	Fence on left bank of the Walker River, bears W., 0.11 chs. dist. thence N., and ESE. along left bank of Walker River, thence across nearly level farmland.
29.70	From this point, the cor. of barbed wire fences, extending N., S. and W., bears W., 0.19 chs. dist.
29.927	Point for the C-N-NW 1/64 sec. cor. of sec. 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. S15 C-N-NW 1/64 2010 Point is located at the S. end of the E. bank of an irrigation ditch, 10 lks. wide, 3 ft. deep, drains N. Thence between cultivated fields, along E. side of irrigation ditch choked with willows.
39.903	The W 1/16 sec. cor. of secs. 10 and 15. <hr/> From the C-N 1/16 sec. cor. of sec. 15. N. 89°46'10" W., on the E-W center line of the NW1/4 sec. 15. Across level cultivated land.
1.20	Left bank of the Walker River, bears NW. and SE., thence across river, course SE.
3.00	Left bank of the Walker River, bears NE. and SW.
10.034	Point for the C-E-NW 1/64 sec. cor. of sec. 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. S15 C-E-NW 1/64 2010 From this point, the cor. of barbed wire fences, extending N., S. and W., bears N. 42° W., 0.29 chs. dist. Thence along S. side of barbed wire fence and cultivated field.
10.20	Barbed wire fence, bears N. and S.

SUBDIVISION OF SECTION 15,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
19.40	Left bank of the Walker River, bears N. and S., thence across river, course S.
20.068	The point for the NW 1/16 sec. cor. of sec. 15.
20.60	Right bank of the Walker River, bears N. and S., thence across nearly level land, through scattered cottonwoods and shadescale.
25.00	Right bank of the Walker River, bears WNW. and ESE., thence across river, course SE.
25.50	Left bank of the Walker River, bears WNW. and ESE.
30.102	Point for the C-W-NW 1/64 sec. cor. of sec. 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. S15 C-W-NW 1/64 2010 Point is located on E. side of a dirt road, 15 lks. wide, bears NW. and SE. Thence along N. side of cultivated land, through scattered cottonwood trees.
37.80	Concrete irrigation ditch, 25 lks. wide, 5 ft. deep, drains SSW.
40.136	The N 1/16 sec. cor. of secs. 15 and 16. <hr/>
	From the C-E-NW 1/64 sec. cor. of sec. 15. N. 0°09'50" E., on the N-S center line of the NE1/4NW1/4 of sec. 15. Across level cultivated land, along E. side of barbed wire fence, bears N. and S.
19.00	Barbed wire fence, bears NE. and SW.
19.75	Concrete lined irrigation ditch, 25 lks. wide, 5 ft. deep, drains N. 50° E.
19.943	The E-W 1/64 sec. cor. of secs. 10 and 15. <hr/>
	From the C-E-W 1/64 sec. cor. of sec. 15. N. 0°09'50" E., on the N-S center line of the SE1/4NW1/4 of sec. 15. Across level land, along W. side of cultivated field.
0.06	Barbed wire fence, bears E. and W.

SUBDIVISION OF SECTION 15,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
13.80	Right bank of the Walker River, bears NE. and WSW., thence across river, course NE.
15.40	Left bank of the Walker River, bears NE. and SW., thence through scattered cottonwoods and along W. side of cultivated field.
19.943	The C-E-NW 1/64 sec. cor. of sec. 15.
	From the C-W-W 1/64 sec. cor. of sec. 15.
	N. 0°13'30" E., on the N-S center line of the SW1/4NW1/4 of sec. 15.
	Across cleared level land.
1.00	Barbed wire fence, bears NNW. and SSE.
4.00	Enter cultivated land, through scattered cottonwood trees.
19.00	Dirt road, 10 lks. wide, bears NW. and SE.
19.960	The C-W-NW 1/64 sec. cor. of sec. 15.
	From the C-N-NW 1/64 sec. cor. of sec. 15.
	N. 89°44'50" W., on the E-W center line of the NW1/4NW1/4 of sec. 15.
	Across level land, along S. side of barbed wire fence and cultivated field.
0.20	Barbed wire fence, bears N. and S.
8.50	Leave S. edge of cultivated field, thence through scattered cottonwood trees and shadescale.
19.20	Left bank of the Walker River, bears N. and S., thence across river, course S.
20.057	The point for the N-N 1/64 sec. cor. of secs. 15 and 16.
	SUBDIVISION OF SECTION 18, T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA
	From the 1/4 sec. cor. of secs. 18 and 19.
	N. 0°08'30" W., on the N-S center line of sec. 18.
	Across mountainous land, covered with sagebrush, shadescale, cheat and bunch grass.
34.20	Graded dirt road, 20 lks. wide, bears N. 50° E. and S. 50° W.
40.077	Point for the center 1/4 sec. cor. of sec. 18, at intersection with the E-W center line.

SUBDIVISION OF SECTION 18,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T13N R28E C 1/4 S18</p> <p style="text-align: center;">2009</p> <p>Begin posting the boundary of the Walker River Indian Reservation with steel sign posts.</p>
59.90	Dirt road, 10 lks. wide, bears SE and NW.
62.40	From this point, the head of a dry spring, course SE., bears W. 1.40 chs. dist.
80.273	The 1/4 sec. cor. of secs. 7 and 18.
	<hr/> <p>From the 1/4 sec. cor. of secs. 17 and 18.</p> <p>S. 89°44'40" W., on the E-W center line of sec. 18.</p> <p>Across mountainous land, covered with sagebrush, shadescall, cheat and bunch grass.</p>
5.20	Dirt road, 10 lks. wide, bears SE. and NW.
31.40	Graded dirt road, 20 lks. wide, bears NW. and ESE.
33.50	Graded dirt road, 20 lks. wide, bears NE. and SW.
39.932	The center 1/4 sec. cor. of sec. 18.
	<p>Begin posting the boundary of the Walker River Indian Reservation with steel sign posts.</p>
57.00	From this point, the summit of a conical peak bears S., 0.60 chs. dist.
79.00	Dirt road, 10 lks. wide, bears NNE. and SSW.
79.174	<p>The 1/4 sec. cor. of secs. 13 and 18, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set flush with the top of a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of the west boundary, T. 13 N., R. 28 E., executed under Group No. 855.</p> <hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 23, T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 23 and 26.</p> <p>N. 0°06'10" E., on the N-S center line of sec. 23.</p> <p>Across level farmland, along barbed wire fence.</p>

SUBDIVISION OF SECTION 23,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
7.00	From this point, the cor. of barbed wire fences, extending N. 55° W., S. 55° E. and S., bears W., 0.08 chs. dist.
8.10	Concrete irrigation ditch, 25 lks. wide, 5 ft. deep, drains S. 55° E., thence across rolling land, through shadescale, cheat and bunch grass.
9.986	Point for the C-S-S 1/64 sec. cor. of sec. 23. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;"> $\begin{array}{c} \text{C} \\ \text{S-S } 1/64 \quad \quad \text{S23} \\ \text{C} \end{array}$ <p>2010</p> </div> <p>From this point, an unrecorded rebar, 5/8 in. diam., firmly set flush with the ground, with plastic cap mkd. PLS 5194, bears S. 24°53' E., 0.045 chs. dist. This position cannot be reconciled with proper procedures and is not utilized in the course of this survey.</p>
14.662	From this point, an unrecorded rebar, 5/8 in. diam., firmly set flush with the ground, with plastic cap mkd. PLS 5194, bears W., 0.012 chs. dist. Thence through developed land.
19.972	Point for the C-S 1/16 sec. cor. of sec. 23. POINT NOT MONUMENTED
23.20	Sunrise Road, asphalt surfaced, 35 lks. wide, bears N. 58° E. and S. 58° W.
29.958	Point for the C-N-S 1/64 sec. cor. of sec. 23. POINT NOT MONUMENTED
37.50	Sunset Drive, asphalt surfaced, 35 lks. wide, bears N. 32° W. and S. 32° E.
39.944	Point for the center 1/4 sec. cor. of sec. 23, at intersection with the E-W center line. Set a PK flush with surface of asphalt driveway. from which A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 29°46' W., 103.6 lks. dist., with brass cap mkd. RM T13N R28E C1/4 S23 68.4 FT TO COR 2009 and an arrow pointing to the cor.

SUBDIVISION OF SECTION 23,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 80°50' W., 99.5 lks. dist., with brass cap mkd. RM T13N R28E C1/4 S23 65.7 FT TO COR 2009 and an arrow pointing to the cor.
47.00	Sunset Drive, asphalt surfaced, 35 lks. wide, bears N. 58° E. and S. 58° W.
49.966	Point for the C-S-N 1/64 sec. cor. of sec. 23. POINT NOT MONUMENTED
57.80	Little Dam Road, graded dirt surface, 50 lks. wide, bears N. 30° W. and S. 30° E.
58.96	Barbed wire fence, parallels road, thence across undeveloped land.
59.988	Point for the C-N 1/16 sec. cor. of sec. 23. POINT NOT MONUMENTED
70.010	Point for the C-N-N 1/64 sec. cor. of sec. 23. POINT NOT MONUMENTED
80.032	The 1/4 sec. cor. of secs. 14 and 23. <hr/> From the 1/4 sec. cor. of secs. 23 and 24. N. 89°49'00" W., on the E-W center line of sec. 23. Across nearly level land, covered with shadscale, cheat and bunch grass.
27.90	Barbed wire fence, parallels road.
28.70	Little Dam Road, asphalt surfaced, 40 lks. wide, bears N. 30° W. and S. 30° E.
40.117	The center 1/4 sec. cor. of sec. 23.
41.65	Sunset Drive, asphalt surfaced, 35 lks. wide, bears N. 32° W. and S. 32° E.
50.00	Descend into river bottom lands, thence through cottonwood trees.
50.176	Point for the C-E-W 1/64 sec. cor. of sec. 23. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;">E-W 1/64 C——C S23 2010</div>

SUBDIVISION OF SECTION 23,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
51.60	Concrete irrigation ditch, 25 lks. wide, 5 ft. deep, drains S. 30° E.
60.235	Point for the C-W 1/16 sec. cor. of sec. 23. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;"> W 1/16 C ——— C S23 2009 </div>
	From this point, the cor. of barbed wire fences, extending N. and W., bears N. 28° W., 0.09 chs. dist.
72.90	From this point, the W. end of barbed wire fence bears N., 0.10 chs. dist.
74.00	Left bank of the Walker River, bears NW. and SE., thence across river, course SE.
75.00	Right bank of the Walker River, bears NW. and SE.
76.80	Barbed wire fence, bears WNW. and ESE.
80.353	The 1/4 sec. cor. of secs. 22 and 23.
	<hr/> From the W 1/16 sec. cor. of secs. 23 and 26. N. 0°00'40" E., on the N-S center line of the SW1/4 of sec. 23. Across level land, along concrete irrigation ditch and W. side of cultivated field.
9.980	Point for the C-S-SW 1/64 sec. cor. of sec. 23, identical with the SW. corner of Indian Allotment No. 108; there is no remaining evidence of the position of the 1922 iron post. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;"> S23 C-S-SW 1/64 2009 </div>
	Cor. is located 0.20 chs. dist., NNW. of floodgate at N. end of concrete irrigation ditch.
	Thence continue on the N-S center line of the SW1/4 of sec. 23, identical with the W. bdy. of Indian Allotment No. 108.
11.50	Right bank of the Walker River, bears ENE. and WSW., thence across river, course ENE.

SUBDIVISION OF SECTION 23,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
13.90	Left bank of the Walker River, bears ENE. and WSW, thence through cottonwood trees.
19.960	Point for the SW 1/16 sec. cor. of sec. 23, at intersection with the E-W center line of the SW1/4, on the W. bdy. of Indian Allotment No. 108; there is no remaining evidence of the position of the 1922 iron post. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. SW 1/16 S23 2009
29.940	Point for the C-N-SW 1/64 sec. cor. of sec. 23, identical with the NW. corner of Indian Allotment No. 108; there is no remaining evidence of the position of the 1922 iron post. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. S23 C-N-SW 1/64 2009
39.920	Thence leaving the W. bdy. of Indian Allotment No. 108 and continuing on the N-S center line of the SW1/4 of sec. 23. The C-W 1/16 sec. cor. of sec. 23. <hr/>
	From the point for the C-S 1/16 sec. cor. of sec. 23. N. 89°47'00" W., on the E-W center line of the SW1/4 of sec. 23. Across nearly level developed land.
5.00	Descend into river bottom lands.
10.044	The point for the C-E-SW 1/64 sec. cor. of sec. 23, on the E. bdy. of Indian Allotment No. 108. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. S23 C-E-SW 1/64 2009
11.00	Concrete lined irrigation ditch, 20 lks. wide, 4 ft. deep, drains S. 50° E.

SUBDIVISION OF SECTION 23,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.088	The SW 1/16 sec. cor. of sec. 23, on the W. Bdy. of Indian Allotment No. 108.
26.10	Left bank of the Walker River, bears N. and S., thence across river, course S.
26.50	Right bank of the Walker River, bears N. and S.
40.174	The S 1/16 sec. cor. of secs. 22 and 23.
	<hr/> <p>From the C-E-SW 1/64 sec. cor. of sec. 23, on the E. Bdy. of Indian Allotment No. 108.</p> <p>N. 0°03'20" E., on the N-S center line of the NE1/4SW1/4 of sec. 23, identical with a portion of the E. bdy. of Indian Allotment No. 108.</p> <p>Across rolling land covered with shadescale, cheat and bunch grass.</p>
9.983	<p>Point for the NE-SW 1/64 sec. cor. of sec. 23, identical with the NE. corner of Indian Allotment No. 108, at intersection with the E-W center line of the NE1/4SW1/4; there is no remaining evidence of the 1922 iron post.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S23 NE-SW 1/64 2009</p>
	<p>Thence leaving the E. bdy. of Indian Allotment No. 108 and continuing on the N-S center line of the NE1/4SW1/4 of sec. 23.</p>
10.60	Concrete irrigation ditch, 25 lks. wide, drains S. 40° W.
17.50	Concrete irrigation ditch, 25 lks. wide, drains S. 30° E.
19.966	The C-E-W 1/64 sec. cor. of sec. 23.
	<hr/> <p>From the point for the C-N-S 1/64 sec. cor. of sec. 23.</p> <p>N. 89°48'00" W., on the E-W center line of the NE1/4SW1/4 of sec. 23.</p> <p>Across rolling land, covered with shadescale, cheat and bunch grass.</p>
9.00	Descend into river bottom lands.
10.45	Concrete lined irrigation ditch, 25 lks. wide, 5 ft. deep, drains S. 40° W., thence through cottonwood trees.

SUBDIVISION OF SECTION 23,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
10.051	The NE-SW 1/64 sec. cor. of sec. 23, identical with the NE. cor. of Indian Allotment No. 108.
	Thence continue on the E-W center line of the NE1/4SW1/4 of sec. 23, identical with the N. bdy. of Indian Allotment No. 108.
20.102	The C-N-SW 1/64 sec. cor. of sec. 23, identical with the NW. cor. of Indian Allotment No. 108.
	From the point for the E-W 1/64 sec. cor. of secs. 23 and 26.
	N. 0°03'20" E., on the N-S center line of the SE1/4SW1/4 of sec. 23.
	Across level cultivated field.
6.50	Leave cultivated field, enter cottonwood trees.
9.80	Right bank of the Walker River, bears NW. and SE., thence across river, course SE.
9.983	Point for the SE-SW 1/64 sec. cor. of sec. 23, identical with the SE. cor. of Indian Allotment No. 108, at intersection with the E-W center line of the SE1/4SW1/4, falls in river where it is impractical to establish a permanent monument.
	Thence continue on the N-S center line of the SE1/4SW1/4 of sec. 23, identical with a portion of the E. bdy. of Indian Allotment No. 108
10.80	Left bank of the Walker River, bears NW. and SE.
11.583	Point for the 1922 witness cor. to the SE-SW 1/64 sec. cor. of sec. 23, identical with the SW cor. of Indian Allotment No. 108, at record distance; there is no remaining evidence of the 1922 iron post. This position no longer has any function.
19.35	Concrete irrigation ditch, 25 lks. wide, 5 ft. deep, drains S. 68° E.
19.966	The C-E-SW 1/64 sec. cor. of sec. 23, on the E. bdy. of Indian Allotment No. 108.
	From the C-S-S 1/64 sec. cor. of sec. 23.
	N. 89°45'50" W., on the E-W center line of the SE1/4SW1/4 of sec. 23.
	Across rolling land, covered with shadecale, cheat and bunch grass.
2.70	Concrete irrigation ditch, 25 lks. wide, 5 ft. deep, drains S. 55° E.
4.00	Barbed wire fence, bears S. 55° E., and N. 55° W. for 0.46 chs. dist., thence W.

SUBDIVISION OF SECTION 23,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
9.40	Left bank of the Walker River, bears NW. and SE., thence across river, course SE.
10.036	The point for the SE-SW 1/64 sec. cor. of sec. 23, identical with the SW. cor. of Indian Allotment No. 108. Thence continue on the E-W center line of the SE1/4SW1/4 of sec. 23, identical with the S. bdy. of Indian Allotment No. 108.
10.55	Right bank of the Walker River, bears NW. and SE.
20.072	The C-S-SW 1/64 sec. cor. of sec. 23, identical with the SW. cor. of Indian Allotment No. 108. <hr/>
	N. 89°46'00" W., on the E-W center line of the SW1/4SW1/4 of sec. 23. Across river bottom lands, covered with scattered cottonwood trees and shadescale.
0.50	Barbed wire fence, bears NNW. and S.
20.072	The S-S 1/64 sec. cor. of secs. 22 and 23. <hr/>
	From the C-N-SW 1/64 sec. cor. of sec. 23, identical with the NW. cor. of Indian Allotment No. 108. N. 89°48'30" W., on the E-W center line of the NW1/4SW1/4 of sec. 23. Across river bottom lands, covered with scattered cottonwood trees and shadescale.
10.30	Left bank of the Walker River, bears NNW. and SSE., thence across river, course SSE.
10.90	Right bank of the Walker River, bears NNW. and SSE.
20.103	The N-S 1/64 sec. cor. of secs. 22 and 23. <hr/>
	From the C-W 1/16 sec. cor. of sec. 23. N. 0°09'20" W., on the N-S center line of the NW 1/4 of sec. 23. Across river bottom lands, covered with scattered cottonwoods, shadescale, cheat and bunch grass.
10.018	Point for the C-S-NW 1/64 sec. cor. of sec. 23. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

SUBDIVISION OF SECTION 23,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">S23 C-S-NW 1/64</p> <p style="text-align: center;">2009</p> <p>From this point, the cor. of fallen barbed wire fences, extending N., S., E. and W., bears N. 64° W., 0.10 chs. dist.</p>
20.036	<p>Point for the NW 1/16 sec. cor. of sec. 23, at intersection with E-W center line of the NW1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S23</p> <p style="text-align: center;">2009</p> <p>From this point, the cor. of a fallen barbed wire fence, extending N. and a standing barbed wire fence, extending W., bears N. 28° W., 0.29 chs. dist.</p> <p>Thence along fallen fence.</p>
27.90	Concrete lined irrigation ditch, 20 lks. wide, 5 ft. deep, drains S. 70° E., leave river bottom lands and cottonwood trees, thence across rolling land.
30.054	<p>Point for the C-N-NW 1/64 sec. cor. of sec. 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S23 C-N-NW 1/64</p> <p style="text-align: center;">2009</p>
40.072	<p>The W 1/16 sec. cor. of secs. 14 and 23.</p> <hr/> <p>From the point for the C-N 1/16 sec. cor. of sec. 23.</p> <p>N. 89°50'40" W., on the E-W center line of the NW1/4 of sec. 23.</p> <p>Across nearly level land, covered with shadecale, cheat and bunch grass.</p>
0.70	Barbed wire fence, bears N. 33° W. and S. 33° E.
1.40	Little Dam Road, 40 lks. wide, bears N. 35° W. and S. 35° E.
4.50	Descend into river bottom lands.
10.103	Point for the C-E-NW 1/64 sec. cor. of sec. 23.

SUBDIVISION OF SECTION 23,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S23 C-E-NW 1/64 2009</p>
11.25	Concrete lined irrigation ditch, 20 lks. wide, drains S. 50° E.
19.10	Dirt road, 15 lks. wide, bears N. and SSE.
20.206	The NW 1/16 sec. cor. of sec. 22. Thence through scattered cotton wood trees.
40.412	The N 1/16 sec. cor. of secs. 22 and 23.
	<hr/> <p>From the C-E-NW 1/64 sec. cor. of sec. 23.</p> <p>N. 0°01'40" W., on the N-S center line of the NE1/4NW1/4 of sec. 23.</p> <p>Across broken lands, covered with shadescale, cheat and bunch grass.</p>
10.020	<p>Point for the NE-NW 1/64 sec. cor. of sec. 23, at intersection with E-W center line of the NW1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S23 NE-NW 1/64 2009</p>
14.70	Barbed wire fence, bears N. 33° W. and S. 33° E.
20.040	The point for the E-W 1/64 sec. cor. of secs. 14 and 23.
	<hr/> <p>From the point for the C-N-N 1/64 sec. cor. of sec. 23.</p> <p>N. 89°51'10" W., on the E-W center line of the NE1/4NW1/4 of sec. 23.</p> <p>Across nearly level land, covered with shadescale, cheat and bunch grass.</p>
7.10	Barbed wire fence, bears N. 33° W. and S. 33° E.
7.90	Little Dam Road, a graded dirt road, 40 lks. wide, bears N. 35° W. and S. 35° E.
10.125	The NE-NW 1/64 sec. cor. of sec. 23.

SUBDIVISION OF SECTION 23,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Thence across broken land.
20.250	The C-N-NW 1/64 sec. cor. of sec. 23.
	<hr/> <p>From the C-E-W 1/64 sec. cor. of sec. 23.</p> <p>N. 0°01'40" W., on the N-S center line of the SE1/4NW1/4 of sec. 23.</p> <p>Across broken lands, covered with shadescall, cheat and bunch grass.</p>
7.30	Leave broken lands, enter nearly level land.
10.020	Point for the SE-NW 1/64 sec. cor. of sec. 23, at intersection with the E-W center line of the SE1/4NW1/4.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S23 SE-NW 1/64 2009</p>
10.20	Descend into river bottom lands.
14.30	Concrete lined irrigation ditch, 20 lks. wide, 5 ft. deep, drains, S. 50° W.
19.10	Concrete lined irrigation ditch, 20 lks. wide, 5 ft. deep, drains, S. 55° E.
20.040	The C-E-NW 1/64 sec. cor. of sec. 23.
	<hr/> <p>From the point for the C-S-N 1/64 sec. cor. of sec. 23.</p> <p>N. 89°49'50" W., on the E-W center line of the SE1/4NW1/4 of sec. 23.</p> <p>Across river bottom lands, covered with scattered cottonwood trees, shadescall, cheat and bunch grass.</p>
10.081	The SE-NW 1/64 sec. cor. of sec. 23.
20.162	The C-S-NW 1/64 sec. cor. of sec. 23.
	<hr/> <p>N. 89°50'00" W., on the E-W center line of the SW1/4NW1/4 of sec. 23.</p> <p>Across river bottom lands, covered with scattered cottonwood trees, shadescall, cheat and bunch grass.</p>
20.162	The S-N 1/64 sec. cor. of secs. 22 and 23.
	<hr/>

SUBDIVISION OF SECTION 23,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the C-N-NW 1/64 sec. cor. of sec. 23.</p> <p>N. 89°51'20" W., on the E-W center line of the NW1/4NW1/4 of sec. 23.</p> <p>Across river bottom lands, covered with scattered cottonwood trees, shadescala, cheat and bunch grass.</p>
3.20	Concrete lined irrigation ditch, 20 lks. wide, 5 ft. deep, drains S. 50° E.
20.251	The N-N 1/64 sec. cor. of secs. 22 and 23.
<p style="text-align: center;">SUBDIVISION OF SECTION 25, T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA</p>	
	<p>From the 1/4 sec. cor. of secs. 25 and 36.</p> <p>N. 0°33'00" W., on the N-S center line of sec. 25.</p> <p>Across rolling land, covered with shadescala, scattered cottonwoods and along W. side of barbed wire fence.</p>
1.90	From this point, the cor. of barbed wire fences, extending S. and S. 75° E., bears E., 0.18 chs. dist.
3.80	Arena Road, a graded dirt road, 15 lks. wide, bears NW. and SE.
4.10	Irrigation ditch, 15 lks. wide, drains SE.
5.00	Concrete lined irrigation ditch, 20 lks. wide, 5 ft. deep, drains SE., leave cottonwood trees.
19.977	Point for the C-S 1/16 sec. cor. of sec. 25.
	POINT NOT MONUMENTED
35.00	Graded dirt road, 50 lks. wide, bears NW. and SE.
39.954	Point for the center 1/4 sec. cor. of sec. 25, at intersection with the E-W center line.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T13N R28E C 1/4 S25</p> <p style="text-align: center;">2009</p> <p>Point is located on SE. edge of gravel road, 25 lks. wide, bears NE. and SW., traversing to a garbage transfer station.</p>
40.72	Barbed wire fence, bears N. 30° W. and S. 30° E.
49.00	Barbed wire fence, bears N. 46° W. and S. 46° E.

SUBDIVISION OF SECTION 25,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
80.058	The 1/4 sec. cor of secs. 24 and 25.
	<hr/> <p>From the 1/4 sec. cor. of secs. 25 and 30, on the E. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of of the west boundary of T. 13 N., R. 29 E., executed under Group No. 181.</p> <p>S. 89°44'00" W., on the E-W center line of sec. 25.</p> <p>Across rolling land, covered with shadescall, cheat and bunch grass.</p>
31.00	Barbed wire fence, bears N. 46° W. and S. 46° E.
36.60	Chain link fence enclosing garbage transfer station, bears N. 60° E. and S. 60° W., thence across transfer station.
38.30	Chain link fence enclosing garbage transfer station, bears N. 30° W. and S. 30° E., thence across rolling land, covered with shadescall, cheat and bunch grass.
40.401	The center 1/4 sec. cor of sec. 25.
40.93	Barbed wire fence, bears N. 30° E. and S. 30° W.
44.90	Graded dirt road, 50 lks. wide, bears N. 45° W. and S. 45° E.
60.217	Point for the C-W 1/16 sec. cor. of sec. 25.
	POINT NOT MONUMENTED
76.65	U.S. Highway No. 95, asphalt surfaced, 50 lks. wide, bears N. 1° E. and S. 1° W.
79.60	Dirt road, 30 lks. wide, bears N. and SSE.
79.87	Dirt road, 32 lks. wide, bears NNW. and SSE.
80.033	The 1/4 sec. cor. of secs. 25 and 26.
	<hr/> <p>From the W 1/16 sec. cor. of secs. 25 and 36.</p> <p>N. 0°21'10" W., on the N-S center line of the SW1/4 of sec. 25.</p> <p>Across level farmland, along W. side of dirt road, and along E. side of barbed wire fence.</p>
9.988	Point for the C-S-SW 1/64 sec. cor. of sec. 25.
	POINT NOT MONUMENTED
19.976	Point for the SW 1/16 sec. cor. of sec. 25, at intersection with the E-W center line of the SW 1/4.

SUBDIVISION OF SECTION 25,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 3 ins. below the surface of a dirt road, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SW 1/16 S25</p> <p style="text-align: center;">2009</p> <p>Point is located in a dirt road, 25 lks. wide, bears N. and S., 5 lks. easterly of the W. edge.</p>
22.50	Arena Road, a graded dirt road, 35 lks. wide, parallels concrete irrigation ditch.
22.80	Concrete lined irrigation ditch, 20 lks. wide, 5 ft. deep, drains S. 85° E.
	Thence across rolling land, through shadescale.
39.893	The point for the C-W 1/16 sec. cor. of sec. 25.
	<hr/> <p>From the point for the C-S 1/16 sec. cor. of sec. 25.</p> <p>S. 89°54'30" W., on the E-W center line of the SW1/4 of sec. 25.</p> <p>Across rolling land, covered with shadescale, cheat and bunch grass.</p>
9.943	<p>Point for the C-E-SW 1/64 sec. cor. of sec. 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S25 C-E-SW 1/64</p> <p style="text-align: center;">2009</p>
11.80	Dirt road, 10 lks. wide, bears NW. and SE.
14.50	Concrete irrigation ditch, 20 lks. wide, 5 ft. deep, drains SE.
14.60	Arena Road, a dirt road, 35 lks. wide, parallels irrigation ditch.
19.70	Concrete irrigation ditch, 10 lks. wide, 4 ft. deep, drains S.
19.886	The SW 1/16 sec. cor. of sec. 25.
19.99	Barbed wire fence, bears N. and S., thence across cultivated field.
29.30	Dirt road, 15 lks. wide, bears N. and S.
29.65	Barbed wire fence, parallels dirt road.
29.772	The C-W-SW 1/64 sec. cor. of sec. 25, perpetuated by person(s) unknown, monumented with a steel T-bar fence post, firmly set,

SUBDIVISION OF SECTION 25,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>with a flagged 16D nail set alongside. This position is in agreement with the position accepted by George M. Wilson, Nevada Professional Land Surveyor No. 3806, as shown on the Record of Survey, recorded as File No. 105699, Office of the County Recorder, Mineral County, Nevada and also accepted by Charles F. Cassano, Nevada Professional Land Surveyor No. 9607, as shown on the Record of Survey, recorded as File No. 108050, Office of the County Recorder, Mineral County, Nevada, and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S25 C-W-SW 1/64 2010</p> <p>Deposit 16D nail inside stainless steel post and reset steel fence post alongside.</p> <hr/> <p>S. 89°35'40" W., beginning new measurement.</p> <p>Thence along old barbed wire fence and a line of cottonwood trees, S. of new barbed wire fence, bears E. and W.</p> <p>6.50 From this point, the cor. of a fence barbed wire fences, extending N., S. and E., bears N., 0.05 chs. dist.</p> <p>6.85 U.S. Highway No. 95, asphalt surfaced, 50 lks. wide, bears N. 1° E. and S. 1° W.</p> <p>7.710 A position established by Charles F. Cassano, Nevada Professional Land Surveyor No. 9607, monumented with a rebar, 5/8 in. dia., firmly set, projecting 4 ins. above the ground, with plastic cap mkd. PLS 9607, as shown on the Record of Survey, recorded as File No. 108050, Office of the County Recorder, Mineral County, Nevada.</p> <p>Cor. is located in barbed wire fence, bears S. and N., 0.05 chs. dist. to the cor. of barbed wire fences, extending N. and W.</p> <p>9.995 The S 1/16 sec. cor. of secs. 25 and 26.</p> <hr/> <p>From the E-W 1/64 sec. cor. of secs. 25 and 36.</p> <p>N. 0°27'00" W., on the N-S center line of the SE1/4SW1/4 of sec. 25.</p> <p>Across nearly level land, covered with shadecale, cheat and bunch grass.</p> <p>7.30 Leave cultivated lands, bears W. and S.</p>
--------	--

SUBDIVISION OF SECTION 25,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
14.50	Arena Road, a dirt road, 35 lks. wide, parallels irrigation ditch.
14.90	Concrete irrigation ditch, 20 lks. wide, 5 ft. deep, drains SE.
18.80	Dirt road, 10 lks. wide, bears NW. and SE.
19.977	The C-E-SW 1/64 sec. cor. of sec. 25.
	From the W-W 1/64 sec. cor. of secs. 25 and 36.
	N. 0°05'20" W., on the N-S center line of the SW1/4SW1/4 of sec. 25.
	Across nearly level developed land, along row of cottonwood trees and E. side of concrete irrigation ditch.
3.209	From this point, a position established by George M. Wilson, Nevada Professional Land Surveyor No. 3806, monumented with a rebar, 1/2 in. dia., firmly set flush with the surface of the ground, bears E., 0.053 chs. dist., as shown on the Record of Survey, recorded as File No. 105699, Office of the County Recorder, Mineral County, Nevada.
3.50	From this point, a bend in concrete lined irrigation ditch, 10 lks. wide, 3 ft. deep, extends W. and drains S., bears W., 0.15 chs. dist.
3.60	From this point, the cor. of barbed wire fences, extending N. and SW., bears E., 0.07 chs. dist., thence along W. side of fence line.
8.1055	Point for the 1/16384 sec. cor., on the N-S center line of the SW1/4SW1/4 of sec. 25.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	1 ----- 16384 2010
9.976	Point for the SW-SW 1/64 sec. cor. of sec. 25, at intersection with the E-W center line of the SW1/4SW1/4.
	POINT NOT MONUMENTED
19.979	The C-W-SW 1/64 sec. cor. of sec. 25.
	From the point for the C-S-SW 1/64 sec. cor. of sec. 25.
	S. 89°49'20" W., on the E-W center line of the SW1/4SW1/4 of sec. 25.
	Across level cultivated land.

SUBDIVISION OF SECTION 25,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
9.85	Barbed wire fence, bears N. and S.
9.932	The point for the SW-SW 1/64 sec. cor. of sec. 25.
17.60	U.S. Highway No. 95, asphalt surfaced, 50 lks. wide, bears N. 6° E. and S. 6° W.
19.921	<p>The S-S 1/64 sec. cor. of secs. 25 and 26, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 13 N., R. 28 E., executed under Group No. 635.</p> <p>Cor. is located in barbed wire fence, bears E. and W.</p> <hr/> <p>From the 1/1024 sec. cor. of secs. 25 and 36.</p> <p>N. 0°09'20" W., on the computed N-S center line of the SW1/4SE1/4SW1/4SW1/4 of sec. 25.</p> <p>Across level cultivated land.</p>
4.988	<p>Point for the 1/1024 sec. cor., on the E-W center line of the SE1/4SW1/4SW1/4 of sec. 25, at its computed position.</p> <p>POINT NOT MONUMENTED</p> <hr/> <p>N. 0°09'20" W., on a portion of the computed N-S center line of the NW1/4SE1/4SW1/4SW1/4 of sec. 25.</p>
3.1175	<p>Point for the 1/16384 sec. cor., on the N-S center line of the NW1/4SE1/4SW1/4SW1/4 of sec. 25, at its computed position.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>1</p> <hr style="width: 20%; margin: 0 auto;"/> <p>16384</p> <p>2010</p> </div> <p>From this cor., the cor. of barbed wire fences, extending N. and W., bears S. 70° E., 0.75 chs. dist.</p> <hr/> <p>S. 89°52'10" W., on the computed E-W center line of the SE1/4NW1/4NW1/4SE1/4SW1/4SW1/4 of sec. 25.</p> <p>Across level cultivated land.</p>
1.243	The point for the 1/16384 sec. cor., on the N-S center line of the NW1/4NW1/4SE1/4SW1/4SW1/4 of sec. 25, at its computed position.

SUBDIVISION OF SECTION 25,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	POINT NOT MONUMENTED
	<hr/> <p>S. 89°52'10" W., on the computed E-W center line of the SW1/4NW1/4NW1/4SE1/4SW1/4SW1/4 of sec. 25.</p> <p>Across level cultivated land.</p>
1.16	Barbed wire fence, bears N. and S.
1.243	The 1/16384 sec. cor., on the N-S center line of the SW1/4SW1/4 of sec. 25.
	<hr/> <p style="text-align: center;">FURTHER SUBDIVISION OF SECTION 21, T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>
	<p>From the C-E 1/16 sec. cor. of sec. 21.</p> <p>N. 0°01'40" E., on the N-S center line of the NE1/4 of sec. 21.</p> <p>Across level land, along E. side of barbed wire fence and W. side of cultivated field.</p>
19.975	<p>Point for the NE 1/16 sec. cor. of sec. 21, at intersection with the E-W center line of the NE1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S21</p> <p style="text-align: center;">2009</p>
	<p>Leave cultivated lands, over shadecale, cheat and bunch grass.</p>
29.963	<p>Point for the C-N-NE 1/64 sec. cor. of sec. 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S21 C-N-NE 1/64</p> <p style="text-align: center;">2009</p>
33.45	West Loop Road, asphalt surfaced, 35 lks. wide, bears N. 40° E. and S. 40° W.
34.10	Power line, parallels West Loop Road.
37.60	From this point, the cor. of chain link fences, extending N. and W., bears W., 0.03 chs., thence along chain link fence.
39.91	Cor. of chain link fences, extending W. and S.

FURTHER SUBDIVISION OF SECTION 21,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.951	<p>The E 1/16 sec. cor. of secs. 16 and 21, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 13 N., R. 28 E., executed under Group No. 635.</p> <hr/> <p>From the N 1/16 sec. cor. of secs. 21 and 22, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 13 N., R. 28 E., executed under Group No. 635.</p> <p>S. 89°58'00" W., on the E-W center line of the NE1/4 of sec. 21.</p> <p>Across cultivated lands.</p>
10.012	<p>Point for the C-E-NE 1/64 sec. cor. of sec. 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S21 C-E-NE 1/64 2009</p>
20.024	<p>The NE 1/16 sec. cor. of sec. 21.</p>
29.70	<p>West Loop Road, asphalt surfaced, curves right to the NE. and curves left to the SW.</p>
30.035	<p>Point for the C-W-NE 1/64 sec. cor. of sec. 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S21 C-W-NE 1/64 2009</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 34°14' E., 92.4 lks. dist., with brass cap mkd. RM C-W-NE 1/64 S21 61.0 FT TO COR 2009 and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 37°55' W., 53.3 lks.</p>

FURTHER SUBDIVISION OF SECTION 21,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	dist., with brass cap mkd. RM C-W-NE 1/64 S21 35.2 FT TO COR 2009 and an arrow pointing to the cor.
40.046	The C-N 1/16 sec. cor. of sec. 21.
	<p>From the N-N 1/64 sec. cor. of secs. 21 and 22, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 13 N., R. 28 E., executed under Group No. 635.</p> <p>Cor. is located on N. side of the cor. of barbed wire fences, extending N., S. and E.</p> <p>S. 89°53'30" W., on the E-W center line of the NE1/4NE1/4 of sec. 21.</p> <p>Across level land, covered with shadescall, cheat and bunch grass, and along N. side of cultivated field.</p>
13.50	Irrigation ditch, bears NE. and SW., leave cultivated lands, through shadescall, cheat and bunch grass.
20.050	The C-N-NE 1/64 sec. cor. of sec. 21.
	<p>From the C-E-E 1/64 sec. cor. of sec. 21.</p> <p>N. 0°07'00" E., on the N-S center line of the SE1/4NE1/4 of sec. 21.</p> <p>Across level cultivated land.</p>
19.998	The C-E-NE 1/64 sec. cor. of sec. 21.
	<p>From the C-W-E 1/64 sec. cor. of sec. 21, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with aluminum cap mkd. as described in the field notes of the subdivision of sec. 21, T. 13 N., R. 28 E., executed under Group No. 635, with a mound of stone, 2 ft. base, 1 ft. high, W. of cor. and a steel fence post set alongside.</p> <p>N. 0°03'50" W., on the N-S center line of the SW1/4NE1/4 of sec. 21.</p> <p>Across nearly level land, covered with shadescall cheat and bunch grass, and along E side of West loop Road.</p>
19.949	The C-W-NE 1/64 sec. cor. of sec. 21.
	<p>FURTHER SUBDIVISION OF SECTION 22, T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <p>From the C-E 1/16 sec. cor. of sec. 22.</p>

FURTHER SUBDIVISION OF SECTION 22,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>N. 0°17'30" W., on the N-S center line of NE1/4 of sec. 22.</p> <p>Across level farmland, between dirt road and concrete lined irrigation ditch.</p>
10.011	<p>Point for the C-S-NE 1/64 sec. cor. of sec. 22.</p> <p>Chisel an X in concrete lined irrigation ditch.</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 20°24' E., 24.4 lks. dist., with brass cap mkd. RM C-S-NE 1/64 S22 16.1 FT TO COR. 2009 and an arrow pointing to the cor.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 76°26' W., 20.6 lks. dist., with brass cap mkd. RM C-S-NE 1/64 S22 13.6 FT TO COR. 2009 and an arrow pointing to the cor.</p> <p>Cor. is located in irrigation ditch, 20 lks. wide, 4 ft. deep, drains S.</p>
19.70	Leave irrigation ditch.
20.022	<p>Point for the NE 1/16 sec. cor. of sec. 22, at intersection with the E-W center line of the NE1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p>NE 1/16 S22</p> <p>2009</p>
30.035	<p>Point for the C-N-NE 1/64 sec. cor. of sec. 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p>S22 C-N-NE 1/64</p> <p>2009</p>
40.048	<p>The E 1/16 sec. cor. of secs. 15 and 22.</p> <hr/> <p>From the N 1/16 sec. cor. of secs. 22 and 23.</p> <p>N. 89°54'50" W., on the E-W center line of the NE1/4 of sec. 22.</p> <p>Across river bottom land, covered with scattered cottonwood trees, shadescale, cheat and bunch grass.</p>

FURTHER SUBDIVISION OF SECTION 22,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
7.30	Left bank of the Walker River, bears NE. and SW., thence across river, course SW.
8.80	Right bank of the Walker River, bears NE. and SW.
10.020	Point for the C-E-NE 1/64 sec. cor. of sec. 22. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. S22 C-E-NE 1/64 2009
15.00	Leave native vegetation, enter farmland.
20.040	The NE 1/16 sec. cor. of sec. 22.
20.50	Intersect curve in concrete lined irrigation ditch, 20 lks. wide, 4 ft. deep, bears from the W. and drains S., thence along irrigation ditch.
29.80	Leave irrigation ditch, bears from the NW., and drains E.
30.061	Point for the C-W-NE 1/64 sec. cor. of sec. 22, on the N. bdy. of Allotment No. 493. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. S22 C-W-NE 1/64 2009
30.45	East Loop Road, 40 lks. wide, bears N. 20° W. and curves right to the SE.
40.082	The C-N 1/16 sec. cor. of sec. 22. <hr/> From the C-E-NE 1/64 sec. cor. of sec. 22. N. 0°21'00" W., on the N-S center line of the NE1/4NE1/4 of sec. 22. Across river bottom lands, covered with cottonwood trees, shadescall, cheat and bunch grass.
2.50	Enter cultivated field, bears NE. and SW.
13.50	Leave cultivated field, thence through scattered cottonwood trees and shadescall.

FURTHER SUBDIVISION OF SECTION 22,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
14.50	Right bank of the Walker River, bears NW. and SE., thence across river, course SE.
15.80	Left bank of the Walker River, bears NW. and SE.
20.024	The E-E 1/64 sec. cor. of secs. 15 and 22.
	<hr/>
	From the C-E-E 1/64 sec. cor. of sec. 22.
	N. 0°21'30" W., on the N-S center line of the SE1/4NE1/4 of sec. 22.
	Across cultivated lands.
10.019	Point for the SE-NE 1/64 sec. cor. of sec. 22, at intersection with the E-W center line of the SE1/4NE1/4.
	Chisel an X in concrete surface of irrigation ditch.
	from which
	A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 44°20' W., 22.1 lks. dist., with brass cap mkd. RM SE-NE 1/64 S22 14.6 FT TO COR 2009 and an arrow pointing to the cor.
	A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 55°57' W., 19.8 lks. dist., with brass cap mkd. RM SE-NE 1/64 S22 13.1 FT TO COR 2009 and an arrow pointing to the cor.
15.00	Leave cultivated field.
17.50	Right bank of the Walker River, bears NW. and SE., thence across river, course SE.
18.20	Right bank of the Walker River, bears NE. and SW., thence through cottonwood trees, willows and shadescale.
20.032	The C-E-NE 1/64 sec. cor. of sec. 22.
	<hr/>
	From the S-N 1/64 sec. cor. of secs. 22 and 23.
	N. 89°54'10" W., on the E-W center line of the SE1/4NE1/4 of sec. 22.
	Across river bottom lands, covered with cottonwood trees, shadescale, cheat and bunch grass.
3.20	Left bank of the Walker River, bears NNE. and SSE., thence across river, course SSE.
3.80	Right bank of the Walker River, bears NNE. and SSE.
5.70	Enter cultivated field.

FURTHER SUBDIVISION OF SECTION 22,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
10.029	The SE-NE 1/64 sec. cor. of sec. 22. Thence along concrete lined irrigation ditch.
20.061	The C-S-NE 1/64 sec. cor. of sec. 22. <hr/>
	From the C-W-E 1/64 sec. cor. of sec. 22. N. 0°14'40" W., on the N-S center line of the SW1/4NE1/4 of sec. 22. Across level farmland, along East Loop Road, asphalt surfaced, 40 lks. wide.
10.013	Point for the SW-NE 1/64 sec. cor. of sec. 22, at intersection with the E-W center line of the SW1/4NE1/4. Set a magnetized nail flush with the asphalt surface. from which A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 61°04' W., 32.6 lks. dist., with brass cap mkd. RM SW-NE 1/64 S22 21.5 FT TO COR 2009 and an arrow pointing to the cor. A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 58°54' W., 35.5 lks. dist., with brass cap mkd. RM SW-NE 1/64 S22 23.4 FT TO COR 2009 and an arrow pointing to the cor.
20.031	The C-W-NE 1/64 sec. cor. of sec. 22. <hr/>
	From the C-S-NE 1/64 sec. cor. of sec. 22. N. 89°57'20" W., on the E-W center line of the SW1/4NE1/4 of sec. 22. Across level farmland and along irrigation ditch.
10.030	The SW-NE 1/64 sec. cor. of sec. 22. Thence across cultivated field.
19.96	Cor. of fences, extending N., S. and W. Thence along fence.
20.060	The C-S-N 1/64 sec. cor. of sec. 22. <hr/>
	From the C-N-NE 1/64 sec. cor. of sec. 22. N. 89°56'30" W., on the E-W center line of the NW1/4NE1/4 of sec. 22.

FURTHER SUBDIVISION OF SECTION 22,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Across cultivated field and along fence.
13.40	Concrete irrigation ditch, 20 lks. wide, 4 ft. deep, drains S. 20° E.
14.20	East Loop Road, asphalt surfaced, 40 lks. wide, parallels irrigation ditch.
20.022	The C-N-N 1/64 sec. cor. of sec. 22.
	<hr/> <p>From the E 1/16 sec. cor. of secs. 22 and 27, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, with the cap sheared off at the surface of the ground.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \text{S22} \\ \text{E } 1/16 \text{ ---} \\ \text{S27} \end{array}$ <p>2010</p> </div> <p>Bury aluminum post alongside the stainless steel post.</p> <p>N. 0°08'00" W., on the N-S center line of the SE1/4 of sec. 22.</p>
0.70	Barbed wire fence, bears E. and W. for 0.06 chs. dist. to the cor. of barbed wire fences, extending N. and W.
	Thence across cultivated fields and along fence.
9.983	Point for the C-S-SE 1/64 sec. cor. of sec. 22.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \text{S22} \\ \text{C-S-SE} \\ 1/64 \end{array}$ <p>2009</p> </div> <p>Cor. is located in fence line, bears N. and S.</p>
19.966	Point for the SE 1/16 sec. cor. of sec. 22, at intersection with the E-W center line of the SE1/4.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>SE 1/16 S22</p> <p>2010</p> </div>

FURTHER SUBDIVISION OF SECTION 22,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Point is located at the cor. of fences, extending S., W. and SW. for 0.60 chs. dist., to cor. of dirt roads, each 20 lks. wide, extending N. and E.
20.00	Cor. of barbed wire fences, extending W. and S.
29.951	Point for the C-N-SE 1/64 sec. cor. of sec. 22. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. S22 C-N-SE 1/64 2009
39.936	The C-E 1/16 sec. cor. of sec. 22. From the S 1/16 sec. cor. of secs. 22 and 23. N. 89°57'40" W., on the E-W center line of the SE 1/4 of sec. 22. Across level farmland, along S. side of graded dirt road.
0.50	Intersect curve in irrigation ditch, 20 lks. wide, 4 ft. deep, bears from W., and drains E., thence along N. side.
10.033	The C-E-SE 1/64 sec. cor. of sec. 22, determined by Rick P. Christen, Nevada Professional Surveyor No. 11178, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, no mks. visible, as shown on Map No. 991002S22, on file with the Walker River Housing Authority, Schurz, Nevada, and is accepted as a careful and faithful determination of the position of the corner. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. S22 C-E-SE 1/64 2009 Deposit rebar inside the stainless steel post.
20.066	The SE 1/16 sec. cor. of sec. 22.
29.60	Barbed wire fence, bears S. and N. for 0.02 chs. dist. to the cor. of fences, extending S. and E.
30.097	Point for the C-W-SE 1/64 sec. cor. of sec. 22. Set a magnetized nail flush with the asphalt surface

FURTHER SUBDIVISION OF SECTION 22,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	from which
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 40°10' W., 62.9 lks. dist., with brass cap mkd. RM C-W-SE 1/64 S22 41.5 FT TO COR 2009 and an arrow pointing to the cor.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 60°13' W., 46.8 lks. dist., with brass cap mkd. RM C-W-SE 1/64 S22 30.9 FT TO COR 2009 and an arrow pointing to the cor.</p> <p>Point falls in asphalt surface of East Loop Road, 35 lks. wide, bears N. and S.</p>
40.128	The C-S 1/16 sec. cor. of sec. 22.
	<hr/> <p>From the C-E-SE 1/64 sec. cor. of sec. 22.</p> <p>N. 0°06'00" W., on the N-S center line of the NE1/4SE1/4 of sec. 22.</p> <p>Across cultivated fields.</p>
0.20	Graded dirt road, 20 lks. wide, bears E. and W.
9.978	Point for the NE-SE 1/64 sec. cor. of sec. 22, at intersection with the E-W center line of the NE1/4SE1/4.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S22 NE-SE 1/64 2009</p>
	<p>From this point, the cor. of fences, extending N., E., and W., bears S. 68° W., 0.16 chs. dist.</p>
19.952	The C-E-E 1/64 sec. cor. of sec. 22.
	<hr/> <p>From the N-S 1/64 sec. cor. of secs. 22 and 23, monumented with a chiseled X in a concrete ditch, from which the 1986 reference monuments</p> <p>An aluminum post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, bears S. 45° E., 12.1 lks. dist., with aluminum cap mkd. RM N-S 1/64 S23 8FT 1986 and an arrow pointing to the cor.</p> <p>An aluminum post, 2 1/2 ins. diam., firmly set, projecting 1 in. above the ground, bears S. 45° W., 9.1 lks. dist., with aluminum cap mkd. mkd. RM N-S 1/64 S22 6FT 1986 and an arrow pointing to the cor.</p>

FURTHER SUBDIVISION OF SECTION 22,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>N. 89°55'20" W., on the E-W center line of the NE1/4SE1/4 of sec. 22.</p> <p>Across cultivated fields and along fence line.</p>
10.035	The NE-SE 1/64 sec. cor. of sec. 22.
10.19	Fence, bears N. and S.
20.073	The C-N-SE 1/64 sec. cor. of sec. 22.
	<hr/> <p>From the E-E 1/64 sec. cor. of secs. 22 and 27, monumented with an aluminum post, 2 1/2 ins. diam., with the the remains consisting of the sheared bottom portion found 6 ins. below the gound surface, with a rebar set by Rick P. Christen, Nevada Professional Surveyor No. 11178, 5/8 in. diam., 18 ins. long, with plastic cap mkd. PLS 11178, alongside the aluminum post as shown on Map No. 99102S22, on file with the Walker River Housing Authority, Schurz, Nevada.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S22 E-E 1/64 S27</p> <p style="text-align: center;">2009</p> <p>Deposit rebar inside stainless steel post and bury aluminum post remains alongside.</p> <p>N. 0°06'50" W., on the N-S center line of the SE1/4SE1/4 of sec. 22.</p> <p>Across level land.</p>
0.02	S. edge of Farm Road, asphalt surfaced, 40 lks. wide, bears E. and W.
0.65	Barbed wire fence, bears E. and W. for 0.03 chs. dist. to the cor. of fences, extending N. and E.
	Thence across cultivated fields and along fence.
19.956	The C-E-SE 1/64 sec. cor. of sec. 22.
	<hr/> <p>From the W-E 1/64 sec. cor. of secs. 22 and 27, monumented with the sheared bottom end of an aluminum post, 2 1/2 ins. diam., recovered 8 ins. below the surface of the ground in an upright position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p>

FURTHER SUBDIVISION OF SECTION 22,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>S22 W-E 1/64 S27</p> <p>2009</p> <p>Bury aluminum post remains alongside stainless steel post.</p> <p>Cor. is located at the intersection of the S. edge of Farm Road, asphalt surfaced, 40 lks. wide, bears E. and W. and East Loop Road, asphalt surfaced, 35 lks. wide, bears N. and S.</p> <p>N. 0°09'20" W., on the N-S center line of the SW1/4SE1/4 of sec. 22.</p> <p>Across level land, along East Loop Road.</p>
9.988	<p>Point for the SW-SE 1/64 sec. cor. of sec. 22, at intersection with the E-W center line of the SW1/4SE1/4.</p> <p>Set a magnetized nail flush with asphalt surface from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 59°00' E., 52.0 lks. dist., with brass cap mkd. RM SW-SE 1/64 S22 34.3 FT TO COR 2009 and an arrow pointing to the cor.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 89°20' W., 43.3 lks. dist., with brass cap mkd. RM SW-SE 1/64 S22 28.6 FT TO COR 2009 and an arrow pointing to the cor.</p> <p>Point falls in the asphalt surface of East Loop Road, 35 lks. wide, bears E. and W.</p>
19.976	<p>The C-W-SE 1/64 se. cor. of sec. 22.</p> <hr/> <p>From the C-S-SE 1/64 sec. cor. of sec. 22.</p> <p>N. 89°59'30" W., on the E-W center line of the SW1/4SE1/4 of sec. 22.</p> <p>Across cultivated field.</p>
10.028	The SW-SE 1/64 sec. cor. of sec. 22.
10.47	<p>Cor. of barbed wire fences, extending N., S. and W.</p> <p>Thence across cultivated field, along fence.</p>
20.055	<p>The C-S-S 1/64 sec. cor. of sec. 22.</p> <hr/> <p>From the C-W-SE 1/64 sec. cor. of sec. 22.</p>

FURTHER SUBDIVISION OF SECTION 22,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>N. 0°09'20" W., on the N-S center line of the NW1/4SE1/4 of sec. 22.</p> <p>Across level farmland, along East Loop Road.</p>
9.989	<p>Point for the NW-SE 1/64 sec. cor. of sec. 22, at intersection with E-W center line of the NW1/4SE1/4.</p> <p>Set a magnetized nail flush with asphalt surface from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 48°52' E., 48.0 lks. dist., with brass cap mkd. RM NW-SE 1/64 S22 31.7 FT TO COR 2009 and an arrow pointing to the cor.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 48°36' W., 47.6 lks. dist., with brass cap mkd. RM NW-SE 1/64 S22 31.4 FT TO COR 2009 and an arrow pointing to the cor.</p> <p>Point falls in the asphalt surface of East Loop Road, 35 lks. wide, bears N. and S.</p>
19.969	<p>The C-W-E 1/64 sec. cor. of sec. 22.</p> <hr/> <p>From the C-N-SE 1/64 sec. cor. of sec. 22.</p> <p>N. 89°56'20" W., on the E-W center line of the NW1/4SE1/4 of sec. 22.</p>
0.15	<p>Concrete lined irrigation ditch, 20 lks. wide, 4 ft. deep, drains S.</p> <p>Thence across level cultivated land.</p>
10.035	<p>The NW-SE 1/64 sec. cor. of sec. 22.</p>
20.071	<p>The C-N-S 1/64 sec. cor. of sec. 22.</p> <hr/> <p>From the C-E-SW 1/64 sec. cor. of sec. 22.</p> <p>N. 0°15'40" W., on the N-S center line of the NE1/4SW1/4 of sec. 22.</p> <p>Across cultivated field.</p>
9.996	<p>Point for the NE-SW 1/64 sec. cor. of sec. 22, at intersection with the E-W center line of the NE1/4SW1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

FURTHER SUBDIVISION OF SECTION 22,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>S22 NE-SW 1/64</p> <p>2009</p>
10.25	Irrigation ditch, drains E.
10.60	<p>From this point, the cor. of fences, extending N. and E., bears E., 0.25 chs. dist.</p> <p>Thence along W. side of fence and cultivated field.</p>
19.989	<p>The C-E-W 1/64 sec. cor. of sec. 22, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. as described in the field notes of the subdivision of the southwest 1/4 of section 22, T. 13 N., R. 28 E., executed under Group No. 635.</p> <p>Cor. is located W., 0.15 chs. dist. of a fence, bears N. and S.</p> <hr/> <p>From the C-N-S 1/64 sec. cor. of sec. 22.</p> <p>N. 89°58'00" W., on the E-W center line of the NE1/4SW1/4 of sec. 22.</p> <p>Across cultivated field, along S. side of irrigation ditch.</p>
10.058	The NE-SW 1/64 sec. cor. of sec. 22.
12.60	Leave cultivated field, thence through shadescale.
14.10	Irrigation ditch, drain SSW.
20.112	<p>The C-N-SW 1/64 sec. cor. of sec. 22.</p> <hr/> <p>From the C-W-SW 1/64 sec. cor. of sec. 22.</p> <p>N. 0°24'10" W., on the N-S center line of the NW1/4SW1/4 of sec. 22.</p> <p>Along Vista Drive, asphalt surfaced, 35 lks. wide.</p>
10.006	<p>Point for the NW-SW 1/64 sec. cor. of sec. 22, at intersection with the E-W center line of the NW1/4SW1/4.</p> <p>Set a magnetized nail flush with the surface of road.</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 81°29' E., 52.1 lks. dist., with brass cap mkd. RM NW-SW 1/64 S22 34.4 FT TO COR 2009 and an arrow pointing to the cor.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 47°36' E., 70.9 lks.</p>

FURTHER SUBDIVISION OF SECTION 22,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>dist., with brass cap mkd. RM NW-SW 1/64 S22 46.8 FT TO COR 2009 and an arrow pointing to the cor.</p> <p>Point falls in the asphalt surface of Vista Drive, 35 lks. wide, bears N. and S.</p>
18.50	Guard rail along west side of Vista Drive, bears NW. and S., thence across cultivated land.
19.34	Concrete lined irrigation ditch, 20 lks. wide, 5 ft. deep, drains S. 15° W.
20.017	<p>The C-W-W 1/64 sec. cor. of sec. 22, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, bent and below the surface of the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 13 N., R. 28 E., executed under Group No. 635. Accepted base of aluminum post as the best available evidence of the position of the 1986 corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>W-W 1/64</p> <p>C ——— C</p> <p>S22</p> <p>2010</p> </div> <p>Bury aluminum post alongside the stainless steel post.</p> <hr/> <p>From the C-N-SW 1/64 sec. cor. of sec. 22.</p> <p>N. 89°56'40" W., on the E-W center line of the NW1/4SW1/4 of sec. 22.</p> <p>Across level land, covered with shadscale, cheat and bunchgrass.</p>
0.30	Irrigation ditch, drains SE.
3.90	Irrigation ditch, drains NE.
4.60	Cor. of barbed wire fences, extending W. and parallel with irrigation ditch.
9.80	E. edge of asphalt surface, W. Loop road, 50 lks. wide, bears N. and S.
10.060	The NW-SW 1/64 sec. cor. of sec. 22.
10.70	<p>Concrete lined irrigation ditch, 20 lks. wide, 4 ft. deep, drains SE.</p> <p>Thence along N. side of concrete lined irrigation ditch, drains W., and cultivated field to the N.</p>

FURTHER SUBDIVISION OF SECTION 22,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.116	The N-S 1/64 sec. cor. of secs. 21 and 22.
	From the C-W 1/16 sec. cor. of sec. 22.
	N. 0°00'10" E., on the N-S center line of the NW1/4 of sec. 22.
	Across nearly level, land covered with shadescale, cheat and bunch grass and along W. side of fence, bears N. and S.
10.014	Point for the C-S-NW 1/64 sec. cor. of sec. 22.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	S22 C-S-NW 1/64
	2009
	From this point, the cor. of fences, extending N., E., S. and W., bears N. 69° E., 0.13 chs. dist.
10.06	Fence, bears E. and W.
20.028	Point for the NW 1/16 sec. cor. of sec. 22, at intersection with the E-W center line of the NW1/4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	NW 1/16 S22
	2009
22.10	From this point, a bend in concrete lined irrigation ditch, 20 lks. wide, 4 ft. deep, bears N. and drains SW., bears W., 0.25 chs. dist.
	Thence along level farmland, along E. side of concrete lined irrigation ditch.
30.038	Point for the C-N-NW 1/64 sec. cor. of sec. 22.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.
	S22 C-N-NW 1/64
	2009
40.048	The W 1/16 sec. cor. of secs. 15 and 22.

FURTHER SUBDIVISION OF SECTION 22,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the C-N 1/16 sec. cor. of sec. 22.</p> <p>N. 89°56'10" W., on the E-W center line of the NW1/4 of sec. 22.</p> <p>Across level farmland.</p>
10.034	<p>Point for the C-E-NW 1/64 sec. cor. of sec. 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S22 C-E-NW 1/64 2009</p>
20.068	The NW 1/16 sec. cor. of sec. 22.
30.104	<p>Point for the C-W-NW 1/64 sec. cor. of sec. 22.</p> <p>POINT NOT MONUMENTED</p>
40.140	The N 1/16 sec. cor. of secs. 21 and 22.
<hr/>	
	<p>From the C-E-NW 1/64 sec. cor. of sec. 22.</p> <p>N. 0°05'20" W., on the N-S center line of the NE1/4NW1/4 of sec. 22.</p> <p>Across level farmland.</p>
10.007	<p>Point for the NE-NW 1/64 sec. cor. of sec. 22, at intersection with the E-W center line of the NE1/4NW1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S22 NE-NW 1/64 2009</p>
	<p>Point falls in irrigation ditch, bears E-W.</p> <p>Thence through shadescale, cheat and bunch grass.</p>
20.018	The E-W 1/64 sec. cor. of secs. 15 and 22.
<hr/>	
	<p>From the C-N-N 1/64 sec. cor. of sec. 22.</p> <p>N. 89°54'50" W., on the E-W center line of the NE1/4NW1/4 sec. 22.</p> <p>Across level land, on N. side of cultivated field.</p>

FURTHER SUBDIVISION OF SECTION 22,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
10.017	The NE-NW 1/16 sec. cor. of sec. 22.
20.034	The C-N-NW 1/64 sec. cor. of sec. 22.
	<hr/> <p>From the C-E-W 1/64 sec. cor. of sec. 22.</p> <p>N. 0°04'50" W., on the N-S center line of the SE1/4NW1/4 of sec. 22.</p> <p>Across level land, along W. side of barbed wire fence and cultivated field.</p>
9.90	Cor. of barbed wire fences, extending N., E., S. and W.
10.009	Point for the SE-NW 1/64 sec. cor. of sec. 22, at intersection with the E-W center line of the SE1/4NW1/4.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S22 SE-NW 1/64 2009</p> <p>Point is located at the cor. of fences, extending N., S., E. and W.</p>
20.028	The C-E-NW 1/64 sec. cor. of sec. 22.
	<hr/> <p>From the C-S-N 1/64 sec. cor. of sec. 22.</p> <p>N. 89°54'20" W., on the E-W center line of the SE1/4NW1/4 of sec. 22.</p> <p>Across cultivated land, along fence.</p>
10.054	The SE-NW 1/64 sec. cor. of sec. 22.
20.103	The C-S-NW 1/64 sec. cor. of sec. 22.
	<hr/> <p>From the C-W-W 1/64 sec. cor. of sec. 22.</p> <p>N. 0°06'50" E., on the N-S center line of the SW1/4NW1/4 of sec. 22.</p> <p>Across level, cultivated land.</p>
0.80	Concrete lined irrigation ditch, 20 lks. wide, drains S. 20° W.
10.006	Point for the SW-NW 1/64 sec. cor. of sec. 22, at intersection with the E-W center line of the SW1/4NW1/4.

FURTHER SUBDIVISION OF SECTION 22,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p>S22 SW-NW 1/64 2009</p>
19.70	Graded dirt road, 15 lks. wide, bears E. and W.
20.013	The point for the C-W-NW 1/64 sec. cor. of sec. 22.
	<hr/> <p>From the C-S-NW 1/64 sec. cor. of sec. 22.</p> <p>N. 89°55'40" W., on the E-W center line of the SW1/4NW1/4 of sec. 22.</p> <p>Across level farm land.</p>
5.20	Vista Drive, asphalt surfaced, 35 lks. wide, bears N. 25° E. and S. 25° W.
6.60	Concrete lined irrigation ditch, 20 lks. wide, 4 ft. deep, drains S. 20° W.
	Thence along dirt road, between cultivated fields.
10.055	The SW-NW 1/64 sec. cor. of sec. 22.
20.108	The S-N 1/64 sec. cor. of secs. 21 and 22.
	<hr/> <p>From the C-N-NW 1/64 sec. cor. of sec. 22.</p> <p>N. 89°55'30" W., on the E-W center line of the NW1/4NW1/4 of sec. 22.</p> <p>Across level land, along barbed wire fence and N. side of cultivated field.</p>
0.35	Concrete lined irrigation ditch, 20 lks. wide, 4 ft. deep, drains S.
7.50	East edge of cultivated field, bears NNE. and E.
	Thence across cultivated field.
20.040	The N-N 1/64 sec. cor. of secs. 21 and 22.
	<hr/> <p>FURTHER SUBDIVISION OF SECTION 26, T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the C-E 1/16 sec. cor. of sec. 26.</p>

FURTHER SUBDIVISION OF SECTION 26,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°10'30" E., on a portion of the N-S center line of the NE1/4 of sec. 26.
	Across level cultivated land.
0.40	Barbed wire fence, bears WNW. and ESE., thence along river bank.
10.113	The C-S-NE 1/64 sec. cor. of sec. 26, identical with the SE. cor. of Indian Allotment No. 493, monumented with an aluminum post, 2 1/2 ins. diam., firmly set 12 ins. below the surface of the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of the N1/2SW1/4NE1/4 of sec. 26, T. 13 N., R. 28 E., executed under Group No. 635.
	From the point for the N 1/16 sec. cor. of secs. 25 and 26.
	N. 89°35'50" W., on the E-W center line of the NE1/4 of sec. 26.
	Across rolling land, covered with shadescale, cheat and bunch grass.
10.004	Point for the C-E-NE 1/64 sec. cor. of sec. 26.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	S26 C-E-NE 1/64 2010
13.80	Dirt road, 15 lks. wide, bears N. and S.
15.30	Power line, bears N. 30° W. and S. 30° E.
19.30	Dirt road, 15 lks. wide, parallels irrigation ditch.
19.70	Concrete lined irrigation ditch, 20 lks. wide, 5 ft. deep, drains S.
20.008	The NE 1/16 sec. cor. of sec. 26, identical with the NE. cor. of Indian Allotment No. 493.
	From the C-E-E 1/64 sec. cor. of sec. 26, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with aluminum cap mkd. as described in the field notes of the subdivision of section 26, T. 13 N., R. 28 E., executed under Group No. 635.
	NORTH, on the N-S center line of the SE1/4NE1/4 of sec. 26.
	Across rolling developed land.
8.40	Barbed wire fence, parallels road.
8.80	Graded dirt road, 15 lks. wide, bears N. 20° W. and S. 20° E.

FURTHER SUBDIVISION OF SECTION 26,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
9.40	Concrete lined irrigation ditch, 20 lks. wide, 5 ft. deep, drains S. 20° E., thence across undeveloped land, through shadescale, cheat and bunch grass.
11.50	Power line, bears N. 30° W. and S. 30° E.
20.059	The C-E-NE 1/64 sec. cor. of sec. 26.
	<hr/> <p>From the C-W-NE 1/64 sec. cor. of sec. 26, on the N. bdy. of Indian Allotment No. 493.</p> <p>N. 0°37'20" W., on the N-S center line of the NW1/4NE1/4 of sec. 26.</p> <p>Across river bottom lands, along E. side of cultivated field.</p>
19.940	The W-E 1/64 sec. cor. of secs. 23 and 26.
	<hr/> <p>From the N-S 1/64 sec. cor. of secs. 25 and 26.</p> <p>N. 89°46'30" W., on the E-W center line of the NE1/4SE1/4 of sec. 26.</p> <p>Across developed land and along fence.</p>
4.50	Left bank of the Walker River, bears NNE. and SW., thence across river, course SW.
5.00	Right bank of the Walker River, bears NNE. and SW., thence across level cultivated land.
19.97	Barbed wire fence, bears S. and N. 0.02 chs. to cor. of barbed wire fences, extending S., E. and W.
20.097	<p>The C-N-SE 1/64 sec. cor. of sec. 26, determined at record bearing and distance from the remaining 1986 reference monument</p> <p>An aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, bears S. 29 1/4° W., 24.0 lks. dist., with aluminum cap mkd. XRM 16 FT 1987 and an arrow pointing to the cor.</p> <p>At the corner point</p> <p>Chisel an X on concrete lined irrigation ditch.</p> <p>from which a new bearing object</p> <p>A stamped X between the letters BO, on the top of operating screw for a floodgate, 2 ft. wide, at E. end of concrete irrigation ditch, bears S. 82°49' E., 42.1 lks. dist.</p> <p>Cor. is located on the top of the N. bank of a concrete lined irrigation ditch, 8 lks. wide, 3 ft. deep, drains E.</p> <hr/> <p>From the S-S 1/64 sec. cor. of secs. 25 and 26.</p>

FURTHER SUBDIVISION OF SECTION 26,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>N. 89°54'30" W., on the E-W center line of the SE1/4SE1/4 of sec. 26.</p> <p>Across river bottom lands, covered with scattered cottonwood trees, willows, shadecale, cheat and bunch grass.</p>
1.90	Left bank of the Walker River, bears NE. and SW., thence across river, course SW.
2.70	Right bank of the Walker River, bears NE. and SW., thence along S. side of barbed wire fence.
20.105	<p>The C-S-SE 1/64 sec. cor. of sec. 26, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with aluminum cap mkd. as described in the field notes of the subdivision of the southeast 1/4 of section 26, T. 13 N., R. 28 E., executed under Group No. 635.</p> <p>From this cor., the cor. of barbed wire fences, extending N. and E., bears N. 78° E., 0.09 chs. dist.</p> <hr/> <p>From the C-N-SE 1/64 sec. cor. of sec. 26.</p> <p>N. 89°50'20" W., on the E-W center line of the NW1/4SE1/4 of sec. 26.</p> <p>Across level cultivated land, along concrete lined irrigation ditch and barbed wire fence.</p>
20.085	<p>The C-N-S 1/64 sec. cor. of sec. 26, monumented with a railroad spike, set flush with the asphalt surface, from which the remaining 1986 reference monument</p> <p style="padding-left: 40px;">An aluminum post, 2 1/2 ins. diam., firmly set, bears N. 73 1/2° W., 30.6 lks. dist., with aluminum cap mkd. XRM 1986. Add the mks. 20.2 FT 2010 and an arrow pointing to the corner on aluminum cap. (Record, 30.3 lks.)</p> <p>and a new bearing object</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 25°22' W., 72.4 lks. dist., with brass cap mkd. RM C-N-S 1/64 S26 47.8 FT TO COR 2010 and an arrow pointing to the cor.</p> <p>Cor. is located in the asphalt surface of Mesquite Road, 35 lks. wide, bears N. and S.</p> <hr/> <p>From the C-W 1/16 sec. cor. of sec. 26, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. as described in the field notes of the subdivision of sec. 26, T. 13 N., R. 28 E., executed under Group No. 635.</p> <p>Cor. is located at the cor. of fences, extending N., S. and W., and in power line, bears E. and W.</p> <p>N. 0°03'00" W., on the N-S center line of the NW1/4 of sec. 26.</p>

FURTHER SUBDIVISION OF SECTION 26,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Across level farmland.
0.50	Intersect curve in irrigation ditch, 20 lks. wide, 5 ft. deep, curves from the N., drains E., thence along E. side of irrigation ditch and W. side of Red Earth Way, a graded dirt road, 15 lks. wide, bears N.
10.032	Point for the C-S-NW 1/64 sec. cor. of sec. 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. S26 C-S-NW 1/64 2010 from which A chiseled X followed by the letters BO, bears S. 54°35' W., 31.8 lks. dist., on W. embankment of a concrete lined irrigation ditch, 1 ft. below top. A chiseled X followed by the letters BO, bears N. 42°33' W., 39.2 lks. dist., on W. embankment of a concrete lined irrigation ditch, 1 ft. below top.
20.064	Point for the NW 1/16 sec. cor. of sec. 26, at intersection with the E-W center line of the NW1/4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. NW 1/16 S26 2010 from which A chiseled X followed by the letters BO, bears S. 48°51' W., 35.3 lks. dist., on W. embankment of a concrete lined irrigation ditch, 1 ft. below top. A chiseled X followed by the letters BO, bears N. 58°11' W., 30.2 lks. dist., on W. embankment of a concrete lined irrigation ditch, 1 ft. below top.
30.056	Point for the C-N-NW 1/64 sec. cor. of sec. 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. S26 C-N-NW 1/64 2010

FURTHER SUBDIVISION OF SECTION 26,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	from which
	<p>A chiseled X followed by the letters BO, bears S. 74°21' W., 27.5 lks. dist., on W. embankment of a concrete lined irrigation ditch, 1 ft. below top.</p> <p>A stamped X between the letters BO, bears N. 29°55' W., 26.6 lks. dist., on top of operating screw for floodgate.</p>
40.048	The W 1/16 sec. cor. of secs. 23 and 26.
	<p>From the C-N 1/16 sec. cor. of sec. 26, identical with the NW cor. of Indian Allotment No. 493.</p> <p>N. 89°53'40" W., on the E-W center line of the NW1/4 of sec. 26.</p> <p>Across river bottom lands, covered with scattered cottonwood trees, shadescale, cheat and bunchgrass.</p>
6.40	Left bank of the Walker River, bears NW. and SE., thence across river, course SE.
8.50	Right bank of the Walker River, bears NW. and SE.
10.13	Cor. of barbed wire fences, extending N. and W., thence along fence.
10.180	Point for the C-E-NW 1/64 sec. cor. of sec. 26.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S26 C-E-NW 1/64 2010</p>
20.05	Barbed wire fence, bears N. and S. for 0.13 chs., to cor. of barbed wire fences, extending E. and S.
20.360	The NW 1/16 sec. cor. of sec. 26.
20.55	Concrete lined irrigation ditch, 20 lks. wide, 5 ft. deep, drains S.
20.80	Barbed wire fence, bears N. and S.
40.00	Barbed wire fence, bears N. and S.
40.432	<p>The N 1/16 sec. cor. of secs. 26 and 27, monumented with a railroad spike set flush with the asphalt surface, the 1986 reference monuments were found disturbed and damaged, were removed and destroyed.</p> <p>from which new bearing objects</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet,</p>

FURTHER SUBDIVISION OF SECTION 26,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>for a reference monument, bears N. 46°40' E., 61.7 lks. dist., with brass cap mkd. RM N 1/16 S26 40.7 FT TO COR 2010 and an arrow pointing to the cor., located in a barbed wire fence, bears N. and S.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 48°00' W., 60.0 lks. dist., with brass cap mkd. RM N 1/16 S27 39.6 FT TO COR 2010 and an arrow pointing to the cor., located in a barbed wire fence, bears N. and S.</p> <p>Cor. is located in the asphalt surface of Farm Road, 35 lks. wide, bears N. and S.</p>
<p>13.70</p> <p>15.10</p> <p>19.75</p> <p>19.90</p> <p>20.065</p>	<p>From the C-N-N 1/64 sec. cor. of sec. 26, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with aluminum cap mkd. as described in the field notes of the subdivision of section 26, T. 13 N., R. 28 E., executed under Group No. 635.</p> <p>N. 89°41'40" W., on the E-W center line of the NE1/4NW1/4 of sec. 26.</p> <p>Across river bottom lands, covered with scattered cotton wood trees, shadescall, cheat and bunch grass.</p> <p>Left bank of the Walker River, bears N. and S., thence across river, course S.</p> <p>Right bank of the Walker River, bears N. and S.</p> <p>Barbed wire fence, bears N. and S.</p> <p>Red Earth Way, a graded dirt road, 15 lks. wide, bears N. and S.</p> <p>The C-N-NW 1/64 sec. cor. of sec. 26.</p>
<p>0.25</p> <p>0.40</p> <p>5.80</p>	<p>From the C-E-W 1/64 sec. cor. of sec. 26, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. as described in the field notes of the subdivision of section 26, T. 13 N., R. 28 E., executed under Group No. 635, with a mound of stone, 2 ft. base, 6 ins. high, N. of cor.</p> <p>N. 0°18'40" E., on the N-S center line of the SE1/4NW1/4 of sec. 26.</p> <p>Across river bottom land, covered with cottonwood trees, shadescall and rabbit brush.</p> <p>Concrete lined irrigation ditch, 10 lks. wide, 3 ft. deep, drains E.</p> <p>Cor. of barbed wire fences, extending N. and ESE., thence along barbed wire fence.</p> <p>Cor. of barbed wire fences, extending N., N. 75° E. and S. 75° W., thence along fallen fence line.</p>

FURTHER SUBDIVISION OF SECTION 26,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.085	The C-E-NW 1/64 sec. cor. of sec. 26.
	From the C-S-NW 1/64 sec. cor. of sec. 26.
	N. 89°52'30" W., on the E-W center line of the SW1/4NW1/4 of sec. 26.
	Across level cultivated land.
0.20	Concrete lined irrigation ditch, 20 lks. wide, 5 ft. deep, drains S.
0.45	Barbed wire fence, bears N. and S.
	Thence across level cultivated field.
19.65	Barbed wire fence, bears N. and S.
20.081	The S-N 1/64 sec. cor. of secs. 26 and 27, monumented with a railroad spike, set flush with the asphalt surface, the 1986 reference monuments were found disturbed and damaged, were removed and destroyed.
	from which new bearing objects
	A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 60°35' E., 50.0 lks. dist., with brass cap mkd. RM S-N 1/64 S26 33.0 FT TO COR 2010 and an arrow pointing to the cor., located in a barbed wire fence, bears N. and S.
	A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 59°33' W., 51.8 lks. dist., with brass cap mkd. RM S-N 1/64 S27 34.2 FT TO COR 2010 and an arrow pointing to the cor., located in a barbed wire fence, bears N. and S.
	Cor. is located in the asphalt surface of Farm Road, 35 lks. wide, bears N. and S.
	From the C-N-NW 1/64 sec. cor. of sec. 26.
	N. 89°50'00" W., on the E-W center line of the NW1/4NW1/4 of sec. 26.
	Across level cultivated land.
0.20	Concrete lined irrigation ditch, 20 lks. wide, 5 ft. deep, drains S.
	Thence across level cultivated field.
0.45	Barbed wire fence, bears N. and S.
19.65	Barbed wire fence, bears N. and S.

FURTHER SUBDIVISION OF SECTION 26,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 20.064</p>	<p>The N-N 1/64 sec. cor. of secs. 26 and 27, monumented with a railroad spike, set flush with the asphalt surface, from which the 1986 reference monuments</p> <p>An aluminum post, 2 1/2 ins. diam., firmly set in a collar of stone, bears N. 54 1/2° E., 48.5 lks. dist., with aluminum cap mkd. RM N-N 1/64 S26 32 FT TO COR 1986 and an arrow pointing to the cor.</p> <p>An aluminum post, 2 1/2 ins. diam., firmly set in a collar of stone, bears N. 54° W., 50.0 lks. dist., with aluminum cap mkd. mkd. RM N-N 1/64 S27 33 FT TO COR 1986 and an arrow pointing to the cor.</p> <p>Cor. is located in the asphalt surface of Farm Road, 35 lks. wide, bears N. and S.</p> <hr/> <p>FURTHER SUBDIVISION OF SECTION 27, T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the C-E-NE 1/64 sec. cor. of sec. 27, determined at the intersection of record distances from the 1986 reference monuments</p> <p>An aluminum post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, bears S. 15°52' W., 9.1 lks. dist., with aluminum cap mkd. RM C-E-NE 1/64 S27 6 FT and an arrow pointing to the cor. (Record, S. 14 1/2° W.)</p> <p>An aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, bears N. 52°05' W., 19.7 lks. dist., with aluminum cap mkd. XRM. (Record, N. 52 1/4° W.) Add the mks. 13 FT 2010 and an arrow pointing to the corner.</p> <p>At the corner point</p> <p>Set a railroad spike, 1 in. square, 3 ins. below the surface of driveway.</p> <p>Cor. is located in a graded dirt driveway, 20 lks. wide, bears ENE. and WSW.</p> <p>N. 0°01'10" W., on the N-S center line of the NE1/4NE1/4 sec. 27.</p> <p>Across dirt driveway.</p> <p>0.25 Floodgate, draining a concrete lined irrigation ditch, 12 lks. wide, 3 ft. deep, leave driveway and along irrigation ditch, bears N.</p> <p>19.60 Bend of concrete lined irrigation ditch, extending E. and drains S.</p> <p>19.80 Barbed wire fence, bears E. and W.</p>
--------------------------	--

FURTHER SUBDIVISION OF SECTION 27,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
19.85	Power line, bears E. and W.
20.041	The E-E 1/64 sec. cor. of secs. 22 and 27.
	<hr/> <p>From the C-N-SE 1/64 sec. cor. of sec. 27, monumented with an aluminum post, 2 1/2 ins. diam., loosely set, projecting 12 ins. above the ground, with aluminum cap mkd. as described in the field notes of the subdivision of the southeast 1/4 of section 27, T. 13 N., R. 28 E., executed under Group No. 635.</p> <p>Straighten and repack the aluminum post.</p> <p>Cor. is located S. 55° E., 4.5 lks. dist., from power pole No. 39145 J46427, from which power lines extend N., S. and W., and S. 20° E., 7.0 lks. dist. from the cor. of barbed wire fences, extending N., S. and W.</p> <p>S. 89°57'30" W., on the E-W center line of the NW1/4SE1/4 of sec. 27.</p> <p>Across level land, along S. side of fence and power line.</p>
20.027	<p>The C-N-S 1/64 sec. cor. of sec. 27, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with aluminum cap mkd. as described in the field notes of the subdivision of sec. 27, T. 13 N., R. 28 E., executed under Group No. 635.</p> <p>Cor. is located on the SW. side of the cor. of barbed wire fences, extending N. and E.</p> <hr/> <p>From the W 1/16 sec. cor. of sec. 27 and 34, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 13 N., R. 28 E., executed under Group No. 635, with a mound of stone, 2 ft. base, 1/2 ft. high, N. of cor.</p> <p>N. 0°07'50" W., on the N-S center line of the SW1/4 of sec. 27.</p> <p>Across nearly level land, covered with shadscale, cheat and bunch grass.</p>
20.033	<p>The SW 1/16 sec. cor. of sec. 27, monumented with an unrecorded rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 2 ins. above ground, with plastic cap mkd. TRI-STATE RLS 6306, and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

FURTHER SUBDIVISION OF SECTION 27,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	SW 1/16 S27
	2009
	Deposit rebar inside stainless steel post.
	Cor. is located at the SE. end of graded dirt road, bears N.

	N. 0°07'50" W., beginning new measurement.
	Along the E. edge of a graded dirt road.
10.018	The C-N-SW 1/64 sec. cor. of sec. 27, monumented with an unrecorded rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 2 ins. above ground, with plastic cap mkd. PLS 11178, and is accepted as a careful and faithful determination of the position of the corner.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	S27
	C-N-SW
	1/64
	2009
	Deposit rebar inside stainless steel post.

	N. 0°07'50" W., beginning new measurement.
5.009	The C-N-N-SW 1/256 sec. cor. of sec. 27, monumented with an unrecorded rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 2 ins. above ground, with plastic cap mkd. PLS 11178, and is accepted as a careful and faithful determination of the position of the corner.

	N. 0°07'50" W., beginning new measurement.
5.009	The C-W 1/16 sec. cor. of sec. 27.

	From the C-S 1/16 sec. cor. of sec. 27, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. as described in the field notes of the subdivision of section 27, T. 13 N., R. 28 E., executed under Group No. 635.
	S. 89°57'10" W., on the E-W center line of the SW1/4 of sec. 27.
	Across nearly level land, covered with shadecale, cheat and bunch grass.
0.30	Irrigation ditch, 15 lks. wide, 4 ft deep, drains SE.

FURTHER SUBDIVISION OF SECTION 27,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
2.80	Power line, bears N. 27° W. and E.
16.20	Cor. of barbed wire fences, extending N. and S. 80° E.
20.163	The SW 1/16 sec. cor. of sec. 27.
	<hr/>
	S. 89°57'10" W., beginning new measurement.
0.15	S. end of graded dirt road, 25 lks. wide, bears N.
3.30	Power line, bears N. 35° W. and S. 35° E.
20.168	The S 1/16 sec. cor. of secs. 27 and 28, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 13 N., R. 28 E., executed under Group No. 635, with a mound of stone, 2 1/2 ft. base, 1 ft. high, W. of cor.
	<hr/>
	From the C-N-S 1/64 sec. cor. of sec. 27.
	S. 89°57'40" W., on the E-W center line of the NE1/4SW1/4 of sec. 27.
	Across level land, covered with shadescale, cheat and bunch grass.
1.98	U.S. Highway No. 95 Alternate, asphalt surfaced, 50 lks. wide, bears N. 42° W. and S. 42° E.
2.80	Barbed wire fence, bears SE. parallel with the highway and W.
20.173	The C-N-SW 1/64 sec. cor. of sec. 27.
	<hr/>
	From the C-E-W 1/64 sec. cor. of sec. 27.
	N. 0°01'50" E., on the N-S center line of the SE1/4NW1/4 of sec. 27.
	Across level land, along W. side of cultivated field.
20.045	The true point for the C-E-NW 1/64 sec. cor. of sec. 27.
	<hr/>
	FURTHER SUBDIVISION OF SECTION 35, T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA
	<hr/>
	From the C-E-E 1/64 sec. cor. of sec. 35, monumented with a railroad spike, set flush with the asphalt surface, mkd. C S. (Record, unmkd.)
	from which new bearing objects

FURTHER SUBDIVISION OF SECTION 35,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 63°49' E., 40.2 lks. dist., with brass cap mkd. RM C-E-E 1/64 S35 26.5 FT TO COR 2010 and an arrow pointing to the cor.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 46°04' W., 30.1 lks. dist., with brass cap mkd. RM C-E-E 1/64 S35 19.9 FT TO COR 2010 and an arrow pointing to the cor.</p> <p>Cor. is located in the asphalt surface of Piute Estates Parkway, 35 lks. wide, extends E. and curves right to the NW.</p> <p>From this cor., a PK nail set flush with asphalt surface, set by person(s) unknown, bears S. 83°35' W., 0.332 chs. dist.</p> <p>N. 0°02'10" E., on the N-S center line of the SE1/4NE1/4 of sec. 35.</p> <p>Across level land, along W. side of cultivated field and along power line.</p> <p>19.35 Cor. of barbed wire fences, extending E. and S.</p> <p>19.79 N. edge of Wavoka Road, asphalt surfaced, 35 lks. wide, bears E. and W.</p> <p>19.817 The C-E-NE 1/64 sec. cor. of sec. 35, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set flush with surface of the ground, with brass cap mkd. as described in the field notes of the survey of the subdivision of the northeast 1/4 of section 35, T. 13 N., R. 28 E., executed under Group No. 670.</p> <hr/> <p>From the NW-NE 1/64 sec. cor. of sec. 35, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 in. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the S1/2NE1/4NW1/4NE1/4 of section 35, T. 13 N., R. 28 E., executed under Group No. 670.</p> <p>N. 89°45'50" W., on a portion of the E-W center line of the NW1/4NE1/4 of sec. 35.</p> <p>Across level land, covered with cottonwood trees, shadescale, cheat and bunch grass, and along barbed wire fence.</p> <p>0.25 Irrigation ditch, 15 lks. wide, 4 ft. deep, drains S.</p> <p>1.50 Leave cottonwood trees.</p> <p>3.00 Cor. of barbed wire fences, extending N., S. and W., thence along fence.</p>
--------	--

FURTHER SUBDIVISION OF SECTION 35,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
10.059	<p>The C-N-N 1/64 sec. cor. of sec. 35, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 in. above the ground, with brass cap mkd. as described in the field notes of the survey of the subdivision of section 35, T. 13 N., R. 28 E., executed under Group No. 670.</p> <hr/> <p>From the E 1/16 sec. cor. of secs. 2 and 35, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the south boundary, T. 13 N., R. 28 E., executed under Group No. 670.</p> <p>N. 0°11'50" E., on the N-S center line of the SE1/4 of sec. 35.</p> <p>Across rolling land, covered with shadescale, cheat and bunch grass.</p>
13.10	Barbed wire fence, parallels old U.S. Hwy. No. 95 Alternate.
14.55	Remains of asphalt, old U.S. Hwy. No. 95 Alternate, 25 lks. wide, bears N. 35° W. and S. 35° E.
16.65	U.S. Highway No. 95 Alternate, asphalt surfaced, 50 lks. wide, curves right to the NW. and curves left to the SE.
19.946	<p>The SE 1/16 sec. cor. of sec. 35, monumented with an unrecorded rebar, 5/8 in. diam., 18 ins. long, firmly set flush with the surface of the ground, with plastic cap mkd. TRI-STATE RLS 6306, and is accepted as a careful and faithful determination of position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S35</p> <p style="text-align: center;">2009</p> <p>Deposit rebar inside stainless steel post.</p> <hr/> <p>N. 0°11'50" E., beginning new measurement.</p>
3.50	Dirt road, 15 lks. wide, bears E. and W.
8.00	Dirt road, 15 lks. wide, bears ENE. and WSW.
14.964	<p>The C-N-N-SE 1/256 sec. cor. of sec. 35, monumented with an unrecorded rebar, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with plastic cap mkd. TRI-STATE RLS 6306, and is accepted as a careful and faithful determination of the position of the corner.</p> <hr/> <p>N. 0°11'50" E., beginning new measurement.</p>

FURTHER SUBDIVISION OF SECTION 35,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
4.988	<p>The C-E 1/16 sec. cor. of sec. 35, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of the subdivision of section 35, T. 13 N., R. 28 E., executed under Group No. 670, with a steel fence post set alongside.</p> <hr/> <p>From the S 1/16 sec. cor. of secs. 35 and 36.</p> <p>N. 89°52'20" W., on the E-W center line of the SE1/4 of sec. 35.</p> <p>Across rolling land, covered with shadescale, cheat and bunch grass.</p>
20.160	<p>The SE 1/16 sec. cor. of sec. 35.</p> <hr/> <p>N. 89°52'30" W., beginning new measurement.</p>
3.40	<p>U.S. Highway No. 95 Alternate, asphalt surfaced, 50 lks. wide, curves SE. and NW.</p>
20.161	<p>The C-S 1/16 sec. cor. of sec. 35, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of the subdivision of section 35, T. 13 N., R. 28 E., executed under Group No. 670.</p> <hr/> <p style="text-align: center;">FURTHER SUBDIVISION OF SECTION 36, T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the C-E 1/16 sec. cor. of sec. 36, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. as described in the field notes of the subdivision of section 36, executed under Group No. 635.</p> <p>From this cor., the cor. of barbed wire fences, extending S. and W., bears N. 5° W., 23 lks. dist.</p> <p>N. 0°04'30" E., on the N-S center line of the NE1/4 of sec. 36.</p> <p>Across river bottom land, covered with shadescale, cheat and bunch grass.</p>
1.70	<p>Power line, bears N. 83° E. and S. 83° W.</p>
19.966	<p>Point for the NE 1/16 sec. cor. of sec. 36, at the intersection with the E-W center line of the NE1/4.</p> <p>Set a PK nail flush with asphalt surface.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet,</p>

FURTHER SUBDIVISION OF SECTION 36,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>for a reference monument, bears N. 18°03' E., 50.9 lks. dist., with brass cap mkd. RM NE 1/16 S36 33.6 FT TO COR 2009 and an arrow pointing to the cor.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 25°55' E., 41.5 lks. dist., with brass cap mkd. RM NE 1/16 S36 27.4 FT TO COR 2009 and an arrow pointing to the cor.</p> <p>Cor. falls on asphalt surface of Double Spring Road, 35 lks. wide, bears E. and W., 6 lks. from S. edge.</p>
38.10	Concrete lined irrigation ditch, 20 lks. wide, 5 ft. deep, drains SE.
39.909	The E 1/16 sec. cor. of secs. 25 and 36.
	<hr/> <p>From the N 1/16 sec. cor. of secs. 31 and 36, on the E. bdy. of the Tp.</p> <p>S. 89°58'30" W., on the E-W center line of the NE 1/4 of sec. 36.</p> <p>Across rolling land, covered with shadescale, cheat and bunch grass.</p>
5.80	Power line, bears N. and S.
5.90	Heart Falls Lane, asphalt surfaced, 35 lks. wide, bears SE. from intersection with Double Spring Road.
7.30	Concrete lined irrigation ditch, 20 lks. wide, 5 ft. deep, drains S. 30° E., thence across river bottom lands.
9.989	<p>Point for the C-E-NE 1/64 sec. cor. of sec. 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S36 C-E-NE 1/64 2009</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 53°25' E., 46.8 lks. dist., with brass cap mkd. RM C-E-NE 1/64 S36 30.9 FT TO COR 2009 and an arrow pointing to the cor.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 29°15' W., 88.6 lks. dist., with brass cap mkd. RM C-E-NE 1/64 S36 58.5 FT TO COR 2009 and an arrow pointing to the cor.</p>

FURTHER SUBDIVISION OF SECTION 36,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Point falls at S. edge of asphalt, Double Spring Road, 35 lks. wide, bears N. 85° E. and W.</p>
	<p>Thence along Double Spring Road.</p>
19.978	<p>The NE 1/16 sec. cor. of sec. 36.</p>
29.989	<p>Point for the C-W-NE 1/64 sec. cor. of sec. 36.</p>
	<p>Set a PK nail flush with asphalt surface.</p>
	<p>from which</p>
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 6°38' E., 37.1 lks. dist., with brass cap mkd. RM NE 1/16 S36 24.5 FT TO COR 2009 and an arrow pointing to the cor.</p>
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 62°54' E., 71.5 lks. dist., with brass cap mkd. RM NE 1/16 S36 47.2 FT TO COR 2009 and an arrow pointing to the cor.</p>
	<p>Point falls on the asphalt surface of Double Spring Road, 35 lks. wide, bears E. and W., 15 lks. from S. edge.</p>
	<p>From this point, an unrecorded nail, set flush with asphalt surface, with brass washer mkd. RLS 3806, bears S. 28°23' W., 0.081 chs. dist., cannot be reconciled with proper procedures, is not harmoniously related to surrounding corners and is not utilized in the course of this survey.</p>
40.000	<p>The C-N 1/16 sec. cor. of sec. 36, monumented with a railroad spike, set flush with the asphalt surface, from which the 1986 reference monuments</p>
	<p>An aluminum post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, in a collar of stone, bears N. 38° E., 34.9 lks. dist., with aluminum cap mkd. RM C-N 1/16 S36 23 FT 1986 and an arrow pointing to the cor.</p>
	<p>An aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, in a collar of stone, bears S. 37 1/2° W., 36.4 lks. dist., with aluminum cap mkd. XRM 1986. Add the mks. 24.0 FT 2010 and an arrow pointing to the cor. to the aluminum cap.</p>
	<p>Cor. is located in the asphalt surface of Double Spring Road, 35 lks. wide, bears E. and W.</p>
	<p>From the C-E-NE 1/64 sec. cor. of sec. 36.</p>
	<p>N. 0°02'00" W., on the N-S center line of the NE1/4NE1/4 of sec. 36.</p>
	<p>Across rolling land, covered with shadescale, cheat and bunch grass.</p>

FURTHER SUBDIVISION OF SECTION 36,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
0.20	Double Springs Road, asphalt surfaced, 40 lks. wide, bears ENE. and W.
4.30	Concrete lined irrigation ditch, 20 lks. wide, 5 ft. deep, drains S. 35° E.
5.60	S. end of barbed wire fence, bears N., thence along fence.
7.80	Cor. of barbed wire fences, extending E. and S.
9.96	Wood post, 5 ins. diam., projecting 6 ft. above ground.
19.956	The E-E 1/16 sec. cor. of secs. 25 and 36.
	<p>From the C-E-E 1/64 sec. cor. of sec. 36, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. as described in the field notes of the subdivision of section 36, T. 13 N., R. 28 E., executed under Group No. 635.</p> <p>N. 0°00'30" E., on the N-S center line of the SE1/4NE1/4 of sec. 36.</p> <p>Across river bottom land, covered with shadescale, cheat and bunch grass, along E. side of graded dirt road, and along W. side of cultivated field.</p>
0.09	Barbed wire fence, bears E. and W., for 0.03 chs. dist. to cor. of fences extending N. and E., thence along barbed wire fence.
18.10	Cor. of barbed wire fences, extending S. and E.
19.957	The C-E-NE 1/64 sec. cor. of sec. 36.
	<p>From the C-W-E 1/64 sec. cor. of sec. 36, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the subdivision of section 36, T. 13 N., R. 28 E., executed under Group No. 635.</p> <p>From this cor., the cor. of barbed wire fences, extending S. and E., bears N. 50° W., 0.40 chs. dist.</p> <p>N. 0°05'00" E., on the N-S center line of the SW1/4NE1/4 of sec. 36.</p> <p>Across river bottom lands, covered with shadescale, cheat and bunch grass, and along W. side of dirt road.</p>
0.25	Barbed wire fence, bears E. and W.
0.50	Power line, bears N. 83° E. and S. 83° W.
19.977	The C-W-NE 1/64 sec. cor. of sec. 36.
	<p>N. 0°14'40" E., on the N-S center line of the NW1/4NE1/4 of sec. 36.</p>

FURTHER SUBDIVISION OF SECTION 36,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Across river bottom lands, covered with shadescale, cheat and bunch grass, and along E. side of cultivated field.
0.50	Cor. of barbed wire fences, extending N. and W., thence along fence.
19.43	Cor. of barbed wire fences, extending N. 76° W. and S.
19.930	The W-E 1/64 sec. cor. of secs. 25 and 36.
	From the 1/4096 sec. cor. of secs. 1 and 36, on the S. bdy. of the Tp.
	N. 0°06'40" E., on the computed N-S center line of the SE1/4SW1/4SW1/4SE1/4SE1/4 of sec. 36.
2.503	Point for the 1/4096 sec. cor. of sec. 36, on the E-W center line of the SW1/4SW1/4SE1/4SE1/4, at its computed position.
	POINT NOT MONUMENTED
	N. 0°06'40" E., on the computed N-S center line of the NE1/4SW1/4SW1/4SE1/4SE1/4 of sec. 36.
2.503	Point for the 1/4096 sec. cor. of sec. 36, on the E-W center line of the SW1/4SE1/4SE1/4, at its computed position.
	POINT NOT MONUMENTED
	N. 0°06'40" E., on the computed N-S center line of the SE1/4NW1/4SW1/4SE1/4SE1/4 of sec. 36.
2.503	Point for the 1/4096 sec. cor. of sec. 36, on the E-W center line of the NW1/4SW1/4SE1/4SE1/4, at its computed position.
	POINT NOT MONUMENTED
	N. 0°06'40" E., on the computed N-S center line of the NE1/4NW1/4SW1/4SE1/4SE1/4 of sec. 36.
2.503	Point for the 1/4096 sec. cor. of sec. 36, on the E-W center line of the SE1/4SE1/4, at its computed position.
	POINT NOT MONUMENTED
	N. 0°06'40" E., on the computed N-S center line of the SE1/4SW1/4NW1/4SE1/4SE1/4 of sec. 36.
2.503	Point for the 1/4096 sec. cor. of sec. 36, on the E-W center line of the SW1/4NW1/4SE1/4SE1/4, at its computed position.
	POINT NOT MONUMENTED

FURTHER SUBDIVISION OF SECTION 36,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°06'40" E., on the computed N-S center line of the NE1/4SW1/4NW1/4SE1/4SE1/4 of sec. 36.
2.503	Point for the 1/4096 sec. cor. of sec. 36, on the E-W center line of the NW1/4SE1/4SE1/4, at its computed position. POINT NOT MONUMENTED
	N. 0°06'40" E., on the computed N-S center line of the NE1/4NW1/4NW1/4SE1/4SE1/4 of sec. 36.
1.773	Intersect the southerly Southern Pacific Railroad right of way line, bears N. 54°40.6' W. and S. 54°40.6' E.
2.15	Barbed wire fence, bears N. 55° W. and S. 55° E.
2.503	Point for the 1/4096 sec. cor. of sec. 36, on the E-W center line of the NW1/4NW1/4SE1/4SE1/4, at its computed position. POINT NOT MONUMENTED
	N. 0°06'40" E., on the computed N-S center line of the NE1/4NW1/4NW1/4SE1/4SE1/4 of sec. 36.
0.20	Lake Pasture Road, asphalt surfaced, 35 lks. wide, parallels railroad track.
1.128	Center line, Southern Pacific Railroad track, parallels right-of-way line.
2.503	The 1/4096 sec. cor. of sec. 36, on the E-W center of the SE1/4. From the E-W 1/64 sec. cor. of secs. 1 and 36, on the S. bdy. of the Tp., monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, in a collar of stone, with aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of the south boundary, T. 13 N., R. 28 E., executed under Group No. 635. N. 0°08'10" E., on the N-S center line of the SE1/4SW1/4 of sec. 36. Across level cultivated land.
0.40	Barbed wire fence, bears E., and W. for 0.09 chs. dist., thence NW.
7.00	Right bank of the Walker River, bears NW. and SE., thence across river, course SE.
9.00	Flume bears NE. and SW., and left bank of the Walker River, bears NW. and SE., thence through cottonwood trees and grass.
10.90	Cor. of barbed wire fences, extending N. and SW., thence along fence.
19.980	The C-E-SW 1/64 sec. cor. of sec. 36, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 1 in.

FURTHER SUBDIVISION OF SECTION 36,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>above the ground, with aluminum cap mkd. as described in the field notes of the subdivision of the southwest 1/4 of section 36, T. 13 N., R. 28 E., executed under Group No. 635.</p> <p>From this cor., the cor. of barbed wire fences, extending E., S. and W., bears NW., 0.03 chs. dist.</p> <hr/> <p>From the C-W-SW 1/64 sec. cor. of sec. 36.</p> <p>N. 0°17'10" W., on the N-S center line of the NW1/4SW1/4 of sec. 36.</p>
6.00	Descend into river bottom lands, through scattered cottonwoods, and along E. side of barbed wire fence.
19.981	<p>The C-W-W 1/64 sec. cor. of sec. 36, identical with the SE. cor. of Indian Allotment No. 106, also identical with a cor. of the Townsite of Schurz, monumented with an iron post, 2 ins. diam., firmly set 3 ins. below the surface of the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the W1/2SW1/4NW1/4 of section 36, T. 13 N., R. 28 E., executed under Group No. 66.</p> <hr/> <p>From the C-E-NW 1/64 sec. cor. of sec. 36, monumented with a railroad spike, set flush with the asphalt surface, from which the 1986 reference monuments</p> <p>An aluminum post, 2 1/2 ins. diam., firmly set, bears N. 58°18' E., 51.8 lks. dist., with aluminum cap mkd. RM C-E-NW 1/64 S36 34 FT TO COR 1986 and an arrow pointing to the cor. (Record, N. 54 3/4° E., 51.5 lks.)</p> <p>An aluminum post, 2 1/2 ins. diam., firmly set, bears N. 54°10' W., 39.4 lks. dist., with aluminum cap mkd. XRM 1986. Add the mks. 26.0 FT 2010 and an arrow point to the cor. on the aluminum cap. (Record bearing, N. 62 1/2° W.)</p> <p>Cor. is located in Double Spring Road, asphalt surfaced, 35 lks. wide, bears E. and W., 0.06 chs. dist. from the N. edge</p> <p>N. 0°00'30" E., on the N-S center line of the NE1/4NW1/4 of sec. 36.</p> <p>Across level developed land.</p>
4.40	Cor. of barbed wire fences, extending N. and SSW., thence along barbed wire fence.
20.031	The E-W 1/64 sec. cor. of secs. 25 and 36.

TOWNSHIP 13 NORTH, RANGE 28 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	General Description
	<p data-bbox="440 317 1463 478">The area encompassed in this survey is rolling open lands in the northeast portion of the township, mountainous in the southwest portion and developed rural and urban lands in the central portion. The elevation ranges from about 4150 feet to 7400 feet above sea level. Walker River runs through sections 4, 9, 15, 22, 23, 26, 35 and 36.</p> <p data-bbox="440 506 1430 636">Vegetation consists of pinyon pine in the upper elevations, sparse juniper near the summit of Black Mountain, cotton wood trees and willows along the Walker River, with sagebrush in the upper elevations transitioning to shadescale at the lower elevations. Grasses are bunch and cheat grass.</p> <p data-bbox="440 663 1446 793">Evidence of mining activity and abandoned mining claims exist throughout the western most sections. The lands surrounding the Walker River are predominantly agricultural. A canal system, originating at Weber Reservoir, located 1 mile north of the township, delivers water throughout the nearby community.</p> <p data-bbox="440 821 1414 898">The soil consists of loam deposits generated from the Wassuck Range to the west and volcanic hills to the north, with sediments deposited from the Walker River.</p> <p data-bbox="440 926 1446 1087">Access is via U.S. Highway No. 95, on the east side of the township, U.S. Highway No. 95 Alternate, traversing northwest through the center of the township, and by numerous improved roads and trails in the area. The town of Schurz, Nevada is located in the southwest portion of the township, approximately 25 miles east of the town of Yerington, Nevada.</p> <hr data-bbox="440 1115 1446 1119"/>

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Michelle E. Martin	Supervisory Range Technician
Matthew N. Black	Surveying Technician
Michael C. Lambeth	Surveying Technician
Jose A. Serna	Surveying Technician
Michael E. Swope	Surveying Technician
Brandon G. Courtright	Survey Aid
Daniel R. Helmricks	Survey Aid

CERTIFICATE OF SURVEY

We, Lance R. Barney, Cadastral Surveyor, and Mark G. Petrosine, Surveying Technician, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 7th day of July, 2009, we have dependently resurveyed portions of the south, east and north boundaries, a portion of the subdivisional lines, portions of the subdivision-of-section lines of certain sections, Indian Allotment No. 108, a portion of Indian Allotment No. 493, and a portion of Mineral Survey No. 4542, subdivided certain sections, and further subdivided certain sections, Township 13 North, Range 28 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

January 3, 2012

(Date)

January 4, 2012

(Date)

Lance R. Barney
(Cadastral Surveyor)

Mark G. Petrosine
(Surveying Technician)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of the dependent resurvey of portions of the south, east and north boundaries, a portion of the subdivisional lines, portions of the subdivision-of-section lines of certain sections, Indian Allotment No. 108, a portion of Indian Allotment No. 493, and a portion of Mineral Survey No. 4542, the subdivision of certain sections, and the further subdivision of certain sections, Township 13 North, Range 28 East, of the Mount Diablo Meridian, in the State of Nevada, executed by Lance A. Barney, Cadastral Surveyor, and Mark G. Petrosine, Surveying Technician, having been critically examined and found correct, are hereby approved.

January 5, 2012

(Date)

David A. Moran
(Chief Cadastral Surveyor, Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

I CERTIFY that the foregoing transcript of the field notes of the above described surveys in T. 13 N., R. 28 E., Mount Diablo Meridian, Nevada, is a true copy of the original field notes.

~~(Date)~~~~(Chief Cadastral Surveyor, Nevada)~~