UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF THE

SURVEY

OF

THE EAST BOUNDARY,

A PORTION OF THE NORTH BOUNDARY,

AND

A PORTION OF THE SUBDIVISIONAL LINES

TOWNSHIP 13 NORTH, RANGE 55 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATE OF NEVADA

EXECUTED BY

Justin V. Haddon, Cadastral Surveyor

Under Special Instructions dated, July 25, 2017

and approved, July 25, 2017

and Amended Special Instructions dated, October 3, 2019

and approved, October 3, 2019

which provided for the surveys included under Group No. 974,

and Assignment Instructions dated, July 25, 2017.

Survey commenced July 28, 2017
Survey completed October 4, 2019

INDEX DIAGRAM

TOWNSHIP 13 NORTH, RANGE 55 EAST, MOUNT DIABLO MERIDIAN, NEVADA

| | | T | | - | | | | | |
|----|------------|-----------|----------|----|-------------|-----|----|----|---|
| | | | | 6 | į | 6 | | 5 | |
| 6 | 5 | 4 | 22 | 3 | 17 | 2 | 12 | 1 | 4 |
| | • | | | | | | | | |
| | | : | | 22 | - | 17 | | 12 | |
| 7 | 8 | 9 | 27 | 10 | 126 | 1 1 | | 10 | |
| | 8 | 9 | 21 | 10 | 16 | 11 | 11 | 12 | 4 |
| | | | | | ļ | | | | |
| | i | | | 21 | | 16 | | 11 | |
| 18 | 17 | 16 | 20 | 15 | 15 | 14 | 10 | 13 | 3 |
| | | | | | | | | | |
| | | | | 20 | | 15 | | 10 | |
| 19 | 20 | 21 | 19 | 22 | 14 | 23 | 9 | 24 | 3 |
| | | | | | | | | | |
| | | | | 10 | - | 1.4 | - | | |
| · | | | | 19 | | 14 | | 9 | |
| 30 | 29 | 28 | 18 | 27 | 13 | 26 | 8 | 25 | 2 |
| | | | | | | | | | |
| | | | | 18 | | 13 | | 8 | |
| 31 | 3 <i>2</i> | 33 | 17 | 34 | 12 | 35 | 7 | 36 | 1 |
| | | | | | | | | | |
| | | | <u> </u> | | | | | | |

TOWNSHIP 13 NORTH, RANGE 55 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The following field notes are those providing for the survey of the east boundary, a portion of the north boundary, and a portion of the subdivisional lines, Township 13 North, Range 55 East, Mount Diablo Meridian, Nevada.

Nevada Protraction Diagram No. 123, Unit No. 61, for Townships 11, 12, 13 and 13 1/2 North, Ranges 55 and 55 1/2 East was approved February 1, 1963.

The survey of a portion of the north boundary of Township 12 North, Range 55 East, was executed concurrently under this same Group.

In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications set forth in the $\underline{\text{Manual of Surveying Instructions}}$, 2009, and the Special Instructions for Group No. 974, dated July 25, 2017, and the Amended Special Instructions dated October 3, 2019.

Measurements were made with Trimble R10 and R8 Global Positioning System (GPS) receivers using the real-time kinematic method and refer to the true meridian based on geodetic methods. The mean bearings of the lines, and horizontal equivalents of ground distances only are entered into the field notes.

The NAD 1983 (2011) (Epoch:2010.0000) geographic position, of the following corners were determined by GPS static observations processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuous Operating Reference Stations (CORS), DP2878 TONO_TONO BRGN NV1999 CORS ARP, DL6904 NVSV SPRING VALLEY CORS ARP, AI8817 ECHO ECHO_BRGN_NV1999 CORS ARP, and carried forward by RTK observations is as follows:

The corner of Tps. 12 and 13 N., Rs. 55 and 55 1/2 E., is as follows:

Latitude: 38°54'43.818" N. Longitude: 115°44'40.955" W.

The corner of secs. 3, 4, 33 and 34, on the north boundary of the township, is as follows:

Latitude: 38°59'56.858" N. Longitude: 115°48'01.538" W.

SURVEY OF THE EAST BOUNDARY, T. 13 N., R. 55 E., MOUNT DIABLO MERIDIAN, NEVADA

Beginning at the cor. of Tps. 12 and 13 N., Rs. 55 and 55 1/2 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 in. above ground, with brass cap mkd. as described in the field notes of the survey of a portion of the E. bdy. of T. 12 N., R. 55 E., executed concurrently under this same Group.

NORTH, bet. secs. 31 and 36.

SURVEY OF THE EAST BOUNDARY, T. 13 N., R. 55 E., MOUNT DIABLO MERIDIAN, NEVADA

| | T. 13 N., R. 55 E., | MOUNT DIABLO MERIDIAN, NEVADA |
|--------|--|--|
| CHAINS | | |
| 40.000 | Point for the 1/4 sec. cor. | of secs. 31 and 36. |
| | Set a stainless steel post, 25 ins. in the ground, over cap mkd. | 28 ins. long, 2 1/2 ins. diam., a plastic-encased magnet, with brass |
| | | T13N 1/4 |
| | | R55E R55½E S36 S31 |
| | | 2017 |
| 80.000 | Point for the cor. of secs. | 25, 30, 31 and 36. |
| | Set a stainless steel post, 25 ins. in the ground, over cap mkd. | 28 ins. long, 2 1/2 ins. diam., a plastic-encased magnet, with brass |
| | | T13N R55E R55½E S25 S30 |
| | | S36 S31 |
| | | 2017 |
| | NORTH, bet. secs. 25 and 30. | • |
| 40.000 | Point for the 1/4 sec. cor. | of secs. 25 and 30. |
| | Set a stainless steel post, 26 ins. in the ground, over cap mkd. | 28 ins. long, 2 1/2 ins. diam., a plastic-encased magnet, with brass |
| | | T13N |
| | | 1/4 |
| | | R55E R55½E S25 S30 |
| | | 2017 |
| 54.25 | Dirt road, 20 lks. wide, bea | ars S. 80° E. and N. 80° W. |
| 80.000 | Point for the cor. of secs. | 19, 24, 25 and 30. |
| | Set a stainless steel post, 27 ins. in the ground, over cap mkd. | 28 ins. long, 2 1/2 ins. diam., a plastic-encased magnet, with brass |
| | | |
| | | |
| | | |
| | | |
| | | |

SURVEY OF THE EAST BOUNDARY, T. 13 N., R. 55 E., MOUNT DIABLO MERIDIAN, NEVADA

| | | HOURT DIADEO MERIDIAN, NEVADA |
|--------|--|--|
| CHAINS | | |
| | | Tl3N |
| | | R55E R55½E |
| | | S24 S19 |
| | | |
| | | S25 S30 |
| | | 2017 |
| | | |
| | | |
| | NORTH, bet. secs. 19 and 24 | • |
| 40.000 | Point for the 1/4 sec. cor. | of secs. 19 and 24. |
| | Set a stainless steel post, 27 ins. in the ground, over cap mkd. | 28 ins. long, 2 1/2 ins. diam., a plastic-encased magnet, with brass |
| | | T13N |
| | | 1/4 |
| | | R55E R55½E |
| | | S24 S19 |
| | | 2017 |
| İ | | 2017 |
| 80.000 | Point for the cor. of secs. | 13, 18, 19 and 24. |
| | Set a stainless steel post, 27 ins. in the ground, over cap mkd. | 28 ins. long, 2 1/2 ins. diam., a plastic-encased magnet, with brass |
| | | T13N |
| | | R55E R55½E |
| | | S13 S18 |
| | | |
| | | S24 S19 |
| · | | 2017 |
| | | |
| | NORTH, bet. secs. 13 and 18. | |
| 40.000 | Point for the 1/4 sec. cor. | |
| | Set a stainless steel post, 26 ins. in the ground, over cap mkd. | 28 ins. long, 2 1/2 ins. diam., a plastic-encased magnet, with brass |
| | | T13N |
| | | 1/4 |
| | | R55E R55½E |
| | | S13 S18 |
| | | 2017 |
| 00.000 | Point for the rest of the | 7 10 12 10 |
| 80.000 | Point for the cor. of secs. | /, 12, 13 and 18. |
| | | |
| | | |
| | | |

SURVEY OF THE EAST BOUNDARY, T. 13 N., R. 55 E., MOUNT DIABLO MERIDIAN, NEVADA

| CHAINS | |
|--------|---|
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. |
| | T13N |
| | R55E R55½E |
| | S12 S 7 |
| | |
| | S13 S18 |
| | 2017 |
| | NORTH, bet. secs. 7 and 12. |
| 8.00 | Dirt road, 15 lks. wide, bears S. 75° E. and N. 75° W. |
| 40.000 | Point for the 1/4 sec. cor. of secs. 7 and 12. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 9 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd. |
| | T13N |
| | 1/4 |
| | R55E R55½E |
| | S12 S 7 |
| | 2017 |
| 80.000 | Point for the cor. of secs. 1, 6, 7 and 12. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. |
| | Tlan |
| | R55E R55½E |
| | S 1 S 6 |
| | S12 S 7 |
| • | 512 5 7 |
| | 2017 |
| | NORTH, bet. secs. 1 and 6. |
| 40.000 | Point for the 1/4 sec. cor. of secs. 1 and 6. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. |
| : | |
| | |
| | |

SURVEY OF THE EAST BOUNDARY, T. 13 N., R. 55 E., MOUNT DIABLO MERIDIAN, NEVADA

| CHAINS | |
|--------|---|
| | T13N 1/4 |
| | R55E R55½E |
| | S 1 S 6 |
| | 2017 |
| 80.000 | Point for the cor. of Tps. 13 and 13 1/2 N., Rs. 55 and 55 1/2 E. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. |
| | T13½N |
| | R55E R55½E S36 S31 |
| | 536 531 |
| | S 1 S 6 |
| | T13N |
| | 2017 |
| | |
| | SURVEY OF A PORTION OF THE NORTH BOUNDARY, T. 13 N., R. 55 E., MOUNT DIABLO MERIDIAN, NEVADA |
| | From the cor. of Tps. 13 and 13 1/2 N., Rs. 55 and 55 1/2 E., hereinbefore described. |
| | WEST, bet. secs. 1 and 36. |
| 40.000 | Point for the 1/4 sec. cor. of secs. 1 and 36. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. |
| | T13½N R55E |
| | S36 |
| | 1/4 — S 1 |
| - | T13N |
| | 2017 |
| 80.000 | Point for the cor. of secs. 1, 2, 35 and 36. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. |
| | |
| | |
| | |
| | |
| | |

SURVEY OF A PORTION OF THE NORTH BOUNDARY, T. 13 N., R. 55 E., MOUNT DIABLO MERIDIAN, NEVADA

| CHAINS | |
|--------|---|
| | T13½N R55E |
| | S35 S36 |
| | S 2 S 1 |
| | T13N |
| | |
| | 2017 |
| | |
| | WEST, bet. secs. 2 and 35. |
| 40.000 | Point for the 1/4 sec. cor. of secs. 2 and 35. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. |
| | T13½N R55E |
| | S35 |
| | 1/4 |
| | S 2 T13N |
| | |
| | 2017 |
| 80.000 | Point for the cor. of secs. 2, 3, 34 and 35. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. |
| | T13½N R55E |
| | S34 S35 |
| | |
| | S 3 S 2 T13N |
| | |
| | 2017 |
| | |
| | WEST, bet. secs. 3 and 34. |
| 40.000 | Point for the 1/4 sec. cor. of secs. 3 and 34. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. |
| | |
| | |
| | |
|] | |
| | |
| | |
| | |
| | |
| | |

SURVEY OF A PORTION OF THE NORTH BOUNDARY, T. 13 N., R. 55 E., MOUNT DIABLO MERIDIAN, NEVADA

| | T. 13 N., R. 55 E., MOUNT DIABLO MERIDIAN, NEVADA |
|--------|---|
| CHAINS | |
| | T13½N R55E |
| | 1/4 — |
| | S 3 |
| | T13N |
| | 2017 |
| 80.000 | Point for the cor. of secs. 3, 4, 33 and 34. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. |
| | T13½N R55E |
| | S33 S34 |
| | S 4 S 3 |
| | T13N |
| | 2017 |
| | |
| | SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 13 N., R. 55 E., MOUNT DIABLO MERIDIAN, NEVADA |
| | From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 in. above ground, with brass cap mkd. as described in the field notes of the survey of a portion of the N. bdy. of T. 12 N., R. 55 E., executed concurrently under this same Group. |
| | N. 0°00'40" W., bet. secs. 35 and 36. |
| 40.000 | Point for the 1/4 sec. cor. of secs. 35 and 36. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. |
| , | T13N R55E |
| | 1/4 S35 S36 |
| | 535 536 |
| | 2017 |
| 80.000 | Point for the cor. of secs. 25, 26, 35 and 36. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. |
| | |
| | |
| | |
| | |

| Tp., hereinbefore described. WEST, bet. secs. 25 and 36. Point for the 1/4 sec. cor. of secs. 25 and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with bracap mkd. T13N R55E S25 1/4 S36 2017 80.000 The cor. of secs. 25, 26, 35 and 36. N. 0°00'40" W., bet. secs. 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with bracap mkd. T13N R55E 1/4 S26 S25 2017 64.10 Dirt road, 20 lks. wide, bears N. 80° E. and S. 80° W. Point for the cor. of secs. 23, 24, 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with bracap mkd. | | 1. 13 N., R. 55 E., MOUNT DIABLO MERIDIAN, NEVADA |
|--|--------|---|
| S26 S25 S35 S36 T13N 2017 From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of th Tp., hereinbefore described. WEST, bet. secs. 25 and 36. Point for the 1/4 sec. cor. of secs. 25 and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brace pmkd. T13N R55E S25 1/4 S36 2017 80.000 The cor. of secs. 25, 26, 35 and 36. N. 0°00'40" W., bet. secs. 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brace pmkd. T13N R55E 1/4 S26 S25 2017 64.10 Dirt road, 20 lks. wide, bears N. 80° E. and S. 80° W. Point for the cor. of secs. 23, 24, 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brace plastic steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brace plast | CHAINS | |
| From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of th Tp., hereinbefore described. WEST, bet. secs. 25 and 36. Point for the 1/4 sec. cor. of secs. 25 and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with bracap mkd. T13N R55E S25 1/4 S36 2017 80.000 The cor. of secs. 25, 26, 35 and 36. N. 0°00'40" W., bet. secs. 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with bracap mkd. T13N R55E 1/4 S26 S25 2017 64.10 Dirt road, 20 lks. wide, bears N. 80° E. and S. 80° W. 80.000 Point for the cor. of secs. 23, 24, 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with bracap mkd. | | |
| From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of th Tp., hereinbefore described. WEST, bet. secs. 25 and 36. Point for the 1/4 sec. cor. of secs. 25 and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with bra cap mkd. T13N R55E S25 1/4 S36 2017 80.000 The cor. of secs. 25, 26, 35 and 36. N. 0°00'40" W., bet. secs. 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with bracap mkd. T13N R55E 1/4 S26 S25 2017 64.10 Dirt road, 20 lks. wide, bears N. 80° E. and S. 80° W. 80.000 Point for the cor. of secs. 23, 24, 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with bracaches and second seco | | S26 S25 |
| From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of th Tp., hereinhefore described. WEST, bet. secs. 25 and 36. 40.000 Point for the 1/4 sec. cor. of secs. 25 and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with bracap mkd. T13N R55E S25 1/4 83.6 2017 80.000 The cor. of secs. 25, 26, 35 and 36. N. 0°00'40" W., bet. secs. 25 and 26. Point for the 1/4 sec. cor. of secs. 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with bracap mkd. T13N R55E 1/4 S26 S25 2017 64.10 Dirt road, 20 1ks. wide, bears N. 80° E. and S. 80° W. Point for the cor. of secs. 23, 24, 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with bracap magn | | S35 S36 |
| From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., hereinbefore described. WEST, bet. secs. 25 and 36. Point for the 1/4 sec. cor. of secs. 25 and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with bracap mkd. T13N R55E S25 1/4 S36 2017 80.000 The cor. of secs. 25, 26, 35 and 36. N. 0°00'40" W., bet. secs. 25 and 26. Point for the 1/4 sec. cor. of secs. 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with bracap mkd. T13N R55E 1/4 S26 S25 2017 64.10 Dirt road, 20 lks. wide, bears N. 80° E. and S. 80° W. Point for the cor. of secs. 23, 24, 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with bracap mkd. | | T13N |
| Tp., hereinbefore described. WEST, bet. secs. 25 and 36. Point for the 1/4 sec. cor. of secs. 25 and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with bracap mkd. T13N R55E S25 1/4 S36 2017 80.000 The cor. of secs. 25, 26, 35 and 36. N. 0°00'40" W., bet. secs. 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with bracap mkd. T13N R55E 1/4 S26 S25 2017 64.10 Dirt road, 20 lks. wide, bears N. 80° E. and S. 80° W. Point for the cor. of secs. 23, 24, 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with bracap mkd. | | 2017 |
| Tp., hereinbefore described. WEST, bet. secs. 25 and 36. Point for the 1/4 sec. cor. of secs. 25 and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with bracap mkd. T13N R55E S25 1/4 S36 2017 80.000 The cor. of secs. 25, 26, 35 and 36. N. 0°00'40" W., bet. secs. 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with bracap mkd. T13N R55E 1/4 S26 S25 2017 64.10 Dirt road, 20 lks. wide, bears N. 80° E. and S. 80° W. Point for the cor. of secs. 23, 24, 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with bracap mkd. | | |
| Point for the 1/4 sec. cor. of secs. 25 and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with bracap mkd. T13N R55E S25 1/4 —— S36 2017 The cor. of secs. 25, 26, 35 and 36. N. 0°00'40" W., bet. secs. 25 and 26. Point for the 1/4 sec. cor. of secs. 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with bracap mkd. T13N R55E 1/4 S26 S25 2017 64.10 Dirt road, 20 lks. wide, bears N. 80° E. and S. 80° W. Point for the cor. of secs. 23, 24, 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with bracap magn | • | From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., hereinbefore described. |
| Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with bracap mkd. T13N R55E S25 1/4 S36 2017 The cor. of secs. 25, 26, 35 and 36. N. 0°00'40" W., bet. secs. 25 and 26. Point for the 1/4 sec. cor. of secs. 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with bracap mkd. T13N R55E 1/4 S26 S25 2017 64.10 Dirt road, 20 lks. wide, bears N. 80° E. and S. 80° W. Point for the cor. of secs. 23, 24, 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with bracap mkd. | | WEST, bet. secs. 25 and 36. |
| 25 ins. in the ground, over a plastic-encased magnet, with bra cap mkd. T13N R55E S25 1/4 S36 2017 The cor. of secs. 25, 26, 35 and 36. N. 0°00'40" W., bet. secs. 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with braccap mkd. T13N R55E 1/4 S26 S25 2017 64.10 Dirt road, 20 lks. wide, bears N. 80° E. and S. 80° W. Point for the cor. of secs. 23, 24, 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with braccap magnet magnet, with braccap magnet magnet, with braccap magnet magnet magnet, with braccap magnet | 40.000 | Point for the 1/4 sec. cor. of secs. 25 and 36. |
| 2017 80.000 The cor. of secs. 25, 26, 35 and 36. N. 0°00'40" W., bet. secs. 25 and 26. 40.000 Point for the 1/4 sec. cor. of secs. 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with braicap mkd. T13N R55E 1/4 S26 S25 2017 64.10 Dirt road, 20 lks. wide, bears N. 80° E. and S. 80° W. 80.000 Point for the cor. of secs. 23, 24, 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brain the ground. | | 25 ins. in the ground, over a plastic-encased magnet, with bras |
| 1/4 — S336 2017 80.000 The cor. of secs. 25, 26, 35 and 36. N. 0°00'40" W., bet. secs. 25 and 26. 40.000 Point for the 1/4 sec. cor. of secs. 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with braicap mkd. T13N R55E 1/4 S26 S25 2017 64.10 Dirt road, 20 lks. wide, bears N. 80° E. and S. 80° W. 80.000 Point for the cor. of secs. 23, 24, 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brains. | | T13N R55E |
| S36 2017 80.000 The cor. of secs. 25, 26, 35 and 36. N. 0°00'40" W., bet. secs. 25 and 26. 40.000 Point for the 1/4 sec. cor. of secs. 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with braccap mkd. T13N R55E 1/4 S26 S25 2017 64.10 Dirt road, 20 lks. wide, bears N. 80° E. and S. 80° W. 80.000 Point for the cor. of secs. 23, 24, 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with braccations in the ground, over a plastic-encased magnet, with braccations in the ground, over a plastic-encased magnet, with braccations in the ground, over a plastic-encased magnet, with braccations in the ground, over a plastic-encased magnet, with braccations in the ground, over a plastic-encased magnet, with braccations in the ground, over a plastic-encased magnet, with braccations in the ground, over a plastic-encased magnet, with braccations in the ground, over a plastic-encased magnet, with braccations in the ground, over a plastic-encased magnet, with braccations in the ground, over a plastic-encased magnet, with braccations in the ground, over a plastic-encased magnet, with braccations in the ground, over a plastic-encased magnet, with braccations in the ground, over a plastic-encased magnet, with braccations in the ground in t | | |
| The cor. of secs. 25, 26, 35 and 36. N. 0°00'40" W., bet. secs. 25 and 26. Point for the 1/4 sec. cor. of secs. 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with braccap mkd. T13N R55E 1/4 S26 S25 2017 64.10 Dirt road, 20 lks. wide, bears N. 80° E. and S. 80° W. 80.000 Point for the cor. of secs. 23, 24, 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brace. | | · · · · · · · · · · · · · · · · · · · |
| The cor. of secs. 25, 26, 35 and 36. N. 0°00'40" W., bet. secs. 25 and 26. Point for the 1/4 sec. cor. of secs. 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with braccap mkd. T13N R55E 1/4 S26 S25 2017 Dirt road, 20 lks. wide, bears N. 80° E. and S. 80° W. Point for the cor. of secs. 23, 24, 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brase in the ground, over a plastic-encased magnet, with brase in the ground, over a plastic-encased magnet, with brase in the ground, over a plastic-encased magnet, with brase in the ground, over a plastic-encased magnet, with brase in the ground, over a plastic-encased magnet, with brase in the ground, over a plastic-encased magnet, with brase in the ground, over a plastic-encased magnet, with brase in the ground. | | |
| N. 0°00'40" W., bet. secs. 25 and 26. Point for the 1/4 sec. cor. of secs. 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with braccap mkd. T13N R55E 1/4 S26 S25 2017 Dirt road, 20 lks. wide, bears N. 80° E. and S. 80° W. Point for the cor. of secs. 23, 24, 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brack. | | 2017 |
| Point for the 1/4 sec. cor. of secs. 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with braccap mkd. T13N R55E 1/4 S26 S25 2017 Dirt road, 20 lks. wide, bears N. 80° E. and S. 80° W. Point for the cor. of secs. 23, 24, 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with bras | 80.000 | The cor. of secs. 25, 26, 35 and 36. |
| Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with braccap mkd. T13N R55E 1/4 S26 S25 2017 64.10 Dirt road, 20 lks. wide, bears N. 80° E. and S. 80° W. 80.000 Point for the cor. of secs. 23, 24, 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with bras | | N. 0°00'40" W., bet. secs. 25 and 26. |
| 26 ins. in the ground, over a plastic-encased magnet, with braceap mkd. T13N R55E 1/4 S26 S25 2017 64.10 Dirt road, 20 lks. wide, bears N. 80° E. and S. 80° W. 80.000 Point for the cor. of secs. 23, 24, 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brase | 40.000 | Point for the 1/4 sec. cor. of secs. 25 and 26. |
| 1/4 S26 S25 2017 64.10 Dirt road, 20 lks. wide, bears N. 80° E. and S. 80° W. 80.000 Point for the cor. of secs. 23, 24, 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with bras | | 26 ins. in the ground, over a plastic-encased magnet, with brass |
| S26 S25 2017 64.10 Dirt road, 20 lks. wide, bears N. 80° E. and S. 80° W. 80.000 Point for the cor. of secs. 23, 24, 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with bras | | T13N R55E |
| Dirt road, 20 lks. wide, bears N. 80° E. and S. 80° W. 80.000 Point for the cor. of secs. 23, 24, 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with bras | | · · |
| Dirt road, 20 lks. wide, bears N. 80° E. and S. 80° W. Point for the cor. of secs. 23, 24, 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with bras | | S26 S25 |
| Point for the cor. of secs. 23, 24, 25 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with bras | | 2017 |
| Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with bras | 64.10 | Dirt road, 20 lks. wide, bears N. 80° E. and S. 80° W. |
| 25 ins. in the ground, over a plastic-encased magnet, with bras | 80.000 | Point for the cor. of secs. 23, 24, 25 and 26. |
| cap mxc. | | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. |
| | | |
| | | |
| | | |

| | T-Park Assertion Control of the Cont |
|----------|--|
| CHAINS | |
| | T13N R55E |
| | S23 S24 |
| | S26 S25 |
| | · |
| | 2017 |
| | From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., hereinbefore described. |
| | WEST, bet. secs. 24 and 25. |
| 40.000 | Point for the 1/4 sec. cor. of secs. 24 and 25. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. |
| | T13N R55E S24 1/4 — S25 |
| | 2017 |
| 80.000 | The cor. of secs. 23, 24, 25 and 26. |
| | N. 0°00'40" W., bet. secs. 23 and 24. |
| 40.000 | Point for the 1/4 sec. cor. of secs. 23 and 24. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. |
| | T13N R55E |
| | 1/4 |
| | S23 S24 |
| | 2017 |
| | Cor. is located in a wash, 4 chs. wide, drains S. 70° E. |
| 80.000 | Point for the cor. of secs. 13, 14, 23 and 24. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. |
| | |
| | |
| | |
| | |
| | |
| | |
| <u> </u> | I |

| | 1. 13 N., R. 55 E., MOUNT DIABLO MERIDIAN, NEVADA |
|--------|---|
| CHAINS | |
| | T13N R55E |
| | S14 S13 |
| | S23 S24 |
| | 2017 |
| | From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., hereinbefore described. |
| | WEST, bet. secs. 13 and 24. |
| 40.000 | Point for the 1/4 sec. cor. of secs. 13 and 24. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd. |
| | T13N R55E |
| ! | \$13 |
| | 1/4 ———————————————————————————————————— |
| | 524 |
| | 2017 |
| | Cor. is located in a wash, 40 lks. wide, drains N. 85° E. |
| 80.000 | The cor. of secs. 13, 14, 23 and 24. |
| | N. 0°00'40" W., bet. secs. 13 and 14. |
| 40.000 | Point for the 1/4 sec. cor. of secs. 13 and 14. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. |
| | T13N R55E |
| | 1/4 |
| | S14 S13 |
| | 2017 |
| 80.000 | Point for the cor. of secs. 11, 12, 13 and 14. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. |
| | |
| | |
| | |
| | |
| | |
| | |

| CHAINS | |
|--------|---|
| | T13N R55E |
| | S11 S12 |
| | S14 S13 |
| | 2017 |
| | |
| | From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., hereinbefore described. |
| | WEST, bet. secs. 12 and 13. |
| 40.000 | Point for the 1/4 sec. cor. of secs. 12 and 13. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. |
| | T13N R55E |
| | S12 |
| | 1/4 |
| | S13 |
| | 2017 |
| 80.000 | The cor. of secs. 11, 12, 13 and 14. |
| | N. 0°00'40" W., bet. secs. 11 and 12. |
| 26.45 | Dirt road, 15 lks. wide, bears S. 75° E. and N. 75° W. |
| 40.000 | Point for the 1/4 sec. cor. of secs. 11 and 12. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. |
| | T13N R55E |
| | 1/4 |
| | S11 S12 |
| | 2017 |
| 80.000 | Point for the sec. cor. of secs. 1, 2, 11 and 12. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. |
| | |
| | |
| | |
| | |
| | |
| | |
| | |

| CHAINS | |
|--------|--|
| | T13N R55E |
| | S 2 S 1 |
| | S11 S12 |
| | |
| | 2017 |
| | |
| | From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., hereinbefore described. |
| | WEST, bet. secs. 1 and 12. |
| 40.000 | Point for the 1/4 sec. cor. of secs. 1 and 12. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. |
| | T13N R55E |
| | S 1 |
| | 1/4 —— S12 |
| | 512 |
| | 2017 |
| 80.000 | The cor. of secs. 1, 2, 11 and 12. |
| · | N. 0°00'40" W., bet. secs. 1 and 2. |
| 40.000 | Point for the 1/4 sec. cor. of secs. 1 and 2. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. |
| | T13N R55E |
| | 1/4 |
| | S 2 S 1 |
| | 2017 |
| 80.000 | The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., hereinbefore described. |
| | From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, flush with surface of ground, with brass cap mkd. as described in the field notes of the survey of a portion of the N. bdy. of T. 12 N., R. 55 E., executed concurrently under this same Group. |
| | N. 0°01'20" W., bet. secs. 34 and 35. |
| | |
| | |
| | |

| | 1. 15 M., R. 55 E., MOUNT DIADLO MERIDIAN, NEVADA |
|--------|--|
| CHAINS | |
| 40.000 | Point for the 1/4 sec. cor. of secs. 34 and 35. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd. |
| | T13N R55E 1/4 S34 S35 |
| | 2017 |
| 80.000 | Point for the cor. of secs. 26, 27, 34 and 35. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. |
| | T13N R55E S27 S26 |
| | S34 S35 |
| | 2017 |
| | |
| | From the cor. of secs. 25, 26, 35 and 36. |
| | WEST, bets. secs. 26 and 35. |
| 40.000 | Point for the 1/4 sec. cor. of secs. 26 and 35. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd. |
| | T13N R55E |
| | S26 1/4 —— |
| | S35 |
| | 2017 |
| 80.000 | The cor. of secs. 26, 27, 34 and 35. |
| | N. 0°01'20" W., bet. secs. 26 and 27. |
| 18.55 | Dirt road, 20 lks. wide, bears N. 14° E. and S. 14° W. |
| 40.000 | Point for the 1/4 sec. cor. of secs. 26 and 27. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. |
| | |
| | |
| | |

| CHAINS | |
|--------|---|
| | T13N R55E |
| | 1/4 S27 S26 |
| | <u>'</u> |
| | 2017 |
| 80.000 | Point for the cor. of secs. 22, 23, 26 and 27. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. |
| | T13N_R55E |
| | S22 S23 |
| | S27 S26 |
| | 2017 |
| | From the cor. of secs. 23, 24, 25 and 26. |
| | WEST, bet. secs. 23 and 26. |
| 40.000 | Point for the 1/4 sec. cor. of secs. 23 and 26. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd. |
| | T13N R55E |
| | S23 |
| | 1/4 —— S26 |
| | 2017 |
| | |
| 80.000 | The cor. of secs. 22, 23, 26 and 27. |
| | N. 0°01'20" W., bet. secs. 22 and 23. |
| 40.000 | Point for the 1/4 sec. cor. of secs. 22 and 23. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. |
| | T13N R55E |
| | 1/4 |
| | S22 S23 |
| | 2017 |
| | |
| | |
| | · |
| | |

| CHAINS | |
|--------|--|
| 80.000 | Point for the cor. of secs. 14, 15, 22 and 23. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. |
| | T13N R55E S15 S14 |
| į | S22 S23 |
| | 2017 |
| 1 | From the cor. of secs. 13, 14, 23 and 24. |
| | WEST, bet. secs. 14 and 23. |
| 40.000 | Point for the 1/4 sec. cor. of secs. 14 and 23. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. |
| | T13N R55E |
| | S14 |
| | 1/4 —— S23 |
| | 2017 |
| 80.000 | The cor. of secs. 14, 15, 22 and 23. |
| | |
| | N. 0°01'20" W., bet. secs. 14 and 15. |
| 40.000 | Point for the 1/4 sec. cor. of secs. 14 and 15. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. |
| | T13N R55E 1/4 S15 S14 |
| | 2017 |
| 80.000 | Point for the cor. of secs. 10, 11, 14 and 15. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd. |
| | |
| | |
| | 1 |

| CHAINS | |
|--------|---|
| | T13N R55E |
| | S10 S11 |
| | S15 S14 |
| | 2017 |
| | · |
| | From the cor. of secs. 11, 12, 13 and 14. |
| | WEST, bet. secs. 11 and 14. |
| 40.000 | Point for the 1/4 sec. cor. of secs. 11 and 14. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. |
| | T13N R55E |
| | S11 1/4 |
| | \$14 |
| | 2017 |
| 80.000 | The cor. of secs. 10, 11, 14 and 15. |
| | N. 0°01'20" W., bet. secs. 10 and 11. |
| 40.000 | Point for the 1/4 sec. cor. of secs. 10 and 11. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. |
| | T13N R55E |
| | 1/4 S10 S11 |
| | 2017 |
| 44.20 | Dirt road, 15 lks. wide, bears S. 75° E. and N. 75° W. |
| 80.000 | Point for the cor. of secs. 2, 3, 10 and 11. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. |
| | |
| | |
| | |
| | |
| | |
| | |

| CHAINS | |
|--------|--|
| | T13N R55E |
| | S 3 S 2 |
| | S10 S11 |
| | 2017 |
| | |
| | From the cor. of secs. 1, 2, 11 and 12. |
| | WEST, bet. secs. 2 and 11. |
| 40.000 | Point for the 1/4 sec. cor. of secs. 2 and 11. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. |
| | T13N R55E |
| | 1/4 — |
| | S11 |
| | 2015 |
| | 2017 |
| 80.000 | The cor. of secs. 2, 3, 10 and 11. |
| | N. 0°01'20" W., bet. secs. 2 and 3. |
| 40.000 | Point for the 1/4 sec. cor. of secs. 2 and 3. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. |
| | T13N R55E |
| | 1/4 |
| | S 3 S 2 |
| | 2017 |
| 80.000 | The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., hereinbefore described. |
| | From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. as described in the field notes of the survey of a portion of the N. bdy. of T. 12 N., R. 55 E., executed concurrently under this same Group. |
| | N. 0°02'10" W., bet. secs. 33 and 34. |
| 40.000 | Point for the 1/4 sec. cor. of secs. 33 and 34. |
| | |
| | |
| | |

| | 1. 13 N., K. 33 E., MOUNT DIABLO MERIDIAN, NEVADA |
|--------|---|
| CHAINS | |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. |
| | T13N R55E |
| | 1/4 |
| | S33 S34 |
| | 2017 |
| 43.45 | Dirt road, 20 lks. wide, bears S. 70° E. and N. 70° W. |
| 80.000 | Point for the cor. of secs. 27, 28, 33 and 34. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. |
| | T13N R55E |
| | S28 S27 |
| | S33 S34 |
| | 555 554 |
| | 2017 |
| | From the cor. of secs. 26, 27, 34 and 35. |
| | WEST, bet. secs. 27 and 34. |
| 6.60 | Dirt road, 20 lks. wide, bears N. 15° E. and S. 15° W. |
| 40.000 | Point for the 1/4 sec. cor. of secs. 27 and 34. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. |
| | T13N R55E |
| | S27 |
| | 1/4 |
| | \$34 |
| | 2017 |
| 80.000 | The cor. of secs. 27, 28, 33 and 34. |
| | N. 0°02'10" W., bet. secs. 27 and 28. |
| 40.000 | Point for the 1/4 sec. cor. of secs. 27 and 28. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. |
| | |
| | |
| | |

| | 1. 13 N., R. 35 E., MOUNT DIABLO MERIDIAN, NEVADA |
|--------|---|
| CHAINS | |
| | T13N R55E |
| | 1/4 |
| | S28 S27 |
| | |
| | 2017 |
| 80.000 | Point for the cor. of secs. 21, 22, 27 and 28. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. |
| | T13N R55E |
| | S21 S22 |
| | . — |
| | S28 S27 |
| | 2017 |
| | From the cor. of secs. 22, 23, 26 and 27. |
| | WEST, bet. secs. 22 and 27. |
| 40.000 | Point for the 1/4 sec. cor. of secs. 22 and 27. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. |
| | T13N R55E |
| | S22 |
| | 1/4 — |
| | S27 |
| | 2017 |
| 80.000 | The cor. of secs. 21, 22, 27 and 28. |
| | N. 0°02'10 W., bet. secs. 21 and 22. |
| 40.000 | Point for the 1/4 sec. cor. of secs. 21 and 22. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. |
| | T13N R55E |
| | 1/4 |
| | S21 S22 |
| | 2017 |
| | |
| | |
| | |
| | |

| | 1. 13 N., K. 33 E., MOUNT DIABLO MERIDIAN, NEVADA |
|--------|--|
| CHAINS | |
| 80.000 | Point for the cor. of secs. 15, 16, 21 and 22. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. |
| | T13N R55E S16 S15 |
| | S21 S22 |
| | 2017 |
| | From the cor. of secs. 14, 15, 22 and 23. |
| | WEST, bet. secs. 15 and 22. |
| 40.000 | Point for the 1/4 sec. cor. of secs. 15 and 22. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd. |
| | T13N R55E |
| | S15 1/4 — |
| | S22 |
| | 2017 |
| 80.000 | The cor. of secs. 15, 16, 21 and 22. |
| | N. 0°02'10" W., bet. secs. 15 and 16. |
| 40.000 | Point for the 1/4 sec. cor. of secs. 15 and 16. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd. |
| | T13N R55E 1/4 S16 S15 |
| | 2017 |
| 80.000 | Point for the cor. of secs. 9, 10, 15 and 16. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. |
| | |
| | |
| | |
| | |

| f | I I I III, II. 33 E., HOURT BIRDIO HEREBER, REVIDIT |
|--------|---|
| CHAINS | |
| | T13N R55E |
| | S 9 S10 |
| | S16 S15 |
| | 2017 |
| | |
| | From the cor. of secs. 10, 11, 14 and 15. |
| | WEST, bet. secs. 10 and 15. |
| 40.000 | Point for the 1/4 sec. cor. of secs. 10 and 15. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. |
| | T13N R55E |
| | S10 |
| | 1/4 —— S15 |
| | |
| | 2017 |
| 80.000 | The cor. of secs. 9, 10, 15 and 16. |
| | N. 0°02'10" W., bet. secs. 9 and 10. |
| 40.000 | Point for the 1/4 sec. cor. of secs. 9 and 10. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. |
| | T13N R55E |
| | 1/4 |
| | s 9 s10 |
| | 2017 |
| 62.30 | Dirt road, 15 lks. wide, bears S. 80° E. and N. 80° W. |
| 80.000 | Point for the cor. of secs. 3, 4, 9 and 10. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. |
| | |
| | |
| | |
| | |
| | |
| | |
| | |

| CHAINS | |
|--------|--|
| | T13N R55E |
| | S 4 S 3 |
| | S 9 S10 |
| | 0015 |
| | 2017 |
| | From the cor. of secs. 2, 3, 10 and 11. |
| | WEST, bet. secs. 3 and 10. |
| 40.000 | Point for the 1/4 sec. cor. of secs. 3 and 10. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd. |
| | T13N R55E |
| | S 3 |
| | 1/4 —— S10 |
| | 310 |
| | 2017 |
| 80.000 | The cor. of secs. 3, 4, 9 and 10. |
| | N. 0°02'10 W., bet. secs. 3 and 4. |
| 40.000 | Point for the 1/4 sec. cor. of secs. 3 and 4. |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. |
| | T13N R55E |
| | 1/4 |
| | S 4 S 3 |
| | 2017 |
| 80.000 | The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., hereinbefore described. |
| | GENERAL DESCRIPTION |
| | The lands contained within the scope of this survey are located |
| | in Nye County, Nevada, in and around the community of Duckwater, Nevada. The land is generally level ground, with areas of hilly terrain, at an average elevation of 5950 ft. above sea level. The vegetation is primarily sagebrush and grass. Access is gained primarily by way of Nevada State Route 379 and numerous dirt and paved roads. |
| | |

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

23

FIELD ASSISTANTS

Bradley F. Dillon

Sup. Cadastral Surveyor

Brandon G. Courtright

Cadastral Surveyor

Griffin B. Dekker

Student Trainee

Kenneth W. Tynan

Student Trainee

CERTIFICATE OF SURVEY

I, Justin V. Haddon, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 25th day of July 2017, and amended special instructions bearing date of the 3rd day of October, 2019, I have surveyed the east boundary, a portion of the north boundary, and a portion of the subdivisional lines of Township 13 North, Range 55 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

DEC 0 3 2019

(Date)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT Reno, Nevada

The foregoing field notes of the survey of the east boundary, a portion of the north boundary, and a portion of the subdivisional lines, Township 13 North, Range 55 East, Mount Diablo Meridian, Nevada, executed by, Justin V. Haddon, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

DEC 0 3 2019

(Date)

(Chief Cadastral Surveyor for Nevada)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above described surveys in Township 13 North, Range 55 East, Mount Diablo Meridian, Nevada, is a true copy of the original field notes.

(Date)

(Chief Cadastral Surveyor for Nevada)