

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF THE THIRD STANDARD PARALLEL SOUTH,
THROUGH PORTIONS OF RANGE 63 EAST,
A PORTION OF THE SOUTH BOUNDARY, THE EAST BOUNDARY
AND A PORTION OF THE SUBDIVISIONAL LINES,
AND METES-AND-BOUNDS SURVEYS OF PORTIONS OF U.S. HIGHWAY NO. 93 AND
NEVADA STATE ROUTE NO. 168, AND A METES-AND-BOUNDS SURVEY IN SECTION 1,
TOWNSHIP 13 SOUTH, RANGE 63 EAST,
OF THE MOUNT DIABLO MERIDIAN,
IN THE STATE OF NEVADA

EXECUTED BY

David J. Passmore, Professional Land Surveyor (VTN, Inc.)

Craig L. Wanless, Cadastral Surveyor (BLM)

Under Special Instructions dated October 9, 2003,
approved October 9, 2003,
and Supplemental Special Instructions dated July 20, 2004, approved
July 20, 2004, and Supplemental Special Instructions dated
September 21, 2004, approved September 21, 2004, which provided for the
surveys included under Group No. 814,
and Assignment Instructions dated October 13, 2003

Survey commenced October 14, 2003

Survey completed September 23, 2004

INDEX DIAGRAM

TOWNSHIP 13 SOUTH, RANGE 63 EAST, MOUNT DIABLO MERIDIAN, NEVADA

	6	4			3	2
6	45 5 44	39 4	3	2	24 1 17 23	
7	43 8 43	38 9 37	10	11	12 15	
18	42 17 41	37 16 36	15 34	14 31	13 14	
19	40 20 39	35 21 34	33 22 32	29 23 28	22 24 12 21	
30	29	28	27 31	27 26 26	20 25 10 19	
31	32	33	34 8	26 35 8	19 36 9 6	

Metes-and-Bounds Survey of the Centerline of Nevada State Route No. 168,
 through Sections 20, 21, 22, 23, 25 and 26 Pg. 47 - 52
 Metes-and-Bounds Survey of a Portion of U.S. Highway No. 93,
 through Sections 5, 8, 17, and 20 Pg. 52 - 56
 Metes-and-Bounds Survey in Section 1 Pg. 56 - 57

003

TOWNSHIP 13 SOUTH, RANGE 63 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The following field notes are those of the dependent resurvey of the Third Standard Parallel South, through portions of Range 63 East, a portion of the south boundary, the east boundary and a portion of the subdivisional lines, and metes-and-bounds surveys of portions of U.S. Highway No. 93 and Nevada State Route No. 168, and a metes-and-bounds survey in section 1, Township 13 South, Range 63 East, Mount Diablo Meridian, Nevada.

The Third Standard Parallel South, through Range 63 East, and the south, east, and west boundaries, and the subdivisional lines were surveyed by U.S. Deputy Surveyors C.F. Putnam and W.F. Benson in 1881, under Contract No. 125.

Before restoring the corners, the lines of the original surveys were retraced and a diligent search made for any evidence of the original corners and other calls of the original field note record.

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, the Special Instructions dated October 9, 2003 and Supplemental Special Instructions dated July 20, 2004, and September 21, 2004, for Group No. 814.

The direction and distances of the lines of this survey were obtained by Trimble 4700 and 5700 Global Positioning System (GPS) receivers using the real-time kinematic method and refer to the true meridian, based on geodetic methods.

The mean bearings of the lines and horizontal equivalents of ground distances only are entered in the field notes.

The geographic position, NAD 1983(1999), of the corner of Townships 13 South, Ranges 63 and 64 East, as determined by survey grade global positioning system receivers, in 2003, from National Geodetic Survey control station, "MOAPA LA PLACE" located in section 32, Township 14 South, Range 66 East, is as follows:

Latitude: 36°45'57.351" N. Longitude: 114°52'23.793" W.

The mean magnetic declination is 15° E., as shown on U.S.G.S. quadrangle map "WILDCAT WASH SW, NEV.", dated 1969.

DEPENDENT RESURVEY OF THE THIRD STANDARD PARALLEL SOUTH,
THROUGH PORTIONS OF RANGE 63 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Reestablishment of the Survey Executed by C.F. Putnam in 1881</p>
	<p>Beginning at the standard cor. of Tps. 12 S., Rs. 63 and 64 E., determined by Bruce R. Scott, Nevada Professional Land Surveyor No. 3579, not recorded, monumented with a rebar, 5/8 in. diam., firmly set, in a mound of stone, 4 ft. diam., 1 ft. high, with a metal tag mkd. LS 3579 BRS. This position is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>SC T13S R63E R64E S36 S31</p> <hr style="width: 10%; margin: auto;"/> <p>2003</p> </div> <p>Deposit the rebar inside of the stainless steel post.</p> <p>S. 89°55'50" W., on the S. bdy. of sec. 36, T. 12 S., R. 63 E.</p> <p>Over nearly level land.</p>
17.091	<p>The closing cor. of Tps. 13 S., Rs. 63 and 64 E., hereinafter described.</p>
18.137	<p>Point for a witness point and intersection with a line parallel to and 100 ft. easterly of the centerline of Nevada State Route No. 7, hereinafter described.</p>
39.625	<p>The standard 1/4 sec. cor. of sec. 36, T. 12 S., R. 63 E., determined by Sam Long, Professional Land Surveyor No. 9047, in 2000, as recorded in Clark County Corner Record, Book No. 20000321, Instrument No. 01049, monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, in mound of stone, 2 ft. diam., 1 ft. high, with an aluminum cap mkd. VTN PLS 9047. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

005

DEPENDENT RESURVEY OF THE THIRD STANDARD PARALLEL SOUTH,
THROUGH PORTIONS OF RANGE 63 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>SC T12S R63E <u>1/4 S36</u></p> <p>2003</p> <p>Deposit the rebar inside of the stainless steel post.</p> <hr/> <p>S. 89°58'10" W., beginning new measurement.</p> <p>6.316 The W-E 1/64 sec. cor. of sec. 1 only, hereinafter described.</p> <p>15.932 The 1/4 sec. cor. of sec. 1 only, hereinafter described.</p> <p>29.00 Gulch, drains SE.</p> <p>33.40 Top of ascent; desc. over SW. slope.</p> <p>40.120 The standard cor. of secs. 35 and 36, T. 12 S., R. 63 E., perpetuated by Timothy J. Wolf, Professional Land Surveyor No. 9677, in 2002, from original evidence no longer in existence, as recorded in Lincoln County Recorder's office, Corner Record Book No. 166, Page No. 347, monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, with aluminum cap mkd. LVVWD T12S S35 S36 SC R63E PLS 9677. This is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <p>SC T12S R63E <u>S35 S36</u></p> <p>2003</p> <p>Deposit the rebar inside of the stainless steel post.</p> <hr/> <p>N. 89°52'20" W., on the S. bdy. of sec. 35, T. 12 S., R. 63 E.</p> <p>14.278 The closing cor. of secs. 1 and 2, hereinafter described.</p> <p>19.00 Gulch, drains SW.</p> <p>33.50 Top of ascent; desc. over SW. slope.</p>
--------	--

006

DEPENDENT RESURVEY OF THE THIRD STANDARD PARALLEL SOUTH,
THROUGH PORTIONS OF RANGE 63 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

40.106

The standard 1/4 sec. cor. of sec. 35, T. 12 S., R. 63 E.,
perpetuated by Sam Long, Professional Land Surveyor No. 9047,
in 2000, as recorded in Clark County Corner Record, Book
No. 20000321, Instrument No. 01049, monumented with a rebar,
5/8 in. diam., firmly set, flush with the surface of the
ground, with a lava stone, 12x10x9 ins., mkd. 1/4 on one face,
set on top of aluminum cap, in a mound of stone, 2 ft. diam.,
1 ft. high, with aluminum cap mkd. VTN PLS 9047.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, over a plastic-encased magnet, in a
collar of stone, with brass cap mkd.

SC
T12S R63E
1/4 S35

2003

Deposit the rebar inside and the original monument alongside
the stainless steel post.

From the standard cor. of secs. 32 and 33, T. 12 S., R. 63 E.,
monumented with a limestone, 14x11x8 ins., mkd. with SC and
3 notches on N. side, and in a mound of stone, 3 ft. diam.,
1 ft. high.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
20 ins. in the ground, over a plastic-encased magnet, and in a
mound of stone, 3 ft. base, to top, with brass cap mkd.

SC
T12S R63E
S32 | S33

2004

Deposit the original monument alongside the stainless steel
post.

The corner is located 30 lks. dist., N. of fence, bears E.
and W.

N. 89°58'50" W., on the S. bdy. of sec. 32, T. 12 S., R. 63 E.

Over nearly level land.

007

DEPENDENT RESURVEY OF THE THIRD STANDARD PARALLEL SOUTH,
THROUGH PORTIONS OF RANGE 63 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
15.980	The closing cor. of secs. 4 and 5, hereinafter described.
40.277	<p>The standard 1/4 sec. cor. of sec. 32, T. 12 S., R. 63 E., perpetuated by Sam Long, Nevada Professional Land Surveyor No. 9047, in 2000, as recorded in Clark County Corner Record Book No. 20000321, Instrument No. 01049, monumented with a rebar, 5/8 in. diam., with a plastic cap mkd. PLS 9047, alongside of which is set a cement stone, 11x6x6 ins. (Record, limestone, 12x10x8 ins.), no marks visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T12S R63E 1/4 S32</p> <p style="text-align: center;">2004</p> <p>Deposit the rebar inside and the original monument alongside the stainless steel post.</p> <p>The corner is located 25 lks. dist., N. of fence, bears E. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°20'50" W., beginning new measurement.</p>
15.976	The 1/4 sec. cor. of sec. 5 only, hereinafter described.
21.191	Point for a witness point and intersection with the centerline of U.S. Highway No. 93, hereinafter described.
40.192	<p>The standard cor. of secs. 31 and 32, T. 12 S., R. 63 E., monumented with a limestone, 15x13x10 ins., mkd. with SC and 1 notch on S. and 5 notches on E. sides, firmly set, and in a mound of stone, 3 ft. diam., 1 ft. high.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">SC T12S R63E S31 S32</p> <p style="text-align: center;">2004</p>

008

DEPENDENT RESURVEY OF THE THIRD STANDARD PARALLEL SOUTH,
THROUGH PORTIONS OF RANGE 63 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Deposit the original monument alongside the stainless steel post.</p> <hr/> <p>N. 89°14'10" W., on the S. bdy. of sec. 31, T. 12 S., R. 63 E.</p> <p>Ascend over gradual E. slope.</p> <p>16.058 Point for the closing cor. of secs. 5 and 6, hereinafter described.</p> <p>40.323 The standard 1/4 sec. cor. of sec. 31, T. 12 S., R. 63 E., monumented with a cement stone, 12x9x6 ins., (Record, limestone), mkd. 1/4 on one face, firmly set in a mound of stone, 2 ft. diam., 1 ft. high.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T12S R63E <u>1/4 S31</u></p> <p style="text-align: center;">2004</p> <p>Deposit the original monument alongside the stainless steel post.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY, T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of the Survey Executed by C.F. Putnam in 1881</p> <hr/> <p>From the cor. of Tps. 13 and 14 S., Rs. 63 and 64 E., perpetuated by Timothy J. Wolf, Nevada Professional Land Surveyor No. 9677, in 2002, as recorded in Clark County Survey Corner Record, Book No. 20031212, Instrument No. 01220, monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, in a mound of stone, 4 ft. diam., 1 ft. high, with aluminum cap mkd. LVVWD T13S R63E 2002 PLS 9677. The original corner monument is now stored in the Las Vegas Valley Water District office, Las Vegas, Nevada.</p>
--------	--

009

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>This is accepted as a careful and faithful perpetuation of the position of the original corner. This corner will now refer to the cor. of Tps. 13 S., Rs. 63 and 64 only.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td>T13S</td><td></td></tr> <tr><td>R63E</td><td>R64E</td></tr> <tr><td>S36</td><td>S31</td></tr> </table> </div> <p>2003</p> <p>Deposit the rebar inside of the stainless steel post.</p> <p>N. 89°15'20" W., on the S. bdy. of sec. 36.</p> <p>Over mountainous land.</p>	T13S		R63E	R64E	S36	S31
T13S							
R63E	R64E						
S36	S31						
1.00	Spur, slopes NE.						
2.60	Gulch, drains NE.						
38.50	Gulch, drains NE.						
39.992	<p>Point for the 1/4 sec. cor. of secs. 1 and 36, at proportionate dist.; there is no remaining evidence of the original corner. This corner will now refer to the cor. of sec. 36 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td>T13S</td><td>R63E</td></tr> <tr><td>1/4</td><td>S36</td></tr> </table> </div> <p>2003</p>	T13S	R63E	1/4	S36		
T13S	R63E						
1/4	S36						
77.00	Base of hill; continue over rolling hills.						
79.984	<p>Point for the cor. of secs. 1, 2, 35, and 36, at proportionate dist.; there is no remaining evidence of the original corner. This corner will now refer to cor. of secs. 35 and 36 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p>						

010

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div style="text-align: center;"> <u>T13S R63E</u> <u>S35 S36</u> 2003 </div>
39.992	<hr/> <p>N. 89°15'20" W., on the S. bdy. of sec. 35.</p> <p>Over rolling hills.</p> <p>Point for the 1/4 sec. cor. of secs. 2 and 35, at proportionate dist.; there is no remaining evidence of the original corner. This corner will now refer to the 1/4 sec. cor. of sec. 35 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <u>T13S R63E</u> <u>1/4 S35</u> 2003 </div>
79.984	<p>Point for the cor. of secs. 2, 3, 34 and 35, at proportionate dist.; there is no remaining evidence of the original corner. This corner will now refer to the cor. of secs. 34 and 35 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <u>T13S R63E</u> <u>S34 S35</u> 2003 </div> <hr/> <p>N. 89°15'20" W., on the S. bdy. of sec. 34.</p> <p>Over nearly level land.</p>
4.00	Over rolling hills.
36.00	Begin ascent over NE. slope.
39.992	<p>The 1/4 sec. cor. of secs. 3 and 34, monumented with a limestone, 10x6x4 ins., loosely set, mkd. 1/4 on one side, with a mound of stone, 2 ft. diam., 8 ins. high, E. of cor. This corner will now refer to the 1/4 sec. cor. of sec. 34 only.</p>

011

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T13S R63E 1/4 S34</p> <p style="text-align: center;">2003</p> <p>Deposit the original monument alongside the stainless steel post.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF THE EAST BOUNDARY, T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of the Survey Executed by C.F. Putnam in 1881</p> <hr/> <p>From the cor. of Tps. 13 S., Rs. 63 and 64 E., hereinbefore described.</p> <p>N. 0°03'30" E., bet. secs. 31 and 36.</p> <p>Descend over N. slope.</p> <p>6.80 Bottom of descent; continue over nearly level land.</p> <p>24.00 Pahrnagat Wash, drains S. 30° E.; continue over nearly level land.</p> <p>26.10 Dirt road, 15 lks. wide, bears N. 80° E. and S. 80° W.</p> <p>29.00 Begin ascent over rolling hills.</p> <p>40.075 Point for the 1/4 sec. cor. of secs. 31 and 36, at proportionate dist.; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T13S 1/4 R63E R64E S36 S31</p> <p style="text-align: center;">2003</p>
--------	--

012

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS									
64.50	Spur, slopes N. 45° W., desc. over NE. slope.								
80.150	<p>The cor. of secs. 25, 30, 31, and 36, perpetuated by Timothy J. Wolf, Nevada Professional Land Surveyor No. 9677, in 2003, from original evidence no longer in existence, as recorded in Clark County Corner Record, Book No. 20031212, Instrument No. 01220, monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, in a mound of stone, 3 ft. diam., 1 ft. high, with an aluminum cap mkd. LVVWD R63E S25 S36 T13S 2002 PLS 9677. This is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <table> <tr><td colspan="2">T13S</td></tr> <tr><td>R63E</td><td>R64E</td></tr> <tr><td>S25</td><td>S30</td></tr> <tr><td>S36</td><td>S31</td></tr> </table> <p>2003</p> <p>Deposit the rebar inside of the stainless steel post.</p> <hr/> <p>N. 0°10'00" E., on the E. bdy. of sec. 25.</p> <p>Ascend over SE. slope.</p>	T13S		R63E	R64E	S25	S30	S36	S31
T13S									
R63E	R64E								
S25	S30								
S36	S31								
3.00	Spur, slopes E.; asc. along E. slope.								
5.90	Spur, slopes E.; desc. over NE. slope.								
9.30	Gulch; drains S. 45° W., asc. over SE. slope.								
15.40	Spur, slopes S. 45° W., desc over NW. slope.								
21.30	Gulch, drains S. 45° W., desc. over NW. slope.								
29.50	Spur, slopes W., desc. over NW. slope.								
39.926	The 1/4 sec. cor. of sec. 30 only, T. 13 S., R. 64 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of the subdivisional lines of T. 13 S., R 64 E., executed concurrently under this same group.								

013

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.262	<p>The 1/4 sec. cor. of secs. 25 and 30, determined by Guy Doty, Nevada Professional Land Surveyor No. 7635, in 1995, as recorded in Clark County Record of Survey, File No. 78, Page No. 46, monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, in a mound of stone, 3 ft. diam., 1 ft. high., with aluminum cap mkd. R GUY DOTY PLS 7635. This is accepted as the best available evidence of the position of the original corner. This corner will now refer to the 1/4 sec. cor. of sec. 25 only.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13S R63E R64E 1/4 S25 </p> <p>2003</p> </div> <p>Deposit the rebar inside of the stainless steel post.</p> <hr/> <p>N. 0°01'20" W., beginning new measurement.</p> <p>Over rolling land.</p>
3.10	Gulch, drains S. 30° W., asc. over SE slope.
15.30	Power line, bears N. 80° E. and S. 80° W.
16.453	Point for a witness point and intersection with the centerline of Nevada State Route No. 168, hereinafter described.
28.10	Spur, slopes S. 40° W., desc. over NW. slope.
39.591	<p>The closing cor. of secs. 19 and 30, T. 13 S., R. 64 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, in a mound of stone, 3 ft. base, to top, with brass cap mkd. as described in the field notes of the survey of the subdivisional lines of T. 13 S., R. 64 E., executed concurrently under this same group.</p>
40.089	<p>Point for the cor. of secs. 19, 24, 25, and 30, at proportionate dist.; there is no remaining evidence of the original corner. This corner will now refer to the cor. of secs. 24 and 25 only.</p>

014

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13S R63E R64E S24 S25 2003</p> </div> <p>The corner falls in a gulch drains W.</p> <hr/> <p>N. 0°01'20" W., on the E. bdy. of sec. 24.</p> <p>Ascend over S. slope.</p> <p>6.60 Spur, slopes W., desc. over NW. slope.</p> <p>10.10 Gulch, drains S. 60° W., asc. over SE. slope.</p> <p>11.30 Ridge, bears N. 60° E. and S. 60° W.; desc. over NW. slope.</p> <p>18.50 Gulch; drains N. 70° W., asc. over SW. slope.</p> <p>29.20 Ridge, bears E. and W., desc. over NW. slope.</p> <p>32.30 Gulch, drains W.; asc. over S. slope.</p> <p>39.501 The 1/4 sec. cor. of sec. 19 only, T. 13 S., R. 64 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, in a mound of stone, 3 ft. base, to top, with brass cap mkd. as described in the field notes of the survey of the subdivisional lines of T. 13 S., R. 64 E., executed concurrently under this same group.</p> <p>40.089 The 1/4 sec. cor. of secs. 19 and 24, determined by Guy Doty, Nevada Professional Land Surveyor No. 7635, in 1995, as recorded in Clark County Record of Survey, File No. 78, Page No. 46, monumented with a rebar, 5/8 in. diam., loosely set, projecting 9 ins. above the ground, in a mound of stone, 3 ft. diam., 1 ft. high., with an aluminum cap mkd. R GUY DOTY PLS 7635. This is accepted as the best available evidence of the position of the original corner. This corner will now refer to the 1/4 sec. cor. of sec. 24 only.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>
--------	---

015

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div style="text-align: center;"> T13S R63E R64E 1/4 S24 2003 </div> <p>Deposit the rebar inside of the stainless steel post.</p> <p>The corner is at top of ridge bears E. and W.</p> <hr/> <p>N. 0°16'10" W., beginning new measurement.</p> <p>Descend over NW. slope.</p> <p>6.40 Gulch, drains S. 70° W., asc. over SW. slope.</p> <p>19.412 The N 1/16 sec. cor. of sec. 19 only, T. 13 S., R. 64 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of the subdivisional lines of T. 13 S., R. 64 E., executed concurrently under this same group.</p> <p>39.412 The closing cor. of secs. 18 and 19, T. 13 S., R. 64 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, in a mound of stone, 4 ft. base, to top, with brass cap mkd. as described in the field notes of the survey of the subdivisional lines of T. 13 S., R. 64 E., executed concurrently under this same group.</p> <p>40.037 The cor. of secs. 13, 18, 19, and 24, perpetuated by Bruce R. Scott, Nevada Professional Land Surveyor No. 3579, not recorded, monumented with a rebar, 5/8 in. diam., with a metal tag mkd. BRS LS 3579, firmly set, alongside of which is laying a lava stone 10x10x5 ins. (Record, limestone, 12x8x3 ins.), mkd. with 3 notches on the S. face, in a mound of stone, 4 ft. diam., 1 ft. high. This corner will now refer to the cor. of secs. 13 and 24 only.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground to solid rock, over a plastic-encased magnet, in a mound of stone, 4 ft. base, 2 ft. high, with brass cap mkd.</p> <div style="text-align: center;"> T13S R63E R64E S13 <hr/> S24 2003 </div>
--------	---

016

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Deposit the rebar inside and the original monument alongside the stainless steel post.</p> <hr/> <p>N. 0°44'40" W., on the E. bdy. of sec. 13.</p> <p>Descend over NW. slope.</p> <p>9.80 Gulch, drains N. 70° W.; asc. over SW. slope.</p> <p>11.90 Top of ascent, slopes W.; desc. over N. slope.</p> <p>34.60 Gulch, drains S. 40° W.; asc. over S. slope.</p> <p>39.379 The 1/4 sec. cor. of sec. 18 only, T. 13 S., R. 64 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, in a mound of stone, 4 ft. base, to top, with brass cap mkd. as described in the field notes of the survey of the subdivisional lines of T. 13 S., R. 64 E., executed concurrently under this same group.</p> <p>39.796 The 1/4 sec. cor. of secs. 13 and 18, monumented with a cement stone, 9x8x6 ins. (Record, 14x10x6 ins.), mkd. 1/4 on one face, firmly set, in a collar of stone. This corner will now refer to the 1/4 sec. cor. of sec. 13 only.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, 1 ft. high, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13S R63E R64E 1/4 S13 </p> <p>2003</p> </div> <p>Deposit the original monument alongside the stainless steel post.</p> <hr/> <p>N. 0°28'10" E., beginning new measurement.</p> <p>Ascend over S. slope.</p> <p>1.10 Top of ridge, bears E. and W.; desc. over N. slope.</p> <p>13.30 Gulch, drains N. 75° W., asc. over SW. slope.</p> <p>16.40 Top of ascent, slopes W.; desc. over N. slope.</p> <p>25.50 Gulch, drains W.; asc. over S. slope.</p> <p>38.00 Top of ascent, slopes W.; desc. over N. slope.</p>
--------	---

017

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.584	The closing cor. of secs. 7 and 18, T. 13 S., R. 64 E., monumented with a stainless steel post, 2 1/2 ins. diam., projecting 8 ins. above the ground and in a collar of stone, with brass cap mkd. as described in the field notes of the survey of the subdivisional lines of T. 13 S., R. 64 E., executed concurrently under this same group.
40.104	<p>Point for the cor. of secs. 7, 12, 13, and 18, at proportionate dist.; there is no remaining evidence of the original corner. This corner will now refer to the cor. of secs. 12 and 13 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 17 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13S R63E R64E S12 S13 2003</p> </div> <p>The corner falls in gulch, drains N. 50° W.</p> <hr/> <p>N. 0°28'10" E., on the E. bdy. of sec. 12.</p> <p>Ascend over S. slope.</p>
7.50	Spur, slopes S. 80° W.; desc. over N. slope.
9.50	Gulch, drains S. 30° W.; asc. over SE. slope.
15.00	Top of ascent, slopes W.; desc. over N. slope.
34.10	Gulch, drains N. 60° W., asc. over SW. slope.
39.479	The 1/4 sec. cor. of sec. 7 only, T. 13 S., R. 64 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground and in a collar of stone with brass cap mkd. as described in the field notes of the survey of the subdivisional lines of T. 13 S., R. 64 E., executed concurrently under this same group.
40.104	The 1/4 sec. cor. of secs. 7 and 12, monumented with a lava stone, 15x7x4 ins., (Record, limestone, 14x10x9 ins.) mkd. 1/4 on one face, in a mound of stone, 2 1/2 ft. diam., 2 ft. high. This corner will now refer to the 1/4 sec. cor. of sec. 12 only.

018

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 9 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13S R63E R64E 1/4 S12</p> <p>2003</p> </div> <p>Deposit the original corner monument alongside the stainless steel post.</p> <hr/> <p>N. 0°39'20" W., beginning new measurement.</p> <p>Over nearly level land.</p> <p>22.70 Gulch drains W.; asc. over S. slope.</p> <p>39.375 The closing cor. of secs. 6 and 7, T. 13 S., R. 64 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of the subdivisional lines of T. 13 S., R. 64 E., executed concurrently under this same group.</p> <p>40.272 The cor. of secs. 1, 6, 7, and 12, perpetuated by Bruce R. Scott, Professional Land Surveyor No. 3579, not recorded, monumented with a rebar, 5/8 in. diam., firmly set, with a metal tag mkd. BRS LS 3579, alongside of which is laying a cement stone, 12x6x5 ins. (Record, limestone, 10x8x4 ins.), mkd. with 5 notches on the S. face and 1 notch on the N. face, in a mound of stone, 3 ft. diam., 1 ft. high. This corner will now refer to the cor. of secs. 1 and 12 only.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 9 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13S R63E R64E S 1 S12</p> <p>2003</p> </div> <p>Deposit the rebar inside and the original monument alongside the stainless steel post.</p> <hr/>
--------	---

019

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>N. 0°46'00" W., on the E. bdy. of sec. 1.</p> <p>Over nearly level land.</p>
6.70	Gulch, drains S. 75° W., asc. over SW. slope.
39.107	The 1/4 sec. cor. of sec. 6 only, T. 13 S., R. 64 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above the ground and in a collar of stone, with brass cap mkd. as described in the field notes of the survey of the subdivisional lines of T. 13 S., R. 64 E., executed concurrently under this same group.
40.064	<p>The 1/4 sec. cor. of secs. 1 and 6, perpetuated by Bruce R. Scott, Nevada Professional Land Surveyor No. 3579, not recorded, monumented with a rebar, 5/8 in. diam., firmly set, with a metal tag mkd. BRS LS 3579, alongside of which is laying a cement stone 16x12x3 ins., (Record, limestone, 14x11x4 ins.), mkd. 1/4 on one face, in a mound of stone, 4 ft. diam., 1 ft. high. This corner will now refer to the 1/4 sec. cor. of sec. 1 only.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13S R63E R64E 1/4 S 1 </p> <p>2003</p> </div> <p>Deposit the rebar and the original monument alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 1°39'10" W., beginning new measurement.</p> <p>Over nearly level land.</p>
31.477	Nevada State Route No. 7, asphalt surfaced, 45 lks. wide, bears N. 20° W. and S. 20° E.
37.175	Point for a witness point and intersection with a line parallel to and 100 ft. easterly of centerline of Nevada State Route No. 7, hereinafter described.

020

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

40.929

Intersect the Third Standard Parallel South.

Point for the closing cor. of Tps. 13 S., Rs. 63 and 64 E.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
18 ins. in the ground, over a plastic-encased magnet, and in a
mound of stone, 3 ft. base, to top, with brass cap mkd.

T12S R63E

S36

S 1	S 6
R63E	R64E

T13S

CC

2003

From this cor., the original closing cor. of Tps. 13 S.,
Rs. 63 and 64 E., determined by person(s) unknown, bears
N. 1°39'10" W., 0.191 chs. dist., monumented with an iron shaft
and gear, 1 in. diam., firmly set, projecting 10 ins. above the
ground, with top of gear mkd. CC 1-6, with a mound of stone, 3
ft. diam., 1 ft. high, S. of the cor. This is accepted as the
best available evidence of the position of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
22 ins. in the ground, over a plastic-encased magnet, 3 ft.
diam., in a collar of stone, with brass cap mkd.

AM

2003

Deposit the iron shaft and gear alongside the stainless steel
post.

The corner is located 16 lks. N. of fence line, bears E. and W.

From this same cor. the standard cor. of Tps. 12 S., Rs. 63 and
64 E., bears N. 89°55'50" E., 17.091 chs. dist.

021

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Reestablishment of the Survey Executed by C.F. Putnam and W.F. Benson in 1881</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 35 and 36, monumented with a lava stone, (Record, limestone), 16x10x8 ins., firmly set, projecting 8 ins. above the ground, mkd. 1/4 on W. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T13S R63E 1/4 S35 S36 2003</p> <p>Deposit the original monument alongside the stainless steel post.</p> <p>N. 0°42'10" W., bet. secs. 35 and 36.</p> <p>Over nearly level land.</p>
34.50	Begin descent over NW. slope.
40.039	<p>Point for the cor. of secs. 25, 26, 35, and 36, at proportionate dist.; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T13S R63E S26 S25 <hr/>S35 S36 2003</p> <hr/>
	<p>From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°18'40" W., bet. secs. 25 and 36.</p>
37.60	Jeep trail, 12 lks. wide, bears NW. and SE.
38.00	Pahranagat Wash, drains SE.

022

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.584	<p>The 1/4 sec. cor. of secs. 25 and 36, monumented with a lime-stone, 15x10x4 ins. (Record, 10x8x6 ins.), mkd. 1/4 on one face, firmly set, projecting 2 ins. above the ground, and in a mound of stone, 2 ft. diam., 8 ins. high.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13S R63E S25 1/4 <u> </u> S36</p> <p>2003</p> </div> <p>Deposit the original monument alongside the stainless steel post.</p>
	N. 86°41'30" W., beginning new measurement.
0.50	Begin ascent over E. slope.
7.00	Top of ridge, bears NW. and SE.; desc. over rolling hills.
40.480	The cor. of secs. 25, 26, 35, and 36.
	N. 0°27'40" E., bet. secs. 25 and 26.
	Descend over NW. slope.
35.50	Spur, slopes W.; desc. over NW. slope.
40.038	<p>The 1/4 sec. cor. of secs. 25 and 26, perpetuated by Timothy J. Wolf, Nevada Professional Land Surveyor No. 9677, in 2002, from original evidence no longer in existence, as recorded in Clark County Corner Record, Book No. 20040511, Instrument No. 01721, monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, in a collar of stone, with an aluminum cap mkd. LVVWD 1/4 S25 S26 PLS 9677 2002. This is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>

023DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>T13S R63E 1/4 S26 S25 2003</p> <p>Deposit the rebar inside of the stainless steel post.</p> <hr/> <p>N. 0°28'50" W., beginning new measurement.</p>
23.80	Bottom of descent; continue over nearly level land.
25.60	Gulch, drains NW.
31.732	Point for a witness point and intersection with the centerline of Nevada State Route No. 168, hereinafter described.
39.253	<p>Point for the cor. of secs. 23, 24, 25, and 26, at proportionate dist.; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <p>T13S R63E S23 S24 S26 S25 2003</p> <hr/> <p>From the cor. of secs. 24 and 25 only, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 88°45'00" W., bet. secs. 24 and 25.</p> <p>Over nearly level land.</p>
20.027	<p>Point for the E 1/16 sec. cor. of secs. 24 and 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p>E 1/16 $\frac{S24}{S25}$ 2003</p>
40.054	Point for the 1/4 sec. cor. of secs. 24 and 25, at proportionate dist.; there is no remaining evidence of the original corner.

024

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> T13S R63E S24 1/4 <u> </u> S25 </div> <p style="text-align: center;">2003</p>
80.108	<p>The cor. of secs. 23, 24, 25, and 26.</p> <hr/> <p>N. 0°24'00" E., bet. secs. 23 and 24.</p>
39.252	<p>Point for the 1/4 sec. cor. of secs. 23 and 24, at proportionate dist.; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> T13S R63E 1/4 S23 S24 </div> <p style="text-align: center;">2003</p>
75.00	<p>Begin ascent over SW. slope.</p>
78.504	<p>The cor. of secs. 13, 14, 23, and 24, perpetuated by Sam Long, Professional Land Surveyor No. 9047, in 2000, as recorded in Clark County Corner Record, Book No. 20000321, Instrument No. 01049, monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, alongside of which is a sandstone, 10x6x4 ins. (Record, 16x14x9 ins.), mkd. with 3 notches on the S. face and 1 notch on E. face, with an aluminum cap mkd. VTN PLS 9047.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> T13S R63E S14 S13 S23 S24 </div> <p style="text-align: center;">2003</p> <p>Deposit the rebar inside and the original monument alongside the stainless steel post.</p> <hr/>

025

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the cor. of secs. 1 and 12 only, on the E. bdy. of Tp., hereinbefore described.</p> <p>S. 89°48'00" W., bet. secs. 1 and 12.</p>
29.564	<p>Point for the W-E 1/64 sec. cor. of secs. 1 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>S 1 W-E 1/64 S12</p> <p>2003</p> </div>
39.419	<p>Point for the 1/4 sec. cor. of secs. 1 and 12, at proportionate dist.; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13S R63E S 1 1/4 <u> </u> S12</p> <p>2003</p> </div>
50.80	Gulch, drains SW.; asc. over E. slope.
59.10	Top of hill; desc. over SW.
78.838	<p>The cor. of secs. 1, 2, 11, and 12, monumented with a mound of stone, 3 1/2 ft. diam., 1 1/2 ft. high. This is accepted as the best available evidence of the position of original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13S R63E S 2 S 1 <u> </u> S11 S12</p> <p>2003</p> </div> <hr/>

026

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>N. 0°23'00" E., bet. secs. 1 and 2.</p> <p>Ascend over SW. slope.</p>
18.80	Top of ascent; continue over nearly level land.
39.687	<p>The 1/4 sec. cor. of secs. 1 and 2, monumented with a lava stone, 16x14x8 ins., no marks visible, firmly set, projecting 6 ins. above the ground, in a mound of stone, 2 1/2 ft. diam., 1 ft. high.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T13S R63E 1/4 S 2 S 1 2003</p> <p>Deposit the original monument alongside the stainless steel post.</p> <hr/> <p>N. 0°07'40" W., beginning new measurement.</p> <p>Over nearly level land.</p>
41.426	<p>The original closing cor. of secs. 1 and 2, monumented with a limestone, 9x8x6 ins., no marks visible, firmly set, projecting 8 ins. above the ground, in a mound of stone, 2 ft. diam., 1 ft. high.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">AM 2003</p> <p>Deposit the original monument alongside the stainless steel post.</p>
41.545	Intersect the Third Standard Parallel South.

027

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

Point for the closing cor. of secs. 1 and 2.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
26 ins. in the ground, over a plastic-encased magnet, and in a
mound of stone, 3 ft. base, to top, with brass cap mkd.

T12S R63E
S35

S 2	S 1
T13S	R63E
CC	

2003

From this cor., the standard cor. of secs. 35 and 36, T. 12 S.,
R. 63 E., bears S. 89°52'20" E., 14.278 chs. dist.,
hereinbefore described.

The point for the 1/4 sec. cor. of sec. 1 only, on the N. bdy.
of the Tp., is at midpoint in departure on the N. bdy. of
sec. 1.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, over a plastic-encased magnet, with
brass cap mkd.

T12S R63E
1/4 S 1
T13S R63E

2003

From this cor., the standard 1/4 sec. cor. of sec. 36,
T. 12 S., R. 63 E., bears N. 89°58'10" E., 15.932 chs. dist.,
hereinbefore described.

The point for the W-E 1/64 sec. cor. of sec. 1 only, on the
N. bdy. of the Tp., is at proportionate dist. in departure on
the N. bdy. of sec. 1.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, over a plastic-encased magnet, and in a
mound of stone, 3 ft. base, to top, with brass cap mkd.

W-E 1/64
S 1

2003

From this cor., the standard 1/4 sec. cor. of sec. 36, bears
N. 89°58'10" E., 6.316 chs. dist., hereinbefore described.

028

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the cor. of secs. 34 and 35, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°00'10" W., bet. secs. 34 and 35.</p> <p>Over nearly level land.</p>
15.10	Begin ascent over rolling hills.
22.80	Top of ascent; desc. over N. slope.
30.70	Gulch, drains E.; asc. over S. slope.
38.859	<p>Point for the 1/4 sec. cor. of secs. 34 and 35, at proportionate dist.; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T13S R63E 1/4 S34 S35 2003</p> <p>Ascend over S. slope.</p>
64.50	Top of ascent; continue over rolling hills.
68.70	Bottom of descent; continue over nearly level land.
70.70	Begin ascent over rolling hills.
77.718	<p>Point for the cor. of secs. 26, 27, 34, and 35, at proportionate dist.; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T13S R63E S27 S26 S34 S35 2003</p> <hr/> <p>From the cor. of secs. 25, 26, 35, and 36.</p> <p>S. 87°44'10" W., bet. secs. 26 and 35.</p>

029

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Descend over W. slope.
3.50	Gulch, drains North; asc. over E. slope.
4.00	Top of ascent; continue over rolling hills.
40.039	Point for the 1/4 sec. cor. of secs. 26 and 35, at proportionate dist.; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd. <div style="text-align: center;"> T13S R63E S26 1/4 $\frac{\quad}{\quad}$ S35 2003 </div> Over rolling hills.
60.00	Bottom of descent; continue over nearly level land.
70.00	Begin ascent over rolling hills.
80.078	The cor. of secs. 26, 27, 34, and 35. <hr/>
	N. 0°20'20" W., bet. secs. 26 and 27. Over rolling hills.
10.10	Top of hill; desc. over North slope.
14.70	Power lines, bears NE. and SW.
17.70	Bottom of desc.; continue over nearly level land.
19.70	Begin ascent over S. slope.
38.859	The 1/4 sec. cor. of secs. 26 and 27, determined by Sam Long, Professional Land Surveyor No. 9047, in 2000, as recorded in Clark County Corner Record, Book No. 20000321, Instrument No. 01049, monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, in a mound of stone, 2 ft. diam., 8 ins. high, with an aluminum cap mkd. VTN PLS 9047. This is accepted as the best available evidence of the position of the original corner. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

030

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>T13S R63E 1/4 S27 S26 2003</p> <p>Deposit the rebar inside of the stainless steel post.</p> <hr/> <p>N. 0°15'10" E., beginning new measurement.</p> <p>Over nearly level land.</p>
40.074	<p>The cor. of secs. 22, 23, 26, and 27, perpetuated by Timothy J. Wolf, Professional Land Surveyor No. 9677, in 2000, as recorded in Clark County Corner Record, Book No. 20000310, Instrument No. 01511, monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, alongside of which is laying a sandstone, (Record, limestone), 12x6x4 ins., with 2 notches on each of two adjacent edges, with an aluminum cap mkd. LVVWD S22 23S 26S S27 1998 PLS 9677.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <p>T13S R63E S22 S23 S27 S26 2003</p> <p>Deposit the rebar inside and the original monument alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 23, 24, 25, and 26.</p> <p>S. 86°18'20" W., bet. secs. 23 and 26.</p> <p>Over nearly level land.</p>
2.50	Jeep trail, 12 lks. wide, bears N. 50° W. and S. 50° E.
8.10	Begin ascent over NE. slope.
14.675	Point for a witness point and intersection with curve of the centerline of Nevada State Route No. 168, hereinafter described.
19.40	Top of ascent; desc. over W. slope.

031

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
21.70	Bottom of descent; continue over nearly level land.
31.20	Begin ascent over E. slope.
32.00	Top of ascent; desc. over W. slope.
39.882	<p>The 1/4 sec. cor. of secs. 23 and 26, perpetuated by Timothy J. Wolf, Professional Land Surveyor No. 9677, in 2000, from original evidence no longer in existence, as recorded in Clark County Corner Record, Book No. 20000310, Instrument No. 01511, monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, with an aluminum cap mkd. LVVWD S23 1/4 S26 1998 PLS 9677. This is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13S R63E S23 1/4 — S26</p> <p>2003</p> </div> <p>Deposit the rebar inside of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 88°38'50" W., beginning new measurement.</p> <p>Ascend over E. slope.</p>
8.60	Top of ascent; continue over nearly level land.
40.255	<p>The cor. of secs. 22, 23, 26, and 27.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>N. 0°03'30" E., bet. secs. 22 and 23.</p>
7.20	Top of ascent; desc. over N. slope.
10.260	Point for a witness point and intersection with the centerline of Nevada State Route No. 168, hereinafter described.
17.00	Bottom of descent; continue over nearly level land.
30.50	Leave flat.

032

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.446	<p>The 1/4 sec. cor. of secs. 22 and 23, perpetuated by Sam Long, Professional Land Surveyor No. 9047, in 2000, as recorded in Clark County Corner Record, Book No. 20000321, Instrument No. 01049, monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, with aluminum cap mkd. VTN PLS 9047, alongside of which is laying a lava stone, 15x10x9 ins.(Record, limestone, 9x7x6 ins.), mkd. 1/4 on one face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13S R63E 1/4 S22 S23</p> <p>2003</p> </div> <p>Deposit the rebar inside and the original monument alongside the stainless steel post.</p> <hr/> <p>N. 0°34'50" W., beginning new measurement.</p>
40.059	<p>The cor. of secs. 14, 15, 22, and 23, perpetuated by Timothy J. Wolf, Professional Land Surveyor No. 9677, in 2000, from original evidence no longer in existence, as recorded in Clark County Corner Record, Book No. 20000310, Instrument No. 01511, monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, with an aluminum cap mkd. S14 155 S22 23S 1998 PLS 9677. This is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13S R63E S15 S14 <hr/>S22 S23</p> <p>2003</p> </div> <p>Deposit the rebar inside of the stainless steel post.</p> <hr/>

033

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the cor. of secs. 13, 14, 23, and 24.</p> <p>S. 88°55'30" W., bet. secs. 14 and 23.</p>
38.10	Gulch, drains S.
40.478	<p>Point for the 1/4 sec. cor. of secs. 14 and 23, at proportionate dist.; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13S R63E</p> <p>S14</p> <p>1/4 <u> </u></p> <p>S23</p> <p>2003</p> </div>
51.90	Jeep trail, 12 lks. wide, bears N. 20° W. and S. 20° E.
54.20	Spur, slopes SE.
80.956	The cor. of secs. 14, 15, 22, and 23.
	<hr/> <p>From the cor. of secs. 26, 27, 34, and 35.</p> <p>N. 87°55'00" W., bet. secs. 27 and 34.</p> <p>Over nearly level land.</p>
23.20	Power lines, bears N. 70° E. and S. 70° W.
40.220	<p>Point for the 1/4 sec. cor. of secs. 27 and 34, at proportionate dist.; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13S R63E</p> <p>S27</p> <p>1/4 <u> </u></p> <p>S34</p> <p>2003</p> </div>
80.440	The cor. of secs. 27, 28, 33, and 34, monumented with a sandstone, 12x8x6 ins., firmly set, projecting 8 ins. above the ground, in a mound of stone, 3 ft. diam., 1 ft. high, mkd. with 1 notch on the S. edge and 3 notches on the E. edge.

034

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td>T13S</td><td>R63E</td></tr> <tr><td>S28</td><td>S27</td></tr> <tr><td>S33</td><td>S34</td></tr> </table> <p>2003</p> </div> <p>Deposit the original monument alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 22, 23, 26, and 27.</p> <p>N. 87°18'10" W., bet. secs. 22 and 27.</p> <p>40.207 Point for the 1/4 sec. cor. of secs. 22 and 27, at proportionate dist.; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td>T13S</td><td>R63E</td></tr> <tr><td>1/4</td><td>S22</td></tr> <tr><td></td><td>S27</td></tr> </table> <p>2003</p> </div> <p>80.414 The cor. of secs. 21, 22, 27, and 28, perpetuated by Sam Long, Professional Land Surveyor No. 9047, in 2000, as recorded in Clark County Corner Record, Book No. 20000321, Instrument No. 01049, monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, with aluminum cap mkd. VTN PLS 9047, alongside of which is laying a cement stone, 9x6x4 ins. (Record, 11x8x6 ins.), dimly mkd. with 3 notches on one edge.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td>T13S</td><td>R63E</td></tr> <tr><td>S21</td><td>S22</td></tr> <tr><td>S28</td><td>S27</td></tr> </table> <p>2003</p> </div>	T13S	R63E	S28	S27	S33	S34	T13S	R63E	1/4	S22		S27	T13S	R63E	S21	S22	S28	S27
T13S	R63E																		
S28	S27																		
S33	S34																		
T13S	R63E																		
1/4	S22																		
	S27																		
T13S	R63E																		
S21	S22																		
S28	S27																		

035

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Deposit the rebar inside and the original monument alongside the stainless steel post.</p> <hr/> <p>N. 0°38'30" W., bet. secs. 21 and 22.</p> <p>Over nearly level land.</p> <p>13.531 Point for a witness point and intersection with the centerline of Nevada State Route No. 168, hereinafter described.</p> <p>39.892 The 1/4 sec. cor. of sec. 21 and 22, perpetuated by Sam Long, Professional Land Surveyor No. 9047, in 2000, as recorded in Clark County Corner Record, Book No. 20000321, Instrument No. 01049, monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, with an aluminum cap mkd. VTN PLS 9047, alongside of which is laying a cement stone, 13x9x6 ins. (Record, 9x6x4 ins.), mkd. 1/4 on one face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> T13S R63E 1/4 S21 S22 2003 </div> <p>Deposit the rebar inside and the original monument alongside the stainless steel post.</p> <hr/> <p>N. 0°23'00" W., beginning new measurement.</p> <p>39.849 The cor. of secs. 15, 16, 21, and 22 monumented with a cement stone, 14x8x6 ins., mkd. X on top, alongside of which is a wooden hub, 2x2 ins. square, in a mound of stone, 3 ft. diam., 1 ft. high.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> T13S R63E S16 S15 <hr/> S21 S22 2003 </div>
--------	---

036

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Deposit the wooden hub inside and the original monument alongside the stainless steel post.
	<hr/> <p>From the cor. of secs. 14, 15, 22, and 23.</p> <p>N. 87°51'30" W., bet. secs. 15 and 22.</p> <p>Over nearly level land.</p>
40.357	<p>Point for the 1/4 cor. of sec. 15 and 22, at proportionate dist.; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13S R63E</p> <p>S15</p> <p>1/4 <u> </u></p> <p>S22</p> <p>2003</p> </div>
52.10	Gulch, drains SE.; continue over nearly level land.
80.714	The cor. of secs. 15, 16, 21, and 22.
	<hr/> <p>From the cor. of secs. 21, 22, 27, and 28.</p> <p>N. 89°47'00" W., bet. secs. 21 and 28.</p> <p>Over nearly level land.</p>
40.428	<p>Point for the 1/4 sec. cor. of secs. 21 and 28, at proportionate dist.; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13S R63E</p> <p>S21</p> <p>1/4 <u> </u></p> <p>S28</p> <p>2003</p> </div>
80.856	<p>The cor. of secs. 20, 21, 28, and 29, determined by Joseph Fielding, Professional Land Surveyor No. 6199, in 1989, as recorded in Clark County Record of Survey, File No. 53, Page No. 23, monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, in a mound of stone, 2 ft. diam., 1 ft. high, with aluminum cap mkd. NEVADA POWER CO PLS 6199. The position of this corner is substantiated by a bearing and distance tie made by the Nevada Department of</p>

037

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Transportation from U.S. Highway No. 93 to the corner as shown on State of Nevada right-of-way application Nev-060729, dated 1963. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, encircled with collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td>T13S</td><td>R63E</td></tr> <tr><td>S20</td><td>S21</td></tr> <tr><td>S29</td><td>S28</td></tr> </table> <p>2003</p> </div> <p>Deposit the rebar inside of the stainless steel post.</p> <hr/> <p>N. 0°30'00" W., bet. secs. 20 and 21.</p> <p>Over nearly level land.</p> <p>20.299 Point for a witness point and intersection with the centerline of Nevada State Route No. 168, hereinafter described.</p> <p>39.824 The 1/4 sec. cor. of secs. 20 and 21, determined by Timothy J. Wolf, Professional Land Surveyor No. 9677, in 2003, as recorded in Clark County Corner Record, Book No. 20031212, Instrument No. 01221, monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, in a mound of stone, 3 ft. diam., 1 ft. high, with aluminum cap mkd. LVVWD 1/4 S20 S21 2002 PLS 9677. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td>T13S</td><td>R63E</td></tr> <tr><td>1/4</td><td></td></tr> <tr><td>S20</td><td>S21</td></tr> </table> <p>2003</p> </div> <p>Deposit the rebar inside of the stainless steel post.</p> <hr/>	T13S	R63E	S20	S21	S29	S28	T13S	R63E	1/4		S20	S21
T13S	R63E												
S20	S21												
S29	S28												
T13S	R63E												
1/4													
S20	S21												

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°39'20" W., beginning new measurement.								
39.893	<p>The cor. of secs. 16, 17, 20, and 21, perpetuated by Timothy J. Wolf, Professional Land Surveyor No. 9677, in 2003, as recorded in Clark County Corner Record, Book No. 20031212, Instrument No. 01221, monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, in a mound of stone, 3 ft. diam., 8 ins. high, with aluminum cap mkd. LVVWD T13S R63E 16 17 20 21 2002 PLS 9677, alongside of which is laying a cement stone, 12x10x8 ins., no marks visible. The position of this corner is substantiated by a bearing and distance tie made by the Nevada Department of Transportation from U.S. Highway No. 93 to the corner as shown on the State of Nevada right-of-way application Nev-060729, dated 1963.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td>T13S</td><td>R63E</td></tr> <tr><td>S17</td><td>S16</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S20</td><td>S21</td></tr> </table> <p>2003</p> </div> <p>Deposit the rebar inside and the original monument alongside the stainless steel post.</p>	T13S	R63E	S17	S16	<hr/>		S20	S21
T13S	R63E								
S17	S16								
<hr/>									
S20	S21								
	<hr/> <p>From the cor. of secs. 15, 16, 21, and 22.</p> <p>N. 89°48'00" W., bet. secs. 16 and 21.</p> <p>Over nearly level land.</p>								
40.466	<p>Point for the 1/4 sec. cor. of secs. 16 and 21, at proportionate dist.; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td>T13S</td><td>R63E</td></tr> <tr><td></td><td>S16</td></tr> <tr><td>1/4</td><td><hr/></td></tr> <tr><td></td><td>S21</td></tr> </table> <p>2003</p> </div>	T13S	R63E		S16	1/4	<hr/>		S21
T13S	R63E								
	S16								
1/4	<hr/>								
	S21								
80.932	<hr/> <p>The cor. of secs. 16, 17, 20, and 21.</p> <hr/>								

039

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>N. 1°07'10" W., bet. secs. 16 and 17.</p> <p>Over nearly level land.</p> <p>39.811 The 1/4 sec. cor. of secs. 16 and 17, monumented with a cement stone, 12x10x10 ins. (Record, 9x8x6 ins.), no marks visible, in a mound of stone, 2 ft. diam., 1 ft. high.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13S R63E 1/4 S17 S16</p> <p>2003</p> </div> <p>Deposit the original monument alongside the stainless steel post.</p> <hr/> <p>N. 2°13'10" W., beginning new measurement.</p> <p>40.049 Point for the cor. of secs. 8, 9, 16, and 17, at proportionate dist.; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13S R63E S 8 S 9 S17 S16</p> <p>2003</p> </div> <hr/> <p>From the 1/4 sec. cor. of secs. 9 and 16, monumented with a mound of stone, 2 ft. diam., 6 ins. high, this position is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p>
--------	--

040

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div data-bbox="883 275 1029 369"> <p>T13N R63E S 9 1/4 <u> </u> S16</p> </div> <div data-bbox="924 396 987 422">2003</div> <div data-bbox="448 457 1040 483">S. 88°30'50" W., bet. secs. 9 and 16.</div> <div data-bbox="448 518 813 543">Over nearly level land.</div> <div data-bbox="302 579 1008 604">40.277 The cor. of secs. 8, 9, 16, and 17.</div> <hr/> <div data-bbox="448 667 1008 693">N. 1°10'00" E., bet. secs. 8 and 9.</div> <div data-bbox="448 728 813 753">Over nearly level land.</div> <div data-bbox="302 789 1442 873">40.027 The 1/4 sec. cor. of secs. 8 and 9, monumented with a cement stone, (Record, sandstone), 9x7x6 ins., no marks visible, in a mound of stone, 3 ft. diam., 1 ft. high.</div> <div data-bbox="448 909 751 934">At the corner point</div> <div data-bbox="448 970 1386 1054">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</div> <div data-bbox="883 1087 1029 1163"> <p>T13S R63E 1/4 S 8 S 9</p> </div> <div data-bbox="924 1190 987 1215">2003</div> <div data-bbox="448 1251 1386 1306">Deposit the original monument alongside the stainless steel post.</div> <hr/> <div data-bbox="448 1369 1114 1394">N. 0°02'20" E., beginning new measurement.</div> <div data-bbox="302 1430 1433 1545">39.740 The cor. of secs. 4, 5, 8, and 9, monumented with a limestone, 10x7x5 ins. (Record, cement stone, 11x9x7 ins.), no marks visible, loosely set, in a mound of stone, 2 ft. diam., 1 ft. high.</div> <div data-bbox="448 1581 751 1606">At the corner point</div> <div data-bbox="448 1642 1386 1726">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</div> <div data-bbox="883 1761 1029 1856"> <p>T13S R63E S 5 S 4 <u> </u> S 8 S 9</p> </div> <div data-bbox="924 1883 987 1908">2003</div>
--------	---

041

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Deposit the original monument alongside the stainless steel post.</p> <hr/> <p>N. 1°05'30" E., bet. secs. 4 and 5.</p> <p>Over nearly level land.</p>
39.641	<p>Point for the 1/4 sec. cor. of secs. 4 and 5, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13S R63E 1/4 S 5 S 4 2004</p> </div>
79.876	<p>Point for the closing cor. of secs. 4 and 5, on the Third Standard Parallel South, at proportionate dist., there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T12S R13E S32 S 5 S 4 T13S R63E CC 2004</p> </div> <p>From this cor., the standard cor. of secs. 32 and 33, T. 12 S., R. 63 E., bears S. 89°58'50" E., 15.980 chs. dist., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 20, 21, 28, and 29.</p> <p>N. 88°44'30" W., bet. secs. 20 and 29.</p> <p>Ascend over a gradual E. slope.</p>
1.40	<p>U.S. Highway No. 93, paved surface, bears N. 10° W. and S. 10° E.</p>
5.60	<p>Power lines, bears N. 10° W. and S. 10° E.</p>

042

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
41.292	<p>Point for the 1/4 sec. cor. of secs. 20 and 29, at proportionate dist.; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <div style="text-align: right;"> T13S R63E S20 1/4 ——— S29 2003 </div> <p>Ascend over gradual E. slope.</p>
82.584	<p>The cor. of secs. 19, 20, 29, and 30, monumented with a mound of stone, 2 1/2 ft. diam., 1 ft. high. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <div style="text-align: right;"> T13S R63E S19 S20 ——— S30 S29 2003 </div> <hr/> <p>N. 0°18'10" W., bet. secs. 19 and 20.</p> <p>Ascend along an E. slope.</p>
39.771	<p>The 1/4 sec. cor. of sec. 19 and 20, monumented with a cement stone 16x7x7 ins. (Record, 11x9x8 ins.), mkd. 1/4 on one face, in a mound of stone, 3 ft. diam., 1 ft. high.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <div style="text-align: right;"> T13S R63E 1/4 S19 S20 2003 </div>

043

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Deposit the original monument alongside the stainless steel post.</p> <hr/> <p>N. 0°07'30" E., beginning new measurement.</p>						
6.00	Top of ascent, slopes E.; desc. along E. slope.						
39.731	<p>The cor. of secs. 17, 18, 19, and 20, monumented with a cement stone, 16x9x4 ins. (Record, sandstone, 18x12x6 ins.), no marks visible, in a mound of stone, 3 ft. diam., 1 ft. high.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 17 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr> <td>T13S</td><td>R63E</td></tr> <tr> <td>S18</td><td>S17</td></tr> <tr> <td>S19</td><td>S20</td></tr> </table> <p>2003</p> </div> <p>Deposit the original monument alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 16, 17, 20, and 21.</p> <p>N. 87°30'50" W., bet. secs. 17 and 20.</p> <p>Ascend over gradual E. slope.</p>	T13S	R63E	S18	S17	S19	S20
T13S	R63E						
S18	S17						
S19	S20						
11.874	Point for a witness point and intersection with the centerline of U.S. Highway No. 93, hereinafter described.						
15.90	Power lines, bears N. 10° W. and S. 10° E.						
39.322	<p>The 1/4 sec. cor. of secs. 17 and 20, monumented with a cement stone, 16x14x11 ins. (Record, 16x13x7 ins.), in a collar of stone, mkd. 1/4 on one face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 17 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr> <td>T13S</td><td>R63E</td></tr> <tr> <td>1/4</td><td>S17</td></tr> <tr> <td></td><td>S20</td></tr> </table> <p>2003</p> </div>	T13S	R63E	1/4	S17		S20
T13S	R63E						
1/4	S17						
	S20						

044

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Deposit the original monument alongside the stainless steel post.</p> <hr/> <p>S. 89°51'40" W., beginning new measurement.</p> <p>Ascend over gradual E. slope.</p>
42.585	<p>The cor. of secs. 17, 18, 19, and 20.</p> <hr/> <p>N. 0°22'20" W., bet. secs. 17 and 18.</p> <p>Descend along E. slope.</p>
26.20	<p>Gulch course E.; asc. along E. slope.</p>
39.708	<p>The 1/4 sec. cor. of secs. 17 and 18, monumented with a lava stone, 16x11x5 ins. (Record, cement stone, 16x14x12 ins.), mkd. 1/4 on one face, in a mound of stone, 2 ft. diam., 10 ins. high.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T13S R63E 1/4 S18 S17 2003</p> <p>Deposit the original monument alongside the stainless steel post.</p> <hr/> <p>N. 0°26'10" E., beginning new measurement.</p> <p>Descend along E. slope.</p>
39.963	<p>The cor. of secs. 7, 8, 17, and 18, monumented with a cement stone, 11x9x4 ins. (Record, 17x14x13 ins.), mkd. with 5 notches on the E. edge, in a mound of stone, 2 ft. diam., 1 ft. high.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p>

045

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS													
	<div data-bbox="878 275 1024 369"> <table> <tr><td>T13S</td><td>R63E</td></tr> <tr><td>S 7</td><td>S 8</td></tr> <tr><td>S18</td><td>S17</td></tr> </table> </div> <div data-bbox="919 394 984 420">2003</div> <div data-bbox="444 451 1390 512">Deposit the original monument alongside the stainless steel post.</div> <hr/> <div data-bbox="444 573 1084 598">From the cor. of secs. 8, 9, 16, and 17.</div> <div data-bbox="444 632 1036 657">N. 87°28'50" W., bet. secs. 8 and 17.</div> <div data-bbox="444 690 924 716">Ascend along gradual E. slope.</div> <div data-bbox="298 751 1442 812">20.819 Point for a witness point and intersection with the centerline of U.S. Highway No. 93, hereinafter described.</div> <div data-bbox="298 842 1117 867">24.80 Power lines, bears N. 10° W. and S. 10° E.</div> <div data-bbox="298 900 1458 1108">40.348 The 1/4 sec. cor. of secs. 8 and 17, monumented with a lava stone, 18x6x4 ins., no marks visible, firmly set in a mound of stone, 2 ft. diam., 6 ins. high. The position of this corner is substantiated by a bearing and distance tie made by the Nevada Department of Transportation from U.S. Highway No. 93 to the corner as shown on State of Nevada right-of-way application Nev-060729, dated 1963.</div> <div data-bbox="444 1142 751 1167">At the corner point</div> <div data-bbox="444 1201 1390 1289">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</div> <div data-bbox="878 1320 1024 1415"> <table> <tr><td>T13S</td><td>R63E</td></tr> <tr><td>S 8</td><td></td></tr> <tr><td>1/4</td><td>S17</td></tr> </table> </div> <div data-bbox="919 1442 984 1467">2003</div> <div data-bbox="444 1499 1390 1560">Deposit the original monument alongside the stainless steel post.</div> <hr/> <div data-bbox="444 1621 1133 1646">S. 89°31'30" W., beginning new measurement.</div> <div data-bbox="298 1682 1003 1707">39.172 The cor. of secs. 7, 8, 17, and 18.</div> <hr/> <div data-bbox="444 1772 1003 1797">N. 0°51'00" E., bet. secs. 7 and 8.</div> <div data-bbox="444 1831 797 1856">Ascend along E. slope.</div>	T13S	R63E	S 7	S 8	S18	S17	T13S	R63E	S 8		1/4	S17
T13S	R63E												
S 7	S 8												
S18	S17												
T13S	R63E												
S 8													
1/4	S17												

046

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.828	<p>The 1/4 sec. cor. of secs. 7 and 8, monumented with a cement stone, 16x12x9 ins., no marks visible, in a mound of stone, 2 ft. diam., 1 ft. high.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13S R63E 1/4 S 7 S 8</p> <p>2003</p> </div> <p>Deposit the original monument alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°28'20" E., beginning new measurement.</p>
39.733	<p>The cor. of secs. 5, 6, 7, and 8, monumented with a cement stone, 14x11x5 ins., (Record, limestone, 18x16x12 ins.), no marks visible, firmly set, projecting 8 ins. above the ground, in a mound of stone, 2 1/2 ft. diam., 1 ft. high. This position is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13S R63E S 6 S 5 <hr style="width: 50%; margin: 0 auto;"/>S 7 S 8</p> <p>2003</p> </div> <p>Deposit the stone alongside the stainless steel post.</p> <hr style="width: 50%; margin: 10px auto;"/> <p>From the cor. of secs. 4, 5, 8, and 9.</p> <p>N. 87°59'50" W., bet. secs. 5 and 8.</p> <p>Ascend over gradual E. slope.</p>
32.894	<p>Point for a witness point and intersection with the centerline of U.S. Highway No. 93, hereinafter described.</p>

047

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
36.75	Power lines, bears N. 10° W. and S. 10° E.
42.203	<p>The 1/4 sec. cor. of secs. 5 and 8, monumented with a mound of stone, 2 ft. diam., 6 ins. high. The position of this corner is substantiated by a bearing and distance tie made by the Nevada Department of Transportation from U.S. Highway No. 93 to the corner as shown on the State of Nevada right-of-way application Nev-060729, dated 1963. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13S R63E</p> <p>S 5</p> <p>1/4 <u> </u></p> <p>S 8</p> <p>2003</p> <hr style="width: 30%; margin: 10px auto;"/> </div> <p>S. 89°38'40" W., beginning new measurement.</p>
37.211	<p>The cor. of secs. 5, 6, 7, and 8.</p> <hr style="width: 80%; margin: 10px auto;"/>
	<p>N. 0°30'30" E., bet. secs. 5 and 6.</p> <p>Ascend along gradual E. slope.</p>
39.783	<p>The 1/4 sec. cor. of secs. 5 and 6, monumented with a cement stone, (Record, limestone), 10x8x7 ins., no marks visible, firmly set in a collar of stone.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13S R63E</p> <p>1/4</p> <p>S 6 S 5</p> <p>2004</p> </div> <p>Deposit the original monument alongside the stainless steel post.</p> <hr style="width: 30%; margin: 10px auto;"/>

048

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	North, beginning new measurement.
8.30	Gulch, course E.; ascend along E. slope.
39.517	Intersect the Third Standard Parallel South.
	Point for the closing cor. of secs. 5 and 6.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	<div style="text-align: center;"> T12S R63E S31 <hr style="width: 50%; margin: 0 auto;"/> <div style="display: inline-block; text-align: left;">S 6</div> <div style="display: inline-block; text-align: left;">S 5</div> <div style="display: inline-block; text-align: left;">T13S</div> <div style="display: inline-block; text-align: left;">R63E</div> </div>
	CC
	2004
	The corner is located 20 lks. dist., N. of fence line, bears E. and W.
	From this cor., the original closing cor. of secs. 5 and 6, monumented with a cement stone, 18x11x7 ins., (Record, limestone, 15x14x9 ins.), mkd. with CC and 1 notch on N. side and 5 notches on E. side, and in a mound of stone, 3 ft. diam., 1 ft. high, bears North, 0.383 chs. dist. This corner now becomes an amended monument.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	AM
	2004
	Deposit the original monument alongside the stainless steel post.
	From this same cor., the standard cor. of secs. 31 and 32, T. 12 S., R. 63 E., bears S. 89°14'10" E., 16.058 chs. dist., hereinbefore described.
	<hr/>
	The point for the 1/4 sec. cor. of sec. 5 only, on the N. bdy. of the Tp., is at midpoint in departure on the N. bdy. of sec. 5.

049

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T12S R63E 1/4 S 5 T13S R63E</p> <p style="text-align: center;">2004</p> <p>From this cor., the standard 1/4 sec. cor. of sec. 32, T. 12 S., R. 63 E., bears S. 89°20'50" E., 15.976 chs. dist., hereinbefore described.</p> <hr/> <p style="text-align: center;">METES-AND-BOUNDS SURVEY OF THE CENTERLINE OF NEVADA STATE ROUTE NO. 168, THROUGH SECTIONS 20, 21, 22, 23, 25, AND 26, T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>The survey of lands for patent conveyance to Coyote Springs Investment, L.L.C., was executed in accordance with the described land in the document titled "Legal Descriptions for CSI Lands Within Clark County, NV".</p> <p>The centerline of the right-of-way for Nevada State Route No. 168 was determined utilizing monuments set by the Nevada Department of Transportation and the description in State of Nevada right-of-way application Nev-065185. Some monuments were found to be not at their geometric position. In those instances, direct bearing and distance ties are reported from a point on the centerline to the Nevada Department of Transportation stations.</p> <p>Witness points were established at intersection of the centerline of the right-of-way and section lines.</p> <hr/> <p>From the point for a witness point, at intersection with the line bet. secs. 25 and 30, on the E. bdy. of T. 13 S., R. 63 E., and the centerline of Nevada State Route No. 168.</p> <p>Set a PK nail and washer flush with the asphalt surface, with washer mkd. WP S25 S30.</p> <p>From this point, a standard Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way, monumented with a brass tablet, set in concrete, mkd. STA D 29+16.33 PT DIST 60.37, bears N. 78°40'50" E., 35.314 chs. dist.</p>
--------	---

050

METES-AND-BOUNDS SURVEY OF THE CENTERLINE OF NEVADA STATE
ROUTE NO. 168, THROUGH SECTIONS 20, 21, 22, 23, 25, AND 26,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From this same point, a standard Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way, monumented with a brass tablet, set in concrete, mkd. STA D 29+16.33 PT DIST 43.02, bears N. 81°13'50" E., 35.309 chs. dist.</p> <p>S. 80°10'00" W., on the centerline of Nevada State Route No. 168, in sec. 25.</p>
10.500	<p>Point of Curvature. Not monumented.</p> <hr/> <p>Thence along the arc of a circular curve to the right, having a radius of 5000.00 ft.; the long chord of said arc bears N. 80°13'40" W., 50.854 chs. dist.</p>
5.403	<p>Point on Curve. Not monumented.</p> <p>From this point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA D 62+95.59 POT O₁ 62+95.59 PC DIST 67.90, bears S. 9°50'00" E., 1.222 chs. dist.</p> <p>From this same point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA D 62+95.59 POT O₁ 62+95.59 PC DIST 62.90, bears N. 9°50'00" W., 0.760 chs. dist.</p>
46.432	<p>Point on Curve. Not monumented.</p> <p>From this point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. O₁ 90+33.82 PT DIST 89.50, bears N. 29°22'50" E., 1.161 chs. dist.</p>
46.577	<p>Point on Curve. Not monumented.</p> <p>From this point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA D 90+42.67 PT O₁ 90+43.29 DIST 89.34, bears N. 29°22'50" E., 1.169 chs. dist.</p>
51.860	<p>Point of Tangency. Not monumented.</p> <hr/>

051

METES-AND-BOUNDS SURVEY OF THE CENTERLINE OF NEVADA STATE
ROUTE NO. 168, THROUGH SECTIONS 20, 21, 22, 23, 25, AND 26,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 60°37'10" W. on the centerline, beginning new measurement.
22.248	Point on Tangent, monumented with an aluminum cap, 2 1/2 ins. diam., firmly set in asphalt mkd. PLS 9677.
22.469	Point for a witness point, at intersection with the line bet. secs. 25 and 26. Set a PK nail and washer flush with the asphalt surface, with washer mkd. WP S25 S26 HWY 168.
	Thence N. 60°37'10" W. on the centerline of Nevada State Route No. 168, in sec. 26.
1.125	Point of Curvature, monumented with an aluminum cap, 1 1/2 ins. diam., firmly set in asphalt, mkd. PLS 9677. From this point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way, but not utilized to determine the Point of Curvature, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA D 109+49.04 PC DIST 77.20, bears N. 28°41'40" E., 1.170 chs. dist. From this point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way, but not utilized to determine the Point of Curvature, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA D 109+49.04 PC DIST 84.70, bears S. 29°28'30" W., 1.283 chs. dist.
	Thence along the arc of a circular curve to the left, having a radius of 5000.00 ft.; the chord of said arc bears N. 72°48'00" W., 31.962 chs. dist.
15.029	Point for a witness point, at intersection with the line bet. secs. 23 and 26. Set a PK nail and washer flush with the asphalt surface, with washer mkd. WP S23 S26 HWY 168.
	Continue on curve of the centerline of Nevada State Route No. 168, in sec. 23.
17.174	Point of Tangency. Not monumented. From this point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way, but not utilized to determine the Point of Curvature, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA D 130+74.46 PT DIST 78.39, bears N. 4°41'00" E., 1.188 chs. dist.

052

METES-AND-BOUNDS SURVEY OF THE CENTERLINE OF NEVADA STATE
ROUTE NO. 168, THROUGH SECTIONS 20, 21, 22, 23, 25, AND 26,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From this same point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way, but not utilized to determine the Point of Curvature, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA D 130+74.46 PT DIST 88.10, bears S. 5°19'40" W., 1.335 chs. dist.</p>
	<p>N. 84°59'00" W. on the centerline, beginning new measurement.</p>
40.592	<p>Point on Tangent. Not monumented.</p> <p>From this point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way and the Point of Curvature, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA D 157+56.58 POT DIST 59.61, bears N. 5°01'00" E., 0.903 chs. dist.</p>
	<p>From this same point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way and the Point of Curvature, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA D 157+56.58 POT DIST 87.12, bears S. 5°01'00" W., 1.320 chs. dist.</p>
48.782	<p>Point for a witness point, at intersection with the line bet. secs. 22 and 23.</p> <p>Set a PK nail and washer flush with the asphalt surface, with washer mkd. WP S22 S23 HWY 168.</p>
	<p>N. 84°59'30" W. on the centerline of Nevada State Route No. 168, in sec. 22.</p>
22.989	<p>Point on Tangent. Not monumented.</p> <p>From this point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way and the Point of Curvature, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA D 178+14.87 POT DIST 86.76, bears N. 5°00'30" E., 1.315 chs. dist.</p> <p>From this point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way and the Point of Curvature, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA D 178+14.87 POT DIST 99.80, bears S. 5°00'30" W., 1.512 chs. dist.</p>

053

METES-AND-BOUNDS SURVEY OF THE CENTERLINE OF NEVADA STATE
ROUTE NO. 168, THROUGH SECTIONS 20, 21, 22, 23, 25, AND 26,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
49.352	<p>Point on Tangent. Not monumented.</p> <p>From this point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way and the Point of Tangency, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA D 195+52.86 POT DIST 90.85, bears N. 5°00'30" E., 1.377 chs. dist.</p> <p>From this point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way, and the Point of Tangency, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA D 195+52.86 POT DIST 69.20, bears S. 5°00'30" W., 1.048 chs. dist.</p>
80.794	<p>Point for a witness point, at intersection with the line bet. secs. 21 and 22.</p> <p>Set a PK nail and washer flush with the asphalt surface, with washer mkd. WP S21 S22 HWY 168.</p>
	<hr/> <p>N. 85°00'00" W. on the centerline of Nevada State Route No. 168, in sec. 21.</p>
3.310	<p>Point on Tangent. Not monumented.</p> <p>From this point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA D 218+46.92 POT DIST 49.87, bears N. 5°00'00" E., 0.756 chs. dist.</p> <p>From this point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA D 218+46.92 POT DIST 55.58, bears S. 5°00'00" W., 0.842 chs. dist.</p>
50.814	<p>Point on Tangent. Not monumented.</p> <p>From this point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA D 249+83.52 POT DIST 63.37, bears N. 5°00'00" E., 0.960 chs. dist.</p>

054

METES-AND-BOUNDS SURVEY OF THE CENTERLINE OF NEVADA STATE
ROUTE NO. 168, THROUGH SECTIONS 20, 21, 22, 23, 25, AND 26,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From this point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA D 249+83.52 POT DIST 69.52, bears S. 5°00'00" W., 1.053 chs. dist.</p>
81.187	<p>Point for a witness point and intersection with the line bet. secs. 20 and 21.</p> <p>Set a PK nail and washer flush with the asphalt surface, with washer mkd. WP S20 S21 HWY 168.</p>
4.138	<p>N. 85°00'20" W. on the centerline of Nevada State Route No. 168, in sec. 20.</p> <p>Point for a witness point, at intersection with the centerline of U.S. Highway No. 93.</p> <p>Set a PK nail and washer flush with the asphalt surface, with washer mkd. WP HWY 93 HWY 168.</p> <p>From this point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way of U.S. Highway No. 93, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA A 1751+18.92 POT DIST 74.90, bears S. 9°27'10" E., 44.597 chs. dist.</p> <p>From this same point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way of U.S. Highway No. 93, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA A 1751+18.92 POT DIST 75.00, bears S. 6°32'00" E., 44.596 chs. dist.</p>
	<p>METES-AND-BOUNDS SURVEY OF A PORTION OF U.S. HIGHWAY NO. 93, THROUGH SECTIONS 5, 8, 17, AND 20, T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA</p>
	<p>MEMORANDUM</p> <p>The survey of lands for patent conveyance to Coyote Springs Investment, L.L.C., was executed in accordance with the described land in the document titled "Legal Descriptions for CSI Lands Within Clark County, NV".</p>

055

METES-AND-BOUNDS SURVEY OF A PORTION OF U.S. HIGHWAY NO. 93,
THROUGH SECTIONS 5, 8, 17, AND 20,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>The centerline of the right-of-way for U.S. Highway No. 93 was determined utilizing monuments set by the Nevada Department of Transportation and the description in State of Nevada right-of-way application Nev-060729.</p> <p>Witness points were established at intersection with the centerline of the right-of-way and section lines.</p> <hr/> <p>From the witness point at the intersection of U.S Highway No. 93 and Nevada State Route No. 168, hereinbefore described.</p> <p>N. 7°59'40" W., on the centerline of U.S. Highway No. 93, in sec. 20.</p> <p>28.848 Point on Tangent. Not monumented.</p> <p>From this point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA A 1799+65.33 POT DIST 74.49, bears N. 82°00'20" E., 1.129 chs. dist.</p> <p>From this same point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA A 1799+65.33 POT DIST 74.50, bears S. 82°00'20" W., 1.129 chs. dist.</p> <p>60.155 Point for a witness point, at intersection with the line bet. secs. 17 and 20.</p> <p>Set a PK nail and washer flush with the asphalt surface, with washer mkd. WP S17 S20 HWY93.</p> <hr/> <p>N 7°59'40" W., on the centerline of U.S. Highway No. 93, in sec. 17.</p> <p>9.675 Point on Tangent. Not monumented.</p> <p>From this point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA A 1826+70.00 POT DIST 74.58, bears N. 82°00'20" E., 1.130 chs. dist.</p> <p>From this same point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way, monumented with a standard Nevada Department of transportation brass tablet, set in concrete, mkd. STA A 1826+70.00 POT DIST 74.60, bears S. 82°00'20" W., 1.130 chs. dist.</p>
--------	---

METES-AND-BOUNDS SURVEY OF A PORTION OF U.S. HIGHWAY NO. 93,
THROUGH SECTIONS 5, 8, 17, AND 20,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
53.315	<p>Point on Tangent. Not monumented.</p> <p>From this point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA A 1855+49.79 POT DIST 75.47, bears N. 82°00'20" E., 1.144 chs. dist.</p> <p>From this same point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA A 1855+49.79 POT DIST 75.20, bears S. 82°00'20" W., 1.139 chs. dist.</p>
80.592	<p>Point on Tangent. Not monumented.</p> <p>From this point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA A 1873+49.90 POT DIST 75.10, bears N. 82°00'20" E., 1.138 chs. dist.</p> <p>From this same point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA A 1873+49.90 POT DIST 74.50, bears S. 82°00'20" W., 1.129 chs. dist.</p>
81.010	<p>Point for a witness point, at intersection with the line bet. secs. 8 and 17.</p> <p>Set a PK nail and washer flush with the asphalt surface, with washer mkd. WP S8 S17 HWY 93.</p> <hr/> <p>N. 7°59'50" W., on the centerline of U.S. Highway No. 93, in sec. 8.</p>
30.247	<p>Point on Tangent. Not monumented.</p> <p>From this point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA A 1893+73.27 POT DIST 74.25, bears N. 82°00'10" E., 1.125 chs. dist.</p>

057

METES-AND-BOUNDS SURVEY OF A PORTION OF U.S. HIGHWAY NO. 93,
THROUGH SECTIONS 5, 8, 17, AND 20,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From this same point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA A 1893+73.27 POT DIST 74.75, bears S. 82°00'10" W., 1.132 chs. dist.</p>
77.447	<p>Point on Tangent. Not monumented.</p>
	<p>From this point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA A 1924+88.18 POT DIST 75.45, bears N. 82°00'10" E., 1.143 chs. dist.</p>
	<p>From this same point, a Nevada Department of Transportation highway station not utilized to determine the centerline of the right-of-way, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA A 1924+88.18 POT DIST 80, bears S. 82°00'10" W., 1.129 chs. dist.</p>
80.779	<p>Point for a witness point, at intersection with the line bet. secs. 5 and 8.</p> <p>Set a PK nail and washer flush with the asphalt surface, with washer mkd. WP S5 S8 HWY93.</p>
	<p>N. 7°59'50" W., on the centerline of U.S. Highway No. 93, in sec. 5.</p>
37.192	<p>Point on Tangent. Not monumented.</p>
	<p>From this point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA A 1951+62.54 POT DIST 74.08, bears N. 82°00'10" E., 1.122 chs. dist.</p>
	<p>From this same point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA A 1951+62.54 POT DIST 59.71, bears S. 82°00'10" W., 0.902 chs. dist.</p>
79.737	<p>Point for a witness point, at intersection with the line bet. secs. 5 and 32, on the N. bdy. of the Tp.</p> <p>Set a PK nail and washer flush with the asphalt surface, with washer mkd. WP S5 S32 HWY93.</p>

058

METES-AND-BOUNDS SURVEY OF A PORTION OF U.S. HIGHWAY NO. 93,
THROUGH SECTIONS 5, 8, 17, AND 20,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

From this point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA A 1979+77.40 POT 0+00 DIST 74.97, bears N. 85°04'10" E., 1.127 chs. dist. This monument was found not at its geometric position.

From this same point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA A 1979+77.40 POT 0+00 DIST 75.06, bears N. 84°34'10" W., 1.155 chs. dist. This monument was found not at its geometric position.

METES-AND-BOUNDS SURVEY IN SECTION 1,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

MEMORANDUM

The survey of lands for patent conveyance to Coyote Springs Investment, L.L.C., was executed in accordance with the described land in the document titled "Legal Descriptions for CSI Lands Within Clark County, NV".

The centerline of the right-of-way for Nevada State Route No. 7, (formerly, U.S. Highway No. 93), was determined utilizing monuments set by the Nevada Department of Transportation and the description in State of Nevada right-of-way application Nev-060130A. Some monuments were found to be not at their geometric position. In those instances, direct bearing and distance ties are reported from witness points to the highway monuments.

Witness points were established on the offset line; a line parallel and 100 feet easterly of the centerline of the right-of-way.


From the point for a witness point, at intersection with the E. bdy. of sec. 1 with the line parallel and 100 ft. easterly of the centerline of Nevada State Route No. 7.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

059

METES-AND-BOUNDS SURVEY IN SECTION 1,
T. 13 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS




N. $17^{\circ}06'00''$ W., on a line parallel and 100 ft. easterly of the centerline of Nevada State Route No. 7, in sec. 1.

3.928

Point for a witness point, at intersection with the N. bdy. of sec. 1, (Third Standard Parallel South).

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.



From this point, a point on the centerline of Nevada State Route No. 7, determined from a tie to the original closing cor. of Tps. 13 S., Rs. 63 and 64 E., bears N. $84^{\circ}21'10''$ W., 1.644 chs. dist. Not monumented.

GENERAL DESCRIPTION

The lands included in the survey are located in Clark County, Nevada, about 24 miles northwest of the community of Moapa, Nevada. Access is gained by way of U.S. Highway No. 93 and Nevada State Route No. 168.

The area drains easterly and southerly into Wildcat Wash. Coyote Springs Valley runs northerly and southerly through the area surveyed.

The elevations range from approximately 2100 feet above sea level at Pahrnagat Wash in section 31, up to about 3500 feet above sea level near the one-quarter section corner of sections 5 and 6.

No apparent mineral activity was noted in the area during this survey.

060.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Kenneth Burns	Field Technician (VTN)
Kevin Campbell	Field Technician (VTN)

CERTIFICATE OF SURVEY

We, David J. Passmore, Professional Land Surveyor (VTN, Inc.) and Craig L. Wanless, Cadastral Surveyor (BLM), HEREBY CERTIFY upon honor, that in pursuance of Special Instructions bearing date of the 9th day of October, 2003, and Supplemental Special Instructions bearing dates of the 20th day of July, 2004, and the 21st day of September, 2004, we have dependently resurveyed the Third Standard Parallel South, through portions of Range 63 East, a portion of the south boundary, the east boundary and a portion of the subdivisional lines, and executed metes-and-bounds surveys of portions of U.S. Highway No. 93 and Nevada State Route No. 168, and a metes-and-bounds survey in section 1, Township 13 South, Range 63 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

September 27, 2004

(Date)

David J. Passmore
(Professional Land Surveyor)

September 28, 2004

(Date)

Craig L. Wanless
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of the dependent resurvey of the Third Standard Parallel South, through portions of Range 63 East, a portion of the south boundary, the east boundary and a portion of the subdivisional lines, and metes-and-bounds surveys of portions of U.S. Highway No. 93 and Nevada State Route No. 168, and a metes-and-bounds survey in section 1, Township 13 South, Range 63 East, Mount Diablo Meridian, in the State of Nevada, executed by David J. Passmore, Professional Land Surveyor (VTN, Inc.) and Craig L. Wanless, Cadastral Surveyor (BLM), having been critically examined and found correct, are hereby approved.

September 29, 2004

(Date)

Acting

David J. Clark
(Chief Cadastral Surveyor, Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above described surveys in T. 13 S., R. 63 E., Mount Diablo Meridian, Nevada, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor, Nevada)~~