

## United States Department of the Interior

## BUREAU OF LAND MANAGEMENT

Nevada State Office  
P.O. Box 12000 (1340 Financial Blvd)  
Reno, Nevada 89520-0006  
<http://www.nv.blm.gov>

In Reply Refer To:  
9600 (NV-952)  
Group 743, Nevada

DEC 15 2003

## Memorandum


To: Cadastral Lead Quality Assurance Examiner

From: Acting Chief, Branch of Geographic Sciences

Subject: Field Notes, Group No. 743, Nevada

The original field notes for surveys conducted under Group No. 743, Nevada, were approved on July 29, 1997, and sent to the Micrographics Branch for microfilming. No film of the field notes was ever returned and the official hardcopy record of the original field notes is missing.

Per this office's request dated March 18, 2003, the Eastern States Office has provided the attached copy of the official duplicate field notes for Group No. 743, Nevada. You are to stamp each page of these notes "COPY" and place them in the next available area of the volumes for rectangular surveys. This memorandum shall be placed just before the first page (cover page). Each page will be stamped with the corresponding page number for the volume. This memorandum and the copy of the duplicate field notes will then be scanned to be included with Nevada's scanned field note images.



## Attachment:

Copy of Duplicate Field Notes (98 pgs.)

## cc:

Chief, Information Access Center (NV-956)

RECEIVED  
BUR. OF LAND MANAGEMENT  
NEVADA STATE OFFICE

03 MAR 31 AM 7:30

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

Duplicate

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

A PORTION OF THE SOUTH, EAST, WEST, AND NORTH BOUNDARIES,  
A PORTION OF THE SUBDIVISIONAL LINES,  
AND A PORTION OF  
THE SUBDIVISION-OF-SECTION LINES OF SECTIONS 1 AND 24,  
AND THE SUBDIVISION AND FURTHER SUBDIVISION OF SECTIONS  
1, 2, 5, 6, 9, 11, 16, 19, 20, 21, 24, 27, 28, 29, 30, AND 33,  
AND THE METES-AND-BOUNDS SURVEY OF PORTIONS OF  
U.S. HIGHWAY 50 RIGHT-OF-WAY, IN SECTIONS 5 AND 6,  
TOWNSHIP 14 NORTH, RANGE 19 EAST,  
OF THE MOUNT DIABLO MERIDIAN,  
IN THE STATE OF NEVADA

EXECUTED BY

Brian L. Mikkelsen, Cadastral Surveyor

Under Special Instructions dated June 14, 1994,  
and approved June 14, 1994,  
which provided for the surveys included under Group No. 743,  
and Assignment Instructions dated June 14, 1994.

Survey commenced August 11, 1994

Survey completed October 24, 1996

003  
INDEX DIAGRAM

COPY

TOWNSHIP 14 NORTH, RANGE 19 EAST

9					8	12
6	6	43 5	31 4	3	2	1
	42	42	30		14	
					13	
	7	40 8	9	10	11	12
	18	17	16	15	14	13
		39	28			3
	19	38 20	25 21	22	23	24
	37	35	24	19 18		3 11
	30	33 29	22 28	17 27	26	25
4	32	31	21	16	12	
	31	32	19 33	15 34	35	36
					2	

Resurvey of Subdivision-of-Section Lines of Section 1 . . . . .	pp 44-46
Resurvey of Subdivision-of-Section Lines of Section 24 . . . . .	pp 46-47
Further Subdivision of Section 1 . . . . .	pp 47-49
Subdivision of Section 2 . . . . .	pp 49-53
Subdivision of Section 5 . . . . .	pp 53-54
Subdivision of Section 6 . . . . .	pp 54-59
Subdivision of Section 9 . . . . .	pp 59-60
Subdivision of Section 11 . . . . .	pp 60-63
Subdivision of Section 16 . . . . .	pp 63-64
Subdivision of Section 19 . . . . .	pp 64-66
Subdivision of Section 20 . . . . .	pp 66-69
Subdivision of Section 21 . . . . .	pp 69-73
Further Subdivision of Section 24 . . . . .	pp 73-76
Subdivision of Section 27 . . . . .	pp 76-79
Subdivision of Section 28 . . . . .	pp 79-83
Subdivision of Section 29 . . . . .	pp 83-84
Subdivision of Section 30 . . . . .	pp 84-86
Subdivision of Section 33 . . . . .	pp 86-88
U.S. Highway 50 R.O.W., in Sections 5 and 6 . . . . .	pp 88-93

## TOWNSHIP 14 NORTH, RANGE 19 EAST, MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

The following field notes are those of the dependent resurvey of a portion of the south, east, west, and north boundaries, a portion of the subdivisional lines, and a portion of the subdivision-of-section lines of sections 1 and 24, and the subdivision and further subdivision of sections 1, 2, 5, 6, 9, 11, 16, 19, 20, 21, 24, 27, 28, 29, 30, and 33, and the metes-and-bounds survey of portions of U.S. Highway 50 right-of-way, in sections 5 and 6, Township 14 North, Range 19 East, Mount Diablo Meridian, Nevada.

## History of prior surveys

- 1861 - The north, south, east, and west boundaries were surveyed by U.S. Deputy Surveyor J.S. Lawson under Contract "B".
- 1861 - The subdivisional lines were surveyed by U.S. Deputy Surveyor B. Ives under Contract "C".
- 1963 - The north 2 miles of the east boundary were dependently resurveyed by Cadastral Surveyor D.A. Cannon under Group No. 406.
- 1966 - The NW township corner was remonumented by Cadastral Surveyors R.A. Pratt and W.L. Jepson under Group No. 393.
- 1985-86 - The west 3 and one-half miles of the south boundary were dependently resurveyed by Cadastral Surveyors D.L. Dukleth and J.S. Parrish under Group No. 620.
- 1985 - A portion of the south, east, and north boundaries, and a portion of the subdivisional lines were dependently resurveyed and certain sections were subdivided, and Parcel A in section 1 was surveyed by Cadastral Surveyor R.E. Williams under Group No. 624.
- 1987-91 - The west 3 miles of the north boundary were dependently resurveyed by Cadastral Surveyors F. E. Wheeler, D. J. Rogers, and B. L. Mikkelsen under Group No. 647.
- 1991 - A portion of the east boundary and a portion of the subdivisional lines were dependently resurveyed, and section 12 was subdivided by Cadastral Surveyor R.A. Pratt under Group No. 710.
- 1993 - The east 1 mile of the north boundary was dependently resurveyed by Cadastral Surveyor J. H. Honda under Group No. 734.
- 1994 - A portion of the subdivision-of-section lines of section 12 was dependently resurveyed along with the further subdivision of section 12, and the metes-and-bounds survey of Lot 1, section 12 by Cadastral Surveyor B.L. Mikkelsen under Group No. 746.

Before restoring the corners, the lines of the original surveys were retraced and diligent search made for any evidence of the original corners and other calls of the original field note record.

## TOWNSHIP 14 NORTH, RANGE 19 EAST, MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated June 14, 1994, for Group No. 743, Nevada.

The direction of the lines were determined by direct solar observations. The lines were carried forward by sustained angulation being supplemented by other observations of the sun taken throughout the progress of the survey.

The vertical angles of measurements made on the slope were ascertained with a theodolite in good adjustment; the horizontal equivalents only are entered in the field notes.

The geographic position for the cor. of Tps. 14 and 15 N., Rs. 19 and 20 E., is at Lat. 39°06'50.432" N., Long. 119°47'14.073" W., (NAD 1927), identical with U.S.G.S. triangulation station "SEC COR 36/15N/19E".

The mean magnetic declination is 15<sup>1</sup>/<sub>2</sub>° E., as shown on U.S.G.S. quadrangle map "GENOA NV" dated 1994.

---

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

---

Reestablishment of the Survey Executed by  
J.S. Lawson, U.S. Deputy Surveyor,  
in 1861

---

From the <sup>1</sup>/<sub>4</sub> sec. cor. of secs. 2 and 35, monumented with an iron pipe, 2 ins. diam., firmly set, projecting 30 ins. above the ground, as described in the field notes of T. 13 N., R. 19 E., executed under Group No. 620, and as described in the field notes of T. 14 N., R. 19 E., executed under Group No. 624.

Not remonumented.

Cor. is located on level ground in scattered sagebrush.

S. 89°36'00" W., bet. secs. 2 and 35.

39.743

The cor. of secs. 2, 3, 34, and 35, monumented with a rebar, <sup>5</sup>/<sub>8</sub> in. diam., firmly set, 3 ins. below the ground, with aluminum cap mkd. SC 2, 3, 34, 35 RLS 3579, as recorded in Douglas County, book 687, page 1891, document No. 156517; book 596, page 4802, document No. 388745; and book 1296, page 4975, document No. 403935, and is accepted as a careful and faithful reestablishment of the position of the original cor.

Not remonumented.

Cor. is located in an alfalfa field.

---

006

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	S. 89°36'10" W., beginning new measurement.
39.741	<p>The 1/4 sec. cor. of secs. 3 and 34, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd. as described in the field notes of T. 13 N., R. 19 E., executed under Group No. 620.</p> <p>Cor. is located on SE slope in rocky soil with sagebrush.</p>
<p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY, T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA</p>	
<p style="text-align: center;">Reestablishment of the Survey Executed by J.S. Lawson, U.S. Deputy Surveyor, in 1861, and the Resurvey by R. E. Williams, Cadastral Surveyor, in 1985</p>	
9.999	<p>From the S 1/16 sec. cor. of secs. 19 and 24, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above the ground, with aluminum cap mkd. as described in the field notes of T. 14 N., R. 20 E., executed under Group No. 624.</p> <p>N. 0°15'50" E., bet. secs. 19 and 24.</p> <p>Point for the N-S 1/64 sec. cor. of secs. 19 and 24. An iron pipe, 3/4 in. diam. was recovered 6 ins. below the surface lying horizontally, no record of iron pipe found.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">N-S 1/64 S24   S19  1995</p> <p>No suitable trees available for bearing trees.</p> <p>Deposit iron pipe alongside of stainless steel post.</p> <p>Cor. is located on the S edge of a gravel road, in sandy soil with scattered sagebrush.</p>
19.998	<p>The 1/4 sec. cor. of secs. 19 and 24, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with aluminum cap mkd. as described in the field notes of T. 14 N., R. 20 E., executed under Group No. 624, and witnessed by a mound of stone, 3 ft. base, 1 1/2 ft. high, 3 lks. N of cor.</p> <p>Cor. is located at corner of fences, bears E, W and N.</p> <hr/> <p>From the cor. of secs. 13, 18, 19, and 24, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with aluminum cap mkd. as described in the field notes of T. 14 N., R. 20 E., executed under Group No. 624, and witnessed by a mound of stone, 3 ft. base, 1 ft. high, 3 lks. W of cor.</p>

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p> <p>19.916</p> <p>39.832</p>	<p>Cor. is located at corner of fences, bears E, S and N.</p> <p>N. 0°22'50" E., bet. secs. 13 and 18.</p> <p>Point for the S <math>\frac{1}{16}</math> sec. cor. of secs. 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S <math>\frac{1}{16}</math> S13   S18</p> <p style="text-align: center;">1995</p> <p>No suitable trees available for bearing trees.</p> <p>Cor. is located in sandy soil with scattered sagebrush and bitterbrush. West, 19 lks. to a fence, bears N and S.</p> <p>The <math>\frac{1}{4}</math> sec. cor. of secs. 13 and 18, monumented with an aluminum post, 2<math>\frac{1}{2}</math> ins. diam., firmly set, projecting 8 ins. above the ground, with aluminum cap mkd. as described in the field notes of T. 14 N., R. 20 E., executed under Group No. 624, and witnessed by a mound of stone, 2 ft. base, 1 ft. high, 2 lks. W of cor.</p>
<p>DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY, T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA</p>	
<p>Reestablishment of the Survey Executed by J.S. Lawson, U.S. Deputy Surveyor, in 1861</p>	
<p>From the cor. of secs. 25, 30, 31, and 36, monumented with the remains of a wood post, 4 x 4 x 14 ins. with scribe mks. T14NR visible on one side and notches and axe mks. visible on another side, lying loosely in a mound of stone, 3 ft. base, 16 ins. high, from which the remains of the original bearing trees</p> <p>A pine, 34 ins. diam., bears N. 46<math>\frac{1}{4}</math>° E., 113 lks. dist., with 14 19 visible in partially opened upper blaze and healed lower blaze. (Record, 111 lks.)</p> <p>A decayed fir stump, bears S. 4<math>\frac{1}{4}</math>° E., 93 lks. dist., with the fir, dead and down, 36 ins. diam., lying alongside, with illegible scribe mks. and axe mks. visible on remains of the partially decayed blaze. (Record, 91 lks.)</p> <p>A fir, 29 ins. diam., bears S. 37° W., 144 lks. dist., with healed upper and lower blazes.</p> <p>A decayed pine stump, bears N. 73° W., 128 lks. dist., with the pine, dead and down, 31 ins. diam., lying alongside, with T14NR18E S25 BT visible on partially healed blaze. (Record, 130 lks.)</p> <p>At the corner point</p>	

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a brass tablet, <math>3\frac{1}{4}</math> ins. diam., <math>3\frac{1}{2}</math>-in. stem, in drill hole in an exposed boulder, 1 x 1 ft. and 6 ins. below the surface, with top mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr><td colspan="2" style="text-align: center;">T14N</td></tr> <tr><td style="text-align: center;">R18E</td><td style="text-align: center;">R19E</td></tr> <tr><td style="text-align: center;">S25</td><td style="text-align: center;">S30</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td style="text-align: center;">S36</td><td style="text-align: center;">S31</td></tr> </table> <p style="text-align: center;">1994</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 20 ins. diam., bears S. <math>17\frac{3}{4}^\circ</math> E., 46 lks. dist., mkd. T14NR19E S31 BT.</p> <p style="padding-left: 40px;">A fir, 22 ins. diam., bears N. <math>34\frac{1}{2}^\circ</math> W., 176 lks. dist., mkd. T14NR18E S25 BT.</p> <p>Deposit the remains of the original wood post in 4 x 2 ft. mound of stone, 4 lks. W of corner.</p> <p>Cor. is located 17 lks. E of Tahoe Rim Trail, 2 lks. wide, bears N. <math>30^\circ</math> E. and S. <math>30^\circ</math> W., and on a NW slope in rocky soil with pine, fir, and manzanita.</p> <p>N. <math>0^\circ 11' 10''</math> W., bet. secs. 25 and 30.</p> <p>40.217 The <math>\frac{1}{4}</math> sec. cor. of secs. 25 and 30, determined at record bearing and distance from the remains of an original bearing tree</p> <p style="padding-left: 40px;">A pine stump, 9 ins. diam., bears N. <math>24^\circ</math> W., 19 lks. dist., with the scribe mks. BT and chaining notch visible on partially healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr><td colspan="2" style="text-align: center;">T14N</td></tr> <tr><td style="text-align: center;">R18E</td><td style="text-align: center;">R19E</td></tr> <tr><td colspan="2" style="text-align: center;"><math>\frac{1}{4}</math></td></tr> <tr><td style="text-align: center;">S25</td><td style="text-align: center;">S30</td></tr> </table> <p style="text-align: center;">1994</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears N. <math>69^\circ</math> E., 53 lks. dist., mkd. <math>\frac{1}{4}</math> S30 BT.</p> <p style="padding-left: 40px;">A pine, 15 ins. diam., bears N. <math>40\frac{1}{4}^\circ</math> W., 33 lks. dist., mkd. <math>\frac{1}{4}</math> S25 BT.</p> <p>Cor. is located on a SW slope in sandy soil with pine and fir.</p> <hr style="width: 80%; margin-left: 0;"/>	T14N		R18E	R19E	S25	S30			S36	S31	T14N		R18E	R19E	$\frac{1}{4}$		S25	S30
T14N																			
R18E	R19E																		
S25	S30																		
S36	S31																		
T14N																			
R18E	R19E																		
$\frac{1}{4}$																			
S25	S30																		

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

From the cor. of secs. 1, 6, 7, and 12, monumented with an embedded mound of stone, 4 ft. diam., 18 ins. high, and is accepted as the best available evidence of the position of the original cor.

At the corner point

Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 20 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T14N	
R18E	R19E
S 1	S 6
-----	
S12	S 7

1996

from which

A pine, 14 ins. diam., bears N. 51° E., 22 lks. dist., mkd. T14NR19E S6 BT.

A fir, 21 ins. diam., bears S. 37° E., 57 lks. dist., mkd. T14NR19E S7 BT.

A pine, 13 ins. diam., bears S. 31<sup>1</sup>/<sub>2</sub>° W., 120 lks. dist., mkd. X BT.

A pine, 17 ins. diam., bears N. 66<sup>3</sup>/<sub>4</sub>° W., 30 lks. dist., mkd. T14NR18E S1 BT.

Cor. is located on a N slope in sandy soil with pine and fir.

N. 0°16'40" E., bet. secs. 1 and 6.

9.00 Ridge, bears E and W.

19.864 Point for the S <sup>1</sup>/<sub>16</sub> sec. cor. of secs. 1 and 6.

Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 2<sup>1</sup>/<sub>2</sub> ft. base, to top, with brass cap mkd.

S 1/16	
S 1	S 6

1996

from which

A pine, 19 ins. diam., bears N. 39° E., 82 lks. dist., mkd. S 1/16 S6 BT.

A pine, 13 ins. diam., bears N. 23<sup>1</sup>/<sub>2</sub>° W., 83 lks. dist., mkd. S 1/16 S1 BT.

Cor. is located on a steep N slope in sandy soil with pine and fir.

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 30.50</p>	<p>U.S. Highway 50, 4 lanes, bears N. 74° E. and S. 74° W.</p>
<p>39.728</p>	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 1 and 6, monumented with an embedded mound of stone, 3 ft. diam., 10 ins. high, and is accepted as the best available evidence of the position of the original cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T14N R18E R19E <math>\frac{1}{4}</math> S 1   S 6</p> <p style="text-align: center;">1996</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 31 ins. diam., bears S. <math>67\frac{3}{4}^\circ</math> E., 58 lks. dist., mkd. <math>\frac{1}{4}</math> S6 BT.</p> <p style="padding-left: 40px;">A pine, 12 ins. diam., bears S. <math>17\frac{1}{2}^\circ</math> W., 113 lks. dist., mkd. <math>\frac{1}{4}</math> S1 BT.</p> <p>Cor. is located in a ravine, drains W in rocky soil with pine and sagebrush. The Tahoe Rim Trail, 11 lks. wide, bears N, 188 lks., and E, 194 lks.</p> <hr style="width: 30%; margin: 10px auto;"/>
<p>13.00</p>	<p>N. <math>0^\circ 57' 00''</math> E., beginning new measurement.</p>
<p>20.154</p>	<p>Top of rock outcrop on a ridge, bears E and W.</p> <p>Point for the N <math>\frac{1}{16}</math> sec. cor. of secs. 1 and 6.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">N <math>\frac{1}{16}</math> S 1   S 6</p> <p style="text-align: center;">1996</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 23 ins. diam., bears S. <math>65\frac{3}{4}^\circ</math> E., 98 lks. dist., mkd. N <math>\frac{1}{16}</math> S6 BT.</p> <p style="padding-left: 40px;">A pine, 18 ins. diam., bears S. <math>32\frac{1}{4}^\circ</math> W., 62 lks. dist., mkd. N <math>\frac{1}{16}</math> S1 BT.</p> <p>Cor. is located in shallow ravine, drains N. <math>75^\circ</math> W., and in sandy soil with pine and fir.</p>

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS  
40.308

The cor. of Tps. 14 and 15 N., Rs. 18 and 19 E., monumented with an iron post,  $2\frac{1}{2}$  ins. diam., firmly set, projecting 4 ins. above the ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd. as described in the field notes of T. 15 N., R. 19 E., executed under Group No. 647, and also described in the field notes of the 1966 remonumentation of certain cors. in T. 15 N., R. 19 E., executed under Group No. 393, from which an original bearing tree

A fir, 45 ins. diam., bears N.  $62\frac{1}{4}^{\circ}$  E.,  $40\frac{1}{2}$  lks. dist., mkd. with a healed blaze.

and the 1966 bearing trees

A pine, 11 ins. diam., bears S.  $70^{\circ}$  E., 32 lks. dist., mkd. illegible scribe mks. visible in partially healed blaze.

A fir, 34 ins. diam., bears S.  $18\frac{1}{2}^{\circ}$  W.,  $21\frac{1}{2}$  lks. dist., mkd. with illegible scribe mks. visible in partially healed blaze. (Record, S.  $17\frac{1}{2}^{\circ}$  W.)

A fir, 15 ins. diam., bears N.  $37\frac{3}{4}^{\circ}$  W., 40 lks. dist., mkd. with a healed blaze.

Cor. is located on a NE slope in rocky sandy soil with pine and fir.

---

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

---

Reestablishment of the Survey Executed by  
J.S. Lawson, U.S. Deputy Surveyor, in 1861,  
Resurvey by R.E. Williams, Cadastral Surveyor, in 1985,  
Resurvey by J.H. Honda, Cadastral Surveyor, in 1993, and the  
Resurvey by F.E. Wheeler, B.L. Mikkelsen, and D.J. Rogers,  
Cadastral Surveyors, in 1987-91

---

From the cor. of secs. 1, 2, 35, and 36, monumented with a stainless steel post,  $2\frac{1}{2}$  ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. as described in the field notes of T. 15 N., R. 19 E., executed under Group No. 734.

S.  $89^{\circ}22'50''$  W., bet. secs. 2 and 35.

19.931

Point for the E  $\frac{1}{16}$  sec. cor. of secs. 2 and 35.

Set a stainless steel post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

S35  
E  $\frac{1}{16}$  ———  
S 2  
1995

from which

012

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>A granite face, 4 x 3 ft. high, bears S. 36°35' W., 34.5 lks. dist. to X, mkd. BXO on NE face, 6 ft. above ground.</p> <p>A granite boulder, 3 x 6 x 9 ft. high, bears N. 72°08' W., 43.5 lks. dist. to X, mkd. BXO on NE face, 1½ ft. above ground.</p> <p>Cor. is located on a steep N slope near the base of large rock outcrop, in rocky soil with scattered pine and sagebrush.</p>
39.862	<p>The ¼ sec. cor. of secs. 2 and 35, monumented with an aluminum post, 2½ ins. diam., firmly set, projecting 5 ins. above the ground, and in a mound of stone, 5 ft. base, to top, with aluminum cap mkd. as described in the field notes of T. 14 N., R. 19 E., executed under Group No. 624.</p> <p>Note: no evidence of the local rebar with tag mkd. RE 827 as described in the field notes under Group No. 624 was found.</p>
	<p>From the cor. of secs. 5, 6, 31, and 32, monumented with a stainless steel post, 2½ ins. diam., firmly set, projecting 4 ins. above the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd. as described in the field notes of T. 15 N., R. 19 E., executed under Group No. 647, from which the 1987-91 bearing trees</p> <p>A pine, 16 ins. diam., bears N. 8¼° E., 102½ lks. dist., mkd. T15NR19E S32 BT.</p> <p>A pine, 14 ins. diam., bears S. 42¾° E., 87 lks. dist., mkd. T14NR19E S5 BT. (Record, 85 lks.)</p> <p>A pine, 19 ins. diam., bears S. 24¾° W., 20½ lks. dist., mkd. T14NR19E S6 BT.</p> <p>A pine, 16 ins. diam., bears N. 84¾° W., 130 lks. dist., mkd. T15NR19E S31 BT.</p>
	<p>Cor. is located on a steep E slope in sandy soil with pine and fir. EAST, 90 lks., to old Clear Creek road, 60 lks. wide, bears S. 8° E. and N. 8° W.</p> <p>S. 89°01'20" W., bet. secs. 6 and 31.</p>
9.628	<p>The witness point, at the intersection of the E right-of-way of U.S. Highway 50, and the line between secs. 6 and 31, hereinafter described.</p>
15.30	<p>U.S. Highway 50, 4 lanes, bears N. 68° W. and S. 68° E.</p>
19.873	<p>Point for the E ¼ sec. cor. of secs. 6 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: right;">S31 E 1/16 <hr style="width: 50px; margin: 0 auto;"/> S 6 1996</p>
	<p>from which</p> <p>A pine, 6 ins. diam., bears S. 65° E., 112 lks. dist., mkd. X BT.</p> <p>A pine, 8 ins. diam., bears N. 57° W., 37 lks. dist., mkd. E 1/16 S31 BT.</p> <p>Cor. is located on a level "road cut" above U.S. Highway 50 in sandy rocky soil with scattered pine and fir.</p> <p>From this point, a Nevada Highway Department brass disc, 3½ ins. diam., cemented flush with the ground, mkd. "STA 0125+79.78 DIST 104.44 ANGLE 90 DATE SET 1957", bears S. 75°16'30" E., 1.597 chs. dist., and is located on the south side of the highway.</p> <p>From this same point, a Nevada Highway Department brass disc, 3½ ins. diam., cemented flush with the ground, mkd. "STA 0122+14.45 DIST 103.46 ANGLE 90 DATE SET 1957", bears S. 69°45'10" E., 7.114 chs. dist., and is located on the south side of the highway.</p>
39.746	<p>The ¼ sec. cor. of secs. 31 and 6, monumented with a stainless steel post, 2½ ins. diam., firmly set, projecting 2 ins. above the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd. as described in the field notes of T. 15 N., R. 19 E., executed under Group No. 647, from which the 1987-91 bearing trees</p> <p>A fir, 15 ins. diam., bears N. 28½° E., 19 lks. dist., mkd. 1/4 S31 BT in partially healed blaze. (Record, N. 29¾° E.)</p> <p>A pine, 17 ins. diam., bears S. 12¾° W., 27½ lks. dist., mkd. 1/4 S6 BT in partially healed blaze.</p> <p>Cor. is located on a NE slope in sandy soil with pine and fir.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°01'30" W., beginning new measurement.</p>
19.875	<p>Point for the W 1/16 sec. cor. of secs. 6 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: right;">S31 W 1/16 <hr style="width: 50px; margin: 0 auto;"/> S 6 1996</p> <p>from which</p> <p>A pine, 10 ins. diam., bears S. 2¼° W., 101 lks. dist., mkd. W 1/16 S6 BT.</p>

014

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>A pine, 18 ins. diam., bears N. 86° W., 91 lks. dist., mkd. W 1/16 S31 BT.</p> <p>Cor. is located on NE slope in sandy soil with pine and fir.</p>
35.983	<p>The cor. of Tps. 14 and 15 N., Rs. 18 and 19 E.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of the Survey Executed by B. Ives, U.S. Deputy Surveyor, in 1861, and the Resurvey by R.E. Williams, Cadastral Surveyor, in 1985</p> <hr/> <p>From the cor. of secs. 19, 24, 25, and 30, on the E bdy. of the Tp., monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with aluminum cap mkd. as described in the field notes of T. 14 N., R. 20 E., executed under Group No. 624.</p> <p>Cor. is located on level ground in sagebrush and grass at corner of fences, bears S and E.</p> <p>S. 89°35'30" W., bet. secs. 24 and 25.</p>
19.985	<p>Point for the E 1/16 sec. cor. of secs. 24 and 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>S24</p> <p>E 1/16 ———</p> <p>S25</p> <p>1995</p> </div> <p>No trees available for bearing trees.</p>
39.970	<p>Cor. is located on level ground in agricultural area.</p> <p>The 1/4 sec. cor. of secs. 24 and 25, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, buried 6 ins. below the ground, with aluminum cap sheared off, not found, and an iron pipe inside of aluminum post, as described in the field notes of T. 14 N., R. 19 E., executed under Group No. 624.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 46 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T14N R19E S24 1/4 <u>      </u> S25  1995</p> <p>No trees available for bearing trees.</p> <p>Deposit aluminum post and iron pipe alongside of stainless steel post.</p> <p>Set a T post alongside of stainless steel post with a location tag wired to T post.</p> <p>Cor. is located in a producing agricultural field.</p> <hr/> <p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 1 and 2, monumented with an aluminum post, <math>2\frac{1}{2}</math> ins. diam., firmly set, projecting 6 ins. above the ground, with aluminum cap mkd. as described in the field notes of T. 14 N., R. 19 E., executed under Group No. 624, and witnessed by a mound of stone, 3 ft. base, <math>1\frac{1}{2}</math> ft. high, 2 lks. W of cor.</p> <p>Cor. is located on a S slope in sandy soil with sagebrush.</p> <p>N. <math>0^{\circ}36'40''</math> E., bet. secs. 1 and 2.</p>
19.882	<p>The N <math>\frac{1}{16}</math> sec. cor. of secs. 1 and 2, monumented with a rebar, <math>\frac{1}{2}</math> in. diam., firmly set, projecting 5 ins. above the ground, with plastic cap mkd. JAMES P. HADDEN PLS 5286, as recorded in Douglas County, book 297, page 488, document No. 406122, and is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S 2   S 1  1995</p> <p>Deposit rebar alongside of stainless steel post.</p> <p>Cor. is located on a steep N slope near a granite boulder with bitterbrush and sagebrush.</p> <hr/> <p>N. <math>0^{\circ}37'00''</math> E., beginning new measurement.</p>
19.780	<p>The cor. of secs. 1, 2, 35, and 36, on the N bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 26, 27, 34, and 35, monumented with a rebar, <math>\frac{5}{8}</math> in. diam., firmly set, projecting 1 in. above the ground,</p>

016

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

with aluminum cap mkd. 26, 27, 34, 35 LS 3579, as recorded in Douglas County, book 596, page 4802, document No. 388745, and book 1296, page 4975, document No. 403935, and is accepted as a careful and faithful reestablishment of the position of the original cor.

Not remonumented.

Cor. is located on gentle E slope in rocky soil southeasterly of farm buildings.

From this point, the cor. of secs. 25, 26, 35, and 36, bears N. 89°21'50" E., 79.895 chs. dist., monumented with an aluminum post, 2½ ins. diam., firmly set, buried 3 ins. below the ground, with aluminum cap sheared off and lying on surface.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 34 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

T14N	R19E
S26	S25
S35	S36

1995

from which

A railroad tie, 7 x 9 ins. diam., bears East, 8 lks. dist., mkd. with a location tag.

Deposit aluminum post and cap alongside of stainless steel post.

Cor. is located on level ground in corral system on pasture land.

From this same point, the cor. of secs. 2, 3, 34, and 35, on the S bdy. of the Tp., bears S. 0°12'20" W., 80.171 chs. dist., hereinbefore described.

N. 0°13'20" W., bet. secs. 26 and 27.

40.079

The ¼ sec. cor. of secs. 26 and 27, monumented with a rebar, 5/8 in. diam., firmly set, projecting 10 ins. above the ground, with no cap or tag, with the original cornerstone, a metasandstone, 24 x 12 x 4 ins., and chiseled 1/4, alongside rebar, in a mound of stone, 4 ft. diam., 12 ins. high.

Not remonumented.

Cor. is located on an E slope in rocky soil with sagebrush and bitterbrush.

From the ¼ sec. cor. of secs. 10 and 11, monumented with an aluminum post, 2½ ins. diam., firmly set, projecting 3 ins. above the ground, with aluminum cap mkd. as described in the field notes of T. 14 N., R. 19 E., executed under Group No. 624, and witnessed by a mound of stone, 2 ft. base, 1½ ft. high, 2 lks. W of cor.

017

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
19.717	<p>Cor. is located on a S slope along a fence, bears N and S, in sandy soil with scattered sagebrush.</p> <p>N. 0°08'10" W., bet. secs. 10 and 11.</p> <p>Point for the N <sup>1</sup>/<sub>16</sub> sec. cor. of secs. 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 20 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3<sup>1</sup>/<sub>2</sub> ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S10 S11 1995</p> <p>No trees available for bearing trees.</p>
39.434	<p>Cor. is located on steep S slope in sandy soil with sagebrush and bitterbrush.</p> <p>The cor. of secs. 2, 3, 10, and 11, monumented with an aluminum post, 2<sup>1</sup>/<sub>2</sub> ins. diam., firmly set, projecting 8 ins. above the ground, and in a collar of stone, 1<sup>1</sup>/<sub>2</sub> ft. base, to top, with aluminum cap mkd. as described in the field notes of T. 14 N., R. 19 E., executed under Group No. 624.</p> <p>Cor. is located on a steep SW slope on the SW side of a large rock outcrop, in sandy rocky soil with scattered sagebrush.</p>
19.875	<p>From the <sup>1</sup>/<sub>4</sub> sec. cor. of secs. 2 and 11, monumented with an aluminum post, 2<sup>1</sup>/<sub>2</sub> ins. diam., firmly set, projecting 5 ins. above the ground, and in a collar of stone, 2 ft. base, to top, with aluminum cap mkd. as described in the field notes of T. 14 N., R. 19 E., executed under Group No. 624.</p> <p>S. 88°31'40" W., bet. secs. 2 and 11.</p> <p>Point for the W <sup>1</sup>/<sub>16</sub> sec. cor. of secs. 2 and 11.</p> <p>Set a brass tablet, 3<sup>1</sup>/<sub>4</sub> ins. diam., 3<sup>1</sup>/<sub>2</sub>-in. stem, in drill hole in granite boulder, 8 x 3<sup>1</sup>/<sub>2</sub> x 3 ft. high, with top mkd.</p> <p style="text-align: center;">S 2 W 1/16 ——— S11 1995</p>
39.750	<p>from which</p> <p>A boulder, 3 x 1<sup>1</sup>/<sub>2</sub> x 4 ft. high, bears S. 35°30' W., 40.0 lks. dist. to X, mkd. BXO on NE face, 2 ft. above ground.</p> <p>Cor. is located 20 lks. N of ravine, drains S. 70° E., with scattered pine and sagebrush.</p> <p>The cor. of secs. 2, 3, 10, and 11.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 33 and 34, monumented with an embedded mound of stone, 3 ft. diam., 12 ins. high, from which the remains of the original bearing trees</p> <p>A pine snag, 15 ins. diam., bears N. 16° E., 51 lks. dist., mkd. <math>\frac{1}{4}</math> visible in opened blaze. (Record, N. 20° E.)</p> <p>A pine, 26 ins. diam., bears N. 38° W., 36 lks. dist., mkd. 4 visible in opened blaze. (Record, N. 35° W., 33 lks.)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 20 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T14N R19E <math>\frac{1}{4}</math> S33   S34</p> <p style="text-align: center;">1996</p> <p>from which</p> <p>A pine, 19 ins. diam., bears N. 44° E., 76 lks. dist., mkd. <math>\frac{1}{4}</math> S34 BT.</p> <p>Cor. is located on steep E slope in rocky soil with pine and sagebrush.</p> <p>N. 0°14'40" W., bet. secs. 33 and 34.</p>
20.055	<p>The N <math>\frac{1}{16}</math> sec. cor. of secs. 33 and 34, monumented with a rebar, <math>\frac{5}{8}</math> in. diam., firmly set, projecting 6 ins. above the ground, with aluminum cap mkd. RLS 3579, as recorded in Douglas County, book 596, page 4802, document No. 388745, and book 1296, page 4975, document No. 403935, and is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 20 ins. in the ground, over a plastic-encased magnet and in a mound of stone, <math>2\frac{1}{2}</math> ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">N <math>\frac{1}{16}</math> S33   S34</p> <p style="text-align: center;">1996</p> <p>from which</p> <p>A rock outcrop, 21 x 20 x 16 ft. high, bears N. 81°37' E., 140.3 lks. dist. to X, mkd. BXO on SW face, 2 ft. above ground.</p> <p>A boulder, 4 x 4 x 4 ft. high, bears N. 67°09' W., 105.1 lks. dist. to X, mkd. BXO on E face, 3 ft. above ground.</p> <p>Deposit rebar alongside of stainless steel post.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p> <p>20.072</p>	<p>Cor. is located on steep S slope in rocky soil with sagebrush.</p> <hr/> <p>N. 0°16'30" W., beginning new measurement.</p> <p>The cor. of secs. 27, 28, 33, and 34, determined at record bearing and distance from the remains of an original bearing tree</p> <p style="padding-left: 40px;">A mountain mahogany snag, 7 ins. diam., bears S. 16½° W., 159 lks. dist., with the scribe mks. 14NR19E S33 visible on partially healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 2px;">T14N</td> <td style="padding: 2px;">R19E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px;">S28</td> <td style="padding: 2px;">S27</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px;">S33</td> <td style="padding: 2px;">S34</td> </tr> </table> <p style="text-align: center;">1995</p> <p>from which</p> <p style="padding-left: 40px;">A mountain mahogany, 7 ins. diam., bears N. 17° E., 67 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A mountain mahogany, 14 ins. diam., bears S. 36½° E., 57 lks. dist., mkd. T14NR19E S34 BT.</p> <p>Cor. is located on a steep SE slope in rocky soil with scattered mountain mahogany and sagebrush.</p>	T14N	R19E	S28	S27	S33	S34
T14N	R19E						
S28	S27						
S33	S34						
<p>40.155</p>	<hr/> <p>From the cor. of secs. 26, 27, 34, and 35.</p> <p>S. 89°13'50" W., bet. secs. 27 and 34.</p> <p>The ¼ sec. cor. of secs. 27 and 34, monumented with a rebar, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, and in a mound of stone, 1½ ft. diam., with aluminum cap mkd. 27, 34 RLS 3579, as recorded in Douglas County, book 596, page 4802, document No. 388745, and book 1296, page 4975, document No. 403935, and is accepted as a careful and faithful reestablishment of the position of the original cor.</p> <p>Not remonumented.</p> <p>Cor. is located on steep E slope in a ravine, 2 lks. wide, drains E.</p> <hr/> <p>S. 89°13'30" W., beginning new measurement.</p>						

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 40.158</p>	<p>The cor. of secs. 27, 28, 33, and 34.</p>
<p>19.852</p>	<p>N. 0°09'10" W., bet. secs. 27 and 28.</p> <p>Point for the S <math>\frac{1}{16}</math> sec. cor. of secs. 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 25 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S <math>\frac{1}{16}</math> S28   S27</p> <p style="text-align: center;">1995</p> <p>from which</p> <p style="padding-left: 40px;">A mountain mahogany, 11 ins. diam., bears N. 62° E., 13 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A pine, 35 ins. diam., bears N. 54° W., 81 lks. dist., mkd. S <math>\frac{1}{16}</math> S28 BT.</p> <p>Cor. is located on a steep E slope in rocky soil with mountain mahogany and scattered pine and sagebrush.</p>
<p>39.704</p>	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 27 and 28, determined at record dist. from the remains of the original bearing trees</p> <p style="padding-left: 40px;">A pine snag, 39 ins. diam., bears N. 74<math>\frac{1}{4}</math>° E., 27 lks. dist., with the scribe mks. S visible in partially healed blaze. (Record, N. 77° E.)</p> <p style="padding-left: 40px;">A pine, 12 ins. diam., bears N. 79° W., 94 lks. dist., with two healed blazes. (Record, N. 78° W.)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 18 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T14N R19E <math>\frac{1}{4}</math> S28   S27</p> <p style="text-align: center;">1995</p> <p>from which</p> <p style="padding-left: 40px;">A large rock outcrop, bears S. 65°00' E., 58.2 lks. dist. to X, mkd. BXO on NW face, 4 ft. above ground.</p> <p>Cor. is located on a steep NE slope in rocky soil with scattered pine and mountain mahogany.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N. 0°01'20" E., beginning new measurement.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 20.066</p>	<p>Point for the N <math>\frac{1}{16}</math> sec. cor. of secs. 27 and 28.</p> <p>Set a brass tablet, <math>3\frac{1}{4}</math> ins. diam., <math>3\frac{1}{2}</math>-in. stem, in drill hole in large rock outcrop, 8 x 6 x 10 ft. high, with top mkd.</p> <p style="text-align: center;">N <math>\frac{1}{16}</math> S28 S27</p> <p style="text-align: center;">1995</p> <p>from which</p> <p style="padding-left: 40px;">A rock face, 5 x 3 ft. high, bears N. <math>14^{\circ}05'</math> E., 51.2 lks. dist. to X, mkd. BXO on SW face, 1 ft. below the top.</p> <p style="padding-left: 40px;">A rock face, 3 x 6 ft. high, bears N. <math>76^{\circ}37'</math> W., 51.8 lks. dist. to X, mkd. BXO on E face, 3 ft. below the top.</p> <p>Cor. is located on a steep S rocky slope with scattered sagebrush.</p>
<p>30.099</p>	<p>Point for the N-N <math>\frac{1}{64}</math> sec. cor. of secs. 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">N-N <math>\frac{1}{64}</math> S28 S27</p> <p style="text-align: center;">1995</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 17 ins. diam., bears S. <math>77\frac{1}{2}^{\circ}</math> E., 38 lks. dist., mkd. N-N <math>\frac{1}{64}</math> S27 BT.</p> <p style="padding-left: 40px;">A pine, 21 ins. diam., bears S. <math>38^{\circ}</math> W., 81 lks. dist., mkd. N-N <math>\frac{1}{64}</math> S28 BT.</p> <p>Cor. is located on a steep NE slope in loose soil with scattered pine and mountain mahogany.</p>
<p>40.132</p>	<p>The cor. of secs. 21, 22, 27, and 28, monumented with an aluminum post, <math>2\frac{1}{2}</math> ins. diam., firmly set, projecting 6 ins. above the ground, with aluminum cap mkd. as described in the field notes of T. 14 N., R. 19 E., executed under Group No. 624, and witnessed by a scattered mound of stone, 4 ft. base, 1 ft. high, 3 lks. W of cor.</p> <p>Cor. is located on a steep E slope in rocky soil with scattered sagebrush.</p> <hr/> <p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 22 and 27, monumented with an aluminum post, <math>2\frac{1}{2}</math> ins. diam., firmly set, projecting 6 ins. above the ground, with aluminum cap mkd. as described in the field notes of T. 14 N., R. 19 E., executed under Group No. 624, and witnessed by a mound of stone, 3 ft. base, <math>1\frac{1}{2}</math> ft. high, 2 lks. N of cor.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS									
	<p>Cor. is located on level ground in fence, bears N and S, in rocky soil with sagebrush and bitterbrush.</p> <p>S. 88°29'30" W., bet. secs. 22 and 27.</p>								
19.950	<p>Point for the W <math>\frac{1}{16}</math> sec. cor. of secs. 22 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 20 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3<math>\frac{1}{2}</math> ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td></td> <td style="text-align: right;">S22</td> </tr> <tr> <td style="text-align: right;">W <math>\frac{1}{16}</math></td> <td style="text-align: right;">-----</td> </tr> <tr> <td></td> <td style="text-align: right;">S27</td> </tr> <tr> <td></td> <td style="text-align: right;">1996</td> </tr> </table> </div> <p>from which</p> <p>A boulder, 5<math>\frac{1}{2}</math> x 5 x 2<math>\frac{1}{2}</math> ft. high, bears N. 25°30' E., 52.4 lks. dist. to X, mkd. BXO on SW face, 2 ft. above ground.</p> <p>A boulder, 3 x 2 x <math>\frac{1}{2}</math> ft. high, bears S. 45°06' W., 86.5 lks. dist. to X, mkd. BXO on top.</p>		S22	W $\frac{1}{16}$	-----		S27		1996
	S22								
W $\frac{1}{16}$	-----								
	S27								
	1996								
39.900	<p>Cor. is located on a NE slope in rocky soil with sagebrush.</p> <p>The cor. of secs. 21, 22, 27, and 28.</p> <hr/> <p>N. 0°02'00" W., bet. secs. 21 and 22.</p>								
40.540	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 21 and 22, monumented with an aluminum post, 2<math>\frac{1}{2}</math> ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. as described in the field notes of T. 14 N., R. 19 E., executed under Group No. 624, and witnessed by a mound of stone, 2 ft. base, 1 ft. high, 2 lks. W. of cor.</p> <p>From this point, a rebar, <math>\frac{1}{2}</math> in. diam., firmly set, projecting 8 ins. above the ground, and in a mound of stone, 3 ft. base, with no tags or mks. found, bears N. 12°51' W., 87 lks. dist.</p> <hr/> <p>From the cor. of secs. 4, 5, 32, and 33, on the S bdy. of the Tp., monumented with a stainless steel post, 2<math>\frac{1}{2}</math> ins. diam., firmly set, projecting 8 ins. above the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd. as described in the field notes of T. 13 N., R. 19 E., executed under Group No. 620, from which the remains of the original bearing trees</p> <p>A pine stump, size indeterminate, bears S. 86<math>\frac{1}{2}</math>° E., 51 lks. dist., no marks found.</p> <p>A decayed pine stump, size indeterminate, bears S. 4° W., 47 lks. dist., no marks found.</p> <p>A decayed pine stump, size indeterminate, bears N. 62<math>\frac{3}{4}</math>° W., 62 lks. dist., no marks found.</p>								

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

A stump hole, bears N. 12° E., 187 lks. dist., with a pine, dead and down, 24 ins. diam., lying alongside stump hole, with a chaining notch visible in partially healed blaze.

A pine, 21 ins. diam., bears S. 34<sup>1</sup>/<sub>2</sub>° W., 68 lks. dist., with healed upper blaze and partially opened lower blaze, no visible scribing.

A pine stump, 60 ins. diam., bears N. 10° W., 130 lks. dist., with T and a chaining notch visible in partially healed blaze. (Record, N. 8<sup>1</sup>/<sub>2</sub>° W., 126 lks.)

At the corner point

Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 24 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T14N	R19E
S29	S28
S32	S33

1995

from which

A pine, 28 ins. diam., bears N. 15<sup>3</sup>/<sub>4</sub>° E., 240 lks. dist., mkd. T14NR19E S28 BT.

A pine, 25 ins. diam., bears S. 35<sup>1</sup>/<sub>2</sub>° E., 148 lks. dist., mkd. T14NR19E S33 BT.

A pine, 18 ins. diam., bears N. 66<sup>3</sup>/<sub>4</sub>° W., 210 lks. dist., mkd. T14NR19E S29 BT.

Cor. is located on a steep ridge, bears SE and NW, in rocky soil with scattered pine and fir.

From the cor. of secs. 27, 28, 33, and 34.

S. 89°45'00" W., bet. secs. 28 and 33.

19.747 Point for the E <sup>1</sup>/<sub>16</sub> sec. cor. of secs. 28 and 33.

Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

E 1/16	S28
	S33

1996

from which

A cedar, 17 ins. diam., bears S. 3° W., 34 lks. dist., mkd. E 1/16 S33 BT.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>and the 1985 bearing trees</p> <p>A pine, 23 ins. diam., bears N. 72° E., 107 lks. dist., mkd. T14NR19E S33 BT.</p> <p>A pine, 29 ins. diam., bears S. 37<sup>1</sup>/<sub>4</sub>° E., 103 lks. dist., mkd. T13NR19E S4 BT.</p> <p>A pine, 27 ins. diam., bears S. 76<sup>1</sup>/<sub>2</sub>° W., 114 lks. dist., mkd. T13NR19E S5 BT.</p> <p>A pine, 19 ins. diam., bears N. 52<sup>1</sup>/<sub>2</sub>° W., 60 lks. dist., mkd. T14NR19E S32 BT.</p> <p>Cor. is located on a steep S talus slope with pine and manzanita. N. 0°01'30" W., bet. secs. 32 and 33.</p>
39.813	<p>The <sup>1</sup>/<sub>4</sub> sec. cor. of secs. 32 and 33, monumented with an embedded mound of stone, 2<sup>1</sup>/<sub>2</sub> ft. diam., 8 ins. high, from which the remains of the original bearing trees</p> <p>A stump hole, bears S. 79° E., 101 lks. dist., with a pine, dead and down, 12 ins. diam., lying alongside stump hole, with weathered upper and lower blazes and faint scribe marks visible on lower blaze. (Record, S. 76<sup>1</sup>/<sub>2</sub>° E., 100 lks.)</p> <p>A sawed pine stump, 32 ins. diam., bears S. 75° W., 96 lks. dist., no marks found. (Record, S. 72° W., 97 lks.)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 20 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T14N R19E 1/4 S32 S33  1996</p> <p>from which</p> <p>A pine, 13 ins. diam., bears S. 83<sup>3</sup>/<sub>4</sub>° E., 60 lks. dist., mkd. 1/4 S33 BT.</p> <p>A pine, 14 ins. diam., bears N. 21<sup>1</sup>/<sub>2</sub>° W., 114 lks. dist., mkd. 1/4 S32 BT.</p> <p>Cor. is located on steep S slope in rocky soil with mountain mahogany and scattered pine and juniper.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°05'10" W., beginning new measurement.</p>
40.143	<p>The cor. of secs. 28, 29, 32, and 33, monumented with an embedded mound of stone, 5 ft. diam., 12 ins. high, from which the remains of the original bearing trees</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>A pine, 22 ins. diam., bears N. <math>62\frac{1}{4}^{\circ}</math> W., 113 lks. dist., mkd. E 1/16 S28 BT.</p> <p>Cor. is located on a steep SE slope in sandy rocky soil with pine, fir, and cedar.</p> <p>39.494 The <math>\frac{1}{4}</math> sec. cor. of secs. 28 and 33, monumented with a rebar, <math>\frac{5}{8}</math> in. diam., firmly set, projecting 6 ins. above the ground, and in a mound of stone, 3 ft. base, to top, with aluminum cap mkd. 28, 33, RLS 3579, from which the original bearing tree</p> <p>A juniper, 17 ins. diam., bears S. <math>69^{\circ}</math> W., 375 lks. dist., mkd. <math>\frac{1}{4}</math> S on partially healed upper blaze and BT and a chaining notch on partially healed lower blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 20 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T14N R19E S28 <math>\frac{1}{4}</math> ——— S33  1996</p> <p>from which</p> <p>A boulder, 25 x 25 ft. high and flush with the ground, bears N. <math>62^{\circ}55'</math> W., 277.7 lks. dist. to X, mkd. BXO on SE face, 5 ft. above ground.</p> <p>Deposit rebar inside of stainless steel post.</p> <p>Cor. is located on a steep SE talus slope with scattered mountain mahogany and sagebrush.</p> <hr/> <p>S. <math>89^{\circ}26'20''</math> W., beginning new measurement.</p>
39.320	<p>The cor. of secs. 28, 29, 32, and 33.</p> <hr/> <p>N. <math>0^{\circ}28'20''</math> W., bet. secs. 28 and 29.</p>
40.034	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 28 and 29, determined at record bearing and distance from an original bearing tree</p> <p>A pine, 28 ins. diam., bears S. <math>56\frac{1}{2}^{\circ}</math> W., 78 lks. dist., with upper and lower healed blazes.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 18 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T14N R19E 1/4 S29 S28  1995</p> <p>from which</p> <p style="padding-left: 40px;">A boulder, 6 x 4 x 4 ft. high, bears N. 65°50' E., 57.0 lks. dist. to X, mkd. BXO on SW face, 2<sup>1</sup>/<sub>2</sub> ft. above ground.</p> <p>Cor. is located on a steep NE slope in rocky soil with scattered pine, mountain mahogany, and juniper.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°17'50" E., beginning new measurement.</p>
20.039	<p>Point for the N <sup>1</sup>/<sub>16</sub> sec. cor. of secs. 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 24 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S29 S28  1995</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 19 ins. diam., bears S. 72<sup>3</sup>/<sub>4</sub>° E., 23 lks. dist., mkd. N 1/16 S28 BT.</p> <p style="padding-left: 40px;">A pine, 22 ins. diam., bears N. 82<sup>1</sup>/<sub>4</sub>° W., 103 lks. dist., mkd. N 1/16 S29 BT.</p> <p>Cor. is located on a steep N slope in rocky soil with pine and manzanita.</p>
40.078	<p>The cor. of secs. 20, 21, 28, and 29, monumented with an embedded mound of stone, 3 ft. diam., from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A pine stump, 36 ins. diam., bears S. 58° E., 127 lks. dist., with chaining notch visible. (Record, S. 60° E., 124 lks.)</p> <p style="padding-left: 40px;">A pine stump, 44 ins. diam., bears S. 34<sup>1</sup>/<sub>2</sub>° W., 149 lks. dist., with no visible markings. (Record, S. 44<sup>1</sup>/<sub>2</sub>° W., 143 lks.)</p> <p style="padding-left: 40px;">A decayed fir stump, bears N. 25° W., 245 lks. dist., with the fir, dead and down, 36 ins. diam., lying downhill to the E of the stump, with 20 visible in partially healed upper blaze and BT and chaining notch visible in partially healed lower blaze.</p> <p>At the corner point</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS							
	<p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <table border="1" data-bbox="889 394 1039 508"> <tr> <td>T14N</td> <td>R19E</td> </tr> <tr> <td>S20</td> <td>S21</td> </tr> <tr> <td>S29</td> <td>S28</td> </tr> </table> <p>1995</p> <p>from which</p> <p>A pine, 16 ins. diam., bears S. 53° E., 68 lks. dist., mkd. T14NR19E S28 BT.</p> <p>A pine, 13 ins. diam., bears S. 45° W., 134 lks. dist., mkd. T14NR19E S29 BT.</p> <p>A juniper, 13 ins. diam., bears N. 32° W., 246 lks. dist., mkd. T14NR19E S20 BT.</p> <p>Cor. is located on a ridge, bears E and W, in rocky soil with scattered pine, fir, and juniper.</p> <hr/> <p>From the cor. of secs. 21, 22, 27, and 28.</p> <p>S. 89°50'00" W., bet. secs. 21 and 28.</p>	T14N	R19E	S20	S21	S29	S28
T14N	R19E						
S20	S21						
S29	S28						
<p>19.702</p>	<p>Point for the E <sup>1</sup>/<sub>16</sub> sec. cor. of secs. 21 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 24 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <table border="1" data-bbox="808 1249 987 1327"> <tr> <td>E 1/16</td> <td>S21</td> </tr> <tr> <td></td> <td>S28</td> </tr> </table> <p>1995</p> <p>from which</p> <p>A pine, 40 ins. diam., bears S. 49<sup>1</sup>/<sub>2</sub>° W., 80 lks. dist., mkd. E 1/16 S28 BT.</p> <p>A pine, 21 ins. diam., bears N. 28<sup>1</sup>/<sub>2</sub>° W., 36 lks. dist., mkd. E 1/16 S21 BT.</p> <p>Cor. is located on a steep N slope in rocky soil with pine, fir, and sagebrush.</p>	E 1/16	S21		S28		
E 1/16	S21						
	S28						
<p>39.404</p>	<p>The <sup>1</sup>/<sub>4</sub> sec. cor. of secs. 21 and 28, determined at record bearing and distance from an original bearing tree</p> <p>A pine, 31 ins. diam., bears N. 52° W., 115 lks. dist., with healed upper and lower blazes.</p> <p>At the corner point</p>						

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 23 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T14N R19E S21 1/4 <u>        </u> S28  1995</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears S. 18° E., 186 lks. dist., mkd. 1/4 S28 BT.</p> <p>Cor. is located on a steep SE slope, 41 lks. N of ravine, drains N. 52° E., in rocky soil with pine, fir, cedar, mountain mahogany, and sagebrush.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°45'20" W., beginning new measurement.</p>
19.712	<p>Point for the W <sup>1</sup>/<sub>16</sub> sec. cor. of secs. 21 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 24 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S21 W 1/16 <u>        </u> S28  1995</p> <p>from which</p> <p style="padding-left: 40px;">A rock face, 6 x 3 ft. high, bears S. 68° W., 21.9 lks. dist. to X, mkd. BXO on NE face, 1 ft. above ground.</p> <p style="padding-left: 40px;">A rock face, 2 x 2 ft. high, bears N. 3° W., 63.8 lks. dist. to X, mkd. BXO on SE face, 1 ft. above ground.</p> <p>Cor. is located on a steep NE slope in rocky soil with pine, fir, and sagebrush.</p>
39.424	<p>The cor. of secs. 20, 21, 28, and 29.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>N. 0°30'20" W., bet. secs. 20 and 21.</p>
20.159	<p>Point for the S <sup>1</sup>/<sub>16</sub> sec. cor. of secs. 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>

029

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">S 1/16 S20   S21</p> <p style="text-align: center;">1995</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 40 ins. diam., bears S. 32° E., 215 lks. dist., mkd. S 1/16 S21 BT.</p> <p style="padding-left: 40px;">A pine, 35 ins. diam., bears S. 24° W., 323 lks. dist., mkd. S 1/16 S20 BT.</p> <p>Cor. is located on a steep NE slope in rocky soil with pine and sagebrush.</p>
38.736	<p>An original line tree, a fir, 46 ins. diam., in good condition, with upper and lower notches on the N and S faces. This now becomes an angle point</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., set 23 ins. in the ground, and in a mound of stone, 3 ft. base, to top, for a reference monument, bears N. 44°53'30" E., 49.7 lks. dist., with brass cap mkd. RM T14N R19E S21 AP 32.8 FT 1995 and an arrow pointing to the corner.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., set 23 ins. in the ground, and in a mound of stone, 3 ft. base, to top, for a reference monument, bears N. 45°05'30" W., 50.1 lks. dist., with brass cap mkd. RM T14N R19E S20 AP 33.1 FT 1995 and an arrow pointing to the corner.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°30'20" W., beginning new measurement.</p>
1.494	<p>The <sup>1</sup>/<sub>4</sub> sec. cor. of secs. 20 and 21, determined at record bearing and distance from an original bearing tree</p> <p style="padding-left: 40px;">A pine, 24 ins. diam., bears S. 87° W., 142 lks. dist., with healed upper and lower blazes.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 21 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T14N R19E 1/4 S20   S21</p> <p style="text-align: center;">1995</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 21 ins. diam., bears N. 61<sup>1</sup>/<sub>4</sub>° E., 85 lks. dist., mkd. 1/4 S21 BT.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Cor. is located in a steep N draw in rocky soil with pine, fir, and scattered manzanita and chinquapin.</p> <hr/> <p>N. 0°10'00" W., beginning new measurement.</p>
19.879	<p>Point for the N <math>\frac{1}{16}</math> sec. cor. of secs. 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S20 S21</p> <p style="text-align: center;">1995</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 22 ins. diam., bears N. 77° E., 190 lks. dist., mkd. N 1/16 S21 BT.</p> <p style="padding-left: 40px;">A pine, 19 ins. diam., bears S. 65° W., 76 lks. dist., mkd. N 1/16 S20 BT.</p>
39.291	<p>Cor. is located on a steep NE slope, 50 lks. W of a draw, drains N, in rocky soil with fir and scattered pine.</p> <p>An original line tree, a cedar, 40 ins. diam., in good condition, with healed upper and lower blazes on the N and S faces. This now becomes an angle point</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., set 20 ins. in the ground, and in a mound of stone, 3 ft. base, to top, for a reference monument, bears S. 38°19'00" E., 55.9 lks. dist., with brass cap mkd. RM T14N R19E S21 AP 36.9 FT 1995 and an arrow pointing to the corner.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., set 10 ins. in the ground, and in a mound of stone, 4 ft. base, to top, for a reference monument, bears S. 42°28'30" W., 36.1 lks. dist., with brass cap mkd. RM T14N R19E S20 AP 23.8 FT 1995 and an arrow pointing to the corner.</p> <hr/> <p>N. 0°10'00" W., beginning new measurement.</p>
0.435	<p>The cor. of secs. 16, 17, 20, and 21, determined at record dist. from the NE and SE original bearing trees</p> <p style="padding-left: 40px;">A cedar, 42 ins. diam., bears N. 52° E., 14 lks. dist., with 4N9E 16 BT and chaining notch visible in partially healed blaze. (Record, N. 56° E.)</p> <p style="padding-left: 40px;">A cedar, 48 ins. diam., bears S. 77° E., 33 lks. dist., with T14NR19E S2 visible in partially healed upper blaze and healed lower blaze. (Record, S. 79° E.)</p>

031

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

A pine, 54 ins. diam., bears S. 40° W., 70 lks. dist., with  
healed upper and lower blazes. (Record, S. 37° W., 75 lks.)

At the corner point

Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 20 ins.  
in the ground, over a plastic-encased magnet and in a mound of  
stone, 4 ft. base, to top, with brass cap mkd.

T14N	R19E
S17	S16

S20	S21
-----	-----

1995

from which

A granite face, 7 x 4 ft. high, bears S. 45°15' W., 15.2 lks.  
dist. to X, mkd. BXO on NE face, 2 ft. below top.

A pine, 18 ins. diam., bears N. 84° W., 47 lks. dist., mkd.  
T14NR19E S17 BT.

Cor. is located on a steep NE slope in rocky soil with cedar,  
pine, fir, and manzanita.

---

From the cor. of secs. 15, 16, 21, and 22, monumented with an  
aluminum post, 2<sup>1</sup>/<sub>2</sub> ins. diam., firmly set, projecting 4 ins. above  
the ground, with aluminum cap mkd. as described in the field notes  
of T. 14 N., R. 19 E., executed under Group No. 624, from which  
the remains of an original bearing tree, not recovered in the 1985  
survey.

A pine stump, 36 ins. diam., bears S. 68° W., 281 lks. dist.,  
mkd. with an illegible scribe mark.

Cor. is located on gentle E slope in sandy soil with pine and  
scattered sagebrush.

S. 89°15'00" W., bet. secs. 16 and 21.

19.785

Point for the E <sup>1</sup>/<sub>16</sub> sec. cor. of secs. 16 and 21.

Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 23 ins.  
in the ground, over a plastic-encased magnet and in a mound of  
stone, 3 ft. base, to top, with brass cap mkd.

E 1/16	S16
	S21

1995

from which

A cedar, 26 ins. diam., bears N. 20° E., 68 lks. dist., mkd.  
E 1/16 S16 BT.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.570	<p>A cedar, 36 ins. diam., bears S. 64° E., 91 lks. dist., mkd. E 1/16 S21 BT.</p> <p>Cor. is located on a steep SE slope in rocky soil with cedar, pine, and scattered sagebrush, bitterbrush, and manzanita.</p> <p>The 1/4 sec. cor. of secs. 16 and 21, determined at record bearing and distance from the remains of an original bearing tree</p> <p>A stump hole, bears N. 43° W., 81 lks. dist., with a pine, dead and down, 39 ins. diam., lying alongside stump hole, with illegible scribe mks. visible in opened blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T14N R19E S16 1/4 ——— S21  1995</p> <p>from which</p> <p>A pine, 19 ins. diam., bears N. 78 1/4° E., 121 lks. dist., mkd. 1/4 S16 BT.</p> <p>A pine, 9 ins. diam., bears S. 15 1/2° E., 33 lks. dist., mkd. 1/4 S21 BT.</p> <p>Cor. is located on a steep NE slope in sandy soil with pine and fir.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°18'30" W., beginning new measurement.</p>
19.835	<p>Point for the W 1/16 sec. cor. of secs. 16 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S16 W 1/16 ——— S21  1995</p> <p>from which</p> <p>A pine, 15 ins. diam., bears S. 8 1/4° E., 59 lks. dist., mkd. W 1/16 S21 BT.</p> <p>A boulder, 8 x 3 x 7 ft. high, bears N. 73°15' W., 6.5 lks. dist. to X, mkd. BXO on SE face, 2 ft. above ground.</p>

033

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.670	<p>Cor. is located on a steep E slope in rocky soil with pine, fir, and scattered sagebrush.</p> <p>The cor. of secs. 16, 17, 20, and 21.</p> <hr/> <p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 4 and 9, monumented with an aluminum post, <math>2\frac{1}{2}</math> ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. DEPT. OF AGRICULTURE, U.S. FOREST SERVICE, CADASTRAL SURVEY, T14N R19E <math>\frac{1}{4}</math> S4 S9 1993, from which an original bearing tree</p> <p style="padding-left: 40px;">A pine, 36 ins. diam., bears S. <math>70^{\circ}</math> E., 39 lks. dist., mkd. with a healed blaze.</p> <p>and the U. S. Forest Service bearing tree</p> <p style="padding-left: 40px;">A pine, 18 ins. diam., bears N. <math>30^{\circ}</math> W., 64 lks. dist., mkd. <math>\frac{1}{4}</math> S4 BT.</p> <p>Cor. is located on level ground in sandy soil with pine and scattered fir.</p> <p>S. <math>88^{\circ}59'50''</math> W., bet. secs. 4 and 9.</p>
39.489	<p>The cor. of secs. 4, 5, 8, and 9, monumented with an aluminum post, <math>2\frac{1}{2}</math> ins. diam., firmly set, projecting 3 ins. above the ground, and in a mound of stone, 4 ft. base, to top, with aluminum cap mkd. DEPT. OF AGRICULTURE, U.S. FOREST SERVICE, CADASTRAL SURVEY, T14N R19E S4 S5 S8 S9 1993, from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A sawed pine stump, 7 ins. diam., bears N. <math>82\frac{1}{2}^{\circ}</math> E., 148 lks. dist., with no mks. visible. (Record, 146 lks.)</p> <p style="padding-left: 40px;">A stump hole, bears S. <math>11^{\circ}</math> E., 84 lks. dist., with a pine, dead and down, 24 ins. diam., lying alongside stump hole, with no mks. visible. (Record, S. <math>13^{\circ}</math> E.)</p> <p style="padding-left: 40px;">A sawed pine stump, 32 ins. diam., bears S. <math>43^{\circ}</math> W., 271 lks. dist., with no visible mks. found.</p> <p style="padding-left: 40px;">A pine, 22 ins. diam., bears N. <math>32^{\circ}</math> W., 88 lks. dist., mkd. with illegible scribe mks. in opened blaze.</p> <p>and the U. S. Forest Service bearing trees</p> <p style="padding-left: 40px;">A pine, 12 ins. diam., bears N. <math>13^{\circ}</math> E., 68 lks. dist., mkd. T14NR19E S4 BT.</p> <p style="padding-left: 40px;">A pine, 13 ins. diam., bears S. <math>74^{\circ}</math> E., 102 lks. dist., mkd. T14NR19E S9 BT.</p> <p style="padding-left: 40px;">A pine, 32 ins. diam., bears S. <math>38^{\circ}</math> W., 304 lks. dist., mkd. T14NR19E S8 BT.</p> <p>Cor. is located on a steep SE slope in sandy soil with pine, fir and manzanita.</p> <hr/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.966	<p>N. 0°07'00" E., bet. secs. 4 and 5.</p> <p>The <math>\frac{1}{4}</math> sec. cor. of secs. 4 and 5, monumented with an aluminum post, <math>2\frac{1}{2}</math> ins. diam., firmly set, projecting 4 ins. above the ground, and in a mound of stone, <math>3\frac{1}{2}</math> ft. base, to top, with aluminum cap mkd. DEPT. OF AGRICULTURE, U.S. FOREST SERVICE, CADASTRAL SURVEY, T14N R19E <math>\frac{1}{4}</math> S4 S5 1993, and is accepted as the best available evidence of the position of the original cor., from which the U. S. Forest Service bearing trees</p> <p>A pine, 21 ins. diam., bears S. <math>89\frac{3}{4}^{\circ}</math> E., 38 lks. dist., mkd. <math>\frac{1}{4}</math> S4 BT.</p> <p>A pine, 17 ins. diam., bears N. <math>28\frac{3}{4}^{\circ}</math> W., 88 lks. dist., mkd. <math>\frac{1}{4}</math> S5 BT.</p> <p>Cor. is located on NE spur in sandy soil with pine sagebrush, manzanita, and bitterbrush.</p> <hr/> <p>N. 0°10'20" W., beginning new measurement.</p>
40.651	<p>The cor. of secs. 4, 5, 32, and 33, on the N bdy. of the Tp., monumented with a stainless steel post, <math>2\frac{1}{2}</math> ins. diam., firmly set, projecting 4 ins. above the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd. as described in the field notes of T. 15 N., R. 19 E., executed under Group No. 647, from which the 1987-91 bearing trees</p> <p>A pine, 8 ins. diam., bears N. <math>54\frac{1}{2}^{\circ}</math> E., <math>122\frac{1}{2}</math> lks. dist., mkd. XBT. (Record, <math>122\frac{1}{2}</math> lks.)</p> <p>A pine, 8 ins. diam., bears S. <math>24^{\circ}</math> E., 26 lks. dist., mkd. XBT. (Record, S. <math>25\frac{1}{2}^{\circ}</math> E., <math>27\frac{1}{2}</math> lks.)</p> <p>A pine, 5 ins. diam., bears S. <math>13\frac{3}{4}^{\circ}</math> W., 99 lks. dist., no mks.</p> <p>A pine, 10 ins. diam., bears N. <math>74\frac{1}{4}^{\circ}</math> W., 16 lks. dist., mkd. XBT.</p> <p>Cor. is located on an E slope in sandy soil with sagebrush.</p> <hr/> <p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 29 and 32, determined at record distance from the original bearing trees</p> <p>A pine, 10 ins. diam., bears N. <math>77\frac{1}{2}^{\circ}</math> E., 32 lks. dist., with <math>\frac{1}{4}</math> S visible in partially healed upper blaze and BT and chaining notch visible in partially healed lower blaze. (Record, N. <math>82^{\circ}</math> E.)</p> <p>A pine, 8 ins. diam., bears N. <math>54^{\circ}</math> W., 45 lks. dist., with <math>\frac{1}{4}</math> S visible in partially healed upper blaze and BT and chaining notch visible in partially healed lower blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 16 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

035

34

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T14N R19E S29 1/4 ——— S32  1995</p> <p>Cor. is located on the N side of ridge, bears N. 68° W. and S. 68° E., in rocky soil with pine and hemlock.</p> <p>S. 89°33'20" W., bet. secs. 29 and 32.</p> <p>39.615 The cor. of secs. 29, 30, 31, and 32, determined at record distance from the remains of the original bearing trees</p> <p style="padding-left: 40px;">A pine snag, 36 ins. diam., bears S. 66½° E., 416 lks. dist., with T14NR19E S32 BT and chaining notch visible on partially healed blaze. (Record, S. 67½° E.)</p> <p style="padding-left: 40px;">A juniper, 70 ins. diam., bears West, 257 lks. dist., with T14 R19 S30 BT and chaining notch visible in partially healed blaze. (Record, cedar, N. 88° W.)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T14N R19E S30   S29 ——— ——— S31   S32  1994</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 22 ins. diam., bears S. 34° E., 248 lks. dist., mkd. T14NR19E S32 BT.</p> <p>No other suitable trees available for bearing trees.</p> <p>Cor. is located on a steep SE slope in rocky soil with scattered pine, juniper, and sagebrush.</p>
39.390	<p>S. 89°08'50" W., bet. secs. 30 and 31.</p> <p>Point for the ¼ sec. cor. of secs. 30 and 31, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T14N R19E S30 1/4 <u>        </u> S31  1994</p>
	<p>from which</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears N. 2<sup>1</sup>/<sub>4</sub>° E., 45 lks. dist., mkd. 1/4 S30 BT.</p> <p style="padding-left: 40px;">A pine, 11 ins. diam., bears S. 79<sup>1</sup>/<sub>4</sub>° W., 40 lks. dist., mkd. 1/4 S31 BT.</p> <p>Cor. is located on a SW slope in sandy soil with pine, fir, and sagebrush.</p>
77.756	<p>The cor. of secs. 25, 30, 31, and 36, on the W bdy. of the Tp., hereinbefore described.</p> <hr/>
	<p>From the cor. of secs. 29, 30, 31, and 32.</p> <p>N. 0°07'40" W., bet. secs. 29 and 30.</p>
39.211	<p>The <sup>1</sup>/<sub>4</sub> sec. cor. of secs. 29 and 30, monumented with a mound of stone, 3 ft. diam., 12 ins. high, from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A stump hole, bears S. 58° E., 24 lks. dist., with a pine, dead and down, 9 ins. diam., lying alongside stump hole, no scribe mks. visible. (Record, S. 61° E., 28 lks.)</p> <p style="padding-left: 40px;">A stump hole with decayed remains, 14 ins. diam., bears S. 38° W., 23 lks. dist. (Record, S. 31° W.)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T14N R19E 1/4 S30 S29  1994</p>
	<p>from which</p> <p style="padding-left: 40px;">A pine, 9 ins. diam., bears N. 49<sup>3</sup>/<sub>4</sub>° E., 23 lks. dist., mkd. 1/4 S29 BT.</p> <p style="padding-left: 40px;">A pine, 11 ins. diam., bears N. 46<sup>1</sup>/<sub>4</sub>° W., 31 lks. dist., mkd. 1/4 S30 BT.</p> <p>Cor. is located on a steep rocky slope with pine, fir and scattered sagebrush.</p> <hr/>

037

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.013	<p>N. 0°02'10" E., beginning new measurement.</p> <p>Point for the N <math>\frac{1}{16}</math> sec. cor. of secs. 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 16 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">N <math>\frac{1}{16}</math> S30 S29</p> <p style="text-align: center;">1994</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 14 ins. diam., bears S. 80<math>\frac{1}{4}</math>° E., 268 lks. dist., mkd. N <math>\frac{1}{16}</math> S29 BT.</p> <p>Cor. is located on a SE slope in rocky soil with scattered pine, fir, and sagebrush.</p>
32.732	<p>An original line tree, a pine, 31 ins. diam., in good condition, with healed upper and lower blazes on the N and S faces. This now becomes an angle point</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., set 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, for a reference monument, bears S. 42°52'00" E., 75.8 lks. dist., with brass cap mkd. RM T14N R19E S29 AP 50 FT. 1995 and an arrow pointing to the corner.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., set 12 ins. in the ground, and in a mound of stone, 4 ft. base, to top, for a reference monument, bears S. 46°08'40" W., 54.5 lks. dist., with brass cap mkd. RM T14N R19E S30 AP 36 FT. 1995 and an arrow pointing to the corner.</p>
7.502	<p>N. 0°02'10" E., beginning new measurement.</p> <p>The cor. of secs. 19, 20, 29, and 30, monumented with an embedded mound of stone, 3 ft. diam., 8 ins. high, and a rebar, <math>\frac{5}{8}</math> in. diam., firmly set, projecting 2 ins. above the ground, with brass tag mkd. LS 1278, no record of this rebar found, from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A stump hole, bears N. 46<math>\frac{1}{2}</math>° E., 103 lks. dist., with a pine, dead and down, 19 ins. diam., lying alongside stump hole, with BT and a chaining notch visible on partially healed blaze. (Record, N. 54° E., 102 lks.)</p> <p style="padding-left: 40px;">A fir, 38 ins. diam., bears S. 9° W., 52 lks. dist., with healed upper and lower blazes. (Record, S. 11° W., 50 lks.)</p> <p style="padding-left: 40px;">A pine, 25 ins. diam., bears N. 8° W., 23 lks. dist., with scribe mks. 14N 19E visible in partially healed blaze. (Record, N. 13° W., 25 lks.)</p> <p>At the corner point</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS									
	<p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 18 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T14N</td> <td>R19E</td> </tr> <tr> <td>S19</td> <td>S20</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td>S30</td> <td>S29</td> </tr> </table> <p style="text-align: center;">1994</p> <p>from which</p> <p>A pine, 13 ins. diam., bears N. 87<sup>3</sup>/<sub>4</sub>° E., 45 lks. dist., mkd. T14NR19E S20 BT.</p> <p>A pine, 12 ins. diam., bears S. 16<sup>1</sup>/<sub>2</sub>° E., 98 lks. dist., mkd. T14NR19E S29 BT.</p> <p>A fir, 23 ins. diam., bears S. 40<sup>1</sup>/<sub>2</sub>° W., 76 lks. dist., mkd. T14NR19E S30 BT.</p> <p>Deposit rebar alongside of stainless steel post.</p> <p>Cor. is located on a moderate N slope in rocky soil with pine, fir, and sagebrush.</p> <hr/> <p>From the cor. of secs. 20, 21, 28, and 29.</p> <p>S. 88°46'00" W., bet. secs. 20 and 29.</p>	T14N	R19E	S19	S20			S30	S29
T14N	R19E								
S19	S20								
S30	S29								
19.706	<p>Point for the E <sup>1</sup>/<sub>16</sub> sec. cor. of secs. 20 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>E 1/16</td> <td>S20</td> </tr> <tr> <td></td> <td style="border-top: 1px solid black;">S29</td> </tr> </table> <p style="text-align: center;">1995</p> <p>from which</p> <p>A pine, 16 ins. diam., bears S. 53<sup>3</sup>/<sub>4</sub>° W., 105 lks. dist., mkd. E 1/16 S29 BT.</p> <p>A pine, 18 ins. diam., bears N. 28° W., 71 lks. dist., mkd. E 1/16 S20 BT.</p> <p>Cor. is located on a steep S slope in rocky soil with pine, fir, and sagebrush.</p>	E 1/16	S20		S29				
E 1/16	S20								
	S29								
39.412	<p>The <sup>1</sup>/<sub>4</sub> sec. cor. of secs. 20 and 29, monumented with an embedded mound of stone, 3 ft. diam., and a rebar, <sup>1</sup>/<sub>4</sub> in. diam., firmly set, projecting 8 ins. above the ground, no tag or mks., from which the original bearing trees</p>								

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

A hemlock, 20 ins. diam., bears S. 21 $\frac{1}{2}$ ° E., 43 lks. dist.,  
with healed upper and lower blazes. (Record, S. 16 $\frac{1}{2}$ ° E.,  
45 lks.)

A hemlock, 23 ins. diam., bears N. 10° W., 16 lks. dist.,  
with / 4 S visible in partially opened blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 20 ins.  
in the ground, over a plastic-encased magnet and in a mound of  
stone, 3 ft. base, to top, with brass cap mkd.

T14N R19E  
S20  
1/4 ———  
S29

1995

Deposit rebar alongside of stainless steel post.

Cor. is located on a steep N slope in rocky soil with hemlock,  
pine and scattered sagebrush.

S. 88°57'40" W., beginning new measurement.

1.990

An original line tree, a hemlock, 18 ins. diam., in good  
condition, with healed upper and lower notches on the E and W  
faces. This now becomes an angle point

from which

A stainless steel post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., set 20  
ins. in the ground, and in a mound of stone, 2 $\frac{1}{2}$  ft. base, to  
top, for a reference monument, bears N. 46°48'00" E., 14.2  
lks. dist., with brass cap mkd. RM T14N R19E S20 AP 9.4 FT  
1995 and an arrow pointing to the corner.

A stainless steel post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., set 22  
ins. in the ground, and in a mound of stone, 2 $\frac{1}{2}$  ft. base, to  
top, for a reference monument, bears S. 63°18'00" E., 15.3  
lks. dist., with brass cap mkd. RM T14N R19E S29 AP 10.1 FT  
1995 and an arrow pointing to the corner.

S. 88°57'40" W., beginning new measurement.

17.947

Point for the W  $\frac{1}{16}$  sec. cor. of secs. 20 and 29.

Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 22 ins.  
in the ground, over a plastic-encased magnet and in a mound of  
stone, 3 ft. base, to top, with brass cap mkd.

S20  
W 1/16 ———  
S29

1995

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS											
37.871	<p>from which</p> <p>A pine, 6 ins. diam., bears S. <math>9\frac{1}{4}^{\circ}</math> W., 35 lks. dist., mkd. W <math>\frac{1}{16}</math> S29 BT.</p> <p>A pine, 18 ins. diam., bears N. <math>2\frac{3}{4}^{\circ}</math> W., 78 lks. dist., mkd. W <math>\frac{1}{16}</math> S20 BT.</p> <p>Cor. is located on a steep N slope in rocky soil with pine and fir.</p> <p>The cor. of secs. 19, 20, 29, and 30.</p>										
19.795	<p>S. <math>89^{\circ}52'40''</math> W., bet. secs. 19 and 30.</p> <p>Point for the E <math>\frac{1}{16}</math> sec. cor. of secs. 19 and 30.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, <math>3\frac{1}{2}</math> ft. base, to top, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td></td> <td style="text-align: center;">S19</td> </tr> <tr> <td style="text-align: center;">E <math>\frac{1}{16}</math></td> <td style="text-align: center;">—————</td> </tr> <tr> <td></td> <td style="text-align: center;">S30</td> </tr> <tr> <td></td> <td style="text-align: center;">1994</td> </tr> </table>		S19	E $\frac{1}{16}$	—————		S30		1994		
	S19										
E $\frac{1}{16}$	—————										
	S30										
	1994										
39.590	<p>from which</p> <p>A pine, 23 ins. diam., bears S. <math>39\frac{1}{4}^{\circ}</math> W., 111 lks. dist., mkd. E <math>\frac{1}{16}</math> S30 BT.</p> <p>A pine, 17 ins. diam., bears N. <math>53\frac{1}{4}^{\circ}</math> W., 81 lks. dist., mkd. E <math>\frac{1}{16}</math> S19 BT.</p> <p>Cor. is located on a S slope in rocky sandy soil with pine and sagebrush.</p> <p>The <math>\frac{1}{4}</math> sec. cor. of secs. 19 and 30, determined at record bearing and distance from the remains of an original bearing tree</p> <p>A pine snag, 24 ins. diam., bears N. <math>64\frac{1}{2}^{\circ}</math> E., 32 lks. dist., with scribe mks. BT and chaining notch visible on partially healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a plastic-encased magnet and in a mound of stone, <math>2\frac{1}{2}</math> ft. base, to top, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td></td> <td style="text-align: center;">T14N R19E</td> </tr> <tr> <td></td> <td style="text-align: center;">S19</td> </tr> <tr> <td style="text-align: center;"><math>\frac{1}{4}</math></td> <td style="text-align: center;">—————</td> </tr> <tr> <td></td> <td style="text-align: center;">S30</td> </tr> <tr> <td></td> <td style="text-align: center;">1994</td> </tr> </table> <p>from which</p>		T14N R19E		S19	$\frac{1}{4}$	—————		S30		1994
	T14N R19E										
	S19										
$\frac{1}{4}$	—————										
	S30										
	1994										

041

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>A pine, 13 ins. diam., bears N. <math>53\frac{1}{2}^{\circ}</math> E., 49 lks. dist., mkd. <math>\frac{1}{4}</math> S19 BT.</p> <p>A pine, 12 ins. diam., bears S. <math>21\frac{3}{4}^{\circ}</math> E., 27 lks. dist., mkd. <math>\frac{1}{4}</math> S30 BT.</p> <p>Cor. is located on a NE slope in sandy soil with pine and fir.</p> <hr/> <p>From the cor. of secs. 19, 20, 29, and 30.</p> <p>N. <math>0^{\circ}01'20''</math> W., bet. secs. 19 and 20.</p>
20.018	<p>Point for the S <math>\frac{1}{16}</math> sec. cor. of secs. 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S <math>\frac{1}{16}</math> S19 S20 1994</p>
	<p>from which</p> <p>A pine, 15 ins. diam., bears N. <math>35^{\circ}</math> E., 81 lks. dist., mkd. S <math>\frac{1}{16}</math> S20 BT.</p> <p>A pine, 12 ins. diam., bears N. <math>64^{\circ}</math> W., 13 lks. dist., mkd. S <math>\frac{1}{16}</math> S19 BT.</p> <p>Cor. is located on an E slope in rocky soil with pine and fir.</p>
40.036	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 19 and 20, monumented with an embedded mound of stone, 3 ft. diam., 12 ins. high, from which the remains of the original bearing trees</p> <p>A fir snag, 30 ins. diam., bears S. <math>43^{\circ}</math> E., 9 lks. dist., with the scribe mks. BT and chaining notch visible in opened blaze. (Record, S. <math>65^{\circ}</math> E.)</p> <p>A pine, 17 ins. diam., bears S. <math>79^{\circ}</math> W., 17 lks. dist., with a healed blaze partially opened no scribe mks. visible. (Record, S. <math>88^{\circ}</math> W., 14 lks.)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 19 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T14N R19E <math>\frac{1}{4}</math> S19 S20 1994</p> <p>from which</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS									
39.982	<p>A pine, 11 ins. diam., bears N. 65° E., 59 lks. dist., mkd. 1/4 S20 BT.</p> <p>Cor. is located on a steep N slope in rocky soil with pine and fir.</p> <hr/> <p>N. 0°03'20" W., beginning new measurement.</p> <p>The cor. of secs. 17, 18, 19, and 20, monumented with an embedded mound of stone, 4 ft. diam., 12 ins. high, from which the remains of the original bearing trees</p> <p>A pine stump, 28 ins. diam., bears N. 61° E., 32 lks. dist., no mks. found. (Record, N. 59° E., 31 lks.)</p> <p>A fir, 25 ins. diam., bears S. 51° E., 91 lks. dist., mkd. with a healed blaze. (Record, 51 lks.)</p> <p>A pine, 21 ins. diam., bears N. 60° W., 52 lks. dist., mkd. T14N R19E S18 visible in opened blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <table border="1" data-bbox="885 1039 1031 1144"> <tr> <td>T14N</td> <td>R19E</td> </tr> <tr> <td>S18</td> <td>S17</td> </tr> <tr> <td colspan="2"><hr/></td> </tr> <tr> <td>S19</td> <td>S20</td> </tr> </table> <p>1995</p> <p>from which</p> <p>A pine, 23 ins. diam., bears N. 23 3/4° E., 93 lks. dist., mkd. T14NR19E S17 BT.</p> <p>A pine, 15 ins. diam., bears S. 13 1/2° W., 207 lks. dist., mkd. T14NR19E S19 BT.</p> <p>Cor. is located on a steep E slope in rocky soil with scattered pine and fir.</p> <hr/>	T14N	R19E	S18	S17	<hr/>		S19	S20
T14N	R19E								
S18	S17								
<hr/>									
S19	S20								
39.415	<p>From the cor. of secs. 16, 17, 20, and 21.</p> <p>S. 88°53'50" W., bet. secs. 17 and 20.</p> <p>Point for the 1/4 sec. cor. of secs. 17 and 20, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>								

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T14N R19E S17 1/4 <u>        </u> S20  1995</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 12 ins. diam., bears S. 34° W., 82 lks. dist., mkd. 1/4 S20 BT.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 38<sup>1</sup>/<sub>4</sub>° W., 43 lks. dist., mkd. 1/4 S17 BT.</p> <p>Cor. is located on steep E slope in rocky soil with scattered pine and fir.</p>
78.830	<p>The cor. of secs. 17, 18, 19, and 20.</p> <hr/> <p>From the cor. of secs. 7, 8, 17, and 18, monumented with the decayed remains of a wooden post in an embedded mound of stone, 3<sup>1</sup>/<sub>2</sub> ft. diam., 18 ins. high, from which the remaining original bearing trees</p> <p style="padding-left: 40px;">A pine, 30 ins. diam., bears N. 8° E., 77 lks. dist., mkd. with BT and illegible scribe mks. and a chaining notch in partially healed blaze. (Record, 76 lks.)</p> <p style="padding-left: 40px;">A pine, 47 ins. diam., bears N. 29° W., 102 lks. dist., mkd. T14N R19E S7 in partially healed upper blaze and BT and a chaining notch in partially healed lower blaze. (Record, N. 30° W., 100 lks.)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T14N R19E S 7   S 8 <u>        </u> S18   S17  1996</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 21 ins. diam., bears S. 75<sup>3</sup>/<sub>4</sub>° E., 97 lks. dist., mkd. T14NR19E S17 BT.</p> <p style="padding-left: 40px;">A pine, 17 ins. diam., bears S. 30° W., 116 lks. dist., mkd. T14NR19E S18 BT.</p> <p>Cor. is located on a NW slope in sandy soil with pine and scattered fir.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.596	<p>N. 0°11'50" E., bet. secs. 7 and 8.</p> <p>Point for the 1/4 sec. cor. of secs. 7 and 8, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T14N R19E 1/4 S 7   S 8</p> <p style="text-align: center;">1996</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 17 ins. diam., bears S. 73° E., 80 lks. dist., mkd. 1/4 S8 BT.</p> <p style="padding-left: 40px;">A pine, 21 ins. diam., bears N. 31 1/4° W., 80 lks. dist., mkd. 1/4 S7 BT.</p>
79.192	<p>Cor. is located on a SW slope in sandy soil with pine, fir, and sagebrush. North, 129 lks., to a spur, bears E and W, and South, 162 lks., to a ravine, 5 lks. wide, drains N. 80° W.</p> <p>Point for the cor. of secs. 5, 6, 7, and 8, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T14N R19E S 6   S 5 ----- S 7   S 8</p> <p style="text-align: center;">1996</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 67° E., 34 lks. dist., mkd. T14NR19E S5 BT.</p> <p style="padding-left: 40px;">A pine, 15 ins. diam., bears S. 39 3/4° E., 93 lks. dist., mkd. T14NR19E S8 BT.</p> <p style="padding-left: 40px;">A pine, 31 ins. diam., bears S. 80° W., 112 lks. dist., mkd. T14NR19E S7 BT.</p> <p style="padding-left: 40px;">A pine, 28 ins. diam., bears N. 53° W., 137 lks. dist., mkd. X BT.</p> <p>Cor. is located on SE slope in sandy soil with pine and fir.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.149	<p>From the cor. of secs. 4, 5, 8, and 9.</p> <p>S. 88°45'00" W., bet. secs. 5 and 8.</p> <p>The <math>\frac{1}{4}</math> sec. cor. of secs. 5 and 8, determined at record distance from the remains of the original bearing trees</p> <p style="padding-left: 40px;">A fir snag, 31 ins. diam., bears S. 58° E., 76 lks. dist., mkd. <math>\frac{1}{4}</math> S visible in opened blaze. (Record, S. 55° E.)</p> <p style="padding-left: 40px;">A pine stump, 17 ins. diam., bears N. 30° W., 45 lks. dist., with no visible scribe mks. (Record, N. 36° W.)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T14N R19E</p> <p>S 5</p> <hr style="width: 50px; margin: 0 auto;"/> <p><math>\frac{1}{4}</math> S 8</p> <p>1996</p> </div> <p>from which</p> <p style="padding-left: 40px;">A pine, 19 ins. diam., bears N. <math>46\frac{1}{4}</math>° E., 77 lks. dist., mkd. <math>\frac{1}{4}</math> S5 BT.</p> <p style="padding-left: 40px;">A pine, 16 ins. diam., bears S. 19° W., 59 lks. dist., mkd. <math>\frac{1}{4}</math> S8 BT.</p> <p>Cor. is located on NE slope in sandy rocky soil with pine and fir. East, 143 lks., to a ravine, 2 lks. wide, drains N. 55° E., and South, 63 lks., to a ravine, 2 lks. wide, drains N. 70° E.</p> <hr style="width: 200px; margin: 10px auto;"/> <p>S. 89°13'30" W., beginning new measurement.</p>
39.597	<p>The cor. of secs. 5, 6, 7, and 8.</p> <hr style="width: 600px; margin: 10px auto;"/>
39.787	<p>S. 89°58'30" W., bet. secs. 6 and 7.</p> <p>The <math>\frac{1}{4}</math> sec. cor. of secs. 6 and 7, monumented with an embedded mound of stone, <math>2\frac{1}{2}</math> ft. diam., 12 ins. high, from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A decayed pine stump, 34 ins. diam., bears S. 53° W., 8 lks. dist., mkd. BT and chaining notch. (Record, S. 48° W., 7 lks.)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

046

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T14N R19E S 6 1/4 <math>\frac{\quad}{\quad}</math> S 7  1996</p> <p>from which</p> <p>A boulder, 6 x 4 x 2 ft. high, bears N. 89°38' E., 31.0 lks. dist. to X, mkd. BXO at S end, on the top of the boulder.</p> <p>A pine, 18 ins. diam., bears S. 6<sup>3</sup>/<sub>4</sub>° E., 94 lks. dist., mkd. 1/4 S7 BT.</p> <p>Cor. is located on a N slope in sandy soil with pine and scattered fir and manzanita and bitterbrush. East, 300 lks., to a dirt road, 10 lks. wide, bears N. 20° E. and S. 40° W., and at bottom of a ravine, 100 lks. wide, drains N. 20° E.</p> <hr/> <p>S. 89°05'40" W., beginning new measurement.</p>
20.067	<p>Point for the W <sup>1</sup>/<sub>16</sub> sec. cor. of secs. 6 and 7.</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 23 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S 6 W 1/16 <math>\frac{\quad}{\quad}</math> S 7  1996</p> <p>from which</p> <p>A pine, 12 ins. diam., bears N. 38° E., 30 lks. dist., mkd. W 1/16 S6 BT.</p> <p>A pine, 20 ins. diam., bears S. 20<sup>1</sup>/<sub>2</sub>° E., 171 lks. dist., mkd. W 1/16 S7 BT.</p> <p>Cor. is located on steep NE slope in sandy rocky soil with fir and scattered pine.</p>
37.625	<p>The cor. of secs. 1, 6, 7, and 12, on the W bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 5, 6, 7, and 8.</p> <p>N. 0°47'00" W., bet. secs. 5 and 6.</p>
39.600	<p>The <sup>1</sup>/<sub>4</sub> sec. cor. of secs. 5 and 6, monumented with an aluminum post, 2<sup>1</sup>/<sub>2</sub> ins. diam., firmly set, projecting 3 ins. above the ground, and in a mound of stone, 3 ft. base, to top, with aluminum cap mkd. DEPT. OF AGRICULTURE, U.S. FOREST SERVICE, CADASTRAL SURVEY, T14N R19E 1/4 S5 S6 1993, and is accepted as the best available evidence of the position of the original cor., from which the U.S. Forest Service bearing trees</p>

047

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>A fir, 16 ins. diam., bears S. <math>68\frac{1}{4}^{\circ}</math> E., 8 lks. dist., mkd. <math>1/4</math> S5 BT.</p>
	<p>A pine, 10 ins. diam., bears N. <math>81\frac{1}{4}^{\circ}</math> W., 77 lks. dist., mkd. <math>1/4</math> S6 BT.</p>
	<p>Cor. is located in a shallow drainage area in sandy soil with pine and fir.</p>
	<p>_____</p> <p>N. <math>0^{\circ}23'00''</math> W., beginning new measurement.</p>
7.20	<p>U.S. Highway 50, 4 lanes, bears N. <math>82^{\circ}</math> E. and S. <math>82^{\circ}</math> W.</p>
20.453	<p>The N <math>1/16</math> sec. cor. of secs. 5 and 6, monumented with an aluminum post, <math>2\frac{1}{2}</math> ins. diam., firmly set, projecting 2 ins. above the ground, and in a mound of stone, 3 ft. base, to top, with aluminum cap mkd. DEPT. OF AGRICULTURE, U.S. FOREST SERVICE, CADASTRAL SURVEY, T14N R19E N <math>1/16</math> S5 S6 1993, and is accepted as a careful and faithful determination of the position of the cor., from which the U.S. Forest Service bearing trees</p> <p>A pine, 26 ins. diam., bears N. <math>60\frac{1}{2}^{\circ}</math> E., 104 lks. dist., mkd. N <math>1/16</math> S5 BT.</p> <p>A pine, 26 ins. diam., bears S. <math>79\frac{1}{2}^{\circ}</math> W., 45 lks. dist., mkd. N <math>1/16</math> S6 BT.</p> <p>Cor. is located on a steep E slope in sandy soil with pine, fir, and bitterbrush.</p>
	<p>_____</p> <p>N. <math>0^{\circ}22'20''</math> W., beginning new measurement.</p>
8.60	<p>U.S. Highway 50, 4 lanes, on a curve, bears N. <math>57^{\circ}</math> W. and S. <math>60^{\circ}</math> E.</p>
11.216	<p>The witness point, at the intersection of the N right-of-way of HWY 50, and the line between secs. 5 and 6, hereinafter described.</p>
20.662	<p>The cor. of secs. 5, 6, 31, and 32, on the N bdy. of the Tp., hereinbefore described.</p>
	<p>_____</p>
	<p>DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISION-OF-SECTION LINES OF SECTION 1, T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA</p>
	<p>_____</p> <p>Reestablishment of the Survey Executed by R.E. Williams, Cadastral Surveyor, in 1985</p>
	<p>_____</p> <p>From the <math>1/4</math> sec. cor. of secs. 1 and 6, on the E bdy. of the Tp., monumented with an aluminum post, <math>2\frac{1}{2}</math> ins. diam., firmly set, buried 12 ins. below the ground, with aluminum cap mkd. as described in the field notes of T. 14 N., R. 20 E., executed under Group No. 624, from which the 1985 reference monuments</p>

DEPENDENT RESURVEY OF A PORTION OF THE  
SUBDIVISION-OF-SECTION LINES OF SECTION 1,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>An aluminum post, 2<sup>1</sup>/<sub>2</sub> ins. diam., firmly set, projecting 2 ins. above the ground, bears N. 49°54' E., 45.5 lks. dist., mkd. XRM 30 FT 1985 and an arrow pointing to the cor.</p> <p>An aluminum post, 2<sup>1</sup>/<sub>2</sub> ins. diam., firmly set, projecting 1 in. above the ground, bears S. 40°30' E., 45.5 lks. dist., mkd. RM 1/4 S6 30 FT 1985 and an arrow pointing to the cor.</p> <p>Cor. is located below the surface of a graded dirt road, 30 lks. wide, bears E and W.</p> <p>S. 89°40'50" W., on the E and W center line of sec. 1.</p>
20.091	<p>The C-E <sup>1</sup>/<sub>16</sub> sec. cor. of sec. 1, monumented with a rebar, <sup>5</sup>/<sub>8</sub> in. diam., firmly set, projecting 2 ins. above the ground, with brass tag mkd. RLS 1350, as recorded in Douglas County, book 376, page 179, document No. 87622, and in book 1077, page 962, document No. 14081 and is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 23 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 2<sup>1</sup>/<sub>2</sub> ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>E 1/16</p> <p>C ——— C</p> <p>S 1</p> <p>1995</p> </div> <p>No trees available for bearing trees.</p> <p>Deposit rebar alongside of stainless steel post.</p> <p>From this point, an iron pipe, <sup>3</sup>/<sub>4</sub> in. diam., firmly set, projecting 1 in. above the ground, with brass tag mkd. RLS 827, bears S. 1°03' W., 8.5 lks. dist.</p> <p>Cor. is located under a barb wire fence, bears N and S, and on an E slope in sandy soil with sagebrush.</p>
19.917	<p>S. 89°42'40" W., beginning new measurement.</p> <p>The center <sup>1</sup>/<sub>4</sub> sec. cor. of sec. 1, monumented with an aluminum post, 2<sup>1</sup>/<sub>2</sub> ins. diam., firmly set, projecting 5 ins. above the ground, and in a mound of stone, 2<sup>1</sup>/<sub>2</sub> ft. base, to top, with aluminum cap mkd. as described in the field notes of T. 14 N., R. 19 E., executed under Group No. 624, and witnessed by a mound of stone, 3 ft. base, 2 ft. high, 2 lks. W of cor.</p> <p>No trees available for bearing trees.</p> <p>Cor. is located on a SE slope in sandy soil with sagebrush.</p>
20.100	<p>S. 89°38'50" W., beginning new measurement.</p> <p>Point for the C-W <sup>1</sup>/<sub>16</sub> sec. cor. of sec. 1.</p>

049

48

DEPENDENT RESURVEY OF A PORTION OF THE  
SUBDIVISION-OF-SECTION LINES OF SECTION 1,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.200	<p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 24 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">W 1/16 C ——— C S 1</p> <p style="text-align: center;">1995</p> <p>No trees available for bearing trees.</p> <p>Cor. is located on a SE slope in sandy soil with sagebrush.</p> <p>The <sup>1</sup>/<sub>4</sub> sec. cor. of secs. 1 and 2.</p>
9.957	<p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISION-OF-SECTION LINES OF SECTION 24, T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of the Survey Executed by R.E. Williams, Cadastral Surveyor, in 1985</p> <hr/> <p>From the C-S <sup>1</sup>/<sub>16</sub> sec. cor. of sec. 24, monumented with an aluminum post, 2<sup>1</sup>/<sub>2</sub> ins. diam., firmly set, projecting 1 in. above the ground, with aluminum cap mkd. as described in the field notes of T. 14 N., R. 19 E., executed under Group No. 624.</p> <p>Cor. is located in a fence, bears E and W.</p> <p>N. 0°00'10" W., on the N and S center line of sec. 24.</p> <p>Point for the C-N-S <sup>1</sup>/<sub>64</sub> sec. cor. of sec. 30.</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 24 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 2<sup>1</sup>/<sub>2</sub> ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">C-N-S 1/64 S24</p> <p style="text-align: center;">1995</p> <p>No suitable trees available for bearing trees.</p> <p>Cor. is located on a S slope in sandy soil with sagebrush and bitterbrush.</p>
19.914	<p>The center <sup>1</sup>/<sub>4</sub> sec. cor. of sec. 24, monumented with an aluminum post, 2<sup>1</sup>/<sub>2</sub> ins. diam., firmly set, projecting 6 ins. above the ground, with aluminum cap mkd. as described in the field notes of T. 14 N., R. 19 E., executed under Group No. 624, and witnessed by a mound of stone, 3<sup>1</sup>/<sub>2</sub> ft. base, 1 ft. high, 2 lks. W of cor.</p> <hr/> <p>From the <sup>1</sup>/<sub>4</sub> sec. cor. of secs. 19 and 24, on the E bdy. of the Tp., hereinbefore described.</p>

050

DEPENDENT RESURVEY OF A PORTION OF THE  
SUBDIVISION-OF-SECTION LINES OF SECTION 24,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.080	<p>S. 89°22'00" W., on the E and W center line of sec. 24.</p> <p>Point for the C-E <math>\frac{1}{16}</math> sec. cor. of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">E <math>\frac{1}{16}</math> C <math>\frac{\quad}{S24}</math> C S24</p> <p style="text-align: center;">1995</p> <p>No suitable trees available for bearing trees.</p> <p>Cor. is located on a S slope in rocky soil with sagebrush.</p>
30.120	<p>The C-W-E <math>\frac{1}{64}</math> sec. cor. of sec. 24, monumented with an iron pipe, <math>\frac{7}{8}</math> in. diam., firmly set, projecting 4 ins. above the ground, no tags or mks. visible, and no record of this monument found, and is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 23 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">C-W-E <math>\frac{1}{64}</math> S24</p> <p style="text-align: center;">1995</p> <p>Deposit iron pipe alongside of stainless steel post.</p> <p>Cor. is located 36 lks. S of a fence, bears E and W on a steep W slope in rocky soil with sagebrush.</p>
10.048	<p>S. 89°21'40" W., beginning new measurement.</p> <p>The center <math>\frac{1}{4}</math> sec. cor. of sec. 24.</p> <hr/> <p style="text-align: center;">FURTHER SUBDIVISION OF SECTION 1, T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>
20.019	<p>From the C-E <math>\frac{1}{16}</math> sec. cor. of sec. 1.</p> <p>N. 0°02'30" E., on the N and S center line of the NE<math>\frac{1}{4}</math> of sec. 1.</p> <p>The NE <math>\frac{1}{16}</math> sec. cor. of sec. 1, monumented with a rebar, <math>\frac{5}{8}</math> in. diam., firmly set, projecting 4 ins. above the ground, with brass tag mkd. RLS 1350, as recorded in Douglas County, book 376, page 179, document No. 87622, and is accepted as a careful and faithful determination of the position of the cor.</p>

FURTHER SUBDIVISION OF SECTION 1,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S 1</p> <p style="text-align: center;">1995</p> <p>No trees available for bearing trees.</p> <p>Deposit rebar alongside of stainless steel post.</p> <p>Cor. is located on a steep NE slope in sandy soil with sagebrush. S. 4° W., 91 lks., to corner of fences, bears S and W.</p> <hr/> <p>N. 0°17'10" E., beginning new measurement.</p>
16.50	U.S. Highway 50, 4 lanes, bears S. 84° E and N. 84° W.
19.920	<p>The E 1/16 sec. cor. of secs. 1 and 36, on the N bdy. of the Tp., monumented with a stainless steel post, 2<sup>1</sup>/<sub>2</sub> ins. diam., firmly set, projecting 18 ins. above the ground, and in a mound of stone, 3<sup>1</sup>/<sub>2</sub> ft. base, to top, with aluminum cap mkd. as described in the field notes of T. 15 N., R. 19 E., executed under Group No. 734.</p> <p>Cor. is located on a steep S slope in sandy soil with sagebrush and bitterbrush.</p> <hr/> <p>From the N 1/16 sec. cor. of secs. 1 and 6, on the E bdy. of the Tp., monumented with an aluminum post, 2<sup>1</sup>/<sub>2</sub> ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. as described in the field notes of T. 14 N., R. 20 E., executed under Group No. 624.</p> <p>Cor. is located on level ground in sandy soil with sagebrush.</p> <p>S. 89°40'40" W., on the E and W center line of the NE<sup>1</sup>/<sub>4</sub> of sec. 1.</p>
20.050	<p>The NE 1/16 sec. cor. of sec. 1.</p> <hr/> <p>S. 89°27'10" W., beginning new measurement.</p>
19.883	<p>The C-N 1/16 sec. cor. of sec. 1, monumented with an aluminum post, 2<sup>1</sup>/<sub>2</sub> ins. diam., firmly set, projecting 6 ins. above the ground, with aluminum cap mkd. as described in the field notes of T. 14 N., R. 19 E., executed under Group No. 624, and witnessed by a mound of stone, 2 ft. base, 1 ft. high, 3 lks. W of cor.</p> <p>Cor. is located on a steep N slope in sandy soil with sagebrush.</p> <hr/> <p>From the E 1/16 sec. cor. of secs. 1 and 12, monumented with a stainless steel post, 2<sup>1</sup>/<sub>2</sub> ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of T. 14 N., R. 19 E., executed under Group No. 710.</p>

FURTHER SUBDIVISION OF SECTION 1,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.030	<p>Cor. is located on level ground in sandy soil with sagebrush and bitterbrush.</p> <p>N. 0°04'00" W., on the N and S center line of the SE<sup>1</sup>/<sub>4</sub> of sec. 1.</p> <p>The C-E <sup>1</sup>/<sub>16</sub> sec. cor. of sec. 1.</p> <hr/>
19.906	<p>From the C-W <sup>1</sup>/<sub>16</sub> sec. cor. of sec. 1.</p> <p>N. 0°22'40" E., on the N and S center line of the NW<sup>1</sup>/<sub>4</sub> of sec. 1.</p> <p>Point for the NW <sup>1</sup>/<sub>16</sub> sec. cor. of sec. 1, at intersection with the E and W center line of the NW<sup>1</sup>/<sub>4</sub>.</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 24 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S 1</p> <p style="text-align: center;">1995</p> <p>No trees available for bearing trees.</p>
39.757	<p>Cor. is located on a NW slope in sandy soil with sagebrush and bitterbrush.</p> <p>The W <sup>1</sup>/<sub>16</sub> sec. cor. of secs. 1 and 36, on the N bdy. of the Tp., monumented with a stainless steel post, 2<sup>1</sup>/<sub>2</sub> ins. diam., firmly set, projecting 4 ins. above the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd. as described in the field notes of T. 15 N., R. 19 E., executed under Group No. 734, from which the 1993 bearing tree</p> <p style="padding-left: 40px;">A pinion pine, 31 ins. diam., bears N. 9<sup>1</sup>/<sub>4</sub>° E., 73 lks. dist., mkd. W 1/16 S36 BT.</p> <p>Cor. is located on N slope in sandy soil with scattered sagebrush.</p> <hr/>
20.016	<p>From the C-N <sup>1</sup>/<sub>16</sub> sec. cor. of sec. 1.</p> <p>S. 89°34'40" W., on the E and W center line of the NW<sup>1</sup>/<sub>4</sub> of sec. 1.</p> <p>The NW <sup>1</sup>/<sub>16</sub> sec. cor. of sec. 1.</p>
40.035	<p>The N <sup>1</sup>/<sub>16</sub> sec. cor. of secs. 1 and 2.</p> <hr/>
<p>SUBDIVISION OF SECTION 2, T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>	
40.155	<p>From the <sup>1</sup>/<sub>4</sub> sec. cor. of secs. 2 and 11.</p> <p>N. 0°26'10" E., on the N and S center line of sec. 2.</p> <p>The center <sup>1</sup>/<sub>4</sub> sec. cor. of sec. 2, monumented with a rebar, <sup>5</sup>/<sub>8</sub> in. diam., firmly set, projecting 4 ins. above the ground, with plastic cap mkd. JAMES P. HADDEN PLS 5286, as recorded in Douglas</p>

053

SUBDIVISION OF SECTION 2,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>County, book 297, page 488, document No. 406122, and is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 24 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T14N R19E C 1/4 S 2</p> <p style="text-align: center;">1995</p> <p>No suitable trees available for bearing trees.</p> <p>Deposit rebar alongside of stainless steel post.</p> <p>Cor. is located on a SE slope in rocky soil with sagebrush and bitterbrush.</p> <hr/> <p>N. 0°26'00" E., beginning new measurement.</p>
20.080	<p>Point for the C-N <sup>1</sup>/<sub>16</sub> sec. cor. of sec. 2.</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">C N 1/16   S 2 C</p> <p style="text-align: center;">1995</p> <p>from which</p> <p style="padding-left: 40px;">A boulder, 12 x 6 x 6 ft. high, bears N. 27°54' E., 47.5 lks. dist. to X, mkd. BXO on N face, 4<sup>1</sup>/<sub>2</sub> ft. above ground.</p> <p style="padding-left: 40px;">A pine, 14 ins. diam., bears S. 34<sup>1</sup>/<sub>4</sub>° E., 38 lks. dist., mkd. CN 1/16 S2 BT.</p> <p>Cor. is located on a steep NE slope in sandy soil with scattered pine and sagebrush.</p>
39.763	<p>The <sup>1</sup>/<sub>4</sub> sec. cor. of secs. 2 and 35, on the N bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the <sup>1</sup>/<sub>4</sub> sec. cor. of secs. 1 and 2.</p> <p>S. 89°14'40" W., on the E and W center line of sec. 2.</p>
19.871	<p>The C-E <sup>1</sup>/<sub>16</sub> sec. cor. of sec. 2, monumented with a rebar, <sup>5</sup>/<sub>8</sub> in. diam., firmly set, projecting 4 ins. above the ground, with plastic cap mkd. JAMES P. HADDEN PLS 5286, as recorded in Douglas County, book 297, page 488, document No. 406122, and is accepted as a careful and faithful determination of the position of the cor.</p>

SUBDIVISION OF SECTION 2,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 25 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> $\begin{array}{c} E \ 1/16 \\ C \ \frac{\quad}{\quad} \ C \\ S \ 2 \\ 1995 \end{array}$ <p>No suitable trees available for bearing trees.</p> <p>Deposit rebar alongside of stainless steel post.</p> <p>Cor. is located in a draw, drains to the SE, in sandy soil with sagebrush and bitterbrush.</p> <hr/> <p>S. 89°12'50" W., beginning new measurement.</p>
19.870	<p>The center <sup>1</sup>/<sub>4</sub> sec. cor. of sec. 2.</p> <hr/> <p>S. 89°15'40" W., beginning new measurement.</p>
19.435	<p>Point selected for the witness cor. to the C-W <sup>1</sup>/<sub>16</sub> sec. cor. of sec. 2.</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> $\begin{array}{c} WC \\ W \ 1/16 \\ C \ \leftarrow \frac{\quad}{\quad} \ C \\ S \ 2 \\ 1995 \end{array}$ <p>from which</p> <p>A granite boulder, 6 x 3<sup>1</sup>/<sub>2</sub> x 2<sup>1</sup>/<sub>2</sub> ft. high, bears S. 51°50' W., 6.9 lks. dist. to X, mkd. BXO on W face, 2 ft. above ground.</p> <p>A granite boulder, 8 x 7 x 7 ft. high, bears N. 14°38' W., 21.8 lks. dist. to X, mkd. BXO on NW face, 3<sup>1</sup>/<sub>2</sub> ft. above ground.</p> <p>Cor. is located on a W slope near the top of a ridge in rocky soil with sagebrush, bitterbrush, and scattered pine.</p>
19.808	<p>Point for the C-W <sup>1</sup>/<sub>16</sub> sec. cor. of sec. 2, falls on a precipitous ledge, where it is impracticable to establish a permanent monument.</p>
39.616	<p>The <sup>1</sup>/<sub>4</sub> sec. cor. of secs. 2 and 3, monumented with an aluminum post, 2<sup>1</sup>/<sub>2</sub> ins. diam., firmly set, projecting 3 ins. above the</p>

SUBDIVISION OF SECTION 2,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>ground, with aluminum cap mkd. as described in the field notes of T. 14 N., R. 19 E., executed under Group No. 624, and witnessed by a mound of stone, 2<sup>1</sup>/<sub>2</sub> ft. base, 2<sup>1</sup>/<sub>2</sub> ft. high, 3 lks. W of cor.</p> <p>from which</p> <p>A pine, 21 ins. diam., bears N. 74<sup>1</sup>/<sub>2</sub>° E., 63 lks. dist., mkd. 1/4 S2 BT.</p> <p>A pine, 13 ins. diam., bears S. 17<sup>1</sup>/<sub>4</sub>° W., 36 lks. dist., mkd. 1/4 S3 BT.</p> <p>Cor. is located in a N and S saddle in sandy rocky soil with pine and bitterbrush.</p>
19.979	<p>From the C-E <sup>1</sup>/<sub>16</sub> sec. cor. of sec. 2.</p> <p>N. 0°30'30" E., on the N and S center line of the NE<sup>1</sup>/<sub>4</sub> of sec. 2.</p> <p>The NE <sup>1</sup>/<sub>16</sub> sec. cor. of sec. 2, monumented with a rebar, <sup>5</sup>/<sub>8</sub> in. diam., firmly set, projecting 3 ins. above the ground, with plastic cap mkd. JAMES P. HADDEN PLS 5286, as recorded in Douglas County, book 297, page 488, document No. 406122, and is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 24 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S 2 1995</p> <p>No suitable trees available for bearing trees.</p> <p>Deposit rebar alongside of stainless steel post.</p> <p>Cor. is located on a steep NE slope in rocky soil with sagebrush and bitterbrush.</p>
19.728	<p>N. 0°32'20" E., beginning new measurement.</p> <p>The E <sup>1</sup>/<sub>16</sub> sec. cor. of secs. 2 and 35, on the N bdy. of the Tp., hereinbefore described.</p>
19.903	<p>From the N <sup>1</sup>/<sub>16</sub> sec. cor. of secs. 1 and 2.</p> <p>S. 89°31'30" W., on the E and W center line of the NE<sup>1</sup>/<sub>4</sub> of sec. 2.</p> <p>The NE <sup>1</sup>/<sub>16</sub> sec. cor. of sec. 2.</p> <p>S. 89°30'30" W., beginning new measurement.</p>

SUBDIVISION OF SECTION 2,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS 19.894	<p>The C-N <math>\frac{1}{16}</math> sec. cor. of sec. 2.</p> <hr/> <p>From the W <math>\frac{1}{16}</math> sec. cor. of secs. 2 and 11. N. <math>0^{\circ}31'10''</math> E., on the N and S center line of the SW<math>\frac{1}{4}</math> of sec. 2.</p>
40.410	<p>The true point for the C-W <math>\frac{1}{16}</math> sec. cor. of sec. 2.</p> <hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 5, T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 5 and 8. N. <math>0^{\circ}27'50''</math> W., on the N and S center line of sec. 5.</p>
39.944	<p>Point for the center <math>\frac{1}{4}</math> sec. cor. of sec. 5, at intersection with the E and W center line.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 18 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T14N R19E C 1/4 S 5</p> <p style="text-align: center;">1996</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 13 ins. diam., bears S. <math>79^{\circ}</math> E., 23 lks. dist., mkd. C 1/4 S5 BT.</p> <p style="padding-left: 40px;">A fir, 33 ins. diam., bears S. <math>26^{\circ}</math> E., 18 lks. dist., mkd. C 1/4 S5 BT.</p> <p>Cor. is located steep N slope in rocky soil with pine and fir. North, 90 lks., to a creek, 2 lks. wide, course N. <math>81^{\circ}</math> E.</p>
60.422	<p>Point for the C-N <math>\frac{1}{16}</math> sec. cor. of sec. 5.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 23 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">C N 1/16   S 5 C</p> <p style="text-align: center;">1996</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 32 ins. diam., bears N. <math>21\frac{1}{2}^{\circ}</math> E., 39 lks. dist., mkd. CN 1/16 S5 BT.</p> <p style="padding-left: 40px;">A pine, 23 ins. diam., bears S. <math>47\frac{1}{2}^{\circ}</math> E., 69 lks. dist., mkd. CN 1/16 S5 BT.</p>

057

SUBDIVISION OF SECTION 5,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	Cor. is located on E slope in sandy soil with pine, manzanita, sagebrush, and bitterbrush.
80.823	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 5 and 32, on the N bdy. of the Tp., monumented with a stainless steel post, <math>2\frac{1}{2}</math> ins. diam., firmly set, projecting 3 ins. above the ground, and in a collar of stone, 2 ft. base, to top, with brass cap mkd. as described in the field notes of T. 15 N., R. 19 E., executed under Group No. 647, from which the 1987-91 bearing trees</p> <p style="padding-left: 40px;">A pine, 31 ins. diam., bears N. <math>82\frac{1}{4}^{\circ}</math> E., 152 lks. dist., mkd. <math>\frac{1}{4}</math> S32 BT in partially healed blaze.</p> <p style="padding-left: 40px;">A pine, 18 ins. diam., bears S. <math>11\frac{1}{4}^{\circ}</math> W., 62 lks. dist., mkd. <math>\frac{1}{4}</math> S5 BT in partially healed blaze.</p> <p>Cor. is located on E slope in sandy soil with scattered pine and sagebrush.</p> <hr/> <p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 4 and 5.</p> <p>S. <math>88^{\circ}43'50''</math> W., on the E and W center line of sec. 5.</p>
39.550	The center $\frac{1}{4}$ sec. cor. of sec. 5.
79.368	The $\frac{1}{4}$ sec. cor. of secs. 5 and 6.
	<hr/> <p>From the C-N <math>\frac{1}{16}</math> sec. cor. of sec. 5.</p> <p>S. <math>88^{\circ}41'30''</math> W., on the E and W center line of the NW<math>\frac{1}{4}</math> of sec. 5.</p>
27.884	The witness point, at the intersection of the E right-of-way of U.S. Highway 50 and the E and W center line of the NW $\frac{1}{4}$ of sec. 5, hereinafter described.
31.10	U.S. Highway 50, 4 lanes, bears N. $15^{\circ}$ W. and S. $15^{\circ}$ E.
39.787	The N $\frac{1}{16}$ sec. cor. of secs. 5 and 6.
	<hr/> <p>SUBDIVISION OF SECTION 6, T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>
	<p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 6 and 7.</p> <p>N. <math>0^{\circ}33'10''</math> W., on the N and S center line of sec. 6.</p>
19.684	<p>Point for the C-S <math>\frac{1}{16}</math> sec. cor. of sec. 6.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 25 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

SUBDIVISION OF SECTION 6,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;"> <math display="block">\begin{array}{c} C \\ S\ 1/16 \mid S\ 6 \\ C \end{array}</math> </p> <p style="text-align: center;">1996</p> <p>from which</p> <p>A pine, 29 ins. diam., bears N. 82<sup>1</sup>/<sub>4</sub>° E., 52 lks. dist., mkd. CS 1/16 S6 BT.</p> <p>A granite boulder, 8 x 7 x 6 ft. high, bears S. 8°20' E., 74.1 lks. dist. to X, mkd. BXO on N face, 3 ft. below top.</p> <p>Cor. is located a NE slope in sandy soil with scattered pine, fir, sagebrush, and bitterbrush.</p>
37.246	The witness point, at the intersection of the S right-of-way of U.S. Highway 50 and the N and S center line of sec. 6, hereinafter described.
39.368	<p>Point for the center <sup>1</sup>/<sub>4</sub> sec. cor. of sec. 6, falls in busy U. S. Highway 50 and the inherent dangers of attempting to occupy this point preclude setting any standard BLM monument.</p> <p>Set a PK nail, 1<sup>1</sup>/<sub>2</sub> ins. long, <sup>1</sup>/<sub>4</sub> in. diam., in asphalt.</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., set 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, for a reference monument, bears N. 38°48'40" E., 352.6 lks. dist., with brass cap mkd. RM S6 C 1/4 232.7 FT 1996 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., set 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, for a reference monument, bears N. 38°52'00" W., 299.1 lks. dist., with brass cap mkd. RM S6 C 1/4 197.4 FT 1996 and an arrow pointing to the corner.</p>
39.49	U.S. Highway 50, 4 lanes, bears N. 85° E. and S. 85° W.
59.659	<p>Point for the C-N <sup>1</sup>/<sub>16</sub> sec. cor. of sec. 6.</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 24 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;"> <math display="block">\begin{array}{c} C \\ N\ 1/16 \mid S\ 6 \\ C \end{array}</math> </p> <p style="text-align: center;">1996</p> <p>from which</p> <p>A pine, 20 ins. diam., bears S. 9<sup>1</sup>/<sub>2</sub>° W., 34 lks. dist., mkd. CN 1/16 S6 BT.</p>

SUBDIVISION OF SECTION 6,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>A pine, 19 ins. diam., bears S. <math>86\frac{1}{2}^{\circ}</math> W., 46 lks. dist., mkd. X BT.</p> <p>Cor. is located on a steep E slope in sandy soil with pine and scattered fir. SW, 150 lks., to a very large rock outcrop.</p>
80.052	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 6 and 31, on the N bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 5 and 6.</p> <p>S. <math>89^{\circ}38'30''</math> W., on the E and W center line of sec. 6.</p>
19.811	<p>Point for the C-E <math>\frac{1}{16}</math> sec. cor. of sec. 6.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>E 1/16 C ——— C S 6</p> <p>1996</p> </div> <p>from which</p> <p>A pine, 23 ins. diam., bears S. <math>13\frac{1}{2}^{\circ}</math> W., 41 lks. dist., mkd. CE 1/16 S6 BT.</p> <p>A pine, 14 ins. diam., bears N. <math>60^{\circ}</math> W., 7 lks. dist., mkd. X BT.</p> <p>Cor. is located on a NE slope in sandy soil with pine and scattered fir.</p> <p>From this point, a Nevada Highway Department brass disc, <math>3\frac{1}{2}</math> ins. diam., cemented flush with the ground, mkd "STA X 74+15.50 DIST 141.08 ANGLE 90 DATE SET 1957", bears N. <math>87^{\circ}45'50''</math> W., 3.704 chs. dist., and is located on the south side of the highway.</p> <p>From this same point, a Nevada Highway Department brass disc, <math>3\frac{1}{2}</math> ins. diam., cemented flush with the ground, mkd. "STA X 74+15.50 DIST 77.75 ANGLE 90 DATE SET 1957", bears N. <math>55^{\circ}31'20''</math> W., 5.795 chs. dist., and is located on the north side of the highway.</p>
23.583	<p>The witness point, at the intersection of the E right-of-way of U.S. Highway 50 and the E and W center line of sec. 6, hereinafter described.</p>
39.622	<p>The center <math>\frac{1}{4}</math> sec. cor. of sec. 6.</p>
40.45	<p>U.S. Highway 50, 4 lanes, on a curve, bears N. <math>80^{\circ}</math> E. and S. <math>85^{\circ}</math> W.</p>
59.724	<p>Point for the C-W <math>\frac{1}{16}</math> sec. cor. of sec. 6.</p>

SUBDIVISION OF SECTION 6,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
76.665	<p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">W 1/16 C ——— C S 6</p> <p style="text-align: center;">1996</p> <p>from which</p> <p>A pine, 13 ins. diam., bears S. 42<sup>1</sup>/<sub>4</sub>° E., 28 lks. dist., mkd. CW 1/16 S6 BT.</p> <p>A granite boulder, 7 x 6 x 5 ft. high, bears S. 60°21' W., 37.4 lks. dist. to X, mkd. BXO on NE face, 3<sup>1</sup>/<sub>2</sub> ft. above ground.</p> <p>Cor. is located on SW slope in sandy soil with pine and scattered fir.</p>
3.70	<p>The <sup>1</sup>/<sub>4</sub> sec. cor. of secs. 1 and 6, on the W bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the C-E <sup>1</sup>/<sub>16</sub> sec. cor. of sec. 6.</p> <p>N. 0°28'00" W., on the N and S center line of the NE<sup>1</sup>/<sub>4</sub> of sec. 6.</p>
20.372	<p>U.S Highway 50, 4 lanes, bears N. 71° E. and S. 71° W.</p> <p>Point for the NE <sup>1</sup>/<sub>16</sub> sec. cor. of sec. 6, at intersection with the E and W center line of the NE<sup>1</sup>/<sub>4</sub>.</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
40.899	<p style="text-align: center;">NE 1/16 S 6</p> <p style="text-align: center;">1996</p> <p>from which</p> <p>A boulder, 5 x 3 ft. wide and flush with ground, bears S. 47°50' E., 43.2 lks. dist. to X, mkd. BXO on NW face, <sup>1</sup>/<sub>2</sub> ft. above ground.</p> <p>A pine, 15 ins. diam., bears S. 9<sup>1</sup>/<sub>2</sub>° E., 90 lks. dist., mkd. NE 1/16 S6 BT.</p> <p>Cor. is located on NW slope in sandy soil with pine and scattered fir.</p> <p>The E <sup>1</sup>/<sub>16</sub> sec. cor. of secs. 6 and 31, on the N bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the N <sup>1</sup>/<sub>16</sub> sec. cor. of secs. 5 and 6.</p>

SUBDIVISION OF SECTION 6,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
19.840	S. 89°24'40" W., on the E and W center line of the NE <sup>1</sup> / <sub>4</sub> of sec. 6. The NE <sup>1</sup> / <sub>16</sub> sec. cor. of sec. 6.
39.682	The C-N <sup>1</sup> / <sub>16</sub> sec. cor. of sec. 6.
<hr/>	
From the W <sup>1</sup> / <sub>16</sub> sec. cor. of secs. 6 and 7.	
19.779	N. 0°36'30" W., on the N and S center line of the SW <sup>1</sup> / <sub>4</sub> of sec. 6. Point for the SW <sup>1</sup> / <sub>16</sub> sec. cor. of sec. 6, at intersection with the E and W center line of the SW <sup>1</sup> / <sub>4</sub> .
Set a stainless steel post, 28 ins. long, 2 <sup>1</sup> / <sub>2</sub> ins. diam., 23 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.	
SW 1/16 S 6 1996	
from which	
A pine, 7 ins. diam., bears N. 55 <sup>3</sup> / <sub>4</sub> ° E., 34 lks. dist., mkd. X BT.	
A granite boulder, 4 x 4 x 3 ft. high, bears N. 17°48' W., 96.5 lks. dist. to X, mkd. BXO on top face, 3 ft. above ground.	
Cor. is located on NE slope in sandy soil with pine, fir, manzanita, and chinguapin.	
32.339	The witness point, at the intersection of the S right-of-way of U.S. Highway 50 and the N and S center line of the SW <sup>1</sup> / <sub>4</sub> of sec. 6, hereinafter described.
35.10	U.S. Highway 50, 4 lanes, bears N. 74° E. and S. 74° W.
39.559	The C-W <sup>1</sup> / <sub>16</sub> sec. cor. of sec. 6.
<hr/>	
From the C-S <sup>1</sup> / <sub>16</sub> sec. cor. of sec. 6.	
20.084	S. 89°21'50" W., on the E and W center line of the SW <sup>1</sup> / <sub>4</sub> of sec. 6. The SW <sup>1</sup> / <sub>16</sub> sec. cor. of sec. 6.
37.334	The S <sup>1</sup> / <sub>16</sub> sec. cor. of secs. 1 and 6, on the W bdy. of the Tp., hereinbefore described.
<hr/>	
From the C-W <sup>1</sup> / <sub>16</sub> sec. cor. of sec. 6.	
20.214	N. 0°14'00" W., on the N and S center line of the NW <sup>1</sup> / <sub>4</sub> of sec. 6. Point for the NW <sup>1</sup> / <sub>16</sub> sec. cor. of sec. 6, at intersection with the E and W center line of the NW <sup>1</sup> / <sub>4</sub> .

SUBDIVISION OF SECTION 6,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

NW 1/16 S 6

1996

from which

A pine, 13 ins. diam., bears N. 35<sup>1</sup>/<sub>2</sub>° E., 58 lks. dist., mkd.  
X BT.

A pine, 23 ins. diam., bears N. 63<sup>1</sup>/<sub>4</sub>° W., 38 lks. dist., mkd.  
NW 1/16 S6 BT.

Cor. is located on SE slope in sandy soil with pine, fir, and snowbrush.

40.471 The W <sup>1</sup>/<sub>16</sub> sec. cor. of secs. 6 and 31, on the N bdy. of the Tp., hereinbefore described.

From the C-N <sup>1</sup>/<sub>16</sub> sec. cor. of sec. 6.

S. 89°25'00" W., on the E and W center line of the NW<sup>1</sup>/<sub>4</sub> of sec. 6.

19.988 The NW <sup>1</sup>/<sub>16</sub> sec. cor. of sec. 6.

36.512 The N <sup>1</sup>/<sub>16</sub> sec. cor. of secs. 1 and 6, on the W bdy. of the Tp., hereinbefore described.

SUBDIVISION OF SECTION 9,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

From the <sup>1</sup>/<sub>4</sub> sec. cor. of secs. 9 and 16, determined by persons unknown, monumented with a rebar, <sup>5</sup>/<sub>8</sub> in. diam., firmly set, projecting 3 ins. above the ground, and in a mound of stone, 2 ft. base. This position relates harmoniously with the sec. cor. to the east and to the topography call east of the cor. and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 24 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T14N R19E

S 9

1/4

S16

1996

from which

SUBDIVISION OF SECTION 9,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
36.000	<p>A pine, 30 ins. diam., bears S. 80<sup>1</sup>/<sub>4</sub>° E., 119 lks. dist., mkd. 1/4 S16 BT.</p> <p>A pine, 15 ins. diam., bears N. 44° W., 112 lks. dist., mkd. 1/4 S9 BT.</p> <p>Deposit rebar alongside of stainless steel post.</p> <p>Cor. is located on steep NE slope in sandy rocky soil with pine and sagebrush. East, 85 lks., to a ravine, 2 lks. wide, drains N. 34° E. (Record, 95 lks.)</p> <p>From this point, the cor. of secs. 9, 10, 15, and 16, bears N. 89°06'20" E., 39.506 chs. dist., monumented with an iron pipe, 2 ins. diam., firmly set, projecting 3<sup>1</sup>/<sub>2</sub> ft. above ground, as described in the field notes of T. 14 N., R. 19 E., executed under Group No. 624.</p> <p>N. 0°07'40" W., on the N and S center line of sec. 9.</p> <p>Point for a witness point on the N and S center line of sec. 9.</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 24 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>WP T14NR19E C   S 9 C  1996</p> </div> <p>from which</p> <p>A cedar, 31 ins. diam., bears S. 86<sup>1</sup>/<sub>4</sub>° E., 24 lks. dist., mkd. WP S9 BT.</p> <p>A pine, 23 ins. diam., bears S. 31<sup>3</sup>/<sub>4</sub>° W., 79 lks. dist., mkd. X BT.</p> <p>Cor. is located on E slope in sandy soil with pine, cedar, and scattered sagebrush and bitterbrush.</p>
79.419	<p>The <sup>1</sup>/<sub>4</sub> sec. cor. of secs. 4 and 9.</p> <hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 11, T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the <sup>1</sup>/<sub>4</sub> sec. cor. of secs. 11 and 14, monumented with an aluminum post, 2<sup>1</sup>/<sub>2</sub> ins. diam., firmly set, projecting 6 ins. above the ground, with aluminum cap mkd. as described in the field notes of T. 14 N., R. 19 E., executed under Group No. 624, and witnessed by a mound of stone, 3 ft. base, 1<sup>1</sup>/<sub>2</sub> ft. high, 2 lks. N of cor.</p> <p>Cor. is located along a fence, bears N and S, in sandy rocky soil with sagebrush and bitterbrush.</p>

SUBDIVISION OF SECTION 11,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.996	<p>N. 0°03'50" E., on the N and S center line of sec. 11.</p> <p>The center 1/4 sec. cor. of sec. 11, monumented with an iron pipe, 1 in. diam., firmly set, projecting 3 ins. above the ground, with no mks. found, as recorded in Douglas County, book 1172, page 76, document No. 62567, and is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T14N R19E C 1/4 S11</p> <p style="text-align: center;">1995</p> <p>No suitable trees available for bearing trees.</p> <p>Deposit iron pipe alongside of stainless steel post.</p> <p>Cor. is located SW of corner of fences, bears W, N and S, on a gentle S slope in sandy soil with scattered sagebrush.</p>
19.993	<p>N. 0°06'10" E., beginning new measurement.</p> <p>The C-N 1/16 sec. cor. of sec. 11, monumented with a rebar, 1/2 in. diam., firmly set, projecting 5 ins. above the ground, with no mks. found, this cor. position fits harmoniously with the distances shown on the Alpine View Estates map as recorded in Douglas County, book 1172, page 76, document No. 62567, and is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">C N 1/16   S11 C</p> <p style="text-align: center;">1995</p> <p>No suitable trees available for bearing trees.</p> <p>Deposit rebar alongside of stainless steel post.</p> <p>Cor. is located near corner of fences, bears S and W, on a SE slope in sandy soil with sagebrush.</p>
19.986	<p>N. 0°30'10" W., beginning new measurement.</p> <p>The 1/4 sec. cor. of secs. 2 and 11.</p>

SUBDIVISION OF SECTION 11,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 11 and 12, monumented with an aluminum post, <math>2\frac{1}{2}</math> ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. as described in the field notes of T. 14 N., R. 19 E., executed under Group No. 624, and witnessed by a mound of stone, 2 ft. base, 1 ft. high, 2 lks. W of cor. The mks. 1991 were not stamped on cap as described under Group No. 710.</p> <p>Cor. is located on a S slope in sandy soil with sagebrush.</p> <p>S. <math>89^{\circ}18'30''</math> W., on the E and W center line of sec. 11.</p>
39.862	<p>The center <math>\frac{1}{4}</math> sec. cor. of sec. 11.</p> <hr/>
	<p>S. <math>89^{\circ}19'20''</math> W., beginning new measurement.</p>
19.899	<p>The C-W <math>\frac{1}{16}</math> sec. cor. of sec. 11, monumented with an iron pipe, 1 in. diam., firmly set, projecting 1 in. above the ground, with no mks. found, as recorded in Douglas County, book 1172, page 76, document No. 62567, and is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 1 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>W <math>\frac{1}{16}</math></p> <p>C ——— C</p> <p>S11</p> <p>1995</p> </div> <p>No suitable trees available for bearing trees.</p> <p>Deposit iron pipe alongside of stainless steel post.</p> <p>Cor. is located at corner of fences, bears N, S and SE, in sandy soil with sagebrush.</p> <hr/>
19.889	<p>S. <math>89^{\circ}18'20''</math> W., beginning new measurement.</p> <p>The <math>\frac{1}{4}</math> sec. cor. of secs. 10 and 11.</p> <hr/>
20.015	<p>From the C-W <math>\frac{1}{16}</math> sec. cor. of sec. 11.</p> <p>N. <math>0^{\circ}07'50''</math> E., on the N and S center line of the NW<math>\frac{1}{4}</math> of sec. 11.</p> <p>The NW <math>\frac{1}{16}</math> sec. cor. of sec. 11, determined from the remains of a drill hole, in a deteriorating granite outcrop, with a T fence post alongside, this position fits harmoniously with the property lines of the private lots, as recorded in Douglas County, book 1172, page 76, document No. 62567, and is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the corner point</p>

SUBDIVISION OF SECTION 11,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 24 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S11</p> <p style="text-align: center;">1995</p> <p>No suitable trees available for bearing trees.</p> <p>Cor. is located on the NE edge of granite outcrop on a S slope in rocky decomposed granite soil with sagebrush and scattered pine.</p> <hr/> <p>N. 0°27'30" W., beginning new measurement.</p>
19.690	<p>The W <sup>1</sup>/<sub>16</sub> sec. cor. of secs. 2 and 11.</p> <hr/> <p>From the C-N <sup>1</sup>/<sub>16</sub> sec. cor. of sec. 11.</p> <p>S. 89°23'00" W., on the E and W center line of the NW<sup>1</sup>/<sub>4</sub> of sec. 11.</p>
19.888	<p>The NW <sup>1</sup>/<sub>16</sub> sec. cor. of sec. 11.</p> <hr/> <p>S. 88°27'20" W., beginning new measurement.</p>
19.987	<p>The N <sup>1</sup>/<sub>16</sub> sec. cor. of secs. 10 and 11.</p> <hr/>
	<p style="text-align: center;">SUBDIVISION OF SECTION 16, T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the <sup>1</sup>/<sub>4</sub> sec. cor. of secs. 16 and 21.</p> <p>N. 0°02'40" W., on the N and S center line of sec. 16.</p>
36.000	<p>Point for a witness point on the N and S center line of sec. 16.</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">WP T14NR19E C   S16 C</p> <p style="text-align: center;">1996</p> <p>from which</p> <p>A cedar, 19 ins. diam., bears N. 69<sup>1</sup>/<sub>2</sub>° E., 96 lks. dist., mkd. X BT.</p> <p>A pine, 22 ins. diam., bears N. 28<sup>3</sup>/<sub>4</sub>° W., 72 lks. dist., mkd. WP S16 BT.</p>

SUBDIVISION OF SECTION 16,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Cor. is located on spur, slopes S. 60° E., in sandy rocky soil with cedar, pine, and sagebrush.
80.255	The 1/4 sec. cor. of secs. 9 and 16.
<hr/> SUBDIVISION OF SECTION 19, T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA <hr/>	
40.108	<p>From the 1/4 sec. cor. of secs. 19 and 30.          N. 0°01'30" W., on the N and S center line of sec. 19.</p> <p>Point for the center 1/4 sec. cor. of sec. 19, at intersection with the E and W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T14N R19E C 1/4 S19 1994</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 16 ins. diam., bears S. 76° E., 40 lks. dist., mkd. C 1/4 S19 BT.</p> <p style="padding-left: 40px;">A pine, 9 ins. diam., bears N. 9° W., 36 lks. dist., mkd. X BT.</p>
80.044	<p>Cor. is located on a steep N slope in sandy rocky soil with pine and fir.</p> <p>The 1/4 sec. cor. of secs. 18 and 19, monumented with an embedded mound of stone, 3 ft. diam., 12 ins. high, from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A decayed fir stump, 30 ins. diam., bears S. 8° E., 83 lks. dist., mkd. with BT and a chaining notch. (Record, 85 lks.)</p> <p style="padding-left: 40px;">A decayed fir stump, 24 ins. diam., bears N. 51° W., 38 lks. dist., mkd. BT. (Record, 36 lks.)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T14N R19E S18 1/4 ——— S19 1994</p> <p>from which</p>

SUBDIVISION OF SECTION 19,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>A pine, 9 ins. diam., bears N. <math>51\frac{3}{4}^{\circ}</math> E., 81 lks. dist., mkd. 1/4 S18 BT.</p> <p>A pine, 25 ins. diam., bears S. <math>6^{\circ}</math> W., 91 lks. dist., mkd. 1/4 S19 BT.</p> <p>Cor. is located on a steep E slope in sandy soil with scattered pine and fir. North, 268 lks., to a dirt road, 15 lks. wide, bears N. <math>30^{\circ}</math> W. and S. <math>30^{\circ}</math> E., and East, 100 lks., to a dirt road, 15 lks. wide, bears N. <math>25^{\circ}</math> W. and S. <math>25^{\circ}</math> E.</p>
19.794	<p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 19 and 20.</p> <p>S. <math>89^{\circ}58'50''</math> W., on the E and W center line of sec. 19.</p> <p>Point for the C-E <math>\frac{1}{16}</math> sec. cor. of sec. 19.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">E 1/16 C ——— C S19 1994</p> <p>from which</p> <p>A hemlock, 16 ins. diam., bears S. <math>33\frac{1}{4}^{\circ}</math> W., 47 lks. dist., mkd. CE 1/16 S19 BT.</p> <p>A pine, 8 ins. diam., bears N. <math>30\frac{1}{4}^{\circ}</math> W., 28 lks. dist., mkd. X BT.</p> <p>Cor. is located on a steep N slope in sandy rocky soil with pine, hemlock, and fir.</p>
39.588	<p>The center <math>\frac{1}{4}</math> sec. cor. of sec. 19.</p>
77.997	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 19 and 24, on the W bdy. of the Tp., monumented with a mound of stone, 2 ft. base, 8 ins. high, from which an original bearing tree</p> <p>A pine, 29 ins. diam., bears N. <math>20^{\circ}</math> W., 17 lks. dist., with 1/4 S visible in opened blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 20 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T14N R18E R19E 1/4 S24   S19 1994</p>

SUBDIVISION OF SECTION 19,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>from which</p> <p style="padding-left: 40px;">A pine, 25 ins. diam., bears N. 35° E., 35 lks. dist., mkd. 1/4 S19 BT.</p> <p>Cor. is located on a gentle NE slope in sandy rocky soil with pine and sagebrush.</p> <hr/> <p>From the E 1/16 sec. cor. of secs. 19 and 30.</p> <p>N. 0°01'30" W., on the N and S center line of the SE 1/4 of sec. 19.</p> <p>40.072 The C-E 1/16 sec. cor. of sec. 19.</p> <hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 20, T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 20 and 29.</p> <p>N. 0°20'40" W., on the N and S center line of sec. 20.</p> <p>20.099 Point for the C-S 1/16 sec. cor. of sec. 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;"> <math display="block">\begin{array}{c} C \\ S \ 1/16 \   \ S20 \\ C \end{array}</math>             1995         </p> <p>from which</p> <p style="padding-left: 40px;">A pine, 30 ins. diam., bears S. 17 1/4° E., 105 lks. dist., mkd. CS 1/16 S20 BT.</p> <p>Cor. is located on a steep N slope in sandy rocky soil with pine and fir.</p> <p>40.198 Point for the center 1/4 sec. cor. of sec. 20, at intersection with the E and W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">           T14N R19E            C 1/4 S20              1995         </p> <p>from which</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears N. 6 1/4° E., 37 lks. dist., mkd. X BT.</p>
--------	--

SUBDIVISION OF SECTION 20,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>A fir, 17 ins. diam., bears S. <math>43\frac{1}{4}^{\circ}</math> E., 12 lks. dist., mkd. C <math>\frac{1}{4}</math> S20 BT.</p> <p>Cor. is located on a steep SE slope in rocky soil with fir and scattered pine.</p>
80.047	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 17 and 20.</p>
19.648	<p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 20 and 21. S. <math>88^{\circ}42'50''</math> W., on the E and W center line of sec. 20.</p>
	<p>Point for the C-E <math>\frac{1}{16}</math> sec. cor. of sec. 20.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;"> <math display="block">\begin{array}{c} E \frac{1}{16} \\ C \frac{\quad}{\quad} C \\ S20 \\ 1995 \end{array}</math> </p> <p>from which</p> <p>A pine, 9 ins. diam., bears N. <math>51\frac{3}{4}^{\circ}</math> E., 71 lks. dist., mkd. CE <math>\frac{1}{16}</math> S20 BT.</p> <p>A pine, 8 ins. diam., bears S. <math>72\frac{1}{2}^{\circ}</math> E., 68 lks. dist., mkd. X BT.</p> <p>Cor. is located on a steep N slope in rocky soil with pine and fir.</p>
39.296	<p>The center <math>\frac{1}{4}</math> sec. cor. of sec. 20.</p>
59.108	<p>Point for the C-W <math>\frac{1}{16}</math> sec. cor. of sec. 20.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;"> <math display="block">\begin{array}{c} W \frac{1}{16} \\ C \frac{\quad}{\quad} C \\ S20 \\ 1995 \end{array}</math> </p> <p>from which</p> <p>A pine, 20 ins. diam., bears S. <math>51\frac{3}{4}^{\circ}</math> E., 125 lks. dist., mkd. CW <math>\frac{1}{16}</math> S20 BT.</p> <p>A fir, 7 ins. diam., bears S. <math>73\frac{1}{2}^{\circ}</math> W., 85 lks. dist., mkd. X BT.</p> <p>Cor. is located on a very steep E slope in rocky soil with scattered pine and fir.</p>

SUBDIVISION OF SECTION 20,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS 78.920	The 1/4 sec. cor. of secs. 19 and 20.
20.130	<hr/> <p>From the E 1/16 sec. cor. of secs. 20 and 29. N. 0°25'30" W., on the N and S center line of the SE 1/4 of sec. 20. Point for the SE 1/16 sec. cor. of sec. 20, at intersection with the E and W center line of the SE 1/4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S20 1995</p> <p>from which</p> <p style="padding-left: 40px;">A hemlock, 23 ins. diam., bears S. 81° W., 39 lks. dist., mkd. SE 1/16 S20 BT.</p> <p style="padding-left: 40px;">A hemlock, 25 ins. diam., bears N. 1/2° W., 53 lks. dist., mkd. X BT.</p> <p>Cor. is located on a very steep N slope in rocky soil with scattered hemlock and pine.</p>
40.214	The C-E 1/16 sec. cor. of sec. 20.
19.678	<hr/> <p>From the S 1/16 sec. cor. of secs. 20 and 21. S. 88°40'30" W., on the E and W center line of the SE 1/4 of sec. 20.</p>
39.356	The SE 1/16 sec. cor. of sec. 20.
20.056	<hr/> <p>The C-S 1/16 sec. cor. of sec. 20.</p> <hr/> <p>From the W 1/16 sec. cor. of secs. 20 and 29. N. 0°10'10" W., on the N and S center line of the SW 1/4 of sec. 20. Point for the SW 1/16 sec. cor. of sec. 20, at intersection with the E and W center line of the SW 1/4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">SW 1/16 S20 1995</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 24 ins. diam., bears N. 64° E., 110 lks. dist., mkd. SW 1/16 S20 BT.</p>

SUBDIVISION OF SECTION 20,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.113	<p>A pine, 7 ins. diam., bears S. <math>51\frac{1}{4}^{\circ}</math> E., 66 lks. dist., mkd. X BT.</p> <p>Cor. is located on a NE slope in rocky soil with pine and fir.</p> <p>The C-W <math>\frac{1}{16}</math> sec. cor. of sec. 20.</p>
19.874	<p>From the C-S <math>\frac{1}{16}</math> sec. cor. of sec. 20.</p> <p>S. <math>88^{\circ}50'10''</math> W., on the E and W center line of the SW<math>\frac{1}{4}</math> of sec. 20.</p>
39.742	<p>The SW <math>\frac{1}{16}</math> sec. cor. of sec. 20.</p> <p>The S <math>\frac{1}{16}</math> sec. cor. of secs. 19 and 20.</p>

SUBDIVISION OF SECTION 21,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

20.180	<p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 21 and 28.</p> <p>N. <math>0^{\circ}09'20''</math> W., on the N and S center line of sec. 21.</p> <p>Point for the C-S <math>\frac{1}{16}</math> sec. cor. of sec. 21.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 21 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;"> <math display="block">\begin{array}{c} C \\ S \frac{1}{16}   S21 \\ C \end{array}</math>           1995         </p>
40.360	<p>from which</p> <p>A pine, 30 ins. diam., bears S. <math>5\frac{3}{4}^{\circ}</math> E., 81 lks. dist., mkd. CS <math>\frac{1}{16}</math> S21 BT.</p> <p>A pine, 34 ins. diam., bears S. <math>88\frac{3}{4}^{\circ}</math> W., 30 lks. dist., mkd. CS <math>\frac{1}{16}</math> S21 BT.</p> <p>Cor. is located 30 lks. N of a dirt road, 15 lks. wide, bears S. <math>45^{\circ}</math> E. and N. <math>45^{\circ}</math> W., on a steep NE slope in rocky soil with pine, fir, cedar, mountain mahogany, and chinquapin brush.</p> <p>Point for the center <math>\frac{1}{4}</math> sec. cor. of sec. 21, at intersection with the E and W center line.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 20 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">           T14N R19E            C <math>\frac{1}{4}</math> S21            1995         </p>

SUBDIVISION OF SECTION 21,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
60.312	<p>No suitable trees available for bearing trees.</p> <p>Cor. is located on a steep NW slope in rocky soil with mountain mahogany, manzanita, and sagebrush.</p> <p>Point for the C-N <math>\frac{1}{16}</math> sec. cor. of sec. 21.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 23 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;"> <math display="block">\begin{array}{c} C \\ N \frac{1}{16}   S21 \\ C \end{array}</math>           1995         </p> <p>from which</p> <p style="padding-left: 40px;">A pine, 6 ins. diam., bears N. <math>88\frac{1}{4}^\circ</math> E., 16 lks. dist., mkd. CN <math>\frac{1}{16}</math> S21 BT.</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears N. <math>49\frac{1}{4}^\circ</math> W., 12 lks. dist., mkd. CN <math>\frac{1}{16}</math> S21 BT.</p>
80.264	<p>Cor. is located on a steep NE slope in rocky soil with pine, fir, and manzanita, sagebrush, and bitterbrush.</p> <p>The <math>\frac{1}{4}</math> sec. cor. of secs. 16 and 21.</p>
19.741	<p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 21 and 22.</p> <p>S. <math>89^\circ 34' 10''</math> W., on the E and W center line of sec. 21.</p> <p>Point for the C-E <math>\frac{1}{16}</math> sec. cor. of sec. 21.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;"> <math display="block">\begin{array}{c} E \frac{1}{16} \\ C \frac{\quad}{S21} C \\ 1995 \end{array}</math> </p> <p>from which</p> <p style="padding-left: 40px;">A pine, 19 ins. diam., bears N. <math>83^\circ</math> W., 83 lks. dist., mkd. CE <math>\frac{1}{16}</math> S21 BT.</p> <p style="padding-left: 40px;">A pine, 27 ins. diam., bears N. <math>17^\circ</math> W., 184 lks. dist., mkd. CE <math>\frac{1}{16}</math> S21 BT.</p>
39.482	<p>Cor. is located 50 lks. S of a ravine, drains S. <math>45^\circ</math> E., on a steep E slope in rocky soil with pine, manzanita, and sagebrush.</p> <p>The center <math>\frac{1}{4}</math> sec. cor. of sec. 21.</p>
59.316	<p>Point for the C-W <math>\frac{1}{16}</math> sec. cor. of sec. 21.</p>

SUBDIVISION OF SECTION 21,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a brass tablet, <math>3\frac{1}{4}</math> ins. diam., <math>3\frac{1}{2}</math>-in. stem, in drill hole in rock outcrop, 1 x 3 x 2 ft. high, with top mkd.</p> <p style="text-align: center;">W 1/16 C ——— C S21 1995</p> <p>from which</p> <p>A pine, 23 ins. diam., bears S. <math>21^\circ</math> E., 140 lks. dist., mkd. CW 1/16 S21 BT.</p> <p>An exposed rock face, 3 x 3 x 4 ft. high, bears N. <math>89^\circ 58'</math> W., 14.9 lks. dist. to X, mkd. BXO on E face, 3 ft. above ground.</p> <p>Cor. is located on a steep NE slope in rocky soil with pine, scattered fir and manzanita.</p>
69.233	<p>Point for the C-W-W <math>\frac{1}{64}</math> sec. cor. of sec. 21.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">C-W-W 1/64 S21 1995</p> <p>from which</p> <p>A pine, 30 ins. diam., bears N. <math>23\frac{3}{4}^\circ</math> E., 37 lks. dist., mkd. CWW 1/64 S21 BT.</p> <p>A pine, 9 ins. diam., bears S. <math>58\frac{1}{2}^\circ</math> E., 54 lks. dist., mkd. X BT.</p> <p>Cor. is located on a NE slope in rocky soil with pine, fir, cedar, and chinquapin brush. East, 2.90 chs., to a ridge, bears N. <math>11^\circ</math> E. and S. <math>11^\circ</math> W.</p>
79.150	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 20 and 21.</p> <hr/> <p>From the C-E <math>\frac{1}{16}</math> sec. cor. of sec. 21.</p> <p>N. <math>0^\circ 05' 30''</math> W., on the N and S center line of the NE <math>\frac{1}{4}</math> of sec. 21.</p>
20.007	<p>Point for the NE <math>\frac{1}{16}</math> sec. cor. of sec. 21, at intersection with the E and W center line of the NE <math>\frac{1}{4}</math>.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

SUBDIVISION OF SECTION 21,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>NE 1/16 S21</p> <p>1995</p> <p>from which</p> <p>A pine, 33 ins. diam., bears N. 8° E., 208 lks. dist., mkd. NE 1/16 S21 BT.</p> <p>A pine, 46 ins. diam., bears N. 17° W., 115 lks. dist., mkd. NE 1/16 S21 BT.</p> <p>Cor. is located 1 ch. N of a dirt road, 23 lks. wide, bears S. 80° E. and W, on an E slope in rocky soil with scattered pine, manzanita, and sagebrush.</p>
40.016	The E <sup>1</sup> / <sub>16</sub> sec. cor. of secs. 16 and 21.
	<hr/> <p>From the N <sup>1</sup>/<sub>16</sub> sec. cor. of secs. 21 and 22, monumented with an aluminum post, 2<sup>1</sup>/<sub>2</sub> ins. diam., firmly set, projecting 3 ins. above the ground, with aluminum cap mkd. as described in the field notes of T. 14 N., R. 19 E., executed under Group No. 624, and witnessed by a mound of stone, 2<sup>1</sup>/<sub>2</sub> ft. base, 1<sup>1</sup>/<sub>2</sub> ft. high, 2 lks. W of cor.</p> <p>S. 89°24'50" W., on the E and W center line of the NE<sup>1</sup>/<sub>4</sub> of sec. 21.</p>
19.761	The NE <sup>1</sup> / <sub>16</sub> sec. cor. of sec. 21.
39.524	The C-N <sup>1</sup> / <sub>16</sub> sec. cor. of sec. 21.
	<hr/> <p>From the C-S <sup>1</sup>/<sub>16</sub> sec. cor. of sec. 21.</p> <p>S. 89°43'30" W., on the E and W center line of the SW<sup>1</sup>/<sub>4</sub> of sec. 21.</p>
39.545	The S <sup>1</sup> / <sub>16</sub> sec. cor. of secs. 20 and 21.
	<hr/> <p>From the C-W <sup>1</sup>/<sub>16</sub> sec. cor. of sec. 21.</p> <p>N. 0°09'40" W., on the N and S center line of the NW<sup>1</sup>/<sub>4</sub> of sec. 21.</p>
19.916	<p>Point for the NW <sup>1</sup>/<sub>16</sub> sec. cor. of sec. 21, at intersection with the E and W center line of the NW<sup>1</sup>/<sub>4</sub>.</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 20 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>
	<p>NW 1/16 S21</p> <p>1995</p> <p>from which</p> <p>A boulder, 6 x 6 x 4<sup>1</sup>/<sub>2</sub> ft. high, bears S. 28°17' W., 19.5 lks. dist. to X, mkd. BXO on NE face, 1 ft. above ground.</p>

SUBDIVISION OF SECTION 21,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>A pine, 35 ins. diam., bears N. <math>63\frac{3}{4}^{\circ}</math> W., 80 lks. dist., mkd. NW <math>\frac{1}{16}</math> S21 BT.</p> <p>Cor. is located on a steep NE slope in rocky soil with pine, fir, manzanita, and sagebrush.</p>
39.815	<p>The W <math>\frac{1}{16}</math> sec. cor. of secs. 16 and 21.</p> <hr/>
	<p>From the C-N <math>\frac{1}{16}</math> sec. cor. of sec. 21.</p> <p>S. <math>89^{\circ}27'40''</math> W., on the E and W center line of the NW<math>\frac{1}{4}</math> of sec. 21.</p>
19.834	<p>The NW <math>\frac{1}{16}</math> sec. cor. of sec. 21.</p>
29.751	<p>Point for the C-W-NW <math>\frac{1}{64}</math> sec. cor. of sec. 21.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">C-W-NW <math>\frac{1}{64}</math> S21  1995</p> <p>from which</p> <p>A pine, 28 ins. diam., bears N. <math>27\frac{3}{4}^{\circ}</math> E., 58 lks. dist., mkd. CWNW <math>\frac{1}{64}</math> S21 BT.</p> <p>A pine, 16 ins. diam., bears N. <math>56\frac{1}{2}^{\circ}</math> W., 46 lks. dist., mkd. CWNW <math>\frac{1}{64}</math> S21 BT.</p> <p>Cor. is located on a steep NW slope in rocky soil with pine, fir, mountain mahogany, and sagebrush.</p>
39.668	<p>The N <math>\frac{1}{16}</math> sec. cor. of secs. 20 and 21.</p> <hr/> <p>From the C-W-W <math>\frac{1}{64}</math> sec. cor. of sec. 21.</p> <p>N. <math>0^{\circ}09'50''</math> W., on the N and S center line of the SW<math>\frac{1}{4}</math> of the NW<math>\frac{1}{4}</math> of sec. 21.</p>
19.897	<p>The C-W-NW <math>\frac{1}{64}</math> sec. cor. of sec. 21.</p> <hr/>
	<p style="text-align: center;">FURTHER SUBDIVISION OF SECTION 24, T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the E <math>\frac{1}{16}</math> sec. cor. of secs. 24 and 25.</p> <p>N. <math>0^{\circ}08'50''</math> E., on the N and S center line of the SE<math>\frac{1}{4}</math> of sec. 24.</p> <p>19.955 Point for the SE <math>\frac{1}{16}</math> sec. cor. of sec. 24, at intersection with the E and W center line of the SE<math>\frac{1}{4}</math>. An iron pipe, <math>\frac{3}{4}</math> in. diam. was recovered 6 ins. below the surface lying horizontally, no record of iron pipe found.</p>

FURTHER SUBDIVISION OF SECTION 24,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S24</p> <p style="text-align: center;">1995</p> <p>No suitable trees available for bearing trees.</p> <p>Deposit iron pipe alongside of stainless steel post.</p> <p>Cor. is located 1.70 chs. S of a gravel road, 42 lks. wide, bears N. 80° E. and S. 80° W., in an agricultural area in sandy soil with scattered sagebrush.</p>
29.940	<p>The C-N-SE 1/64 sec. cor. of sec. 24, monumented with an iron pipe, 3/4 in. diam., firmly set, projecting 3 ins. above the ground, no tags or mks. visible, and no record of this monument found, and is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">C-N-SE 1/64 S24</p> <p style="text-align: center;">1995</p> <p>No suitable trees available for bearing trees.</p> <p>Deposit iron pipe alongside of stainless steel post.</p> <p>Cor. is located on a S slope in rocky soil with scattered sagebrush.</p>
9.971	<p style="text-align: center;">N. 0°06'20" E., beginning new measurement.</p> <p>The C-E 1/16 sec. cor. of sec. 24.</p>
20.033	<p>From the S 1/16 sec. cor. of secs. 19 and 24, on the E bdy. of the Tp., hereinbefore described.</p> <p>S. 89°29'10" W., on the E and W center line of the SE 1/4 of sec. 24.</p>
30.032	<p>The SE 1/16 sec. cor. of sec. 24.</p>
30.032	<p>The C-W-SE 1/64 sec. cor. of sec. 24, monumented with an iron pipe, 3/4 in. diam., firmly set, 6 ins. below the ground, no tags or mks. visible, and no record of this monument found, and is accepted as a careful and faithful determination of the position of the cor. This position falls in a well travelled gravel road.</p> <p>At the corner point</p>

FURTHER SUBDIVISION OF SECTION 24,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a copper rod, 24 ins. long, <math>\frac{1}{2}</math> in. diam., 10 ins. below the ground, with <math>1\frac{1}{2}</math> in. brass cap mkd. X 1995.</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., set 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, for a reference monument, bears S. <math>53^{\circ}53'</math> E., 100 lks. dist., with brass cap mkd. RM S24 C-W-SE <math>\frac{1}{64}</math> 66FT 1995 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., set 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, for a reference monument, bears S. <math>36^{\circ}07'</math> W., 100 lks. dist., with brass cap mkd. RM S24 C-W-SE <math>\frac{1}{64}</math> 66FT 1995 and an arrow pointing to the corner.</p> <p>No suitable trees available for bearing trees.</p> <p>Deposit iron pipe alongside of copper rod.</p> <p>Cor. is located in a gravel road, 45 lks. wide, bears N. <math>75^{\circ}</math> E. and S. <math>75^{\circ}</math> W.</p> <hr/> <p>S. <math>89^{\circ}29'20''</math> W., beginning new measurement.</p>
10.045	<p>The C-S <math>\frac{1}{16}</math> sec. cor. of sec. 24.</p> <hr/> <p>From the N-S <math>\frac{1}{64}</math> sec. cor. of secs. 19 and 24, on the E bdy. of the Tp., hereinbefore described.</p> <p>S. <math>89^{\circ}26'50''</math> W., on the E and W center line of the NE<math>\frac{1}{4}</math> of the SE<math>\frac{1}{4}</math> of sec. 24.</p>
20.053	<p>The C-N-SE <math>\frac{1}{64}</math> sec. cor. of sec. 24.</p> <hr/> <p>From the C-W-SE <math>\frac{1}{64}</math> sec. cor. of sec. 24.</p> <p>N. <math>0^{\circ}00'40''</math> E., on the N and S center line of the NW<math>\frac{1}{4}</math> of the SE<math>\frac{1}{4}</math> of sec. 24.</p>
9.967	<p>The NW-SE <math>\frac{1}{64}</math> sec. cor. of sec. 24, monumented with an iron pipe, <math>\frac{3}{4}</math> in. diam., firmly set, projecting 3 ins. above the ground, no tags or mks. visible, and no record of this monument found, and is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">NW-SE 1/64 S24 1995</p>

FURTHER SUBDIVISION OF SECTION 24,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>No suitable trees available for bearing trees.</p> <p>Deposit iron pipe alongside of stainless steel post.</p> <p>Cor. is located on a S slope in rocky soil with scattered sagebrush.</p> <hr/>
9.968	<p>N. 0°00'10" E., beginning new measurement.</p> <p>The C-W-E <math>\frac{1}{64}</math> sec. cor. of sec. 24.</p> <hr/>
10.022	<p>From the C-N-SE <math>\frac{1}{64}</math> sec. cor. of sec. 24.</p> <p>S. 89°22'50" W., on the E and W center line of the NW<math>\frac{1}{4}</math> of the SE<math>\frac{1}{4}</math> of sec. 24.</p> <p>The NW-SE <math>\frac{1}{64}</math> sec. cor. of sec. 24.</p> <hr/>
10.047	<p>S. 89°25'40" W., beginning new measurement.</p> <p>The C-N-S <math>\frac{1}{64}</math> sec. cor. of sec. 24.</p> <hr/>
39.959	<p>From the C-S <math>\frac{1}{16}</math> sec. cor. of sec. 24.</p> <p>S. 89°29'40" W., on the E and W center line of the SW<math>\frac{1}{4}</math> of sec. 24.</p> <p>The S <math>\frac{1}{16}</math> sec. cor. of secs. 23 and 24, monumented with an aluminum post, 2<math>\frac{1}{2}</math> ins. diam., firmly set, projecting 3 ins. above the ground, with aluminum cap mkd. as described in the field notes of T. 14 N., R. 19 E., executed under Group No. 624, and witnessed by a mound of stone, 4 ft. base, 2 ft. high, 4 lks. W of cor.</p> <p>Cor. is located on a gentle slope in rocky soil with sagebrush.</p> <hr/>
	<p style="text-align: center;">SUBDIVISION OF SECTION 27, T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>
39.888	<p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 27 and 34.</p> <p>N. 0°15'00" W., on the N and S center line of sec. 27.</p> <p>The center <math>\frac{1}{4}</math> sec. cor. of sec. 27, monumented with a rebar, <math>\frac{5}{8}</math> in. diam., firmly set, projecting 2 ins. above the ground, with aluminum cap mkd. C 1/4 SEC 27 RLS 3579, as recorded in Douglas County, book 596, page 4802, document No. 388745, and book 1296, page 4975, document No. 403935, and is accepted as a careful and faithful determination of the position of the cor.</p> <p>Cor. is located on steep NE slope in sandy soil with sagebrush and bitterbrush.</p> <p>Not remonumented.</p> <hr/>
	<p>N. 0°14'40" W., beginning new measurement.</p>

SUBDIVISION OF SECTION 27,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS 20.229	<p>The C-N <math>\frac{1}{16}</math> sec. cor. of sec. 27, monumented with a rebar, <math>\frac{5}{8}</math> in. diam., firmly set, projecting 5 ins. above the ground, and in a collar of stone, <math>1\frac{1}{2}</math> ft. diam., with aluminum cap mkd. C 1/16 S27 C RLS 3579, as recorded in Douglas County, book 596, page 4802, document No. 388745, and book 1296, page 4975, document No. 403935, and is accepted as a careful and faithful determination of the position of the cor.</p> <p>Not remonumented.</p> <p>Cor. is located on an E slope in sandy rocky soil with sagebrush and bitterbrush.</p>
	<p>N. <math>0^{\circ}16'40''</math> W., beginning new measurement.</p>
10.112	<p>The C-N-N <math>\frac{1}{64}</math> sec. cor. of sec. 27, monumented with a rebar, <math>\frac{5}{8}</math> in. diam., firmly set, projecting 2 ins. above the ground, with aluminum cap mkd. 1/64 COR RLS 3579, as recorded in Douglas County, book 596, page 4802, document No. 388745, and is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 21 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">C-N-N 1/64 S27 1996</p> <p>No trees available for bearing trees.</p> <p>Deposit rebar alongside of stainless steel post.</p> <p>Cor. is located on an E slope in rocky soil with sagebrush and bitterbrush. West, <math>3\frac{1}{2}</math> lks., to a fence, bears N and S.</p>
	<p>N. <math>0^{\circ}14'00''</math> W., beginning new measurement.</p>
10.114	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 22 and 27.</p> <hr/> <p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 26 and 27.</p> <p>S. <math>88^{\circ}57'40''</math> W., on the E and W center line of sec. 27.</p>
40.172	<p>The center <math>\frac{1}{4}</math> sec. cor. of sec. 27.</p> <hr/> <p>S. <math>88^{\circ}57'50''</math> W., beginning new measurement.</p>
20.049	<p>The C-W <math>\frac{1}{16}</math> sec. cor. of sec. 27, monumented with a rebar, <math>\frac{5}{8}</math> in. diam., firmly set, projecting 3 ins. above the ground, and in a mound of stone, <math>1\frac{1}{2}</math> ft. diam., with aluminum cap mkd. W 1/16 C C S27 RLS 3579, as recorded in Douglas County, book 596, page 4802,</p>

SUBDIVISION OF SECTION 27,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.040	<p>document No. 388745, and is accepted as a careful and faithful determination of the position of the cor.</p> <p>Not remonumented.</p> <p>Cor. is located on steep NE slope on the S side of a rock outcrop in rocky loose soil with sagebrush and scattered mountain mahogany.</p> <hr/> <p>S. 88°57'20" W., beginning new measurement.</p> <p>The <math>\frac{1}{4}</math> sec. cor. of secs. 27 and 28.</p>
20.146	<hr/> <p>From the C-W <math>\frac{1}{16}</math> sec. cor. of sec. 27.</p> <p>N. 0°06'30" W., on the N and S center line of the NW<math>\frac{1}{4}</math> of sec. 27.</p> <p>Point for the NW <math>\frac{1}{16}</math> sec. cor. of sec. 27, at intersection with the E and W center line of the NW<math>\frac{1}{4}</math>.</p>
30.219	<p>Not monumented.</p> <p>Point for the C-N-NW <math>\frac{1}{64}</math> sec. cor. of sec. 27.</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">C-N-NW 1/64 S27  1996</p>
40.292	<p>No trees available for bearing trees.</p> <p>Cor. is located on a NE slope in rocky sandy soil with sagebrush.</p> <p>The W <math>\frac{1}{16}</math> sec. cor. of secs. 22 and 27.</p>
20.001	<hr/> <p>From the C-N <math>\frac{1}{16}</math> sec. cor. of sec. 27.</p> <p>S. 88°43'30" W., on the E and W center line of the NW<math>\frac{1}{4}</math> of sec. 27.</p> <p>The NW <math>\frac{1}{16}</math> sec. cor. of sec. 27.</p>
39.995	<p>The N <math>\frac{1}{16}</math> sec. cor. of secs. 27 and 28.</p>
19.971	<hr/> <p>From the C-N-N <math>\frac{1}{64}</math> sec. cor. of sec. 27.</p> <p>S. 88°36'40" W., on the E and W center line of the NE<math>\frac{1}{4}</math> of the NW<math>\frac{1}{4}</math> of sec. 27.</p> <p>The C-N-NW <math>\frac{1}{64}</math> sec. cor. of sec. 27.</p> <hr/> <p>From the C-N-NW <math>\frac{1}{64}</math> sec. cor. of sec. 27.</p>

SUBDIVISION OF SECTION 27,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

19.972

S.  $88^{\circ}36'30''$  W., on the E and W center line of the NW $\frac{1}{4}$  of the NW $\frac{1}{4}$  of sec. 27.

The N-N  $\frac{1}{64}$  sec. cor. of secs. 27 and 28.

SUBDIVISION OF SECTION 28,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

19.882

From the  $\frac{1}{4}$  sec. cor. of secs. 28 and 33.

N.  $0^{\circ}00'20''$  W., on the N and S center line of sec. 28.

Point for the C-S  $\frac{1}{16}$  sec. cor. of sec. 28.

Set a brass tablet,  $3\frac{1}{4}$  ins. diam.,  $3\frac{1}{2}$ -in. stem, in drill hole on exposed boulder,  $1 \times 1\frac{1}{2} \times 1\frac{1}{2}$  ft. high, with top mkd.

$$\begin{array}{c} C \\ S \frac{1}{16} | S28 \\ C \end{array}$$

1996

from which

A pine, 13 ins. diam., bears N.  $72\frac{1}{2}^{\circ}$  E., 85 lks. dist., mkd. CS  $\frac{1}{16}$  S28 BT.

A granite boulder,  $13 \times 7 \times 8$  ft. high, bears S.  $32^{\circ}14'$  W., 28.0 lks. dist. to X, mkd. BXO on NE face,  $2\frac{1}{2}$  ft. above ground.

Cor. is located on very steep N slope with pine and juniper.

39.764

Point for the center  $\frac{1}{4}$  sec. cor. of sec. 28, at intersection with the E and W center line.

Set a stainless steel post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

$$\begin{array}{c} T14N R19E \\ C \frac{1}{4} S28 \end{array}$$

1996

from which

A pine, 34 ins. diam., bears S.  $37^{\circ}$  E., 125 lks. dist., mkd. C  $\frac{1}{4}$  S28 BT.

A pine, 22 ins. diam., bears S.  $85\frac{1}{4}^{\circ}$  W., 36 lks. dist., mkd. C  $\frac{1}{4}$  S28 BT.

Cor. is located on steep NE slope in rocky soil with scattered pine and fir.

59.828

Point for the C-N  $\frac{1}{16}$  sec. cor. of sec. 28.

SUBDIVISION OF SECTION 28,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

$$N \frac{1}{16} \begin{array}{c} C \\ | \\ S28 \\ | \\ C \end{array}$$

1996

from which

A pine, 24 ins. diam., bears N. 87 $\frac{1}{2}$ ° E., 16 lks. dist., mkd. X BT.

A pine, 20 ins. diam., bears N. 59 $\frac{3}{4}$ ° W., 17 lks. dist., mkd. CN 1/16 S28 BT.

Cor. is located on a steep S slope in rocky soil with pine and scattered mountain mahogany.

79.892

The  $\frac{1}{4}$  sec. cor. of secs. 21 and 28.

From the  $\frac{1}{4}$  sec. cor. of secs. 27 and 28.

S. 89°50'00" W., on the E and W center line of sec. 28.

19.693

Point for the C-E  $\frac{1}{16}$  sec. cor. of sec. 28.

Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 8 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 5 ft. base, to top, with brass cap mkd.

$$E \frac{1}{16} \\ C \frac{\quad}{S28} C$$

1996

from which

A pine, 21 ins. diam., bears N. 48° W., 181 lks. dist., mkd. CE 1/16 S28 BT.

A boulder, 6 x 5 x 10 ft. high, bears N. 83°21' W., 110.5 lks. dist. to X, mkd. BXO on E face, 2 ft. above ground.

Cor. is located on steep N slope in rocky soil with scattered pine, cedar, fir, and mountain mahogany.

39.386

The center  $\frac{1}{4}$  sec. cor. of sec. 28.

59.206

Point for the C-W  $\frac{1}{16}$  sec. cor. of sec. 28.

Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

SUBDIVISION OF SECTION 28,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">W 1/16 C ——— C S28 1996</p>
	<p>from which</p> <p>A fir, 10 ins. diam., bears N. 35<sup>1</sup>/<sub>4</sub>° E., 44 lks. dist., mkd. X BT.</p> <p>A pine, 17 ins. diam., bears N. 32° W., 62 lks. dist., mkd. CW 1/16 S28 BT.</p> <p>Cor. is located on a steep S slope in rocky soil with pine and fir.</p>
79.026	<p>The 1/4 sec. cor. of secs. 28 and 29.</p> <hr/>
20.065	<p>From the C-E 1/16 sec. cor. of sec. 28.</p> <p>N. 0°00'30" E., on the N and S center line of the NE<sup>1</sup>/<sub>4</sub> of sec. 28.</p> <p>Point for the NE 1/16 sec. cor. of sec. 28, at intersection with the E and W center line of the NE<sup>1</sup>/<sub>4</sub>.</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S28 1996</p>
40.130	<p>from which</p> <p>A pine, 11 ins. diam., bears N. 50<sup>1</sup>/<sub>2</sub>° E., 67 lks. dist., mkd. NE 1/16 S28 BT.</p> <p>A cedar, 6 ins. diam., bears N. 40<sup>1</sup>/<sub>2</sub>° W., 59 lks. dist., mkd. X BT.</p> <p>Cor. is located on E edge of a ridge, bears SE and NW, in rocky soil with scattered pine, cedar, and mountain mahogany.</p>
	<p>The E 1/16 sec. cor. of secs. 21 and 28.</p> <hr/>
19.697	<p>From the N 1/16 sec. cor. of secs. 27 and 28.</p> <p>S. 89°50'00" W., on the E and W center line of the NE<sup>1</sup>/<sub>4</sub> of sec. 28.</p>
	<p>The NE 1/16 sec. cor. of sec. 28.</p>
39.394	<p>The C-N 1/16 sec. cor. of sec. 28.</p> <hr/>
	<p>From the E 1/16 sec. cor. of secs. 28 and 33.</p> <p>N. 0°04'50" W., on the N and S center line of the SE<sup>1</sup>/<sub>4</sub> of sec. 28.</p>

085

SUBDIVISION OF SECTION 28,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 19.868</p>	<p>Point for the SE <math>\frac{1}{16}</math> sec. cor. of sec. 28, at intersection with the E and W center line of the SE <math>\frac{1}{4}</math>.</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 20 ins. in the ground, over a plastic-encased magnet and in a talus slope, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S28</p> <p style="text-align: center;">1996</p> <p>Raise a mound of stone, 3 ft. base, 1<math>\frac{1}{2}</math> ft. high, 6 lks. W of cor. from which</p> <p style="padding-left: 40px;">A boulder, 12 x 30 x 28 ft. high, bears N. 18°26' E., 60.4 lks. dist. to X, mkd. BXO on SW face, 15 ft. above ground.</p> <p style="padding-left: 40px;">A mountain mahogany, 5 ins. diam., bears N. 83° W., 25 lks. dist., mkd. X BT.</p> <p>Cor. is located on steep S talus slope with mountain mahogany and scattered pine.</p>
<p>39.735</p>	<p>The C-E <math>\frac{1}{16}</math> sec. cor. of sec. 28.</p> <hr/> <p>From the S <math>\frac{1}{16}</math> sec. cor. of secs. 27 and 28.</p> <p>S. 89°47'40" W., on the E and W center line of the SE <math>\frac{1}{4}</math> of sec. 28.</p>
<p>19.720</p>	<p>The SE <math>\frac{1}{16}</math> sec. cor. of sec. 28.</p>
<p>39.440</p>	<p>The C-S <math>\frac{1}{16}</math> sec. cor. of sec. 28.</p> <hr/> <p>From the C-W <math>\frac{1}{16}</math> sec. cor. of sec. 28.</p> <p>N. 0°08'40" E., on the N and S center line of the NW <math>\frac{1}{4}</math> of sec. 28.</p>
<p>20.052</p>	<p>Point for the NW <math>\frac{1}{16}</math> sec. cor. of sec. 28, at intersection with the E and W center line of the NW <math>\frac{1}{4}</math>.</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 20 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S28</p> <p style="text-align: center;">1996</p> <p>from which</p> <p style="padding-left: 40px;">A large rock outcrop, bears S. 21°42' W., 67.5 lks. dist. to X, mkd. BXO on E face, 3 ft. from the top.</p> <p style="padding-left: 40px;">A rock outcrop, 20 x 30 x 15 ft. high, bears N. 36°58' W., 53.3 lks. dist. to X, mkd. BXO on SE face, 2 ft. above ground.</p>

SUBDIVISION OF SECTION 28,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.103	<p>Cor. is located on steep SE slope in rocky soil with scattered pine and fir.</p> <p>The W <math>\frac{1}{16}</math> sec. cor. of secs. 21 and 28.</p>
19.766	<p>From the C-N <math>\frac{1}{16}</math> sec. cor. of sec. 28.</p> <p>S. <math>89^{\circ}47'40''</math> W., on the E and W center line of the NW<math>\frac{1}{4}</math> of sec. 28.</p>
39.532	<p>The NW <math>\frac{1}{16}</math> sec. cor. of sec. 28.</p> <p>The N <math>\frac{1}{16}</math> sec. cor. of secs. 28 and 29.</p>
<p>SUBDIVISION OF SECTION 29, T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA</p>	
39.777	<p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 29 and 32.</p> <p>N. <math>0^{\circ}08'50''</math> E., on the N and S center line of sec. 29.</p> <p>Point for the center <math>\frac{1}{4}</math> sec. cor. of sec. 29, at intersection with the E and W center line.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 20 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T14N R19E C 1/4 S29 1995</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 12 ins. diam., bears S. <math>37\frac{1}{4}^{\circ}</math> E., 89 lks. dist., mkd. C 1/4 S29 BT.</p> <p style="padding-left: 40px;">A pine, 11 ins. diam., bears N. <math>40\frac{1}{4}^{\circ}</math> W., 90 lks. dist., mkd. X BT.</p>
59.822	<p>Cor. is located on a steep E slope in rocky soil with scattered pine.</p> <p>Point for the C-N <math>\frac{1}{16}</math> sec. cor. of sec. 29.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 26 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">C N 1/16   S29 C</p> <p style="text-align: center;">1995</p> <p>from which</p>

SUBDIVISION OF SECTION 29,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>A boulder, 4 x 2 x 2 ft. high, bears N. 62°53' E., 46.7 lks. dist. to X, mkd. BXO on SW face, 1 ft. above ground.</p> <p>A pine, 9 ins. diam., bears N. 59<sup>3</sup>/<sub>4</sub>° W., 132 lks. dist., mkd. CN 1/16 S29 BT.</p> <p>Cor. is located on a steep S talus slope with aspen and scattered pine.</p>
79.867	<p>The 1/4 sec. cor. of secs. 20 and 29.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 28 and 29.</p> <p>S. 88°44'30" W., on the E and W center line of sec. 29.</p>
39.313	<p>The center 1/4 sec. cor. of sec. 29.</p>
79.109	<p>The 1/4 sec. cor. of secs. 29 and 30.</p> <hr/> <p>From the N 1/16 sec. cor. of secs. 28 and 29.</p> <p>S. 88°45'20" W., on the E and W center line of the NE<sup>1</sup>/<sub>4</sub> of sec. 29.</p>
39.363	<p>The C-N 1/16 sec. cor. of sec. 29.</p> <hr/> <p>From the C-N 1/16 sec. cor. of sec. 29.</p> <p>S. 88°42'00" W., on the E and W center line of the NW<sup>1</sup>/<sub>4</sub> of sec. 29.</p>
39.832	<p>The N 1/16 sec. cor. of secs. 29 and 30.</p> <hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 30, T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 30 and 31.</p> <p>N. 0°11'50" W., on the N and S center line of sec. 30.</p>
39.723	<p>Point for the center 1/4 sec. cor. of sec. 30, at intersection with the E and W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T14N R19E C 1/4 S30</p> <p style="text-align: center;">1994</p> <p>from which</p> <p>A pine, 14 ins. diam., bears N. 86° E., 52 lks. dist., mkd. C 1/4 S30 BT.</p>

SUBDIVISION OF SECTION 30,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
59.835	<p>A pine, 11 ins. diam., bears N. <math>30\frac{1}{2}^{\circ}</math> W., 45 lks. dist., mkd. X BT.</p> <p>Cor. is located 20 lks. W of a dirt road, 12 lks. wide, bears N. <math>20^{\circ}</math> E. and S. <math>20^{\circ}</math> W., on a SW slope in sandy soil with pine and fir.</p> <p>Point for the C-N <math>\frac{1}{16}</math> sec. cor. of sec. 30.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> $\begin{array}{c} \text{C} \\ \text{N } 1/16 \text{   S30} \\ \text{C} \end{array}$ <p style="text-align: center;">1994</p> <p>from which</p> <p>A pine, 13 ins. diam., bears N. <math>44^{\circ}</math> E., 32 lks. dist., mkd. X BT.</p> <p>A pine, 14 ins. diam., bears S. <math>11\frac{1}{4}^{\circ}</math> E., 29 lks. dist., mkd. CN <math>\frac{1}{16}</math> S30 BT.</p> <p>Cor. is located on a SE slope in sandy rocky soil with pine and fir.</p>
79.947	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 19 and 30.</p> <hr/> <p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 29 and 30.</p> <p>S. <math>89^{\circ}53'20''</math> W., on the E and W center line of sec. 30.</p>
19.715	<p>Point for the C-E <math>\frac{1}{16}</math> sec. cor. of sec. 30.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> $\begin{array}{c} \text{E } 1/16 \\ \text{C } \frac{\quad}{\quad} \text{C} \\ \text{S30} \end{array}$ <p style="text-align: center;">1994</p> <p>from which</p> <p>A pine, 14 ins. diam., bears S. <math>69\frac{1}{2}^{\circ}</math> E., 27 lks. dist., mkd. X BT.</p> <p>A pine, 14 ins. diam., bears S. <math>37^{\circ}</math> W., 30 lks. dist., mkd. CE <math>\frac{1}{16}</math> S30 BT.</p> <p>Cor. is located on a N slope in sandy soil with pine and fir.</p>
39.430	<p>The center <math>\frac{1}{4}</math> sec. cor. of sec. 30.</p>

SUBDIVISION OF SECTION 30,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS  
77.781

The  $\frac{1}{4}$  sec. cor. of secs. 25 and 30, on the W bdy. of the Tp., hereinbefore described.

From the C-E  $\frac{1}{16}$  sec. cor. of sec. 30.

N.  $0^{\circ}04'50''$  W., on the N and S center line of the NE $\frac{1}{4}$  of sec. 30.

20.062 Point for the NE  $\frac{1}{16}$  sec. cor. of sec. 30, at intersection with the E and W center line of the NE $\frac{1}{4}$ .

Set a stainless steel post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

NE  $\frac{1}{16}$  S30

1994

from which

A pine, 18 ins. diam., bears S.  $13\frac{3}{4}^{\circ}$  E., 69 lks. dist., mkd. NE  $\frac{1}{16}$  S30 BT.

A pine, 9 ins. diam., bears S.  $75\frac{1}{4}^{\circ}$  W., 17 lks. dist., mkd. X BT.

Cor. is located on a S slope in sandy rocky soil with scattered pine.

40.228 The E  $\frac{1}{16}$  sec. cor. of secs. 19 and 30.

From the N  $\frac{1}{16}$  sec. cor. of secs. 29 and 30.

N.  $89^{\circ}58'00''$  W., on the E and W center line of the NE $\frac{1}{4}$  of sec. 30.

19.755 The NE  $\frac{1}{16}$  sec. cor. of sec. 30.

39.510 The C-N  $\frac{1}{16}$  sec. cor. of sec. 30.

SUBDIVISION OF SECTION 33,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

From the  $\frac{1}{4}$  sec. cor. of secs. 4 and 33, on the S bdy. of the Tp., monumented with a stainless steel post,  $2\frac{1}{2}$  ins. diam., firmly set, projecting 8 ins. above the ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd. as described in the field notes of T. 13 N., R. 19 E. executed under Group No. 620, from which the remains of the original bearing trees

A decayed stump, 12 ins. diam., bears S.  $10^{\circ}$  W., 27 lks. dist., no visible mks. found.

A stump hole, bears N.  $65^{\circ}$  W., 50 lks. dist., with a decayed pine stump, dead and down, 16 ins. diam., lying alongside stump hole, no visible mks. found.

and the 1985-86 bearing trees

SUBDIVISION OF SECTION 33,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>A pine, 15 ins. diam., bears N. 52<sup>3</sup>/<sub>4</sub>° E., 110 lks. dist., mkd. 1/4 S33 BT visible in partially healed blaze.</p> <p>A pine, 15 ins. diam., bears S. 36° W., 128<sup>1</sup>/<sub>2</sub> lks. dist., mkd. 1/4 S4 BT visible in partially healed blaze.</p> <p>Cor. is located on steep SE slope in rocky soil with pine and scattered fir. South, 50 lks., to a ravine, 10 lks. wide, drains S. 59° E.</p> <p>N. 0°12'00" W., on the N and S center line of sec. 33.</p>
39.781	<p>Point for the center <sup>1</sup>/<sub>4</sub> sec. cor. of sec. 33, at intersection with the E and W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 10 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T14N R19E C 1/4 S33</p> <p style="text-align: center;">1996</p> <p>from which</p> <p style="padding-left: 40px;">A rock outcrop, 35 x 25 x 5 ft. high, bears N. 14°45' E., 38.0 lks. dist. to X, mkd. BXO on S face, 3 ft. from top.</p> <p style="padding-left: 40px;">A cedar, 14 ins. diam., bears S. 24<sup>1</sup>/<sub>2</sub>° W., 59 lks. dist., mkd. C 1/4 S33 BT.</p> <p>Cor. is located on very steep rocky E slope with cedar, pine, and sagebrush.</p>
59.901	<p>Point for the C-N <sup>1</sup>/<sub>16</sub> sec. cor. of sec. 33.</p> <p>Not monumented.</p>
80.021	<p>The <sup>1</sup>/<sub>4</sub> sec. cor. of secs. 28 and 33.</p> <hr/> <p>From the <sup>1</sup>/<sub>4</sub> sec. cor. of secs. 33 and 34.</p> <p>S. 89°35'00" W., on the E and W center line of sec. 33.</p>
19.770	<p>Point for the C-E <sup>1</sup>/<sub>16</sub> sec. cor. of sec. 33.</p> <p>Not monumented.</p>
39.540	<p>The center <sup>1</sup>/<sub>4</sub> sec. cor. of sec. 33.</p>
78.943	<p>The <sup>1</sup>/<sub>4</sub> sec. cor. of secs. 32 and 33.</p> <hr/> <p>From the C-E <sup>1</sup>/<sub>16</sub> sec. cor. of sec. 33.</p> <p>N. 0°13'50" W., on the N and S center line of the NE<sup>1</sup>/<sub>4</sub> of sec. 33.</p>
20.088	<p>Point for the NE <sup>1</sup>/<sub>16</sub> sec. cor. of sec. 33, at intersection with the E and W center line of the NE<sup>1</sup>/<sub>4</sub>.</p>

091

SUBDIVISION OF SECTION 33,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 2<sup>1</sup>/<sub>2</sub> ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S33</p> <p style="text-align: center;">1996</p> <p>from which</p> <p>A pine, 12 ins. diam., bears N. 75<sup>3</sup>/<sub>4</sub>° E., 73 lks. dist., mkd. NE 1/16 S33 BT.</p> <p>A rock outcrop, 8 x 5 x 5 ft. high, bears S. 83°00' W., 42.5 lks. dist. to X, mkd. BXO on E face, 1 ft. above ground.</p> <p>Cor. is located on steep SE slope in rocky soil with scattered pine, mountain mahogany, and sagebrush.</p> <hr/> <p>40.183 The E <sup>1</sup>/<sub>16</sub> sec. cor. of secs. 28 and 33.</p> <hr/> <p>From the N <sup>1</sup>/<sub>16</sub> sec. cor. of secs. 33 and 34.</p> <p>S. 89°40'50" W., on the E and W center line of the NE<sup>1</sup>/<sub>4</sub> of sec. 33.</p> <p>19.763 The NE <sup>1</sup>/<sub>16</sub> sec. cor. of sec. 33.</p> <p>39.521 The C-N <sup>1</sup>/<sub>16</sub> sec. cor. of sec. 33.</p> <hr/> <p style="text-align: center;">METES-AND-BOUND SURVEY OF PORTIONS OF U. S. HIGHWAY 50 RIGHT-OF-WAY, IN SECTIONS 5 AND 6, T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">MEMORANDUM</p> <p>The boundaries of the metes-and-bound survey of portions of U.S. Highway 50 right-of-way in sections 5 and 6, were determined by the deed descriptions recorded in Douglas County, Nevada in Book A-1 Deeds, Page 226, document No. 8616 and in Book C-1 Deeds, Page 491, document No. 12523.</p> <p>NOTE: There appeared to be an ambiguity in regards to the width of the right-of-way described in the deed document No. 12523, Parcel No. 1. A four hundred (400) foot width is stated which is in conflict with the 18.632 acres stated at the end of Parcel No. 1 description. Examining the NDOT (Nevada Department of Transportation) maps and with discussions with Mr. Crebo Hancock, in Right-of-Way Engineering at NDOT, all the NDOT maps show a three hundred (300) foot right-of-way, which also agrees with the stated 18.623 acres, therefore determining the intent to be a three hundred (300) foot right-of-way, I establish the boundaries.</p> <p>Several brass discs in concrete (set in 1957 under contract 971 for NDOT) were recovered and used to establish the described boundaries of the right-of-way. Following the intent of the deed descriptions portions of the boundary were either extended or intersected to conform to the subdivisional lines of the pertinent section.</p>
--------	---

METES-AND-BOUND SURVEY OF PORTIONS  
OF U. S. HIGHWAY 50 RIGHT-OF-WAY, IN SECTIONS 5 AND 6,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From the witness point at the intersection of the E and W center line of the NW<sup>1</sup>/<sub>4</sub> of sec. 5, and the easterly right-of-way of U.S. Highway 50.</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 23 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">             WP              N ——— N              S 5              1996           </p> <p>from which</p> <p style="padding-left: 40px;">A pine, 11 ins. diam., bears N. 15° E., 71 lks. dist., mkd. WP S5 BT.</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears N. 81° E., 46 lks. dist., mkd. WP S5 BT.</p> <p>Cor. is located on steep NW slope in sandy soil with pine, scattered fir and chinquapin.</p> <p>Thence along the easterly right-of-way of U.S. Highway 50, along the arc of a curve concave to the left having a radius of 13.636 chs. (900 feet), the chord of said arc bears N. 33°14'20" W., 9.332 chs. (615.89 feet).</p>
9.524	<p>Point for Angle Point No. 1, sec. 5.</p> <p>Not monumented.</p> <hr style="width: 30%; margin: 20px auto;"/>
4.144	<p>Thence along the easterly right-of-way of U.S. Highway 50, N. 70°03'21" W., 4.144 chs. (273.49 feet) dist.</p> <p>Point for Angle Point No. 2, sec. 5.</p> <p>Not monumented.</p> <hr style="width: 30%; margin: 20px auto;"/>
3.065	<p>Thence along the easterly right-of-way of U.S. Highway 50, along a spiral curve concave to the right, subtended by a chord which bears N. 60°28'06" W., 3.065 chs. (202.29 feet) dist.</p> <p>Point for Angle Point No. 3, sec. 5.</p> <p>Not monumented.</p> <hr style="width: 30%; margin: 20px auto;"/>
	<p>Thence on the easterly right-of-way of U.S. Highway 50, along the arc of a curve concave to the right having a radius of 9.848 chs. (650 feet), the chord of said arc bears N. 53°55'55" W., 0.366 chs. (24.15 feet) dist.</p>

093

METES-AND-BOUND SURVEY OF PORTIONS  
OF U. S. HIGHWAY 50 RIGHT-OF-WAY, IN SECTIONS 5 AND 6,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS  
0.366

Point for a witness point at the intersection of the line between secs. 5 and 6, and the easterly right-of-way of U.S. Highway 50.

Set a stainless steel post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

WP

S 6 | S 5

1996

from which

A pine, 18 ins. diam., bears N.  $66\frac{1}{4}^{\circ}$  E., 148 lks. dist., mkd. WP S5 BT.

A pine, 22 ins. diam., bears N.  $17\frac{1}{4}^{\circ}$  W., 27 lks. dist., mkd. WP S6 BT.

Cor. is located on ridge, bears N.  $60^{\circ}$  E. and S.  $60^{\circ}$  W., in sandy soil with pine and scattered fir.

---

From the witness point at the intersection of the line between secs. 5 and 6, and the easterly right-of-way of U.S. Highway 50.

Thence on the easterly right-of-way of U.S. Highway 50, along the arc of a curve concave to the right having a radius of 9.848 chs. (650 feet), the chord of said arc bears N.  $49^{\circ}24'06''$  W., 1.191 chs. (78.58 feet) dist.

1.191 Point for Angle Point No. 1, sec. 6.

Not monumented.

---

Thence along the easterly right-of-way of U.S. Highway 50, along a spiral curve concave to the right, subtended by a chord which bears N.  $40^{\circ}27'55''$  W., 3.065 chs. (202.29 feet) dist.

3.065 Point for Angle Point No. 2, sec. 6.

Not monumented.

---

Thence along the easterly right-of-way of U.S. Highway 50, N.  $37^{\circ}56'11''$  W., 1.096 chs. (72.33 feet) dist.

1.096 Point for Angle Point No. 3, sec. 6.

Not monumented.

---

Thence along the easterly right-of-way of U.S. Highway 50, along a spiral curve concave to the left, subtended by a chord which bears N.  $40^{\circ}22'12''$  W., 3.237 chs. (213.66 feet) dist.

METES-AND-BOUND SURVEY OF PORTIONS  
OF U. S. HIGHWAY 50 RIGHT-OF-WAY, IN SECTIONS 5 AND 6,  
T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 3.237</p>	<p>Point for Angle Point No. 4, sec. 6.</p> <p>Not monumented.</p> <hr/> <p>Thence on the easterly right-of-way of U.S. Highway 50, along the arc of a curve concave to the left having a radius of 14.394 chs. (950 feet), the chord of said arc bears N. 52°56'29" W., 4.009 chs. (264.59 feet) dist.</p>
<p>4.022</p>	<p>Point for Angle Point No. 5, sec. 6.</p> <p>Not monumented.</p> <hr/> <p>Thence along the easterly right-of-way of U.S. Highway 50, along a spiral curve concave to the left, subtended by a chord which bears N. 62°36'19" W., 0.928 chs. (61.24 feet) dist.</p>
<p>0.928</p>	<p>Point for a witness point at the intersection of the line between secs. 6 and 31, on the N bdy. of the Tp., and the easterly right-of-way of U.S. Highway 50.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>WP S 31 ----- S 6 1996.</p> </div> <p>from which</p> <p style="padding-left: 40px;">A pine, 33 ins. diam., bears S. 67½° E., 137 lks. dist., mkd. WP S6 BT.</p> <p style="padding-left: 40px;">A pine, 19 ins. diam., bears N. 50° W., 110 lks. dist., mkd. WP S31 BT.</p> <p>Cor. is located on a steep NE slope in sandy soil with pine and fir.</p> <hr/> <p>From the witness point at the intersection of the E and W center line of sec. 6, and the southerly right-of-way of U.S. Highway 50.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

095

METES-AND-BOUND SURVEY OF PORTIONS OF U. S. HIGHWAY 50 RIGHT-OF-WAY, IN SECTIONS 5 AND 6, T. 14 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

WP  
C — S 6 C

1996

from which

A pine, 23 ins. diam., bears N. 85° E., 101 lks. dist., mkd. WP S6 BT.

A pine, 24 ins. diam., bears S. 8° E., 71 lks. dist., mkd. WP S6 BT.

Cor. is located 61 lks. S of dirt road, 15 lks. wide, bears N. 75° E. and S. 75° W., on N slope in sandy soil with pine and fir.

Thence on the southerly right-of-way of U.S. Highway 50, along the arc of a curve concave to the right having a radius of 32.576 chs. (2150 feet), the chord of said arc bears S. 78°34'22" W., 8.306 chs. (548.21 feet) dist.

8.329

Point for Angle Point No. 6, sec. 6.

Not monumented.

Thence along the southerly right-of-way of U.S. Highway 50, S. 85°53'50" W., 6.817 chs. (449.94 feet) dist.

6.817

Point for Angle Point No. 7, sec. 6.

Not monumented.

Thence on the southerly right-of-way of U.S. Highway 50, along the arc of a curve concave to the left having a radius of 50.758 chs. (3350 feet), the chord of said arc bears S. 85°17'14" W., 1.081 chs. (71.31 feet) dist.

1.081

Point for a witness point at the intersection of the N and S center line of sec. 6, and the southerly right-of-way of U.S. Highway 50.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 2 ft. base, to top, with brass cap mkd.

WP

C  
| S 6  
C

1996

from which



TOWNSHIP 14 NORTH, RANGE 19 EAST, MOUNT DIABLO MERIDIAN

CHAINS

GENERAL DESCRIPTION

Township 14 North, Range 19 East, is located SW of Carson City, Nevada, in Douglas County. Portions of U.S. Highway 50 run through the northern portion of the township. Jacks Valley Road runs through the eastern portion of the township.

The terrain ranges from the Carson Range of the Sierra Nevadas in the western portion of the township to the lower Carson Valley in the eastern portion.

The elevation ranges from 9150 feet above sea level at Genoa Peak, to approximately 4600 feet above sea level in Carson Valley.

All the major drainages drain to the east into Carson Valley and into the Carson River.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

B L M

Michael Collie	Supervisory Land Surveyor
Mark Petrosine	Surveying Technician
Todd Burrill	Surveying Technician
Susan Sarantopoulos	Surveying Technician
Ted Cazier	Surveying Technician
Daniel Johnson	Survey Aid
Mike Gyarmathy	Survey Aid
Graham Ross	Survey Aid


U S F S

Sean Sullivan	Surveying Technician
Lori Percival	Survey Aid

## CERTIFICATE OF SURVEY

I, Brian L. Mikkelsen, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 14th day of June, 1994, I have dependently resurveyed a portion of the south, east, west, and north boundaries, a portion of the subdivisional lines, and a portion of the subdivision-of-section lines of sections 1 and 24, and subdivided and further subdivided sections 1, 2, 5, 6, 9, 11, 16, 19, 20, 21, 24, 27, 28, 29, 30, and 33, and surveyed by metes-and-bounds portions of U.S. Highway 50 right-of-way, in sections 5 and 6, Township 14 North, Range 19 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

July 23, 1997  
(Date)

  
(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Reno, Nevada

The foregoing field notes of the dependent resurvey of a portion of the south, east, west, and north boundaries, a portion of the subdivisional lines, and a portion of the subdivision-of-section lines of sections 1 and 24, and the subdivision and further subdivision of sections 1, 2, 5, 6, 9, 11, 16, 19, 20, 21, 24, 27, 28, 29, 30, and 33, and the metes-and-bounds survey of portions of U.S. Highway 50 right-of-way, in sections 5 and 6, Township 14 North, Range 19 East, Mount Diablo Meridian, Nevada, executed by Brian L. Mikkelsen, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.


July 29, 1997  
(Date)

  
(Acting Chief Cadastral Surveyor, Nevada)

## CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 14 N., R. 19 E., M.D.M., Nevada, is a true copy of the original field notes.

July 29, 1997  
(Date)

  
(Acting Chief Cadastral Surveyor, Nevada)