

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

PORTIONS OF THE SOUTH, EAST AND NORTH BOUNDARIES,
A PORTION OF THE SUBDIVISIONAL LINES
AND A PORTION OF THE SUBDIVISION-OF-SECTION LINES OF SECTION 5,
THE SUBDIVISION OF SECTIONS 2, 3, 4, 11, 12 AND 13,
THE FURTHER SUBDIVISION OF SECTION 5,
AND A METES-AND-BOUNDS SURVEY IN SECTION 5,
TOWNSHIP 14 NORTH, RANGE 27 EAST,
OF THE MOUNT DIABLO MERIDIAN,
IN THE STATE OF NEVADA

EXECUTED BY

Douglas A. Potts, Cadastral Surveyor
Mark G. Petrosine, Surveying Technician

Under Special Instructions dated June 9, 2006,
and approved June 9, 2006,
which provided for the surveys included under Group No. 837,
and Assignment Instructions dated June 12, 2006.

Survey commenced June 15, 2006

Survey completed July 29, 2008

INDEX DIAGRAM

TOWNSHIP 14 NORTH, RANGE 27 EAST, MOUNT DIABLO MERIDIAN, NEVADA

6	14 5	12 29 28 4	10 3 26 27	9 2 23 24	8 1 7 22
7 31	8 30	9	10	11 19 24	12 6 18
18	17	16	15	18 14	13 4 17
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35 16	36 3 2

Dependent Resurvey of a Portion of the

Subdivision-of-Section Lines of Section 5	p.	32.
Subdivision of Section 2	pp.	32 - 40.
Subdivision of Section 3	pp.	40 - 48.
Subdivision of Section 4	pp.	48 - 54.
Subdivision of Section 11	pp.	54 - 62.
Subdivision of Section 12	pp.	62 - 65.
Subdivision of Section 13	pp.	65 - 73.
Further Subdivision of Section 5	pp.	73 - 75.
Metes-and-Bounds Survey in Section 5	pp.	75 - 76.

TOWNSHIP 14 NORTH, RANGE 27 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>The following field notes are those of the dependent resurvey of portions of the south, east and north boundaries, a portion of the subdivisional lines and a portion of the subdivision-of-section lines of section 5, the subdivision of sections 2, 3, 4, 11, 12 and 13, the further subdivision of section 5, and a metes-and-bounds survey in section 5, Township 14 North, Range 27 East, Mount Diablo Meridian, Nevada.</p> <p>The north and east boundaries, the east three and one-half miles of the south boundary, and a portion of the subdivisional lines were surveyed by U.S. Deputy Surveyors H.E. Franks and J.S. Mullen in 1904 under Contract No. 237. The corner of Townships 14 and 15 North, Ranges 27 and 28 East was remonumented by James W. Hardison, Public Land Surveyor and Belvel Boyd, Transitman, P.W.A., in 1937 under Group No. 181. A portion of the east boundary of section 1, Township 14 North, Range 26 East, and portions of the north and east boundaries, and a portion of the subdivisional lines, Township 14 North, Range 27 East, were dependently resurveyed, and section 5 was subdivided by Cadastral Surveyor R.A. Pratt in 1989 under Group No. 670. Other official surveys remote to this area are not included.</p> <p>Before restoring the corners, the lines of the original surveys were retraced and diligent search made for any evidence of the original corners and other calls of the original field note record.</p> <p>The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.</p> <p>The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 837, dated June 9, 2006.</p> <p>Measurements were made with Trimble 4700, 5700, and 5800 Global Positioning System (GPS) receivers, utilizing real-time kinematic (RTK) and static methods and refer to the true meridian based on geodetic methods. The mean bearings of the lines and horizontal equivalents of ground distances only are entered in the field notes.</p> <p>The NAD 1983 (CORS 96) geographic position of the corner of Townships 13 and 14 North, Ranges 27 and 28 East, determined from GPS static observations post processed by the National Geodetic Survey, Online Positioning User Service(OPUS), utilizing Continuously Operating Reference Stations(CORS) AUSTIN 1 CORS ARP, GARLIC CORS ARP, GABBS CORS ARP, and UPSAL HOGBACK CORS ARP, in 2006, and carried forward by RTK observations is as follows:</p> <p>Latitude: 39°01'33.451" N. Longitude: 118°54'11.356" W.</p> <p>The 1987 mean magnetic declination is 15°30' E., as shown on the 7 1/2 minute U.S.G.S. quadrangle map "Weber Reservoir, Nevada", provisional edition dated 1987.</p>
--------	---

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Reestablishment of a Portion the Survey Executed by H.E. Franks and J.S. Mullen, U.S. Deputy Surveyors, in 1904</p>
	<p>Beginning at the cor. of Tps. 13 and 14 N., Rs. 27 and 28 E., perpetuated by person(s) unknown, monumented with a rebar, 24 ins. long, 1 in. diam., firmly set, projecting 2 ins. above the ground, with the remains of a cottonwood post, 3x3x8 ins. long, lying loose alongside, and is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T14N R27E R28E S36 S31 S 1 S 6 T13N</p> </div> <p>2007</p> <p>Deposit the rebar and the remains of the cottonwood post alongside the stainless steel post and below the surface of the ground.</p> <p>N. 89°58'10" W., bet. secs. 1 and 36.</p> <p>Over nearly level land covered with low brush, cheat and bunch grass.</p>
21.78	Center of pavement, U.S. Alternate Highway No. 95, 50 lks. wide, bears N. 56 3/4° W. and S. 56 3/4° E.
33.70	Center of the remains of the pavement, U.S. Alternate Highway No. 95, 50 lks. wide, bears N. 56 3/4° W. and S. 56 3/4° E.
40.127	<p>Point for the 1/4 sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T14N R27E S36 1/4 ——— S 1 T13N</p> </div> <p>2007</p> <p>From this point, a Nevada Department of Transportation concrete block, 6 ins. square, firmly set, projecting 8 ins. above the ground, with brass wire projecting from top center, bears S. 77°37' E., 1.246 chs. dist.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS									
43.45	Powerline, wood poles, bears N. 55° W. and S. 55° E.								
80.254	<p>The cor. of secs. 1, 2, 35 and 36, monumented with a weathered redwood post, 33 ins. long, 4 ins. square, firmly set, projecting 12 ins. above the ground, with the scribe mks. T1N S36 visible on the SE. face and illegible scribe mks. on the other faces.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td>T14N</td><td>R27E</td></tr> <tr><td>S35</td><td>S36</td></tr> <tr><td>S 2</td><td>S 1</td></tr> <tr><td colspan="2">T13N</td></tr> </table> <p>2006</p> </div> <p>Deposit the original redwood post alongside the stainless steel post and below the surface of the ground.</p> <p>Corner is located under a barbed wire fence, wood posts, bears N. and S., with a wood board, 1x3x30 ins. long, scribed 1/4 S36, suspended over corner in fence. Also, a split rail post of the barbed wire fence, with the scribe mks. 1/4 visible on the N. face, is located 2 lks. N. of the corner.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY, T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of a Portion the Survey Executed by H.E. Franks and J.S. Mullen, U.S. Deputy Surveyors, in 1904 and a Portion of the Dependent Resurvey Executed by Robert A. Pratt, Cadastral Surveyor, in 1989</p> <hr/> <p>From the cor. of Tps. 13 and 14 N., Rs. 27 and 28 E., hereinbefore described.</p> <p>N. 0°09'20" W., bet. secs. 31 and 36.</p> <p>Over nearly level land covered with low brush and cheat and bunch grass.</p>	T14N	R27E	S35	S36	S 2	S 1	T13N	
T14N	R27E								
S35	S36								
S 2	S 1								
T13N									
40.031	<p>The 1/4 sec. cor. of secs. 31 and 36, monumented with the remains of a cottonwood post, recovered 6 ins. below the surface of the ground, with upper portion of post, 3x3x24 ins. long, no mks. visible, lying loose on the surface.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>								

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>T14N R27E R28E 1/4 S36 S31 2006</p> <p>Deposit the remains of the original cottonwood post alongside the stainless steel post and below the surface of the ground.</p> <hr/> <p>N. 0°00'40" E., beginning new measurement.</p>
40.006	<p>The cor. of secs. 25, 30, 31 and 36, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 14 N., R. 27 E., executed under Group No. 670, and a mound of stone, 2 ft. base, 1 ft. high, W. of the cor.</p> <hr/> <p>From the cor. of secs. 13, 18, 19 and 24, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 14 N., R. 27 E., executed under Group No. 670, with an inverted iron pipe, 2 ins. diam., projecting 6 ins. above the ground, with split flanges, set alongside the stainless steel post.</p> <p>N. 0°00'10" E., bet. secs. 13 and 18.</p> <p>Over rolling land covered with low brush, cheat and bunch grass.</p>
19.986	<p>Point for the S 1/16 sec. cor. of secs. 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p>S 1/16 S13 S18 2006</p> <p>Set a steel sign post alongside the stainless steel post.</p>
28.50	Enter bottom land, through scattered willows and meadow grass.
29.60	Right bank of the Walker River, bears NW. and SE.; thence across river, course SE.
29.979	True point for the N-S 1/64 sec. cor. of secs. 13 and 18, falls on the left bank of the Walker River, bears NW. and SE., where it is impractical to set a permanent monument.
31.176	Point selected for the witness cor. to the N-S 1/64 sec. cor. of secs. 13 and 18.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">WC N-S 1/64 S13 S18 ↓ 2007</p>
	<p>Set a steel sign post alongside the stainless steel post.</p>
39.972	<p>Point for the 1/4 sec. cor. of secs. 13 and 18, at proportionate distance; there is no remaining evidence of the original corner.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T14N R27E R28E 1/4 S13 S18 2007</p>
	<p>Set a steel post alongside the stainless steel post.</p>
56.40	<p>Bottom of steep embankment, bears E. and W.; leave bottom land.</p>
58.60	<p>Top of embankment, bears ENE. and WSW.; thence over rolling land covered with low brush, cheat and bunch grass.</p>
59.958	<p>Point for the N 1/16 sec. cor. of secs. 13 and 18.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">N 1/16 S13 S18 2006</p>
	<p>Set a steel sign post alongside the stainless steel post.</p>
66.75	<p>Dirt road, 15 lks. wide, bears NW. and SE.</p>
79.944	<p>The cor. of secs. 7, 12, 13 and 18, monumented with a weathered redwood post, 4 ins. square, firmly set, projecting 10 ins. above the ground, with the scribe mks. T14N S7 visible on the NE. face and illegible scribe mks. on another face, with a stainless steel tag of unknown origin, 1 in. diam., nailed to the top of redwood post, mkd. USBR 1177.</p>

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T14N T27N R28E S12 S 7 S13 S18</p> <p>2006</p> </div> <p>Deposit the original redwood post alongside the stainless steel post and below the surface of the ground.</p> <hr/> <p>N. 0°03'20" W., bet. secs. 7 and 12.</p> <p>Over nearly level, rolling land covered with low brush, cheat and bunch grass.</p> <p>39.00 Graded dirt road, 10 lks. wide, bears NE. and SW.</p> <p>39.912 The 1/4 sec. cor. of secs. 7 and 12, monumented with a rotted redwood post, 1x3x8 ins. long, firmly set, projecting 3 ins. above the ground, with a stone, 5x3x3 ins., recovered from alongside and below the surface of the ground. No mks. were visible on either the redwood post or the stone.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T14N R27E R28E 1/4 S12 S 7</p> <p>2006</p> </div> <p>Deposit the remains of the original redwood post and the stone memorial alongside the stainless steel post and below the surface of the ground.</p> <hr/> <p>N. 0°00'20" W., beginning new measurement.</p> <p>6.45 Graded dirt road, 30 lks. wide, bears WNW. and ESE.</p> <p>40.072 The cor. of secs. 1, 6, 7 and 12, determined at the E. side of a scattered mound of stone, 3 ft. base, 1 ft. high. This point is accepted as the best available evidence of the position of the original corner.</p>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T14N R27E R28E S 1 S 6 S12 S 7</p> <p>2006</p> </div> <p>Rebuild the mound of stone around the stainless steel post, 3 ft. base, to top.</p> <hr/> <p>N. 0°32'20" E., bet. secs. 1 and 6.</p> <p>Over rolling land covered with low brush, cheat and bunch grass.</p> <p>39.610 The 1/4 sec. cor. of secs. 1 and 6, monumented with a weathered redwood post, 3x4 ins., firmly set, projecting 9 ins. above the ground, with the scribe mks. S6 visible on the E. face and S1 on the W. face, with a stone, 9x4x4 ins., mkd. with a chiseled X, recovered from alongside and below the surface of the ground.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T14N R27E R28E 1/4 S 1 S 6</p> <p>2006</p> </div> <p>Deposit the original redwood post and the stone memorial alongside the stainless steel post and below the surface of the ground.</p> <hr/> <p>N. 0°27'20" W., beginning new measurement.</p> <p>40.386 The cor. of Tps. 14 and 15 N., Rs. 27 and 28 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey and completion of the S. and W. boundaries of T. 15 N., R. 28 E., executed under Group No. 181.</p> <hr/>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p>	<p>Reestablishment of a Portion the Survey Executed by H.E. Franks and J.S. Mullen, U.S. Deputy Surveyors, in 1904 and a Portion of the Dependent Resurvey Executed by Robert A. Pratt, Cadastral Surveyor, in 1989</p> <hr/> <p>From the cor. of Tps. 14 and 15 N., Rs. 27 and 28 E., hereinbefore described.</p> <p>N. 89°59'40" W., bet. secs. 1 and 36.</p> <p>Over nearly level, rolling land covered with low brush, cheat and bunch grass.</p> <p>39.780 The 1/4 sec. cor. of secs. 1 and 36, monumented with a weathered redwood post, 3x3 1/2 ins., firmly set, projecting 10 ins. above the ground, no mks. visible, with a stone, 4x4x3 ins., mkd. with a chiseled X, recovered from alongside and below the surface of the ground.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T15N R27E S36 1/4 <u> </u> S 1 T14N</p> <p>2006</p> </div> <p>Deposit the original redwood post and the stone memorial alongside the stainless steel post and below the surface of the ground.</p> <hr/> <p>N. 89°59'10" W., beginning new measurement.</p> <p>39.837 The cor. of secs. 1, 2, 35 and 36, monumented with a weathered redwood post, 32 ins. long, 3 1/2 ins. square, firmly set, projecting 15 ins. above the ground, with the scribe mks. 15N S36 visible on the NE. face, with a stone, 4x2 1/2x2 ins., mkd. with a chiseled X, recovered from alongside and below the surface of the ground.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T15N R27E S35 S36 S 2 S 1 T14N</p> <p>2006</p> </div>
---------------	--

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Deposit the original redwood post and the stone memorial alongside the stainless steel post and below the surface of the ground.</p> <p>Corner is located under a barbed wire fence, wood and steel posts, bears N. and S.</p> <hr/> <p>N. 89°59'30" W., bet. secs. 2 and 35.</p> <p>Over nearly level, gently rolling land covered with low brush, cheat and bunch grass.</p>
40.079	<p>The 1/4 sec. cor. of secs. 2 and 35, monumented with a weathered redwood post, 32 ins. long, 3 1/2 ins. square, firmly set, projecting 9 ins. above the ground, with the scribe mks. S35 visible on the N. face, with a stone, 3x3x1 1/2 ins., mkd. with a chiseled X, recovered from below the redwood post.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T15N R27E S35 1/4 $\frac{\quad}{S\ 2}$ T14N 2006</p> </div> <p>Deposit the original redwood post and the stone memorial alongside the stainless steel post and below the surface of the ground.</p> <hr/> <p>S. 89°56'30" W., beginning new measurement.</p>
19.972	<p>Point for the W 1/16 sec. cor. of secs. 2 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>W 1/16 $\frac{S35}{S\ 2}$ 2006</p> </div> <p>Set a steel sign post alongside the stainless steel post.</p>
38.70	Top of bluff; descend into bottom land.
39.60	Toe of slope; enter willows, scattered tamarisk and meadow grass.

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS									
39.944	<p>The cor. of secs. 2, 3, 34 and 35, perpetuated by person(s) unknown, monumented with a steel T post, 24 ins. long, 1 in. diam., firmly set, projecting 1 in. above the ground, with a stainless steel tag of unknown origin nailed to the top, mkd. USBR 1118, with a weathered redwood post, 4x4x20 ins. long, no mks. visible, and a weathered redwood post of unknown origin, 2 1/2x3x30 ins. long, with ground point and illegible scribe mks. visible, lying loose alongside the steel T post.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td>T15N</td><td>R27E</td></tr> <tr><td>S34</td><td>S35</td></tr> <tr><td>S 3</td><td>S 2</td></tr> <tr><td colspan="2">T14N</td></tr> </table> <p>2006</p> </div> <p>From this cor., a rebar of unknown origin, 28 ins. long, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, in the remains of an aerial photo panel, bears N. 65° E., 0.009 chs. dist.</p> <p>Deposit the original redwood post, the redwood post with ground point, the steel T-post and the rebar alongside the stainless steel post and below the surface of the ground.</p>	T15N	R27E	S34	S35	S 3	S 2	T14N	
T15N	R27E								
S34	S35								
S 3	S 2								
T14N									
	<hr/> <p>N. 89°58'20" W., bet. secs. 3 and 34.</p>								
	<p>Over bottom land subject to flooding, through willows, scattered tamarisk, cattails and meadow grass.</p>								
4.10	Graded dirt road, 15 lks. wide, bears NW. and SE.								
10.011	<p>Point for the E-E 1/64 sec. cor. of secs. 3 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td>E-E 1/64</td><td>S34</td></tr> <tr><td></td><td>S 3</td></tr> </table> <p>2006</p> </div> <p>Set a steel sign post alongside the stainless steel post.</p>	E-E 1/64	S34		S 3				
E-E 1/64	S34								
	S 3								
12.90	Graded dirt road, 25 lks. wide, bears NW. and SE.								
20.022	Point for the E 1/16 sec. cor. of secs. 3 and 34.								

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> $\begin{array}{r} \text{E } 1/16 \quad \frac{\text{S34}}{\text{S } 3} \\ 2006 \end{array}$ <p>Set a steel sign post alongside the stainless steel post.</p>
30.033	<p>Point for the W-E 1/64 sec. cor. of secs. 3 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> $\begin{array}{r} \text{W-E } 1/64 \quad \frac{\text{S34}}{\text{S } 3} \\ 2006 \end{array}$ <p>Set a steel sign post alongside the stainless steel post.</p>
40.044	<p>Point for the 1/4 sec. cor. of secs. 3 and 34, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> $\begin{array}{r} \text{T15N R27E} \\ \text{1/4} \quad \frac{\text{S34}}{\text{S } 3} \\ \text{T14N} \\ 2006 \end{array}$ <p>Set a steel sign post alongside the stainless steel post.</p>
41.00	Enter dense cattails.
49.00	Leave dense cattails.
50.055	<p>Point for the E-W 1/64 sec. cor. of secs. 3 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> $\begin{array}{r} \text{E-W } 1/64 \quad \frac{\text{S34}}{\text{S } 3} \\ 2006 \end{array}$ <p>Set a steel sign post alongside the stainless steel post.</p>

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
60.066	<p>Point for the W 1/16 sec. cor. of secs. 3 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> $\text{W } 1/16 \frac{\text{S34}}{\text{S } 3}$ <p>2007</p> <p>Set a steel sign post alongside the stainless steel post.</p>
70.077	<p>Point for the W-W 1/64 sec. cor. of secs. 3 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> $\text{W-W } 1/64 \frac{\text{S34}}{\text{S } 3}$ <p>2006</p>
80.088	<p>The cor. of secs. 3, 4, 33 and 34, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 14 N., R. 27 E., executed under Group No. 670, with a redwood post, 4 ins. square, projecting 6 ins. above the ground, alongside the stainless steel post.</p>
	<hr/> <p>N. 89°48'20" W., bet. secs. 4 and 33.</p> <p>Over nearly level bottom land, through willows, cattails and meadow grass.</p>
9.970	<p>Point for the E-E 1/64 sec. cor. of secs. 4 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> $\text{E-E } 1/64 \frac{\text{S33}}{\text{S } 4}$ <p>2006</p> <p>Set a steel sign post alongside the stainless steel post.</p>
19.940	<p>Point for the E 1/16 sec. cor. of secs. 4 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	$\begin{array}{r} \text{S33} \\ \text{E } 1/16 \frac{\text{---}}{\text{S } 4} \end{array}$ <p>2006</p> <p>Set a steel sign post alongside the stainless steel post.</p>
29.910	True point for the W-E 1/64 sec. cor. of secs. 4 and 33, falls in a pond, 75 lks. wide, where it is impractical to establish a permanent monument.
30.264	<p>Point selected for the witness cor. to the W-E 1/64 sec. cor. of secs. 4 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> $\begin{array}{r} \text{W C} \\ \text{S33} \\ \text{W-E } 1/64 \frac{\text{---}}{\text{S } 4} \rightarrow \end{array}$ <p>2006</p>
39.880	<p>The 1/4 sec. cor. of secs. 4 and 33, monumented with a stainless steel post, 2 1/2 ins. diam., set flush with the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 14 N., R. 27 E., executed under Group No. 670, with an iron pipe, 2 ins. diam., set alongside the stainless steel post, 1 in. below the surface of the ground.</p> <p>From this cor., an iron pipe of unknown origin, 2 ins. diam., set flush with the surface of the ground, bears N. 0°15' W., 0.057 chs. dist.</p> <p>Set a steel sign post alongside the stainless steel post.</p> <hr/> <p>N. 89°40'00" W., beginning new measurement.</p>
9.976	<p>Point for the E-W 1/64 sec. cor. of secs. 4 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> $\begin{array}{r} \text{S33} \\ \text{E-W } 1/64 \frac{\text{---}}{\text{S } 4} \end{array}$ <p>2006</p> <p>Set a steel sign post alongside the stainless steel post.</p>
19.952	<p>Point for the W 1/16 sec. cor. of secs. 4 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	$\begin{array}{r} \text{S33} \\ \text{W } 1/16 \text{ ---} \\ \text{S } 4 \end{array}$ <p>2006</p> <p>Set a steel sign post alongside the stainless steel post.</p>
29.928	<p>Point for the W-W 1/64 sec. cor. of secs. 4 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> $\begin{array}{r} \text{S33} \\ \text{W-W } 1/64 \text{ ---} \\ \text{S } 4 \end{array}$ <p>2006</p> <p>Set a steel sign post alongside the stainless steel post.</p>
37.794	<p>Point selected for the witness cor. to the cor. of secs. 4, 5, 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> $\begin{array}{c} \text{WC} \\ \text{T15N R27E} \\ \begin{array}{c c} \text{S32} & \text{S33} \\ \hline \text{S } 5 & \text{S } 4 \end{array} \\ \text{T14N} \end{array}$ <p>2007</p>
38.90	Left bank of the Walker River, bears NE. and SW.; thence across river, course irregularly S.
39.904	True point for the cor. of secs. 4, 5, 32 and 33, determined by the method of irregular boundary adjustment, falls on the right bank of the Walker River, bears N. and S., where it enters a pond to S., and at a place impractical to set a permanent monument.
	<hr/> <p>S. 89°12'00" W., bet. secs. 5 and 32.</p> <p>Over bottom land, through willows, scattered tamarisk, cattails and meadow grass.</p>
0.319	Point for the 1989 witness cor. to secs. 4, 5, 32 and 33, at record distance; there was no remaining evidence found. This position now serves no further function.
3.10	E. bank of pond, bears N. and S.
5.60	W. bank of pond, bears NW. and SE., continue through willows, scattered tamarisk, cattails and meadow grass.

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
9.985	<p>Point for the E-E 1/64 sec. cor. of secs. 5 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> $\text{E-E } 1/64 \frac{S32}{S 5}$ <p>2006</p> <p>Set a steel sign post alongside the stainless steel post.</p>
19.970	<p>Point for the E 1/16 sec. cor. of secs. 5 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> $\text{E } 1/16 \frac{S32}{S 5}$ <p>2006</p> <p>Set a steel sign post alongside the stainless steel post.</p>
29.955	<p>Point for the W-E 1/64 sec. cor. of secs. 5 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> $\text{W-E } 1/64 \frac{S32}{S 5}$ <p>2006</p> <p>Set a steel sign post alongside the stainless steel post.</p>
32.60	Toe of bluff, bears NW. and SE.
34.20	Top of bluff; thence over rolling land covered with low brush, cheat and bunch grass.
39.940	<p>The 1/4 sec. cor. of secs. 5 and 32, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 14 N., R. 27 E., executed under Group No. 670, with an iron pipe, 1 in. diam., projecting 7 ins. above the ground, set alongside the stainless steel post.</p> <hr/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Reestablishment of a Portion the Survey Executed by H.E. Franks and J.S. Mullen, U.S. Deputy Surveyors, in 1904 and a Portion of the Dependent Resurvey Executed by Robert A. Pratt, Cadastral Surveyor, in 1989</p>
	<p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°00'40" W., bet. secs. 35 and 36.</p> <p>Ascend gentle S. slope, through low brush, cheat and bunch grass, and along a barbed wire fence line, wood posts, posting the boundary of the Walker River Indian Reservation with steel sign posts.</p>
20.02	From this point, a well-embedded mound of stone of unknown origin, 2 ft. diam., bears W., 0.05 chs. dist.
25.80	Powerline, wood poles, bears N. 55° W. and S. 55° E.
33.96	From this point, the N. end of barbed wire fence, extending S., bears W., 0.09 chs. dist.
34.25	Remains of old U.S. Alternate Highway No. 95, 15 lks. wide, bears NW. and SE.
34.40	From this point, the S. end of a barbed wire fence, wood posts, extending NNW. to a cattle guard, bears E., 0.19 chs. dist.
34.569	Intersect a Nevada Department of Transportation wood post, 4 ins. square, firmly set, projecting 4 ft. above the ground.
35.027	From this point, a Nevada Department of Transportation concrete block, 6 ins. square, firmly set, projecting 6 ins. above the ground, with brass wire projecting from top center, bears E., 0.060 chs. dist.
36.382	From this point, a Nevada Department of Transportation wood post, 4 ins. square, firmly set, projecting 4 ft. above the ground, bears W., 0.007 chs. dist.
37.58	From this point, the cor. of barbed wire fences extending S. and NNE., bears E., 0.10 chs. dist.
38.20	Center of pavement, Alternate U.S. Highway No. 95, bears N. 56 3/4° W. and S. 56 3/4° E.
40.011	<p>The 1/4 sec. cor. of secs. 35 and 36, monumented with a limestone(record: granite), 12x10 ins., firmly set, projecting 8 ins. above the ground, with 1/4 chiseled on W. face at ground surface, with a Nevada Department of Transportation wood post, 4 ins. square, firmly set, projecting 4 ft. above the ground, alongside the stone.</p> <p>Chisel an X on top center of mkd. stone.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>from which</p> <p>A stainless steel post, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 67°58' E., 81.1 lks. dist., with brass cap mkd. RM 1/4 S36 2006 53.5 FT TO COR and an arrow pointing to the cor.</p> <p>A stainless steel post, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 15°49' W., 80.2 lks. dist., with brass cap mkd. RM 1/4 S35 2006 52.9 FT TO COR and an arrow pointing to the cor.</p> <hr/> <p>N. 0°05'00" W., beginning new measurement.</p>
1.793	From this point, a Nevada Department of Transportation wood post, 4 ins. square, firmly set, projecting 4 ft. above the ground, bears W., 0.005 chs. dist.
8.50	Foot of hill.
14.00	Spur, slopes ESE.
40.156	<p>The cor. of secs. 25, 26, 35 and 36, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 14 N., R. 27 E., executed under Group No. 670, with a mound of stone, 3 ft. base, 1 1/2 ft. high, W. of cor.</p> <hr/> <p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°50'10" W., bet. secs. 13 and 24.</p> <p>Over rolling land covered with low brush, cheat and bunch grass.</p>
5.60	Dirt road, 15 lks. wide, bears NW. and SE.
20.023	<p>Point for the E 1/16 sec. cor. of secs. 13 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{r} \text{E } 1/16 \quad \frac{S13}{S24} \\ 2006 \end{array}$ </div>
40.046	<p>The 1/4 sec. cor. of secs. 13 and 24, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 14 N., R. 27 E., executed under Group No. 670.</p> <hr/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the 1/4 sec. cor. of secs. 13 and 14, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 14 N., R. 27 E., executed under Group No. 670, with a redwood post, 3 1/2 ins. square, projecting 14 ins. above the ground, with illegible scribe mks. visible, and an iron pipe, 1 in. diam., projecting 6 ins. above the ground, set alongside the stainless steel post.</p> <p>Corner is located under a barbed wire fence, wood and steel posts, bears N. and S.</p> <p>N. 0°10'50" E., bet. secs. 13 and 14.</p> <p>Over rolling land, covered with low brush, cheat and bunch grass, and along barbed wire fence.</p> <p>2.85 Dirt road, 15 lks. wide, bears NE. and SW.</p> <p>20.045 Point for the N 1/16 sec. cor. of secs. 13 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S14 S13 2006</p> <p>40.090 The cor. of secs. 11, 12, 13 and 14, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 14 N., R. 27 E., executed under Group No. 670, with a redwood post, 3 1/2 ins. square, projecting 10 ins. above the ground, set alongside the stainless steel post.</p> <p>Corner is located under a barbed wire fence, wood and steel posts, bears N. and S.</p> <hr/> <p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°41'10" W., bet. secs. 12 and 13.</p> <p>Over rolling land covered with low brush, cheat and bunch grass.</p> <p>15.50 Graded dirt road, 15 lks. wide, bears NW. and SE.</p> <p>19.956 Point for the E 1/16 sec. cor. of secs. 12 and 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">E 1/16 $\frac{S12}{S13}$ 2006</p>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Set a steel sign post alongside the stainless steel post.
26.60	Top of bluff, bears NW. and SE.; descend into bottom land, through willows, scattered tamarisk, cattails and meadow grass.
39.912	Point for the 1/4 sec. cor. of secs. 12 and 13, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;"> T14N R27E S12 1/4 $\frac{\quad}{\quad}$ S13 2006 </div>
	Set a steel sign post alongside the stainless steel post.
49.890	Point for the E-W 1/64 sec. cor. of secs. 12 and 13. POINT NOT MONUMENTED
52.70	Left bank of the Walker River, bears NW. and SE.; thence across river, course SE.
53.30	Right bank of the Walker River, bears NW. and SE.
58.00	Enter rolling land covered with low brush, cheat and bunch grass.
59.868	Point for the W 1/16 sec. cor. of secs. 12 and 13. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;"> W 1/16 $\frac{S12}{S13}$ 2006 </div>
	Set a steel sign post alongside the stainless steel post.
66.10	Graded dirt road, 15 lks. wide, bears NNE. and SSW.
79.824	The cor. of secs. 11, 12, 13 and 14. <hr/> N. 0°04'20" W., bet. secs. 11 and 12. Over rolling land covered with low brush, cheat and bunch grass, and along barbed wire fence.
1.34	From this point, the N. end of barbed wire fence extending S., bears E., 0.02 chs. dist.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
9.946	<p>Point for the S-S 1/64 sec. cor. of secs. 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S-S 1/64 S11 S12 2006</p> <p>Set a steel sign post alongside the stainless steel post.</p>
11.25	Dirt road, 15 lks. wide, bears NW. and SE.
13.50	Enter bottomland, through willows, scattered tamarisk, cattails and meadow grass.
19.892	<p>Point for the S 1/16 sec. cor. of secs. 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S11 S12 2006</p> <p>Set a steel sign post alongside the stainless steel post.</p>
29.838	<p>Point for the N-S 1/64 sec. cor. of secs. 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">N-S 1/64 S11 S12 2006</p> <p>Set a steel sign post alongside the stainless steel post.</p>
39.784	<p>Point for the 1/4 sec. cor. of secs. 11 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T14N R27E 1/4 S 11 S 12 2006</p> <p>Set a steel sign post alongside the stainless steel post.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
47.40	Right bank of the Walker River, bears NW. and SE.; thence across river, course SE.
48.40	Left bank of the Walker River, bears NW. and SE.
49.730	Point for the S-N 1/64 sec. cor. of secs. 11 and 12. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. S-N 1/64 S11 S12 2006 Set a steel sign post alongside the stainless steel post.
54.00	Enter gently rolling land covered with low brush, cheat and bunch grass.
54.46	From this point, the S. end of a barbed wire fence, wood and steel posts, extending N., bears E., 0.24 chs. dist.; thence along W. side of barbed wire fence.
59.676	Point for the N 1/16 sec. cor. of secs. 11 and 12. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. N 1/16 S11 S12 2006 Set a steel sign post alongside the stainless steel post. Corner is located W., 0.09 chs. dist., of barbed wire fence, bears N. and S.
69.622	Point for the N-N 1/64 sec. cor. of secs. 11 and 12. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. N-N 1/64 S11 S12 2006 Set a steel sign post alongside the stainless steel post.
79.568	The cor. of secs. 1, 2, 11 and 12, monumented with a weathered redwood post, 3x4x35 ins. long, firmly set, projecting 8 ins. above the ground, with illegible scribe mks. on the NE. face.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{r l} \text{T14N R27E} & \\ \hline \text{S } 2 & \text{S } 1 \\ \hline \text{S11} & \text{S12} \end{array}$ </div> <p style="text-align: center;">2006</p> <p>Deposit the original redwood post alongside the stainless steel post and below the surface of the ground.</p> <p>Set a steel sign post alongside the stainless steel post.</p> <p>Corner is located under a barbed wire fence, wood and steel posts, bears N. and S.</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°51'50" W., bet. secs. 1 and 12.</p> <p>Over nearly level, rolling land covered with low brush, cheat and bunch grass.</p> <p>40.201 The 1/4 sec. cor. of secs. 1 and 12, monumented with a weathered redwood post, 3x4x35 ins. long, firmly set, projecting 10 ins. above the ground, no mks. visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{r l} \text{T14N R27E} & \\ \hline \text{S } 1 & \\ 1/4 & \hline \text{S12} & \end{array}$ </div> <p style="text-align: center;">2006</p> <p>Deposit the original redwood post alongside the stainless steel post and below the surface of the ground.</p> <hr/> <p>N. 89°49'50" W., beginning new measurement.</p> <p>19.832 Point for the W 1/16 sec. cor. of secs. 1 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	$\begin{array}{r} S\ 1 \\ W\ 1/16 \quad \hline S12 \end{array}$ <p>2006</p>
30.10	Graded dirt road, 30 lks. wide, bears WNW. and ESE.
39.50	Dirt road, 15 lks. wide, bears NNE. and S.
39.664	The cor. of secs. 1, 2, 11 and 12.
	<hr/> <p>N. 0°02'50" E., bet. secs. 1 and 2.</p> <p>Over nearly level land covered with low brush, cheat and bunch grass, and along barbed wire fence.</p>
2.00	Graded dirt road, 30 lks. wide, bears WNW. and ESE.
19.976	Point for the S 1/16 sec. cor. of secs. 1 and 2.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the ground, over a plastic-encased magnet, with brass cap mkd.
	$\begin{array}{r} S\ 1/16 \\ S\ 2 \quad \quad S\ 1 \end{array}$ <p>2006</p>
	Cor. is located E., 0.11 chs. dist. of barbed wire fence, bears N. and S.
39.952	The 1/4 sec. cor. of secs. 1 and 2, monumented with a weathered redwood post, 3x4x35 ins. long, firmly set, projecting 16 ins. above the ground, no mks. visible, with a stone, 3x3x1 ins., faintly chiseled X, recovered from alongside and below the surface of the ground.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	$\begin{array}{r} T14N\ R27E \\ 1/4 \\ S\ 2 \quad \quad S\ 1 \end{array}$ <p>2006</p>
	Deposit the original redwood post and the stone memorial alongside the stainless steel post.
	Corner is located under a barbed wire fence, bears N. and S.
	<hr/> <p>N. 0°21'40" E., beginning new measurement.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Continue along barbed wire fence, bears N. and S.
40.034	The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., hereinbefore described.
	From the cor. of secs. 11, 12, 13 and 14.
	S. 89°53'40" W., bet. secs. 11 and 14.
	Over rolling land covered with low brush, cheat and bunch grass.
9.979	Point for the E-E 1/64 sec. cor. of secs. 11 and 14.
	POINT NOT MONUMENTED
19.958	Point for E 1/16 sec. cor. of secs. 11 and 14.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	E 1/16 $\frac{S11}{S14}$
	2006
39.916	The 1/4 sec. cor. of secs. 11 and 14, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 14 N., R. 27 E., executed under Group No. 670, with a weathered redwood post, 3x5 ins., projecting 13 ins. above the ground, with scribe mks. S11 visible, set alongside the stainless steel post.
	From the cor. of secs. 1, 2, 11 and 12.
	N. 89°54'20" W., bet. secs. 2 and 11.
	Over gently rolling land covered with low brush, cheat and bunch grass.
2.70	Dirt road, 15 lks. wide, bears NW. and SE.
6.00	Enter bottom land, subject to flooding, through willows, scattered tamarisk and meadow grass.
19.927	Point for the E 1/16 sec. cor. of secs. 2 and 11.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	E 1/16 $\frac{S 2}{S11}$
	2006
	Set a steel sign post alongside the stainless steel post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
26.20	Left bank of the Walker River, bears NNW. and SSE.; thence across river, course S.
27.10	Right bank of the Walker River, bears N. and S.; enter dense willows and cattails.
34.00	Enter willows, scattered tamarisk and meadow grass.
37.112	Point selected for the witness cor. to the 1/4 sec. cor. of secs. 2 and 11. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;"> WC T14N R27E S 2 ←1/4 $\frac{\quad}{S11}$ 2007 </div>
	Set a steel sign post alongside the stainless steel post.
37.30	E. bank of pond; thence across pond.
39.854	True point for the 1/4 sec. cor. of secs. 2 and 11, at proportionate distance; there is no remaining evidence of the original corner; falls in pond where it is impractical to set a permanent monument.
40.30	W. bank of pond; thence through willows, scattered tamarisk and meadow grass.
50.90	Tributary of the Walker River, 20 lks. wide, course SSW.
57.00	Enter gently rolling land covered with low brush, cheat and bunch grass.
59.781	Point for the W 1/16 sec. cor. of secs. 2 and 11. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;"> W 1/16 $\frac{S 2}{S11}$ 2006 </div>
	From this point, a weathered redwood post of unknown origin, 4x4x24 ins. long, no mks. visible, was found lying loose nearby, the original position indeterminable, not utilized in the course of this survey. Deposit the redwood post and set a steel sign post alongside the stainless steel post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
67.35	Graded dirt road, 15 lks. wide, bears NNE. and SSW.
79.708	<p>The cor. of secs. 2, 3, 10 and 11, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 14 N., R. 27 E., executed under Group No. 670, with a weathered redwood post, 4 ins. square, projecting 15 ins. above the ground, with scribe mks. 14N S3 visible, an inverted iron pipe, 2 ins. diam., projecting 4 ins. above the ground, with split flanges, and a steel fence post, projecting 4 ft. above the ground, set alongside the stainless steel post.</p> <hr/> <p>N. 0°02'00" W., bet. secs. 2 and 3.</p> <p>Over gently rolling land covered with low brush, cheat and bunch grass.</p>
12.90	Dirt road, 15 lks. wide, bears NW. and SE.
16.00	Descend into bottom land, through willows, scattered tamarisk, cattails and meadow grass.
19.926	<p>Point for the S 1/16 sec. cor. of secs. 2 and 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>S 1/16 S 3 S 2</p> <p>2006</p> </div> <p>Set a steel sign post alongside the stainless steel post.</p>
29.889	<p>Point for the N-S 1/64 sec. cor. of secs. 2 and 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>N-S 1/64 S 3 S 2</p> <p>2006</p> </div> <p>Set a steel sign post alongside the stainless steel post.</p>
30.10	Right bank of the Walker River, bears NW. and SE.; thence across river, course NE.
30.70	Left bank of the Walker River, bears NW. and SE.
39.852	Point for the 1/4 sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T14N R27E 1/4 S 3 S 2</p> <p style="text-align: center;">2006</p> <p>Set a steel sign post alongside the stainless steel post.</p>
49.815	<p>Point for the S-N 1/64 sec. cor. of secs. 2 and 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S-N 1/64 S 3 S 2</p> <p style="text-align: center;">2006</p> <p>Set a steel sign post alongside the stainless steel post.</p>
59.778	<p>Point for the N 1/16 sec. cor. of secs. 2 and 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S 3 S 2</p> <p style="text-align: center;">2006</p> <p>Set a steel post alongside the stainless steel post.</p>
70.75	<p>Graded dirt road, 30 lks. wide, bears NW. and SE.</p>
79.814	<p>The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>S. 89°58'30" W., bet. secs. 3 and 10.</p> <p>Over gently rolling land covered with low brush, cheat and bunch grass.</p>
20.021	<p>Point for the E 1/16 sec. cor. of secs. 3 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	$\begin{array}{r} \text{S } 3 \\ \text{E } 1/16 \quad \hline \text{S } 10 \end{array}$ <p>2006</p>
40.042	<p>The 1/4 sec. cor. of secs. 3 and 10, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 14 N., R. 27 E., executed under Group No. 670, with a weathered redwood post, 3 ins. square, projecting 12 ins. above the ground, with scribe mks. S3 visible, set alongside the stainless steel post.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 3 and 4, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 14 N., R. 27 E., executed under Group No. 670; with a weathered redwood post, 4 ins. square, projecting 18 ins. above the ground, and an inverted iron pipe, 1 in. diam., projecting 10 ins. above the ground, with split flanges, set alongside the stainless steel post.</p> <p>N. 0°00'50" W., bet. secs. 3 and 4.</p> <p>Over gently rolling land covered with low brush, cheat and bunch grass.</p>
8.50	Graded dirt road, 15 lks. wide, bears WNW. and ESE.
12.50	Descend into bottom land, through willows, scattered tamarisk, cattails and meadow grass.
19.90	Right bank of the Walker River, bears NW. and SE.; thence across river, course SE.
20.062	True point for the N 1/16 sec. cor. of secs. 3 and 4, falls in the Walker River, where it is impractical to set a permanent monument.
20.80	Left bank of the Walker River, bears NW. and SE.; enter willows, scattered tamarisk, cattails and meadow grass.
20.955	<p>Point selected for the witness cor. to the N 1/16 sec. cor. of secs. 3 and 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC</p> <p>N 1/16</p> <p>S 4 S 3</p> <p>↓</p> <p>2006</p> </div>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
30.50	Center of old river channel, 80 lks. wide, course ESE.
39.983	The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., hereinbefore described.
	<p>From the 1/4 sec. cor. of secs. 4 and 5, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 14 N., R. 27 E., executed under Group No. 670, with a weathered redwood post, 3 ins. square, projecting 16 ins. above the ground, set alongside the stainless steel post.</p> <p>Set a steel sign post alongside the stainless steel post.</p> <p>N. 0°07'30" E., bet. secs. 4 and 5.</p> <p>Over gently rolling, nearly level land, covered with low brush, cheat and bunch grass.</p>
14.35	Dirt road, 15 lks. wide, bears NW. and SE.
20.179	Point for the N 1/16 sec. cor. of secs. 4 and 5.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S 5 S 4</p> <p style="text-align: center;">2006</p> <p>Set a steel sign post alongside the stainless steel post.</p> <p>Descend into bottom land, through willows, scattered tamarisk, cattails and meadow grass.</p>
27.80	Right bank of the Walker River, bears ENE. and SW.; thence across river, course ENE.
28.30	Left bank of the Walker River, bears ENE. and WSW.; thence through willows, scattered tamarisk, cattails and meadow grass.
30.198	Point for control determined latitudinally at midpoint in distance bet. the N 1/16 sec. cor. of secs. 4 and 5 and the true point for the cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp. This point will control the southerly boundary of Indian Trust Patent No. 459 in sec. 5.
	POINT NOT MONUMENTED
34.80	Left bank of the Walker River, bears NE. and SW.; thence across river, course SW.
35.10	Right bank of the Walker River, bears NE. and SW.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
37.80	S. bank of pond, bears NE. and SW.; thence across pond.
40.217	The true point for the cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., hereinbefore described.
	<p>From the cor. of secs. 8, 9, 16 and 17, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 14 N., R. 27 E., executed under Group No. 670, with a weathered redwood post, 3 ins. square, projecting 5 ins. above the ground, and a weathered wood stake 1x3 ins., projecting 4 ins. above the ground, set along the stainless steel post.</p> <p>S. 89°58'30" W., bet. secs. 8 and 17.</p> <p>Over rolling land covered with low brush, cheat and bunch grass, posting the boundary of the Walker River Indian Reservation with steel sign posts.</p>
3.00	Trail road, 15 lks. wide, bears NW. and SE.
40.013	<p>The 1/4 sec. cor. of secs. 8 and 17, monumented with the rotted remains of a redwood post, recovered from below the surface of the ground, with upper remains of post, 3x3x20 ins. long, no mks. visible, lying loose on the surface of the ground. This position is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T14N R27E</p> <p>S 8</p> <p>1/4 <u> </u></p> <p>S17</p> <p>2006</p> </div> <p>Deposit the remains of the original redwood post alongside the stainless steel post and below the surface of the ground.</p> <hr/> <p>N. 89°40'50" W., beginning new measurement.</p>
33.50	Graded dirt road, 15 lks. wide, bears NE. and SSW.
40.244	The cor. of secs. 7, 8, 17 and 18, monumented with the remains of a redwood post, recovered 8 ins. below the surface of the ground, with upper portion of post, 4x4x24 ins. long, with scribe mks. 14N S8 visible on one face, lying loose nearby, and a rebar of unknown origin, 1/2 in. diam., firmly set, projecting 8 ins. above the ground, alongside the remains of the redwood post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr> <td>T14N</td><td>R27E</td></tr> <tr> <td>S 7</td><td>S 8</td></tr> <tr> <td>S18</td><td>S17</td></tr> </table> <p>2006</p> </div> <p>Deposit the remains of the original redwood post and the rebar alongside the stainless steel post and below the surface of the ground.</p> <hr/> <p>N. 0°03'30" W., bet. secs. 7 and 8.</p> <p>Over rolling land covered with low brush, cheat and bunch grass, posting the boundary of the Walker River Indian Reservation with steel sign posts.</p> <p>1.25 From this point, the SW. cor. of a concrete hut, 3 1/2x4 ft., bears E., 0.06 chs. dist., the long side of which bears N. 87° E.</p> <p>40.090 The 1/4 sec. cor. of secs. 7 and 8, monumented with a weathered redwood post, 3x3x32 ins. long, firmly set, projecting 13 ins. above the ground, no mks. visible, with a stone, 5x4x2 ins., with chiseled X, recovered from alongside and below the surface of the ground.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr> <td>T14N</td><td>R27E</td></tr> <tr> <td>1/4</td><td></td></tr> <tr> <td>S 7</td><td>S 8</td></tr> </table> <p>2006</p> </div> <p>Deposit the original redwood post and the stone memorial alongside the stainless steel post and below the surface of the ground.</p> <hr/> <p>N. 0°04'00" W., beginning new measurement.</p> <p>39.876 The cor. of secs. 5, 6, 7 and 8, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 14 N., R. 27 E., executed under Group No. 670, with a weathered redwood post, 3x4x20 ins. long, with illegible scribe mks. visible, lying loose nearby, and a steel fence post, projecting 4 ft. above the ground, alongside the stainless steel post.</p>	T14N	R27E	S 7	S 8	S18	S17	T14N	R27E	1/4		S 7	S 8
T14N	R27E												
S 7	S 8												
S18	S17												
T14N	R27E												
1/4													
S 7	S 8												

DEPENDENT RESURVEY OF A PORTION OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 5,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">Reestablishment of a Portion the Subdivision Executed by Robert A. Pratt, Cadastral Surveyor, in 1989</p>
	<p>From the C-N 1/16 sec. cor. of sec. 5, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the subdivision of sec. 5, T. 14 N., R. 27 E., executed under Group No. 670.</p> <p>N. 0°08'20" E., on a portion of the N-S center line of sec. 5.</p> <p>Over nearly level, gently rolling land covered with low brush, cheat and bunch grass.</p>
9.858	<p>Point for control determined latitudinally at midpoint in distance bet. the C-N 1/16 sec. cor. of sec. 5 and the 1/4 sec. cor. of secs. 5 and 32, on the N. bdy. of the Tp. This point will control the southerly boundary of Indian Trust Patent No. 459 in sec. 5.</p> <p>POINT NOT MONUMENTED</p>
9.918	<p>The C-N-N 1/64 sec. cor. of sec. 5, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. as described in the field notes of the subdivision of sec. 5, T. 14 N., R. 27 E., executed under Group No. 670.</p>
	<p>N. 0°08'20" E., beginning new measurement.</p>
9.798	<p>The 1/4 sec. cor. of secs. 5 and 32, on the N. bdy. of the Tp., hereinbefore described.</p>
	<p style="text-align: center;">SUBDIVISION OF SECTION 2, T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA</p>
	<p>From the true point for the 1/4 sec. cor. of secs. 2 and 11.</p> <p>N. 0°02'10" E., on the N-S center line of sec. 2.</p> <p>Across pond.</p>
1.60	<p>N. bank of pond, bears E. and W.; enter bottom land, through willows, scattered tamarisk, cattails and meadow grass.</p>
5.30	<p>Slough, 90 lks. wide, 3 ft. deep, bears NE. and SW.</p>
9.976	<p>Point for the C-S-S 1/64 sec. cor. of sec. 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;"> $\begin{array}{c} \text{C} \\ \text{S-S } 1/64 \text{ } \text{ S } 2 \\ \text{C} \end{array}$ </p> <p style="text-align: center;">2006</p>

SUBDIVISION OF SECTION 2,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a steel sign post alongside the stainless steel post.</p> <p>From this point, a weathered redwood post of unknown origin, 4 ins. square, firmly set, projecting 10 ins. above the ground, with illegible scribe mks. visible, bears S. 82°54' E., 0.184 chs. dist., not utilized in the course of this survey.</p>
19.952	<p>Point for the C-S 1/16 sec. cor. of sec. 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} C \\ S\ 1/16 \mid S\ 2 \\ C \end{array}$ <p>2006</p> </div> <p>Set a steel sign post alongside the stainless steel post.</p> <p>From this point, a weathered redwood post of unknown origin, 4 ins. square, firmly set, projecting 3 ins. above the ground, no mks. visible, bears S. 48°06' E., 0.369 chs. dist., not utilized in the course of this survey.</p>
21.50	Slough, 50 lks. wide, 3 ft. deep, bears NE. and SW.
24.50	Right bank of the Walker River, bears NW. and SE.; thence across river, course SE.
26.00	Left bank of the Walker River, bears NW. and SE.
27.00	Left bank of the Walker River, bears NE. and SW.; thence across river, course SW.
29.928	True point for the C-N-S 1/64 sec. cor. of sec. 2, falls in the Walker River, where it is impractical to set a permanent monument.
30.40	Left bank of the Walker River, bears NW. and SE.; thence over bottom land.
31.380	<p>Point selected for the witness cor. to the C-N-S 1/64 sec. cor. of sec. 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} WC \\ C \\ N-S\ 1/64 \mid S\ 2 \\ C \\ \downarrow \end{array}$ <p>2006</p> </div>

SUBDIVISION OF SECTION 2,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
32.50	Graded dirt road, 25 lks. wide, bears NW. and SE.; thence over bottom land covered with low brush, cheat and bunch grass.
39.904	<p>Point for the center 1/4 sec. cor. of sec. 2, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T14N R27E C 1/4 S 2</p> <p style="text-align: center;">2006</p> <p>From this point, a weathered redwood post of unknown origin, 4x4x28 ins. long, lying loose, no mks. visible, bears N. 53° E., 0.11 chs. dist., original position indeterminate, not utilized in the course of this survey.</p>
59.896	<p>Point for the C-N 1/16 sec. cor. of sec. 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;"> $\begin{array}{c} C \\ N\ 1/16 \left S\ 2 \\ C \end{array}$ </p> <p style="text-align: center;">2006</p>
79.923	<p>The 1/4 sec. cor. of secs. 2 and 35, on the N. bdy. of the Tp.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 1 and 2.</p> <p>N. 89°58'30" W., on the E-W center line of sec. 2.</p> <p>Over rolling land covered with low brush, cheat and bunch grass.</p>
19.928	<p>Point for the C-E 1/16 sec. cor. of sec. 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;"> $\begin{array}{c} E\ 1/16 \\ C \text{---} S\ 2 \text{---} C \end{array}$ </p> <p style="text-align: center;">2006</p>
39.856	The center 1/4 sec. cor. of sec. 2.
53.25	Graded dirt road, 30 lks. wide, bears NW. and SE.; thence over bottom land, through willows, scattered tamarisk, cattails and meadow grass.

SUBDIVISION OF SECTION 2,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
59.805	<p>Point for the C-W 1/16 sec. cor. of sec. 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} W \ 1/16 \\ C \text{---} S \ 2 \\ C \end{array}$ <p>2006</p> </div>
79.754	<p>The 1/4 sec. cor. of secs. 2 and 3.</p> <hr/> <p>From the E 1/16 sec. cor. of secs. 2 and 11.</p> <p>N. 0°02'30" E., on the N-S center line of the SE1/4 of sec. 2.</p> <p>Over bottom land, through willows, scattered tamarisk, cattails and meadow grass.</p>
9.982	<p>Point for the C-S-SE 1/64 sec. cor. of sec. 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} S \ 2 \\ C-S-SE \\ 1/64 \end{array}$ <p>2006</p> </div> <p>Set a steel sign post alongside the stainless steel post.</p>
14.50	<p>Enter gently rolling land covered with low brush, cheat and bunch grass.</p>
18.60	<p>Graded dirt road, 25 lks. wide, bears NW. and SE.</p>
19.964	<p>Point for the SE 1/16 sec. cor. of sec. 2, at intersection with the E-W center line of the SE1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} SE \ 1/16 \ S \ 2 \end{array}$ <p>2006</p> </div> <p>Set a steel sign post alongside the stainless steel post.</p>
39.928	<p>The C-E 1/16 sec. cor. of sec. 2.</p> <hr/>

SUBDIVISION OF SECTION 2,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the S 1/16 sec. cor. of secs. 1 and 2.</p> <p>N. 89°56'20" W., on the E-W center line of the SE1/4 of sec. 2.</p> <p>Over gently rolling land covered with low brush, cheat and bunch grass.</p>
19.928	The SE 1/16 sec. cor. of sec. 2.
21.40	Graded dirt road, 25 lks. wide, bears NW. and SE.
23.50	Enter bottom land, through willows, scattered tamarisk and meadow grass.
27.50	Left bank of the Walker River, bears NNW. and SSE.; thence across river, course SSE.
28.50	Right bank of the Walker River, bears NW. and SE.
39.856	The C-S 1/16 sec. cor. of sec. 2.
	<hr/> <p>From the C-S-SE 1/64 sec. cor. of sec. 2.</p> <p>N. 89°55'20" W., on the E-W center line of the SW1/4SE1/4 of sec. 2.</p> <p>Over bottom land, through willows, scattered tamarisk and meadow grass.</p>
8.10	Left bank of the Walker River, bears N. and SSE.; thence across river, course SSE.
9.10	Right bank of the Walker River, bears NW. and SE.; enter bottom land.
19.927	The C-S-S 1/64 sec. cor. of sec. 2.
	<hr/> <p>From the W 1/16 sec. cor. of secs. 2 and 11.</p> <p>N. 0°00'10" E., on the N-S center line of the SW1/4 of sec. 2.</p> <p>Over gently rolling land covered with low brush, cheat and bunch grass.</p>
7.60	From this point, the S. end of fallen barbed wire fence, wood posts, extending N., bears E., 0.07 chs. dist.; thence over bottom land, through willows, scattered tamarisk and meadow grass.
9.970	Point for the C-S-SW 1/64 sec. cor. of sec. 2.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

SUBDIVISION OF SECTION 2,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">S 2 C-S-SW 1/64 2006</p> <p>Corner is located W., 0.08 chs. dist. of fallen barbed wire fence, bears N. and S.</p>
15.70	Tributary of the Walker River, 15 lks. wide, drains SE.
18.35	From this point, the corner of fallen barbed wire fences, wood posts, extending NW. and S., bears E., 0.07 chs. dist.
19.940	<p>Point for the SW 1/16 sec. cor. of sec. 2, at intersection with the E-W center line of the SW1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SW 1/16 S 2 2006</p> <p>Set a steel sign post alongside the stainless steel post.</p>
29.910	<p>Point for the C-N-SW 1/64 sec. cor. of sec. 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 2 C-N-SW 1/64 2006</p> <p>Set a steel sign post alongside the stainless steel post.</p>
34.30	Right bank of the Walker River, bears NE. and SW.; thence across river, course NE.
35.40	Left bank of the Walker River, bears NE. and SW.; thence over bottom land through willows, scattered tamarisk and meadow grass.
39.880	<p>The C-W 1/16 sec. cor. of sec. 2.</p> <hr/> <p>From the C-S 1/16 sec. cor. of sec. 2.</p> <p>N. 89°56'30" W., on the E-W center line of the SW1/4 of sec. 2.</p> <p>Over bottom land, through willows, scattered tamarisk and meadow grass.</p>
19.938	The SW 1/16 sec. cor. of sec. 2.

SUBDIVISION OF SECTION 2,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
22.18	From this point, the corner of fallen barbed wire fences extending W. and SE., bears N., 0.16 chs. dist.; thence along fence line.
28.17	Corner of barbed wire fences extending E., SSE. and NNW.
39.876	The S 1/16 sec. cor. of secs. 2 and 3.
	<hr/>
	From the true point for the C-N-S 1/64 sec. cor. of sec. 2. N. 89°57'30" W., on the E-W center line of the NE1/4SW1/4 of sec. 2.
	Across the Walker River, course SE.
0.50	Right bank of the Walker River, bears NW. and SE.; thence over bottom land, through willows, scattered tamarisk and meadow grass.
3.60	Right bank of the Walker River, bears N. and S.; thence across river, course N.
4.50	Left bank of the Walker River, bears N. and S.; thence over bottom land, through willows, scattered tamarisk and meadow grass.
5.80	Left bank of the Walker River, bears NW. and SE.; thence across river, course SE.
7.10	Right bank of the Walker River, bears NW. and SE.; thence over bottom land, through willows, scattered tamarisk, and meadow grass.
19.944	The C-N-SW 1/64 sec. cor. of sec. 2.
	<hr/>
	From the C-S-S 1/64 sec. cor. of sec. 2. N. 89°55'20" W., on the E-W center line of the SE1/4SW1/4 of sec. 2.
	Over bottom land, through willows, scattered tamarisk, cattails and meadow grass.
17.10	Tributary of the Walker River, 30 lks. wide, course SE.
19.933	The C-S-SW 1/64 sec. cor. of secs. 2.
	<hr/>
	From the C-N-SW 1/64 sec. cor. of sec. 2. N. 89°57'40" W., on the E-W center line of the NW1/4SW1/4 of sec. 2.
	Over bottom land, through willows, scattered tamarisk, cattails and meadow grass.
19.944	The N-S 1/64 sec. cor. of secs. 2 and 3.
	<hr/>

SUBDIVISION OF SECTION 2,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the C-W 1/16 sec. cor. of sec. 2.</p> <p>N. 0°00'10" E., on the N-S center line of the NW1/4 of sec. 2.</p> <p>Over bottom land, through willows, scattered tamarisk, cattails and meadow grass.</p> <p>9.980 Point for the C-S-NW 1/64 sec. cor. of sec. 2, falls in a graded dirt road, 30 lks. wide, bears NW. and SE.</p> <p>Set a copper coated steel rod, 24 ins. long, 1/2 in. diam., 4 ins. below surface of the road, with brass cap, 1 1/2 ins. diam., mkd.</p> <p style="text-align: center;">BLM S 2 C-S-NW 1/64 2006</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, over a plastic-encased magnet, bears N. 54°21' E., 58.6 lks. dist., with brass cap mkd. RM C-S-NW 1/64 S2 38.7 FT TO COR 2006 and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">A stainless steel post, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, over a plastic-encased magnet, bears N. 15°10' W., 150.8 lks. dist., with brass cap mkd. RM C-S-NW 1/64 S2 99.5 FT TO COR 2006 and an arrow pointing to the cor.</p> <p>Thence over rolling land covered with low brush, cheat and bunch grass.</p> <p>19.960 Point for the NW 1/16 sec. cor. of sec. 2, at intersection with the E-W center line of the NW1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S 2 2006</p> <p>39.991 The W 1/16 sec. cor. of secs. 2 and 35, on the N. bdy. of the Tp.</p> <hr/> <p>From the C-N 1/16 sec. cor. of sec. 2.</p> <p>S. 89°55'40" W., on the E-W center line of the NW1/4 of sec. 2.</p>
--------	---

SUBDIVISION OF SECTION 2,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Over rolling land covered with low brush, cheat and bunch grass.
19.960	The NW 1/16 sec. cor. of sec. 2.
25.70	Graded dirt road, 30 lks. wide, bears NW. and SE.
39.920	The N 1/16 sec. cor. of secs. 2 and 3.
	<hr/> <p>From the C-S-NW 1/64 sec. cor. of sec. 2.</p> <p>S. 89°58'20" W., on the E-W center line of the SW1/4NW1/4 of sec. 2.</p> <p>Over bottom land, through willows, scattered tamarisk, cattails and meadow grass.</p>
19.955	The S-N 1/64 sec. cor. of secs. 2 and 3.
	<hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 3, T.14 N., R.27 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 3 and 10.</p> <p>N. 0°02'20" W., on the N-S center line of sec. 3.</p> <p>Over rolling land covered with low brush, cheat and bunch grass.</p>
19.940	<p>Point for the C-S 1/16 sec. cor. of sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} C \\ S\ 1/16\ S\ 3 \\ C \end{array}$ <p>2006</p> </div> <p>Set a steel sign post alongside the stainless steel post.</p>
33.60	Dirt road, 10 lks. wide, bears NW. and SE.
39.880	<p>Point for the center 1/4 sec. cor. of sec. 3, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T14N R27E</p> <p>C 1/4 S 3</p> <p>2006</p> </div>

SUBDIVISION OF SECTION 3,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	From this point, a weathered redwood post of unknown origin, 2x2 1/2x29 ins. long, with ground point, lying loose, no mks. visible, bears N. 4° E., 0.28 chs. dist., not utilized in the course of this survey.
44.00	Descend into bottom land subject to flooding, through willows, scattered tamarisk, cattails and meadow grass.
59.873	Point for the C-N 1/16 sec. cor. of sec. 3, at proportionate distance; falls in area subject to flooding, where it is impractical to set a permanent monument.
69.20	Right bank of the Walker River, bears E. and W.; thence across river, course E.
70.10	Left bank of the Walker River, bears E. and W.
79.851	The 1/4 sec. cor. of secs. 3 and 34, on the N. bdy. of the Tp.
	<hr/> <p>From the 1/4 sec. cor. of secs. 2 and 3.</p> <p>N. 89°59'10" W., on the E-W center line of sec. 3.</p> <p>Over bottom land subject to flooding, through willows, scattered tamarisk, cattails and meadow grass.</p>
7.20	Left bank of the Walker River, bears NW. and SE.; thence across river, course SE.
8.90	Right bank of the Walker River, bears NW. and SE.; thence over bottom land subject to flooding, through willows, scattered tamarisk, cattails and meadow grass.
10.011	<p>Point for the C-E-E 1/64 sec. cor. of sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> $\begin{array}{c} \text{E-E } 1/64 \\ \text{C} \text{-----} \text{C} \\ \text{S } 3 \end{array}$ <p style="text-align: center;">2006</p> <p>Set a steel sign post alongside the stainless steel post.</p>
13.00	Slough, 100 lks. wide, bears NW. and SE.
20.022	<p>Point for the C-E 1/16 sec. cor. of sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> $\begin{array}{c} \text{E } 1/16 \\ \text{C} \text{-----} \text{C} \\ \text{S } 3 \end{array}$ <p style="text-align: center;">2007</p> <p>Set a steel sign post alongside the stainless steel post.</p>

SUBDIVISION OF SECTION 3,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
30.033	True point for the C-W-E 1/64 sec. cor. of sec. 3, falls in an area subject to flooding, where it is impractical to set a permanent monument.
30.50	Enter rolling land covered with low brush, cheat and bunch grass.
30.486	<p>Point selected for the witness cor. to the C-W-E 1/64 sec. cor. of sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \text{WC} \\ \text{W-E } 1/64 \\ \text{C} \xrightarrow{\quad} \text{C} \\ \text{S } 3 \end{array}$ <p>2006</p> </div>
40.044	The center 1/4 sec. cor. of sec. 3.
59.30	Graded dirt road, 15 lks. wide, bears NW. and SE.
60.076	<p>Point for the C-W 1/16 sec. cor. of sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \text{W } 1/16 \\ \text{C} \xrightarrow{\quad} \text{C} \\ \text{S } 3 \end{array}$ <p>2006</p> </div> <p>Set a steel sign post alongside the stainless steel post.</p>
80.108	<p>The 1/4 sec. cor. of secs. 3 and 4.</p> <hr/> <p>From the C-E 1/16 sec. cor. of sec. 3.</p> <p>N. 0°02'10" W., on the N-S center line of the NE1/4 of sec. 3.</p> <p>Over bottom land subject to flooding, through willows, scattered tamarisk, cattails and meadow grass.</p>
14.50	Right bank of the Walker River, bears NW. and SE.; thence across river, course SE.
15.50	Left bank of the Walker River, bears NW. and SE.; thence over bottom land through willows, scattered tamarisk, cattails and meadow grass.
19.960	Point for the NE 1/16 sec. cor. of sec. 3, at intersection with the E-W center line of the NE1/4.

SUBDIVISION OF SECTION 3,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S 3</p> <p style="text-align: center;">2006</p> <p>Set a steel sign post alongside the stainless steel post.</p>
39.966	<p>The E 1/16 sec. cor. of secs. 3 and 34, on the N. bdy. of the Tp.</p> <hr/> <p>From the N 1/16 sec. cor. of secs. 2 and 3.</p> <p>N. 89°53'20" W., on the E-W center line of the NE1/4 of sec. 3.</p> <p>Over bottom land subject to flooding, through willows, scattered tamarisk, cattails and meadow grass.</p>
5.20	<p>Slough, 30 lks. wide, 3 ft. deep, drains SE.</p>
10.011	<p>Point for the C-E-NE 1/64 sec. cor. of sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 3 C-E-NE 1/64</p> <p style="text-align: center;">2006</p>
20.022	<p>The NE 1/16 sec. cor. of sec. 3.</p>
28.30	<p>Left bank of the Walker River, bears NNW. and SSW.; thence across river, course S.</p>
28.80	<p>Right bank of the Walker River, bears NNW. and SSE.; thence over bottom land, through willows, scattered tamarisk and meadow grass.</p>
30.033	<p>Point for the C-W-NE 1/64 sec. cor. of sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 3 C-W-NE 1/64</p> <p style="text-align: center;">2006</p> <p>Set a steel sign post alongside the stainless steel post.</p>
40.044	<p>The point for the C-N 1/16 sec. cor. of sec. 3.</p> <hr/>

SUBDIVISION OF SECTION 3,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the C-E-NE 1/64 sec. cor. of sec. 3.</p> <p>N. 0°02'00" W., on the N-S center line of the NE1/4NE1/4 of sec. 3.</p> <p>Over bottom land, through willows, scattered tamarisk, cattails and meadow grass.</p>
18.00	Graded dirt road, 25 lks. wide, bears NW. and SE.
20.021	The E-E 1/64 sec. cor. of secs. 3 and 34, on the N. bdy. of the Tp.
	<hr/> <p>From the C-E-E 1/64 sec. cor. of sec. 3.</p> <p>N. 0°02'00" W., on the N-S center line of the SE1/4NE1/4 of sec. 3.</p>
0.10	Right bank of the Walker River, bears NW. and SE.; thence across river, course SE.
1.00	Left bank of the Walker River, bears NW. and SE.; thence over bottom land, through willows, scattered tamarisk, cattails and meadow grass.
19.943	The C-E-NE 1/64 sec. cor. of sec. 3.
	<hr/> <p>From the true point for the C-W-E 1/64 sec. cor. of sec. 3.</p> <p>N. 0°02'20" W., on the N-S center line of the SW1/4NE1/4 of sec. 3.</p> <p>Over bottom land, through willows, scattered tamarisk, cattails and meadow grass.</p>
14.40	Right bank of the Walker River, bears NW. and SE.; thence across river, course SE.
15.60	Left bank of the Walker River, bears NW. and SE.; thence over bottom land.
16.50	Left bank of the Walker River, bears NE. and SW.; thence across river, course SW.
17.40	Right bank of the Walker River, bears NE. and SW.; thence over bottom land, through willows, scattered tamarisk, cattails and meadow grass.
19.976	The C-W-NE 1/64 sec. cor. of sec. 3.
	<hr/> <p>N. 0°02'20" W., on the N-S center line of the NW1/4NE1/4 of sec. 3.</p> <p>Over bottom land, through willows, scattered tamarisk, cattails and meadow grass.</p>

SUBDIVISION OF SECTION 3,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
6.90	Right bank of the Walker River, bears NW. and SE.; thence across river, course SE.
7.60	Left bank of the Walker River, bears NW. and SE.; thence over bottom land, through willows, scattered tamarisk and meadow grass.
19.992	The W-E 1/64 sec. cor. of secs. 3 and 34, on the N. bdy. of the Tp.
	<hr/> <p>From the E 1/16 sec. cor. of secs. 3 and 10.</p> <p>N. 0°02'10" W., on the N-S center line of the SE1/4 of sec. 3.</p> <p>Over rolling land covered with low brush, cheat and bunch grass.</p>
19.934	Point for the SE 1/16 sec. cor. of sec. 3, at intersection with the E-W center line of the SE1/4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	SE 1/16 S 3
	2006
26.55	Graded dirt road, 15 lks. wide, bears NW. and SE.; descend into bottom land, through willows, scattered tamarisk and meadow grass.
39.867	The C-E 1/16 sec. cor. of sec. 3.
	<hr/> <p>From the S 1/16 sec. cor. of secs. 2 and 3.</p> <p>S. 89°59'50" W., on the E-W center line of the SE1/4 of sec. 3.</p> <p>Over bottom land, through willows and cattails.</p>
5.00	Enter rolling land covered with low brush, cheat and bunch grass.
7.70	Graded dirt road, 15 lks. wide, bears NW. and SE.
10.011	Point for the C-E-SE 1/64 sec. cor. of sec. 3.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	S 3
	C-E-SE
	1/64
	2006
	Set a steel sign post alongside the stainless steel post.

SUBDIVISION OF SECTION 3,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.022	The SE 1/16 sec. cor. of sec. 3.
40.043	The C-S 1/16 sec. cor. of sec. 3.
	<hr/>
	From the C-E-SE 1/64 sec. cor. of sec. 3.
	N. 0°02'00" W., on the N-S center line of the NE1/4SE1/4 of sec. 3.
	Over rolling land covered with low brush, cheat and bunch grass.
1.30	Graded dirt road, 15 lks. wide, bears NW. and SE.
3.00	Descend into bottom land, through willows, scattered tamarisk, cattails and meadow grass.
19.930	The C-E-E 1/64 sec. cor. of sec. 3.
	<hr/>
	From the C-W 1/16 sec. cor. of sec. 3.
	N. 0°01'40" W., on the N-S center line of the NW1/4 of sec. 3.
	Over rolling land covered with low brush, cheat and bunch grass.
0.80	Graded dirt road, 15 lks. wide, bears NW. and SE.
20.027	Point for the NW 1/16 sec. cor. of sec. 3, at intersection with the E-W center line of the NW1/4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	NW 1/16 S 3
	2006
	From this cor., a weathered redwood post of unknown origin, 2 1/2x3x36 ins. long, no mks. visible, was found lying loose nearby, original position indeterminate, not utilized in the course of this survey.
	Deposit the redwood post and set a steel sign post alongside the stainless steel post.
20.50	Descend into bottom land, through willows, scattered tamarisk, cattails and meadow grass.
27.40	Right bank of the Walker River, bears SE. and SW.; thence across river, course SE.
29.20	Left bank of the Walker River, bears NW. and SE.; thence enter bottom land subject to flooding, through willows, scattered tamarisk, cattails and meadow grass.
39.976	The W 1/16 sec. cor. of secs. 3 and 34, on the N. bdy. of the Tp.
	<hr/>

SUBDIVISION OF SECTION 3,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the point for the C-N 1/16 sec. cor. of sec. 3.</p> <p>N. 89°53'30" W., on the E-W center line of the NW1/4 of sec. 3.</p> <p>Over bottom land subject to flooding, through willows, scattered tamarisk, cattails and grass.</p>
5.00	Enter rolling land covered with low brush, cheat and bunch grass.
10.013	<p>Point for the C-E-NW 1/64 sec. cor. of sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 3 C-E-NW 1/64 2006</p>
20.026	The NW 1/16 sec. cor. of sec. 3.
30.039	<p>Point for the C-W-NW 1/64 sec. cor. of sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 3 C-W-NW 1/64 2006</p> <p>From this cor., a weathered redwood post of unknown origin, 3x3x31 ins. long, no mks. visible, was found lying loose nearby, original position indeterminate, not utilized in the course of this survey.</p> <p>Deposit redwood post and set a steel sign post alongside the stainless steel post.</p>
34.50	Descend into bottom land, through willows, scattered tamarisk and meadow grass.
36.20	Right bank of the Walker River, bears NE. and SW.; thence across river, course NE.
36.70	Left bank of the Walker River, bears NE. and SW.; thence over bottom land, through willows and meadow grass.
39.10	Left bank of the Walker River, bears NW. and SE.; thence across river, course SE.
40.052	The true point for the N 1/16 sec. cor. of secs. 3 and 4.

SUBDIVISION OF SECTION 3,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the C-E-NW 1/64 sec. cor. of sec. 3.</p> <p>N. 0°02'00" W., on the N-S center line of the NE1/4NW1/4 of sec. 3.</p> <p>Over rolling land.</p>
0.50	Descend into bottom land subject to flooding, through willows, scattered tamarisk, cattails and meadow grass.
4.00	Enter rolling land through willows, scattered tamarisk, cattails and meadow grass.
19.963	The E-W 1/64 sec. cor. of secs. 3 and 34, on the N. bdy. of the Tp.
	<hr/> <p>From the C-W-NW 1/64 sec. cor. of sec. 3.</p> <p>N. 0°01'20" W., on the N-S center line of the NW1/4NW1/4 of sec. 3.</p> <p>Over rolling land covered with low brush, cheat and bunch grass.</p>
2.00	Descend into bottom land, through willows, scattered tamarisk, cattails and meadow grass.
2.80	Right bank of the Walker River, bears E. and W.; thence across river, course E.
3.80	Left bank of the Walker River, bears E. and W.; thence over bottom land, through willows, scattered tamarisk, cattails and meadow grass.
19.935	The W-W 1/64 sec. cor. of secs. 3 and 34, on the N. bdy. of the Tp.
	<hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 4, T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 4 and 9.</p> <p>N. 0°02'40" W., on the N-S center line of sec. 4.</p> <p>Over nearly level land covered with low brush, cheat and bunch grass.</p>
36.20	Dirt road, 10 lks. wide, bears NW. and SE.
39.705	<p>Point for the center 1/4 sec. cor. of sec. 4, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

SUBDIVISION OF SECTION 4,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T14N R27E C 1/4 S 4</p> <p style="text-align: center;">2006</p>
48.65	Dirt road, 10 lks. wide, bears E. and W.
54.50	Descend into bottom land, through willows, scattered tamarisk, cattails and meadow grass.
59.800	<p>Point for the C-N 1/16 sec. cor. of sec. 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;"> $\begin{array}{c} C \\ N\ 1/16 \quad \quad S\ 4 \\ C \end{array}$ </p> <p style="text-align: center;">2006</p> <p>Set a steel sign post alongside the stainless steel post.</p>
67.50	Right bank of the Walker River, bears WNW. and NE.; thence across river, course ENE.
68.40	Left bank of the Walker River, bears WSW. and ENE.; thence over bottom land, through willows, scattered tamarisk, cattails and meadow grass.
79.755	The 1/4 sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp.
	<hr/> <p>From the 1/4 sec. cor. of secs. 3 and 4.</p> <p>N. 89°54'20" W., on the E-W center line of sec. 4.</p> <p>Over nearly level land covered with low brush, cheat and bunch grass.</p>
19.931	<p>Point for the C-E 1/16 sec. cor. of sec. 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;"> $\begin{array}{c} E\ 1/16 \\ C \quad \text{---} \quad C \\ S\ 4 \end{array}$ </p> <p style="text-align: center;">2006</p>
39.862	The center 1/4 sec. cor. of sec. 4.
44.70	Graded dirt road, 10 lks. wide, bears NW. and SE.
59.876	Point for the C-W 1/16 sec. cor. of sec. 4.

SUBDIVISION OF SECTION 4,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} W \ 1/16 \\ C \text{-----} C \\ S \ 4 \end{array}$ <p>2006</p> </div>
79.890	<p>The 1/4 sec. cor. of secs. 4 and 5.</p> <hr/> <p>From the C-E 1/16 sec. cor. of sec. 4.</p> <p>N. 0°01'50" W., on the N-S center line of the NE1/4 of sec. 4.</p> <p>Over nearly level land covered with low brush, cheat and bunch grass.</p>
12.30	Graded dirt road, 15 lks. wide, bears WNW. and ESE.
13.00	Descend into bottom land, continue through willows, scattered tamarisk, cattails and meadow grass.
18.50	Right bank of the Walker River, bears NE. and SW.; thence across river, course NE.
19.20	Left bank of the Walker River, bears NE. and SW.; thence over bottom land, through willows, scattered tamarisk, cattails and meadow grass.
20.079	<p>Point for the NE 1/16 sec. cor. of sec. 4, at intersection with the E-W center line of the NE1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>NE 1/16 S 4</p> <p>2006</p> </div>
40.016	<p>Set a steel sign post alongside the stainless steel post.</p> <p>The E 1/16 sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp.</p> <hr/> <p>From the true point for the N 1/16 sec. cor. of secs. 3 and 4.</p> <p>N. 89°51'10" W., on the E-W center line of the NE1/4 of sec. 4.</p> <p>Across the Walker River, course ESE.</p>
0.50	Right bank of the Walker River, bears NW. and ESE.; enter bottom land, through willows, scattered tamarisk, cattails and meadow grass.
9.967	Point for the C-E-NE 1/64 sec. cor. of sec. 4.

SUBDIVISION OF SECTION 4,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 4 C-E-NE 1/64 2006</p> <p>Set a steel sign post alongside the stainless steel post.</p>
12.20	Right bank of the Walker River, bears NE. and SW.; thence across river, course NE.
15.70	Right bank of the Walker River, bears NW. and SE.; thence over bottom land, through willows, scattered tamarisk and meadow grass.
17.90	Right bank of the Walker River, bears SW. and NE.; thence across river, course NE.
18.60	Left bank of the Walker River, bears NE. and SW.; thence over bottom land, through willows, scattered tamarisk and meadow grass.
19.934	The NE 1/16 sec. cor. of sec. 4.
23.30	Left bank of the Walker River, bears NW. and SE.; thence across river, course SE.
24.20	Right bank of the Walker River, bears NW. and SE.; thence over bottom land, through willows, scattered tamarisk, cattails and meadow grass.
26.50	Enter gently rolling land covered with low brush, cheat and bunch grass.
28.50	Dirt road, 15 lks. wide, bears NNE. and SSW.
29.902	Point for the C-W-NE 1/64 sec. cor. of sec. 4.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 4 C-W-NE 1/64 2006</p> <p>Set a steel sign post alongside the stainless steel post.</p>
39.870	The C-N 1/16 sec. cor. of sec. 4.

SUBDIVISION OF SECTION 4,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the C-E-NE 1/64 sec. cor. of sec. 4.</p> <p>N. 0°01'20" W., on the N-S center line of the NE1/4NE1/4 of sec. 4.</p> <p>Over bottom land, through willows, scattered tamarisk, cattails and meadow grass.</p>
0.50	Right bank of the Walker River, bears E. and W.; thence across river, course E.
1.10	Left bank of the Walker River, bears NE. and W.; thence over bottom land, through willows, scattered tamarisk, cattails and meadow grass.
19.929	The E-E 1/64 sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp.
	<hr/> <p>From the C-W-NE 1/64 sec. cor. of sec. 4.</p> <p>N. 0°02'10" W., on the N-S center line of the NW1/4NE1/4 of sec. 4.</p> <p>Over gently rolling land, covered with low brush, cheat and bunch grass.</p>
0.70	Dirt road, 15 lks. wide, bears ENE and WSW.
1.00	Descend into bottom land, through willows, scattered tamarisk, cattails and meadow grass.
7.10	Right bank of the Walker River, bears NW. and SE.; thence across river, course SE.
7.70	Left bank of the Walker River, bears NW. and SE.; thence over bottom land, through willows, scattered tamarisk, cattails and meadow grass.
19.946	The true point for the W-E 1/64 sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp.
	<hr/> <p>From the C-W 1/16 sec. cor. of sec. 4.</p> <p>N. 0°02'30" E., on the N-S center line of the NW1/4 of sec. 4.</p> <p>Over gently rolling land covered with low brush, cheat and bunch grass.</p>
5.20	Dirt road, 10 lks. wide, bears NW. and SE.
20.137	<p>Point for the NW 1/16 sec. cor. of sec. 4, at intersection with the E-W center line of the NW 1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

SUBDIVISION OF SECTION 4,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	NW 1/16 S 4
	2006
	<p>From this cor., a weathered redwood post of unknown origin, 3x4x34 ins. long, no mks. visible, was found lying loose nearby, original position indeterminate, not utilized in the course of this survey.</p> <p>Deposit the redwood post and set a steel sign post alongside the stainless steel post.</p>
21.50	Descend into bottom land, through willows, scattered tamarisk, cattails and meadow grass.
30.90	Right bank of the Walker River, bears NNW. and SE.; thence across river, course SE.
31.40	Left bank of the Walker River, bears NW. and SE.; thence over bottom land, through willows, scattered tamarisk, cattails and meadow grass.
40.133	The W 1/16 sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp.
	<hr/> <p>From the C-N 1/16 sec. cor. of sec. 4.</p> <p>N. 89°47'20" W., on the E-W center line of the NW1/4 of sec. 4.</p> <p>Over bottom land, through willows, scattered tamarisk, cattails and meadow grass.</p>
6.00	Enter gently rolling land covered with low brush, cheat and bunch grass.
9.992	<p>Point for the C-E-NW 1/64 sec. cor. of sec. 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">S 4 C-E-NW 1/64</p>
	2006
	Set a steel sign post alongside the stainless steel post.
19.984	The NW 1/16 sec. cor. of sec. 4.
27.50	Descend into bottom land, through willows, scattered tamarisk, cattails and meadow grass.
29.976	<p>Point for the C-W-NW 1/64 sec. cor. of sec. 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

SUBDIVISION OF SECTION 4,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">S 4 C-W-NW 1/64 2006</p>
	Set a steel sign post alongside the stainless steel post.
32.00	Enter gently rolling land, covered with low brush, cheat and bunch grass.
39.968	The N 1/16 sec. cor. of secs. 4 and 5.
	<hr/> <p>From the C-E-NW 1/64 sec. cor. of sec. 4.</p> <p>NORTH, on the N-S center line of the NE1/4NW1/4 of sec. 4.</p> <p>Over gently rolling land covered with low brush, cheat and bunch grass.</p>
1.50	Descend into bottom land, through willows, scattered tamarisk, cattails and meadow grass.
5.10	Right bank of the Walker River, bears NE. and SW.; thence across river, course NE.
5.80	Left bank of the Walker River, bears NE. and SW.; thence over bottom land, through willows, scattered tamarisk, cattails and meadow grass.
19.975	The E-W 1/64 sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp.
	<hr/> <p>From the C-W-NW 1/64 sec. cor. of sec. 4.</p> <p>N. 0°05'00" E., on the N-S center line of the NW1/4NW1/4 of sec. 4.</p> <p>Over bottom land, through willows, scattered tamarisk, cattails and meadow grass.</p>
12.00	Right bank of the Walker River, bears ENE. and SW.; thence across river, course ENE.
12.60	Left bank of the Walker River, bears ENE. and SW.; thence over gently rolling land.
20.017	The W-W 1/64 sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp.
	<hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 11, T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 11 and 14.</p> <p>N. 0°02'00" W., on the N-S center line of sec. 11.</p>

SUBDIVISION OF SECTION 11,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Over rolling land covered with low brush, cheat and bunch grass.
19.980	<p>Point for the C-S 1/16 sec. cor. of sec. 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} C \\ S\ 1/16 \left S11 \\ C \end{array}$ <p>2006</p> </div>
39.960	<p>Point for the center 1/4 sec. cor. of sec. 11, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T14N R27E C 1/4 S11</p> <p>2006</p> </div> <p>Set a steel sign post alongside the stainless steel post.</p>
49.897	<p>Point for the C-S-N 1/64 sec. cor. of sec. 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} C \\ S-N\ 1/64 \left S11 \\ C \end{array}$ <p>2006</p> </div> <p>Set a steel sign post alongside the stainless steel post.</p>
59.834	<p>Point for the C-N 1/16 sec. cor. of sec. 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} C \\ N\ 1/16 \left S11 \\ C \end{array}$ <p>2006</p> </div> <p>Set a steel sign post alongside the stainless steel post.</p> <p>Descend in bottom land.</p>

SUBDIVISION OF SECTION 11,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
69.771	<p>Point for the C-N-N 1/64 sec. cor. of sec. 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} C \\ N-N \ 1/64 \mid S11 \\ C \end{array}$ </div> <p style="text-align: center;">2006</p> <p>Set a steel sign post alongside the stainless steel post.</p>
74.00	Tributary of the Walker River, 30 lks. wide, course SE.
78.80	S. bank of pond, bears NW. and SE.; thence across pond.
79.708	The true point for the 1/4 sec. cor. of secs. 2 and 11.
	<hr/> <p>From the 1/4 sec. cor. of secs. 11 and 12.</p> <p>N. 89°51'20" W., on the E-W center line of sec. 11.</p> <p>Over bottom land, through willows, scattered tamarisk, cattails and meadow grass.</p>
9.971	<p>Point for the C-E-E 1/64 sec. cor. of sec. 11.</p> <p>POINT NOT MONUMENTED</p>
16.60	Slough, 15 lks. wide, 2 ft. deep, bears NE. and SW.
19.942	True point for the C-E 1/16 sec. cor. of sec. 11, falls in slough, 15 lks. wide, 3 ft. deep, bears NE. and SW., where it is impractical to set a permanent monument.
20.272	<p>Point selected for the witness cor. to the C-E 1/16 sec. cor. of sec. 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} WC \\ E \ 1/16 \\ C \xrightarrow{\quad} C \\ S11 \end{array}$ </div> <p style="text-align: center;">2007</p>
22.00	Enter rolling land, covered with low brush, cheat and bunch grass.
25.75	Dirt road, 15 lks. wide, bears NW. and SE.

SUBDIVISION OF SECTION 11,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.884	The center 1/4 sec. cor. of sec. 11.
62.90	Graded dirt road, 15 lks. wide, bears NNW. and SSE.
79.750	<p>The 1/4 sec. cor. of secs. 10 and 11, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 14 N., R. 27 E., executed under Group No. 670, with the weathered remains of a redwood post, 3x4x16 ins. long, no mks. visible, lying loose alongside the stainless steel post.</p> <p>Deposit redwood post alongside the stainless steel post and below the surface of the ground.</p> <hr/> <p>From the true point for the C-E 1/16 sec. cor. of sec. 11.</p> <p>N. 0°03'10" W., on the N-S center line of the NE1/4 of sec. 11.</p> <p>Over bottom land subject to flooding, through willows, scattered tamarisk, cattails and meadow grass.</p>
7.70	Slough, 15 lks. wide, 2 ft. deep, bears NE. and SW.
9.941	<p>Point for the C-S-NE 1/64 sec. cor. of sec. 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S11 C-S-NE 1/64 2006</p> <p>Set a steel sign post alongside the stainless steel post.</p>
10.10	Slough, 15 lks. wide, 2 ft. deep, bears NE. and SW.
19.882	Point for the NE 1/16 sec. cor. of sec. 11, at intersection with the E-W center line of the NE1/4, falls in an area subject to flooding, where it is impractical to set a permanent monument.
24.60	Right bank of the Walker River, bears NE. and SW.; thence across river course NE.
25.50	Left bank of the Walker River, bears NE. and SW.; thence over bottom land, through willows, scattered tamarisk, cattails, and meadow grass.
29.823	<p>Point for the C-N-NE 1/64 sec. cor. of sec. 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

SUBDIVISION OF SECTION 11,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">S11 C-N-NE 1/64 2006</p>
39.764	<p>Set a steel sign post alongside the stainless steel post.</p> <p>The E 1/16 sec. cor. of secs. 2 and 11.</p> <hr/> <p>From the N 1/16 sec. cor. of secs. 11 and 12.</p> <p>N. 89°52'40" W., on the E-W center line of the NE1/4 of sec. 11.</p> <p>Over rolling land covered with low brush, cheat and bunch grass.</p>
5.00	<p>Descend into bottom land subject to flooding, through willows, scattered tamarisk, cattails and grass.</p>
6.90	<p>Left bank of the Walker River, bears NW. and SE.; thence across river, course SE.</p>
9.20	<p>Right bank of the Walker River, bears NW. and SE.; thence over bottom land subject to flooding, through willows, scattered tamarisk, cattails and meadow grass.</p>
19.935	<p>The point for the NE 1/16 sec. cor. of sec. 11.</p>
33.50	<p>Enter rolling land covered with low brush, cheat and bunch grass.</p>
39.870	<p>The C-N 1/16 sec. cor. of sec. 11.</p> <hr/> <p>From the N-N 1/16 sec. cor. of secs. 11 and 12.</p> <p>N. 89°53'30" W., on the E-W center line of the NE1/4NE1/4 of sec. 11.</p> <p>Over gently rolling land covered with low brush, cheat and bunch grass.</p>
0.20	<p>Dirt road, 15 lks. wide, bears N. and S.</p>
3.00	<p>Enter bottom land subject to flooding, through willows, scattered tamarisk, cattails and meadow grass.</p>
19.931	<p>The C-N-NE 1/64 sec. cor. of sec. 11.</p> <hr/> <p>From the S-N 1/64 sec. cor. of secs. 11 and 12.</p> <p>N. 89°51'50" W., on the E-W center line of the SE1/4NE1/4 of sec. 11.</p> <p>Over bottom land subject to flooding, through willows, scattered tamarisk, cattails and meadow grass.</p>

SUBDIVISION OF SECTION 11,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
1.90	Left bank of the Walker River, bears NW. and SE.; thence across river, course SE.
3.70	Right bank of the Walker River, bears NW. and SE.; thence over bottom land, through willows, scattered tamarisk, cattails and meadow grass.
19.938	The C-S-NE 1/64 sec. cor. of sec. 11.
	<hr/>
	N. 89°52'00" W., on the E-W center line of the SW1/4NE1/4 of sec. 11.
	Over bottom land, through willows, scattered tamarisk, cattails and meadow grass.
0.20	Slough, 15 lks. wide, 2 ft. deep, bears NE. and SW.
0.90	Slough, 15 lks. wide, 2 ft. deep, bears NW. and SE.
14.50	Enter rolling land, covered with low brush, cheat and bunch grass.
19.938	The C-S-N 1/64 sec. cor. of sec. 11.
	<hr/>
	From the C-N-NE 1/64 sec. cor. of sec. 11.
	N. 89°53'30" W., on the E-W center line of the NW1/4NE1/4 of sec. 11.
	Over bottom land, through willows, scattered tamarisk, and meadow grass.
5.50	Left bank of the Walker River, bears NNW. and SSE.; thence across river, course SE.
6.70	Right bank of the Walker River, bears NW. and SE.; thence over bottom land, through willows, scattered tamarisk, cattails and meadow grass.
19.20	Tributary of the Walker River, 30 lks. wide, course S.
19.931	The C-N-N 1/64 sec. cor. of sec. 11.
	<hr/>
	From the E 1/16 sec. cor. of secs. 11 and 14.
	N. 0°03'10" W., on the N-S center line of the SE1/4 of sec. 11.
	Over rolling land covered with low brush, cheat and bunch grass.
9.968	Point for the C-S-SE 1/64 sec. cor. of sec. 11.
	POINT NOT MONUMENTED
19.936	Point for the SE 1/16 sec. cor. of sec. 11, at intersection with the E-W center line of the SE1/4.

SUBDIVISION OF SECTION 11,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S11</p> <p style="text-align: center;">2006</p> <p>Set a steel post alongside the stainless steel post.</p>
26.40	Dirt road, 15 lks. wide, bears NW. and SE.
29.904	Point for the C-N-SE 1/64 sec. cor. of sec. 11.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S11 C-N-SE 1/64</p> <p style="text-align: center;">2006</p> <p>Set a steel sign post alongside the stainless steel post.</p>
36.50	Descend into bottom land, through willows, scattered tamarisk, cattails and meadow grass.
39.872	The true point for the C-E 1/16 sec. cor. of sec. 11.
	<hr/> <p>From the S 1/16 sec. cor. of secs. 11 and 12.</p> <p>N. 89°58'40" W., on the E-W center line of the SE1/4 of sec. 11.</p> <p>Over bottom land covered with meadow grass.</p>
2.00	Enter rolling land covered with low brush, cheat and bunch grass.
9.975	Point for the C-E-SE 1/64 sec. cor. of sec. 11.
	POINT NOT MONUMENTED
12.35	Dirt road, 15 lks. wide, bears NW. and SE.
19.950	The SE 1/16 sec. cor. of sec. 11.
39.900	The C-S 1/16 sec. cor. of sec. 11.
	<hr/> <p>From the point for the C-E-SE 1/64 sec. cor. of sec. 11.</p> <p>N. 0°03'50" W., on the N-S center line of the NE1/4SE1/4 of sec. 11.</p> <p>Over rolling land covered with low brush, cheat and bunch grass.</p>

SUBDIVISION OF SECTION 11,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
0.50	Enter bottom land, covered with meadow grass.
3.60	Enter bottom land subject to flooding, continue through willows, scattered tamarisk and cattails.
9.957	Point for the NE-SE 1/64 sec. cor. of sec. 11, at intersection with the E-W center line of the NE1/4SE1/4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. S11 NE-SE 1/64 2006 Set a steel sign post alongside the stainless steel post.
19.914	The point for the C-E-E 1/64 sec. cor. of sec. 11. <hr/> From the N-S 1/64 sec. cor. of secs. 11 and 12. N. 89°54'50" W., on the E-W center line of the NE1/4SE1/4 of sec. 11. Over bottom land, through willows, scattered tamarisk, cattails and meadow grass.
9.973	The NE-SE 1/64 sec. cor. of sec. 11.
16.50	Enter rolling land covered with low brush, cheat and bunch grass.
19.946	The C-N-SE 1/64 sec. cor. of sec. 11. <hr/> From the point for the E-E 1/64 sec. cor. of secs. 11 and 14. N. 0°03'50" W., on the N-S center line of the SE1/4SE1/4 of sec. 11. Over rolling land covered with low brush, cheat and bunch grass.
9.957	Point for the SE-SE 1/64 sec. cor. of sec. 11, at intersection with the E-W center line of the SE1/4SE1/4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. S11 SE-SE 1/64 2006 Set a steel sign post alongside the stainless steel post.

SUBDIVISION OF SECTION 11,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
18.80	Dirt road, 15 lks. wide, bears NW. and SE.
19.914	The point for the C-E-SE 1/64 sec. cor. of sec. 11.
	<hr/>
	From the S-S 1/64 sec. cor. of secs. 11 and 12.
	S. 89°57'30" W., on the E-W center line of the SE1/4SE1/4 of sec. 11.
	Over rolling land covered with low brush, cheat and bunch grass.
9.977	The SE-SE 1/64 sec. cor. of sec. 11.
19.954	The point for the C-S-SE 1/64 sec. cor. of sec. 11.
	<hr/>
	SUBDIVISION OF SECTION 12, T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA
	<hr/>
	From the 1/4 sec. cor. of secs. 12 and 13.
	N. 0°14'40" W., on the N-S center line of sec. 12.
	Over bottom land subject to flooding, through willows, scattered tamarisk, cattails and meadow grass.
17.00	Enter rolling land covered with low brush, cheat and bunch grass.
19.925	Point for the C-S 1/16 sec. cor. of sec. 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	$\begin{array}{c} C \\ S\ 1/16 \mid S12 \\ C \end{array}$
	2006
	Set a steel sign post alongside the stainless steel post.
21.50	Dirt road, 10 lks. wide, bears NW. and SE.
39.850	Point for the center 1/4 sec. cor. of sec. 12, at intersection with the E-W center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	$\begin{array}{c} T14N\ R27E \\ C\ 1/4\ S12 \end{array}$
	2006
	Set a steel sign post alongside the stainless steel post.

SUBDIVISION OF SECTION 12,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
59.759	Point for the C-N 1/16 sec. cor. of sec. 12. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;"> $\begin{array}{c} C \\ N\ 1/16 \mid S12 \\ C \end{array}$ <p>2006</p> </div> Set a steel sign post alongside the stainless steel post.
65.40	Graded dirt road, 30 lks. wide, bears NW. and SE.
79.668	The 1/4 sec. cor. of secs. 1 and 12.
	<hr/> From the 1/4 sec. cor. of secs. 7 and 12, of the E. bdy. of the Tp. N. 89°46'40" W., on the E-W center line of sec. 12. Over rolling land covered with low brush, cheat and bunch grass.
40.040	The center 1/4 sec. cor. of sec. 12.
50.20	Dirt road, 15 lks. wide, bears NW. and SE.
56.00	Enter bottom land subject to flooding, continue through willows, scattered tamarisk and cattails.
59.934	Point for the C-W 1/16 sec. cor. of sec. 12, falls in area subject to flooding, where it is impractical to set a permanent monument.
79.828	The 1/4 sec. cor. of secs. 11 and 12.
	<hr/> From the W 1/16 sec. cor. of secs. 12 and 13. N. 0°09'30" W., on the N-S center line of the SW1/4 of sec. 12. Over rolling land covered with low brush, cheat and bunch grass.
5.00	Enter bottom land, through willows, scattered tamarisk, cattails and meadow grass.
6.80	Right bank of the Walker River, bears NW. and SE.; thence across river, course SE.
8.00	Left bank of the Walker River, bears NW. and SE.; thence over bottom land subject to flooding, through willows, scattered tamarisk and cattails.
19.909	Point for the SW 1/16 sec. cor. of sec. 12, at intersection with the E-W center line of the SW1/4, falls in an area subject to flooding, where it is impractical to set a permanent monument.

SUBDIVISION OF SECTION 12,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
29.863	Point for the C-N-SW 1/64 sec. cor. of sec. 12, falls in an area subject to flooding, where it is impractical to set a permanent monument.
39.817	The point for the C-W 1/16 sec. cor. of sec. 12.
	<hr/> <p>From the C-S 1/16 sec. cor. of sec. 12.</p> <p>N. 89°44'00" W., on the E-W center line of the SW1/4 of sec. 12.</p> <p>Descend into bottom land, over low brush, cheat and bunch grass.</p>
3.00	Enter bottom land subject to flooding, through willows, scattered tamarisk, and cattails.
19.926	The point for the SW 1/16 sec. cor. of sec. 12.
39.851	The S 1/16 sec. cor. of secs. 11 and 12.
	<hr/> <p>From the point for the C-N-SW 1/64 sec. cor. of sec. 12.</p> <p>N. 89°45'30" W., on the E-W center line of the NW1/4SW1/4 of sec. 12.</p> <p>Over bottom land subject to flooding, through willows, scattered tamarisk and cattails.</p>
19.910	The N-S 1/64 sec. cor. of secs. 11 and 12.
	<hr/> <p>From the point for the C-W 1/16 sec. cor. of sec. 12.</p> <p>N. 0°09'30" W., on the N-S center line of the NW1/4 of sec. 12.</p> <p>Over bottom land subject to flooding, through willows, scattered tamarisk and cattails.</p>
9.50	Enter rolling land covered with low brush, cheat and bunch grass.
9.950	Point for the C-S-NW 1/64 sec. cor. of sec. 12.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">S12 C-S-NW 1/64</p>
	<p style="text-align: center;">2006</p>
	Set a steel sign post alongside the stainless steel post.
14.40	Dirt road, 15 lks. wide, bears NW. and SE.
19.900	Point for the NW 1/16 sec. cor. of sec. 12, at intersection with the E-W center line of the NW1/4.

SUBDIVISION OF SECTION 12,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S12</p> <p style="text-align: center;">2006</p> <p>Set a steel sign post alongside the stainless steel post.</p>
35.10	Graded dirt road, 30 lks. wide, bears NW. and SE.
39.800	The W 1/16 sec. cor. of secs. 1 and 12.
	<hr/> <p>From the C-N 1/16 sec. cor. of sec. 12.</p> <p>N. 89°48'20" W., on the E-W center line of the NW1/4 of sec. 12.</p> <p>Over rolling land covered with low brush, cheat and bunch grass.</p>
19.863	The NW 1/16 sec. cor. of sec. 12.
30.20	Dirt road, 15 lks. wide, bears NW. and SE.
37.75	Dirt road, 15 lks. wide, bears N. and S.
39.64	Barbed wire fence, steel and wood posts, bears N. and S.
39.726	The N 1/16 sec. cor. of secs. 11 and 12.
	<hr/> <p>From the C-S-NW 1/64 sec. cor. of sec. 12.</p> <p>N. 89°47'40" W., on the E-W center line of the SW1/4NW1/4 of sec. 12.</p> <p>Descend into bottom land, over low brush, cheat and bunch grass.</p>
1.00	Enter land subject to flooding, through willows, scattered tamarisk and cattails.
19.879	The S-N 1/64 sec. cor. of secs. 11 and 12.
	<hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 13, T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 13 and 24.</p> <p>N. 0°05'30" E., on the N-S center line of sec. 13.</p> <p>Over rolling land covered with low brush, cheat and bunch grass.</p>
20.009	<p>Point for the C-S 1/16 sec. cor. of sec. 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

SUBDIVISION OF SECTION 13,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	$\begin{array}{c} C \\ S\ 1/16 \left S13 \\ C \end{array}$ <p style="text-align: center;">2006</p>
40.018	<p>Set a steel sign post alongside the stainless steel post.</p> <p>Point for the center 1/4 sec. cor. of sec. 13, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	$\begin{array}{c} T14N\ R27E \\ C\ 1/4\ S13 \end{array}$ <p style="text-align: center;">2006</p>
50.025	<p>Set a steel sign post alongside the stainless steel post.</p> <p>Point for the C-S-N 1/64 sec. cor. of sec. 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	$\begin{array}{c} C \\ S-N\ 1/64 \left S13 \\ C \end{array}$ <p style="text-align: center;">2006</p>
52.50	<p>Set a steel sign post alongside the stainless steel post.</p> <p>Enter bottom land, through willows, scattered tamarisk, cattails and meadow grass.</p>
60.032	<p>Point for the C-N 1/16 sec. cor. of sec. 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	$\begin{array}{c} C \\ N\ 1/16 \left S13 \\ C \end{array}$ <p style="text-align: center;">2006</p>
61.20	<p>Set a steel sign post alongside the stainless steel post.</p> <p>Right bank of the Walker River, bears NW. and SE.; thence over river course SE.</p>
62.80	<p>Left bank of the Walker River, bears NW. and SE.; thence over bottom land, through willows, scattered tamarisk, cattails and meadow grass.</p>

SUBDIVISION OF SECTION 13,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
70.039	Point for the C-N-N 1/64 sec. cor. of sec. 13. POINT NOT MONUMENTED
80.046	The 1/4 sec. cor. of secs. 12 and 13. <hr/>
	From the 1/4 sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp. N. 89°46'20" W., on the E-W center line of sec. 13. Over bottom land, through willows, scattered tamarisk, cattails and meadow grass.
19.989	Point for the C-E 1/16 sec. cor. of sec. 13. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;">$\begin{array}{c} \text{E } 1/16 \\ \text{C} \text{-----} \text{C} \\ \text{S13} \end{array}$ 2006</div> Set a steel sign post alongside the stainless steel post.
23.30	Left bank of the Walker River, bears NW. and SE.; thence across river, course SE.
24.00	Right bank of the Walker River, bears NW. and SE.; thence over bottom land, though willows, scattered tamarisk, cattails and meadow grass.
33.50	Enter rolling land covered with low brush, cheat and bunch grass.
39.978	The center 1/4 sec. cor. of sec. 13.
49.973	Point for the C-E-W 1/64 sec. cor. of sec. 13. POINT NOT MONUMENTED
59.968	Point for the C-W 1/16 sec. cor. of sec. 13. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;">$\begin{array}{c} \text{W } 1/16 \\ \text{C} \text{-----} \text{C} \\ \text{S13} \end{array}$ 2006</div> Set a steel sign post alongside the stainless steel post.
79.958	The 1/4 sec. cor. of secs. 13 and 14. <hr/>

SUBDIVISION OF SECTION 13,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the C-E 1/16 sec. cor. of sec. 13.</p> <p>N. 0°02'50" E., on the N-S center line of the NE1/4 of sec. 13.</p> <p>Over bottom land, through willows, scattered tamarisk, cattails and meadow grass.</p>
19.999	<p>Point for the NE 1/16 sec. cor. of sec. 13, at intersection with the E-W center line of the NE1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S13</p> <p style="text-align: center;">2006</p> <p>Set a steel sign post alongside the stainless steel post.</p>
34.00	Enter rolling land covered with low brush, cheat and bunch grass.
39.998	The E 1/16 sec. cor. of secs. 12 and 13.
	<hr/> <p>From the N 1/16 sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp.</p> <p>N. 89°43'40" W., on the E-W center line of the NE1/4 of sec. 13.</p> <p>Over rolling land covered with low brush, cheat and bunch grass.</p>
5.00	Enter bottom land, through willows, scattered tamarisk, cattails and meadow grass.
13.00	Enter rolling land covered with low brush, cheat and bunch grass.
16.50	Descend into bottom land, through willows, scattered tamarisk, cattails and meadow grass.
19.973	The NE 1/16 sec. cor. of sec. 13.
26.40	Left bank of the Walker River, bears NW. and SE.; thence across river, course SE.
26.70	Right bank of the Walker River, bears NW. and SE.; thence over bottom land, through willows, scattered tamarisk, cattails and meadow grass.
36.30	Left bank of the Walker River, bears NE. and SW.; thence across river, course SE.
37.70	Right bank of the Walker River, bears NW. and SE.; thence over bottom land, through willows, scattered tamarisk, cattails and meadow grass.
39.946	The C-N 1/16 sec. cor. of sec. 13.

SUBDIVISION OF SECTION 13,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the E 1/16 sec. cor. of secs. 13 and 24.</p> <p>N. 0°02'50" E., on the N-S center line of the SE1/4 of sec. 13.</p> <p>Over rolling land covered with low brush, cheat and bunch grass.</p>
19.997	<p>Point for the SE 1/16 sec. cor. of sec. 13, at intersection with the E-W center line of the SE1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S13</p> <p style="text-align: center;">2006</p> <p>Set a steel sign post alongside the stainless steel post.</p>
29.995	<p>Point for the C-N-SE 1/64 sec. cor. of sec. 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S13 C-N-SE 1/64</p> <p style="text-align: center;">2006</p> <p>From this cor., a weathered redwood post of unknown origin, 3x3x31 ins. long, no mks. visible, was found lying loose nearby, original position indeterminate, not utilized in the course of this survey.</p> <p>Deposit the redwood post and set a steel sign post alongside the stainless steel post.</p>
30.00	Enter bottom land, through willows, scattered tamarisk, cattails and meadow grass.
39.00	Right bank of the Walker River, bears NW. and SE.; thence across river, course SE.
39.20	Left bank of the Walker River, bears NW. and SE.; thence over bottom land, through willows, scattered tamarisk, cattails and meadow grass.
39.993	The C-E 1/16 sec. cor. of sec. 13.
	<hr/> <p>From the S 1/16 sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp.</p> <p>N. 89°48'10" W., on the E-W center line of the SE1/4 of sec. 13.</p> <p>Over rolling land covered with low brush, cheat and bunch grass.</p>
3.10	Dirt road, 15 lks. wide, bears NE. and SW.

SUBDIVISION OF SECTION 13,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
11.20	Dirt road, 15 lks. wide, bears NW. and SE.
20.006	The SE 1/16 sec. cor. of sec. 13.
40.012	The C-S 1/16 sec. cor. of sec. 13.
	<hr/>
	From the true point for the N-S 1/64 sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp.
	N. 89°47'00" W., on the E-W center line of the NE1/4SE1/4 of sec. 13.
	Across the Walker River, course SE.
0.30	Right bank of the Walker River, bears NW. and SE.; thence over bottom land, through willows, scattered tamarisk and meadow grass.
19.50	Leave bottom land; enter rolling land covered with low brush, cheat and bunch grass.
19.998	The C-N-SE 1/64 sec. cor. of sec. 13.
	<hr/>
	From the C-W 1/16 sec. cor. of sec. 13.
	N. 0°08'10" E., on the N-S center line of the NW1/4 of sec. 13.
	Over rolling land covered with low brush, cheat and bunch grass.
10.015	Point for the C-S-NW 1/64 sec. cor. of sec. 13.
	POINT NOT MONUMENTED
20.030	Point for the NW 1/16 sec. cor. of sec. 13, at intersection with the E-W center line of the NW1/4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	NW 1/16 S13
	2006
	Set a steel sign post alongside the stainless steel post.
30.044	Point for the C-N-NW 1/64 sec. cor. of sec. 13.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	S13 C-N-NW 1/64
	2006

SUBDIVISION OF SECTION 13,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From this point, a weathered redwood post of unknown origin, 2x3x27 ins. long, no mks. visible, was found lying loose nearby, the original position indeterminable, not utilized during the course of this survey.</p> <p>Deposit the redwood post and set a steel sign post alongside the stainless steel post.</p>
40.058	<p>The W 1/16 sec. cor. of secs. 12 and 13.</p> <hr/> <p>From the C-N 1/16 sec. cor. of sec. 13.</p> <p>N. 89°43'50" W., on the E-W center line of the NW1/4 of sec. 13.</p> <p>Over bottom land, through willows, scattered tamarisk, cattails and meadow grass.</p>
9.00	<p>Leave bottom land, enter rolling land covered with low brush, cheat and bunch grass.</p>
9.987	<p>Point for the C-E-NW 1/64 sec. cor. of sec. 13.</p> <p>POINT NOT MONUMENTED</p>
19.974	<p>The NW 1/16 sec. cor. of sec. 13.</p>
39.947	<p>The N 1/16 sec. cor. of secs. 13 and 14.</p> <hr/> <p>From the point for the C-E-NW 1/64 sec. cor. of sec. 13.</p> <p>N. 0°06'50" E., on the N-S center line of the NE1/4NW1/4 of sec. 13.</p> <p>Over rolling land covered with low brush, cheat and bunch grass.</p>
6.50	<p>Enter bottom land, through willows, scattered tamarisk, cattails and meadow grass.</p>
10.011	<p>Point for the NE-NW 1/64 sec. cor. of sec. 13, at intersection with the E-W center line of the NE1/4NW1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S13 NE-NW 1/64 2006</p>
17.40	<p>Set a steel sign post alongside the stainless steel post.</p> <p>Right bank of the Walker River, bears NW. and SE.; thence across river, course SE.</p>

SUBDIVISION OF SECTION 13,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
17.90	Left bank of the Walker River, bears NW. and SE.; thence over bottom land, through willows, scattered tamarisk, cattails and meadow grass.
20.022	The point for the E-W 1/64 sec. cor. of secs. 12 and 13.
	From the point for the C-N-N 1/64 sec. cor. of sec. 13.
	N. 89°42'20" W., on the E-W center line of the NE1/4NW1/4 of sec. 13.
	Over bottom land, through willows, scattered tamarisk, cattails and grass.
7.50	Left bank of the Walker River, bears NW. and SE.; thence across river, course SE.
7.80	Right bank of the Walker River, bears NW. and SE.; thence over bottom land, through willows, scattered tamarisk, cattails and meadow grass.
9.983	The NE-NW 1/64 sec. cor. of sec. 13.
13.00	Enter rolling land covered with low brush, cheat and bunch grass.
19.966	The C-N-NW 1/64 sec. cor. of sec. 13.
	From the point for the C-E-W 1/64 sec. cor. of sec. 13.
	N. 0°06'50" E., on the N-S center line of the SE1/4NW1/4 of sec. 13.
	Over rolling land covered with low brush, cheat and bunch grass.
10.011	Point for the SE-NW 1/64 sec. cor. of sec. 13, at intersection with the E-W center line of the SE1/4NW1/4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	S13 SE-NW 1/64 2006
	From this cor., a weathered redwood post of unknown origin, 3x3x32 ins. long, no mks. visible, was found lying loose nearby, original position indeterminate, not utilized in the course of this survey.
	Deposit the redwood post and set a steel sign post alongside the stainless steel post.
20.022	The point for the C-E-NW 1/64 sec. cor. of sec. 13.

SUBDIVISION OF SECTION 13,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the C-S-N 1/64 sec. cor. of sec. 13.</p> <p>N. 89°45'00" W., on the E-W center line of the SE1/4NW1/4 of sec. 13.</p> <p>Over rolling land covered with low brush, cheat and bunch grass.</p>				
9.991	The SE-NW 1/64 sec. cor. of sec. 13.				
19.982	The point for the C-S-NW 1/64 sec. cor. of sec. 13.				
<hr/> <p style="text-align: center;">FURTHER SUBDIVISION OF SECTION 5, T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>					
	<p>From the C-E 1/16 sec. cor. of sec. 5, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. as described in the field notes of the subdivision of section 5, T. 14 N., R. 27 E., executed under Group No. 670.</p> <p>N. 0°08'00" E., on the N-S center line of the NE1/4 of sec. 5.</p> <p>Over rolling land covered with low brush, cheat and bunch grass</p>				
20.007	<p>Point for the NE 1/16 sec. cor. of sec. 5, at intersection with the E-W center line of the NE1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S 5</p> <p style="text-align: center;">2006</p>				
	<p>Set a steel sign post alongside the stainless steel post.</p>				
27.00	<p>Descend into bottom land, through willows, scattered tamarisk, cattails and meadow grass.</p>				
29.945	<p>Point for Angle Point No. 2 of the metes-and-bounds survey in sec. 5, determined latitudinally at midpoint in distance bet. the NE 1/16 sec. cor. of sec. 5 and the E 1/16 sec. cor. of secs. 5 and 32, on the N. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T14N R27E</p> <table style="margin: auto;"><tr><td>E</td></tr><tr><td>AP 2</td></tr><tr><td>S 5</td></tr><tr><td>E</td></tr></table> <p style="text-align: center;">2006</p>	E	AP 2	S 5	E
E					
AP 2					
S 5					
E					
	<p>Set a steel sign post alongside the stainless steel post.</p>				

FURTHER SUBDIVISION OF SECTION 5,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.883	The E 1/16 sec. cor. of secs. 5 and 32, on the N. bdy. of the Tp.
	<hr/> <p>From the N 1/16 sec. cor. of secs. 4 and 5.</p> <p>S. 89°39'40" W., on the E-W center line of the NE1/4 of sec. 5.</p> <p>Over rolling land covered with low brush, cheat and bunch grass.</p>
9.986	<p>Point for the C-E-NE 1/64 sec. cor. of sec. 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">S 5 C-E-NE 1/64 2006</p>
	Set a steel sign post alongside the stainless steel post.
19.972	The NE 1/16 sec. cor. of sec. 5.
29.958	<p>Point for the C-W-NE 1/64 sec. cor. of sec. 5.</p> <p>POINT NOT MONUMENTED</p>
39.944	The C-N 1/16 sec. cor. of sec. 5.
	<hr/> <p>From the C-E-NE 1/64 sec. cor. of sec. 5.</p> <p>N. 0°07'50" E., on the N-S center line of the NE1/4NE1/4 of sec. 5.</p> <p>Over rolling land covered with low brush, cheat and bunch grass.</p>
3.00	Descend into bottom land, through willows, scattered tamarisk, cattails and meadow grass.
9.978	The point for Angle Point No. 1, of a metes-and-bounds survey in sec. 5, hereinafter described.
19.956	The E-E 1/64 sec. cor. of secs. 5 and 32, on the N. bdy. of the Tp.
	<hr/> <p>From the point for the C-W-NE 1/64 sec. cor. of sec. 5.</p> <p>N. 0°08'10" E., on the N-S center line of the NW1/4NE1/4 of sec. 5.</p> <p>Over rolling land covered with low brush, cheat and bunch grass.</p>

FURTHER SUBDIVISION OF SECTION 5,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
7.00	Descend into bottom land, through willows, scattered tamarisk, cattails and meadow grass.
9.898	The point for Angle Point No. 3, of a metes-and-bounds survey in sec. 5, hereinafter described.
19.796	The W-E 1/64 sec. cor. of secs. 5 and 32, on the N. bdy. of the Tp.
<hr/>	
METES-AND-BOUNDS SURVEY IN SECTION 5, T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA	
<hr/>	
From the control point on the line bet. secs. 4 and 5, hereinbefore described.	
Thence S. 89°25'50" W., on a blank line through the NE1/4NE1/4 of sec. 5.	
9.985	Point for Angle Point No. 1, sec. 5, at intersection with the N-S center line of the NE1/4NE1/4.
Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.	
<div style="text-align: center;">T14N R27E EE AP 1 ----- S 5 EE 2006</div>	
Set a steel sign post alongside the stainless steel post.	
Continue on a metes-and-bounds line through the NE1/4NE1/4 of sec. 5, and on a portion of the southerly boundary of Indian Trust Patent No. 459.	
19.970	Angle Point No. 2, sec. 5, hereinbefore described.
<hr/>	
Thence S. 89°25'40" W., through the NW1/4NE1/4 of sec. 5 and on a portion of the southerly boundary of Indian Trust Patent No. 459.	
9.985	Point for Angle Point No. 3, sec. 5, at intersection with the N-S center line of the NW1/4NE1/4.
Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.	

METES-AND-BOUNDS SURVEY IN SECTION 5,
T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div>T14N R27E</div> <div>WE</div> <div>AP 3</div> <div>S 5</div> <div>WE</div> <div>2006</div> <div>Set a steel sign post alongside the stainless steel post.</div> <div>Continue on a blank line through the NW1/4NE1/4 of sec. 5.</div> <div>19.971 The control point on the N-S center line of sec. 5, hereinbefore described.</div> <div>GENERAL DESCRIPTION</div> <div>The land encompassed in this survey lies generally within the Campbell Valley, approximately 8 miles northwest of Schurz, Nevada, and extends south to the northern most foothills of the Wassuck Range. The northern portion of the township is traversed by the Walker River which fills Weber Reservoir.</div>
--------	--

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Don R. Aschenbach	Cadastral Surveyor
Lance A. Barney	Cadastral Surveyor
Nathan P. Trapp	Surveying Technician
Devonte L. Whitmore	Surveying Technician
Michelle E. Martin	Supervisory Range Technician
Derrick J. Rader	Supervisory Range Technician
Larry R. McVey	Volunteer

CERTIFICATE OF SURVEY

We, Douglas A. Potts, Cadastral Surveyor, and Mark G. Petrosine, Surveying Technician, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 9th day of June, 2006, we have dependently resurveyed portions of the south, east and north boundaries, a portion of the subdivisional lines and a portion of the subdivision-of-section lines of section 5, subdivided sections 2, 3, 4, 11, 12 and 13, further subdivided section 5, and surveyed by metes and bounds in section 5, Township 14 North, Range 27 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Land of the United States, and in specific manner described in the foregoing field notes.

September 3, 2008

(Date)

Douglas A. Potts For Douglas A. Potts
(Cadastral Surveyor)

August 29, 2008

(Date)

Mark G. Petrosine
(Surveying Technician)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of the dependent resurvey of portions of the south, east and north boundaries, a portion of the subdivisional lines and a portion of the subdivision-of-section lines of section 5, the subdivision of sections 2, 3, 4, 11, 12 and 13, the further subdivision of section 5, and a metes-and-bounds survey in section 5, Township 14 North, Range 27 East, Mount Diablo Meridian, Nevada, executed by Douglas A. Potts, Cadastral Surveyor and Mark G. Petrosine, Surveying Technician, having been critically examined and found correct, are hereby approved.

September 3, 2008

(Date)

Douglas A. Potts
(Chief Cadastral Surveyor, Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above described surveys in T. 14 N., R. 27 E., Mount Diablo Meridian, Nevada, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor, Nevada)~~