

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF

PORTIONS OF THE SOUTH AND EAST BOUNDARIES,

TOWNSHIP 13 SOUTH, RANGE 47 EAST

AND

THE SURVEY OF THE

SUBDIVISIONAL LINES,

TOWNSHIP 14 SOUTH, RANGE 47 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATE OF NEVADA

EXECUTED BY

Lee T. Wilson, Cadastral Surveyor

Under Special Instructions dated January 4, 2022,

and approved January 4, 2022,

which provided for the surveys included under Group No. 999,

and Assignment Instructions dated January 5, 2022.

Survey commenced January 19, 2022

Survey completed December 4, 2023

INDEX DIAGRAM

TOWNSHIP 14 SOUTH, RANGE 47 EAST, MOUNT DIABLO MERIDIAN, NEVADA

33	34	35	36	6	3	22	2	15	1		
5	4	4	2								
					21	21		15			
	7	39	8	32	9	27	10	20	11	14	12
	38	38		31		26		19		13	
	18	37	17	31	16	26	15	19	14	13	13
	37	37		30		25		18		12	
	19	36	20	30	21	25	22	18	23	11	24
	35	35		29		24		17		11	
	30	34	29	29	28	24	27	17	26	10	25
	34	34		28		23		16		10	
	31	33	32	28	33	23	34	16	35	7	36

## TOWNSHIP 14 SOUTH, RANGE 47 EAST, MOUNT DIABLO MERIDIAN, NEVADA

The following field notes are those of the dependent resurvey of portions of the south and east boundaries, Township 13 South, Range 47 East, and the survey of the subdivisional lines, Township 14 South, Range 47 East, Mount Diablo Meridian, Nevada.

1906 - The west boundary of Township 13 South, Range 48 East, and the south, west, and north boundaries of Township 14 South, Range 47 East, and the west and north boundaries of Township 14 South, Range 48 East, were surveyed by M.D. Heist, U.S. Deputy Surveyor, under contract No. 252. The surveys of the south and west boundaries and a portion of the north boundary of Township 14 South, Range 47 East, and the west and north boundaries of Township 14 South, Range 48 East, were superseded by the 1957 independent resurvey by H.G. Parker, Cadastral Surveyor, under Group No. 368.

1921 - The south and east boundaries of Township 13 South, Range 47 East, were independently resurveyed by E. Voigt, U.S. Cadastral Engineer and W.H. Good, U.S. Transitman, under Group No. 90.

1957 - The south and east boundaries of Township 13 South, Range 47 East, were dependently resurveyed and the south, west, and east boundaries and a portion of the north boundary of Township 14 South, Range 47 East, were independently resurveyed by H.G. Parker, Cadastral Surveyor, under Group No. 368.

1962 - Nevada Protraction Diagram Number 43, Unit Number 105, was approved May 31, 1962.

Numerous original corner monuments, set during the 1906 survey of the boundaries of Townships 13 and 14 South, Ranges 47 and 48 East, were recovered during the course of this survey. Bearing and distance ties are given from the corner of sections 1, 2, 35, and 36, on the south boundary of the Township, to those corners physically located within the boundaries of Township 14 South, Range 47 East.

In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 2009, and the Special Instructions for Group No. 999, dated January 4, 2022.

Meridional subdivisional lines were run parallel to the east boundary of the township, determined by mathematical inverse between the corner of Townships 14 and 15 South, Ranges 47 and 48 East, and the corner of Township 13 South, Ranges 47 1/2 and 48 East, and Township 14 South, Ranges 47 and 48 East, excluding the north tier of sections which were connected to the objective section corners on the north boundary of the Townships, when appropriate.

Measurements were made with Trimble R-8 and R-10 Global Navigation Satellite System (GNSS) receivers using the real-time kinematic (RTK) method and refer to the true meridian based on geodetic methods. The mean bearings of the lines and horizontal equivalents of ground distances only are entered in the field notes.

TOWNSHIP 14 SOUTH, RANGE 47 EAST, MOUNT DIABLO MERIDIAN, NEVADA

The NAD 83(2011)(EPOCH:2010.0000) geographic position of the following corners was determined from the Cadastral Project Control Network, tied to the National Spatial Reference System (NSRS) using Global Positioning System (GPS) static observations processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) DN7518 P094 LASTCHANCECS2006 CORS ARP, DN5639 P093 HAYSTACKHICS2007 CORS ARP, and DK6411 P467 ALABAMAHILCS2006 CORS ARP, and carried forward by RTK observations.

The corner of sections 25, 30, 31, and 36, on the East boundary of the Township, is as follows:

Latitude: 36°41'57.434" N. Longitude: 116°36'52.915" W.

The 1/4 section corner of section 33, on the South boundary of Township 13 South, Range 47 East, is as follows:

Latitude: 36°45'17.899" N. Longitude: 116°43'38.105" W.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 13 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor M.D. Heist in 1906, the Independent Resurvey Executed by U.S. Cadastral Engineer E. Voigt and U.S. Transitman W.H. Good in 1921, and a Portion of the Dependent Resurvey Executed by Cadastral Surveyor H.G. Parker in 1957

Beginning at the SE. cor. of Sec. 36 only, T. 13 S., R. 47 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 7 ins. above the ground, with a mound of stone, 3 ft. diam., 1 1/2 ft. high, W. of the cor., with a quartzite stone, 14x10x8 ins. (1906 Record, 15X10X7), mkd. 14S on a face, 47E on a face, 13S on a face, and 48E on a face, at the center of the mound, with brass cap mkd.

T13S  
R47E  
S36 | S 3  
S10  
R47E  
T14S  
1957

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 13 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	Remark brass cap to read
	T13S R47E S36
	S10 R47E T14S
	2023 1957
	S. 89°58'10" W., on the S. bdy. of sec. 36.
20.442	Point for the cor. of secs. 9 and 10, T. 14 S., R. 47 E., hereinafter described.
23.5	Overhead power line, bears SE. and NW.
28.5	Desert two track road, 15 lks. wide, bears SE. and NW.
40.020	The 1/4 sec. cor. of sec. 36 only, monumented with an iron post, 1 in. diam., firmly set, projecting 13 ins. above the ground, in a mound of stone, 2 ft. diam., 1/2 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of the S. bdy., T. 13 S., R. 47 E., executed under Group No. 368.
	From this corner, a rebar, 5/8 in. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. NEV HWY PIT NO 318 SW COR, bears S. 13°44'10" E., 2.2 lks. dist.
	-----
	S. 89°58'20" W., beginning new measurement.
20.427	Point for the 1/4 sec. cor. of sec. 9 only, T. 14 S., R. 47 E., hereinafter described.
40.003	The cor. of secs. 35 and 36 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.
	T13S R47E S35   S36
	S 9 T14S R47E
	1957
	From this corner, an iron pipe, 1 in. diam., firmly set, projecting 9 ins. above the ground, no record found, bears S. 12°33'50" E., 1.4 lks. dist.
	-----

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 13 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS													
	S. 89°58'10" W., on the S. bdy. of sec. 35.												
20.429	The cor. of secs. 8 and 9 only, T. 14 S., R. 47 E., hereinafter described.												
40.000	The 1/4 sec. cor. of sec. 35 only, monumented with an iron post, 1 in. diam., firmly set, projecting 11 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the S. bdy., T. 13 S., R. 47 E., executed under Group No. 368, with a mound of stone, 2 1/2 ft. diam., 1 ft. high, N. of the cor.  From this corner, an iron pipe, 1 in. diam., firmly set, projecting 7 ins. above the ground, no record found, bears S. 0°36'20" E., 1.0 lk. dist.												
	S. 89°57'20" W., beginning new measurement.												
20.431	The 1/4 sec. cor. of sec. 8 only, T. 14 S., R. 47 E., hereinafter described.												
24.0	Desert two track road, 15 lks. wide, bears SSE. and NNW.												
30.0	Deconstructed Tonopah and Tidewater Railroad grade, bears SSE. and NNW.												
39.994	The cor. of secs. 34 and 35 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 9 ins. above the ground, with brass cap mkd.												
	<table border="1"> <tr> <td>T13S</td> <td>R47E</td> </tr> <tr> <td>S34</td> <td>S35</td> </tr> <tr> <td colspan="2" style="text-align: center;">S 8</td> </tr> <tr> <td colspan="2" style="text-align: center;">R47E</td> </tr> <tr> <td colspan="2" style="text-align: center;">T14S</td> </tr> <tr> <td colspan="2" style="text-align: center;">1957</td> </tr> </table>	T13S	R47E	S34	S35	S 8		R47E		T14S		1957	
T13S	R47E												
S34	S35												
S 8													
R47E													
T14S													
1957													
	From this corner, an iron pipe, 1 in. diam., firmly set, projecting 9 ins. above the ground, no record found, bears S. 2°58'00" E., 1.7 lks. dist.												
	S. 89°59'00" W., on the S. bdy. of sec. 34.												
20.439	The cor. of secs. 7 and 8 only, T. 14 S., R. 47 E., hereinafter described.												
39.980	The 1/4 sec. cor. of sec. 34 only, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the S. bdy., T. 13 S., R. 47 E., executed under Group No. 368.												

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 13 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS																	
	<p>From this corner, an iron pipe, 1 in. diam., firmly set, projecting 12 ins. above the ground, no record found, bears S. 0°07'20" W., 1.2 lks. dist.</p>																
	<p>S. 89°58'10" W., beginning new measurement.</p>																
20.459	<p>The 1/4 sec. cor. of sec. 7 only, T. 14 S., R. 47 E., hereinafter described.</p>																
39.983	<p>The cor. of secs. 33 and 34 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 11 ins. above the ground, with a mound of stone, 2 ft. diam., 1/2 ft. high, W. of the cor., with brass cap mkd.</p>																
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T13S R47E</td> </tr> <tr> <td style="text-align: center;">S33</td> <td style="text-align: center;">S34</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td colspan="2" style="text-align: center;">S 7</td> </tr> <tr> <td colspan="2" style="text-align: center;">T14S</td> </tr> <tr> <td colspan="2" style="text-align: center;">R47E</td> </tr> <tr> <td colspan="2" style="text-align: center;">1957</td> </tr> </table>	T13S R47E		S33	S34	-----		S 7		T14S		R47E		1957			
T13S R47E																	
S33	S34																
-----																	
S 7																	
T14S																	
R47E																	
1957																	
	<p>S. 89°56'20" W., on the S. bdy. of sec. 33.</p>																
6	<p>Amargosa River, dry, 25 chs. wide, drains SE.; across braided, abandoned channels of the Amargosa River.</p>																
20.436	<p>The closing cor. of secs. 7 and 12, T. 14 S., Rs. 46 and 47 E., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, with a mound of stone, 3 ft. diam., 1 1/2 ft. high, S. of the cor., with brass cap mkd.</p>																
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T13S R47E</td> </tr> <tr> <td colspan="2" style="text-align: center;">S33</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">S12</td> <td style="text-align: center;">S 7</td> </tr> <tr> <td style="text-align: center;">R46E</td> <td style="text-align: center;">R47E</td> </tr> <tr> <td colspan="2" style="text-align: center;">CC</td> </tr> <tr> <td colspan="2" style="text-align: center;">T14S</td> </tr> <tr> <td colspan="2" style="text-align: center;">1957</td> </tr> </table>	T13S R47E		S33		-----		S12	S 7	R46E	R47E	CC		T14S		1957	
T13S R47E																	
S33																	
-----																	
S12	S 7																
R46E	R47E																
CC																	
T14S																	
1957																	
	<p>From this corner, an iron pipe, 1 in. diam., firmly set, projecting 11 ins. above the ground, no record found, bears N. 81°37'40" W., 2.5 lks. dist.</p>																
39.999	<p>The 1/4 sec. cor. of sec. 33 only, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above a mound of stone, 3 ft. diam., 1 1/2 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of the S. bdy., T. 13 S., R. 47 E., executed under Group No. 368.</p>																

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,  
T. 13 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS									
	<p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor M.D. Heist in 1906, the Independent Resurvey Executed by U.S. Cadastral Engineer E. Voigt and U.S. Transitman W.H. Good in 1921, and a Portion of the Dependent Resurvey Executed by Cadastral Surveyor H.G. Parker in 1957</p> <hr/>								
	<p>From the SE. cor. of sec. 36 only, T. 13 S., R. 47 E., hereinbefore described.</p>								
	<p>N. 0°00'30" W., on the E. bdy. of sec. 36.</p>								
2.0	Right-of-way fence, bears SE. and NW.								
4.5	Overhead power line, bears SE. and NW.								
8.8	Centerline of U.S. Hwy. No. 95, asphalt surfaced, 55 lks. wide, bears SE. and NW.								
12.596	Point for the cor. of secs. 3 and 10 only, T. 14 S., R. 47 E., hereinafter described.								
13.0	Right-of-way fence, bears SE. and NW.								
33.0	Desert two track road, 15 lks. wide, bears SE. and NW.								
40.001	The 1/4 sec. cor. of sec. 36 only, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above the ground, with a scattered mound of stone, 2 1/2 ft. diam., 1/2 ft. high, W. of the cor., with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">1/4</td> <td></td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">T13S</td> <td></td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">R47E</td> <td></td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">S36</td> <td></td> </tr> </table> <p style="text-align: center;">1957</p> <hr/>	1/4		T13S		R47E		S36	
1/4									
T13S									
R47E									
S36									
	<p>N. 0°01'00" W., beginning new measurement.</p>								
8.641	Point online, monumented with a rebar, 5/8 in. diam., firmly set, projecting 7 ins. above the ground, with aluminum cap mkd. NEV HWY PIT NY 08-9 SW COR, with a steel signpost set alongside.								
12.613	Point for the 1/4 sec. cor. of sec. 3 only, T. 14 S., R. 47 E., hereinafter described.								
39.991	The cor. of secs. 25 and 36 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above the ground, in a mound of stone, 3 1/2 ft. diam., 1 ft. high, with brass cap mkd.								

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,  
T. 13 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

T13S	
R47E	T14S
S25	R47E
S36	

1957

Remark brass cap to read

T13S	
R47E	T14S
S25	R47E
S 3	
S36	

2023

1957

---

SURVEY OF THE SUBDIVISIONAL LINES  
T. 14 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

---

From the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the independent resurvey of the S. bdy., T. 14 S., R. 47 E., executed under Group No. 368, with a mound of stone, 2 ft. diam., 1 1/2 ft. high, W. of the cor.

From this corner, an iron pipe, 1 in. diam., firmly set, projecting 4 ins. above the ground, no record found, bears S. 5°44'00" W., 1.1 lks. dist.

From this same corner, the 1906 1/4 sec. cor. of secs. 6 and 31, Tps. 13 and 14 S., R. 48 E., bears N. 14°36'50" W., 400.444 chs. dist., monumented with a quartzite stone, 12x10x6 ins. (Record, 15x8x5), firmly set, mkd. 1/4 on the N. face, in a mound of stone, 3 ft. diam., 1 ft. high. Monument marked AM, buried in place, and all other evidence of the corner destroyed.

From this same corner, the 1906 cor. of secs. 5, 6, 31, and 32, Tps. 13 and 14 S., R. 48 E., bears N. 8°55'40" W., 392.281 chs. dist., monumented with a basalt stone, 13x7x4 ins. (Record, 15x10x4), lying loose, mkd. with 5 notches on an edge and 1 notch on another, with a mound of stone, 3 ft. diam., 1 1/2 ft. high, W. of the cor. Monument marked AM, buried in place, and all other evidence of the corner destroyed.

From this same corner, the 1906 1/4 sec. cor. of secs. 5 and 32, Tps. 13 and 14 S., R. 48 E., bears N. 3°03'50" W., 388.206 chs. dist., monumented with a quartzite stone, 14x6x2 ins. (Record, 15x9x5), lying loose, mkd. 1/4 on a face, with a mound of stone, 3 1/2 ft. diam., 1/2 ft. high, N. of the cor. Monument marked AM, buried in place, and all other evidence of the corner destroyed.

SURVEY OF THE SUBDIVISIONAL LINES,  
T. 14 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

From this same corner, the 1906 cor. of secs. 4, 5, 32, and 33, Tps. 13 and 14 S., R. 48 E., bears N. 2°52'00" E., 388.175 chs. dist., monumented with a limestone, 12x11x8 ins. (Record, 15x10x5), firmly set, mkd. with 4 notches on E. edge and 2 notches on W. edge, with a mound of stone, 3 ft. diam., 1 ft. high, W. of the cor. Monument marked AM, buried in place, and all other evidence of the corner destroyed.

From this same corner, the 1906 1/4 sec. cor. of secs. 4 and 33, Tps. 13 and 14 S., R. 48 E., bears N. 8°42'00" E., 392.292 chs. dist., monumented with a limestone, 12x8x8 ins. (Record, 15x8x5), firmly set, mkd. 1/4 on the N. face, with remains of mound of earth N. of the cor. Monument marked AM, buried in place, and all other evidence of the corner destroyed.

From this same corner, the 1906 1/4 sec. cor. of secs. 25 and 30, T. 14 S., Rs. 47 and 48 E., bears N. 79°26'10" W., 142.291 chs. dist., monumented with a basalt stone, 20x9x8 ins. (Record, 12x12x6), firmly set, mkd. 1/4 on the W. face, with a mound of stone, 2 ft. diam., 1 ft. high, W. of the cor. Monument marked AM, buried in place, and all other evidence of the corner destroyed.

From this same corner, the 1906 cor. of secs. 19, 24, 25, and 30, T. 14 S., Rs. 47 and 48 E., bears N. 64°40'30" W., 154.749 chs. dist., monumented with a basalt stone, 15x9x6 ins. (Record, 15x10x5), firmly set, mkd. with 4 notches on the N. edge and 2 notches on the S. edge, with a mound of stone, 3 ft. diam., 1 ft. high, W. of the cor. Monument marked AM, buried in place, and all other evidence of the corner destroyed.

From this same corner, the 1906 1/4 sec. cor. of secs. 19 and 24, T. 14 S., Rs. 47 and 48 E., bears N. 52°45'50" W., 175.687 chs. dist., monumented with a lava stone, 13x9x9 ins. (Record, 15x10x8), firmly set, no marks visible, with a mound of stone, 2 1/2 ft. diam., 1 ft. high, W. of the cor. Monument marked AM, buried in place, and all other evidence of the corner destroyed.

From this same corner, the 1906 cor. of secs. 13, 18, 19, and 24, T. 14 S., Rs. 47 and 48 E., bears N. 43°41'20" W., 202.512 chs. dist., monumented with a lava stone, 18x10x10 ins. (Record, 15x12x7), lying loose, mkd. with 3 notches on an edge and 3 notches on another edge, in a scattered mound of stone. Monument marked AM, buried in place, and all other evidence of the corner destroyed.

From this same corner, the 1906 1/4 sec. cor. of secs. 13 and 18, T. 14 S., Rs. 47 and 48 E., bears N. 36°50'50" W., 233.212 chs. dist., monumented with a lava stone, 11x9x6 ins. (Record, 12x10x5), firmly set, mkd. 1/4 on the W. face. Monument marked AM, buried in place, and all other evidence of the corner destroyed.

SURVEY OF THE SUBDIVISIONAL LINES,  
T. 14 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From this same corner, the 1906 cor. of secs. 7, 12, 13, and 18, T. 14 S., Rs. 47 and 48 E., bears N. 31°39'30" W., 266.436 chs. dist., monumented with a basalt stone, 10x8x7 ins. (Record, 15x8x6), firmly set, mkd. with 2 notches on N. edge and 4 notches on S. edge, with a scattered mound of stone W. of the cor. Monument marked AM, buried in place, and all other evidence of the corner destroyed.</p> <p>From this same corner, the 1906 1/4 sec. cor. of secs. 7 and 12, T. 14 S., Rs. 47 and 48 E., bears N. 27°39'00" W., 301.354 chs. dist., monumented with a basalt stone, 9x6x4 ins. (Record, 12x7x7), firmly set, mkd. 1/4 on the W. face. Monument marked AM, buried in place, and all other evidence of the corner destroyed.</p> <p>From this same corner, the 1906 cor. of secs. 1, 6, 7, and 12, T. 14 S., Rs. 47 and 48 E., bears N. 24°29'00" W., 337.414 chs. dist., monumented with a basalt stone, 13x6x6 ins. (Record, 12x9x5), firmly set, mkd. with 5 notches on N. edge and 1 notch on S. edge, with a mound of stone, 2 1/2 ft. diam., 1/2 ft. high, W. of the cor. Monument marked AM, buried in place, and all other evidence of the corner destroyed.</p> <p>From this same corner, the 1906 1/4 sec. cor. of secs. 1 and 6, T. 14 S., Rs. 47 and 48 E., bears N. 21°56'10" W., 374.352 chs. dist., monumented with a basalt stone, 14x9x6 ins. (Record, 18x10x5), firmly set, mkd. 1/4 on the W. face, with a mound of stone, 2 ft. diam., 1/2 ft. high, W. of the cor. Monument marked AM, buried in place, and all other evidence of the corner destroyed.</p> <p>N. 0°01'40" W., bet. secs. 35 and 36.</p>
40.000	<p>Point for the 1/4 sec. cor. of secs. 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T14S R47E 1/4 S35   S36</p> <p style="text-align: center;">2022</p>
80.000	<p>Point for the cor. of secs. 25, 26, 35, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T14S R47E S26   S25 ----- S35   S36</p> <p style="text-align: center;">2022</p>

SURVEY OF THE SUBDIVISIONAL LINES,  
T. 14 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From this point, an iron pipe, 1 in. diam., firmly set, projecting 5 ins. above the ground, in a collar of stone, no record found, bears S. 20°01'00" E., 3.3 lks. dist.</p> <hr/> <p>From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd. as described in the field notes of the independent resurvey of the E. bdy., T. 14 S., R. 47 E., executed under Group No. 368, with a mound of stone, 2 ft. diam., 1 ft. high, W. of the cor.</p> <p>From this corner, an iron pipe, 1 in. diam., firmly set, projecting 9 ins. above the ground, no record found, bears S. 79°26'20" E., 1.8 lks. dist.</p> <p>S. 89°59'50" W., bet. secs. 25 and 36.</p>
12.5	Bladed desert road, 30 lks. wide, bears NNE. and SSW.
40.005	<p>Point for the 1/4 sec. cor. of secs. 25 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center; margin-top: 10px;"> <p>T14S R47E</p> <p>S25</p> <p>1/4 ———</p> <p>S36</p> <p>2022</p> </div>
80.010	<p>The cor. of secs. 25, 26, 35, and 36.</p> <hr/> <p>N. 0°01'40" W., bet. secs. 25 and 26.</p>
40.000	<p>Point for the 1/4 sec. cor. of secs. 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center; margin-top: 10px;"> <p>T14S R47E</p> <p>1/4</p> <p>S26   S25</p> <p>2022</p> </div>
80.000	<p>Point for the cor. of secs. 23, 24, 25, and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

SURVEY OF THE SUBDIVISIONAL LINES,  
T. 14 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T14S R47E S23   S24 ———— S26   S25  2022
	<p>From this point, an iron pipe, 1 in. diam., firmly set, projecting 6 ins. above the ground, in a collar of stone, no record found, bears S. 20°24'10" E., 8.5 lks. dist.</p> <hr/> <p>From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. as described in the field notes of the independent resurvey of the E. bdy., T. 14 S., R. 47 E., executed under Group No. 368.</p> <p>From this corner, an iron pipe, 2 ins. diam., firmly set, projecting 4 ins. above the ground, no record found, bears S. 74°27'40" E., 2.0 lks. dist.</p> <p>S. 89°59'00" W., bet. secs. 24 and 25.</p>
0.2	Bladed desert road, 30 lks. wide, bears NNE. and SSW.
40.005	<p>Point for the 1/4 sec. cor. of secs. 24 and 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	T14S R47E S24 1/4 ——— S25  2022
80.010	The cor. of secs. 23, 24, 25, and 26.
	N. 0°01'40" W., bet. secs. 23 and 24.
40.000	<p>Point for the 1/4 sec. cor. of secs. 23 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	T14S R47E 1/4 S23   S24  2022
63.0	Cross braided desert road, 50 lks. wide, bears SE. and NW.

SURVEY OF THE SUBDIVISIONAL LINES,  
T. 14 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS									
63.5	Overhead power line, bears SE. and NW.								
80.000	<p>Point for the cor. of secs. 13, 14, 23, and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T14S R47E</td></tr> <tr><td>S14</td><td>S13</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S23</td><td>S24</td></tr> </table> <p>2022</p> </div> <p>From this point, an iron pipe, 1 in. diam., firmly set, projecting 1 in. above the ground, no record found, bears S. 21°54'10" E., 14.5 lks. dist.</p> <hr/> <p>From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd. as described in the field notes of the independent resurvey of the E. bdy., T. 14 S., R. 47 E., executed under Group No. 368, with a mound of stone, 2 1/2 ft. diam., 1 1/2 ft. high, W. of the cor.</p> <p>From this corner, an iron pipe, 1 in. diam., firmly set, projecting 6 ins. above the ground, no record found, bears S. 15°14'20" W., 1.7 lks. dist.</p> <p>S. 89°58'00" W., bet. secs. 13 and 24.</p>	T14S R47E		S14	S13	<hr/>		S23	S24
T14S R47E									
S14	S13								
<hr/>									
S23	S24								
39.999	<p>Point for the 1/4 sec. cor. of secs. 13 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T14S R47E</td></tr> <tr><td colspan="2">S13</td></tr> <tr><td>1/4</td><td><hr/></td></tr> <tr><td colspan="2">S24</td></tr> </table> <p>2022</p> </div>	T14S R47E		S13		1/4	<hr/>	S24	
T14S R47E									
S13									
1/4	<hr/>								
S24									
58.5	Right-of-way fence, bears SE. and NW.								
63.4	Centerline of U.S. Hwy. No. 95, asphalt surfaced, 55 lks. wide, bears SE. and NW.								
68.5	Overhead power line, bears SE. and NW.								
70.5	Right-of-way fence, bears SE. and NW.								
79.998	The cor. of secs. 13, 14, 23, and 24.								

SURVEY OF THE SUBDIVISIONAL LINES,  
T. 14 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	N. 0°01'40" W., bet. secs. 13 and 14.
9.1	Right-of-way fence, bears SE. and NW.
11.5	Overhead power line, bears SE. and NW.
15.7	Centerline of U.S. Hwy. No. 95, asphalt surfaced, 55 lks. wide, bears SE. and NW.
20.0	Right-of-way fence, bears SE. and NW.
40.000	Point for the 1/4 sec. cor. of secs. 13 and 14.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.  <div style="text-align: center;">T14S R47E 1/4 S14 S13  2022</div>
80.000	Point for the cor. of secs. 11, 12, 13, and 14.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.  <div style="text-align: center;">T14S R47E S11 S12 ----- S14 S13  2022</div> <p>From this point, an iron pipe, 1 in. diam., firmly set, projecting 3 ins. above the ground, no record found, bears S. 17°49'30" E., 23.4 lks. dist.</p> <hr/> <p>From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the independent resurvey of the E. bdy., T. 14 S., R. 47 E., executed under Group No. 368, with a mound of stone, 3 1/2 ft. diam., 1 1/2 ft. high, W. of the cor.</p> <p>S. 89°59'40" W., bet. secs. 12 and 13.</p>
7.0	Bladed desert road, 15 lks. wide, bears NE. and SW.
10.5	Bladed desert road, 15 lks. wide, bears SE. and NW.
13.5	Bladed desert road, 15 lks. wide, bears NE. and SW.
16.5	Bladed desert road, 15 lks. wide, bears SE. and NW.

SURVEY OF THE SUBDIVISIONAL LINES,  
T. 14 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
23.0	Bladed desert road, 15 lks. wide, bears NE. and SW.
39.998	Point for the 1/4 sec. cor. of secs. 12 and 13.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 3 ft. base, to top, with brass cap mkd.  <div style="text-align: center;"> T14S R47E  S12  1/4 <u>        </u>  S13   2022 </div>
77.8	Bladed desert road, 15 lks. wide, bears SE. and NW.
79.996	The cor. of secs. 11, 12, 13, and 14. <hr/>
	N. 0°01'40" W., bet. secs. 11 and 12.
1.4	Bladed desert road, 15 lks. wide, bears SE. and NW.
40.000	Point for the 1/4 sec. cor. of secs. 11 and 12.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 17 ins. in the ground, to bedrock, over a plastic-encased magnet, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.  <div style="text-align: center;"> T14S R47E  1/4  S11 S12   2022 </div>
73.0	Bladed road, 60 lks. wide, bears NE. and SW.; ascend.
80.000	Point for the cor. of secs. 1, 2, 11, and 12.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.  <div style="text-align: center;"> T14S R47E  S 2   S 1  <u>        </u>  S11   S12   2022 </div> <hr/>

SURVEY OF THE SUBDIVISIONAL LINES,  
T. 14 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, in a collar of stone, with brass cap mkd. as described in the field notes of the independent resurvey of the E. bdy., T. 14 S., R. 47 E., executed under Group No. 368.</p> <p>S. 89°59'10" W., bet. secs. 1 and 12.</p>
29.5	Bladed desert road, 30 lks. wide, bears SE. and NW.
39.999	<p>Point for the 1/4 sec. cor. of secs. 1 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to bedrock, over a plastic-encased magnet, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T14S R47E S 1 1/4 ——— S12  2022</p>
65.5	Bladed road, 60 lks. wide, bears NE. and SW.
79.998	The cor. of secs. 1, 2, 11, and 12.
	<hr/> <p>N. 0°01'00" W., bet. secs. 1 and 2; over mountainous terrain.</p>
40.010	<p>Point for the 1/4 sec. cor. of secs. 1 and 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to bedrock, over a plastic-encased magnet, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T14S R47E 1/4 S 2 S 1  2022</p>
80.020	<p>The cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above a mound of stone, 3 1/2 ft. diam., 3 ft. high, with brass cap, mkd. as described in the field notes of the independent resurvey of a portion of the N. bdy., T. 14 S., R. 47 E., executed under Group No. 368.</p> <hr/>

SURVEY OF THE SUBDIVISIONAL LINES,  
T. 14 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the independent resurvey of the S. bdy., T. 14 S., R. 47 E., executed under Group No. 368, with a mound of stone, 2 ft. diam., 1 1/2 ft. high, W. of the cor.</p> <p>N. 0°02'20" W., bet. secs. 34 and 35.</p>
20.0	Deconstructed Tonopah and Tidewater Railroad grade, bears SSE. and NNW.
22.5	Desert two track road, 10 lks. wide, bears SSE. and NNW.
40.000	<p>Point for the 1/4 sec. cor. of secs. 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T14S R47E 1/4 S34 S35  2022</p>
80.000	<p>Point for the cor. of secs. 26, 27, 34, and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T14S R47E S27 S26 ----- S34 S35  2022</p> <p>From this point, an iron pipe, 1 in. diam., firmly set, projecting 12 ins. above the ground, no record found, bears S. 77°59'10" E., 5.3 lks. dist.</p> <hr/> <p>From the cor. of secs. 25, 26, 35, and 36.</p> <p>S. 89°59'30" W., bet. secs. 26 and 35.</p>
40.012	<p>Point for the 1/4 sec. cor. of secs. 26 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

SURVEY OF THE SUBDIVISIONAL LINES,  
T. 14 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T14S R47E S26 1/4 <hr style="width: 50px; margin: 0 auto;"/> S35 2022</p>
80.024	<p>The cor. of secs. 26, 27, 34, and 35.</p> <hr/>
	<p>N. 0°02'20" W., bet. secs. 26 and 27.</p>
40.000	<p>Point for the 1/4 sec. cor. of secs. 26 and 27. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T14S R47E 1/4 S27 S26 2022</p>
80.000	<p>Point for the cor. of secs. 22, 23, 26, and 27. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T14S R47E S22 S23 <hr style="width: 50px; margin: 0 auto;"/> S27 S26 2022</p> <p>From this point, an iron pipe, 1 in. diam., firmly set, projecting 8 ins. above the ground, no record found, bears S. 54°31'10" E., 11.6 lks. dist.</p> <hr/>
	<p>From the cor. of secs. 23, 24, 25, and 26. S. 89°59'30" W., bet. secs. 23 and 26.</p>
40.012	<p>Point for the 1/4 sec. cor. of secs. 23 and 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

SURVEY OF THE SUBDIVISIONAL LINES,  
T. 14 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T14S R47E S23 1/4 <hr style="width: 50px; margin: 0 auto;"/> S26  2022
80.024	The cor. of secs. 22, 23, 26, and 27.
	N. 0°02'20" W., bet. secs. 22 and 23.
40.000	Point for the 1/4 sec. cor. of secs. 22 and 23.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T14S R47E 1/4 S22 S23  2022
80.000	Point for the cor. of secs. 14, 15, 22, and 23.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T14S R47E S15   S14 <hr style="width: 50px; margin: 0 auto;"/> S22   S23  2022
	From this point, an iron pipe, 1 in. diam., firmly set, projecting 12 ins. above the ground, no record found, bears S. 65°47'40" E., 16.8 lks. dist.
	From the cor. of secs. 13, 14, 23, and 24.  S. 89°59'30" W., bet. secs. 14 and 23.
16.5	Overhead power line, bears SE. and NW.
17.0	Power line road, 20 lks. wide, bears SE. and NW.
40.012	Point for the 1/4 sec. cor. of secs. 14 and 23.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

SURVEY OF THE SUBDIVISIONAL LINES,  
T. 14 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T14S R47E S14 1/4 <u>        </u> S23  2022</p>
80.024	<p>The cor. of secs. 14, 15, 22, and 23.</p> <hr/>
	<p>N. 0°02'20" W., bet. secs. 14 and 15.</p>
40.000	<p>Point for the 1/4 sec. cor. of secs. 14 and 15.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T14S R47E 1/4 S15 S14  2022</p>
57.5	<p>Cross braided desert road, 50 lks. wide, bears NE. and SW.</p>
63.5	<p>Power line road, 15 lks. wide, bears SE. and NW.</p>
64.0	<p>Overhead power line, bears SE. and NW.</p>
80.000	<p>Point for the cor. of secs. 10, 11, 14, and 15.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T14S R47E S10 S11 <u>        </u> S15 S14  2022</p> <p>From this point, an iron pipe, 1 in. diam., firmly set, projecting 4 ins. above the ground, no record found, bears S. 57°31'10" E., 27.5 lks. dist.</p> <hr/>
	<p>From the cor. of secs. 11, 12, 13, and 14.  S. 89°59'30" W., bet. secs. 11 and 14.</p>
40.012	<p>Point for the 1/4 sec. cor. of secs. 11 and 14.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

SURVEY OF THE SUBDIVISIONAL LINES,  
T. 14 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T14S R47E S11 1/4 <u>        </u> S14  2022
49.0	Right-of-way fence, bears SSE. and NNW.
53.5	Bladed road, bears NE. and SW.
63.9	Centerline of U.S. Hwy. No. 95, asphalt surfaced, 55 lks. wide, bears SE. and NW.
68.0	Overhead power line, bears SE. and NW.
76.0	Right-of-way fence, bears SE. and NW.
80.024	The cor. of secs. 10, 11, 14, and 15.
	N. 0°02'20" W., bet. secs. 10 and 11.
8.5	Right-of-way fence, bears SSE. and NNW.
12.0	Overhead power line, bears SE. and NW.
16.3	Centerline of U.S. Hwy. No. 95, asphalt surfaced, 55 lks. wide, bears SE. and NW.
20.5	Right-of-way fence, bears SE. and NW.
21.0	Desert two track road, 20 lks. wide, bears SE. and NW.
40.000	Point for the 1/4 sec. cor. of secs. 10 and 11.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T14S R47E 1/4 S10 S11  2022
78.5	Desert two track road, 15 lks. wide, bears NE. and SW.
80.000	Point for the cor. of secs. 2, 3, 10, and 11.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

SURVEY OF THE SUBDIVISIONAL LINES,  
T. 14 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T14S R47E S 3   S 2 <hr style="width: 50%; margin: auto;"/>S10   S11  2022</p>
40.012	<p>From the cor. of secs. 1, 2, 11, and 12. S. 89°59'30" W., bet. secs. 2 and 11. Point for the 1/4 sec. cor. of secs. 2 and 11. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
73.5	<p style="text-align: center;">T14S R47E S 2 1/4 <hr style="width: 50%; margin: auto;"/>S11  2022</p>
80.024	<p>Desert two track road, 15 lks. wide, bears NE. and SW. The cor. of secs. 2, 3, 10, and 11.</p>
40.008	<p>S. 89°59'50" W., bet. secs. 3 and 10. Point for the 1/4 sec. cor. of secs. 3 and 10. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
59.565	<p style="text-align: center;">T14S R47E S 3 1/4 <hr style="width: 50%; margin: auto;"/>S10  2022</p>
59.565	<p>Intersect the E. bdy. of sec. 36, T. 13 S., R. 47 E. Point for the cor. of secs. 3 and 10 only. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p>

SURVEY OF THE SUBDIVISIONAL LINES,  
T. 14 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS									
	<table style="margin-left: auto; margin-right: auto;"> <tr><td></td><td style="border-left: 1px solid black;">T14S</td></tr> <tr><td></td><td style="border-left: 1px solid black;">R47E</td></tr> <tr><td style="border-right: 1px solid black;">T13S</td><td style="border-left: 1px solid black;">S 3</td></tr> <tr><td style="border-right: 1px solid black;">R47E</td><td style="border-left: 1px solid black;">S10</td></tr> </table>		T14S		R47E	T13S	S 3	R47E	S10
	T14S								
	R47E								
T13S	S 3								
R47E	S10								
	2022								
	From this point, the SE. cor. of sec. 36 only, T. 13 S., R. 47 E., hereinbefore described, bears S. 0°00'30" E., 12.596 chs. dist.								
	Point for the 1/4 sec. cor. of sec. 3 only, T. 14 S., R. 47 E., is on the E. bdy. of T. 13 S., R. 47 E., and at midpoint in latitude on the W. bdy. of sec. 3.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr><td style="border-right: 1px solid black;">T13S</td><td style="border-left: 1px solid black;">T14S</td></tr> <tr><td style="border-right: 1px solid black;">R47E</td><td style="border-left: 1px solid black;">R47E</td></tr> <tr><td></td><td style="border-left: 1px solid black;">1/4 S 3</td></tr> </table>	T13S	T14S	R47E	R47E		1/4 S 3		
T13S	T14S								
R47E	R47E								
	1/4 S 3								
	2022								
	From this point, the 1/4 sec. cor. of sec. 36 only, T. 13 S., R. 47 E., hereinbefore described, bears S. 0°01'00" E., 12.613 chs. dist.								
	From the cor. of secs. 2, 3, 10, and 11.								
	N. 0°01'00" W., bet. secs. 2 and 3.								
40.012	Point for the 1/4 sec. cor. of secs. 2 and 3.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr><td style="border-right: 1px solid black;">T14S</td><td style="border-left: 1px solid black;">R47E</td></tr> <tr><td></td><td style="border-left: 1px solid black;">1/4</td></tr> <tr><td style="border-right: 1px solid black;">S 3</td><td style="border-left: 1px solid black;">S 2</td></tr> </table>	T14S	R47E		1/4	S 3	S 2		
T14S	R47E								
	1/4								
S 3	S 2								
	2022								
80.024	The cor. of secs. 2, 3, 34, and 35, on the N. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above a mound of stone, 3 1/2 ft. diam., 1 1/2 ft. high, with brass cap mkd. as described in the field notes of the independent resurvey of a portion of the N. bdy., T. 14 S., R. 47 E., executed under Group No. 368.								

SURVEY OF THE SUBDIVISIONAL LINES,  
T. 14 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd. as described in the field notes of the independent resurvey of the S. bdy., T. 14 S., R. 47 E., executed under Group No. 368, with a mound of stone, 2 1/2 ft. diam., 1 1/2 ft. high, W. of the cor.</p> <p>From this corner, an iron pipe, 1 in. diam., firmly set, projecting 8 ins. above the ground, no record found, bears N. 75°41'10" W., 1.0 lk. dist.</p> <p>N. 0°02'50" W., bet. secs. 33 and 34.</p>
40.000	<p>Point for the 1/4 sec. cor. of secs. 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T14S R47E 1/4 S33 S34</p> <p style="text-align: center;">2022</p>
80.000	<p>Point for the cor. of secs. 27, 28, 33, and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T14S R47E S28 S27 ----- S33 S34</p> <p style="text-align: center;">2022</p> <p>From this point, an iron pipe, 1 in. diam., firmly set, projecting 8 ins. above the ground, no record found, bears S. 78°21'40" E., 17.9 lks. dist.</p>
40.008	<p>From the cor. of secs. 26, 27, 34, and 35.</p> <p>S. 89°59'50" W., bet. secs. 27 and 34.</p> <p>Point for the 1/4 sec. cor. of secs. 27 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p>

SURVEY OF THE SUBDIVISIONAL LINES,  
T. 14 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T14S R47E S27 1/4 <u>        </u> S34  2022</p>
33.0	Desert two track road, 15 lks. wide, bears SSE. and NNW.
34.5	Deconstructed Tonopah and Tidewater Railroad grade, bears SSE. and NNW.
80.016	The cor. of secs. 27, 28, 33, and 34.
40.000	<hr/> <p>N. 0°02'50" W., bet. secs. 27 and 28.</p>
	<p>Point for the 1/4 sec. cor. of secs. 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p>
80.000	<p style="text-align: center;">T14S R47E 1/4 S28   S27  2022</p>
	<p>Point for the cor. of secs. 21, 22, 27, and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p>
40.008	<p style="text-align: center;">T14S R47E S21   S22 <u>        </u> S28   S27  2022</p>
	<p>Cor. is located on SW. slope of railroad grade, bears SSE. and NNW.</p> <hr/>
40.008	<p>From the cor. of secs. 22, 23, 26, and 27.</p> <p>S. 89°59'50" W., bet. secs. 22 and 27.</p>
	<p>Point for the 1/4 sec. cor. of secs. 22 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p>

SURVEY OF THE SUBDIVISIONAL LINES,  
T. 14 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T14S R47E S22 1/4 <u>        </u> S27  2022</p>
78.5	Desert two track road, 15 lks. wide, bears SSE. and NNW.
80.016	The cor. of secs. 21, 22, 27, and 28.
	<hr/> <p>N. 0°02'50" W., bet. secs. 21 and 22.</p>
2.5	Desert two track road, 15 lks. wide, bears SSE. and NNW.
40.000	Point for the 1/4 sec. cor. of secs. 21 and 22.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T14S R47E 1/4 S21   S22  2022</p>
55.0	Cross braided desert road, 90 lks. wide, bears NE. and SW.
80.000	Point for the cor. of secs. 15, 16, 21, and 22.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T14S R47E S16   S15 <hr/>S21   S22  2022</p>
	<p>From this point, an iron pipe, 1 in. diam., firmly set, projecting 3 ins. above the ground, in a collar of stone, no record found, bears S. 75°56'10" E., 51.1 lks. dist.</p>
	<hr/> <p>From the cor. of secs. 14, 15, 22, and 23. S. 89°59'50" W., bet. secs. 15 and 22.</p>
40.008	Point for the 1/4 sec. cor. of secs. 15 and 22.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p>

SURVEY OF THE SUBDIVISIONAL LINES,  
T. 14 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T14S R47E S15 1/4 <u>        </u> S22  2022
56.5	Cross braided desert road, 90 lks. wide, bears NE. and SW.
80.016	The cor. of secs. 15, 16, 21, and 22.
	N. 0°02'50" W., bet. secs. 15 and 16.
40.000	Point for the 1/4 sec. cor. of secs. 15 and 16.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T14S R47E 1/4 S16 S15  2022
80.000	Point for the cor. of secs. 9, 10, 15, and 16.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T14S R47E S 9   S10 <u>        </u> S16   S15  2022
	From this point, an iron pipe, 1 in. diam., firmly set, projecting 4 ins. above the ground, no record found, bears S. 74°22'30" E., 65.5 lks. dist.
	From the cor. of secs. 10, 11, 14, and 15.  S. 89°59'50" W., bet. secs. 10 and 15.
16.0	Overhead power line, bears SE. and NW.
16.5	Power line road, 15 lks. wide, bears SE. and NW.
40.008	Point for the 1/4 sec. cor. of secs. 10 and 15.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.

SURVEY OF THE SUBDIVISIONAL LINES,  
T. 14 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T14S R47E S10 1/4 <hr style="width: 50px; margin: 0 auto;"/> S15  2022
80.016	The cor. of secs. 9, 10, 15, and 16. <hr/>
	N. 0°02'50" W., bet. secs. 9 and 10.
40.000	Point for the 1/4 sec. cor. of secs. 9 and 10.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T14S R47E 1/4 S 9   S10  2022
64.0	Power line road, 15 lks. wide, bears SE. and NW.
64.5	Overhead power line, bears SE. and NW.
67.394	Intersect the S. bdy. of sec. 36, T. 13 S., R. 47 E.  Point for the cor. of secs. 9 and 10 only.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T13S R47E <hr style="width: 50px; margin: 0 auto;"/> S 9   S10 T14S R47E  2022
	From this point, a rebar, 5/8 in. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. NEV HW PIT NO 318 SE COR, with a steel signpost set alongside, bears N. 83°17'20" W., 3.8 lks. dist.  From this same point, the 1/4 sec. cor. of sec. 36 only, T. 13 S., R. 47 E., hereinbefore described, bears S. 89°58'10" W., 19.578 chs. dist. <hr/>

SURVEY OF THE SUBDIVISIONAL LINES,  
T. 14 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 9 ins. above the ground, with brass cap mkd. as described in the field notes of the independent resurvey of the S. bdy., T. 14 S., R. 47 E., executed under Group No. 368, with a mound of stone, 2 ft. diam., 1 ft. high, W. of the cor.</p> <p>N. 0°03'30" W., bet. secs. 32 and 33.</p>
40.000	<p>Point for the 1/4 sec. cor. of secs. 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T14S R47E 1/4 S32 S33</p> <p style="text-align: center;">2022</p> <p>From this point, an iron pipe, 3 1/2 ins. diam., firmly set, projecting 15 ins. above the ground, in a concrete base, 1 1/2 ft. diam., with brass cap mkd. U.S. DEPARTMENT OF THE INTERIOR GAGING STATION GEOLOGICAL SURVEY, bears S. 79°20'10" W., 6.042 chs. dist.</p>
56.5	<p>Cross braided desert road, 80 lks. wide, bears NNE. and curving SW.</p>
80.000	<p>Point for the cor. of secs. 28, 29, 32, and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T14S R47E S29 S28 ----- S32 S33</p> <p style="text-align: center;">2022</p> <p>From this point, an iron pipe, 1 in. diam., firmly set, projecting 8 ins. above the ground, no record found, bears S. 88°15'00" E., 8.3 lks. dist.</p> <hr/> <p>From the cor. of secs. 27, 28, 33, and 34.</p> <p>S. 89°59'40" W., bet. secs. 28 and 33.</p>
40.005	<p>Point for the 1/4 sec. cor. of secs. 28 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

SURVEY OF THE SUBDIVISIONAL LINES,  
T. 14 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">T14S R47E S28 1/4 ——— S33  2022</p>
70.5	Cross braided desert road, 40 lks. wide, bears NE. and curving SW.
80.010	The cor. of secs. 28, 29, 32, and 33.
	N. 0°03'30" W., bet. secs. 28 and 29.
40.000	Point for the 1/4 sec. cor. of secs. 28 and 29.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.
	T14S R47E 1/4 S29 S28  2022
80.000	Point for the cor. of secs. 20, 21, 28, 29.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.
	T14S R47E S20 S21 ————— S29 S28  2022
	From this point, an iron pipe, 1 in. diam., firmly set, projecting 6 ins. above the ground, in a collar of stone, no record found, bears S. 80°13'30" E., 15.3 lks. dist.
	From the cor. of secs. 21, 22, 27, and 28.  S. 89°59'40" W., bet. secs. 21 and 28.
35.5	Bladed desert road, 25 lks. wide, bears NE. and SW.
40.005	Point for the 1/4 sec. cor. of secs. 21 and 28.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

SURVEY OF THE SUBDIVISIONAL LINES,  
T. 14 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T14S R47E S21 1/4 <hr style="display: inline-block; width: 50px; border: 0.5px solid black;"/> S28  2022
80.010	The cor. of secs. 20, 21, 28, 29.  <hr style="width: 100%;"/> N. 0°03'30" W., bet. secs. 20 and 21.
40.000	Point for the 1/4 sec. cor. of secs. 20 and 21.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	T14S R47E 1/4 S20   S21  2022
80.000	Point for the cor. of secs. 16, 17, 20, and 21.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T14S R47E S17   S16 <hr style="width: 50%; margin: 0 auto;"/> S20   S21  2022
	From this point, an iron pipe, 1 1/4 ins. diam., firmly set, projecting 10 ins. above the ground, no record found, bears S. 77°39'00" E., 21.1 lks. dist.
	<hr style="width: 100%;"/> From the cor. of secs. 15, 16, 21, and 22.  S. 89°59'40" W., bet. secs. 16 and 21.
40.005	Point for the 1/4 sec. cor. of secs. 16 and 21.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

SURVEY OF THE SUBDIVISIONAL LINES,  
T. 14 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T14S R47E S16 1/4 <hr style="display: inline-block; width: 1em; vertical-align: middle;"/> S21  2022
43.0	Desert two track road, 15 lks. wide, bears SSE. and NNW.
45.5	Deconstructed Tonopah and Tidewater Railroad grade, bears SSE. and NNW.
80.010	The cor. of secs. 16, 17, 20, and 21.
	N. 0°03'30" W., bet. secs. 16 and 17.
40.000	Point for the 1/4 sec. cor. of secs. 16 and 17.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T14S R47E 1/4 S17   S16  2022
60.5	Deconstructed Tonopah and Tidewater Railroad grade, bears SSE. and NNW.
63.0	Desert two track road, 15 lks. wide, bears SSE. and NNW.
80.000	Point for the cor. of secs. 8, 9, 16, and 17.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T14S R47E S 8   S 9 <hr style="display: inline-block; width: 1em; vertical-align: middle;"/> S17   S16  2022
	From this point, an iron pipe, 1 in. diam., firmly set, projecting 1 in. above the ground, in a collar of stone, no record found, bears S. 75°03'40" E., 29.0 lks. dist.
	From the cor. of secs. 9, 10, 15, and 16.  S. 89°59'40" W., bet. secs. 9 and 16.
40.005	Point for the 1/4 sec. cor. of secs. 9 and 16.

SURVEY OF THE SUBDIVISIONAL LINES,  
T. 14 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T14S R47E S 9 1/4 ——— S16  2022</p>
80.010	<p>The cor. of secs. 8, 9, 16, and 17.</p> <hr/> <p>N. 0°03'30" W., bet. secs. 8 and 9.</p>
40.000	<p>Point for the 1/4 sec. cor. of secs. 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T14S R47E 1/4 S 8   S 9  2022</p>
67.360	<p>Intersect the S. bdy. of sec. 35, T. 13 S., R. 47 E.</p> <p>Point for the cor. of secs. 8 and 9 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T13S R47E ——— S 8   S 9 T14S R47E  2022</p> <p>From this point, the 1/4 sec. cor. of sec. 35 only, T. 13 S., R. 47 E., hereinbefore described, bears S. 89°58'10" W., 19.571 chs. dist.</p> <hr/> <p>Point for the 1/4 sec. cor. of sec. 9 only, T. 14 S., R. 47 E., is on the S. bdy. of T. 13 S., R. 47 E., and at midpoint in departure on the N. bdy. of sec. 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

SURVEY OF THE SUBDIVISIONAL LINES,  
T. 14 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T13S R47E <hr style="width: 50px; margin: auto;"/> 1/4 S 9 T14S R47E  2022
	From this point, the cor. of secs. 35 and 36 only, T. 13 S., R. 47 E., hereinbefore described, bears S. 89°58'20" W., 19.576 chs. dist.
	From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd. as described in the field notes of the independent resurvey of the S. bdy., T. 14 S., R. 47 E., executed under Group No. 368, with a mound of stone, 2 ft. diam., 1 ft. high, W. of the cor.
	From this corner, an iron pipe, 1 in. diam., firmly set, projecting 4 ins. above the ground, no record found, bears S. 75°55'50" W., 1.4 lks. dist.
	N. 0°04'10" W., bet. secs. 31 and 32.
40.000	Point for the 1/4 sec. cor. of secs. 31 and 32.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T14S R47E 1/4 S31 S32  2022
80.000	Point for the cor. of secs. 29, 30, 31, and 32.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T14S R47E S30 S29 <hr style="width: 50px; margin: auto;"/> S31 S32  2022
	From this point, an iron pipe, 1 in. diam., firmly set, projecting 3 ins. above the ground, no record found, bears N. 45°38'20" E., 12.6 lks. dist.

SURVEY OF THE SUBDIVISIONAL LINES,  
T. 14 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	From the cor. of secs. 28, 29, 32, and 33. S. 89°59'30" W., bet. secs. 29 and 32.
40.002	Point for the 1/4 sec. cor. of secs. 29 and 32. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.  <div style="text-align: center;">T14S R47E S29 1/4 ——— S32  2022</div>
52.5	Cross braided desert road, 1.6 chs. wide, bears SE. and NW.
80.004	The cor. of secs. 29, 30, 31, and 32. <hr/>
	N. 89°59'30" W., bet. secs. 30 and 31.
40.000	Point for the 1/4 sec. cor. of secs. 30 and 31. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.  <div style="text-align: center;">T14S R47E S30 1/4 ——— S31  2022</div>
80.003	The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd. as described in the field notes of the independent resurvey of the W. bdy., T. 14 S., R. 47 E., executed under Group No. 368, with a mound of stone, 2 ft. diam., 1 ft. high, W. of the cor.  From this corner, an iron pipe, 1 in. diam., firmly set, projecting 8 ins. above the ground, no record found, bears N. 82°36'50" W., 1.2 lks. dist. <hr/>
	From the cor. of secs. 29, 30, 31, and 32. N. 0°04'10" W., bet. secs. 29 and 30.
27.0	Cross braided desert road, 1.5 chs. wide, bears SE. and NW.
40.000	Point for the 1/4 sec. cor. of secs. 29 and 30.

SURVEY OF THE SUBDIVISIONAL LINES,  
T. 14 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T14S R47E 1/4 S30 S29</p> <p style="text-align: center;">2022</p>
80.000	<p>Point for the cor. of secs. 19, 20, 29, and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T14S R47E S19 S20 ----- S30 S29</p> <p style="text-align: center;">2022</p> <p>From this point, an iron pipe, 1 in. diam., firmly set, projecting 4 ins. above the ground, no record found, bears N. 0°42'40" E., 12.7 lks. dist.</p>
40.002	<p>From the cor. of secs. 20, 21, 28, and 29.</p> <p>S. 89°59'30" W., bet. secs. 20 and 29.</p> <p>Point for the 1/4 sec. cor. of secs. 20 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T14S R47E S20 1/4 ----- S29</p> <p style="text-align: center;">2022</p>
80.004	<p>The cor. of secs. 19, 20, 29, and 30.</p>
40.000	<p>N. 89°58'40" W., bet. secs. 19 and 30.</p> <p>Point for the 1/4 sec. cor. of secs. 19 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

SURVEY OF THE SUBDIVISIONAL LINES,  
T. 14 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T14S R47E S19 1/4 <u>        </u> S30  2022
52.5	Cross braided desert road, 2.0 chs. wide, bears SE. and NW.
79.994	The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd. as described in the field notes of the independent resurvey of the W. bdy., T. 14 S., R. 47 E., executed under Group No. 368, with a mound of stone, 2 1/2 ft. diam., 1 ft. high, W. of the cor.  From this point, an iron pipe, 1 in. diam., firmly set, projecting 6 ins. above the ground, no record found, bears S. 79°52'50" W., 1.2 lks. dist.
	From the cor. of secs. 19, 20, 29, and 30. N. 0°04'10" W., bet. secs. 19 and 20.
40.000	Point for the 1/4 sec. cor. of secs. 19 and 20.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T14S R47E 1/4 S19   S20  2022
80.000	Point for the cor. of secs. 17, 18, 19, and 20.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T14S R47E S18   S17 <u>        </u> S19   S20  2022
	From this point, an iron pipe, 1 in. diam., firmly set, projecting 2 ins. above the ground, no record found, bears N. 24°44'00" W., 15.3 lks. dist.

SURVEY OF THE SUBDIVISIONAL LINES,  
T. 14 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From the cor. of secs. 16, 17, 20, and 21.</p> <p>S. 89°59'30" W., bet. secs. 17 and 20.</p>
40.002	<p>Point for the 1/4 sec. cor. of secs. 17 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, to bedrock, over a plastic-encased magnet, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T14S R47E S17 1/4 ——— S20  2022</p>
80.004	<p>The cor. of secs. 17, 18, 19, and 20.</p> <hr/> <p>N. 89°58'00" W., bet. secs. 18 and 19.</p>
40.000	<p>Point for the 1/4 sec. cor. of secs. 18 and 19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T14S R47E S18 1/4 ——— S19  2022</p>
79.986	<p>The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd. as described in the field notes of the independent resurvey of the W. bdy., T. 14 S., R. 47 E., executed under Group No. 368, with a mound of stone, 2 1/2 ft. diam., 1 ft. high, W. of the cor.</p> <p>From this corner, an iron pipe, 1 in. diam., firmly set, projecting 8 ins. above the ground, no record found, bears S. 84°07'50" E., 1.5 lks. dist.</p> <hr/> <p>From the cor. of secs. 17, 18, 19, and 20.</p> <p>N. 0°04'10" W., bet. secs. 17 and 18.</p>
40.000	<p>Point for the 1/4 sec. cor. of secs. 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

SURVEY OF THE SUBDIVISIONAL LINES,  
T. 14 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T14S R47E 1/4 S18   S17  2022
80.000	Point for the cor. of secs. 7, 8, 17, and 18.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.  T14S R47E S 7   S 8 <hr style="width: 50%; margin: auto;"/> S18   S17  2022
	From the cor. of secs. 8, 9, 16, and 17.  S. 89°59'30" W., bet. secs. 8 and 17.
9.0	Desert two track road, 15 lks. wide, bears SSE. and NNW.
11.0	Deconstructed Tonopah and Tidewater Railroad grade, bears SSE. and NNW.
40.002	Point for the 1/4 sec. cor. of secs. 8 and 17.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.  T14S R47E S 8 1/4 <hr style="width: 50%; margin: auto;"/> S17  2022
80.004	The cor. of secs. 7, 8, 17, and 18.  N. 89°57'10" W., bet. secs. 7 and 18.
40.000	Point for the 1/4 sec. cor. of secs. 7 and 18.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.

SURVEY OF THE SUBDIVISIONAL LINES,  
T. 14 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T14S R47E S 7 1/4 <hr style="width: 50px; display: inline-block; vertical-align: middle;"/> S18  2022
79.976	<p>The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. as described in the field notes of the independent resurvey of the W. bdy., T. 14 S., R. 47 E., executed under Group No. 368, with a mound of stone, 2 ft. diam., 1 ft. high, W. of the cor.</p> <p>From this corner, an iron pipe, 1 in. diam., firmly set, projecting 9 ins. above the ground, no record found, bears N. 86°04'40" W., 1.2 lks. dist.</p> <hr/> <p>From the cor. of secs. 7, 8, 17, and 18. N. 0°04'10" W., bet. secs. 7 and 8.</p>
40.000	<p>Point for the 1/4 sec. cor. of secs. 7 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	T14S R47E 1/4 S 7   S 8  2022
67.325	<p>Intersect the S. bdy. of sec. 34, T. 13 S., R. 47 E.</p> <p>Point for the cor. of secs. 7 and 8 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	T13S R47E <hr style="width: 50px; display: inline-block; vertical-align: middle;"/> S 7   S 8 T14S R47E  2022
	<p>From this point, the 1/4 sec. cor. of sec. 34 only, T. 13 S., R. 47 E., hereinbefore described, bears S. 89°59'00" W., 19.541 chs. dist.</p> <hr/>

SURVEY OF THE SUBDIVISIONAL LINES,  
T. 14 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

Point for the 1/4 sec. cor. of sec. 8 only, T. 14 S., R. 47 E., is on the S. bdy. of T. 13 S., R. 47 E., and at midpoint in departure on the N. bdy. of sec. 8.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

T13S R47E

1/4 S 8

T14S R47E

2022

From this point, the cor. of secs. 34 and 35 only, T. 13 S., R. 47 E., hereinbefore described, bears S. 89°57'20" W., 19.563 chs. dist.

---

Point for the 1/4 sec. cor. of sec. 7 only, T. 14 S., R. 47 E., is on the S. bdy. of T. 13 S., R. 47 E., and at 40 chs. W. in departure from the corner of secs. 7 and 8 only, on the N. bdy. of sec. 7.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

T13S R47E

1/4 S 7

T14S R47E

2022

From this point, the cor. of secs. 33 and 34 only, T. 13 S., R. 47 E., hereinbefore described, bears S. 89°58'10" W., 19.524 chs. dist.

---

## T. 14 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

## GENERAL DESCRIPTION

The elevation above sea level in the township ranges from approximately 2500 feet in the southeast portion of the township to approximately 2800 feet in the northwest portion of the township. Sections 1, 2, 12, and 13 contain rough mountains with elevation approaching 3700 feet. The rest of the township is nearly level with general drainage following the (dry) Amargosa River southeast through the township.

No springs, flowing streams, or other water sources were observed during the course of the survey. Vegetation consists of creosote and cacti.

The area has a history of mining with evidence of old mining claims visible throughout the township. No active mining was observed during the course of this survey.

Primary access is provided by U.S. Hwy. No. 95, which runs generally southeast and northwest through sections 10, 11, 13, 14, and 24. Secondary access is provided by bladed roads leaving the highway to the northeast and southwest in section 14 and southerly in section 19, Township 14 South, Range 48 East. The latter, providing access to the Big Dune recreation area. Further access is provided by various bladed roads and tracks extending throughout the township.

Overhead power lines follow the highway corridor through the northeastern portion of the township. The deconstructed Tonopah and Tidewater Railroad grade runs southeast, entering the township in section 8 and leaving the township in section 35.

There are no settlers living within the township.

---

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Miguel A. Garcia	Cadastral Surveyor
Carlos Gil-Mendoza	Cadastral Surveyor
Michael O. Jones	Cadastral Surveyor
Kelly R. Totten	Cadastral Surveyor
Shane T. Trotter	Cadastral Surveyor
Mark G. Petrosine	Survey Technician
Alex J. Yetsko	Survey Technician

CERTIFICATE OF SURVEY

I, Lee T. Wilson, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing the date of the 4<sup>th</sup> day of January, 2022, I have dependently resurveyed portions of the south and east boundaries, Township 13 South, Range 47 East, and surveyed the subdivisional lines, Township 14 South, Range 47 East, of the Mount Diablo Meridian, in the state of Nevada, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

JAN 04 2024

(Date)

Lee T. Wilson

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Reno, Nevada

The foregoing field notes of the dependent resurvey of portions of the south and east boundaries, Township 13 South, Range 47 East, and the survey of the subdivisional lines, Township 14 South, Range 47 East, of the Mount Diablo Meridian, Nevada, executed by Lee T. Wilson, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

JAN 04 2024

(Date)

Michael O. Hummer

(Chief Cadastral Surveyor for Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above described surveys in Townships 13 and 14 South, Range 47 East, Mount Diablo Meridian, Nevada, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor for Nevada)~~