

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF

THE THIRD STANDARD PARALLEL NORTH THROUGH A PORTION OF RANGE 65 EAST,
A PORTION OF THE WEST BOUNDARY AND A PORTION OF THE SUBDIVISIONAL LINES,
AND THE CORRECTIVE DEPENDENT RESURVEY OF

A PORTION OF THE SUBDIVISIONAL LINES,

THE SUBDIVISION OF SECTION 7,

AND METES-AND-BOUNDS SURVEYS IN SECTIONS 3, 7, AND 18,

TOWNSHIP 15 NORTH, RANGE 65 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATE OF NEVADA

EXECUTED BY

Joseph J. Johnson, Cadastral Surveyor

Under Special Instructions dated July 18, 2013,

and approved July 18, 2013,

and Supplemental Special Instructions dated May 21, 2014,

and approved May 21, 2014,

and Supplemental Special Instructions dated November 17, 2014,

and approved November 17, 2014,

and Supplemental Special Instructions dated December 10, 2014,

and approved December 10, 2014

which provided for the surveys included under Group No. 927,

and Assignment Instructions dated July 18, 2013.

Survey commenced July 21, 2013

Survey completed December 11, 2014

INDEX DIAGRAM

TOWNSHIP 15 NORTH, RANGE 65 EAST, MOUNT DIABLO MERIDIAN, NEVADA

			33			34			
			3			2			
6	5	4	9	3	4	2	1		
						8			
7	8	9	10		11		12		
3									
8									
18	7	17	16	15		14	13		
5									
19	20		21	22		23	24		
30	29		28	27		26	25		
31	32	33	34		35	36			

Subdivision of Section 7 pp. 11 - 12.
 Metes-and-Bounds Survey in Section 3..... pp. 12 - 23.
 Metes-and-Bounds Survey in Sections 7 and 18..... pp. 23 - 32.

TOWNSHIP 15 NORTH, RANGE 65 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The following field notes are those of the dependent resurvey of the Third Standard Parallel North through a portion of Range 65 East, a portion of the west boundary and a portion of the subdivisional lines, and the corrective dependent resurvey of a portion of the subdivisional lines, the subdivision of Section 7, and metes-and-bounds surveys in sections 3, 7, and 18, Township 15 North, Range 65 East, Mount Diablo Meridian, Nevada.

The Third Standard Parallel North (north boundary) was surveyed by U.S. Deputy Surveyors E.B. Monroe and A.G. Bateman in 1871 under Contract No. 44. The west boundary was surveyed by U.S. Deputy Surveyors E.B. Monroe and A.G. Bateman in 1872 under Contract No. 48. The south and east boundaries and subdivisional lines were surveyed by U.S. Deputy Surveyors E.B. Monroe and A.G. Bateman in 1874 under Contract No. 63. The Third Standard Parallel North through a portion of Range 64 East (north boundary), and the west boundary were dependently resurveyed by Cadastral Surveyors Horace G. Parker, Eldon W. Sibley and Robert A. Pratt in 1967-68 under Group No. 454. The Third Standard Parallel North through a portion of Range 65 East (north boundary), was dependently resurveyed in 1975, and a portion of the subdivisional lines was dependently resurveyed in 1976 by Cadastral Surveyor R.A. Pratt under Group No. 524.

Before restoring the corners, the lines of the original surveys were retraced and a diligent search made for any evidence of the original corners and other calls of the original field note record.

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 2009, and the Special Instructions for Group No. 927, dated July 18, 2013, Supplemental Special Instructions dated May 21, 2014, Supplemental Special Instructions dated November 17, 2014 and Supplemental Special Instructions dated December 10, 2014.

Measurements were made with Trimble R8-3 Global Positioning System (GPS) receivers using the real-time kinematic method. The direction of each line is with reference to the true meridian. All bearings are mean bearings and the distances are reported as horizontal measurement at a mean ground elevation of 7,500 feet above sea level.

The NAD83 (2011) (EPOCH:2010.0000) geographic position, of the following corners were determined from GPS static observations processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuous Operating Reference Stations (CORS) AI8817 ECHO ECHO_BRGN_NV1999 CORS ARP, AI0950 EGAN EGAN_BRGN_NV1996 CORS ARP, DL7692 GOSH GOSH BRGN UT1996 CORS ARP, DM7135 NVPI PIOCHE CORS ARP, DL6904 NVSV SPRING VALLEY CORS ARP, and carried forward by RTK observations, is as follows:

TOWNSHIP 15 NORTH, RANGE 65 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The cor. of secs. 13, 18, 19 and 24 on the W. bdy. of the Tp., is as follows:

Latitude: 39°09'29.643" N. Longitude: 114°43'31.319" W.

The standard 1/4 sec. cor. of sec. 34, T. 16 N., R. 65 E. is as follows:

Latitude: 39°12'03.754" N. Longitude: 114°38'51.363" W.

The May 27, 2014 mean magnetic declination was determined to be 12°26' E., as obtained from the National Oceanic and Atmospheric Administration's National Geophysical Data Center declination calculator.

DEPENDENT RESURVEY OF THE THIRD STANDARD PARALLEL NORTH
THROUGH A PORTION OF RANGE 65 EAST,
MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of a Portion of the Survey Executed by
U.S. Deputy Surveyors E.B. Monroe and A.G. Bateman in 1871
and a Portion of the Dependent Resurvey Executed by
Cadastral Surveyor R.A. Pratt in 1975

Beginning at the standard 1/4 sec. cor. of sec. 34, monumented with a limestone, 10x9x5 ins., lying on top of a mound of stone, 1 1/2 ft. base, 1 ft. high, no visible marks. This is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

SC
T16N R65E
1/4 S34

2013

Bury the limestone alongside the stainless steel post.

S. 89°04'40" W., on the S. bdy. of sec. 34.

12.80 Ridge bears N. 50° E. and S. 30° W.

17.540 The closing cor. of secs. 2 and 3, T. 15 N., R. 65 E., hereinafter described.

36.70 Ravine, drains N. 20° W.

DEPENDENT RESURVEY OF THE THIRD STANDARD PARALLEL NORTH
THROUGH A PORTION OF RANGE 65 EAST,
MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
38.656	The standard cor. of secs. 33 and 34, monumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stone, 3 ft. base, 2 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of the Third Standard Parallel North through Range 65 East, executed under Group No. 524.
	S. 89°40'50" W., on the S. bdy. of sec. 33.
18.303	The N 1/4 sec. cor. of sec. 3, T. 15 N., R. 65 E., hereinafter described.
28.50	Ridge, bears NE. and SW.
39.556	The standard 1/4 sec. cor. of sec. 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the Third Standard Parallel North through a portion of Range 65 East, executed under Group No. 524.
	S. 89°41'40" W., beginning new measurement.
18.163	The closing cor. of secs. 3 and 4, T. 15 N., R. 65 E., hereinafter described.
38.999	The E 1/16 sec. cor. of sec. 4 only, T. 15 N., R. 65 E., monumented with an iron post, 2 1/2 ins. diam., firmly set projecting 7 ins. above a mound of stone, 4 ft. base, 2 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 15 N., R. 65 E., executed under Group No. 524.
39.562	The standard cor. of secs. 32 and 33, monumented with an iron post, 2 1/2 ins. diam., projecting 6 ins. above a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of the Third Standard Parallel North through a portion of Range 65 East, executed under Group No. 524.
DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY, T. 15 N., R. 65 E., MOUNT DIABLO MERIDAN, NEVADA	
Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyors E.B. Monroe and A.G. Bateman in 1872 and a Portion of the Dependent Resurvey Executed by Cadastral Surveyors H.G. Parker, E.W. Sibley and R.A. Pratt in 1967-68.	
	From the cor. of secs. 7, 12, 13 and 18, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 13 ins. above a mound of stone, 5 ft. base, 2 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of the

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 15 N., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	E. bdy., T. 15 N., R. 64 E., executed under Group No. 454. N. 1°12'00" W., bet. secs. 7 and 12.
20.354	<p>Point for the S 1/16 sec. cor. of secs. 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S12 S 7</p> <p style="text-align: center;">2014</p>
40.708	<p>The 1/4 sec. cor. of secs. 7 and 12, monumented with an iron post, 2 1/2 ins. diam., firmly set, in a mound of stone, 4 ft. base, 2 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of the E. bdy., T. 15 N., R. 65 E., executed under Group No. 454, with an iron post 2 ins. diam., inverted and set alongside.</p>
<hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 15 N., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>	
<p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyors E.B. Monroe and A.G. Bateman in 1874 and a Portion of the Dependent Resurvey Executed by Cadastral Surveyor R.A. Pratt in 1976</p> <hr/>	
<p>From the cor. of secs. 2, 3, 10 and 11, determined at a depression within a scattered mound of stone, with an iron post, 2 1/2 ins. diam., 28 ins. long, lying loose on the ground alongside, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 15 N., R. 65 E., executed under Group No. 524.</p>	
<p>At the corner point</p>	
<p>Reset the iron post, 25 ins. in the ground and add the marks 2014 to brass cap.</p>	
<p>N. 4°21'00" E., bet. secs. 2 and 3.</p>	
39.226	<p>Point for the 1/4 sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 N., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">T15N R65E 1/4 S 3 S 2</p> <p style="text-align: center;">2014</p> <p>75.118 Intersect the Third Standard Parallel North.</p> <p>Point for the closing cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T16N R65E S34</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 3</td> <td style="padding: 0 5px;"> </td> <td style="padding: 0 5px;">S 2</td> </tr> <tr> <td colspan="3" style="border-top: 1px solid black; border-bottom: 1px solid black;"></td> </tr> <tr> <td colspan="3" style="text-align: center;">T15N R65E</td> </tr> <tr> <td colspan="3" style="text-align: center;">CC</td> </tr> </table> <p style="text-align: center;">2014</p> <p>From this point, the standard 1/4 sec. cor. of sec. 34, T. 16 N., R. 65 E., bears N. 89°04'40" E., 17.540 chs. dist., hereinbefore described.</p> <hr/> <p>From the point for the cor. of secs. 17, 18, 19 and 20, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to bedrock, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T15N R65E</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S18</td> <td style="padding: 0 5px;"> </td> <td style="padding: 0 5px;">S17</td> </tr> <tr> <td colspan="3" style="border-top: 1px solid black; border-bottom: 1px solid black;"></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S19</td> <td style="padding: 0 5px;"> </td> <td style="padding: 0 5px;">S20</td> </tr> </table> <p style="text-align: center;">2014</p> <p>From this point, a position determined as the cor. of secs. 17, 18, 19, and 20, by Dean Neubauer, Nevada Professional Land Surveyor No. 9392, in 2008, bears N. 1°27'40" E., 0.200 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, projecting 4 ins. above a collar of stone, with an aluminum cap mkd. SUMMIT PLS 9392, as recorded in White Pine County, Nevada, Record of Survey Map No. 1072, File No. 343243. This position was determined using improper control and is not utilized in the course of this survey.</p>	S 3		S 2				T15N R65E			CC			S18		S17				S19		S20
S 3		S 2																				
T15N R65E																						
CC																						
S18		S17																				
S19		S20																				

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 N., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

From this same point, the 1/4 sec. cor. of secs. 16 and 21, perpetuated by Dean Neubauer, Nevada Professional Land Surveyor No. 9392, in 2008, bears S. 89°46'00" E., 116.221 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, in a mound of stone, 2 ft. base, 1 ft. high., with an aluminum cap mkd. SUMMIT PLS 9392, with a limestone, 5x5x9 ins. lying loose on the mound of stone, clearly mkd. 1/4 on one face, as recorded in White Pine County, Nevada, Record of Survey Map No. 1072, File No. 343243. This is accepted as a careful and faithful perpetuation of the position of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.

T15N R65E

S16

1/4 —

S21

2014

Bury rebar alongside stainless steel post.

From this same point, a position determined as the cor. of secs. 16, 17, 20 and 21, by Dean Neubauer, Nevada Professional Land Surveyor No. 9392, in 2008, bears S. 89°55'30" E., 77.452 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, projecting 3 ins. above a mound of stone, 2 ft. base, 1 ft. high., with an aluminum cap mkd. SUMMIT PLS 9392, as recorded in White Pine County, Nevada, Record of Survey Map No. 1072, File No. 343243. This position is not utilized during the course of this survey.

From this same point, the 1/4 sec. cor. of secs. 29 and 30, bears S. 2°10'40" E., 120.838 chs. dist., monumented with a limestone, 5x5x10 ins., lying flat on top of an embedded mound of stone, 3 ft. base, 6 ins. high, clearly mkd. 1/4 on a face.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.

T15N R65E

1/4

S30|S29

2014

Bury the mkd. stone alongside stainless steel post.

From this same point, a rebar, 5/8 in. diam., bears S. 3°12'00" E., 78.254 chs. dist., firmly set, in a mound of stone, 3 ft. base, 2 ft. high, with aluminum cap mkd. SUMMIT PLS

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 N., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>9392, with a steel fence post set alongside, mkd. with black paint, W.C. S 136.38 FT TO COR. SEC COR 19-20/30-29 #7720. This position is not utilized during the course of this survey.</p> <p>The control lines were fully retraced and a careful search was made for evidence of intervening corners, none of which were recovered.</p> <p>S. 89°50'40" W., bet. secs. 18 and 19.</p>
38.580	<p>Point for the 1/4 sec. cor. of secs. 18 and 19, at proportionate distance, there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T15N R65E S18 1/4 — S19</p> <p style="text-align: center;">2014</p>
76.543	<p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the E. bdy., T. 15 N., R. 64 E., executed under Group No. 454, with a cedar post, 4 ins. diam., set alongside, from which the 1967-68 bearing trees</p> <p style="padding-left: 40px;">A juniper, 14 ins. diam., bears N. 28 1/2° E., 89 lks. dist., mkd. T15N R65E S18 BT.</p> <p style="padding-left: 40px;">A juniper, 10 ins. diam., bears S. 64° E., 47 lks. dist., mkd. T15N R65E S19 BT.</p> <p style="padding-left: 40px;">A juniper, 16 ins. diam., bears S. 57 1/2° W., 109 lks. dist., mkd. T15N R64E S24 BT.</p> <p style="padding-left: 40px;">A juniper, 14 ins. diam., bears N. 15 1/4° W., 65 lks. dist., mkd. T15N R64E S13 BT.</p>
40.274	<p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 1°59'10" W., bet. secs. 17 and 18.</p> <p>Point for the 1/4 sec. cor. of secs. 17 and 18, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 N., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T15N R65E 1/4 S18 S17 2014
80.548	The cor. of secs. 7, 8, 17 and 18, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 1 ft. above a mound of stone, 4 ft. base, 2 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 15 N., R. 65 E., executed under Group No. 524.
	<hr/> N. 89°31'20" W., bet. secs. 7 and 18.
37.921	The 1/4 sec. cor. of secs. 7 and 18, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 9 ins. above a mound of stone, 4 ft. base, 2 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 15 N., R. 65 E., executed under Group No. 524.
	<hr/> N. 89°29'30" W., beginning new measurement.
20.510	Trail road, 15 lks. wide, bears N. 6°01'10" E. and S. 9°15'10" W.
20.891	The witness point at the intersection with a line 25 ft. westerly of and parallel with the centerline of a trail road, hereinafter described.
37.530	The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., hereinbefore described.
	<hr/> CORRECTIVE DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 15 N., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA
	<hr/> Correction of a Portion of the Dependent Resurvey Executed by Cadastral Surveyor R.A. Pratt in 1976
	<hr/> From the cor. of secs. 2, 3, 10 and 11. S. 89°59'50" W., bet. secs. 3 and 10.
33.20	Spur, slopes S. 30° W.
39.968	Point for the 1/4 sec. cor. of secs. 3 and 10, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

CORRECTIVE DEPENDENT RESURVEY
OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 N., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T15N R65E S 3 1/4 — S10 2014
	From this cor., the 1976 1/4 sec. cor. of secs. 3 and 10, bears N. 89°09'20" E., 2.475 chs. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, in a mound of stone, 4 ft. base, 2 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 15 N., R. 65 E., executed under Group No. 524. This position was erroneously monumented and no longer functions as the 1/4 sec. cor. of secs. 3 and 10. Remove the 1976 markings, add the marks AM to the brass cap, invert and bury in place.
58.499	The witness point at the intersection with a line 15 ft. easterly of and parallel with the apparent centerline of a trail with the line bet. secs. 3 and 10, hereinafter described.
58.759	Trail, 8 lks. wide, bears N. 19°21'10" E., and SW.
79.936	The cor. of secs. 3, 4, 9 and 10, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 15 N., R. 65 E., executed under Group No. 524.
	N. 5°13'30" E., bet. secs. 3 and 4.
16.50	Ravine, with trail road in the bottom, drains S. 70° W.
21.395	Trail, 8 lks. wide, bears N. 74°55'10" E. and SW.
21.638	The witness point at the intersection with a line 15 ft. northerly of and parallel with the apparent centerline of a trail with the line bet. secs. 3 and 4, hereinafter described.
38.784	Point for the 1/4 sec. cor. of secs. 3 and 4, at proportionate distance. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T15N R65E 1/4 S 4 S 3 2014
	From this cor., the 1976 1/4 sec. cor. of secs. 3 and 4, bears S. 37°53'20" W., 0.096 chs. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, in a mound of stone, 3 ft. base,

CORRECTIVE DEPENDENT RESURVEY
OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 N., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>2 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 15 N., R. 65 E., executed under Group No. 524. This position was erroneously monumented and no longer functions as the 1/4 sec. cor. of secs. 3 and 4. Remove the 1976 markings, add the marks AM to the brass cap, invert and bury in place.</p>
58.176	<p>Point for the N 1/16 sec. cor. of secs. 3 and 4, at proportionate distance.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S 4 S 3</p> <p style="text-align: center;">2014</p> <p>From this cor., the 1976 N 1/16 sec. cor. of secs. 3 and 4, bears N. 75°17'20" W., 0.133 chs. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, in a mound of stone, 4 ft. base, 2 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 15 N., R. 65 E., executed under Group No. 524. This position was erroneously monumented and no longer functions as the N 1/16 sec. cor. of secs. 3 and 4. Remove the 1976 markings, add the marks AM to the brass cap, invert and bury in place.</p>
74.562	<p>Intersect the Third Standard Parallel North.</p> <p>The closing cor. of secs. 3 and 4, monumented with an iron post, 2 1/2 ins. diam., firmly set and in a mound of stone, 3 ft. base, 2 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the Third Standard Parallel North through Range 65 East, executed under Group No. 524.</p> <p>From this cor., the standard 1/4 sec. cor. of sec. 33, T. 16 N., R. 65 E., bears N. 89°41'40" E., 18.163 chs. dist., hereinbefore described.</p> <hr/> <p>The point for the N 1/4 sec. cor. of sec. 3, is on the Third Standard Parallel North and at midpoint in departure on the N. bdy. of sec. 3</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>





CORRECTIVE DEPENDENT RESURVEY
OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 N., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>T16N R65E</p> <hr style="width: 10%; margin: auto;"/> <p>1/4 S 3 T15N R65E</p> <p>2013</p> <p>From this point, the standard sec. cor. of secs. 33 and 34, T. 16 N., R. 65 E., bears N. 89°40'50' E., 18.303 chs. dist., hereinbefore described.</p> <hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 7, T. 15 N., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 7 and 18. N. 1°10'10" E., on the N-S center line of sec. 7.</p>
20.266	<p>Point for the C-S 1/16 sec. cor. of sec. 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;"> C S 1/16 S 7 C </p> <p>2014</p>
40.532	<p>Point for the center 1/4 sec. cor. of sec. 7, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15N R65E C 1/4 S 7</p> <p>2014</p>
80.986	<p>The 1/4 sec. cor. of secs. 6 and 7, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 9 ins. above the ground, with brass cap mkd. as described in the field notes of the remonumentation of a corner in T. 15 N., R. 65 E., remonumented under Group No. 393, from which the 1971 bearing trees</p> <p style="padding-left: 40px;">A juniper, 12 ins. diam., bears S. 43° E., 51 lks. dist., mkd. 1/4 S7 BT.</p> <p style="padding-left: 40px;">A juniper, 8 ins. diam., bears N. 18° W., 21 lks. dist., mkd. X BT.</p> <hr/>

SUBDIVISION OF SECTION 7,
T. 15 N., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From the 1/4 sec. cor. of secs. 7 and 8, monumented with an iron post, 2 1/2 ins. diam., firmly set, in a mound of stone, 4 ft. base, 3 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 15 N., R. 65 E., executed under Group No. 524. The 1976 bearing trees were searched for but no evidence of the bearing trees was recovered.</p> <p>N. 89°15'40" W., on the E-W center line of sec. 7.</p>
36.905	The center 1/4 sec. cor. of sec. 7.
76.113	The 1/4 sec. cor. of secs. 7 and 12, on the W. bdy. of the Tp.
	<hr/> <p>From the C-S 1/16 sec. cor. of sec. 7.</p> <p>N. 89°22'20" W., on the E-W center line of the SW1/4 of sec. 7.</p>
19.383	Trail road, 15 lks. wide, bears NE. and S. 3°43'10" W.
19.762	The witness point at the intersection with a line 25 ft. westerly of and parallel with the centerline of a trail road, hereinafter described.
38.370	The S 1/16 sec. cor. of secs. 7 and 12, on the W. bdy. of the Tp.
	<hr/> <p style="text-align: center;">METES-AND-BOUNDS SURVEY IN SECTION 3, T. 15 N., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">MEMORANDUM</p> <p>The following metes-and-bounds survey identifies a line 15 ft. northerly and easterly of and parallel with the apparent centerline of a trail and begins at the intersection with the line between sections 3 and 10, and ends at the intersection with the line between sections 3 and 4.</p> <hr/> <p>From the point for a witness point at the intersection of the first course of this metes-and-bounds survey with the line bet. secs. 3 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>





METES-AND-BOUNDS SURVEY IN SECTION 3,
T. 15 N., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">WP T15N R65E S 3  S10 2014</p> <p>From this point, the 1/4 sec. cor. of secs. 3 and 10, hereinbefore described, bears N. 89°59'50" E., 18.531 chs. dist. N. 19°21'10" E., in sec. 3.</p>
1.283	<p>Point for Angle Point No. 1, sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T15N R65E S 3 } AP1  2014</p> <hr/> <p>N. 22°32'50" W., on line 1-2.</p>
0.829	<p>Point for Angle Point No. 2, sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T15N R65E S 3 } AP2  2014</p> <hr/> <p>N. 50°51'50" W., on line 2-3.</p>
0.763	<p>Point for Angle Point No. 3, sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T15N R65E S 3 } AP3  2014</p> <hr/>





METES-AND-BOUNDS SURVEY IN SECTION 3,
T. 15 N., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 64°50'50" W., on line 3-4.
1.180	Point for Angle Point No. 4, sec. 3.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	<p style="text-align: center;">T15N R65E</p> <p style="text-align: center;">S 3 \ AP4</p> <p style="text-align: center;">2014</p> <hr style="width: 30%; margin: auto;"/>
	N. 84°42'30" W., on line 4-5.
0.691	Point for Angle Point No. 5, sec. 3.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.
	<p style="text-align: center;">T15N R65E</p> <p style="text-align: center;">AP5</p> <p style="text-align: center;">S 3</p> <p style="text-align: center;">2014</p> <hr style="width: 30%; margin: auto;"/>
	N. 69°31'40" W., on line 5-6.
0.500	Point for Angle Point No. 6, sec. 3.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 2 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	<p style="text-align: center;">T15N R65E</p> <p style="text-align: center;">AP6</p> <p style="text-align: center;">S 3</p> <p style="text-align: center;">2014</p> <hr style="width: 30%; margin: auto;"/>
	N. 48°02'20" W., on line 6-7.
1.269	Point for Angle Point No. 7, sec. 3.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

METES-AND-BOUNDS SURVEY IN SECTION 3,
T. 15 N., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T15N R65E  2014</p> <hr/>
1.078	<p>N. 19°25'50" E., on line 7-8.</p> <p>Point for Angle Point No. 8, sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T15N R65E  2014</p> <hr/>
1.446	<p>N. 7°55'50" W., on line 8-9.</p> <p>Point for Angle Point No. 9, sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T15N R65E  2014</p> <hr/>
1.416	<p>N. 38°11'00" W., on line 9-10.</p> <p>Point for Angle Point No. 10, sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T15N R65E  2014</p> <hr/>
3.133	<p>N. 59°45'00" W., on line 10-11.</p> <p>Point for Angle Point No. 11, sec. 3.</p>





METES-AND-BOUNDS SURVEY IN SECTION 3,
T. 15 N., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15N R65E</p> <p style="text-align: center;">S 3  AP11</p> <p style="text-align: center;">2014</p> <hr style="width: 30%; margin: auto;"/>
	<p>N. 4°16'40" W., on line 11-12.</p>
0.929	<p>Point for Angle Point No. 12, sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15N R65E</p> <p style="text-align: center;">S 3  AP12</p> <p style="text-align: center;">2014</p> <hr style="width: 30%; margin: auto;"/>
	<p>N. 51°41'30" E., on line 12-13.</p>
1.151	<p>Point for Angle Point No. 13, sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15N R65E</p> <p style="text-align: center;">S 3  AP13</p> <p style="text-align: center;">2014</p> <hr style="width: 30%; margin: auto;"/>
	<p>N. 13°59'20" E., on line 13-14.</p>
1.145	<p>Point for Angle Point No. 14, sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15N R65E</p> <p style="text-align: center;">S 3  AP14</p> <p style="text-align: center;">2014</p> <hr style="width: 30%; margin: auto;"/>

METES-AND-BOUNDS SURVEY IN SECTION 3,
T. 15 N., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 7°54'40" E., on line 14-15.
0.979	<p>Point for Angle Point No. 15, sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15N R65E S 3 } AP15 2014</p> <hr/>
0.559	<p>N. 31°09'20" W., on line 15-16.</p> <p>Point for Angle Point No. 16, sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15N R65E S 3 \ AP16 2014</p> <hr/>
0.795	<p>N. 53°07'50" W., on line 16-17.</p> <p>Point for Angle Point No. 17, sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15N R65E S 3 \ AP17 2014</p> <hr/>
1.211	<p>N. 76°36'10" W., on line 17-18.</p> <p>Point for Angle Point No. 18, sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

METES-AND-BOUNDS SURVEY IN SECTION 3,
T. 15 N., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T15N R65E</p> <div style="text-align: center;">  </div>
<p>1.816</p>	<p>S. 89°28'10" W., on line 18-19.</p> <p>Point for Angle Point No. 19, sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T15N R65E</p> <div style="text-align: center;">  </div>
<p>1.034</p>	<p>N. 27°18'30" W., on line 19-20.</p> <p>Point for Angle Point No. 20, sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T15N R65E</p> <div style="text-align: center;">  </div>
<p>1.950</p>	<p>N. 12°35'50" W., on line 20-21.</p> <p>Point for Angle Point No. 21, sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T15N R65E</p> <div style="text-align: center;">  </div> <p>N. 17°10'00" E., on line 21-22.</p>




METES-AND-BOUNDS SURVEY IN SECTION 3,
T. 15 N., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
0.560	<p>Point for Angle Point No. 22, sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15N R65E S 3 { AP22 2014</p> <hr/>
	<p>N. 28°52'50" E., on line 22-23.</p>
1.060	<p>Point for Angle Point No. 23, sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15N R65E S 3 } AP23 2014</p> <hr/>
	<p>N. 7°26'10" E., on line 23-24.</p>
0.617	<p>Point for Angle Point No. 24, sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15N R65E S 3 { AP24 2014</p> <hr/>
	<p>N. 16°59'00" E., on line 24-25.</p>
1.051	<p>Point for Angle Point No. 25, sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>





METES-AND-BOUNDS SURVEY IN SECTION 3,
T. 15 N., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T15N R65E</p> <p style="text-align: center;">S 3 } AP25</p> <p style="text-align: center;">2014</p> <hr/>
2.254	<p>N. 45°30'40" W., on line 25-26.</p> <p>Point for Angle Point No. 26, sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T15N R65E</p> <p style="text-align: center;">S 3 } AP26</p> <p style="text-align: center;">2014</p> <hr/>
0.759	<p>N. 27°10'20" W., on line 26-27.</p> <p>Point for Angle Point No. 27, sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T15N R65E</p> <p style="text-align: center;">S 3 } AP27</p> <p style="text-align: center;">2014</p> <hr/>
1.006	<p>S. 82°49'10" W., on line 27-28.</p> <p>Point for Angle Point No. 28, sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T15N R65E</p> <p style="text-align: center;">S 3</p> <p style="text-align: center;">AP28</p> <p style="text-align: center;">2014</p> <hr/>
	<p>S. 35°50'00" W., on line 28-29.</p>


METES-AND-BOUNDS SURVEY IN SECTION 3,
T. 15 N., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
0.326	<p>Point for Angle Point No. 29, sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15N R65E</p> <p style="text-align: center;">S 3 </p> <p style="text-align: center;">2014</p> <hr style="width: 50%; margin: auto;"/>
1.522	<p>S. 63°59'00" W., on line 29-30.</p> <p>Point for Angle Point No. 30, sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15N R65E</p> <p style="text-align: center;">AP30 </p> <p style="text-align: center;">2014</p> <hr style="width: 50%; margin: auto;"/>
1.425	<p>S. 87°27'10" W., on line 30-31.</p> <p>Point for Angle Point No. 31, sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15N R65E</p> <p style="text-align: center;">S 3 </p> <p style="text-align: center;">2014</p> <hr style="width: 50%; margin: auto;"/>
0.809	<p>S. 88°55'50" W., on line 31-32.</p> <p>Point for Angle Point No. 32, sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

METES-AND-BOUNDS SURVEY IN SECTION 3,
T. 15 N., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T15N R65E</p> <p style="text-align: center;">S 3  AP32</p> <p style="text-align: center;">2014</p> <hr/>
0.632	<p>N. 44°35'50" W., on line 32-33.</p> <p>Point for Angle Point No. 33, sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T15N R65E</p> <p style="text-align: center;">S 3  AP33</p> <p style="text-align: center;">2014</p> <hr/>
0.984	<p>N. 72°20'00" W., on line 33-34.</p> <p>Point for Angle Point No. 34, sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T15N R65E</p> <p style="text-align: center;">S 3  AP34</p> <p style="text-align: center;">2014</p> <hr/>
0.992	<p>S. 81°53'40" W., on line 34-35.</p> <p>Point for Angle Point No. 35, sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T15N R65E</p> <p style="text-align: center;">S 3  AP35</p> <p style="text-align: center;">2014</p> <hr/> <p>S. 74°55'10" W., on the last course of this metes-and-bounds survey.</p>




METES-AND-BOUNDS SURVEY IN SECTION 3,
T. 15 N., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
0.805	<p>Point for a witness point at the intersection of the last course of this metes-and-bounds survey with the line bet. secs. 3 and 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">WP T15N R65E</p>  <p style="text-align: center;">2014</p> <p>From this point, the 1/4 sec. cor. of secs. 3 and 4, hereinbefore described, bears N. 5°13'30" E., 17.146 chs. dist.</p> <hr/> <p style="text-align: center;">METES-AND-BOUNDS SURVEY IN SECTIONS 7 AND 18, T. 15 N., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">MEMORANDUM</p> <p>The following metes-and-bounds survey identifies a line 25 ft. westerly of and parallel with the apparent centerline of a trail road and begins at the intersection with the line between sections 13 and 18, on the west boundary of the township, and ends at the intersection with the E-W center line of the SW1/4 of sec. 7.</p> <hr/> <p>From the witness point at the intersection of the first course of this metes-and-bounds survey with the line bet. secs. 13 and 18, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the E. bdy., T. 15 N., R. 64 E., executed concurrently under this same Group.</p> <p>From this point, the 1/4 sec. cor. of secs. 13 and 18, on the W. bdy of the Tp., bears N. 1°12'30" W., 4.725 chs. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 11 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the E. bdy., T. 15 N., R. 64 E., executed under Group No. 454, with a steel fence post set alongside, and a mound of stone 3 ft. base, 1 ft. high, W. of cor.</p> <p>N. 33°58'00" E., in sec. 18.</p>
1.339	Point for Angle Point No. 1, sec. 18.

METES-AND-BOUNDS SURVEY IN SECTIONS 7 AND 18,
T. 15 N., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15N R65E</p> <p style="text-align: center;">AP1 / S18</p> <p style="text-align: center;">2014</p> <hr/>
2.016	<p>N. 26°42'50" E., on line 1-2.</p> <p>Point for Angle Point No. 2, sec. 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15N R65E</p> <p style="text-align: center;">AP2 / S18</p> <p style="text-align: center;">2014</p> <hr/>
1.885	<p>N. 41°36'40" E., on line 2-3.</p> <p>Point for Angle Point No. 3, sec. 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15N R65E</p> <p style="text-align: center;">AP3 / S18</p> <p style="text-align: center;">2014</p> <hr/>
1.926	<p>N. 70°27'30" E., on line 3-4.</p> <p>Point for Angle Point No. 4, sec. 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T15N R65E</p> <p style="text-align: center;">AP4 / S18</p> <p style="text-align: center;">2014</p> <hr/>

METES-AND-BOUNDS SURVEY IN SECTIONS 7 AND 18,
T. 15 N., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 89°03'20" E., on line 4-5.
3.282	Point for Angle Point No. 5, sec. 18.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T15N R65E
	
	2014
	N. 67°10'30" E., on line 5-6.
1.138	Point for Angle Point No. 6, sec. 18.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T15N R65E
	
	2014
	N. 53°05'20" E., on line 6-7.
2.363	Point for Angle Point No. 7, sec. 18.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T15N R65E
	
	2014
	N. 39°59'10" E., on line 7-8.
3.251	Point for Angle Point No. 8, sec. 18.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

METES-AND-BOUNDS SURVEY IN SECTIONS 7 AND 18,
T. 15 N., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T15N R65E</p> <p style="text-align: center;">AP8 / S18</p> <p style="text-align: center;">2014</p> <hr/>
4.421	<p>N. 31°57'00" E., on line 8-9.</p> <p>Point for Angle Point No. 9, sec. 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T15N R65E</p> <p style="text-align: center;">AP9 / S18</p> <p style="text-align: center;">2014</p> <hr/>
2.224	<p>N. 19°16'30" E., on line 9-10.</p> <p>Point for Angle Point No. 10, sec. 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T15N R65E</p> <p style="text-align: center;">AP10 / S18</p> <p style="text-align: center;">2014</p> <hr/>
2.822	<p>N. 10°09'40" E., on line 10-11.</p> <p>Point for Angle Point No. 11, sec. 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T15N R65E</p> <p style="text-align: center;">AP11 } S18</p> <p style="text-align: center;">2014</p> <hr/>
3.619	<p>N. 4°09'10" W., on line 11-12.</p> <p>Point for Angle Point No. 12, sec. 18.</p>


METES-AND-BOUNDS SURVEY IN SECTIONS 7 AND 18,
T. 15 N., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15N R65E AP12 } S18 2014</p> <hr/>
	<p>N. 9°20'00" W., on line 12-13.</p>
2.703	<p>Point for Angle Point No. 13, sec. 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15N R65E AP13 } S18 2014</p> <hr/>
	<p>N. 0°52'50" W., on line 13-14.</p>
4.041	<p>Point for Angle Point No. 14, sec. 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15N R65E AP14 / S18 2014</p> <hr/>
	<p>N. 4°03'30" E., on line 14-15.</p>
3.035	<p>Point for Angle Point No. 15, sec. 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15N R65E AP15 \ S18 2014</p> <hr/>





METES-AND-BOUNDS SURVEY IN SECTIONS 7 AND 18,
T. 15 N., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
<p>1.374</p>	<p>N. 20°10'30" W., on line 15-16.</p> <p>Point for Angle Point No. 16, sec. 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15N R65E AP16 / S18 2014</p> <hr/>
<p>5.225</p>	<p>N. 1°39'00" W., on line 16-17.</p> <p>Point for Angle Point No. 17, sec. 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15N R65E AP17 / S18 2014</p> <hr/>
<p>2.365</p>	<p>N. 8°39'50" E., on line 17-18.</p> <p>Point for Angle Point No. 18, sec. 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15N R65E AP18 } S18 2014</p> <hr/>
<p>1.695</p>	<p>N. 1°27'10" W., on line 18-19.</p> <p>Point for Angle Point No. 19, sec. 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

METES-AND-BOUNDS SURVEY IN SECTIONS 7 AND 18,
T. 15 N., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T15N R65E AP19 \ S18 2014</p> <hr style="width: 50%; margin: auto;"/>
1.234	<p>N. 19°38'30" W., on line 19-20.</p> <p>Point for Angle Point No. 20, sec. 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T15N R65E AP20 / S18 2014</p> <hr style="width: 50%; margin: auto;"/>
2.213	<p>N. 9°15'10" E., on the last course in sec. 18</p> <p>Point for a witness point at the intersection with the line bet. secs. 7 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">WP T15N R65E</p> <div style="text-align: center;">  </div> <p style="text-align: center;">2014</p> <p>From this point, the cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., hereinbefore described, bears N. 89°29'30" W., 16.639 chs. dist.</p> <hr style="width: 80%; margin: auto;"/>
2.789	<p>N. 6°01'10" E., in sec. 7.</p> <p>Point for Angle Point No. 1, sec. 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

METES-AND-BOUNDS SURVEY IN SECTIONS 7 AND 18,
T. 15 N., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T15N R65E</p> <p style="text-align: center;">AP1  S 7</p> <p style="text-align: center;">2014</p> <hr/>
1.916	<p>N. 17°52'50" E., on line 1-2.</p> <p>Point for Angle Point No. 2, sec. 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T15N R65E</p> <p style="text-align: center;">AP2  S 7</p> <p style="text-align: center;">2014</p> <hr/>
1.733	<p>N. 25°23'50" E., on line 2-3.</p> <p>Point for Angle Point No. 3, sec. 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T15N R65E</p> <p style="text-align: center;">AP3  S 7</p> <p style="text-align: center;">2014</p> <hr/>
1.776	<p>N. 19°46'10" E., on line 3-4.</p> <p>Point for Angle Point No. 4, sec. 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T15N R65E</p> <p style="text-align: center;">AP4  S 7</p> <p style="text-align: center;">2014</p> <hr/>
1.466	<p>N. 2°53'40" E., on line 4-5.</p> <p>Point for Angle Point No. 5, sec. 7.</p>

METES-AND-BOUNDS SURVEY IN SECTIONS 7 AND 18,
T. 15 N., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15N R65E AP5 } S 7 2014</p> <hr/>
	<p>N. 7°52'20" W., on line 5-6.</p>
4.463	<p>Point for Angle Point No. 6, sec. 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15N R65E AP6 } S 7 2014</p> <hr/>
	<p>N. 0°47'00" W., on line 6-7.</p>
3.554	<p>Point for Angle Point No. 7, sec. 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15N R65E AP7 } S 7 2014</p> <hr/>
	<p>N. 9°48'50" W., on line 7-8.</p>
1.249	<p>Point for Angle Point No. 8, sec. 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15N R65E AP8 } S 7 2014</p> <hr/>

METES-AND-BOUNDS SURVEY IN SECTIONS 7 AND 18,
T. 15 N., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p> <p>1.792</p>	<p>N. 3°43'10" E., on the last course of this metes-and-bounds survey.</p> <p>Point for a witness point, at the intersection of the last course of this metes-and-bounds survey with the E-W centerline of the SW1/4 of sec. 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>WP</p> <p>T15N R65E</p> <p>S</p> <p>S ——— S</p> <p> </p> <p> 7</p> <p>2014</p> </div> <p>From this point, the S 1/16 sec. cor. of secs. 7 and 12, on the W. bdy. of the Tp., hereinbefore described, bears N. 89°22'20" W., 18.608 chs. dist.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The land encompassed in this survey ranges from approximately 7000 ft. above sea level in the west to 9000 ft. above sea level in the east. The terrain is generally very mountainous, and is in the vicinity of Cave Lake State Park. The vegetation is primarily juniper in the lower elevations with mountain mahogany and fir in the upper elevations. Access to the area is by way of Nevada State Route 486 and numerous forest roads.</p> <hr/>
----------------------------	---

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS


Bradley F. Dillon	Cadastral Surveyor
Josephina M. Campbell	Surveying Technician
Anthony W. Swope	Surveying Technician
Tallon A. Ricci	Survey Aid
Matthew J. White	Field Assistant
Christopher S. Bourgoine	Field Assistant

CERTIFICATE OF SURVEY

I, Joseph J. Johnson, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 18th day of July, 2013, supplemental special instructions bearing date of the 21st day of May, 2014, supplemental special instructions bearing date of the 17th day of November, 2014 and supplemental special instructions bearing date of the 10th day of December, 2014, I have dependently resurveyed the Third Standard Parallel North through a portion of Range 65 East, a portion of the west boundary and a portion of the subdivisional lines, and correctively dependently resurveyed a portion of the subdivisional lines, and subdivided section 7 and executed metes-and-bounds surveys in sections 3, 7 and 18, Township 15 North, Range 65 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

DEC 17 2014

(Date)



(Cadastral Surveyor)


CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of the dependent resurvey of the Third Standard Parallel North through a portion of Range 65 East, a portion of the west boundary and a portion of the subdivisional lines, and the corrective dependent resurvey of a portion of the subdivisional lines, the subdivision of section 7 and metes-and-bounds surveys in sections 3, 7 and 18, Township 15 North, Range 65 East, Mount Diablo Meridian, Nevada, executed by Joseph J. Johnson, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

DEC 17 2014

(Date)



(Chief Cadastral Surveyor for Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 15 N., R. 65 E. Mount Diablo Meridian, Nevada, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor for Nevada)~~