

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF THE

SURVEY OF THE

SOUTH AND WEST BOUNDARIES AND
A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 15 SOUTH, RANGE 47 EAST,
OF THE MOUNT DIABLO MERIDIAN,
IN THE STATE OF NEVADA

EXECUTED BY

Lee T. Wilson, Cadastral Surveyor

Under Special Instructions dated January 4, 2022,
and approved January 4, 2022,
which provided for the surveys included under Group No. 999,
and Assignment Instructions dated January 5, 2022.

Survey commenced January 19, 2022

Survey completed January 25, 2022

INDEX DIAGRAM

TOWNSHIP 15 SOUTH, RANGE 47 EAST, MOUNT DIABLO MERIDIAN, NEVADA

7	6	20	5	17	4	15	3	13	2	11	1
	20		20		17		15		13		11
7	7	19	8	17	9	14	10	12	11	10	12
	19		18		16		14		12		9
8	18		17		16		15		14		13
8	19		20		21		22		23		24
			29		28		27		26		25
					33		34		35		36
					6		5		4		2

Nevada
California

TOWNSHIP 15 SOUTH, RANGE 47 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The following field notes are those of the survey of the south and west boundaries and a portion of the subdivisional lines, Township 15 South, Range 47 East, Mount Diablo Meridian, Nevada.

1873 - The Eastern Boundary of the State of California, (former California-Nevada State Boundary line) was surveyed by U.S. Astronomer and Surveyor A.W. Von Schmidt, under contract dated July 20, 1872.

1893-1899 - The Oblique Boundary line between California and Nevada (present California-Nevada State Boundary line) was surveyed by the U.S. Coast and Geodetic Survey.

1906 - A portion of the California-Nevada State boundary line was retraced, the south boundary of Township 14 South, Range 47 East and the south and west boundaries of Township 14 South, Range 48 East were surveyed by M.D. Heist, U.S. Deputy Surveyor, under Contract Number 252. The surveys of the south boundary of Township 14 South, Range 47 East and the south and west boundaries of Township 14 South, Range 48 East were superseded by the 1957 Independent Resurvey by H.G. Parker, Cadastral Surveyor, under Group Number 368.

1957 - The north boundary was independently resurveyed and the east boundary surveyed by H.G. Parker, Cadastral Surveyor, under Group Number 368.

1962 - Nevada Protraction Diagram Number 43, Unit Number 105, was approved May 31, 1962.

Numerous original corner monuments set during the 1906 survey of the boundaries of Township 14 and 15 South, Ranges 47 and 48 East were recovered during the course of this survey. Bearing and distance ties are given from the corner of Townships 15 and 16 South, Ranges 47 and 48 East, to those corners physically located within the boundaries of sections 1 thru 12, Township 15 South, Range 47 East.

In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 2009, and the Special Instructions for Group Number 999, dated January 4, 2022.

Measurements were made with Trimble R-8 and R-10 Global Navigation Satellite System (GNSS) receivers using the real-time kinematic (RTK) method and refer to the true meridian based on geodetic methods. The mean bearings of the lines and horizontal equivalents of ground distances only are entered in the field notes.

Meridional subdivisional lines were run parallel to the East boundary of the Township, determined by mathematical inverse between the corner of Township 15 and 16 South, Ranges 47 and 48 East and the corner of Townships 14 and 15 South, Ranges 47 and 48 East, excluding the north tier of sections which were connected to the objective section corners on the north boundary of the Townships.

TOWNSHIP 15 SOUTH, RANGE 47 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The NAD 83(2011)(EPOCH:2010.0000) geographic position of the following corners was determined from the Cadastral Project Control Network, tied to the National Spatial Reference System (NSRS) using Global Positioning System (GPS) static observations processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) DN7518 P094 LASTCHANCECS2006 CORS ARP, DN5639 P093 HAYSTACKHICS2007 CORS ARP, and DK6411 P467 ALABAMAHILCS2006 CORS ARP, and carried forward by RTK observations.

The corner of Townships 15 and 16 South, Ranges 47 and 48 East, is as follows:

Latitude: 36°35'51.986" N. Longitude: 116°36'52.749" W.

The corner of Townships 14 and 15 South, Ranges 46 and 47 East, is as follows:

Latitude: 36°41'05.207" N. Longitude: 116°43'21.846" W.

SURVEY OF THE SOUTH BOUNDARY,
T. 15 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

Beginning at the cor. of Tps. 15 and 16 S., Rs. 47 and 48 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd.

T15S	
R47E	R48E
S36	S31

S 1	S 6
T16S	

1957

From this corner, the 1906 cor. of secs. 25, 30, 31, and 36, T. 14 S., Rs. 47 and 48 E., bears N. 25°17'40" W., 515.387 chs. dist., monumented with a basalt stone, 15x9x6 ins. (Record, 12x9x5), firmly set, mkd. with 5 notches on the north edge and 1 notch on the south edge, with a mound of stone, 2 1/2 ft. diam., 1/2 ft. high, W. of the cor. Monument marked AM, buried in place, and all other evidence of the corner destroyed.

From this same corner, the 1906 1/4 sec. cor. of secs. 31 and 36, T. 14 S., Rs. 47 and 48 E., bears N. 27°20'40" W., 479.390 chs. dist., monumented with a basalt stone, 14x7x6 ins. (Record, 18x10x5), firmly set, mkd. 1/4 on the W. face. Monument marked AM, buried in place, and all other evidence of the corner destroyed.

SURVEY OF THE SOUTH BOUNDARY,
T. 15 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

From this same corner, the 1906 cor. of Tps. 14 and 15 S., Rs. 47 and 48 E., bears N. 29°43'20" W., 444.142 chs. dist., monumented with a lava stone, 20x8x6 ins. (Record, 20x8x4), firmly set, mkd. 15S on the S. face, 6 notches on the SE. edge, and other illegible markings. Monument marked AM, buried in place, and all other evidence of the corner destroyed.

From this same corner, the 1906 1/4 sec. cor. of secs. 1 and 36, Tps. 14 and 15 S., R. 47 E., bears N. 34°01'30" W., 465.373 chs. dist., monumented with a lava stone, 9x7x6 ins. (Record, 14x8x5), firmly set, mkd. 1/4 on the N. face. Monument marked AM, buried in place, and all other evidence of the corner destroyed.

From this same corner, the 1906 cor. of secs. 1, 2, 35, and 36, Tps. 14 and 15 S., R. 47 E., bears N. 37°55'50" W., 488.999 chs. dist., monumented with a lava stone, 8x6x6 ins. (Record, 15x7x5), firmly set, mkd. with 1 notch on the E. edge and 5 notches on the W. edge. Monument marked AM, buried in place, and all other evidence of the corner destroyed.

From this same corner, the 1906 1/4 sec. cor. of secs. 2 and 35, Tps. 14 and 15 S., R. 47 E., bears N. 41°27'40" W., 514.659 chs. dist., monumented with a lava stone, 11x7x6 ins. (Record, 14x8x5), firmly set, mkd. 1/4 on the N. face. Monument marked AM, buried in place, and all other evidence of the corner destroyed.

From this same corner, the 1906 cor. of secs. 2, 3, 34, and 35, Tps. 14 and 15 S., R. 47 E., bears N. 44°38'50" W., 542.101 chs. dist., monumented with a pine post, 3x3x24 ins. (Record, 4x4x36), firmly set, no mks. visible, with a lava stone, 6x6x4 ins., mkd. with 4 notches on an edge, no other marks visible, lying loose alongside. Monuments marked AM, buried in place, and all other evidence of the corner destroyed.

From this same corner, the 1906 1/4 sec. cor. of secs. 3 and 34, Tps. 14 and 15 S., R. 47 E., bears N. 47°31'10" W., 571.029 chs. dist., monumented with a basalt stone, 12x6x3 ins. (Record, 18x15x3), firmly set, mkd. 1/4 on the N. face. Monument marked AM, buried in place, and all other evidence of the corner destroyed.

From this same corner, the 1906 cor. of secs. 3, 4, 33, and 34, Tps. 14 and 15 S., R. 47 E., bears N. 50°06'20" W., 601.267 chs. dist., monumented with a basalt stone, 14x11x7 ins. (Record, 15x9x5), firmly set, mkd. with 3 notches on the E. edge and 3 notches on the W. edge, with a mound of stone, 2 ft. diam., 1/2 ft. high, W. of the cor. Monument marked AM, buried in place, and all other evidence of the corner destroyed.

From this same corner, the 1906 1/4 sec. cor. of secs. 6 and 31, Tps. 14 and 15 S., R. 48 E., bears N. 25°09'00" W., 426.178 chs. dist., monumented with a basalt stone, 10x9x5 ins. (Record, 12x8x6), firmly set, mkd. 1/4 on the N. face, with a weathered mound of earth N. of the cor. Monument marked AM, buried in place, and all other evidence of the corner destroyed.

SURVEY OF THE SOUTH BOUNDARY,
T. 15 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From this same corner, the 1906 cor. of secs. 5, 6, 31, and 32, Tps. 14 and 15 S., R. 48 E., bears N. 20°04'10" W., 410.798 chs. dist., monumented with a basalt stone, 15x9x9 ins. (Record, 15x10x9), firmly set, mkd. with 5 notches on the E. edge and 1 notch on the W. edge. Monument marked AM, buried in place, and all other evidence of the corner destroyed.</p> <p>From this same corner, the 1906 1/4 sec. cor. of secs. 5 and 32, Tps. 14 and 15 S., R. 48 E., bears N. 14°38'50" W., 398.876 chs. dist., monumented with a basalt stone, 12x9x7 ins. (Record, 12x9x6), firmly set, mkd. 1/4 on the N. face, with a mound of stone, 2 1/2 ft. diam., 1/2 ft. high, N. of the cor. Monument marked AM, buried in place, and all other evidence of the corner destroyed.</p> <p>From this same corner, the 1906 cor. of secs. 4, 5, 32, and 33, Tps. 14 and 15 S., R. 48 E., bears N. 8°56'40" W., 390.734 chs. dist., monumented with a basalt stone, 13x8x7 ins. (Record, 12x8x6), firmly set, mkd. with 4 notches on the E. edge and 2 notches on the W. edge, with a mound of stone, 2 1/2 ft. diam., 1 ft. high, W. of the cor. Monument marked AM, buried in place, and all other evidence of the corner destroyed.</p> <p>WEST bet. secs. 1 and 36.</p>						
40.000	<p>Point for the 1/4 sec. cor. of secs. 1 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center; margin-top: 20px;"> <p>T15S R47E</p> <p>S36</p> <p>1/4 ———</p> <p>S 1</p> <p>T16S</p> <p>2022</p> </div>						
80.000	<p>Point for the cor. of secs. 1, 2, 35, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to bedrock, over a plastic-encased magnet, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin-top: 20px;"> <p>T15S R47E</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S35</td> <td style="padding: 0 5px;">S36</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 2</td> <td style="padding: 0 5px;">S 1</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 5px;">T16S</td> </tr> </table> <p>2022</p> </div>	S35	S36	S 2	S 1	T16S	
S35	S36						
S 2	S 1						
T16S							
40.000	<p>WEST bet. secs. 2 and 35.</p> <p>Point for the 1/4 sec. cor. of secs. 2 and 35.</p>						

SURVEY OF THE SOUTH BOUNDARY,
T. 15 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p>	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, to bedrock, over a plastic-encased magnet, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T15S R47E S35 1/4 ——— S 2 T16S</p> <p style="text-align: center;">2022</p>
<p>80.000</p>	<p>Point for the cor. of secs. 2, 3, 34, and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15S R47E S34 S35 ——— ——— S 3 S 2 T16S</p> <p style="text-align: center;">2022</p>
<p></p>	<p>WEST bet. secs. 3 and 34.</p>
<p>17.5</p>	<p>Desert two track road, 10 lks. wide, bears SSE. and NNW.</p>
<p>49.0</p>	<p>Desert two track road, 10 lks. wide, bears N. and S.</p>
<p>53.0</p>	<p>Desert two track road, 10 lks. wide, bears SSE. and NNW.</p>
<p>40.000</p>	<p>Point for the 1/4 sec. cor. of secs. 3 and 34.</p>
<p>80.000</p>	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T15S R47E S34 1/4 ——— S 3 T16S</p> <p style="text-align: center;">2022</p> <p>Point for the cor. of secs. 3, 4, 33, and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p>

SURVEY OF THE SOUTH BOUNDARY,
T. 15 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="text-align: center;">T15S R47E</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;">S33</td> <td style="text-align: center;">S34</td> </tr> <tr> <td style="border-top: 1px solid black; text-align: center;">S 4</td> <td style="border-left: 1px solid black; border-right: 1px solid black; border-top: 1px solid black; padding: 0 5px;">S 3</td> <td style="border-top: 1px solid black; text-align: center;">T16S</td> </tr> <tr> <td colspan="3" style="text-align: center; padding-top: 10px;">2022</td> </tr> </table>	T15S R47E	S33	S34	S 4	S 3	T16S	2022		
T15S R47E	S33	S34								
S 4	S 3	T16S								
2022										
8.879	<p>WEST bet. secs. 4 and 33.</p> <p>Intersect the U.S. Coast and Geodetic Survey California-Nevada Oblique Boundary Line.</p> <p>Point for the cor. of secs. 4 and 33, Tps. 15 and 16 S., R. 47 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> </div> <p style="text-align: center;">2022</p> <p>From this point, Monument No. 98 on the U.S. Coast and Geodetic Survey California-Nevada Oblique Boundary Line bears S. 46°47'20" E., 95.773 chs. dist., monumented with a drill hole, 1/2 in. diam., 1/4 in. deep, in the face of a boulder, projecting 30x24x14 ins. above the ground, with a pine post, 3 ins. square, 4 ft. long, firmly set on top, mkd. with nails, N on the NE. face, C on the SW. face, and 98 on the NW. face, in a mound of stone, 6 ft. diam., 2 1/2 ft. high, with a steel fence post set alongside.</p> <p>From this same point, Monument No. 97 on the U.S. Coast and Geodetic Survey California-Nevada Oblique Boundary Line bears N. 46°48'00" W., 106.574 chs. dist., monumented with a brass disk, firmly set in a concrete base, projecting 12x12x4 ins. above the ground, in the center of a mound of earth, 7 ft. diam., 1 1/2 ft. high, mkd. U.S. COAST & GEODETIC SURVEY TRIANGULATION STATION FOR INFORMATION WRITE TO THE DIRECTOR WASHINGTON D.C. \$250 FINE OR IMPRISONMENT FOR DISTURBING THIS MARK NO 97 1899 1949 and a triangle, with a pine post, 3 1/2 ins. square, 48 ins. long, mkd. with nails, 97 on a face, C on another face, and other illegible markings, lying loose alongside, and with a steel fence post set alongside.</p>									

SURVEY OF THE WEST BOUNDARY,
T. 15 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From the cor. of Tps. 14 and 15 S., Rs. 46 and 47 E., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the independent resurvey of the S. bdy., T. 14 S., R. 47 E., executed under Group No. 368, with a mound of stone, 3 ft. diam., 1 1/2 ft. high, E. of the cor.</p> <p>From this corner, an iron pipe, 1 in. diam., firmly set, projecting 12 ins. above the ground, no record found, bears N. 3°23'30" E., 0.7 lks. dist.</p> <p>SOUTH, bet. secs. 1 and 6.</p>
40.000	<p>Point for the 1/4 sec. cor. of secs. 1 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15S R46E R47E 1/4 S 1 S 6</p> <p style="text-align: center;">2022</p>
80.000	<p>Point for the cor. of secs. 1, 6, 7, and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15S R46E R47E S 1 S 6 ----- S12 S 7</p> <p style="text-align: center;">2022</p>
	<p>SOUTH, bet. secs. 7 and 12.</p>
40.000	<p>Point for the 1/4 sec. cor. of secs. 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to bedrock, over a plastic-encased magnet, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T15S R46E R47E 1/4 S12 S 7</p> <p style="text-align: center;">2022</p>

SURVEY OF THE WEST BOUNDARY,
T. 15 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS 80.000	<p>Point for the cor. of secs. 7, 12, 13, and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to bedrock, over a plastic-encased magnet, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T15S</td></tr> <tr><td>R46E</td><td>R47E</td></tr> <tr><td>S12</td><td>S 7</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S13</td><td>S18</td></tr> </table> <p>2022</p> </div>	T15S		R46E	R47E	S12	S 7	<hr/>		S13	S18
T15S											
R46E	R47E										
S12	S 7										
<hr/>											
S13	S18										
40.000	<p>SOUTH, bet. secs. 13 and 18.</p> <p>Point for the 1/4 sec. cor. of secs. 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to bedrock, over a plastic-encased magnet, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T15S</td></tr> <tr><td>R46E</td><td>R47E</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>S13</td><td>S18</td></tr> </table> <p>2022</p> </div>	T15S		R46E	R47E	1/4		S13	S18		
T15S											
R46E	R47E										
1/4											
S13	S18										
80.000	<p>Point for the cor. of secs. 13, 18, 19, and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T15S</td></tr> <tr><td>R46E</td><td>R47E</td></tr> <tr><td>S13</td><td>S18</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S24</td><td>S19</td></tr> </table> <p>2022</p> </div>	T15S		R46E	R47E	S13	S18	<hr/>		S24	S19
T15S											
R46E	R47E										
S13	S18										
<hr/>											
S24	S19										
21.908	<p>SOUTH, bet. secs. 19 and 24.</p> <p>Intersect the U.S. Coast and Geodetic Survey California-Nevada Oblique Boundary Line.</p> <p>Point for the cor. of secs. 19 and 24, T. 15 S., Rs. 46 and 47 E.</p>										

SURVEY OF THE WEST BOUNDARY,
T. 15 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T15S R46E R47E S24 S19 2022</p> </div> <p>From this point, Monument No. 97 on the U.S. Coast and Geodetic Survey California-Nevada Oblique Boundary Line, hereinbefore described, bears S. 46°43'40" E., 211.754 chs. dist.</p> <p>From this same point, Monument No. 96 on the U.S. Coast and Geodetic Survey California-Nevada Oblique Boundary Line, bears N. 46°45'10" W., 281.066 chs. dist., monumented with a brass disk, firmly set in a concrete base, projecting 12x12x7 ins. above the ground, mkd. U.S. COAST & GEODETIC SURVEY TRIANGULATION STATION FOR INFORMATION WRITE TO THE DIRECTOR WASHINGTON D.C. \$250 FINE OR IMPRISONMENT FOR DISTURBING THIS MARK NO 96 1899 1949 and a triangle, with a wood post, 3 1/2 ins. square, 50 ins. long, mkd. with nails, 96 on a face, C on another face, and N on another face, lying loose alongside, and with a steel fence post set alongside.</p> <hr/> <p style="text-align: center;">SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 15 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of the W. bdy., T. 15 S., R. 48 E., executed under Group No. 368.</p> <p>From this corner, an iron pipe, 1 in. diam., firmly set, projecting 3 ins. above the ground, no record found, bears S. 87°38'50" E., 1.6 lks. dist.</p> <p>S. 89°58'40" W., bet. secs. 12 and 13.</p>
3.0	Bladed desert road, 25 lks. wide, bears SSE. and NNW.
39.991	Point for the 1/4 sec. cor. of secs. 12 and 13.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T15S R47E S12 1/4 ——— S13 2022</p>
57.0	Deconstructed Tonopah and Tidewater Railroad grade, bears SSE. and NNW.
79.982	<p>Point for the cor. of secs. 11, 12, 13, and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15S R47E S11 S12 ——— ——— S14 S13 2022</p> <p>From this point, the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp., hereinbefore described, bears S. 0°02'00" E., 320.000 chs. dist.</p> <hr/> <p>N. 0°02'00" W., bet. secs. 11 and 12.</p>
40.000	<p>Point for the 1/4 sec. cor. of secs. 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15S R47E 1/4 S11 S12 2022</p>
80.000	<p>Cor. is located on deconstructed Tonopah and Tidewater Railroad grade, bears SSE. and NNW.</p> <p>Point for the cor. of secs. 1, 2, 11, and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T15S R47E S 2 S 1 <hr style="width: 50%; margin: auto;"/> S11 S12 2022
	<p>From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 9 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of the W. bdy., T. 15 S., R. 48 E., executed under Group No. 368.</p> <p>From this corner, an iron pipe, 1 in. diam., firmly set, projecting 4 ins. above the ground, no record found, bears S. 88°59'50" E., 1.4 lks. dist.</p> <p>S. 89°58'30" W., bet. secs. 1 and 12.</p>
23.5	Bladed desert road, 25 lks. wide, bears. N. and S.
39.992	Point for the 1/4 sec. cor. of secs. 1 and 12. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T15S R47E S 1 1/4 ——— S12 2022
79.984	The cor. of secs. 1, 2, 11, and 12.
	N. 0°02'30" W., bet. secs. 1 and 2.
40.024	Point for the 1/4 sec. cor. of secs. 1 and 2. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T15S R47E 1/4 S 2 S 1 2022
63.5	Cross braided desert road, 4 chs. wide, bears NE. and SW.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 80.048</p>	<p>The cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the independent resurvey of the S. bdy., T. 14 S., R. 47 E., executed under Group No. 368, with a mound of stone, 2 ft. diam., 1 1/2 ft. high, W. of the cor.</p> <p>From this corner, an iron pipe, 1 in. diam., firmly set, projecting 4 ins. above the ground, no record found, bears S. 5°44'00" W., 1.1 lks. dist.</p>
	<p>From the cor. of secs. 11, 12, 13, and 14.</p> <p>WEST, bet. secs. 11 and 14.</p>
<p>40.000</p>	<p>Point for the 1/4 sec. cor. of secs. 11 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T15S R47E S11 1/4 ——— S14 2022</p> </div>
<p>80.000</p>	<p>Point for the cor. of secs. 10, 11, 14, and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T15S R47E S10 S11 ——— ——— S15 S14 2022</p> </div> <p>From this point, the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., hereinbefore described, bears S. 0°02'30" E., 320.000 chs. dist.</p>
<p>40.000</p>	<p>N. 0°02'30" W., bet. secs. 10 and 11.</p> <p>Point for the 1/4 sec. cor. of secs. 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">T15S R47E 1/4 S10 S11</p> <p style="text-align: center;">2022</p>
80.000	<p>Point for the cor. of secs. 2, 3, 10, and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15S R47E S 3 S 2 ----- S10 S11</p> <p style="text-align: center;">2022</p> <p>From this point, an iron pipe, 1 in. diam., firmly set, projecting 2 ins. above the ground, no record found, bears S. 58°00'00" W., 13.4 lks. dist.</p> <hr/> <p>From the cor. of secs. 1, 2, 11, and 12.</p> <p>WEST, bet. secs. 2 and 11.</p>
23.0	<p>Deconstructed Tonopah and Tidewater Railroad grade, bears SSE. and NNW.</p>
40.000	<p>Point for the 1/4 sec. cor. of secs. 2 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15S R47E S 2 1/4 ----- S11</p> <p style="text-align: center;">2022</p>
80.000	<p>The cor. of secs. 2, 3, 10, and 11.</p> <hr/> <p>N. 0°04'10" W., bet. secs. 2 and 3.</p>
40.018	<p>Point for the 1/4 sec. cor. of secs. 2 and 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T15S R47E 1/4 S 3 S 2</p> <p style="text-align: center;">2022</p>
80.036	<p>The cor. of secs. 2, 3, 34, and 35, on the N. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the independent resurvey of the S. bdy., T. 14 S., R. 47 E., executed under Group No. 368, with a mound of stone, 2 ft. diam., 1 1/2 ft. high, W. of the cor.</p> <p>From this corner, an iron pipe, 1 in. diam., firmly set, projecting 3 ins. above the ground, no record found, bears N. 2°08'00" E., 1.5 lks. dist.</p> <hr/> <p>From the cor. of secs. 10, 11, 14, and 15.</p> <p>WEST, bet. secs. 10 and 15.</p>
40.000	<p>Point for the 1/4 sec. cor. of secs. 10 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T15S R47E S10 1/4 ——— S15</p> <p style="text-align: center;">2022</p>
80.000	<p>Point for the cor. of secs. 9, 10, 15, and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T15S R47E S 9 S10 ————— ————— S16 S15</p> <p style="text-align: center;">2022</p>
40.000	<p>From this point, the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., hereinbefore described, bears S. 0°03'10" E., 320.000 chs. dist.</p> <hr/> <p>N. 0°03'10" W., bet. secs. 9 and 10.</p> <p>Point for the 1/4 sec. cor. of secs. 9 and 10.</p>

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15S R47E 1/4 S 9 S10</p> <p style="text-align: center;">2022</p>
80.000	<p>Point for the cor. of secs. 3, 4, 9, and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15S R47E S 4 S 3 ----- S 9 S10</p> <p style="text-align: center;">2022</p> <p>From this point, an iron pipe, 1 in. diam., firmly set, projecting 5 ins. above the ground, no record found, bears S. 89°15'10" W., 21.1 lks. dist.</p>
	<p>From the cor. of secs. 2, 3, 10, and 11.</p> <p>WEST, bet. secs. 3 and 10.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15S R47E S 3 1/4 ----- S10</p> <p style="text-align: center;">2022</p>
80.000	<p>The cor. of secs. 3, 4, 9, and 10.</p>
40.017	<p>N. 0°05'20" W., bet. secs. 3 and 4.</p> <p>Point for the 1/4 sec. cor. of secs. 3 and 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">T15S R47E 1/4 S 4 S 3</p> <p style="text-align: center;">2022</p>
80.034	<p>The cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd. as described in the field notes of the independent resurvey of the S. bdy., T. 14 S., R. 47 E., executed under Group No. 368, with a mound of stone, 2 1/2 ft. diam., 1 1/2 ft. high, W. of the cor.</p> <p>From this corner, an iron pipe, 1 in. diam., firmly set, projecting 8 ins. above the ground, no record found, bears N. 75°41'10" W., 1.0 lk. dist.</p> <hr/> <p>From the cor. of secs. 9, 10, 15, and 16.</p> <p>WEST, bet. secs. 9 and 16.</p>
40.000	<p>Point for the 1/4 sec. cor. of secs. 9 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
80.000	<p style="text-align: center;">T15S R47E S 9 1/4 ——— S16</p> <p style="text-align: center;">2022</p> <p>Point for the cor. of secs. 8, 9, 16, and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15S R47E S 8 S 9 ——— ——— S17 S16</p> <p style="text-align: center;">2022</p> <p>From this point, the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., hereinbefore described, bears SOUTH, 320.000 chs. dist. in latitude and EAST, 80.330 chs. dist. in departure.</p> <hr/>

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	N. 0°03'50" W., bet. secs. 8 and 9.
40.000	Point for the 1/4 sec. cor. of secs. 8 and 9. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;">T15S R47E 1/4 S 8 S 9 2022</div>
80.000	Point for the cor. of secs. 4, 5, 8, and 9. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;">T15S R47E S 5 S 4 ----- S 8 S 9 2022</div> <p>From this point, an iron pipe, 1 in. diam., firmly set, projecting 8 ins. above the ground, no record found, bears S. 75°52'40" W., 15.5 lks. dist.</p> <hr/> <p>From the cor. of secs. 3, 4, 9, and 10. WEST, bet. secs. 4 and 9.</p>
40.000	Point for the 1/4 sec. cor. of secs. 4 and 9. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;">T15S R47E S 4 1/4 ----- S 9 2022</div>
80.000	The cor. of secs. 4, 5, 8, and 9.
40.014	N. 0°06'30" W., bet. secs. 4 and 5. Point for the 1/4 sec. cor. of secs. 4 and 5.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15S R47E 1/4 S 5 S 4</p> <p style="text-align: center;">2022</p>
80.028	<p>The cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 9 ins. above the ground, with brass cap mkd. as described in the field notes of the independent resurvey of the S. bdy., T. 14 S., R. 47 E., executed under Group No. 368, with a mound of stone, 2 ft. diam., 1 ft. high, W. of the cor.</p> <p>From this corner, an iron pipe, 1 in. diam., firmly set, projecting 5 ins. above the ground, no record found, bears S. 84°54'10" W., 1.4 lks. dist.</p> <hr/> <p>From the cor. of secs. 8, 9, 16, and 17.</p> <p>WEST, bet. secs. 8 and 17.</p>
40.000	<p>Point for the 1/4 sec. cor. of secs. 8 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15S R47E S 8 1/4 ——— S17</p> <p style="text-align: center;">2022</p>
77.5	<p>Cross braided desert road, 1.2 chs. wide, bears NNE. and SSW.</p>
80.000	<p>Point for the cor. of secs. 7, 8, 17, and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15S R47E S 7 S 8 ——— ——— S18 S17</p> <p style="text-align: center;">2022</p>

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From this point, the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., hereinbefore described, bears SOUTH, 320.000 chs. dist. in latitude and EAST, 160.360 chs. dist. in departure.</p> <hr/> <p>N. 89°59'30" W., bet. secs. 7 and 18.</p>
13.0	Cross braided desert road, 1.5 chs. wide, bears SSE. and NNW.
40.000	<p>Point for the 1/4 sec. cor. of secs. 7 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T15S R47E S 7 1/4 ——— S18 2022</p> </div>
80.325	<p>The cor. of secs. 7, 12, 13, and 18 on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 7, 8, 17, and 18.</p> <p>N. 0°04'30" W., bet. secs. 7 and 8.</p>
40.000	<p>Point for the 1/4 sec. cor. of secs. 7 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T15S R47E 1/4 S 7 S 8 2022</p> </div>
80.000	<p>Point for the cor. of secs. 5, 6, 7, and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T15S R47E S 6 S 5 ————— S 7 S 8 2022</p> </div>

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From this point, an iron pipe, 1 1/4 ins. diam., firmly set, projecting 3 ins. above the ground, no record found, bears N. 77°14'00" W., 17.5 lks. dist.</p>
	<p>From the cor. of secs. 4, 5, 8, and 9. WEST, bet. secs. 5 and 8.</p>
40.000	<p>Point for the 1/4 sec. cor. of secs. 5 and 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T15S R47E S 5 1/4 ——— S 8 2022</p>
49.0	<p>Cross braided desert road, 2 chs. wide, bears NNE. and SSW.</p>
80.000	<p>The cor. of secs. 5, 6, 7, and 8.</p>
	<p>N. 89°59'30" W., bet. secs. 6 and 7.</p>
40.000	<p>Point for the 1/4 sec. cor. of secs. 6 and 7. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T15S R47E S 6 1/4 ——— S 7 2022</p>
40.5	<p>Desert two track road, 20 lks. wide, bears SSE. and NNW.</p>
80.205	<p>The cor. of secs. 1, 6, 7, and 12 on the W. bdy. of the Tp., hereinbefore described.</p>
	<p>From the cor. of secs. 5, 6, 7, and 8. N. 0°07'20" W., bet. secs. 5 and 6.</p>
40.008	<p>Point for the 1/4 sec. cor. of secs. 5 and 6. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Miguel A. Garcia	Cadastral Surveyor
Carlos Gil-Mendoza	Cadastral Surveyor
Michael O. Jones	Cadastral Surveyor
Kelly R. Totten	Cadastral Surveyor
Shane T. Trotter	Cadastral Surveyor
Mark G. Petrosine	Survey Technician
Alex J. Yetsko	Survey Technician

CERTIFICATE OF SURVEY

I, Lee T. Wilson, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing the date of the 4th day of January, 2022, I have surveyed the south and west boundaries and a portion of the subdivisional lines, Township 15 South, Range 47 East, of the Mount Diablo Meridian, in the state of Nevada, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

JAN 04 2024

(Date)

Lee T. Wilson

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of the survey of the south and west boundaries and a portion of the subdivisional lines, Township 15 South, Range 47 East, of the Mount Diablo Meridian, Nevada, executed by Lee T. Wilson, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

JAN 04 2024

(Date)

Mahmud H. Hummer

(Chief Cadastral Surveyor for Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above described surveys in Township 15 South, Range 47 East, Mount Diablo Meridian, Nevada, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor for Nevada)~~