

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

A PORTION OF THE WEST BOUNDARY,

THE NORTH BOUNDARY

AND A PORTION THE SUBDIVISIONAL LINES,

AND THE SUBDIVISION OF CERTAIN SECTIONS,

TOWNSHIP 15 SOUTH, RANGE 67 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATE OF NEVADA

EXECUTED BY

Don R. Aschenbach, Cadastral Surveyor

Under Special Instructions dated September 28, 2006,

and approved September 28, 2006,

which provided for the surveys included under Group No. 841,

and Assignment Instructions dated October 2, 2008.

Survey commenced October 10, 2008

Survey completed July 14, 2011

TOWNSHIP 15 SOUTH, RANGE 67 EAST, MOUNT DIABLO MERIDIAN, NEVADA

10	9	8	8	7	6
5 6	33 5	27 4	23 3	18 2	14 1
32	32	26	23	18	14
3 7	31 8	26 9	22 10	17 11	13 12
30	30	25	21	17	12
2 18	29 17	24 16	19 15	16 14	12 13
28	28	23	18	15	11
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Subdivision of Section 7	pp. 34 - 38
Subdivision of Section 8	pp. 38 - 40
Subdivision of Section 15	pp. 40 - 41
Subdivision of Section 16	pp. 41 - 44
Subdivision of Section 17	pp. 44 - 48

TOWNSHIP 15 SOUTH, RANGE 67 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The following field notes are those of the dependent resurvey of a portion of the west boundary, the north boundary and a portion of the subdivisional lines, and the subdivision of certain sections, Township 15 South, Range 67 East, Mount Diablo Meridian, Nevada.

The exterior boundaries and the subdivisional lines were surveyed by U.S. Deputy Surveyors R.H. Woods and W.H. Myrick in 1881 under Contract No. 109. The east boundary was dependently resurveyed by Cadastral Surveyor D.R. Beck in 1970 under Group No. 468. On April 7, 2000, the plat approved June 13, 1881 for T. 14 S., R. 67 E., was suspended.

Before restoring the corners, the lines of the original surveys were retraced and a diligent search made for any evidence of the position of the original corners and other calls of the original field note record.

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 841, dated September 28, 2006.

Measurements were made with Trimble 5700 Global Positioning System (GPS) receivers using the real-time kinematic (RTK) method and refer to the true meridian based on geodetic methods. The mean bearings of the lines and horizontal equivalents of ground distances only are entered in the field notes.

The NAD 1983 (CORS 96) geographic position of the corner of sections 13, 18, 19 and 24, on the east boundary of the township, determined from GPS static observations processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) NVCA CARLTON SQUARE 2 CORS ARP, NVBM BERMUDA CORS ARP and NVLM AMS WT FACILITY CORS ARP, in 2008, and carried forward by RTK observations, is as follows:

Latitude: 36°37'23.882" N.

Longitude: 114°26'20.267" W.

The 1980 mean magnetic declination is 14°30' E., as shown on U.S.G.S. 7 1/2 minute quadrangle map "OVERTON, NEV", provisional edition 1983.

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY
T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Reestablishment of a Portion of the Survey Executed by R.H. Woods and W.H. Myrick, U.S. Deputy Surveyors, in 1881</p> <hr/>										
	<p>Beginning at the cor. of secs. 13, 18, 19 and 24, monumented with a sandstone, 8x6x6 ins. (Record, limestone, 10x10x6 ins.), firmly set, projecting 4 ins. above the ground, plainly mkd. with 3 grooves on S. face and 3 grooves on N. face, in a mound of stone, 3 ft. base, 1 ft. high.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td>T15S</td><td></td></tr> <tr><td>R66E</td><td>R67E</td></tr> <tr><td>S13</td><td>S18</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S24</td><td>S19</td></tr> </table> <p>2008</p> </div> <p>Bury the mkd. stone alongside the stainless steel post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Cor. is located on a spur, slopes N.</p> <p>N. 0°03'10" E., bet. secs. 13 and 18.</p> <p>Over broken land.</p>	T15S		R66E	R67E	S13	S18	<hr/>		S24	S19
T15S											
R66E	R67E										
S13	S18										
<hr/>											
S24	S19										
5.30	Dry wash, 200 lks. wide, drains NE.										
38.50	Dry wash, 30 lks. wide, drains NE.										
40.128	<p>The 1/4 sec. cor. of secs. 13 and 18, monumented with a sandstone, 17x12x11 ins. (Record, granite, 10x8x6 ins.), firmly set in a mound of stone, 3 ft. base, 6 ins. high, plainly mkd. 1/4 on the E. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td>T15S</td><td></td></tr> <tr><td>1/4</td><td></td></tr> <tr><td>R66E</td><td>R67E</td></tr> <tr><td>S13</td><td>S18</td></tr> </table> <p>2008</p> </div> <p>Bury the mkd. stone alongside the stainless steel post.</p> <hr/>	T15S		1/4		R66E	R67E	S13	S18		
T15S											
1/4											
R66E	R67E										
S13	S18										

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY
T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°15'20" W., beginning new measurement.
	Over broken land.
1.40	Dry wash, 20 lks. wide, drains E.
40.387	<p>The cor. of secs. 7, 12, 13 and 18, monumented with a sandstone, 15x7x6 ins., firmly set in a mound of stone, 4 ft. base, 2 ft. high, plainly mkd. with 4 grooves on S. face and 2 grooves on N. face, witnessed by R. Guy Doty, Nevada Professional Surveyor No. 7635, with a rebar, 5/8 in. diam., projecting 8 ins. above ground, firmly set alongside, with aluminum cap mkd. R GUY DOTY PLS 7635, as recorded in Clark County, Nevada, File 147, Page 26 of Surveys.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T15S R66E R67E S12 S 7 ----- S13 S18</p> <p>2008</p> </div> <p>Bury the mkd. stone and rebar alongside the stainless steel post.</p>
	N. 0°58'00" E., bet. secs. 7 and 12.
	Over broken ground.
20.001	The S 1/16 sec. cor. of secs. 7 and 12, determined by R. Guy Doty, Nevada Professional Surveyor No. 7635, monumented with a rebar, 5/8 in. diam., firmly set, projecting 1 in. above the ground, with aluminum cap mkd. R GUY DOTY PLS 7635, as recorded in Clark County, Nevada, File 147, Page 26 of Surveys, and is accepted as a careful and faithful determination of the position of the corner.
	N. 0°58'00" E., beginning new measurement.
9.50	Center of Union Pacific Railroad tracks, bears SE. and NW.
10.25	Wire fence, bears SE. and NW.
20.001	<p>Point for the 1/4 sec. cor. of secs. 7 and 12, at proportionate distance; there is no remaining evidence of the position of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a collar of stone, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY
T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>T15S 1/4 R66E R67E S12 S 7</p> <p>2009</p>
20.50	Muddy River, 40 lks. wide, 2 ft. deep, course SE.
37.60	Chain link fence, 5 ft. high, bears E. and W.
40.002	<p>The N 1/16 sec. cor. of secs. 7 and 12, determined by R. Guy Doty, Nevada Professional Surveyor No. 7635, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set 1 in. below the surface of the ground, as recorded in Clark County, Nevada, File 147, Page 26 of Surveys, with aluminum cap unreadable, and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. below the surface of a jeep trail, over a plastic-encased magnet, with brass cap mkd.</p> <p>N 1/16 S12 S 7</p> <p>2009</p> <p>from which I add</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground, encircled in a collar of stone, for a reference monument, bears N. 0°26' E., 38.3 lks. dist., with brass cap mkd. RM N1/16 S7 25.3 FT TO COR 2009 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground, encircled in a collar of stone, for a reference monument, bears N. 59°45' E., 36.1 lks. dist., with brass cap mkd. RM N1/16 S7 23.8 FT TO COR 2009 and an arrow pointing to the corner.</p> <p>Bury the rebar alongside the stainless steel post.</p> <p>Cor. is located in a jeep trail, 20 lks. wide, bears SE. and NW.</p> <hr/> <p>N. 0°58'00" E., beginning new measurement.</p>
0.90	Dry wash, 40 lks. wide, drains SW.
2.40	Single pole powerline, bears SE. and NW.
20.001	<p>The cor. of secs. 1, 6, 7 and 12, monumented with an unrecorded aluminum post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, in mound of stone, 5 ft. base, 1 ft. high, with aluminum cap, 3 1/2 ins. diam., mkd. CLARK COUNTY RLS 2050 S1 S6 S7 S12. This position has been adopted and recorded by various professional land surveyors and is accepted the best available evidence of the position of the original corner.</p> <hr/>

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY
T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 2°10'20" W., bet. secs. 1 and 6.
	Over rolling hills.
7.60	Single pole powerline, bears SE. and NW.
28.10	Underground water lines, bears SE. and NW.
38.90	Double pole powerline, bears SE. and NW.
40.538	<p>The 1/4 sec. cor. of secs. 1 and 6, perpetuated by Brett N. Lane, Nevada Professional Land Surveyor No. 7641, monumented with a rebar, 5/8 in. diam., firmly set in an embedded mound of stone, 3 ft. base, 6 ins. high, with aluminum cap mkd. PLS 7641 1989, as recorded in Clark County, Nevada, File 54, Page 73 of Surveys, with a basalt stone, 9x7x5 ins. (Record, post, 4 ins. diam.), plainly mkd. 1/4 on a face, lying loosely in the mound of stone, from which reference monuments set by Lane</p> <p>A rebar, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with aluminum cap, 1 1/2 ins. diam., mkd. RM PLS 7641 71.36, bears N. 82°42' E., 1.081 chs. dist.</p> <p>A rebar, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with aluminum cap, 1 1/2 ins. diam., mkd. RM PLS 7641 67.98, bears S. 23°50' E., 1.030 chs. dist.</p> <p>A rebar, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with aluminum cap, 1 1/2 ins. diam., mkd. RM PLS 7641 85.62, bears S. 83°28' W., 1.297 chs. dist.</p> <p>A rebar, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with aluminum cap, 1 1/2 ins. diam., mkd. RM PLS 7641 67.13, bears N. 26°43' W., 1.017 chs. dist.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T15S 1/4 R66E R67E S 1 S 6</p> <p>2009</p> </div> <p>Bury the mkd. stone and rebar alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 3°20'20" W., beginning new measurement.</p>
38.00	Center of asphalt surface, E. bound lane of Interstate Route No. 15, 60 lks. wide, bears NE. and SW.

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY
T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.75	Center of asphalt surface, W. bound lane of Interstate Route No. 15, 60 lks. wide, bears NE. and SW.
40.264	<p>The cor. of Tps. 14 and 15 S., Rs. 66 and 67 E., reestablished by Brett N. Lane, Nevada Professional Land Surveyor No. 7641, monumented with a brass tablet, 2 ins. diam., firmly set in concrete, 12 ins. below the surface of the ground, mkd. T14S R66E R67E S1 S6 S31 S36 PLS 7641 1989, as recorded in Clark County, Nevada, File 54, Page 73 of Surveys, and is accepted as a careful and faithful reestablishment of the position of the original corner, from which reference monuments set by Lane</p> <p>A rebar, 5/8 in. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap, 1 1/2 ins. diam., mkd. RM PLS 7641 30.02, bears N. 31°02' E., 45.5 lks. dist.</p> <p>A rebar, 5/8 in. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap, 1 1/2 ins. diam., mkd. RM PLS 7641 29.88, bears N. 31°10' W., 45.3 lks. dist.</p> <hr/> <p>DEPENDENT RESURVEY OF THE NORTH BOUNDARY, T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of the Survey Executed by R.H. Woods and W.H. Myrick, U.S. Deputy Surveyors, in 1881</p> <hr/> <p>From the cor. of Tps. 14 and 15 S., Rs. 67 and 68 E., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the west boundary of T. 15 S., R. 68 E., executed under Group No. 468, with a mound of stone, 3 ft. base, 2 ft. high, S. of cor.</p> <p>N. 89°53'50" W., bet. secs. 1 and 36.</p> <p>Over plateaus and broken ground.</p>
7.40	Rim of plateau, bears irregularly SE. and NW.
39.721	<p>Point for the 1/4 sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of the position of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T14S R67E S36 1/4 — S 1 T15S 2008</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>

DEPENDENT RESURVEY OF THE NORTH BOUNDARY,
T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS											
40.50	Dry wash, 20 lks. wide, drains NW.										
64.60	Dry wash, 40 lks. wide, drains SW.										
76.90	Rim of plateau, bears irregularly NE. and SW.										
79.442	Point for the cor. of secs. 1, 2, 35 and 36, at proportionate distance; there is no remaining evidence of the position of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd. <div style="text-align: center;"> <table> <tr><td>T14S</td><td>R67E</td></tr> <tr><td>S35</td><td>S36</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 2</td><td>S 1</td></tr> <tr><td colspan="2">T15S</td></tr> </table> 2008 </div>	T14S	R67E	S35	S36	<hr/>		S 2	S 1	T15S	
T14S	R67E										
S35	S36										
<hr/>											
S 2	S 1										
T15S											
	<hr/> <p>N. 89°53'50" W., bet. secs. 2 and 35.</p> <p>Over plateaus and broken ground.</p>										
29.10	Rim of plateau, bears irregularly SE. and NW.										
39.721	Point for the 1/4 sec. cor. of secs. 2 and 35, at proportionate distance; there is no remaining evidence of the position of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd. <div style="text-align: center;"> <table> <tr><td>T14S</td><td>R67E</td></tr> <tr><td>S35</td><td></td></tr> <tr><td>1/4</td><td><hr/></td></tr> <tr><td>S 2</td><td></td></tr> <tr><td colspan="2">T15S</td></tr> </table> 2008 </div>	T14S	R67E	S35		1/4	<hr/>	S 2		T15S	
T14S	R67E										
S35											
1/4	<hr/>										
S 2											
T15S											
40.10	Dry wash, 20 lks. wide, drains SW.										
64.30	Dry wash, 40 lks. wide, drains SW.										
79.442	Point for the cor. of secs. 2, 3, 34 and 35, at proportionate distance; there is no remaining evidence of the position of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a collar of stone, with brass cap mkd.										

DEPENDENT RESURVEY OF THE NORTH BOUNDARY,
T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div> <div> <div>T14S R67E</div> <div>S34 S35</div> <div>S 3 S 2</div> <div>T15S</div> </div> <div>2008</div> </div> <hr/> <p>N. 89°53'50" W., bet. secs. 3 and 34.</p> <p>Over rolling hills.</p> <p>39.721 Point for the 1/4 sec. cor. of secs. 3 and 34, at proportionate distance; there is no remaining evidence of the position of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div> <div> <div>T14S R67E</div> <div>S34</div> <div>1/4</div> <div>S 3</div> <div>T15S</div> </div> <div>2009</div> </div> <p>75.50 Jeep trail, 20 lks. wide, bears NE. and SW.</p> <p>79.442 Point for the cor. of secs. 3, 4, 33 and 34, at proportionate distance; there is no remaining evidence of the position of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div> <div> <div>T14S R67E</div> <div>S33 S34</div> <div>S 4 S 3</div> <div>T15S</div> </div> <div>2008</div> </div> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <hr/> <p>N. 89°53'50" W., bet. secs. 4 and 33.</p> <p>Over rolling hills.</p> <p>14.60 Dry wash, 50 lks. wide, drains S.</p> <p>38.40 Dry wash, 30 lks. wide, drains SE.</p> <p>39.721 Point for the 1/4 sec. cor. of secs. 4 and 33, at proportionate distance; there is no remaining evidence of the position of the original corner.</p>
--------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

DEPENDENT RESURVEY OF THE NORTH BOUNDARY,
T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T14S R67E S33 1/4 — S 4 T15S 2009</p>
79.442	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>Point for the cor. of secs. 4, 5, 32 and 33, at proportionate distance; there is no remaining evidence of the position of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T14S R67E S32 S33 — — S 5 S 4 T15S 2009</p>
	<p>N. 89°53'50" W., bet. secs. 5 and 32.</p> <p>Over rolling hills.</p>
35.10	Center of asphalt surface, Nevada State Route 169, 42 lks. wide, bears SE. and NW.
39.721	<p>The 1/4 sec. cor. of secs. 5 and 32, perpetuated by Brent Ross Woolsey, Nevada Professional Land Surveyor No. 4301, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 2 ins. above the ground, with aluminum cap, 1 1/2 ins. diam., mkd. B R WOOLSEY 1/4 5 32 RLS 4301, as recorded in Clark County, Nevada, File 31, Page 49 of Surveys, with a limestone, 19x13x6 ins. (Record granite, 16x11x8 ins.), plainly mkd. 1/4 on a face, loosely set alongside, and a steel fence post SW. of the rebar.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T14S R67E S32 1/4 — S 5 T15S 2008</p>

DEPENDENT RESURVEY OF THE NORTH BOUNDARY,
T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Bury the mkd. stone and rebar alongside the stainless steel post.</p> <hr/> <p>N. 89°16'50" W., beginning new measurement.</p>						
41.139	<p>The cor. of secs. 5, 6, 31 and 32, perpetuated by Brett N. Lane, Nevada Professional Land Surveyor No. 7641, monumented with an aluminum tablet, 1 1/2 ins. diam., cemented flush in bedrock, mkd. PLS 7641 1989, as recorded in Clark County, Nevada, Survey File 54, Page 73. A limestone, 16x9x6 ins., plainly mkd. with 5 grooves on a face and 1 groove on adjoining face, was found laying loose in a mound of stone, 8 ft. base, 2 ft. high, S. of cor., from which reference monuments set by Lane</p> <p>A rebar, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with aluminum cap, 1 1/2 ins. diam., mkd. PLS 7641 97.29, bears N. 15°26' E., 1.475 chs. dist.</p> <p>A rebar, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with aluminum cap, 1 1/2 ins. diam., mkd. PLS 7641 67.02, bears S. 66°13' E., 1.016 chs. dist.</p> <p>A rebar, 5/8 in. diam., firmly set, projecting 5 ins. above the ground, with aluminum cap, 1 1/2 ins. diam., mkd. PLS 7641 55.53, bears S. 44°15' W., 0.841 chs. dist.</p> <p>A rebar, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with aluminum cap, 1 1/2 ins. diam., mkd. PLS 7641 88.56, bears N. 47°46' W., 1.342 chs. dist.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., on bedrock, over a plastic-encased magnet and the aluminum tablet, and in a mound of stone, 6 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T14S R67E</p> <table> <tr> <td>S31</td> <td>S32</td> </tr> <tr> <td>S 6</td> <td>S 5</td> </tr> <tr> <td colspan="2">T15S</td> </tr> </table> <p>2008</p> </div> <p>Bury the mkd. stone alongside the stainless steel post.</p> <hr/> <p>N. 89°36'10" W., bet. secs. 6 and 31.</p> <p>Over low rolling hills.</p>	S31	S32	S 6	S 5	T15S	
S31	S32						
S 6	S 5						
T15S							
34.85	Right-of-way fence, bears NE. and SW.						
40.456	Point for the 1/4 sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the position of the original corner.						

DEPENDENT RESURVEY OF THE NORTH BOUNDARY,
T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T14S R67E S31 1/4 — S 6 T15S 2009</p>
60.40	Double pole powerline, bears SE. and NW.
61.10	Center of asphalt surface, E. bound lane of Interstate Route No. 15, 60 lks. wide, bears NE. and SW.
76.85	Center of asphalt surface, W. bound lane of Interstate Route No. 15, 60 lks. wide, bears NE. and SW.
81.620	The cor. of Tps. 14 and 15 S., Rs. 66 and 67 E., hereinbefore described.
<hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of a Portion of the Survey Executed by R.H. Woods and W.H. Myrick, U.S. Deputy Surveyors, in 1881</p> <hr/> <p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the west boundary of T. 15 S., R. 68 E., executed under Group No. 468, with a mound of stone, 3 ft. base, 1 1/2 ft. high, W. of cor.</p> <p>S. 88°49'50" W., bet. secs. 13 and 24.</p> <p>Over rolling hills.</p>	
39.822	<p>The 1/4 sec. cor. of secs. 13 and 24, reestablished by Lynn R. Elam, Nevada Professional Land Surveyor No. 4320, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with aluminum cap mkd. CLARK COUNTY NEV. RLS 4320 1/4 S13 S24, as recorded in Clark County, Nevada, File 31, Page 33 of Surveys, with a steel fence post alongside. This position has been adopted and recorded by various other professional land surveyors, and is accepted as the best available evidence of the position of the original corner.</p> <hr/> <p>S. 88°49'50" W., beginning new measurement.</p> <p>Over rolling land.</p>
1.50	Jeep trail, 20 lks. wide, bears NE. and SW.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.822	<p>The cor. of secs. 13, 14, 23 and 24, reestablished by Lynn R. Elam, Nevada Professional Land Surveyor No. 4320, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 1 in. above the ground, with aluminum cap mkd. CLARK COUNTY NEV. RLS 4320 S13 S14 S23 S24, as recorded in Clark County, Nevada, File 31, Page 33 of Surveys, with a steel fence post alongside. This position has been adopted and recorded by various other professional land surveyors and is accepted as a the best available evidence of the position of the original corner.</p> <hr/> <p>N. 1°38'00" W., bet. secs. 13 and 14.</p> <p>Over low rolling hills.</p>
39.999	<p>Point for the 1/4 sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the position of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T15S R67E 1/4 S14 S13</p> <p>2008</p> </div>
46.60	Dry wash, 40 lks. wide, drains SW.
51.00	Dry wash, 40 lks. wide, drains W.
79.998	<p>Point for the cor. of secs. 11, 12, 13 and 14, at proportionate distance; there is no remaining evidence of the position of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T15S R67E S11 S12 <hr/>S14 S13</p> <p>2008</p> </div> <hr/> <p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the west boundary of T. 15 S., R. 68 E., executed under Group No. 468, with a mound of stone, 4 ft. base, 3 ft. high, W. of cor.</p> <p>S. 89°18'30" W., bet. secs. 12 and 13.</p> <p>Over rolling hills.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.10	Dry wash, 10 lks. wide, drains SW.
40.011	Point for the 1/4 sec. cor. of secs. 12 and 13, at proportionate distance; there is no remaining evidence of the position of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a collar of stone, with brass cap mkd. <div style="text-align: center;"> T15S R67E S12 1/4 ——— S13 2008 </div>
63.90	Dry wash, 60 lks. wide, drains SSE.
80.022	The cor. of secs. 11, 12, 13 and 14. <hr/> N. 0°59'20" W., bet. secs. 11 and 12. Over rolling hills. 39.989 Point for the 1/4 sec. cor. of secs. 11 and 12, at proportionate distance; there is no remaining evidence of the position of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;"> T15S R67E 1/4 S11 S12 2008 </div>
62.70	Dry wash, 60 lks. wide, drains SE.
79.978	Point for the cor. of secs. 1, 2, 11 and 12, at proportionate distance; there is no remaining evidence of the position of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;"> T15S R67E S 2 S 1 ——— S11 S12 2008 </div> <hr/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the west boundary of T. 15 S., R. 68 E., executed under Group No. 468, with a mound of stone, 4 ft. base, 3 ft. high, W. of cor.</p> <p>S. 89°46'40" W., bet. secs. 1 and 12.</p> <p>Over plateaus and broken ground.</p>
8.70	Rim of plateau, bears NE. and SW.
39.757	<p>Point for the 1/4 sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the position of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T15S R67E</p> <p>S 1</p> <p>1/4 —</p> <p>S12</p> <p>2008</p> </div>
77.70	Dry wash, 20 lks. wide, drains S.
79.514	The cor. of secs. 1, 2, 11 and 12.
	<hr/> <p>N. 1°15'40" W., bet. secs. 1 and 2.</p> <p>Over rolling hills.</p>
39.992	<p>Point for the 1/4 sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the position of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T15S R67E</p> <p>1/4</p> <p>S 2 S 1</p> <p>2008</p> </div>
50.50	Dry wash, 50 lks. wide, drains SW.
77.20	Rim of plateau, bears NE. and SW.
79.834	The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., hereinbefore described.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>S. 88°49'10" W., bet. secs. 14 and 23.</p> <p>Over low rolling hills.</p>
22.90	Double pole powerline, bears SE. and NW.
30.20	Double pole powerline, bears SE. and NW.
39.948	<p>The 1/4 sec. cor. of secs. 14 and 23, reestablished by Lynn R. Elam, Nevada Professional Land Surveyor No. 4320, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with aluminum cap mkd. CLARK COUNTY NEV. RLS 4320 1/4 S14 S23, as recorded in Clark County, Nevada, File 31, Page 34 of Surveys. This position has been adopted and recorded by various other professional land surveyors and is accepted as the best available evidence of the position of the original corner.</p> <p>From this cor., the cor. of fences extending S. and W., bears NORTH, 5 lks. dist.</p> <hr/> <p>S. 88°49'10" W., beginning new measurement.</p>
19.974	<p>The W 1/16 sec. cor. of secs. 14 and 23, monumented with an unrecorded rebar, 5/8 in. diam., firmly set 8 ins. below the surface of the ground, with aluminum cap, 1 1/2 ins. diam., mkd. HASKEW ENG LS 3849, later recovered and utilized by R. Guy Doty, Nevada Professional Land Surveyor No. 7635, as recorded in Clark County, Nevada, File 90, Page 90 of Surveys, and is accepted as a careful and faithful determination of the position of the corner.</p> <hr/> <p>S. 88°49'10" W., beginning new measurement.</p>
10.00	Jeep trail, 20 lks. wide, bears NNW. and S.
19.977	<p>The cor. of secs. 14, 15, 22 and 23, reestablished by Stephen F. Turner, Nevada Professional Land Surveyor No. 1803, in 1970, record monument being an iron post, 2 ins. diam., as recorded in Clark County, Nevada, File 20, Page 50 of Surveys, later recovered and utilized by Lynn R. Elam, Nevada Professional Land Surveyor No. 4320, in 1977, remonumented with an aluminum post, 2 1/2 ins. diam., firmly set flush with the surface of the ground, with aluminum cap mkd. CLARK COUNTY NEV. RLS 4320 S14 S15 S22 S23, as recorded in Clark County, Nevada, File 30, Page 98 of Surveys. This position has since been adopted and recorded by various other professional land surveyors, used locally during urban development and is accepted as the best available evidence of the position of the original corner.</p> <p>From this cor., the cor. of fences extending E. and NE., bears NORTH, 5 lks. dist.</p> <hr/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 1°53'50" W., bet. secs. 14 and 15. Over brush covered flats.
0.60	Jeep trail, 20 lks. wide, bears NE. and SW.
13.20	Center of old asphalt road, 30 lks. wide, bears E. and W.
15.80	S. shore of Bowman Reservoir, bears E. and W., thence across the surface of the water.
39.35	N. shore of Bowman Reservoir, bears E. and W.
40.299	Point for the 1/4 sec. cor. of secs. 14 and 15, at proportionate distance; there is no remaining evidence of the position of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;"> T15S R67E 1/4 S15 S14 2008 </div>
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
42.60	Double pole powerline, bears SE. and NW.
44.50	Double pole powerline, bears SE. and NW.
80.598	Point for the cor. of secs. 10, 11, 14 and 15, at proportionate distance; there is no remaining evidence of the position of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;"> T15S R67E S10 S11 <hr/> S15 S14 2008 </div>
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor. From this cor., a steel pipe of unknown origin, 1 in. diam., firmly set, projecting 3 ft. above the ground, bears S. 81°21' E., 3.66 chs. dist. This position is not harmoniously related to surrounding corners, cannot be reconciled with proper procedures and is not utilized during the course of this survey.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>S. 89°14'40" W., bet. secs. 11 and 14.</p> <p>Over low rolling hills.</p>
40.131	<p>Point for the 1/4 sec. cor. of secs. 11 and 14, at proportionate distance; there is no remaining evidence of the position of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T15S R67E</p> <p>S11</p> <p>1/4 —</p> <p>S14</p> <p>2008</p> </div>
80.262	<p>The cor. of secs. 10, 11, 14 and 15.</p> <hr/> <p>N. 0°38'20" W., bet. secs. 10 and 11.</p> <p>Over low rolling hills.</p>
40.280	<p>Point for the 1/4 sec. cor. of secs. 10 and 11, at proportionate distance; there is no remaining evidence of the position of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T15S R67E</p> <p>1/4</p> <p>S10 S11</p> <p>2008</p> </div>
80.560	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Point for the cor. of secs. 2, 3, 10 and 11, at proportionate distance; there is no remaining evidence of the position of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T15S R67E</p> <p>S 3 S 2</p> <hr/> <p>S10 S11</p> <p>2008</p> </div> <hr/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>S. 89°39'50" W., bet. secs. 2 and 11.</p> <p>Over low rolling hills.</p>
14.20	Dry wash, 100 lks. wide, drains SE.
39.881	<p>Point for the 1/4 sec. cor. of secs. 2 and 11, at proportionate distance; there is no remaining evidence of the position of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15S R67E S 2 1/4 — S11</p> <p style="text-align: center;">2008</p>
79.762	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>The cor. of secs. 2, 3, 10 and 11.</p> <hr/> <p>N. 1°02'00" W., bet. secs. 2 and 3.</p> <p>Over low rolling hills.</p>
40.284	<p>Point for the 1/4 sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the position of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15S R67E 1/4 S 3 S 2</p> <p style="text-align: center;">2008</p>
80.437	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>N. 88°49'40" W., bet. secs. 15 and 22.</p> <p>Over flats and low hills.</p>
0.30	Jeep trail, 20 lks. wide, bears NE. and WSW.
40.50	Gravel road, 20 lks. wide, bears N. and SW.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
41.294	<p>The 1/4 sec. cor. of secs. 15 and 22, reestablished by Lynn R. Elam, Nevada Professional Land Surveyor No. 4320, monumented with an aluminum post, 2 1/2 ins. diam., as recorded in Clark County, Nevada, File 30, Page 98 of Surveys, with top portion sheared off and missing, and with an unrecorded rebar, 5/8 in. diam., 18 ins. long, firmly set alongside, with aluminum cap mkd. R GUY PLS 7635. This position has been adopted and recorded by various other professional land surveyors and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T15S R67E S15 1/4 — S22</p> <p>2009</p> </div> <p>Bury the aluminum post remains and rebar alongside the stainless steel post.</p> <hr/> <p>N. 88°49'40" W., beginning new measurement.</p>
1.90	Center of asphalt surface, Nevada State Route 169, 42 lks. wide, bears SE. and NW.
40.75	Concrete lined irrigation ditch, 4 ft. wide, 2 ft. deep, course SW.
40.787	<p>The cor. of secs. 15, 16, 21 and 22, reestablished by Lynn R. Elam, Nevada Professional Land Surveyor No. 4320, monumented with a brass tablet, 1 1/2 ins. diam., firmly embedded in the W. wall of a concrete lined irrigation ditch, mkd. 4320 S15 S16 S21 S22, as recorded in Clark County, Nevada, File 30, Page 98 of Surveys. This position has been adopted and recorded by various other professional land surveyors and is accepted as the best available evidence of the position of the original corner.</p> <hr/> <p>N. 0°33'30" W., bet. secs. 15 and 16.</p> <p>Over low rolling hills.</p>
16.70	Irrigation ditch, 40 lks. wide, course NE.
20.693	<p>The S 1/16 sec. cor. of secs. 15 and 16, determined by R. Guy Doty, Nevada Professional Land Surveyor No. 7635, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 1 in. above the ground, with aluminum cap, 1 1/2 ins. diam., mkd. R GUY DOTY PLS 7635, as recorded in Clark County, Nevada, File 70, Page 6 of Surveys. This is accepted as a careful and faithful determination of the position of the corner.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S16 S15</p> <p style="text-align: center;">2009</p> <p>Bury the rebar alongside the stainless steel post.</p> <hr/> <p>N. 0°32'40" W., beginning new measurement.</p> <p>2.10 Single pole powerline, bears E. and W.</p> <p>9.70 Underground water line, bears E. and W.</p> <p>20.692 The 1/4 sec. cor. of secs. 15 and 16, reestablished by Brent Ross Woolsey, Nevada Professional Land Surveyor No. 4301, the record monument being a rebar, 1/2 in. diam., with cap mkd. RLS 4301, as recorded in Clark County, Nevada, File 31, Page 49 of Surveys, later recovered and accepted by R. Guy Doty, Nevada Professional Land Surveyor No. 7635, remonumented with a rebar, 1/2 in. diam., 18 ins. long, firmly set, projecting 6 ins. above the ground, as recorded in Clark County, Nevada, File 85, Page 25 of Surveys, with a steel fence post alongside. This is accepted as a careful and faithful reestablishment of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T15S R67E 1/4 S16 S15</p> <p style="text-align: center;">2009</p> <p>Bury the rebar and reset steel fence post alongside the stainless steel post.</p> <hr/> <p>N. 0°33'40" W., beginning new measurement.</p> <p>20.673 The N 1/16 sec. cor. of secs. 15 and 16, determined by Brent Ross Woolsey, Nevada Professional Land Surveyor No. 4301, the record monument being a rebar with cap mkd. RLS 4301, as recorded in Clark County, Nevada, File 30, Page 9 of Parcel Maps, later recovered and accepted by R. Guy Doty, Nevada Professional Land Surveyor No. 7635, remonumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 1 in. above the ground, as recorded in Clark County, Nevada, File 85, Page 25 of Surveys. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p>
--------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S16 S15 2009</p> <p>Bury the rebar alongside the stainless steel post.</p> <hr/> <p>N. 0°32'40" W., beginning new measurement.</p>
4.00	Center of asphalt surface, Nevada State Route 169, 42 lks. wide, bears SE. and NW.
20.692	<p>The cor. of secs. 9, 10, 15 and 16, reestablished by Brent Ross Woolsey, Nevada Professional Land Surveyor No. 4301, monumented with a rebar, 1/2 in. diam., 18 ins. long, firmly set, projecting 2 ins. above the ground, with aluminum cap, 1 1/2 ins. diam., mkd. B R WOOLSEY 9 10 15 16, PLS 4301, as recorded in Clark County, Nevada, File 31, Page 49 of Surveys. This position is accepted as a careful and faithful reestablishment of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T15S R67E S 9 S10 S16 S15 2008</p> <p>Bury the rebar alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>N. 87°14'10" W., bet. secs. 10 and 15.</p> <p>Over low rolling hills.</p>
40.136	<p>Point for the 1/4 sec. cor. of secs. 10 and 15, at proportionate distance; there is no remaining evidence of the position of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15S R67E S10 1/4 — S15 2008</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
58.50	Double pole powerline, bears SE. and NW.
60.204	Point for the W 1/16 sec. cor. of secs. 10 and 15. POINT NOT MONUMENTED
61.60	Double pole powerline, bears SE. and NW.
72.60	Dry wash, 150 lks. wide, drains S.
80.272	The cor. of secs. 9, 10, 15 and 16. <hr/>
	N. 0°12'20" W., bet. secs. 9 and 10. Over low rolling hills.
11.30	Double pole powerline, bears SE. and NW.
13.10	Double pole powerline, bears SE. and NW.
39.274	Point for the 1/4 sec. cor. of secs. 9 and 10, at proportionate distance; there is no remaining evidence of the position of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a collar of stone, with brass cap mkd. T15S R67E 1/4 S 9 S10 2008
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
53.50	Dry wash, 60 lks. wide, drains SW.
60.70	Dry wash, 60 lks. wide, drains SE.
67.80	Dry wash, 40 lks. wide, drains SW.
78.548	Point for the cor. of secs. 3, 4, 9 and 10, at proportionate distance; there is no remaining evidence of the position of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd. T15S R67E S 4 S 3 <hr/> S 9 S10 2008 <hr/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>N. 88°39'30" W., bet. secs. 3 and 10.</p>
39.782	<p>Point for the 1/4 sec. cor. of secs. 3 and 10, at proportionate distance; there is no remaining evidence of the position of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15S R67E S 3 1/4 — S10 2009</p>
79.564	<p>The cor. of secs. 3, 4, 9 and 10.</p> <hr/> <p>N. 0°59'40" W., bet. secs. 3 and 4.</p> <p>Over low rolling hills.</p>
39.280	<p>Point for the 1/4 sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the position of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15S R67E 1/4 S 4 S 3 2008</p>
78.717	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>S. 89°30'30" W., bet. secs. 16 and 21.</p> <p>Over low rolling hills and dense river bottom.</p>
19.963	<p>The E 1/16 sec. cor. of secs. 16 and 21, determined by Richard L. Hafen, Nevada Professional Land Surveyor No. 4428, monumented with a brass tablet, 2 ins. diam., firmly set flush in a concrete pad, mkd. E 1/16 S16 S21 RLS 4428 2007, as recorded in Clark County, Nevada, File 61, Page 63 of Surveys, and is accepted as a careful and faithful determination of the position of the corner, with an unrecorded rebar, 1/2 in. diam., loosely set alongside, with plastic cap mkd. RLS 4986.</p> <hr/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	S. 89°30'30" W., beginning new measurement.
19.963	<p>Point for the 1/4 sec. cor. of secs. 16 and 21, at proportionate distance; there is no remaining evidence of the position of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> T15S R67E S16 1/4 ——— S21 2009 </div>
22.30	Muddy River, 40 lks. wide, 2 ft. deep, course SE.
46.50	Center of Union Pacific Railroad tracks, bears SE. and NW.
59.889	<p>The cor. of secs. 16, 17, 20 and 21, perpetuated by Richard L. Hafen, Nevada Professional Land Surveyor No. 4428, the record monument being a rebar with plastic cap mkd. R.L.S. 4428, as recorded in Clark County, Nevada, File 55, Page 60 of Surveys, later recovered and accepted by James H. Turner, Nevada Professional Land Surveyor No. 10356, remonumented with a brass tablet, 2 ins. diam., firmly embedded flush in a concrete pad, with top mkd. 1996 S16 S17 S20 S21 PLS 10356, as recorded in Clark County, Nevada, File 87, Page 17 of Surveys. This is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <hr/> <p>N. 0°29'30" W., bet. secs. 16 and 17.</p> <p>Over low rolling hills and dense river bottoms.</p>
6.65	Center of Union Pacific Railroad tracks, bears SE. and NW.
8.10	Muddy River, 40 lks. wide, 2 ft. deep, course SE.
8.40	Single pole powerline, bears SE. and NW.
20.357	<p>The S 1/16 sec. cor. of secs. 16 and 17, determined by R. Guy Doty, Nevada Professional Surveyor No. 7635, monumented with a concrete nail, set flush with rock outcrop, with brass tag mkd. PLS 7635. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented flush in drill hole on limestone rock outcrop, with top mkd.</p> <div style="text-align: center;"> S 1/16 S17 S16 2009 </div> <p>Dispose of concrete nail with brass tag.</p> <hr/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°29'30" W., beginning new measurement.
20.357	<p>The 1/4 sec. cor. of secs. 16 and 17, reestablished by R. Guy Doty, Nevada Professional Land Surveyor No. 7635, monumented with an aluminum tablet (record, brass), 2 ins. diam., firmly set flush in a concrete slab, 12x12 ins., mkd. 1/4 16 17 PLS 7635, as recorded in Clark County, Nevada, File 67, Page 9 of Surveys.</p> <p>This position has been adopted by adjacent land owners and professional land surveyors and is accepted the best available evidence of the position of the original corner.</p> <hr/> <p>N. 0°29'30" W., beginning new measurement.</p>
14.90	Overhead telephone line, bears SE. and NW.
29.80	Underground water line, bears E. and W.
30.70	Single pole powerline, bears SE. and NW.
40.714	<p>The cor. of secs. 8, 9, 16 and 17, reestablished by R. Guy Doty, Nevada Professional Land Surveyor No. 7635, monumented with an aluminum tablet, 2 ins. diam., firmly set flush in a concrete pad, 12x12 ins., mkd. 8 9 16 17 PLS 7635, as recorded in Clark County, Nevada, File 67, Page 9 of Surveys. This position has been adopted by adjacent land owners and professional land surveyors and is accepted as the best available evidence of the position of the original corner.</p> <hr/> <p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>N. 89°06'50" W., bet. secs. 9 and 16.</p> <p>Over low rolling hills.</p>
11.10	Center of asphalt surface, Nevada State Route 169, 42 lks. wide, bears SE. and NW.
25.80	Center of asphalt surface, Solid Waste Convenience Center access road, 33 lks. wide, bears NE. and SW.
40.385	<p>The 1/4 sec. cor. of secs. 9 and 16, perpetuated by James H. Turner, Nevada Professional Land Surveyor No. 10356, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set flush with the surface of the ground, with aluminum cap, 1 1/2 ins. diam., mkd. 1/4 S9 S16 PLS 10356 1996, as recorded in Clark County, Nevada, File 87, Page 17 of Surveys. This is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>T15S R67E S 9 1/4 ——— S16</p> <p>2009</p> <p>Bury the rebar alongside the stainless steel post.</p> <hr/> <p>S. 86°10'30" W., beginning new measurement.</p> <p>32.50 Dry wash, 150 lks. wide, drains S.</p> <p>39.442 The cor. of secs. 8, 9, 16 and 17.</p> <hr/> <p>N. 1°41'40" E., bet. secs. 8 and 9.</p> <p>Over low rolling hills.</p> <p>40.719 The 1/4 sec. cor. of secs. 8 and 9, perpetuated by R. Guy Doty, Nevada Professional Land Surveyor No. 7635, monumented with a brass tablet, 2 ins. diam., firmly set flush in a concrete slab, 12x12 ins., mkd. 1/4 8 9 PLS 7635, as recorded in Clark County, Nevada, File 67, Page 9 of Surveys, and is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <hr/> <p>N. 1°55'30" W., beginning new measurement.</p> <p>21.50 Center of asphalt surface, Nevada State Route 169, 42 lks. wide, bears SE. and NW.</p> <p>24.30 Double pole powerline, bears SE. and NW.</p> <p>26.10 Double pole powerline, bears SE. and NW.</p> <p>37.082 The cor. of secs. 4, 5, 8 and 9, perpetuated by R. Guy Doty, Nevada Professional Land Surveyor No. 7635, monumented with a brass tablet, 2 ins. diam., firmly set flush in a concrete slab, 12x12 ins., mkd. 4 5 8 9 PLS 7635, as shown on the unrecorded survey plat "Record Map of Survey for Reilly C. Jensen", obtained from R. Guy Doty during the course of this survey, and is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <hr/> <p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>S. 87°59'20" W., bet. secs. 4 and 9.</p> <p>Over low rolling hills.</p> <p>8.20 Dry wash, 50 lks. wide drains SE.</p> <p>28.90 Enter disturbed mining area, edge bears N. and S.</p>
--------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.765	<p>Point for the 1/4 sec. cor. of secs. 4 and 9, at proportionate distance; there is no remaining evidence of the position of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> T15S R67E S 4 1/4 — S 9 </div> <p style="text-align: center;">2009</p> <p>Set a steel fence post alongside.</p> <p>from which</p> <p style="padding-left: 40px;">A brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented flush in drill hole on a concrete footing, for a reference monument, bears N. 65°56' E., 127.1 lks. dist., mkd. RM 1/4 S4 83.87 FT TO COR and an arrow pointing to the corner.</p> <p style="padding-left: 40px;">The W. leg of a conveyor support, projecting 1 ft. above the ground, bears S. 55°33' E., 160.6 lks. dist., mkd. with an "X".</p>
59.60	Leave disturbed mining area, edge bears N. and S., enter rolling hills.
79.530	The cor. of secs. 4, 5, 8 and 9.
	<hr/> <p>N. 0°56'20" W., bet. secs. 4 and 5.</p> <p>Over low rolling hills.</p>
40.912	<p>Point for the 1/4 sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the position of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> T15S R67E 1/4 S 5 S 4 </div> <p style="text-align: center;">2009</p>
81.650	<p>The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., hereinbefore described.</p> <hr/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>N. 89°13'40" W., bet. secs. 17 and 20.</p>
20.302	<p>Point for the E 1/16 sec. cor. of secs. 17 and 20.</p> <p>POINT NOT MONUMENTED</p>
40.604	<p>The 1/4 sec. cor. of secs. 17 and 20, reestablished by R. Guy Doty, Nevada Professional Land Surveyor No. 7635, monumented with an aluminum tablet, 2 ins. diam., firmly set flush in a concrete slab, 12x12 ins., mkd. 1/4 17 20 PLS 7635, as recorded in Clark County, Nevada, File 67, Page 9 of Surveys, and encircled in a mound of stone, 4 ft. base, 6 ins. high. This is accepted as a careful and faithful reestablishment of the position of the original corner.</p> <p>Cor. is located on a spur, slopes NE.</p> <hr/> <p>N. 89°14'00" W., beginning new measurement.</p>
20.301	<p>Point for the W 1/16 sec. cor. of secs. 17 and 20.</p> <p>POINT NOT MONUMENTED</p>
40.602	<p>The cor. of secs. 17, 18, 19 and 20, monumented with an unrecorded aluminum post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above the ground, with aluminum cap mkd. CLARK COUNTY NEV. RLS 4320 S17 S18 S19 S20, with a mound of stone, 5 ft. base, 2 ft. high and a steel fence post N. of cor. and a mound of stone, 5 ft. base, 2 ft. high, S. of cor. This position has been adopted and recorded by various other professional land surveyors and is accepted as of the best available evidence of the position of the original corner.</p> <hr/> <p>S. 89°46'20" W., bet. secs. 18 and 19.</p> <p>Over mountainous terrain.</p>
40.478	<p>True point for the 1/4 sec. cor. of secs. 18 and 19, at proportionate distance; there is no remaining evidence of the position of the original corner, falls on a steep NW slope, where it is impractical to establish a permanent monument.</p>
40.990	<p>Point selected for the witness 1/4 sec. cor. of secs. 18 and 19.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented flush in drill hole on limestone outcrop, with top mkd.</p> <div style="text-align: center;"> <p>WC</p> <p>T15S R67E</p> <p>S18</p> <p>1/4 →</p> <p>S19</p> </div> <p>2008</p> <p>Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W. of cor.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
80.763	The cor. of secs. 13, 18, 19 and 24, on the W. bdy of the Tp., hereinbefore described.
	<hr/> <p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 0°17'40" W., bet. secs. 17 and 18.</p>
20.214	Point for the S 1/16 sec. cor. of secs. 17 and 18.
	POINT NOT MONUMENTED
35.90	Ridge, bears SE. and NW.
40.428	<p>The 1/4 sec. cor. of secs. 17 and 18, perpetuated by R. Guy Doty, Nevada Professional Land Surveyor No. 7635, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 8 ins. above the ground, encircled in an embedded mound of stone, 3 ft. base, 6 ins. high, with aluminum cap, 1 1/2 ins. diam., mkd. R GUY DOTY PLS 7635, as recorded in Clark County, Nevada, File 67, Page 9 of Surveys, with a limestone, 11x10x6 ins. (Record, granite stone, 15x14x10 ins.), plainly mkd. 1/4 on a face, lying loosely in the mound of stone.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T15S R67E 1/4 S18 S17 2008</p> <p>Bury the mkd. stone and rebar alongside the stainless steel post.</p> <hr/> <p>N. 1°03'50" E., beginning new measurement.</p>
20.048	Point for the N 1/16 sec. cor. of secs. 17 and 18.
	POINT NOT MONUMENTED
40.096	<p>The cor. of secs. 7, 8, 17 and 18, perpetuated by R. Guy Doty, Nevada Professional Land Surveyor No. 7635, monumented with a brass tablet, 2 ins. diam., firmly set flush in a concrete pad, 12x12 ins., with top mkd. S7 S8 S17 S18 PLS 7635, with a limestone, 10x8x4 ins. (Record, wooden post, 4 ins. sq.), plainly mkd. with 4 grooves on S. face and 5 grooves on E. face, loosely set alongside, in mound of stone, 5 ft. base, 1 ft. high, as recorded in Clark County, Nevada, File 67, Page 9 of Surveys.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <hr/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>N. 89°52'20" W., bet. secs. 8 and 17.</p> <p>Over ridges and thru valleys.</p>
36.10	Single pole powerline, bears SE. and NW.
39.974	<p>The 1/4 sec. cor. of secs. 8 and 17, reestablished by R. Guy Doty, Nevada Professional Land Surveyor No. 7635, monumented with an aluminum tablet, 2 ins. diam., firmly set flush in a concrete slab, 12x12 ins., mkd. 1/4 8 17 PLS 7635, as recorded in Clark County, Nevada, File 67, Page 9 of Surveys. This is accepted as a careful and faithful reestablishment of the position of the original corner.</p> <hr/> <p>N. 89°52'20" W., beginning new measurement.</p>
2.00	Underground water line, bears SE. and NW.
19.987	<p>The W 1/16 sec. cor. of secs. 8 and 17, determined by R. Guy Doty, Nevada Professional Land Surveyor No. 7635, monumented with a rebar, 5/8 in. diam., firmly set, projecting 1 in. above a concrete slab, 16x16 ins., with aluminum cap, 1 1/2 ins. diam., mkd. R GUY DOTY PLS 7635, as recorded in Clark County, Nevada, File 67, Page 9 of Surveys. This is accepted as a careful and faithful determination of the position of the corner.</p> <hr/> <p>N. 89°52'20" W., beginning new measurement.</p>
12.30	Muddy River, 40 lks. wide, 2 ft. deep, course SE.
17.70	Center of Union Pacific Railroad tracks, bears SE. and NW.
19.987	<p>The cor. of secs. 7, 8, 17 and 18.</p> <hr/> <p>S. 89°46'30" W., bet. secs. 7 and 18.</p> <p>Over rolling terrain.</p>
20.380	<p>Point for the E 1/16 sec. cor. of secs. 7 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>S 7</p> <p>E 1/16 ———</p> <p>S18</p> <p>2009</p> </div>
40.760	<p>The 1/4 sec. cor. of secs. 7 and 18, reestablished by R. Guy Doty, Nevada Professional Land Surveyor No. 7635, monumented with a brass tablet, 2 ins. diam., firmly set flush in limestone outcrop, with top mkd. T15S R67E 1/4 7 18 PLS 7635, as recorded in Clark County, Nevada, File 147, Page 26 of Surveys, with a</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>steel fence post alongside and a mound of stone, 3 ft. base, 2 ft. high, E. of cor. This is accepted as a careful and faithful reestablishment of the position of the original corner.</p> <hr/> <p>S. 89°46'30" W., beginning new measurement.</p>
20.382	<p>The W 1/16 sec. cor. of secs. 7 and 18, determined by R. Guy Doty, Nevada Professional Land Surveyor No. 7635, monumented with a rebar, 5/8 in. diam., firmly set flush with the surface of the ground, with aluminum cap, 1 1/2 ins. diam., mkd. R GUY DOTY PLS 7635, as recorded in Clark County, Nevada, File 147, Page 26 of Surveys, with a steel fence post alongside. This is accepted as a careful and faithful determination of the position of the corner.</p> <hr/> <p>S. 89°46'30" W., beginning new measurement.</p>
3.20	Dry wash, 50 lks. wide, drains N.
4.20	Dry wash, 40 lks. wide, drains NE.
20.286	<p>The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 0°06'20" W., bet. secs. 7 and 8.</p> <p>Over low rolling hills.</p>
3.70	Center of Union Pacific Railroad tracks, bears SE. and NW.
20.006	<p>The S 1/16 sec. cor. of secs. 7 and 8, determined by R. Guy Doty, Nevada Professional Land Surveyor No. 7635, monumented with an aluminum tablet, 1 1/2 ins. diam., firmly set flush in a concrete slab, 12x12 ins., markings unreadable, as recorded in Clark County, Nevada, File 147, Page 26 of Surveys, with a steel fence post alongside, and is accepted as a careful and faithful determination of the position of the corner.</p> <hr/> <p>N. 0°06'20" W., beginning new measurement.</p>
0.60	Muddy River, 40 lks. wide, 2 ft. deep, course NE.
5.60	Underground water line, bears SE. and NW.
8.00	Single pole powerline, bears SE. and NW.
20.006	<p>The 1/4 sec. cor. of secs. 7 and 8, reestablished by R. Guy Doty, Nevada Professional Land Surveyor No. 7635, monumented with a brass tablet, 2 ins. diam., firmly set flush in a concrete slab, 12x12 ins., mkd. T15S R67E 1/4 7 8 PLS 7635, as recorded in Clark County, Nevada, File 147, Page 26 of Surveys, encircled in a mound of stone, 6 ft. base, 1 ft. high, with a steel fence post alongside, and is accepted as a careful and faithful reestablishment of the position of the original corner.</p> <hr/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°06'20" W., beginning new measurement.
20.006	Point for the N 1/16 sec. cor. of secs. 7 and 8. POINT NOT MONUMENTED
40.012	The cor. of secs. 5, 6, 7 and 8, perpetuated by R. Guy Doty, Nevada Professional Land Surveyor No. 7635, monumented with a brass tablet, 2 ins. diam., firmly set flush in a concrete slab, 12x12 ins., surrounded in a mound of stone, 5 ft. base, 2 ft. high, with a wooden post, 4x4 ins. (Record, limestone, 20x17x10 ins.), alongside, with brass top mkd. T15S R67E 5 6 7 8 PLS 7635, as recorded in Clark County, Nevada, File 147, Page 26 of Surveys. This is accepted as a careful and faithful perpetuation of the position of the original corner. From the cor. of secs. 4, 5, 8 and 9. N. 89°22'40" W., bet. secs. 5 and 8. Over rolling hills.
3.10	Dry wash, 50 lks. wide, drains SSW.
4.90	Center of asphalt surface, Nevada State Route 169, 42 lks. wide, bears SE. and NW.
16.70	Double pole powerline, bears SE. and NW.
19.60	Double pole powerline, bears SE. and NW.
40.236	The 1/4 sec. cor. of secs. 5 and 8, perpetuated by R. Guy Doty, Nevada Professional Land Surveyor No. 7635, recovering a wooden post, 4 ins. sq. (Record, sandstone, 18x11x5 ins.) set in a rock mound and remonumented with a brass tablet, 2 ins. diam., firmly set flush in a concrete slab, 12x12 ins., with top mkd. T15S R67E 1/4 5 8 PLS 7635, as shown on the unrecorded survey plat "Record Map of Survey for Reilly C. Jensen", obtained from R. Guy Doty during the course of this survey, and is accepted as a careful and faithful perpetuation of the position of the original corner. N. 87°07'10" W., beginning new measurement.
39.858	The cor. of secs. 5, 6, 7 and 8. S. 89°45'00" W., bet. secs. 6 and 7. Over rolling hills.
20.005	Point for the E 1/16 sec. cor. of secs. 6 and 7. POINT NOT MONUMENTED
40.010	The 1/4 sec. cor. of secs. 6 and 7, reestablished by R. Guy Doty, Nevada Professional Land Surveyor No. 7635, monumented with a brass tablet, 2 ins. diam., firmly set flush in a concrete slab, 12x12 ins., surrounded in a mound of stone, 3 ft. base, 1 ft. high, with top mkd. T15S R67E 1/4 6 7 PLS 7635, as

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>recorded in Clark County, Nevada, File 147, Page 26 of Surveys, and is accepted as a careful and faithful reestablishment of the position of the original corner.</p> <hr/> <p>S. 89°45'00" W., beginning new measurement.</p>
14.70	Underground water line, bears SE. and NW.
17.10	Single pole powerline, bears SE. and NW.
20.005	<p>The W 1/16 sec. cor. of secs. 6 and 7, determined by R. Guy Doty, Nevada Professional Land Surveyor No. 7635, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set flush with the surface of the ground, with aluminum cap, 1 1/2 ins. diam., mkd. R GUY DOTY PLS 7635, as recorded in Clark County, Nevada, File 147, Page 26 of Surveys, and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>S 6 W 1/16 — S 7</p> <p>2009</p> </div> <p>Bury the rebar alongside the stainless steel post.</p> <p>From this point, the most southerly cor. of a brick pumphouse, 33.5x28 ft., bears N. 46°20' E., 3.50 chs. dist., the long side of which bears N. 43° W. and S. 43° E.</p> <hr/> <p>S. 89°45'00" W., beginning new measurement.</p>
19.905	<p>The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. of 5, 6, 7 and 8.</p> <p>N. 1°33'20" W., bet. secs. 5 and 6.</p> <p>Over low rolling hills.</p>
26.00	Double pole powerline, bears SE. and NW.
39.80	Double pole powerline, bears SE. and NW.
39.974	<p>Point for the 1/4 sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the position of the original corner.</p> <p>Set a copper coated steel stake, 1/2 in. diam., 24 ins. long, 10 ins. below the surface of the ground, with cap, 1 1/2 ins. diam., mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>T15S R67E 1/4 S 6 S 5 2009</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 10°50' E., 87.0 lks. dist., with brass cap mkd. RM 1/4 S5 57.4 FT TO COR 2009 and an arrow pointing to corner.</p> <p>A brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented flush in drill hole in a limestone boulder, for a reference monument, bears S. 37°07' W., 79.2 lks. dist., mkd. RM 1/4 S6 52.3 FT TO COR 2009 and an arrow pointing to the corner.</p> <p>Cor. is located in powerline road, 20 lks. wide, bears SE. and NW.</p> <p>79.818 The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp. hereinbefore described.</p>
	<hr/> <p>SUBDIVISION OF SECTION 7, T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 7 and 18.</p> <p>N. 0°25'30" E., on the N-S centerline of sec. 7.</p> <p>Over steep and rocky ridges.</p> <p>20.002 The C-S 1/16 sec. cor. of sec. 7, determined by R. Guy Doty, Nevada Professional Land Surveyor No. 7635, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set flush with the surface of the ground, with aluminum cap, 1 1/2 ins. diam., mkd. R GUY DOTY PLS 7635, as recorded in Clark County, Nevada, File 147, Page 26 of Surveys, and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p>S 1/16 $\begin{array}{c} C \\ \\ C \end{array}$ S 7</p> <p>2009</p> <p>Bury the rebar alongside the stainless steel post.</p> <hr/>

SUBDIVISION OF SECTION 7,
T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°25'30" E., beginning new measurement.
0.10	Center of Union Pacific Railroad tracks, bears SE. and NW.
2.50	Muddy River, 40 lks. wide, 2 ft. deep, course NE.
20.002	<p>The center 1/4 sec. cor. of sec. 7, determined by R. Guy Doty, Nevada Professional Land Surveyor No. 7635, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 1 in. above the ground, with aluminum cap, 1 1/2 ins. diam., mkd. R GUY DOTY PLS 7635, as recorded in Clark County, Nevada, File 147, Page 26 of Surveys, and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T15S R67E C 1/4 S 7</p> <p style="text-align: center;">2009</p> <p>Bury the rebar alongside the stainless steel post.</p> <hr/> <p>N. 0°25'30" E., beginning new measurement.</p>
20.002	<p>Point for the C-N 1/16 sec. cor. of sec. 7.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented flush in drill hole on a limestone outcrop, with top mkd.</p> <p style="text-align: center;">C N 1/16 S 7 C</p> <p style="text-align: center;">2009</p>
30.10	Single pole powerline, bears SE. and NW.
31.40	Underground water line, bears SE. and NW.
40.004	<p>The 1/4 sec. cor. of secs. 6 and 7.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 7 and 8.</p> <p>S. 89°45'40" W., on the E-W centerline of sec. 7.</p> <p>Over low rolling hills.</p>
2.80	Single pole powerline, bears SE. and NW.
15.60	Underground water line, bears SE. and NW.
20.193	The C-E 1/16 sec. cor. of sec. 7, determined by R. Guy Doty, Nevada Professional Land Surveyor No. 7635, monumented with an aluminum tablet, 1 1/2 ins. diam., firmly set, projecting 1 in. above a concrete slab, 16x12 ins., with top mkd. R GUY DOTY PLS

SUBDIVISION OF SECTION 7,
T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	7635, as recorded in Clark County, Nevada, File 147, Page 26 of Surveys, with a wooden railroad tie alongside, and is accepted as a careful and faithful determination of the position of the corner.
	<hr/>
	S. 89°45'40" W., beginning new measurement.
20.193	The center 1/4 sec. cor. of sec. 7.
	<hr/>
	S. 89°45'40" W., beginning new measurement.
20.193	Point for the C-W 1/16 sec. cor. of sec. 7.
	POINT NOT MONUMENTED
39.85	Muddy River, 40 lks. wide, 2 ft. deep, course SE.
40.289	The 1/4 sec. cor. of secs. 7 and 12, on the W. bdy. of the Tp.
	<hr/>
	From the C-E 1/16 sec. cor. of sec. 7.
	N. 0°09'40" E., on the N-S centerline of the NE1/4 of sec. 7.
5.10	Underground water line, bears SE. and NW.
17.60	Single pole powerline, bears SE. and NW.
20.004	Point for the NE 1/16 sec. cor. of sec. 7, at intersection with the E-W centerline of the NE1/4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.
	NE 1/16 S 7
	2009
40.006	The point for the E 1/16 sec. cor. of secs. 6 and 7.
	<hr/>
	From the point for the N 1/16 sec. cor. of secs. 7 and 8.
	S. 89°45'20" W., on the E-W centerline of the NE1/4 of sec. 7.
20.098	The NE 1/16 sec. cor. of sec. 7.
21.60	Dry wash, 50 lks. wide, drains SW.
25.90	Single pole powerline, bears SE. and NW.
27.50	Underground water line, bears SE. and NW.
40.196	The C-N 1/16 sec. cor. of sec 7.
	<hr/>

SUBDIVISION OF SECTION 7,
T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the E 1/16 sec. cor. of secs. 7 and 18.</p> <p>N. 0°09'40" E., on the N-S centerline of the SE1/4 of sec. 7.</p>
18.90	Center of Union Pacific Railroad tracks, bears SE. and NW.
20.004	<p>The SE 1/16 sec. cor. of sec. 7, determined by R. Guy Doty, Nevada Professional Land Surveyor No. 7635, monumented with an aluminum tablet, 1 1/2 ins. diam., firmly set, projecting 1 in. above a concrete slab, 16x12 ins., with top mkd. R GUY DOTY PLS 7635, as recorded in Clark County, Nevada, File 147, Page 26 of Surveys, and is accepted as a careful and faithful determination of the position of the corner.</p> <hr/> <p>N. 0°09'40" E., beginning new measurement.</p>
7.20	Muddy River, 40 lks. wide, 2 ft. deep, course NE.
20.002	<p>The C-E 1/16 sec. cor. of sec. 7.</p> <hr/> <p>From the S 1/16 sec. cor. of secs. 7 and 8.</p> <p>S. 89°46'10" W., on the E-W centerline of the SE1/4 of sec. 7.</p>
8.50	Muddy River, 40 lks. wide, 2 ft. deep, course NE.
20.287	<p>The SE 1/16 sec. cor. of sec. 7.</p> <hr/> <p>S. 89°46'10" W., beginning new measurement.</p>
5.20	Center of Union Pacific Railroad tracks, bears SE and NW.
15.40	Center of Union Pacific Railroad tracks, bears NE. and SW.
19.80	Center of Union Pacific Railroad tracks, bears SE. and NW.
20.286	<p>The C-S 1/16 sec. cor. of sec. 7.</p> <hr/> <p>From the point for the C-W 1/16 sec. cor. of sec. 7.</p> <p>N. 0°41'40" E., on the N-S centerline of the NW1/4 of sec. 7.</p>
20.000	<p>The NW 1/16 sec. cor. of sec. 7, determined by R. Guy Doty, Nevada Professional Land Surveyor No. 7635, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 2 ins. above the ground, with aluminum cap, 1 1/2 ins. diam., mkd. R GUY DOTY PLS 7635, as recorded in Clark County, Nevada, File 147, Page 26 of Surveys, and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a collar of stone, with brass cap mkd.</p>

SUBDIVISION OF SECTION 7,
T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	NW 1/16 S 7
	2009
	Bury the rebar alongside the stainless steel post.
	N. 0°41'40" E., beginning new measurement.
20.001	The W 1/16 sec. cor. of secs. 6 and 7.
	From the C-N 1/16 sec. cor. of sec. 7.
	S. 89°45'20" W., on the E-W centerline of the NW1/4 of sec. 7.
20.099	The NW 1/16 sec. cor. of sec. 7.
	S. 89°45'20" W., beginning new measurement.
20.001	The N 1/16 sec. cor. of secs. 7 and 12, on the W. bdy. of the Tp.
<p style="text-align: center;">SUBDIVISION OF SECTION 8, T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA</p>	
	From the 1/4 sec. cor. of secs. 8 and 17.
	N. 0°13'40" W., on the N-S centerline of sec. 8.
	Over low rolling hills.
0.40	Single pole powerline, bears SE. and NW.
20.177	Point for the C-S 1/16 sec. cor. of sec. 8.
	POINT NOT MONUMENTED
32.50	Dry wash, 40 lks. wide, drains SW.
33.00	Jeep trail, 20 lks. wide, bears NE. and SW.
40.354	The center 1/4 sec. cor. of sec. 8, determined by R. Guy Doty, Nevada Professional Land Surveyor No. 7635, monumented with a brass tablet, 2 ins. diam., firmly set flush in a concrete slab, 12x12 ins., with top mkd. T15S R67E CTR 1/4 SEC 8 PLS 7635, as shown on the unrecorded survey plat "Record Map of Survey for Reilly C. Jensen", obtained from R. Guy Doty during the course of this survey, and is accepted as a careful and faithful determination of the position of the corner.
	N. 0°13'20" W., beginning new measurement.
37.754	The 1/4 sec. cor. of secs. 5 and 8.

SUBDIVISION OF SECTION 8,
T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the 1/4 sec. cor. of secs. 8 and 9.</p> <p>S. 89°38'40" W., on the E-W centerline of sec. 8.</p> <p>Over low rolling hills.</p>
31.80	Dry wash, 40 lks. wide, drains SW.
32.00	Jeep trail, 20 lks. wide, bears NE. and SW.
41.337	The center 1/4 sec. cor. of sec. 8.
	<hr/> <p>S. 89°38'20" W., beginning new measurement.</p>
19.942	Point for the C-W 1/16 sec. cor. of sec. 8.
	POINT NOT MONUMENTED
38.884	The 1/4 sec. cor. of secs. 7 and 8.
	<hr/> <p>From the W 1/16 sec. cor. of secs. 8 and 17.</p> <p>N. 0°09'30" W., on the N-S centerline of the SW1/4 of sec. 8.</p>
8.60	Underground water line, bears SE. and NW.
20.092	<p>The SW 1/16 sec. cor. of sec. 8, determined by R. Guy Doty, Nevada Professional Land Surveyor No. 7635, monumented with an aluminum tablet, 1 1/2 ins. diam., firmly set, projecting 1 in. above a concrete slab, 16x12 ins., with top mkd. R GUY DOTY PLS 7635, as shown on the unrecorded survey plat "Map of Record for Reilly C. Jensen", obtained from R. Guy Doty during the course of this survey, with a steel fence post alongside, and is accepted as a careful and faithful determination of the position of the corner.</p> <hr/> <p>N. 0°10'10" W., beginning new measurement.</p>
0.20	Single pole powerline, bears SE. and NW.
20.091	The point for the C-W 1/16 sec. cor. of sec. 8.
	<hr/> <p>From the point for the C-S 1/16 sec. cor. of sec. 8.</p> <p>S. 89°53'10" W., on the E-W centerline of the SW1/4 of sec. 8.</p>
19.80	Single pole powerline, bears SE. and NW.
19.964	The SW 1/16 sec. cor. of sec. 8.
	<hr/> <p>S. 89°53'10" W., beginning new measurement.</p>
12.20	Underground water line, bears SE. and NW.
14.80	Muddy River, 40 lks. wide, 2 ft. deep, course SE.

SUBDIVISION OF SECTION 8,
T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
19.964	The S 1/16 sec. cor. of secs. 7 and 8.
	<hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 15, T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>
	From 1/4 sec. cor. of secs. 15 and 22.
	N. 1°02'20" W., on the N-S centerline of sec. 15.
	Over flats with low rolling hills.
40.838	Point for the center 1/4 sec. cor. of sec. 15, at intersection with the E-W center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T15S R67E C 1/4 S15 2009
46.30	Barbed wire fence, bears E. and W.
61.249	Point for the C-N 1/16 sec. cor. of sec 15.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	$\begin{array}{c} C \\ N\ 1/16\ \left \right. S15 \\ C \end{array}$ 2009
68.50	Double pole powerline, bears SE. and NW.
70.40	Double pole powerline, bears SE. and NW.
81.660	The 1/4 sec. cor. of secs. 10 and 15.
	<hr/> <p>From the 1/4 sec. cor. of secs. 14 and 15.</p> <p>N. 88°02'00" W., on the E-W centerline of sec. 15.</p> <p>Over flats and low rolling hills.</p>
40.711	The center 1/4 sec. cor. of sec. 15.
60.939	Point for the C-W 1/16 sec. cor. of sec. 15.
	POINT NOT MONUMENTED
65.10	Center of asphalt surface, Nevada State Route 169, 42 lks. wide, bears SE. and NW.

SUBDIVISION OF SECTION 15,
T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
81.167	<p>The 1/4 sec. cor. of secs. 15 and 16.</p> <hr/> <p>From the point for the C-W 1/16 sec. cor. of sec. 15.</p> <p>N. 0°47'40" W., on the N-S centerline of the NW1/4 of sec. 15.</p> <p>Over flats and rolling hills.</p>
20.547	<p>Point for the NW 1/16 sec. cor. of sec. 15, at intersection with the E-W centerline of the NW1/4.</p> <p>POINT NOT MONUMENTED</p> <p>From this point, a position determined by Brent Ross Woolsey, Nevada Professional Land Surveyor No. 4301, monumented with a rebar, 1/2 in. diam., with plastic cap mkd. PLS 4301, as recorded in Clark County, Nevada, File 21, Page 19 of Parcels, bears N. 0°17'50" W., 0.252 chs. dist. This point was determined using improper control and is not utilized during the course of this survey.</p>
41.094	<p>The point for the W 1/16 sec. cor. of secs. 10 and 15.</p> <hr/> <p>From the C-N 1/16 sec. cor. of sec. 15.</p> <p>N. 87°38'10" W., on the E-W centerline of the NW1/4 of sec. 15.</p>
20.147	<p>The point for the NW 1/16 sec. cor. of sec. 15.</p>
36.702	<p>From this point, a property corner, determined by Brent Ross Woolsey, Nevada Professional Land Surveyor No. 4301, monumented with a rebar, 1/2 in. diam., with plastic cap mkd. PLS 4301, as recorded in Clark County, Nevada, Record of Survey File No. 21, Page No. 54, bears SOUTH, 0.069 chs. dist.</p>
37.70	<p>Center of asphalt surface, Nevada State Route 169, 42 lks. wide, bears SE. and NW.</p>
38.533	<p>From this point, a property corner, determined by Brent Ross Woolsey, Nevada Professional Land Surveyor No. 4301, monumented with a rebar, 1/2 in. diam., with plastic cap mkd. PLS 4301, as recorded in Clark County, Nevada, Record of Survey File No. 21, Page No. 54, bears SOUTH, 0.039 chs. dist.</p>
40.294	<p>The N 1/16 sec. cor. of secs. 15 and 16.</p> <hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 16, T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 16 and 21.</p> <p>N. 0°51'50" W., on the N-S centerline of sec. 16.</p> <p>Over rolling hills.</p>
19.10	<p>Spur, slopes W.</p>

SUBDIVISION OF SECTION 16,
T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.526	<p>Point for the C-S 1/16 sec. cor. of sec. 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} C \\ S\ 1/16\ \ S16 \\ C \end{array}$ <p>2009</p> </div>
21.40	Dry wash, 20 lks. wide, drains W.
23.00	Underground telephone line, bears SE. and NW.
41.052	<p>The center 1/4 sec. cor. of sec. 16, determined by James H. Turner, Nevada Professional Land Surveyor No. 10356, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 1 in. above the ground, with aluminum cap, 1 1/2 ins. diam., mkd 1996 C1/4 S16 PLS 10356, as recorded in Clark County, Nevada, File 87, Page 17 of Surveys, and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T15S R67E C 1/4 S16</p> <p>2009</p> </div> <p>Bury the rebar alongside the stainless steel post.</p> <p>From this point, the SW cor. of the Solid Waste Convenience Center Site for Moapa Valley, monumented with a rebar, 5/8 in. diam., firmly set 12 ins. below the surface of the ground, as recorded in Clark County, Nevada, File 107, Page 32 of Surveys, bears N. 24°26'00" E., 11.762 chs. dist.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 0°51'50" W., beginning new measurement.</p>
6.20	Single pole powerline, bears SE. and NW.
41.00	Dry wash, 40 lks. wide, drains SE.
42.672	<p>The 1/4 sec. cor. of secs. 9 and 16.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>From the 1/4 sec. cor. of secs. 15 and 16.</p> <p>S. 89°01'50" W., on the E-W centerline of sec. 16.</p> <p>Over low rolling hills.</p>
20.073	Point for the C-E 1/16 sec. cor. of sec. 16.

SUBDIVISION OF SECTION 16,
T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	POINT NOT MONUMENTED
22.50	Underground water line, bears SE. and NW.
30.30	Single pole powerline, bears SE. and NW.
35.00	Center of asphalt surface, Solid Waste Convenience Center access road, 33 lks. wide, bears SE. and NW.
40.146	The center 1/4 sec. cor. of sec. 16.
	<hr/>
	S. 89°01'30" W., beginning new measurement
21.80	Underground telephone line, bears SE. and NW.
39.659	The 1/4 sec. cor. of secs. 16 and 17.
	<hr/>
	From the E 1/16 sec. cor. of secs. 16 and 21.
	N. 0°42'20" W., on the N-S centerline of the SE1/4 of sec. 16.
8.20	South rim of gravel pit, bears SE. and NW.
18.40	North rim of gravel pit, bears E. and SW.
20.609	Point for the SE 1/16 sec. cor. of sec. 16, at intersection with the E-W center line of the SE 1/4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	SE 1/16 S16
	2009
35.00	Single pole powerline, bears SE. and NW.
39.50	Underground water line, bears SE. and NW.
41.218	The point for the C-E 1/16 sec. cor. of sec. 16.
	<hr/>
	From the S 1/16 sec. cor. of secs. 15 and 16.
	S. 89°16'10" W., on the E-W centerline of the SE1/4 of sec. 16.
20.016	The SE 1/16 sec. cor. of sec. 16.
30.90	Center of asphalt surface, Solid Waste Convenience Center access road, 33 lks. wide, bears SE. and NW.
37.10	Underground telephone line, bears SE. and NW.
40.034	The C-S 1/16 sec. cor. of sec. 16.
	<hr/>

SUBDIVISION OF SECTION 16,
T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	S. 89°16'00" W., on the E-W centerline of the SW1/4 of sec. 16.
4.50	Dry wash, 30 lks. wide, drains SE.
39.791	The S. 1/16 sec. cor. of secs. 16 and 17.
<hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 17 T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>	
	From the 1/4 sec. cor. of secs. 17 and 20.
	N. 0°03'20" W., on the N-S centerline of sec. 17.
	Over low rolling hills.
15.40	Muddy River, 40 lks. wide, 2 ft. deep, course SE.
20.284	Point for the C-S 1/16 sec. cor. of sec. 17.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	$\begin{array}{c} C \\ S\ 1/16 \quad \quad S17 \\ C \end{array}$
	2009
29.40	Center of Union Pacific Railroad tracks, bears SE. and NW.
40.568	The center 1/4 sec. cor. of sec. 17, determined by R. Guy Doty, Nevada Professional Land Surveyor No. 7635, monumented with an aluminum tablet, 2 ins. diam., firmly set flush in a concrete slab, 12x12 ins., with top mkd. CTR 1/4 SEC 17 PLS 7635, as recorded in Clark County, Nevada, File 67, Page 9 of Surveys, and is accepted as a careful and faithful determination of the position of the corner.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	<hr/>
	N. 0°03'50" W., beginning new measurement.
20.199	The C-N 1/16 sec. cor. of sec. 17, determined by R. Guy Doty, Nevada Professional Land Surveyor No. 7635, monumented with an aluminum tablet, 1 1/2 ins. diam., firmly set flush in a concrete slab, 16x16 ins., with top mkd. CS 1/16 SEC 17 PLS 7635, as recorded in Clark County, Nevada, File 67, Page 9 of Surveys, and is accepted as a careful and faithful determination of the position of the corner.
	<hr/>
	N. 0°03'10" W., beginning new measurement.
6.00	Single pole powerline, bears NE. and SW.
17.40	Underground water line, bears SE. and NW.

SUBDIVISION OF SECTION 17,
T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.203	The 1/4 sec. cor. of secs. 8 and 17.
	<hr/> <p>From the 1/4 sec. cor. of secs. 16 and 17.</p> <p>N. 89°25'40" W., on the E-W centerline of sec. 17.</p>
12.90	Single pole powerline, bears SE. and NW.
20.144	<p>The C-E 1/16 sec. cor. of sec. 17, determined by R. Guy Doty, Nevada Professional Land Surveyor No. 7635, monumented with a rebar, 5/8 in. diam., firmly set in a concrete slab, 12x12 ins., projecting 1 in. above the concrete, with aluminum cap, 1 1/2 ins. diam., mkd. R GUY DOTY PLS 7635, as recorded in Clark County, Nevada, File 147, Page 27 of Surveys, and is accepted as a careful and faithful determination of the position of the corner.</p> <hr/>
	N. 89°25'40" W., beginning new measurement.
10.072	<p>The C-W-E 1/64 sec. cor. of sec. 17, determined by R. Guy Doty, Nevada Professional Land Surveyor No. 7635, monumented with an aluminum cap, 1 1/2 ins. diam., firmly set flush in a concrete slab, 18x18 ins., with top mkd. R GUY DOTY PLS 7635, as recorded in Clark County, Nevada, File No. 147, Page 27 of Surveys, and is accepted as a careful and faithful determination of the position of the corner.</p> <hr/>
	N. 89°25'40" W., beginning new measurement.
10.072	The center 1/4 sec. cor. of sec. 17.
	<hr/> <p>N. 89°26'10" W., beginning new measurement.</p>
12.40	Center of Union Pacific Railroad tracks, bears SE. and NW.
18.60	Muddy River, 40 lks. wide, 2 ft. deep, course SE.
20.383	<p>The C-W 1/16 sec. cor. of sec. 17, determined by R. Guy Doty, Nevada Professional Land Surveyor No. 7635, monumented with a rebar, 5/8 in. diam., firmly set in a concrete slab, 12x12 ins., projecting 3 ins. above the concrete, with aluminum cap, 1 1/2 ins. diam., mkd. R GUY DOTY PLS 7635, as recorded in Clark County, Nevada, File 67, Page 9 of Surveys, with a carsonite post alongside, and is accepted as a careful and faithful determination of the position of the corner.</p>
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

SUBDIVISION OF SECTION 17,
T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">W 1/16 C——C S17 2010</p>
	<p>Bury the rebar alongside the stainless steel post.</p> <hr/> <p>N. 89°26'10" W., beginning new measurement.</p>
20.383	<p>The 1/4 sec. cor. of secs. 17 and 18.</p> <hr/> <p>From the point for the E 1/16 sec. cor. of secs. 17 and 20.</p> <p>N. 0°16'20" W., on the N-S centerline of the SE1/4 of sec. 17.</p>
3.10	Muddy River, 40 lks. wide, 2 ft. deep, course SE.
11.90	Center of Union Pacific Railroad tracks, bears SE. and NW.
20.319	<p>The SE 1/16 sec. cor. of sec. 17, determined by R. Guy Doty, Nevada Professional Land Surveyor No. 7635, monumented with an aluminum tablet, 1 1/2 ins. diam., firmly set flush in a concrete slab, 24x18 ins., with top mkd. R GUY DOTY PLS 7635, as recorded in Clark County, Nevada, File 147, Page 27 of Surveys, with a steel fence post alongside, and is accepted as a careful and faithful determination of the position of the corner.</p> <hr/> <p>N. 0°16'40" W., beginning new measurement.</p>
20.321	<p>The C-E 1/16 sec. cor. of sec. 17.</p> <hr/> <p>From the S 1/16 sec. cor. of secs. 16 and 17.</p> <p>N. 89°19'50" W., on the E-W centerline of the SE1/4 of sec. 17.</p>
20.223	<p>The SE 1/16 sec. cor. of sec. 17.</p> <hr/> <p>N. 89°19'30" W., beginning new measurement.</p>
3.60	Center of Union Pacific Railroad tracks, bears SE. and NW.
10.113	<p>The C-W-SE 1/64 sec. cor. of sec. 17, determined by R. Guy Doty, Nevada Professional Land Surveyor No. 7635, monumented with an aluminum tablet, 1 1/2 ins. diam., firmly set flush in a concrete slab, 24x36 ins., with top mkd. R GUY DOTY PLS 7635, as recorded in Clark County, Nevada, File 147, Page 27 of Surveys, with a steel fence post alongside, and is accepted as a careful and faithful determination of the position of the corner.</p> <hr/> <p>N. 89°19'30" W., beginning new measurement.</p>
10.113	<p>The C-S 1/16 sec. cor. of sec. 17.</p> <hr/>

SUBDIVISION OF SECTION 17,
T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the point for the W 1/16 sec. cor. of secs. 17 and 20.</p> <p>N. 0°10'30" W., on the N-S centerline of the SW1/4 of sec. 17.</p>
20.249	<p>Point for the SW 1/16 sec. cor. of sec. 17, at intersection with the E-W center line of the SW 1/4.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented flush in drill hole on limestone outcrop, with top mkd.</p> <p style="text-align: center;">SW 1/16 S17</p> <p style="text-align: center;">2009</p> <p>Raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.</p>
40.498	<p>The C-W 1/16 sec. cor. of sec. 17.</p> <hr/> <p>From the C-S 1/16 sec. cor. of sec. 17</p> <p>N. 89°20'10" W., on the E-W centerline of the SW1/4 of sec. 17.</p>
3.20	Muddy River, 40 lks. wide, 2 ft. deep, course SE.
20.342	The SW 1/16 sec. cor. of sec. 17.
40.684	<p>The point for the S 1/16 sec. cor. of secs. 17 and 18.</p> <hr/> <p>From the C-W 1/16 sec. cor. of sec. 17.</p> <p>N. 0°30'00" E., on the N-S centerline of the NW1/4 of sec. 17.</p>
7.90	Center of Union Pacific Railroad tracks, bears SE. and NW.
12.30	Muddy River, 40 lks. wide, 2 ft. deep, course SE.
20.125	<p>The NW 1/16 sec. cor. of sec. 17, determined by R. Guy Doty, Nevada Professional Land Surveyor No. 7635, monumented with an aluminum tablet, 2 ins. diam., firmly set flush in a concrete slab, 12x12 ins., with top mkd. NW 1/16 PLS 7635, as recorded in Clark County, Nevada, File 67, Page 9 of Surveys, with a steel fence post alongside, and is accepted as a careful and faithful determination of the position of the corner.</p> <hr/> <p>N. 0°30'00" E., beginning new measurement.</p>
20.122	<p>The W 1/16 sec. cor. of secs. 8 and 17.</p> <hr/> <p>From the C-N 1/16 sec. cor. of sec. 17.</p> <p>N. 89°38'30" W., on the E-W center of the NW1/4 of sec. 17.</p>
20.183	<p>The NW 1/16 sec. cor. of sec. 17.</p> <hr/>

SUBDIVISION OF SECTION 17,
T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 89°39'30" W., beginning new measurement.
20.184	<p>The point for the N 1/16 sec. cor. of secs. 17 and 18.</p> <hr/> <p>GENERAL DESCRIPTION</p> <p>The north half of T. 15 S., R. 67 E. is located approximately 2 miles north of Logandale, Nevada. The Muddy River traverses thru the township in a southeasterly direction. The elevation ranges from about 1500 to 1900 feet above sea level. The soil ranges from sandy to very rocky. The vegetation consists of greasewood and bud sage on the flats with tamarack along the river bottom.</p> <p>Access to the area is provided by Nevada State Route 169 and by several trails roads traversing the area.</p> <hr/>

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Michelle E. Martin	Supervisory Range Technician
Matthew J. White	Supervisory Range Technician
Edward J. Graham, Jr.	Surveying Technician
Jonathan Grayson	Surveying Technician

CERTIFICATE OF SURVEY

I, Don R. Aschenbach, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 28th day of September, 2006, I have dependently resurveyed a portion of the west boundary, the north boundary and a portion of the subdivisional lines, and subdivided certain sections, Township 15 South, Range 67 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

September 13, 2011

(Date)

Don R. Aschenbach
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of the dependent resurvey of a portion of the west boundary, the north boundary and a portion of the subdivisional lines, and the subdivision of certain sections, Township 15 South, Range 67 East, Mount Diablo Meridian, Nevada, executed by Don R. Aschenbach, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

September 13, 2011

(Date)

David P. Moran
(Chief Cadastral Surveyor for Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 15 S., R. 67 E., Mount Diablo Meridian, Nevada, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor for Nevada)~~