

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

THE THIRD STANDARD PARALLEL NORTH
THROUGH A PORTION OF RANGE 20 EAST
AND A PORTION OF THE SUBDIVISIONAL LINES,
THE SUBDIVISION OF SECTION 36
AND A METES-AND-BOUNDS SURVEY OF A PORTION
OF THE CENTERLINE OF U.S. HIGHWAY NO. 50,
TOWNSHIP 16 NORTH, RANGE 20 EAST,
OF THE MOUNT DIABLO MERIDIAN,
IN THE STATE OF NEVADA

EXECUTED BY

Clarence D. Strickland, Cadastral Surveyor

Under Special Instructions dated November 20, 2012,
and approved November 20, 2012,
which provided for the surveys included under Group No. 920,
and Assignment Instructions dated November 20, 2012.

Survey commenced December 3, 2012

Survey completed March 18, 2014

INDEX DIAGRAM

TOWNSHIP 16 NORTH, RANGE 20 EAST, MOUNT DIABLO MERIDIAN, NEVADA

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	5 36 2

Subdivision of Section 36 pp. 6 - 8.
 Metes-and-Bounds Survey of a Portion of the Centerline of
 U. S. Highway No. 50 pp. 9 - 10.

TOWNSHIP 16 NORTH, RANGE 20 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The following field notes are those of the dependent resurvey of the Third Standard Parallel North through a portion of Range 20 East and a portion of the subdivisional lines, the subdivision of section 36 and a metes-and-bounds survey of a portion of the centerline of U.S. Highway No. 50, Township 16 North, Range 20 East, Mount Diablo Meridian, Nevada.

The south (Third Standard Parallel North) and east (Carson River Guide Meridian) boundaries were surveyed by U.S. Deputy Surveyor B. Ives in 1861 under Contract "A". The west and north boundaries were surveyed by U.S. Deputy Surveyor J.S. Lawson in 1861 under Contract "B". A portion of the subdivisional lines and the meanders of Washoe Lake were surveyed by U.S. Deputy Surveyor P.C. Rector in 1865 under Contract "G2". A portion of the subdivisional lines were surveyed by U.S. Deputy Surveyor A.J. Hatch in 1874 under Contract No. 64. The remaining subdivisional lines were surveyed by U.S. Deputy Surveyor W.W. Skinner in 1875 under Contract No. 68. The north boundary was dependently resurveyed by Cadastral Engineers J.W. Hardison and Q. Campbell in 1947 under Group No. 343. A portion of the east boundary (Carson River Guide Meridian) was dependently resurveyed by Cadastral Surveyor C.D. Strickland concurrently under this same Group.

Before restoring the corners, the lines of the original surveys were retraced and a diligent search made for any evidence of the position of the original corners and other calls of the original field note record.

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 2009, and the Special Instructions for Group No. 920, dated November 20, 2012.

Measurements were made with Trimble R-8 Global Positioning System (GPS) receivers using the real-time kinematic (RTK) method and refer to the true meridian based on geodetic methods. The mean bearings of the lines and horizontal equivalents of ground distances only are entered in the field notes.

The NAD 1983 (2011) (EPOCH:2010.0000) geographic position, of the following corners were determined from GPS static observations processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuous Operation Reference Stations (CORS) RNO1 NW RENO COOP CORS ARP, ZOLE ZOLEZZI COOP CORS ARP and DOT1 CARSON CITY COOP CORS ARP and carried forward by RTK observations.

The standard cor. of Tps. 15 and 16 N., Rs. 20 and 21 E., is as follows:

Latitude: 39°12'03.309" N. Longitude: 119°40'38.994" W.

TOWNSHIP 16 NORTH, RANGE 20 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>The 1/4 sec. cor. of secs. 35 and 36, is as follows:</p> <p>Latitude: 39°12'29.448" N. Longitude: 119°41'46.287" W.</p> <p>The April 23, 2013 mean magnetic declination was determined to be 13°49' E., as obtained from the National Oceanic and Atmospheric Administration's National Geophysical Data Center declination calculator.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF THE THIRD STANDARD PARALLEL NORTH THROUGH A PORTION OF RANGE 20 EAST, MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor B. Ives in 1861</p> <hr/> <p>Beginning at the standard cor. of Tps. 15 and 16 N., Rs. 20 and 21 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the Third Standard Parallel North through a portion of Range 21 East, executed concurrently under this same Group.</p> <p>from which</p> <p style="padding-left: 40px;">A juniper stump, 8 ins. diam., bears N. 66°49' W., 174.2 lks. dist. (Record N. 67 1/2° W., 172 lks.) with no scribe mks. visible.</p> <p>Cor. is located at the north edge of a dirt road, 15 lks. wide, bears E. and W.</p> <p>From this cor., National Geodetic Survey Control (formerly U.S. Coast and Geodetic Survey) station "Empire", monumented with a standard brass disk, 3 ins. diam., firmly set in bedrock, flush with the ground, mkd. EMPIRE 1951, bears N. 36°24'20" E., 20.285 chs. dist.</p> <p>S. 89°59'30" W., on the S. bdy. of sec. 36.</p> <p>Over rolling terrain with scattered sagebrush.</p> <p>0.36 Graveled road, 30 lks. wide, bears N. and S.</p> <p>7.12 Graveled road, 18 lks. wide, bears NW. and SE.</p> <p>8.50 Center of the Virginia & Truckee Railway tracks, on a curve concave to the northeast.</p> <p>9.972 The E-E 1/64 sec. cor. of sec. 1 only, T. 15 N., R. 20 E., monumented with a magnetic nail, set flush with asphalt surface, as described in the field notes of the dependent resurvey of a portion of the subdivisional lines of T. 15 N., R. 20 E., executed concurrently under this same Group.</p>
--------	--

DEPENDENT RESURVEY OF THE THIRD STANDARD PARALLEL NORTH
THROUGH A PORTION OF RANGE 20 EAST,
MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	from which
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, for a reference monument, bears S. 44°25' W., 116.2 lks. dist., with brass cap mkd. RM E-E 1/64 S1 76.7 FT TO COR 2013, and an arrow pointing to the cor.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 10 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, for a reference monument, bears N. 80°25' W., 120.4 lks. dist., with brass cap mkd. RM 79.5 FT TO COR 2013, and an arrow pointing to the cor.</p>
18.12	Trail road, 12 lks. wide, bears NW. and SE.
19.944	The E 1/16 sec. cor. of sec. 1 only, T. 15 N., R. 20 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines of T. 15 N., R. 20 E., executed concurrently under this same Group.
20.100	<p>The standard E 1/16 sec. cor. of sec. 36, determined by Bruce R. Scott, Nevada Professional Land Surveyor No. 3579, in 1985, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 2 ins. above the ground, with tag wired to rebar mkd., RLS 3579, as recorded in Carson City, Nevada, Parcel Map, Book 5, Page 1343, File No. 53472. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SC E 1/16 S36</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">2013</p> <p>Insert rebar inside stainless steel post.</p> <hr style="width: 10%; margin: auto;"/> <p>S. 89°59'30" W., beginning new measurement.</p> <p>Over nearly level terrain with scattered sagebrush.</p>
11.50	Dirt runway, 75 lks. wide, bears NE. and SW.
17.30	Dirt road, 40 lks. wide, bears NW. and SE.

DEPENDENT RESURVEY OF THE THIRD STANDARD PARALLEL NORTH
THROUGH A PORTION OF RANGE 20 EAST,
MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
19.788	The 1/4 sec. cor. of sec. 1 only, T. 15 N., R. 20 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above a mound of stone, 3 ft. diam., with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines of T. 15 N., R. 20 E., executed concurrently under this same Group.
20.100	<p>The standard 1/4 sec. cor. of sec. 36, monumented with a stainless steel pipe, 2 ins. diam., firmly set, projecting 2 ins. above the ground, encircled in a collar of stone, with a wooden hub, tack and washer set in center of pipe, washer is mkd. RLS 2096. This position has been adopted and recorded by numerous professional land surveyors and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">SC T16N R20E 1/4 S36 <hr style="width: 10%; margin: auto;"/></p> <p style="text-align: center;">2013</p> <p>Bury pipe alongside stainless steel post.</p> <hr style="width: 30%; margin: auto;"/> <p>S. 89°59'00" W, beginning new measurement.</p> <p>Over rolling terrain.</p>
1.282	The witness point at the intersection of the easterly right-of-way line of U.S. Highway No. 50 with the S. bdy. of sec. 36, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the metes-and-bounds surveys in T. 15 N., R. 20 E., executed concurrently under this same Group.
1.29	Barbed wire fence, bears NE. and SW.
4.373	The point for the intersection of the centerline of U.S. Highway No. 50 with the S. bdy. of sec. 36, hereinafter described.
4.57	Center of asphalt surface, U.S. Highway No. 50, 130 lks. wide, on a curve concave to the NW.
7.45	Barbed wire fence, bears NE. and SW.
16.62	Power transmission line, bears N. 32° E. and S. 32° W.
19.595	From this point, a rebar, 5/8 in. diam., firmly set, in a mound of stone, 3 ft. diam., with a plastic cap mkd. WM Donovan JR PLS 2617, bears SOUTH, 0.893 chs. dist. Not utilized during the course of this survey.
37.90	Power transmission line, bears N. 34° E. and S. 34° W.

DEPENDENT RESURVEY OF THE THIRD STANDARD PARALLEL NORTH
THROUGH A PORTION OF RANGE 20 EAST,
MOUNT DIABLO MERIDIAN, NEVADA

CHAINS					
39.577	<p>The closing cor. of secs. 1 and 2, T. 15 N., R. 20 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above a mound of stone, 4 ft. diam., with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 15 N., R. 20 E., executed concurrently under this same Group.</p>				
40.166	<p>The standard cor. of secs. 35 and 36, monumented with a granite stone, 17x8x7 ins., loosely set in a mound of stone, 4 1/2 ft. diam., with X scribed at top of the stone. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 17 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>SC</p> <table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td>T16N</td> <td>R20E</td> </tr> <tr> <td>S35</td> <td>S36</td> </tr> </table> <p>2013</p> </div> <p>Bury stone alongside stainless steel post.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 16 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor P.C. Rector in 1865</p> <hr/> <p>From the standard cor. of secs. 35 and 36, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°07'10" E., bet. secs. 35 and 36.</p> <p>Over rolling terrain.</p>	T16N	R20E	S35	S36
T16N	R20E				
S35	S36				
40.099	<p>The 1/4 sec. cor. of secs. 35 and 36, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 6 ins. above the ground, in a scattered mound of stone, with a tag wired to rebar mkd. LS 1350. This position has been adopted and recorded by numerous professional land surveyors and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>				

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 16 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">T16N R20E 1/4 S35 S36</p> <p style="text-align: center;">2013</p> <p>Insert rebar inside stainless steel pipe.</p> <hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 36, T. 16 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the standard 1/4 sec. cor. of sec. 36, on the S. bdy. of the Tp.</p> <p>N. 0°01'50" W., on the N-S center line of sec. 36.</p> <p>Over rolling terrain with scattered sagebrush.</p> <p>4.95 Power transmission line, bears E. and W.</p> <p>6.257 A rebar, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with tag wired to rebar mkd. RLS 3579, set by Bruce R. Scott, Nevada Professional Land Surveyor No. 3579, in 1985, as recorded in Carson City, Nevada, Parcel Map, Book 5, Page 1343, File No. 53472.</p> <p>6.359 Barbed wire fence, bears NE. and SW.</p> <p>16.346 The point for the intersection of the centerline of U.S. Highway No. 50 with the N-S center line of sec. 36, hereinafter described.</p> <p>17.09 Center of asphalt surface, U.S. Highway No. 50, 130 lks. wide, on a curve concave to the SE.</p> <p>20.052 The C-S 1/16 sec. cor. of sec. 36, determined by Bruce R. Scott, Nevada Professional Land Surveyor No. 3579, in 1985, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, buried 11 ins. below the ground, with the top 4 ins. bent, with remains of tag wire attached to rebar, as recorded in Carson City, Nevada, Parcel Map, Book 5, Page 1343, File No. 53472. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">C S 1/16 S36 C</p> <p style="text-align: center;">2013</p> <p>Bury rebar alongside stainless steel post.</p> <hr/>
--------	--

SUBDIVISION OF SECTION 36,
T. 16 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>N. 0°01'50" W., beginning new measurement.</p> <p>Over rolling terrain with scattered sagebrush.</p>
6.18	Power transmission line, bears N. 32° E. and S. 32° W.
10.53	Trail road, 12 lks. wide, bears NE. and SW.
20.052	<p>Point for the center 1/4 sec. cor. of sec. 36, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T16N R20E C 1/4 S36</p> <p style="text-align: center;">2013</p> <p>From this point, a position determined by James A. Rankin, Nevada Professional Land Surveyor No. 1350, in 1982, monumented with a rebar, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, in a mound of stone, 1 ft. diam., with tag wired to rebar, mkd. LS 1350, as recorded in Carson City, Nevada, Parcel Map, Book 4, Page 922, File No. 10083, bears N. 86°42'20" E., 0.092 chs. dist. The position of this monument on the ground does not correlate well with the dimensions on said recorded Parcel Map and is not utilized during the course of this survey.</p>
35.98	Power transmission line, bears N. 34° E. and S. 34° W.
40.010	<p>Point for the C-N 1/16 sec. cor. of sec. 36.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">C N 1/16 S36 C</p> <p style="text-align: center;">2013</p> <p>From this point, a point determined by James A. Rankin, Nevada Professional Land Surveyor No. 1350, in 1982, monumented with a rebar, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with tag wired to rebar, mkd. LS 1350, as recorded in Carson City, Nevada, Parcel Map, Book 4, Page 922, File No. 10083, bears N. 71°20'40" E., 0.147 chs. dist. The position of this monument on the ground does not correlate well with the dimensions on said recorded Parcel Map and is not utilized during the course of this survey.</p>
49.60	Trail road, 12 lks. wide, bears NE. and SW.

SUBDIVISION OF SECTION 36,
T. 16 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
59.968	<p>The 1/4 sec. cor. of secs. 25 and 36, determined by person(s) unknown, monumented with a steel pipe, 1 1/2 ins. diam., 14 ins. long, firmly set, projecting 3 ins. above the ground, encircled in a scattered mound of stone. This position has been adopted and recorded by numerous professional land surveyors and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T16N R20E S25 1/4 — S36</p> <p>2013</p> </div> <p>Insert pipe inside stainless steel post.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 31 and 36, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the west boundary (Carson River Guide Meridian), T. 16 N., R. 21 E., executed concurrently under this same Group.</p> <p>S. 89°58'20" W. on the E-W center line of sec. 36.</p> <p>Over rolling terrain with scattered sagebrush.</p>
9.69	Barbed wire fence, bears N. 62° W. and S. 62° E.
16.66	Center of the Virginia & Truckee Railway tracks, on a curve concave to the northeast.
23.53	Barbed wire fence, bears NE. and SW.
25.97	Center of asphalt surface, U.S. Highway No. 50, 130 lks. wide, on a curve concave to the SE.
27.54	Barbed wire fence, bears NE. and SW.
31.39	Power transmission line, bears N. 32° E. and S. 32° W.
40.229	The center 1/4 sec. cor. of sec. 36.
50.97	Power transmission line, bears N. 34° E. and S. 34° W.
80.286	The 1/4 sec. cor. of secs. 35 and 36.

METES-AND-BOUNDS SURVEY OF A PORTION OF THE
 CENTERLINE OF U.S. HIGHWAY NO. 50,
 T. 16 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From the point for the intersection of the centerline of U.S. Highway No. 50 with the S. bdy. of sec. 36.</p> <p>POINT NOT MONUMENTED</p> <p>From this point, a Nevada Department of Transportation right-of-way monument, a concrete post, 6x6 ins., firmly set, projecting 6 ins. above the ground, mkd. with an N cast into a face, bears S. 34°18'10" W. 65.695 chs. dist. This monument is not utilized in this metes-and-bounds survey for the alignment of U.S. Highway No. 50.</p> <p>From this same point, the N. side of a Nevada Department of Transportation right-of-way monument, a wood post, 4x4 ins., firmly set, projecting 36 ins. above the ground, mkd. NHD on a face, bears S. 37°30'50" W., 73.630 chs. dist. The concrete post is missing. A point N. 28°07'30" W., 0.005 chs. dist., from the N. side of the wood post is utilized for the true position of the reference point.</p> <p>Thence along the arc of a circular curve to the left having a radius of 5000.00 ft., the long chord of said arc bears N. 11°07'50" E., 1.249 chs. dist., on the centerline of U.S. Highway No. 50.</p>
1.249	<p>Point of Tangency.</p> <p>POINT NOT MONUMENTED</p> <p>From this point, a Nevada Department of Transportation right-of-way monument, a concrete post, 6x6 ins., firmly set, projecting 2 ins. above the ground, mkd. with an N cast into a face, bears S. 79°20'30" E., 3.030 chs. dist.</p> <hr/> <p>Thence N. 10°39'30" E.</p>
1.889	<p>Point of Curvature.</p> <p>POINT NOT MONUMENTED</p> <p>From this point, a Nevada Department of Transportation right-of-way monument, a concrete post, 6x6 ins., firmly set, projecting 5 ins. above the ground, mkd. with an N cast into a face, bears S. 79°20'30' E., 3.030 chs. dist.</p> <p>From this point, a Nevada Department of Transportation right-of-way monument, a concrete post, 6x6 ins., firmly set, projecting 1 in. above the ground, mkd. with an N cast into a face, bears N. 79°20'30' W., 3.030 chs. dist.</p> <hr/> <p>Thence along the arc of a circular curve to the right having a radius of 5000.00 ft., the long chord of said arc bears N. 15°52'55" E., 13.794 chs. dist.</p>
13.814	<p>Point for the intersection of the centerline of U.S. Highway No. 50 with the N-S center line of sec. 36.</p> <p>POINT NOT MONUMENTED</p>

METES-AND-BOUNDS SURVEY OF A PORTION OF THE
CENTERLINE OF U.S. HIGHWAY NO. 50,
T. 16 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p>	<p>From this point, a Nevada Department of Transportation right-of-way monument, a concrete post, 6x6 ins., firmly set, projecting 4 ins. above the ground, mkd. with an N cast into a face, bears N. 0°06'20" E., 3.983 chs. dist.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The lands included in the survey are located in Carson City and Lyon County, Nevada, approximately 5 miles east of Carson City, Nevada. The vegetation in the undeveloped area is generally sagebrush and grasses. The area is hilly with an average elevation of 4700 ft. above sea level with drainage generally to the southeast. The land use is mixed with part urban and part rural.</p> <p>Access is provided by numerous paved and dirt roads by way of U.S. Highway No. 50.</p> <hr/>
---------------	--

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Thomas E. Casinger	Cadastral Surveyor
Bradley F. Dillon	Cadastral Surveyor
Michael E. Swope	Cadastral Surveyor
Cathy E. Schmersal	Survey Aid

CERTIFICATE OF SURVEY

I, Clarence D. Strickland, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 20th day of November, 2012, I have dependently resurveyed the Third Standard Parallel North through a portion of Range 20 East and a portion of the subdivisional lines, subdivided section 36 and executed a metes-and-bounds survey of a portion of the centerline of U.S. Highway No. 50, Township 16 North, Range 20 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

JUN 25 2014

(Date)

Clarence D. Strickland

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of the dependent resurvey of the Third Standard Parallel North through a portion of Range 20 East and a portion of the subdivisional lines, the subdivision of sec. 36 and a metes-and-bounds survey of a portion of the centerline of U.S. Highway No. 50, Township 16 North, Range 20 East, of the Mount Diablo Meridian, Nevada, executed by Clarence D. Strickland, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

JUN 25 2014

(Date)

David D. Moran

(Chief Cadastral Surveyor for Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above described surveys in Township 16 North, Range 20 East, Mount Diablo Meridian, Nevada, is a true copy of the original field notes.~~

~~_____
(Date)~~

~~_____
(Chief Cadastral Surveyor for Nevada)~~