

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY

OF

A PORTION OF THE SUBDIVISIONAL LINES
AND PORTIONS OF CERTAIN MINERAL SURVEYS,
THE SUBDIVISION OF SECTIONS 5 AND 6,
AND METES-AND-BOUNDS SURVEYS OF CERTAIN GOLD HILL TOWNSITE LOTS,
TOWNSHIP 16 NORTH, RANGE 21 EAST,
OF THE MOUNT DIABLO MERIDIAN,
IN THE STATE OF NEVADA

EXECUTED BY

Brock R. Clifford, Supervisory Cadastral Surveyor

Brandon G. Courtright, Cadastral Surveyor

Under Special Instructions dated August 18, 2014,

approved August 21, 2014,

which provided for the surveys included under Group No. 937,

and Assignment Instructions dated August 21, 2014.

Survey commenced August 25, 2014

Survey completed January 8, 2016

INDEX DIAGRAM

TOWNSHIP 16 NORTH, RANGE 21 EAST, MOUNT DIABLO MERIDIAN, NEVADA

6 4	5 5 2	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Subdivision of Section 5 pp. 46 - 48
 Subdivision of Section 6 pp. 48 - 51

MINERAL SURVEY INDEX

M.S. No. 42, Office No. 169	pp. 6 - 7
M.S. No. 48, Office No. 175	pp. 8 - 17
M.S. No. 49, Office No. 176	pp. 17 - 24
M.S. No. 51, Office No. 178	pp. 24 - 28
M.S. No. 53, Office No. 180	pp. 28 - 31
M.S. No. 55, Office No. 182	pp. 31 - 34
M.S. No. 65, Office No. 188	pp. 34 - 37
M.S. No. 100, Office No. 221	pp. 37 - 40
M.S. No. 117, Office No. 236	pp. 40 - 46

GOLD HILL TOWNSITE INDEX

Lot No. 17, Block 6, Range C	pp. 51 - 54
Lot Nos. 26, 28, 30 and 31, Block 6, Range C	pp. 54 - 65
Lot Nos. 43 and 43 1/2, Block 8, Range D	pp. 65 - 68
Unpatented Lot No. 51, Block 8, Range D	pp. 68 - 73
Lot Nos. 53 and 54, Block 8, Range D	pp. 74 - 76

TOWNSHIP 16 NORTH, RANGE 21 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines and portions of certain mineral surveys, the subdivision of sections 5 and 6, and metes-and-bounds surveys of certain Gold Hill Townsite Lots, Township 16 North, Range 21 East, Mount Diablo Meridian, Nevada.

The north, south, east and west boundaries, and a portion of the subdivisional lines were surveyed by U.S. Deputy Surveyor B. Ives in 1865. A portion of the subdivisional lines were surveyed by U.S. Deputy Surveyor R.W. Norris in 1867. A portion of the subdivisional lines were dependently resurveyed by Cadastral Engineer C.S. Swanholm in 1932-35. A portion of the north boundary was dependently resurveyed by Cadastral Surveyors D.D. Morlan and R.E. Williams in 1993-2004.

HISTORY OF MINERAL SURVEYS PERTAINING TO RESURVEY

<u>Mineral Survey</u> (Office No.)	<u>Date</u>	<u>U.S. Mineral</u> <u>Surveyors</u>	<u>Cancellation Date</u> (If applicable)
M.S. 42(169)	1868	J.F. Kidder	
M.S. 48(175)	1869	T.D. Parkinson	
M.S. 49(176)	1869	I.E. James	
M.S. 50(177)	1869	I.E. James	
M.S. 51(178)	1870	I.E. James	
M.S. 53(180)	1872	H. Hochholzer	
M.S. 55(182)	1872	H. Hochholzer	
M.S. 65(188)	1873	H. Hochholzer	
M.S. 68(191)	1873	H. Hochholzer	
M.S. 81(203)	1874	D.H. Barker	
M.S. 84(206)	1874	D.H. Barker	
M.S. 86(208)	1877	C.F. Hoffman	
M.S. 87(209)	1874	I.E. James	December 31, 2014
M.S. 88(210)	1874	R.E. Browne	
M.S. 97(218)	1874	R.E. Browne	December 31, 2014
M.S. 100(221)	1875	R.E. Browne	
M.S. 102(223)	1875	R.E. Browne	December 31, 2014
M.S. 110(229)	1875	I.E. James	December 31, 2014
M.S. 117(236)	1876	I.E. James	
M.S. 125(243)	1876	C.F. Hoffmann	
M.S. 134(252)	1877	A. Craven	December 31, 2014
M.S. 140(258)	1879	L.F.J. Wrinkle	
M.S. 141(259)	1879	A. Craven	December 31, 2014
M.S. 1723	1895	A.J. Chalmers	
M.S. 4599	1924	E.D. Boyle	December 31, 2014
M.S. 4728	1934	F.M. Spencer	
M.S. 4971	1981	W.F. Mueller	December 31, 2014

Before restoring the corners, the lines of the original surveys were retraced and a diligent search made for any evidence of the original corners and other calls of the original field note record.

TOWNSHIP 16 NORTH, RANGE 21 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

Angle Point numbers were assigned to corners of certain Gold Hill Townsite lots to facilitate reference to their respective locations.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 2009, and the Special Instructions for Group No. 937, dated August 18, 2014.

Measurements were made with Trimble R8 Global Positioning System (GPS) receivers using the real-time kinematic method. The direction of each line is with reference to the true meridian. All bearings are mean bearings and the distances are reported as horizontal measurement at a mean ground elevation of 5,800 feet above sea level.

The NAD 1983 (2011) (EPOCH:2010.0000) geographic position, of the following corners were determined from GPS static observations processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuous Operating Reference Stations (CORS) P150 MARTISPEAKCN2008 CORS ARP, DOT1 CARSON CITY COOP CORS ARP, and ZOLE ZOLEZZI COOP CORS ARP, and carried forward by RTK observations.

The corner of sections 4, 5, 32 and 33, on the N. bdy. of the Tp., is as follows:

Latitude: 39°17'17.282" N. Longitude: 119°38'24.416" W.

The corner of sections 1, 6, 7 and 12, on the W. bdy. of the Tp., is as follows:

Latitude: 39°16'24.923" N. Longitude: 119°40'39.081" W.

The August 25, 2014 mean magnetic declination was determined to be 13°40' E., as obtained from the National Oceanic and Atmospheric Administration's National Geophysical Data Center declination calculator.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 16 N., R. 21 E. MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of a Portion of the Survey Executed by
U.S. Deputy Surveyor R.W. Norris in 1867

Beginning at the 1/4 sec. cor. of secs. 5 and 8, determined by person(s) unknown, monumented with an iron pipe, 1 1/2 ins. diam., 32 ins. long, firmly set, projecting 8 ins. above a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high. This position has been adopted by professional land surveyors and is accepted as the best available evidence of the position of the original corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.

T16N	R21E
S 5	
1/4	—
S 8	

2014

Bury the iron pipe alongside the stainless steel post.

From this corner, the cor. of secs. 4, 5, 8 and 9, bears S. 89°49'30" E., 40.490 chs. dist., determined by Wm. Michael Donovan, Jr., Nevada Professional Land Surveyor No. 2617, monumented with a rebar, 5/8 in. diam., 24 ins. long, firmly set, 3 ins. below the surface of the ground, with plastic cap mkd. PLS 2617 4-5-8-9. This position has been adopted by other professional land surveyors and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.

T16N	R21E
S 5	S 4
—	—
S 8	S 9

2014

Deposit the rebar inside the stainless steel post.

N. 89°40'50" W., bet. secs. 5 and 8.

Descend.

- 4.60 Enter bottom of Gold Canyon.
- 4.632 Intersect line 4-5, Mineral Survey No. 53, Woodville claim, at a point from which the point for Cor. No. 5, identical with Cor. No. 4, Mineral Survey No. 94, Tarto claim hereinafter described, bears S. 8°55'20" E., 4.072 chs. dist.
- 5.30 Powerline, bears S. 35° E. and N. 35° W.
- 5.61 Gold Canyon and Nevada State Route 342, asphalt surface, 35 lks. wide, bears S. 35° E. and N. 35° W.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS									
7.549	Intersect line 1-2, Mineral Survey No. 53, Woodville claim, identical with a portion of line 6-7, Mineral Survey No. 48, Justice and Independent claim, at a point from which the point for Cor. No. 2, hereinafter described, bears N. 41°18'00" W., 0.504 chs. dist.								
13.625	Intersect line 8-1, Mineral Survey No. 48, Justice and Independent claim, at a point from which Cor. No. 1, Mineral Survey No. 117, Chonta claim, hereinafter described, bears N. 41°18'00" W., 5.390 chs. dist.								
28.10	Summit of hill, begin descent.								
38.167	The cor. of secs. 5, 6, 7 and 8, determined by person(s) unknown, monumented with an iron rod, 5/8 in. diam., 36 ins. long, firmly set, flush in a mound of stone, 3 ft. base, 1 ft. high, with a washer, 2 3/4 ins. diam., welded to the top, mkd. 5-6-7-8. This position has been adopted by other professional land surveyors and is accepted as the best available evidence of the position of the original corner.								
	At the corner point								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T16N R21E</td> </tr> <tr> <td style="text-align: center;">S 6</td> <td style="text-align: center;">S 5</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">S 7</td> <td style="text-align: center;">S 8</td> </tr> </table>	T16N R21E		S 6	S 5	-----		S 7	S 8
T16N R21E									
S 6	S 5								

S 7	S 8								
	2014								
	Invert and bury the iron rod alongside the stainless steel post.								
	From this corner, Cor. No. 1, cancelled Mineral Survey No. 4971, HOMRF #1 mill site, bears N. 76°38'50" W., 31.097 chs. dist., monumented with an iron pipe, 2 1/2 ins. diam., heavily bent over and buried 10 ins. below the surface of the ground, with the remains of a brass cap mkd. 1 MS4971.								
	N. 89°22'20" W., bet. secs. 6 and 7.								
7.05	Trail road, 15 lks. wide, bears N. 25° E. and S. 15° W.								
37.37	Remains of old road, overgrown by brush, 15 lks. wide, bears N. and S.								
39.39	Seasonal creek, drains S. 10° E.								

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.944	<p>The 1/4 sec. cor. of secs. 6 and 7, determined by Walter G. Reid, Nevada Professional Land Surveyor No. 235, monumented with a rebar, 5/8 in. diam., firmly set, projecting 9 ins. above ground, with aluminum cap mkd. RLS235 6-7 1/4 COR. This position has been adopted by other professional land surveyors and is accepted as the best available evidence of the position of the original corner.</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground, for a reference monument, bears N. 54°48'10" E., 14.6 lks. dist., with brass cap mkd. RM T16N R21E 1/4 S6 9.6 FT TO COR 2014, and an arrow pointing to the cor.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 36°08'40" E., 14.8 lks. dist., with brass cap mkd. RM T16N R21E 1/4 S7 9.7 FT TO COR 2014, and an arrow pointing to the cor.</p> <p>Cor. is located in the corner of barbed wire fences, extending N., E. and W.</p> <p>From this corner, Cor. No. 1, cancelled Mineral Survey No. 4971, HOMRF #1 mill site, hereinbefore described, bears N. 57°46'30" E., 12.630 chs. dist.</p> <p>From this same corner, the cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., determined by person(s) unknown, bears N. 89°24'30" W., 40.915 chs. dist., monumented with an iron rod, 5/8 in. diam., firmly set, flush in a mound of stone, 4 ft. base, 1 1/2 ft. high, with a washer, 2 3/4 ins. diam., welded to the top, with a steel fence post loosely set alongside, and a wood post, 4x4x45 ins., lying loose alongside, with aluminum tag mkd. NW1/4 NW1/4 SEC7 T16N R21E MDBM PATENTED. This position has been adopted by professional land surveyors and is accepted as the best available evidence of the position of the original corner.</p> <p>From this cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., a position determined by person(s) unknown, bears N. 65°03'10" W., 0.071 chs. dist., monumented with a steel bolt, 3/4 in. diam., firmly set, with a 1 1/2 ins. square nut, no discernible marks.</p> <hr/> <p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 1°13'30" W., bet. secs. 5 and 6.</p>
18.309	Intersect line 2-3, unpatented Lot No. 51, Block 8, Range D, Gold Hill Townsite, at a point from which Angle Point No. 3, hereinafter described, bears N. 57°34'40" E., 4.300 chs. dist.
20.40	Powerline, bears E. and W.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
35.155	Intersect line 8-9, unpatented Lot No. 51, Block 8, Range D, Gold Hill Townsite, at a point from which Angle Point No. 9, hereinafter described, bears N. 58°23'40" W., 1.693 chs. dist.
40.393	<p>The 1/4 sec. cor. of secs. 5 and 6, reestablished by John S. Parrish, Nevada Professional Land Surveyor No. 9475, in 2012, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, flush in a collar of stone, with aluminum cap mkd. T16N R21E 1/4 S6 S5 PLS9475 2011, as recorded in Storey County, Nevada, File No. 116315, and is accepted as a careful and faithful reestablishment of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T16N R21E 1/4 S 6 S 5</p> <p style="text-align: center;">2014</p> <p>Insert the rebar inside the stainless steel post.</p> <p>From this corner, the cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., bears N. 1°13'30" W., 40.393 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above an embedded mound of stone, 5 ft. diam., with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 17 N., R. 21 E., executed under Group No. 736.</p> <p>From this cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., Triangulation station "WHEELER MONUMENT RESET" bears N. 23°10'10" E., 44.088 chs. dist., monumented with a standard disk mkd. WHEELER MONUMENT 1897 1951, firmly set in the top of a concrete pier projecting 4 1/2 ft. above the ground.</p>
<hr/> <p>DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 42, T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>	
<p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Mineral Surveyor J.F. Kidder in 1868</p> <hr/>	
<p>Front Lode Consolidated claim on the Middle lode</p>	
<p>From the point for the post used as the point of commencement, determined by grant boundary adjustment between the cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., and the 1/4 sec. cor. of secs. 5 and 6; there is no remaining evidence of the original corner.</p>	

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 42,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">MS 42 — F-L-C</p> <p style="text-align: center;">2015</p> <p>From this point, the 1/4 sec. cor. of secs. 5 and 6, hereinbefore described, bears S. 35°16'00" W., 11.854 chs. dist.</p> <p>From this same point, the cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., hereinbefore described, bears N. 14°05'20" W., 31.658 chs. dist.</p> <p>Thence S. 10°44'00" E., on the second course of the claim, on the opposite bearing of the first course when restored by grant boundary adjustment.</p> <p>1.89 Nevada State Route 342, asphalt surface, 35 lks. wide, bears N. 10° E. and S. 10° W.</p> <p>5.77 Nevada State Route 342, asphalt surface, 35 lks. wide, bears S. 30° E. and N. 30° W.</p> <p>9.898 Intersect the E-W center line of sec. 5, at a point from which the 1/4 sec. cor. of secs. 5 and 6, hereinbefore described, bears N. 89°41'40" W., 8.688 chs. dist.</p> <p>10.880 Intersect line 1-2, Lot No. 43, identical with line 3-4, unpatented Lot No. 42, Block 8, Range D, Gold Hill Townsite, at a point from which Angle Point No. 1, identical with Angle Point No. 4, hereinafter described, bears N. 85°51'40" E., 0.112 chs. dist.</p> <p>15.152 Point for the post on the S. end of the claim, determined at record distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">MS 42 — F-L-C</p> <p style="text-align: center;">S End</p> <p style="text-align: center;">2015</p> <hr/>
--------	--

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 48,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA


CHAINS

Reestablishment of Portions of the Survey Executed by
U.S. Deputy Mineral Surveyor T.D. Parkinson in 1869

Justice and Independent claim on the Comstock lode

From the point for Cor. No. 1, Mineral Survey No. 48, Justice and Independent claim, identical with Cor. No. 3, Mineral Survey No. 55, Keystone claim, determined at the intersection of a line extending from Cor. No. 8, Mineral Survey No. 48, Justice and Independent claim, parallel with a line between Cor. Nos. 2 and 7, Mineral Survey No. 48, Justice and Independent claim, and a line extending from Cor. No. 2, Mineral Survey No. 48, Justice and Independent claim, at record angle; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.



2015

From this point, a position determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, bears N. 89°45'20" W., 0.142 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, with aluminum cap mkd. COR3 MS55 COR1 MS48 PLS10836 2012, as recorded in Storey County, Nevada, File No. 117835. Not utilized in the course of this survey.

From this same point, an iron pipe, 3/4 in. diam., firmly set, projecting 7 ins. above the ground, bears N. 42°00'20" W., 1.391 chs. dist.


Thence N. 67°01'00" E., on line 1-2, Mineral Survey No. 48, Justice and Independent claim, identical with a portion of line 3-4, Mineral Survey No. 55, Keystone claim.

4.785

Point for Cor. No. 2, Mineral Survey No. 48, Justice and Independent claim, determined at the extension of the bearing between Cor. Nos. 7 and 3, Mineral Survey No. 48, Justice and Independent claim, and record distance from Cor. No. 3; there is no remaining evidence of the original corner.


Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 48,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<div style="text-align: center;">  <p>MS 55 KE T16N MS 48 R21E J-I S 5 COR 2</p> <p>2015</p> </div>
	<p>From this point, a position determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, bears N. 84°11'40" W., 0.146 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, 3 ins. below the surface of the ground, with aluminum cap mkd. COR2 MS48 J MS55 K T16N R21E S5 PLS10836 2012, as recorded in Storey County, Nevada, File No. 117835. Not utilized in the course of this survey.</p>
	<p>Thence S. 41°18'00" E., on line 2-3, Mineral Survey No. 48, Justice and Independent claim.</p>
0.376	<p>Intersect line 1-2, Lot No. 53, Block 8, Range D, Gold Hill Townsite, at a point from which Angle Point No. 1, hereinafter described, bears N. 68°08'20" E., 0.983 chs. dist.</p>
2.989	<p>Intersect line 3-4, Lot No. 54, identical with line 1-2, unpatented Lot No. 55, Block 8, Range D, Gold Hill Townsite, at a point from which Angle Point No. 4, identical with Angle Point No. 1, hereinafter described, bears N. 49°29'10" E., 0.761 chs. dist.</p>
3.300	<p>Cor. No. 4, Mineral Survey No. 117, Chonta claim, hereinafter described.</p>
	<p>Continue measurement on line 2-3, Mineral Survey No. 48, Justice and Independent claim, identical with line 4-15, Mineral Survey No. 117, Chonta claim.</p>
10.500	<p>Cor. No. 3, Mineral Survey No. 48, Justice and Independent claim, identical with Cor. No. 15, Mineral Survey No. 117, Chonta claim, determined by person(s) unknown, monumented with a rebar, 1/2 in. diam., 35 ins. long, firmly set, projecting 13 ins. above the ground, with a wood post, 4x6 ins., firmly set alongside, projecting 2 ft. above the ground, no visible marks. This position was adopted by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, as recorded in Storey County, Nevada, File No. 117835, and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 48,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS



2015

Bury the rebar alongside the stainless steel post, leave the wood post in place.


Thence N. 48°45'00" E., on line 3-4, Mineral Survey No. 48, Justice and Independent claim.

0.877 Intersect line 2-3, Lot No. 30, Block 6, Range C, Gold Hill Townsite, at a point from which Angle Point No. 2, identical with Angle Point No. 7, Lot No. 26, Block 6, Range C, Gold Hill Townsite, hereinafter described, bears N. 37°37'20" W., 1.706 chs. dist.

9.253 Cor. No. 4, Mineral Survey No. 48, Justice and Independent claim, identical with Angle Point No. 1, Lot No. 28, and Angle Point No. 4, unpatented Lot No. 27, on line 7-8, Lot No. 26, Block 6, Range C, Gold Hill Townsite, determined by person(s) unknown, monumented with a rebar, 3/8 in. diam., 36 ins. long, firmly set, projecting 23 ins. above the ground, and perpetuated by William G. Turney, Nevada Professional Land Surveyor No. 9394, with a rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 3 ins. above the ground, with plastic cap mkd. W TURNEY. This position has been adopted by other professional land surveyors and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.



2015

Bury both rebar alongside the stainless steel post.

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 48,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	Thence S. 42°23'00" E., on line 4-5, Mineral Survey No. 48, Justice and Independent claim.
0.807	Intersect line 3-4, Mineral Survey No. 53, Woodville claim, at a point from which Cor. No. 3, hereinafter described, bears S. 80°38'30" W., 0.035 chs. dist.
5.452	<p>Cor. No. 5, Mineral Survey No. 48, Justice and Independent claim, determined by person(s) unknown, monumented with a rebar, 1/2 in. diam., 35 ins. long, loosely set, projecting 23 ins. above a mound of stone, 3 ft. base, 1 ft. high. This position was adopted by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, as recorded in Storey County, Nevada, File No. 117835, and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, in a drill hole in bedrock, with top mkd.</p> <div data-bbox="852 828 1079 953" style="text-align: center;"> <p>MS 48 J-I COR 5</p> <p>MS 53 WO</p> </div> <p>2015</p> <p>Bury the rebar in a mound of stone, 3 ft. base, 1 ft. high, N. of cor.</p>
	Thence S. 48°45'00" W., on line 5-6, Mineral Survey No. 48, Justice and Independent claim.
3.123	Intersect line 2-3, Mineral Survey No. 53, Woodville claim, at a point from which Cor. No. 3, hereinafter described, bears N. 8°28'20" W., 5.545 chs. dist.
3.136	From this point, a position determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, bears NORTH, 0.046 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, with aluminum cap mkd. WC T16N R21E S5 MS48 J COR2 MS53 W, as recorded in Storey County, Nevada, File No. 117835.
4.625	Intersect line 5-1, Lot No. 30, identical in part with a portion of line 2-3, unpatented Lot No. 29, Block 6, Range C, Gold Hill Townsite, at a point from which Angle Point No. 5, on line 2-3, hereinafter described, bears S. 36°59'20" E., 0.420 chs. dist.
9.356	Point for Cor. No. 6, Mineral Survey No. 48, Justice and Independent claim, determined at the intersection of a line between Cor. Nos. 3 and 7, Mineral Survey No. 48, Justice and Independent claim, with a line extending from Cor. No. 5, Mineral Survey No. 48, Justice and Independent claim, and parallel with line 3-4, Mineral Survey No. 48, Justice and Independent claim; there is no remaining evidence of the original corner.

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 48,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a rebar, 18 ins. long, 5/8 in. diam., 6 ins. below the surface of a 3 1/2 ft. berm along the edge of an active mining site, with aluminum cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>MS 48 GHT J-I Lot 31 COR 6</p> <p>2015</p> </div> <p style="text-align: center; margin: 10px 0;">_____</p> <p>Thence S. 41°18'00" E., on a portion of line 6-7, Mineral Survey No. 48, Justice and Independent claim.</p> <p>2.288 Intersect line 3-4, Lot No. 31, identical with line 3-4, unpatented Lot No. 32, Block 6, Range C, Gold Hill Townsite, at a point from which the point for Angle Point No. 3, Lot No. 31, identical with Angle Point No. 4, unpatented Lot No. 32, Block 6, Range C, Gold Hill Townsite, hereinafter described, bears S. 59°05'00" W., 0.612 chs. dist.</p> <p>9.665 The point for Cor. No. 2, Mineral Survey No. 53, Woodville claim, hereinafter described.</p> <hr style="width: 100%;"/> <p>From the point for Cor. No. 7, Mineral Survey No. 48, Justice and Independent claim, identical with Cor. No. 3, Mineral Survey No. 84, Tarto claim, on line 5-1, Mineral Survey No. 53, Woodville claim, determined at the extension of a line from Cor. No. 8, Mineral Survey No. 48, Justice and Independent claim, through Cor. No. 7, Mineral Survey No. 140, Silver Hill claim, identical with Cor. No. 2, Mineral Survey No. 84, Tarto claim, and at record distance from Cor. No. 7, Mineral Survey No. 140, Silver Hill claim, identical with Cor. No. 2, Mineral Survey No. 84, Tarto claim; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>MS 48 MS 53 J-I WO COR 7</p> <p>MS 84 TA COR 3</p> <p>2015</p> </div> <p>From this point, a position determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, bears S. 3°58'30" W., 0.012 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, with aluminum cap mkd. T16N R21E MS53 W COR7 MS48 J COR3 MS84 T PLS10836 2012, as recorded in Storey County, Nevada, File No. 117835. Not utilized in the course of this survey.</p>
--------	---


DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 48,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p> <p>1.379</p>	<p>Thence S. 49°41'00" W., on line 7-8, Mineral Survey No. 48, Justice and Independent claim, identical with line 3-2, Mineral Survey No. 84, Tarto claim.</p> <p>Point for Cor. No. 2, Mineral Survey No. 84, Tarto claim, identical with Cor. No. 7, Mineral Survey No. 140, Silver Hill claim, determined by grant boundary adjustment between Cor. No. 2, Mineral Survey No. 140, Silver Hill claim, identical with Cor. No. 1, Mineral Survey No. 81, Sierra claim, and Cor. No. 6, Mineral Survey No. 140, Silver Hill claim, identical with Cor. No. 1, Mineral Survey No. 84, Tarto claim, Cor. No. 4, Mineral Survey No. 50, Echo claim, and Cor. No. 5, Mineral Survey No. 1723, Succor lode; there is no remaining evidence of the original corner.</p> <p>POINT NOT MONUMENTED</p> <p>Point is located in active mining site.</p> <p>From this point, the point for Cor. No. 6, Mineral Survey No. 140, Silver Hill claim, identical with Cor. No. 1, Mineral Survey No. 84, Tarto claim, Cor. No. 4, Mineral Survey No. 50, Echo claim, and Cor. No. 5, Mineral Survey No. 1723, Succor lode, bears S. 51°49'00" E., 5.118 chs. dist., determined at the extension of the line bet. Cor. No. 3, Mineral Survey No. 4728, Brown lode and Cor. No. 4, Mineral Survey No. 4728, Hardluck lode and at record distance from Cor. No. 4, Mineral Survey No. 4728, Hardluck lode; there is no remaining evidence of the original corner.</p> <p>Set a magnetic nail, flush with the surface of Nevada State Route 342, 35 lks. wide, bears S. 25° E. and N. 25° W.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 23 ins. in the ground, over a plastic encased magnet, for a reference monument, bears N. 81°59'40" E., 132.4 lks. dist., with brass cap mkd. RM MS50 EC COR4 MS84 TA COR1 MS140 S-H COR6 MS1753 SU COR5 87.4 FT TO COR 2015, and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 23 ins. in the ground, over a plastic encased magnet, for a reference monument, bears N. 5°05'50" W., 284.4 lks. dist., with brass cap mkd. RM MS50 EC COR4 MS84 TA COR1 MS140 S-H COR6 MS1753 SU COR5 187.7 FT TO COR 2015, and an arrow pointing to the cor.</p> <p>From this point for Cor. No. 6, Mineral Survey No. 140, Silver Hill claim, identical with Cor. No. 1, Mineral Survey No. 84, Tarto claim, Cor. No. 4, Mineral Survey No. 50, Echo claim, and Cor. No. 5, Mineral Survey No. 1723, Succor lode, the point for Cor. No. 4, Mineral Survey No. 4728, Hardluck lode, on line 3-4, Mineral Survey No. 50, Echo claim, bears S. 42°53'50" E., 8.244 chs. dist., determined at record bearing and distance from Cor. No. 1, Mineral Survey No. 4728, Hardluck lode; there is no remaining evidence of the original corner.</p>
----------------------------	---

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 48,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.



2016

Point is located 5 lks. E. of E. edge of asphalt, of Nevada State Route 342.


From this point for Cor. No. 4, Mineral Survey No. 4728, Hardluck lode, a position determined by John S. Parrish, Nevada Professional Land Surveyor No. 9475, in 2012, bears S. 37°07'40" W., 0.013 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, with aluminum cap mkd. T16N R21E MS50 MS4728 M COR4 PLS9475 2012, with a rebar, 1/2 in. diam., 36 ins. long, lying loose alongside, as recorded in Storey County, Nevada, File No. 119273. Not utilized in the course of this survey.

From this same point for Cor. No. 4, Mineral Survey No. 4728, Hardluck lode, Cor. No. 1, Mineral Survey No. 4728, Hardluck lode, bears N. 28°10'00" E., 9.611 chs. dist., determined by person(s) unknown, monumented with a rebar, 1/2 in. diam., 36 ins. long, firmly set, projecting 7 ins. above the ground, and in a ring of stone, 3 ft. diam., with a steel fence post set alongside, and the remains of a charred wood post, 3x3x14 ins., lying loose alongside. This is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

MS 4728 FR



2015


Bury the rebar and wood post alongside the stainless steel post, leave the steel fence post in place.

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 48,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

From this same point for Cor. No. 4, Mineral Survey No. 4728, Hardluck lode, the point for Cor. No. 3, Mineral Survey No. 4728, Brown lode, bears S. 42°53'50" E., 14.828 chs. dist., determined at record bearing and distance from Cor. No. 2, Mineral Survey No. 4728, Brown lode; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.




Cor. is located 12 lks. E. of E. edge of the asphalt of Nevada State Route 342.

From this point for Cor. No. 3, Mineral Survey No. 4728, Brown lode, Cor. No. 2, Mineral Survey No. 4728, Brown lode, bears N. 35°30'00" E., 9.882 chs. dist., determined by person(s) unknown, and perpetuated by John S. Parrish, Nevada Professional Land Surveyor No. 9475, monumented with a rebar, 5/8 in. diam., 36 ins. long, firmly set, flush in an embedded mound of stone, 3 ft. diam., with aluminum cap mkd. T16N R21E S8 MS4728 COR2 B PLS9475 2012, with a partially charred wood post, 4x4x32 ins., no discernible marks, lying loose alongside, as recorded in Storey County, Nevada, File No. 119273, and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.




Bury the rebar and the wood post alongside the stainless steel post.

Continue measurement on line 7-8, Mineral Survey No. 48, Justice and Independent claim, identical with line 7-1, Mineral Survey No. 140, Silver Hill claim.

4.544

Point for Cor. No. 8, Mineral Survey No. 48, Justice and Independent claim, identical with Cor. No. 1, Mineral Survey No. 140, Silver Hill claim, determined by grant boundary adjustment between Cor. No. 2, Mineral Survey No. 140, Silver Hill claim, identical with Cor. No. 1, Mineral Survey No. 81,

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 48,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Sierra claim, and Cor. No. 6, Mineral Survey No. 140, Silver Hill claim, identical with Cor. No. 1, Mineral Survey No. 84, Tarto claim, Cor. No. 4, Mineral Survey No. 50, Echo claim, and Cor. No. 5, Mineral Survey No. 1723, Succor lode; there is no remaining evidence of the original corner.</p> <p>POINT NOT MONUMENTED</p> <p>Point is located in active mining site.</p> <p>From this point, Cor. No. 2, Mineral Survey No. 140, Silver Hill claim, identical with Cor. No. 1, Mineral Survey No. 81, Sierra claim, bears S. 17°53'00" W., 4.573 chs. dist., determined by Wm. Michael Donovan, Jr., and perpetuated by John S. Parrish, Nevada Professional Land Surveyor No. 9475, in 2012, monumented with a rebar, 5/8 in. diam., 28 ins. long, firmly set, projecting 2 ins. above the ground, with aluminum cap mkd. MS86 H COR1 MS81 C UNPAT MS140 COR2 L PLS9475 2012, with an iron pipe, 4 ins. diam., firmly set, projecting 3 ft. above the ground, and a steel fence post loosely set alongside, as recorded in Storey County, Nevada, File No. 119273. This position has been adopted by other professional land surveyors and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;">  </div> <p>Bury the rebar alongside the stainless steel post, leave the iron pipe in place and the steel fence post lying lose alongside.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Thence N. 41°18'00" W., on line 8-1, Mineral Survey No. 48, Justice and Independent claim.</p> <p>8.107 Intersect the line bet. secs. 5 and 8, at a point from which the 1/4 sec. cor. of secs. 5 and 8, hereinbefore described, bears S. 89°40'50" E., 13.625 chs. dist.</p> <p>13.497 Cor. No. 1, Mineral Survey No. 117, Chonta claim, hereinafter described.</p>
--------	--


DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 48,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p> <p>17.361</p> <p>31.694</p>	<p>Continue measurement on line 8-1, Mineral Survey No. 48, Justice and Independent claim, identical with line 1-3, Mineral Survey No. 117, Chonta claim.</p> <p>The point for Cor. No. 3, Mineral Survey No. 117, Chonta claim, hereinafter described.</p> <p>Continue measurement on line 8-1, Mineral Survey No. 48, Justice and Independent claim.</p> <p>Cor. No. 1, Mineral Survey No. 48, Justice and Independent claim, identical with Cor. No. 3, Mineral Survey No. 55, Keystone claim.</p>
<p>DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 49, T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA</p>	
<p>Reestablishment of Portions of the Survey Executed by U.S. Deputy Mineral Surveyor I.E. James in 1869</p>	
<p>Gold Canyon claim on the Comstock lode</p>	
<p>From Cor. No. 8, Mineral Survey No. 49, Lot A, reestablished by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, with aluminum cap mkd. T16N R21E S5 COR8 MS49A F PLS10836 2012, as recorded in Storey County, Nevada, File No. 117835, and is accepted as a careful and faithful reestablishment of the position of the original corner.</p>	
<p>CORNER NOT REMONUMENTED</p>	
<p>Cor. is located in yard of private residence.</p>	
<p>From this cor., a rebar, 5/8 in. diam., firmly set, projecting 7 ins. above a collar of stone, bears S. 42°30'40" W., 0.206 chs. dist.</p>	
<p>Thence S. 15°24'30" E., on a portion of the third course of the claim.</p>	
<p>10.932</p>	<p>Intersect the E-W center line of sec. 5, at a point from which the 1/4 sec. cor. of secs. 5 and 6, hereinbefore described, bears N. 89°41'40" W., 15.304 chs. dist.</p>
<p>11.060</p>	<p>Intersect line 1-2, Lot No. 17, identical with line 3-4, unpatented Lot No. 16, Block 6, Range C, Gold Hill Townsite, at a point from which the point for Angle Point No. 1, identical with the point for Angle Point No. 4, hereinafter described, bears N. 61°03'10" E., 0.817 chs. dist.</p>
<p>16.773</p>	<p>Cor. No. 1, Mineral Survey No. 49, Lot B, hereinafter described.</p>

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 49,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
16.778	Intersect line 3-4, Lot No. 17, identical with line 1-2, unpatented Lot No. 19, Block 6, Range C, Gold Hill Townsite, at a point from which Angle Point No. 4, identical with Angle Point No. 1, hereinafter described, bears N. 66°33'40" E., 0.454 chs. dist.
18.289	Cor. No. 8, Mineral Survey No. 49, Lot B, hereinafter described.
19.034	Intersect line 3-4, Mineral Survey No. 100, Memphis Claim, at a point from which Cor. No. 3, identical with Cor. No. 3, Mineral Survey No. 51, Lady Washington claim, hereinafter described, bears S. 75°21'30" W., 0.139 chs. dist.
20.333	<p>Point for Post No. 4, Mineral Survey No. 49, Lot B, determined on the extension of a line from Cor. No. 8, Mineral Survey No. 49, Lot A, through Cor. No. 8, Mineral Survey No. 49, Lot B, at record distance along the third course of the claim; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="812 901 1006 1098" style="text-align: center;"> <p>MS 49 / G-C ↓ S End 2015</p> </div> <hr/> <p style="text-align: center;">Lot B</p> <p>From Cor. No. 1, Mineral Survey No. 49, Lot B, on the lode line of Mineral Survey No. 49, Gold Canyon claim, reestablished by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, flush with the surface of the ground, with aluminum cap mkd. T16N R21E S5 COR1 MS49B PLS10836 2012, as recorded in Storey County, Nevada, File No. 117835, and is accepted as a careful and faithful reestablishment of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div data-bbox="876 1616 1023 1875" style="text-align: center;"> <p>LOT 17 GHT</p> <p>MS 49 / LOT B ↓ COR 1 2015</p> </div>

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 49,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Insert the rebar inside the stainless steel post.</p>
	<p>Thence N. 74°57'20" E., on line 1-2, Mineral Survey No. 49, Lot B.</p>
0.035	<p>Intersect line 3-4, Lot No. 17, identical with line 1-2, unpatented Lot No. 19, Block 6, Range C, Gold Hill Townsite, at a point from which Angle Point No. 4, identical with Angle Point No. 1, hereinafter described, bears N. 66°33'40" E., 0.419 chs. dist.</p>
0.90	<p>Powerline, bears S. 15° E. and N. 15° W.</p>
1.515	<p>Cor. No. 2, Mineral Survey No. 49, Lot B, determined by Walter G. Reid, Nevada Professional Land Surveyor No. 235, monumented with a rebar, 5/8 in. diam., 24 ins. long, firmly set, projecting 6 ins. above the ground, with aluminum cap mkd. SURVEY NO 49B COR2 RLS235, as shown on an unrecorded map titled MAP TO SHOW 50' ROAD EASEMENT ACROSS MINING CLAIM LOT & SURVEY NO. 49 PORTION OF THE W. 1/2 SEC. 5 T. 16 N., R. 21 E., M.D.B. & M. GOLD HILL STOREY COUNTY, NEVADA. This position was adopted by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, as recorded in Storey County, Nevada, File No. 117835, and is accepted as the best available evidence of the position of the original corner.</p>
	<p>At the corner point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<div style="text-align: center;">  <p>T16N R21E S 5</p> <p>MS 49 LOT B COR 2</p> <p>2015</p> </div>
	<p>Insert the rebar inside the stainless steel post.</p>
	<p>Thence N. 15°24'20" W., on line 2-3, Mineral Survey No. 49, Lot B.</p>
5.010	<p>Point for Cor. No. 3, Mineral Survey No. 49, Lot B, an unmonumented position determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, as recorded in Storey County, Nevada, File No. 117835, reestablished in this survey at record angle and distance from Cor. No. 4. This position is accepted as a careful and faithful determination of the position of the original corner.</p>
	<p>Set a rebar, 18 ins. long, 5/8 in., diam., 6 ins. below surface of Keystone Circle, with aluminum cap mkd.</p>

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 49,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

BLM

T16N MS 49
R21E LOT B
S 5 COR 3

2015

from which

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, and in a collar of stone, for a reference monument, bears N. 34°01'50" E., 141.5 lks. dist., with brass cap mkd. RM MS49 LOTB COR3 93.4 FT TO COR 2015, and an arrow pointing to the cor.

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, and in a collar of stone, for a reference monument, bears S. 55°48'20" E., 123.6 lks. dist., with brass cap mkd. RM MS49 LOTB COR3 81.6 FT TO COR 2015, and an arrow pointing to the cor.

From this point, a position determined by Walter G. Reid, Nevada Professional Land Surveyor No. 235, monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of Keystone Circle, bears S. 17°06'00" E., 0.021 chs. dist., with a partially destroyed aluminum cap mkd. COR3, as shown on an unrecorded map titled MAP TO SHOW 50' ROAD EASEMENT ACROSS MINING CLAIM LOT & SURVEY NO. 49 PORTION OF THE W. 1/2 SEC. 5 T. 16 N., R. 21 E., M.D.B. & M. GOLD HILL STOREY COUNTY, NEVADA. In 2012, this position was determined by Crook to be disturbed and is not utilized in the course of this survey.

Thence N. 74°35'30" E., on line 3-4, Mineral Survey No. 49, Lot B.

- 0.20 Keystone Circle, maintained dirt surface, 25 lks. wide, bears S. 20° E. and N. 20° W.
- 1.471 Intersect the E-W center line of sec. 5, at a point from which the 1/4 sec. cor. of secs. 5 and 6, hereinbefore described, bears N. 89°41'40" W., 18.407 chs. dist.
- 6.00 Slippery Gulch Road, maintained dirt surface, 20 lks. wide, bears S. 85° E. and N. 85° W.
- 9.087 Intersect line 1-2, Mineral Survey No. 65, Alta claim, monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, with aluminum cap mkd. T16N R21E S6 MS65 MS49B PLS10836 2012, determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, as recorded in Storey County, Nevada, File No. 117835, at a point from which Cor. No. 2, hereinafter described, bears N. 9°07'10" W., 1.815 chs. dist.


DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 49,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
10.000	<p>Point for Cor. No. 4, Mineral Survey No. 49, Lot B, an unmonumented position reestablished by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, as recorded in Storey County, Nevada, File No. 117835, reestablished in this survey at record angle and distance from Cor. No. 5. This position is accepted as a careful and faithful reestablishment of the position of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div data-bbox="844 611 1023 828" style="text-align: center;"> <p>MS 65 AL MS 49 LOT B COR 4 2015</p> </div> <p>Thence S. 15°24'30" E., on line 4-5, Mineral Survey No. 49, Lot B.</p>
2.400	<p>Intersect the E-W center line of sec. 5, at a point from which the center 1/4 sec. cor. of sec. 5, hereinafter described, bears S. 89°41'40" E., 11.913 chs. dist.</p>
8.561	<p>Point for Cor. No. 5, Mineral Survey No. 49, Lot B, an unmonumented position reestablished by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, as recorded in Storey County, Nevada, File No. 117835, reestablished in this survey at record angle from a line between Cor. Nos. 2 and 6, Mineral Survey No. 49, Lot B, and record distance from Cor. No. 6. This position is accepted as a careful and faithful reestablishment of the position of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div data-bbox="828 1419 1071 1595" style="text-align: center;"> <p>MS 49 LOT B COR 5 MS 65 AL 2015</p> </div> <p>Thence S. 74°35'30" W., on line 5-6, Mineral Survey No. 49, Lot B.</p>
1.856	<p>Intersect line 1-2, Mineral Survey No. 65, Alta claim, monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, with aluminum cap mkd. T16N R21E S5 MS65 MS49B PLS10836, determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, as recorded in Storey County, Nevada, File No. 117835, at a point from which</p>

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 49,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA


CHAINS	Cor. No. 5, Mineral Survey No. 100, Memphis claim, hereinafter described, bears S. 9°07'10" E., 5.793 chs. dist.
2.551	Intersect line 4-5, Mineral Survey No. 100, Memphis claim, monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, with aluminum cap mkd. MS49B F MS100 M T16N R21E S5 PLS10836 2012, determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, as recorded in Storey County, Nevada, File No. 117835, at a point from which Cor. No. 4, hereinafter described, bears N. 16°01'00" W., 1.180 chs. dist.
4.528	Intersect line 8-1, Lot No. 26, Block 6, Range C, Gold Hill Townsite, at a point from which Angle Point No. 1, hereinafter described, bears N. 24°35'10" W., 0.933 chs. dist.
9.20	Keystone Circle, maintained dirt surface, 25 lks. wide, bears S. 20° E. and N. 20° W.
10.000	<p>Cor. No. 6, Mineral Survey No. 49, Lot B, determined by Walter G. Reid, Nevada Professional Land Surveyor No. 235, monumented with a rebar, 5/8 in. diam., 24 ins. long, firmly set, projecting 3 ins. above the ground, with aluminum cap mkd. SUR NO 49B COR6 RLS235, as shown on an unrecorded map titled MAP TO SHOW 50' ROAD EASEMENT ACROSS MINING CLAIM LOT & SURVEY NO. 49 PORTION OF THE W. 1/2 SEC. 5 T. 16 N., R. 21 E., M.D.B. & M. GOLD HILL STOREY COUNTY, NEVADA. This position was adopted by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, as recorded in Storey County, Nevada, File No. 117835, and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div data-bbox="836 1274 1047 1481" style="text-align: center;"> </div>
	<p>Insert the rebar inside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/>
	Thence N. 15°21'50" W., on line 6-7, Mineral Survey No. 49, Lot B.
0.043	Intersect line 1-2, Lot No. 26, Block 6, Range C, Gold Hill Townsite, at a point from which Angle Point No. 2, identical with Angle Point No. 1, unpatented Lot 25, Block 6, Range C, Gold Hill Townsite, hereinafter described, bears S. 65°13'50" W., 0.944 chs. dist.

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 49,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
1.279	Intersect line 3-4, Mineral Survey No. 100, Memphis claim, at a point from which Cor. No. 3, identical with Cor. No. 3, Mineral Survey No. 51, Lady Washington claim, hereinafter described, bears S. 75°21'30" W., 1.655 chs. dist.
2.038	<p>Cor. No. 7, Mineral Survey No. 49, Lot B, determined by Walter G. Reid, Nevada Professional Land Surveyor No. 235, monumented with a rebar, 5/8 in. diam., 24 ins. long, firmly set, projecting 5 ins. above the ground, with aluminum cap mkd. SURVEY NO 49-B COR7 RLS235, as shown on an unrecorded map titled MAP TO SHOW 50' ROAD EASEMENT ACROSS MINING CLAIM LOT & SURVEY NO. 49 PORTION OF THE W. 1/2 SEC. 5 T. 16 N., R. 21 E., M.D.B. & M. GOLD HILL STOREY COUNTY, NEVADA. This position was adopted by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, as recorded in Storey County, Nevada, File No. 117835, and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div data-bbox="831 934 992 1197" style="text-align: center;"> <p>MS 49 LOT B COR 7</p>  <p>T16N R21E S 5</p> <p>2015</p> </div>
0.70	Powerline, bears S. 15° E. and N. 15° W.
1.517	<p>Cor. No. 8, Mineral Survey No. 49, Lot B, on the lode line of Mineral Survey No. 49, Gold Canyon claim, reestablished by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, flush with the surface of the ground, with aluminum cap mkd. T16N R21E S5 COR8 MS49B F PLS10836 2012, as recorded in Storey County, Nevada, File No. 117835, and is accepted as a careful and faithful reestablishment of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 49,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS



2015

Insert the rebar inside the stainless steel post.


DEPENDENT RESURVEY OF MINERAL SURVEY NO. 51,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
U.S. Deputy Mineral Surveyor I.E. James in 1870

Lady Washington claim on the Granville lode

From the point for Cor. No. 1, Mineral Survey No. 51, Lady Washington claim, determined at the intersection of record angles extending from Cor. No. 2, Mineral Survey No. 51, Lady Washington claim, identical with Cor. No. 2, Mineral Survey No. 100, Memphis claim, and Cor. No. 6, Mineral Survey No. 51, Lady Washington claim; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.



2015

From this point, a position determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, bears N. 66°43'40" E., 0.100 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, with aluminum cap mkd. COR1 MS51 G T16N R21E S5 PLS10836 2012, as recorded in Storey County, Nevada, File No. 117835. Not utilized in the course of this survey.

Thence N. 28°13'30" W., on line 1-2, Mineral Survey No. 51, Lady Washington claim.

1.176

Cor. No. 1, Mineral Survey No. 100, Memphis claim, hereinafter described.

Continue measurement on line 1-2, Mineral Survey No. 51, Lady Washington claim, identical with line 1-2, Mineral Survey No. 100, Memphis claim.

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 51,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS										
5.794	Intersect line 4-5, Lot No. 26, identical in part with line 3-4, unpatented Lot No. 25, Block 6, Range C, Gold Hill Townsite, at a point from which Angle Point No. 4, Lot No. 26, identical with Angle Point No. 3, unpatented Lot No. 25, hereinafter described, bears N. 78°25'50" E., 0.705 chs. dist.									
9.364	From this point, Cor. No. 6, cancelled Mineral Survey No. 97, Easterly and Westerly claim, bears EAST, 0.018 chs. dist., monumented with a granite stone, 10x6 ins., firmly set, projecting 9 ins. above the ground, mkd. x on top face and P6 on the W. face, with an embedded mound of stone, 3 ft. diam., NE. of cor. and a steel fence post set alongside.									
11.297	<p>Cor. No. 2, Mineral Survey No. 51, Lady Washington claim, identical with Cor. No. 2, Mineral Survey No. 100, Memphis claim, monumented with a granite stone, 18x15x7 ins., firmly set, projecting 6 ins. above the ground, faintly mkd. x on top face and P2 on SW. face, with a mound of stone, 2 1/2 ft. base, 2 ft. high, NE. of cor., and a steel fence post set alongside.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border: none; margin: auto;"> <tr> <td style="padding: 0 5px;">MS 51</td> <td style="border-left: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">MS 100</td> </tr> <tr> <td style="padding: 0 5px;">L-W</td> <td style="border-left: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">ME</td> </tr> <tr> <td style="padding: 0 5px;">COR 2</td> <td style="border-left: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">COR 2</td> </tr> </table> </div> <p style="text-align: center; margin: 10px 0;">2014</p> <p>Bury the mkd. stone, and reset the steel fence post alongside the stainless steel post; leave the mound of stone in place.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Thence N. 13°13'30" W., on line 2-3, Mineral Survey No. 51, Lady Washington claim, identical with line 2-3, Mineral Survey No. 100, Memphis claim.</p>	MS 51		MS 100	L-W		ME	COR 2		COR 2
MS 51		MS 100								
L-W		ME								
COR 2		COR 2								
0.70	Power pole, powerlines extend N. 75° E. and S. 75° W.									
6.899	<p>Cor. No. 3, Mineral Survey No. 51, Lady Washington claim, identical with Cor. No. 3, Mineral Survey No. 100, Memphis claim, monumented with a granite stone, 18x14x3 ins., firmly set, projecting 4 ins. above an embedded mound of stone, 3 ft. diam., mkd. x on top face and P3 on S. face, with a steel fence post set alongside.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p>									

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 51,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS										
	<p style="text-align: center;">T16N R21E S 5</p> <div style="text-align: center;"> <table border="1" style="margin: auto;"> <tr> <td style="padding: 2px;">MS 51</td> <td style="padding: 2px;">MS 100</td> </tr> <tr> <td style="padding: 2px;">L-W</td> <td style="padding: 2px;">ME</td> </tr> <tr> <td style="padding: 2px;">COR 3</td> <td style="padding: 2px;">COR 3</td> </tr> </table> </div> <p style="text-align: center;">2015</p> <p>Bury the mkd. stone and reset the steel fence post alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Thence S. 76°46'30" W., on line 3-4, Mineral Survey No. 51, Lady Washington claim.</p>	MS 51	MS 100	L-W	ME	COR 3	COR 3			
MS 51	MS 100									
L-W	ME									
COR 3	COR 3									
2.500	<p>Cor. No. 11, Mineral Survey No. 117, Chonta claim, hereinafter described.</p> <p>Continue measurement on line 3-4, Mineral Survey No. 51, Lady Washington claim, identical with line 11-12, Mineral Survey No. 117, Chonta claim.</p>									
3.030	<p>Point for Cor. No. 4, Mineral Survey No. 51, Lady Washington claim, identical with Cor. No. 12, Mineral Survey No. 117, Chonta claim, determined at record angle and distance from Cor. No. 3, Mineral Survey No. 51, Lady Washington claim, identical with Cor. No. 3, Mineral Survey No. 100, Memphis claim.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td style="padding: 2px;">MS 117</td> <td></td> </tr> <tr> <td style="padding: 2px;">CH</td> <td></td> </tr> <tr> <td style="padding: 2px;">COR 12</td> <td style="border-left: 1px solid black; padding-left: 5px;"> <table style="margin: 0;"> <tr> <td style="padding: 2px;">MS 51</td> </tr> <tr> <td style="padding: 2px;">L-W</td> </tr> <tr> <td style="padding: 2px;">COR 4</td> </tr> </table> </td> </tr> </table> </div> <p style="text-align: center;">2015</p> <p>Point is located on northeasterly bank of seasonal creek, drains S. 30° E.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Thence S. 13°13'30" E., on line 4-5, Mineral Survey No. 51, Lady Washington claim, identical with line 12-13, Mineral Survey No. 117, Chonta claim.</p>	MS 117		CH		COR 12	<table style="margin: 0;"> <tr> <td style="padding: 2px;">MS 51</td> </tr> <tr> <td style="padding: 2px;">L-W</td> </tr> <tr> <td style="padding: 2px;">COR 4</td> </tr> </table>	MS 51	L-W	COR 4
MS 117										
CH										
COR 12	<table style="margin: 0;"> <tr> <td style="padding: 2px;">MS 51</td> </tr> <tr> <td style="padding: 2px;">L-W</td> </tr> <tr> <td style="padding: 2px;">COR 4</td> </tr> </table>	MS 51	L-W	COR 4						
MS 51										
L-W										
COR 4										
6.40	<p>Powerline, bears N. 75° E. and S. 75° W.</p>									
7.470	<p>Point for Cor. No. 5, Mineral Survey No. 51, Lady Washington claim, identical with Cor. No. 13, Mineral Survey No. 117, Chonta claim, determined at record angle and distance from Cor. No. 4, Mineral Survey No. 51, Lady Washington claim.</p>									

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 51,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">MS 117 MS 51 CH L-W COR 13 COR 5</p> <p style="text-align: center;">2015</p> <hr/> <p>Thence S. 28°13'30" E., on line 5-6, Mineral Survey No. 51, Lady Washington claim, identical with line 13-14, Mineral Survey No. 117, Chonta claim.</p> <p>4.816 Intersect line 4-5, Lot No. 26, identical in part with line 3-4, unpatented Lot No. 25, and with line 3-4 unpatented Lot No. 24, Block 6, Range C, Gold Hill Townsite, at a point from which Angle Point No. 5, Lot No. 26, identical with Angle Point No. 3, unpatented Lot No. 24, hereinafter described, bears S. 78°25'50" W., 2.320 chs. dist.</p> <p>6.022 Cor. No. 14, Mineral Survey No. 117, Chonta claim, hereinafter described.</p> <p>Continue measurement on line 5-6, Mineral Survey No. 51, Lady Washington claim.</p> <p>11.530 Point for Cor. No. 6, Mineral Survey No. 51, Lady Washington claim, determined at record angle and distance from Cor. No. 5, Mineral Survey No. 51, Lady Washington claim; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">MS 51 L-W COR 6</p> <p style="text-align: center;">GHT LOT 26</p> <p style="text-align: center;">2014</p> <p>From this point, a position determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, bears N. 77°29'00" E., 0.095 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, with aluminum cap mkd. T16N R21E S5 COR6 MS51 G PLS10836 2012, as recorded in Storey County, Nevada, File No. 117835. Not utilized in the course of this survey.</p> <hr/> <p>N. 61°46'30" E., on line 6-1, Mineral Survey No. 51, Lady Washington claim.</p>
--------	--

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 51,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
3.075	Cor. No. 1, Mineral Survey No. 51, Lady Washington claim and point of beginning.
	<hr/> <p>DEPENDENT RESURVEY OF MINERAL SURVEY NO. 53, T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>
	<p>Reestablishment of the Survey Executed by U.S. Deputy Mineral Surveyor H. Hochholzer in 1872</p> <hr/>
	<p>Woodville claim on the Woodville lode</p> <p>From the point for Cor. No. 1, Mineral Survey No. 53, Woodville claim, on line 6-7, Mineral Survey No. 48, Justice and Independent claim, determined at record distance from Cor. No. 7, Mineral Survey No. 48, Justice and Independent claim; there is no remaining evidence of the original corner.</p>
	POINT NOT MONUMENTED
	Point is located in active mining site.
	Thence N. 41°18'00" W., on line 1-2, Mineral Survey No. 53, Woodville claim, identical with a portion of line 6-7, Mineral Survey No. 48, Justice and Independent claim.
2.437	Intersect the line bet. secs. 5 and 8, at a point from which the 1/4 sec. cor. of secs. 5 and 8, hereinbefore described, bears S. 89°40'50" E., 7.549 chs. dist.
2.941	Point for Cor. No. 2, Mineral Survey No. 53, Woodville claim, determined at record distance from Cor. No. 1, Mineral Survey No. 53, Woodville claim; there is no remaining evidence of the original corner.
	POINT NOT MONUMENTED
	Point is located in active mining site.
	<p>From this point, a position determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, bears N. 9°34'50" W., 0.754 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, with aluminum cap mkd. WC T16N R21E S5 MS48 J COR2 MS53 W, as recorded in Storey County, Nevada, File No. 117835. Not utilized in the course of this survey.</p> <hr/>
	Thence N. 8°28'20" W., on line 2-3, Mineral Survey No. 53, Woodville claim.
3.30	Nevada State Route 342, asphalt surface, 35 lks. wide, bears S. 35° E. and N. 35° W.
3.90	Powerline, bears S. 35° E. and N. 35° W.


DEPENDENT RESURVEY OF MINERAL SURVEY NO. 53,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
11.495	Intersect line 5-6, Mineral Survey No. 48, Justice and Independent claim, at a point from which Cor. No. 5, hereinbefore described, bears N. 48°45'00" E., 3.123 chs. dist.
13.931	Intersect line 3-4, Lot No. 28, identical with a portion of line 1-2, unpatented Lot No. 29, Block 6, Range C, Gold Hill Townsite, at a point from which Angle Point No. 4, Lot No. 28, identical with Angle Point No. 5, unpatented Lot No. 27, hereinafter described, bears N. 51°28'10" E., 1.476 chs. dist.
16.964	Intersect line 4-1, Lot No. 28, identical with line 4-5, unpatented Lot No. 27, Block 6, Range C, Gold Hill Townsite, at a point from which Angle Point No. 1, Lot No. 28, identical with Angle Point No. 4, unpatented Lot No. 27, and Cor. No. 4, Mineral Survey No. 48, Justice and Independent claim, on line 7-8, Lot No. 26, Block 6, Range C, Gold Hill Townsite, hereinbefore described, bears N. 37°34'30" W., 0.854 chs. dist.
17.040	<p>Cor. No. 3, Mineral Survey No. 53, Woodville claim, determined by person(s) unknown, monumented with a rebar, 1/2 in. diam., 36 ins. long, firmly set, projecting 11 ins. above an embedded mound of stone, 3 ft. diam., with a steel fence post set alongside. This position was adopted by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, as recorded in Storey County, Nevada, File No. 117835, and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>MS 48 J-I</p> <div style="border-left: 1px solid black; border-bottom: 1px solid black; padding-left: 5px; display: inline-block;"> <p>MS 53 WO COR 3</p> </div> </div> <p>2015</p> <p>Bury the rebar alongside the stainless steel post, leave the steel fence post in place.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Thence N. 80°38'30" E., on a portion of line 3-4, Mineral Survey No. 53, Woodville claim.</p>
0.035	Intersect line 4-5, Mineral Survey No. 48, Justice and Independent claim, at a point from which Cor. No. 4, identical with Angle Point No. 1, Lot No. 28, and Angle Point No. 4, unpatented Lot No. 27, on line 7-8, Lot No. 26, Block 6, Range C, Gold Hill Townsite, hereinbefore described, bears N. 42°23'00" W., 0.807 chs. dist.
1.151	Cor. No. 1, Mineral Survey No. 65, Alta claim, hereinafter described.


DEPENDENT RESURVEY OF MINERAL SURVEY NO. 53,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS									
	<p>Thence N. 81°46'20" E., on a portion of line 3-4, Mineral Survey No. 53, Woodville claim, identical with a portion of line 4-1, Mineral Survey No. 65, Alta claim.</p>								
1.862	<p>Cor. No. 4, Mineral Survey No. 53, Woodville claim, determined by person(s) unknown, monumented with a rebar, 1/2 in. diam., 36 ins. long, firmly set, projecting 7 ins. above a mound of stone, 3 ft. base, 1/2 ft. high, with a steel fence post set alongside. This position was adopted by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, as recorded in Storey County, Nevada, File No. 117835, and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1" data-bbox="857 803 1040 948"> <tr> <td colspan="2" data-bbox="889 803 1019 830">MS 65 AL</td> </tr> <tr> <td data-bbox="862 861 954 888">MS 53</td> <td data-bbox="976 861 1040 888">T16N</td> </tr> <tr> <td data-bbox="911 893 954 919">WO</td> <td data-bbox="976 893 1040 919">R21E</td> </tr> <tr> <td data-bbox="873 924 954 951">COR 4</td> <td data-bbox="976 924 1036 951">S 5</td> </tr> </table> <p data-bbox="922 982 987 1009">2015</p> </div> <p>Bury the rebar alongside the stainless steel post, leave the steel fence post on top of the mound of stone.</p>	MS 65 AL		MS 53	T16N	WO	R21E	COR 4	S 5
MS 65 AL									
MS 53	T16N								
WO	R21E								
COR 4	S 5								
	<p>Thence S. 8°55'20" E., on line 4-5, Mineral Survey No. 53, Woodville claim.</p>								
17.920	<p>Intersect the line bet. secs. 5 and 8, at a point from which the 1/4 sec. cor. of secs. 5 and 8, hereinbefore described, bears S. 89°40'50" E., 4.632 chs. dist.</p>								
19.10	<p>Powerline, bears S. 35° E. and N. 35° W.</p>								
19.76	<p>Nevada State Route 342, asphalt surface, 35 lks. wide, bears S. 35° E. and N. 35° W.</p>								
21.992	<p>Point for Cor. No. 5, Mineral Survey No. 53, Woodville claim, identical with Cor. No. 4, Mineral Survey No. 84, Tarto claim, determined at the extension of line 6-7, Mineral Survey No. 48, Justice and Independent claim, and at record distance from Cor. No. 7, identical with Cor. No. 3, Mineral Survey No. 84, Tarto claim, using the record from Mineral Survey No. 84; there is no remaining evidence of the original corner.</p> <p>POINT NOT MONUMENTED</p> <p>Point is located in active mining site.</p>								
	<p>Thence N. 41°18'00" W., on line 5-1, Mineral Survey No. 53, Woodville claim, identical in part with line 3-4, Mineral Survey No. 84, Tarto claim.</p>								



DEPENDENT RESURVEY OF MINERAL SURVEY NO. 53,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
1.227	Cor. No. 7, Mineral Survey No. 48, Justice and Independent claim, identical with Cor. No. 3, Mineral Survey No. 84, Tarto claim, hereinbefore described.
2.939	The point for Cor. No. 1, Mineral Survey No. 53, Woodville claim and point of beginning.
<hr/> DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 55, T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA <hr/>	
Reestablishment of Portions of the Survey Executed by U.S. Deputy Mineral Surveyor H. Hochholzer in 1872 <hr/>	
Keystone claim on the Comstock lode From the point for Cor. No. 1, Mineral Survey No. 55, Keystone claim, determined at record angle and distance from Cor. No. 2, Mineral Survey No. 55, Keystone claim; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.	
	
Point is located at toe of reestablished hill. Thence S. 72°27'00" W., on line 1-2, Mineral Survey No. 55, Keystone claim.	
1.561	Intersect line 2-3, Lot No. 43, Block 8, Range D, Gold Hill Townsite, at a point from which the point for Angle Point No. 3, identical with Angle Point No. 2, Lot No. 43 1/2, Block 8, Range D, Gold Hill Townsite, hereinafter described, bears S. 21°51'40" E., 1.025 chs. dist.
4.546	Point for Cor. No. 2, Mineral Survey No. 55, Keystone claim, determined at record angle and distance from Cor. No. 3, Mineral Survey No. 55, Keystone claim; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush in the ground, over a plastic-encased magnet, with brass cap mkd.

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 55,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<div style="text-align: center;">  <p>2015</p> </div>
	<p>From this point, a position determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, bears S. 85°56'10" W., 0.192 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, 2 ins. below the surface of the ground, with aluminum cap mkd. T16N R21E S5 COR2 MS55 K PLS10836 2012, as recorded in Storey County, Nevada, File No. 117835. Not utilized in the course of this survey.</p>
	<hr/> <p>Thence S. 17°33'00" E., on line 2-3, Mineral Survey No. 55, Keystone claim.</p>
1.284	<p>Intersect line 8-9, unpatented Lot No. 51, Block 8, Range D, Gold Hill Townsite, at a point from which Angle Point No. 8, identical with Angle Point No. 2, unpatented Lot No. 44, Block 8, Range D, Gold Hill Townsite, hereinafter described, bears S. 58°23'40" E., 0.352 chs. dist.</p>
11.30	<p>Powerline, bears N. 65° E. and S. 65° W.</p>
11.652	<p>Intersect line 3-4, unpatented Lot No. 51, Block 8, Range D, Gold Hill Townsite, at a point from which Angle Point No. 4, identical with Angle Point No. 3, unpatented Lot No. 49, Block 8, Range D, Gold Hill Townsite, hereinafter described, bears N. 71°14'10" E., 2.645 chs. dist.</p>
16.364	<p>Cor. No. 3, Mineral Survey No. 55, Keystone claim, identical with Cor. No. 1, Mineral Survey No. 48, Justice and Independent claim, hereinbefore described.</p>
	<hr/> <p>From Cor. No. 2, Mineral Survey No. 48, Justice and Independent claim, on line 3-4, Mineral Survey No. 55, Keystone claim, hereinbefore described.</p>
	<p>Thence N. 67°01'00" E., on a portion of line 3-4, Mineral Survey No. 55, Keystone claim.</p>
1.40	<p>Nevada State Route 342, asphalt surface, 35 lks. wide, bears S. 25° E. and N. 15° W.</p>
1.431	<p>Cor. No. 5, Mineral Survey No. 117, Chonta claim, hereinafter described.</p>
	<p>Continue measurement on line 3-4, Mineral Survey No. 55, Keystone claim, identical with line 5-6, Mineral Survey No. 117, Chonta claim.</p>
2.825	<p>Point for Cor. No. 4, Mineral Survey No. 55, Keystone claim, identical with Cor. No. 6, Mineral Survey No. 117, Chonta claim, determined at the intersection of record angles from Cor. Nos. 3 and 5, Mineral Survey No. 55, Keystone claim; there is no remaining evidence of the original corner.</p>

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 55,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. below the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;">  <p>MS 55 MS 117 KE CH COR 4 COR 6</p> <p>2015</p> </div> <hr style="width: 30%; margin: 10px auto;"/> <p>Thence N. 17°33'00" W., on line 4-5, Mineral Survey No. 55, Keystone claim, identical with line 6-7, Mineral Survey No. 117, Chonta claim.</p> <p>2.10 Powerline, bears S. 25° E. and N. 25° W.</p> <p>5.10 Powerline, bears S. 75° E. and N. 75° W.</p> <p>13.010 Intersect line 3-4, Lot No. 17, identical with line 1-2, unpatented Lot No. 19, Block 6, Range C, Gold Hill Townsite, at a point from which Angle Point No. 3, identical with Angle Point No. 2, hereinafter described, bears S. 66°33'40" W., 0.435 chs. dist.</p> <p>14.544 Intersect line 2-3, Lot No. 17, Block 6, Range C, Gold Hill Townsite, at a point from which Angle Point No. 3, identical with Angle Point No. 2, unpatented Lot No. 19, Block 6, Range C, Gold Hill Townsite, hereinafter described, bears S. 2°13'00" E., 1.637 chs. dist.</p> <p>15.643 Point for Cor. No. 5, Mineral Survey No. 55, Keystone claim, identical with Cor. No. 7, Mineral Survey No. 117, Chonta claim, determined at record angle and distance from Cor. No. 2, Mineral Survey No. 55, Keystone claim; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;">  <p>MS 55 MS 117 KE CH COR 5 COR 7</p> <p>2015</p> </div> <p>Point is located in drainage, drains S. 20° E.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>Thence S. 72°27'00" W., on line 5-1, Mineral Survey No. 55, Keystone claim, identical with line 7-8, Mineral Survey No. 117, Chonta claim.</p> <p>0.909 Cor. No. 8, Mineral Survey No. 117, Chonta claim, hereinafter described.</p>
--------	---

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 55,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Continue measurement on line 5-1, Mineral Survey No. 55, Keystone claim.</p> <p>1.00 Powerline, bears S. 15° E. and N. 15° W.</p> <p>1.44 Nevada State Route 342, asphalt surface, 35 lks. wide, bears S. 15° E. and N. 15° W.</p> <p>1.901 Intersect line 4-5, Lot No. 43, Block 8, Range D, Gold Hill Townsite, at a point from which the point for Angle Point No. 4, identical with Angle Point No. 1, Lot No. 43 1/2, Block 8, Range D, Gold Hill Townsite, hereinafter described, bears S. 21°51'20" E., 0.822 chs. dist.</p> <p>3.030 Cor. No. 1, Mineral Survey No. 55, Keystone claim.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 65, T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of a Portion of the Survey Executed by U.S. Deputy Mineral Surveyor H. Hochholzer in 1873</p> <hr/> <p style="text-align: center;">Alta claim on the Woodville lode</p> <p>From Cor. No. 1, Mineral Survey No. 65, Alta claim, on line 3-4, Mineral Survey No. 53, Woodville claim, monumented with a basalt stone, 22x8x7 ins., firmly set, projecting 4 ins. above the ground, mkd. x on top face and P1 on NE. face, with a mound of stone 2 1/2 ft. base, 1 1/2 ft. high, SW. of cor., and a steel fence post set alongside.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 2px;">T16N</td> <td style="padding: 2px;">MS 65</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px;">R21E</td> <td style="padding: 2px;">AL</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px;">S 5</td> <td style="padding: 2px;">COR 1</td> </tr> </table> <hr style="width: 50%; margin: 5px auto;"/> <p style="margin: 0 auto;">MS 53 WO</p> <p style="margin: 0 auto;">2015</p> </div> <p>Bury the mkd. stone in the mound of stone, alongside the stainless steel post.</p> <p>Thence N. 9°07'10" W., on line 1-2, Mineral Survey No. 65, Alta claim.</p> <p>1.095 Cor. No. 6, Mineral Survey No. 100, Memphis claim, hereinafter described.</p>	T16N	MS 65	R21E	AL	S 5	COR 1
T16N	MS 65						
R21E	AL						
S 5	COR 1						


DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 65,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	Continue measurement on line 1-2, Mineral Survey No. 65, Alta claim, identical with line 5-6, Mineral Survey No. 100, Memphis claim.
1.254	Intersect line 7-8, Lot No. 26, identical in part with line 3-4, unpatented Lot No. 27, Block 6, Range C, Gold Hill Townsite, monumented with a rebar, 5/8 in. diam., firmly set, projecting 2 ins. above a collar of stone, determined by Greg Hess, Nevada Professional Land Surveyor No. 3921, in 2002, as recorded in Storey County, Nevada, File No. 92782, at a point from which Angle Point No. 8, identical with Angle Point No. 3, hereinafter described, bears N. 60°22'30" E., 1.505 chs. dist.
6.875	Intersect line 8-1, Lot No. 26, identical in part with line 2-3, unpatented Lot No. 27, Block 6, Range C, Gold Hill Townsite, at a point from which Angle Point No. 8, identical with Angle Point No. 3, hereinafter described, bears S. 24°35'10" E., 5.286 chs. dist. From this point, a position determined by Greg Hess, Nevada Professional Land Surveyor No. 3921, in 2002, bears N. 15°58'30" W., 0.005 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, projecting 4 ins. above the ground, with tag mkd. PLS3921, as recorded in Storey County, Nevada, File No. 92782.
10.974	Cor. No. 5, Mineral Survey No. 100, Memphis claim, hereinafter described. Continue measurement on line 1-2, Mineral Survey No. 65, Alta claim.
12.00	Powerline, bears N. 75° E. and S. 75° W.
12.330	A position determined by Greg Hess, Nevada Professional Land Surveyor No. 3921, in 2002, monumented with a rebar, 5/8 in. diam., firmly set, projecting 5 ins. above a collar of stone, with tag mkd. PLS3921, as recorded in Storey County, Nevada, File No. 92782.
16.767	Intersect line 5-6, Mineral Survey No. 49, Lot B, monumented with a rebar, hereinbefore described, at a point from which Cor. No. 5, hereinbefore described, bears N. 74°35'30" E., 1.856 chs. dist.
19.70	Slippery Gulch Road, maintained dirt surface, 20 lks. wide, bears S. 20° E. and N. 20° W.
23.289	Intersect the E-W center line of sec. 5, at a point from which the center 1/4 sec. cor. of sec. 5, hereinafter described, bears S. 89°41'40" E., 13.099 chs. dist.
23.864	From this point, Cor. No. 2, cancelled Mineral Survey No. 97, Easterly and Westerly claim, bears EAST, 0.030 chs. dist., monumented with a granite stone, 20x12x6 ins., loosely set, projecting 12 ins. above an embedded mound of stone, 3 ft. diam., mkd. x on top face and NE on W. face, with a steel fence post set alongside.
25.380	Intersect line 3-4, Mineral Survey No. 49, Lot B, monumented with a rebar, hereinbefore described, at a point from which



DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 65,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p>	<p>Cor. No. 4, hereinbefore described, bears N. 74°35'30" E., 0.913 chs. dist.</p>
<p>27.195</p>	<p>Cor. No. 2, Mineral Survey No. 65, Alta claim, monumented with a basalt stone, 12x12x8 ins., loosely set in a mound of stone, 3 1/2 ft. base, 1 ft. high, mkd. x on top face and P2 on SW. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div data-bbox="808 644 1068 810" style="text-align: center;"> <p>T16N R21E S 5</p> </div> <p>2015</p> <p>Bury the mkd. stone alongside the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/> <p>Thence N. 81°06'40" E., on line 2-3, Mineral Survey No. 65, Alta claim.</p>
<p>9.155</p>	<p>Cor. No. 3, Mineral Survey No. 65, Alta claim, monumented with a basalt stone, 22x13x9 ins., firmly set, projecting 6 ins. above a scattered and embedded mound of stone, 3 1/2 ft. diam., mkd. x on top face and P3 on SW. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div data-bbox="865 1348 1101 1514" style="text-align: center;"> <p>T16N R21E S 5</p> </div> <p>2015</p> <p>Bury the mkd. stone alongside the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/> <p>Thence S. 9°04'00" E., on line 3-4, Mineral Survey No. 65, Alta claim.</p>
<p>5.388</p>	<p>Intersect the E-W center line of sec. 5, at a point from which the center 1/4 sec. cor. of sec. 5, hereinafter described, bears S. 89°41'40" E., 3.823 chs. dist.</p>
<p>14.10</p>	<p>Powerline, bears N. 75° E. and S. 75° W.</p>

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 65,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
17.316	A position determined by Greg Hess, Nevada Professional Land Surveyor No. 3921, in 2002, monumented with a rebar, 5/8 in. diam., firmly set, 2 ins. below the surface of the ground, with tag mkd. PLS3921, and a steel fence post set alongside, as recorded in Storey County, Nevada, File No. 92782.
27.247	Cor. No. 4, Mineral Survey No. 65, Alta claim, determined by person(s) unknown, monumented with a rebar, 5/8 in. diam., 20 ins. long, firmly set, projecting 2 ins. above the ground, with a steel fence post set alongside. This position has been adopted by professional land surveyors and is accepted as the best available evidence of the position of the original corner.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	
	2015
	Insert rebar inside the stainless steel post.
	Thence S. 81°21'00" W., on a portion of line 4-1, Mineral Survey No. 65, Alta claim.
7.268	Cor. No. 4, Mineral Survey No. 53, Woodville claim, hereinbefore described.
	<p style="text-align: center;">DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 100, T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA</p>
	<p style="text-align: center;">Reestablishment of Portions of the Survey Executed by U.S. Deputy Mineral Surveyor R.E. Browne in 1875</p>
	<p style="text-align: center;">Memphis claim on the Comstock lode</p>
	From Cor. No. 3, Mineral Survey No. 100, Memphis claim, identical with Cor. No. 3, Mineral Survey No. 51, Lady Washington claim, hereinbefore described.
	Thence N. 75°21'30" E., on line 3-4, Mineral Survey No. 100, Memphis claim.
0.139	Intersect the lode line of Mineral Survey No. 49, Gold Canyon claim, at a point from which Cor. No. 8, Mineral Survey No. 49, Lot B, hereinbefore described, bears N. 15°24'30" W., 0.745 chs. dist.

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 100,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA


CHAINS	
0.90	Powerline, bears S. 15° E. and N. 15° W.
1.655	Intersect line 6-7, Mineral Survey No. 49, Lot B, at a point from which Cor. No. 7, hereinbefore described, bears N. 15°21'50" W., 0.759 chs. dist.
2.30	Keystone Circle, maintained dirt surface, 25 lks. wide, bears S. 20° E. and N. 20° W.
9.091	Point for Cor. No. 4, Mineral Survey No. 100, Memphis claim, at record angle and distance from Cor. No. 3, Mineral Survey No. 100, Memphis claim; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in collar of stone, with brass cap mkd.
	<div style="text-align: right; margin-right: 100px;">MS 49 Lot B</div>  <p style="text-align: center;">2015</p> <hr style="width: 30%; margin: 10px auto;"/> <p>Thence S. 16°01'00" E., on line 4-5, Mineral Survey No. 100, Memphis claim.</p>
1.180	Intersect line 5-6, Mineral Survey No. 49, Lot B, monumented with a rebar, hereinbefore described, at a point from which Cor. No. 5, hereinbefore described, bears N. 74°35'30" E., 2.551 chs. dist.
6.939	Point for Cor. No. 5, Mineral Survey No. 100, Memphis claim, on line 1-2, Mineral Survey No. 65, Alta claim, determined at record distance from Cor. No. 6, Mineral Survey No. 100, Memphis claim, on line 1-2, Mineral Survey No. 65, Alta claim; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	 <p style="text-align: center;">2015</p>

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 100,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From this point, a position determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, bears N. 7°05'10" W., 0.016 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, with aluminum cap mkd. T16N R21E S5 COR5 MS100 M MS6 W PLS10836, as recorded in Storey County, Nevada, File No. 117835. Not utilized in the course of this survey.</p> <hr/> <p>From Cor. No. 6, Mineral Survey No. 100, Memphis claim, on line 1-2, Mineral Survey No. 65, Alta claim, monumented with a basalt stone, 20x13x6 ins., firmly set, projecting 4 ins. above an embedded mound of stone, 4 ft. diam., mkd. x on top face and P1 on N. face, with a steel fence post set alongside.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">MS 100</td> <td style="padding: 2px 5px;"></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">ME</td> <td style="padding: 2px 5px;"></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">COR 6</td> <td style="padding: 2px 5px;">MS 65</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">T16N</td> <td style="padding: 2px 5px;">AL</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">R21E</td> <td style="padding: 2px 5px;"></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S 5</td> <td style="padding: 2px 5px;"></td> </tr> </table> <p style="margin-top: 5px;">2015</p> </div> <p>Bury the mkd. stone alongside the stainless steel post.</p> <p>Thence S. 75°41'30" W., on line 6-1, Mineral Survey No. 100, Memphis claim.</p> <p>0.565 Intersect line 7-8, Lot No. 26, identical in part with line 3-4, unpatented Lot No. 27, Block 6, Range C, Gold Hill Townsite, at a point from which Angle Point No. 4, Mineral Survey No. 48, Justice and Independent claim, identical with Angle Point No. 1, Lot No. 28, and Angle Point No. 4, unpatented Lot No. 27, Block 6, Range C, Gold Hill Townsite, hereinafter described, bears S. 60°22'30" W., 1.064 chs. dist.</p> <p>6.101 Point for Cor. No. 1, Mineral Survey No. 100, Memphis claim, on line 1-2, Mineral Survey No. 51, Lady Washington claim, determined at record distance from Cor. No. 2, Mineral Survey No. 100, Memphis claim; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>	MS 100		ME		COR 6	MS 65	T16N	AL	R21E		S 5	
MS 100													
ME													
COR 6	MS 65												
T16N	AL												
R21E													
S 5													

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 100,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS



2014

From this point, a position determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, bears N. 54°50'20" E., 0.092 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, with aluminum cap mkd. MS51 G COR1 MS100 M T16N R21E S5 COR5 PLS10836, 2012, as recorded in Storey County, Nevada, File No. 117835. Not utilized in the course of this survey.


DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 117,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of Portions of the Survey Executed by
U.S. Deputy Mineral Surveyor I.E. James in 1876

Chonta claim on the Front Comstock Ledge

From the point for Cor. No. 1, Mineral Survey No. 117, Chonta claim, on line 8-1, Mineral Survey No. 48, Justice and Independent claim, determined at record distance from Cor. No. 3, Mineral Survey No. 117, Chonta claim; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.




2015

From this point, a position determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, bears N. 68°23'00" W., 0.104 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, projecting 1 in. above the ground, with aluminum cap mkd. COR1 MS117 FCL MS48 J T16N R21E S5 PLS10836 2012, as recorded in Storey County, Nevada, File No. 117835. Not utilized in the course of this survey.

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 117,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
1.667	<p>Thence S. 70°06'40" W., on line 1-2, Mineral Survey No. 117, Chonta claim.</p> <p>Point for Cor. No. 2, Mineral Survey No. 117, Chonta claim, determined at the extension of the bearing between Cor. Nos. 3 and 4, Mineral Survey No. 117, Chonta claim, and record distance from Cor. No. 3; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div data-bbox="857 611 1052 783" style="text-align: center;"> <p>MS 117 CH COR 2</p> <p>T16N R21E S 5</p> <p>2015</p> </div> <p>From this point, a position determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, bears N. 71°41'40" W., 0.105 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, with aluminum cap mkd. T16N R21E S5 COR2 MS117 FCL PLS10836 2012, as recorded in Storey County, Nevada, File No. 117835. Not utilized in the course of this survey.</p>
3.606	<p>Thence N. 15°48'50" W., on line 2-3, Mineral Survey No. 117, Chonta claim.</p> <p>Point for Cor. No. 3, Mineral Survey No. 117, Chonta claim, on line 8-1, Mineral Survey No. 48, Justice and Independent claim, determined at the intersection of the extension of line 4-5, Mineral Survey No. 117, Chonta claim, with line 8-1, Mineral Survey No. 48, Justice and Independent claim; there is no remaining evidence of the original corner.</p> <p>POINT NOT MONUMENTED</p> <p>Point is located in active mining site.</p> <p>From this point, a position determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, bears S. 41°18'10" W., 0.115 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, with aluminum cap mkd. WC FCL T16N R21E S5 COR3 MS117 MS48 J PLS10836 2012, as recorded in Storey County, Nevada, File No. 117835. Not utilized in the course of this survey.</p> <p>From the point for Cor. No. 4, Mineral Survey No. 117, Chonta claim, on line 2-3, Mineral Survey No. 48, Justice and Independent claim, determined at the intersection of the extension of the bearing between Cor. Nos. 8 and 5, Mineral Survey No. 117, Chonta claim, with line 2-3, Mineral Survey</p>


DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 117,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>No. 48, Justice and Independent claim; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;">  <p>2015</p> </div> <p>From this point, a position determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, bears N. 81°12'10" W., 0.136 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, with aluminum cap mkd. MS48 J T16N R21E S5 COR4 MS117 FCL PLS10836 2012, as recorded in Storey County, Nevada, File No. 117835. Not utilized in the course of this survey.</p> <p>Thence N. 15°48'50" W., on line 4-5, Mineral Survey No. 117, Chonta claim.</p> <p>0.342 Intersect line 3-4, Lot No. 54, identical with line 1-2, unpatented Lot No. 55, Block 8, Range D, Gold Hill Townsite, at a point from which Angle Point No. 4, identical with Angle Point No. 1, hereinafter described, bears N. 49°29'10" E., 0.614 chs. dist.</p> <p>2.025 Intersect line 4-1, Lot No. 53, Block 8, Range D, Gold Hill Townsite, at a point from which the point for Angle Point No. 4, identical with Angle Point No. 1, Lot No. 54, Block 8, Range D, Gold Hill Townsite, hereinafter described, bears S. 37°09'40" E., 0.426 chs. dist.</p> <p>3.158 Point for Cor. No. 5, Mineral Survey No. 117, Chonta claim, on line 3-4, Mineral Survey No. 55, Keystone claim, determined at record distance from Cor. No. 6, Mineral Survey No. 117, Chonta claim, identical with Cor. No. 4, Mineral Survey No. 55, Keystone claim; there is no remaining evidence of the original corner.</p> <p>Set a magnetic nail, flush with the surface of Nevada State Route 342, 35 lks. wide, bears S. 35° E. and N. 35° W., curving N. 10° W.</p> <p>From this point, a position determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, bears N. 83°17'30" W., 0.151 chs. dist., monumented with a PK Nail and aluminum tag, set flush with the surface of Nevada State Route 342, mkd. PLS10836, as recorded in Storey County, Nevada, File No. 117835. Not utilized in the course of this survey.</p>

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 117,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the point for Cor. No. 8, Mineral Survey No. 117, Chonta claim, on line 5-1, Mineral Survey No. 55, Keystone claim, determined at record distance from Cor. No. 7, Mineral Survey No. 117, Chonta claim, identical with Cor. No. 5, Mineral Survey No. 55, Keystone claim; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">T16N</td> <td style="padding: 2px 5px;">MS 117</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">R21E</td> <td style="padding: 2px 5px;">CH</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S 5</td> <td style="padding: 2px 5px;">COR 8</td> </tr> </table> <p style="margin: 5px 0;">MS 55 KE</p> <p style="margin: 5px 0;">2015</p> </div> <p>From this point, a position determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, bears N. 88°32'40" E., 0.196 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, with aluminum cap mkd. T16N R21E S5 COR8 MS117 MS55 K PLS10836 2012, as recorded in Storey County, Nevada, File No. 117835. Not utilized in the course of this survey.</p> <p>Thence N. 15°48'50" W., on line 8-9, Mineral Survey No. 117, Chonta claim.</p> <p>3.60 Powerline, bears S. 15° E. and N. 15° W.</p> <p>5.338 Intersect the E-W center line of sec. 5, at a point from which the 1/4 sec. cor. of secs. 5 and 6, hereinbefore described, bears N. 89°41'40" W., 9.803 chs. dist.</p> <p>12.136 Point for Cor. No. 9, Mineral Survey No. 117, Chonta claim, determined at the extension of the bearing between Cor. Nos. 5 and 8, Mineral Survey No. 117, Chonta claim, and at record distance from Cor. No. 8; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 2px 5px;">T16N R21E</td> <td style="border-left: 1px solid black; padding: 2px 5px;"></td> </tr> <tr> <td style="padding: 2px 5px;">S 5</td> <td style="border-left: 1px solid black; padding: 2px 5px;"></td> </tr> </table> <div style="margin-left: 100px; margin-top: 5px;"> <table style="border-collapse: collapse;"> <tr> <td style="border-left: 1px solid black; border-bottom: 1px solid black; padding: 2px 5px;">MS 117</td> </tr> <tr> <td style="border-left: 1px solid black; padding: 2px 5px;">CH</td> </tr> <tr> <td style="border-left: 1px solid black; padding: 2px 5px;">COR 9</td> </tr> </table> </div> <p style="margin: 5px 0;">2015</p> </div> <p>From this point, a position determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, bears S. 88°36'10" W., 0.232 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, with aluminum cap mkd. T16N R21E COR9 MS117 FCL PLS10836 2012,</p>	T16N	MS 117	R21E	CH	S 5	COR 8	T16N R21E		S 5		MS 117	CH	COR 9
T16N	MS 117													
R21E	CH													
S 5	COR 8													
T16N R21E														
S 5														
MS 117														
CH														
COR 9														

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 117,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>as recorded in Storey County, Nevada, File No. 116315. Not utilized in the course of this survey.</p> <hr/> <p>Thence N. 68°01'30" E., on line 9-10, Mineral Survey No. 117, Chonta claim.</p> <p>0.60 Powerline, bears S. 5° E. and N. 5° W.</p> <p>2.607 Point for Cor. No. 10, Mineral Survey No. 117, Chonta claim, determined by parallel sidelines and at record distance from Cor. No. 11, Mineral Survey No. 117, Chonta claim; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;">  <p>T16N R21E S 5 MS 117 CH COR 10 2015</p> </div> <p>From this point, a position determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, bears N. 60°23'10" E., 0.054 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, with aluminum cap mkd. T16N R21E S5 COR10 MS117 FCL PLS10836 2012, as recorded in Storey County, Nevada, File No. 117835. Not utilized in the course of this survey.</p> <hr/> <p>Thence S. 15°48'50" E., on line 10-11, Mineral Survey No. 117, Chonta claim.</p> <p>7.827 Intersect the E-W center line of sec. 5, at a point from which the 1/4 sec. cor. of secs. 5 and 6, hereinbefore described, bears N. 89°41'40" W., 12.501 chs. dist.</p> <p>9.361 Intersect line 1-2, Lot No. 17, identical with line 3-4, unpatented Lot No. 16, Block 6, Range C, Gold Hill Townsite, at a point from which Angle Point No. 2, identical with Angle Point No. 3, hereinafter described, bears S. 61°03'10" W., 0.710 chs. dist.</p> <p>14.806 Intersect line 3-4, Lot No. 17, identical with line 1-2, unpatented Lot No. 19, Block 6, Range C, Gold Hill Townsite, at a point from which Angle point No. 3, identical with Angle Point No. 2, hereinafter described, bears S. 66°33'40" W., 2.053 chs. dist.</p> <p>16.591 Point for Cor. No. 11, Mineral Survey No. 117, Chonta claim, on line 3-4, Mineral Survey No. 51, Lady Washington claim, determined at record distance from Cor. No. 12, Mineral Survey No. 117, Chonta claim; there is no remaining evidence of the original corner.</p>
--------	---

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 117,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, over a plastic-encased magnet, and in a
collar of stone, with brass cap mkd.

MS 117 | T16N
CH | R21E
COR 11 | S 5

MS 51 L-W

2015

Point is located in drainage, drains S. 30° E.

From this point, a position determined by David C. Crook, Nevada
Professional Land Surveyor No. 10836, in 2012, bears
S. 12°07'00" E., 0.012 chs. dist., monumented with a rebar,
5/8 in. diam., firmly set, flush with the surface of the ground,
with aluminum cap mkd. T16N R21E COR11 MS117 FCL MS51 G PLS10836
2012, as recorded in Storey County, Nevada, File No. 117835.
Not utilized in the course of this survey.

From the point for Cor. No. 14, Mineral Survey No. 117, Chonta
claim, on line 5-6, Mineral Survey No. 51, Lady Washington
claim, determined at the intersection of line 5-6, Mineral
Survey No. 51, Lady Washington claim, with a line between the
end points of the end lines of Mineral Survey No. 117, Chonta
claim, when projected northeasterly to total 200 ft.; there is
no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
26 ins. in the ground, over a plastic-encased magnet, and in a
collar of stone, with brass cap mkd.

MS 117
CH
COR 14

MS 51
L-W

GHT
LOT
26

2015

From this point, a position determined by David C. Crook, Nevada
Professional Land Surveyor No. 10836, in 2012, bears
N. 24°15'20" W., 0.860 chs. dist., monumented with a rebar,
5/8 in. diam., firmly set, flush with the surface of the ground,
with aluminum cap mkd. COR15 MS117 FCL MS51 G PLS10836 2012, as
recorded in Storey County, Nevada, File No. 117835. Not
utilized in the course of this survey.

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 117,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Thence S. 16°22'50" E., on line 14-15, Mineral Survey No. 117, Chonta claim.
5.00	Powerline, bears S. 30° E. and N. 30° W.
5.529	Intersect line 6-7, Lot No. 26, Block 6, Range C, Gold Hill Townsite, at a point from which Angle Point No. 7, identical with Angle Point No. 2, Lot 30, Block 6, Range C, Gold Hill Townsite, hereinafter described, bears S. 37°37'20" E., 0.490 chs. dist.
7.945	Cor. No. 15, Mineral Survey No. 117, Chonta claim, identical with Cor. No. 3, Mineral Survey No. 48, Justice and Independent claim, hereinbefore described.
<hr/> <p>SUBDIVISION OF SECTION 5, T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>	
From the 1/4 sec. cor. of secs. 5 and 8.	
N. 0°13'10" E., on the N-S center line of sec. 5.	
32.50	Powerline, bears N. 75° E. and S. 75° W.
40.387	Point for the center 1/4 sec. cor. of sec. 5, at intersection with the E-W center line.
Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.	
<p>T16N R21E C 1/4 S 5</p>	
<p>2014</p>	
From this point, the 1/4 sec. cor. of secs. 5 and 32, on the N. bdy. of the Tp., bears N. 0°13'10" E., 40.687 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, flush in a mound of stone, 3 ft. base, 1 1/2 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 17 N., R. 21 E., executed under Group No. 736.	
From this same point, the 1/4 sec. cor. of secs. 4 and 5, bears S. 89°41'40" E., 40.328 chs. dist., at proportionate distance; there is no remaining evidence of the original corner.	
Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.	

SUBDIVISION OF SECTION 5,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	T16N R21E 1/4 S 5 S 4 2014
	<p>From this 1/4 sec. cor. of secs. 4 and 5, the cor. of secs. 4, 5, 8 and 9, hereinbefore described, bears S. 0°00'20" E., 40.294 chs. dist.</p> <p>From this same 1/4 sec. cor. of secs. 4 and 5, the cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., bears N. 0°00'20" W., 41.200 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, flush in a mound of stone, 3 ft. base, 1 1/2 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the S. bdy., T. 17 N., R. 21 E., executed under Group No. 736.</p>
	<p>From the center 1/4 sec. cor. of sec. 5.</p> <p>N. 89°41'40" W., on the E-W center line of sec. 5.</p>
3.823	Intersect line 3-4, Mineral Survey No. 65, Alta claim, at a point from which Cor. No. 3, hereinbefore described, bears N. 9°04'00" W., 5.388 chs. dist.
11.913	Intersect line 4-5, Mineral Survey No. 49, Lot B, at a point from which Cor. No. 4, hereinbefore described, bears N. 15°24'30" W., 2.400 chs. dist.
13.099	Intersect line 1-2, Mineral Survey No. 65, Alta claim, at a point from which Cor. No. 2, hereinbefore described, bears N. 9°07'10" W., 3.906 chs. dist.
13.80	Slippery Gulch Road, maintained dirt surface, 20 lks. wide, bears S. 45° E. and N. 45° W.
18.20	Slippery Gulch Road, maintained dirt surface, 20 lks. wide, bears N. 50° E. and S. 50° W.
20.773	Intersect line 3-4, Mineral Survey No. 49, Lot B, at a point from which Cor. No. 3, hereinbefore described, bears S. 74°35'30" W., 1.471 chs. dist.
22.10	Keystone Circle, maintained dirt surface, 25 lks. wide, bears S. 20° E. and N. 20° W.
23.068	Intersect line 4-1, Lot No. 17, Block 6, Range C, Gold Hill Townsite, at a point from which the point for Angle Point No. 1, identical with Angle Point No. 4, unpatented Lot No. 16, Block 6, Range C, Gold Hill Townsite, hereinafter described, bears N. 12°01'50" W., 0.283 chs. dist.
23.622	Intersect line 1-2, Lot No. 17, identical with line 3-4, unpatented Lot No. 16, Block 6, Range C, Gold Hill Townsite, at a point from which the point for Angle Point No. 1, identical with Angle Point No. 4, hereinafter described, bears N. 61°03'10" E., 0.565 chs. dist.

SUBDIVISION OF SECTION 5,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
23.876	Intersect the lode line of Mineral Survey No. 49, Gold Canyon claim, at a point from which Cor. No. 1, Mineral Survey No. 49, Lot B, hereinbefore described, bears S. 15°24'30" E., 5.841 chs. dist.
26.679	Intersect line 10-11, Mineral Survey No. 117, Chonta claim, at a point from which Cor. No. 10, hereinbefore described, bears N. 15°48'50" W., 7.827 chs. dist.
29.30	Powerline, bears S. 15° E. and N. 15° W.
29.59	Nevada State Route 342, asphalt surface, 35 lks. wide, bears S. 15° E. and N. 15° W.
29.377	Intersect line 8-9, Mineral Survey No. 117, Chonta claim, at a point from which Cor. No. 8, on line 5-1, Mineral Survey No. 55, Keystone claim, hereinbefore described, bears S. 15°48'50" E., 5.338 chs. dist.
30.492	Intersect the lode line of Mineral Survey No. 42, Front Lode Consolidated claim, at a point from which the post on the S. end of the claim, hereinbefore described, bears S. 10°44'00" E., 5.254 chs. dist.
39.180	The 1/4 sec. cor. of secs. 5 and 6.
<hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 6, T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>	
	From the 1/4 sec. cor. of secs. 6 and 7.
	N. 0°42'30" W., on the N-S center line of sec. 6.
20.158	<p>The C-S 1/16 sec. cor. of sec. 6, determined by Wm. Michael Donovan, Jr., Nevada Professional Land Surveyor No. 2617, perpetuated by John S. Parrish, Nevada Professional Land Surveyor No. 9475, monumented with a rebar, 5/8 in. diam., firmly set, projecting 5 ins. above the ground, with aluminum cap mkd. T16N R21E C-S 1/16 S6 PLS9475 2011, as recorded in Storey County, Nevada, File No. 116315, and is accepted as a careful and faithful determination of the position of the corner.</p> <p>From this cor., a position determined by person(s) unknown, bears S. 65°37'20" E., 0.491 chs. dist., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 6 ins. above a mound of stone, 2 1/2 ft. base, 1 ft. high, with a washer, 2 3/4 ins. diam., welded to the top, mkd. 1/16 COR. Not utilized in the course of this survey.</p> <p>From this same cor., a position determined by Wm. Michael Donovan, Jr., Nevada Professional Land Surveyor No. 2617, bears S. 2°43'10" W., 0.076 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, projecting 1 in. above the ground, with plastic cap mkd. WM DONOVAN JR PLS2617. Not utilized in the course of this survey.</p> <hr/>

SUBDIVISION OF SECTION 6,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>N. 0°43'10" W., beginning new measurement.</p>
20.174	<p>The center 1/4 sec. cor. of sec. 6, determined by John S. Parrish, Nevada Professional Land Surveyor No. 9475, in 2012, monumented with a rebar, 5/8 in. diam., firmly set, 4 ins. below the surface of an improved gravel road, with aluminum cap mkd. T16N R21E C1/4 S6 PLS9475 2011, as recorded in Storey County, Nevada, File No. 116315, and is accepted as a careful and faithful determination of the position of the corner.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 18 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, for a reference monument, bears N. 43°22'40" E., 91.7 lks. dist., with brass cap mkd. RM T16N R21E C 1/4 60.5 FT TO COR S6 RM 2014, and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 20 ins. in the ground, and in a mound of stone, 3 ft. base, to top, for a reference monument, bears S. 46°50'10" E., 99.5 lks. dist., with brass cap mkd. RM T16N R21E C1/4 65.7 FT TO COR S6 2014, and an arrow pointing to the cor.</p> <p>From this cor., a position determined by John S. Parrish, Nevada Professional Land Surveyor No. 9475, in 2012, bears N. 0°42'50" W., 3.825 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, projecting 3 ins. above a collar of stone, with aluminum cap mkd. MS68 POL PLS 9475 2011, as recorded in Storey County, Nevada, File No. 116315.</p> <p>From this same cor., a position determined by John S. Parrish, Nevada Professional Land Surveyor No. 9475, in 2012, bears N. 0°42'50" W., 13.032 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, flush in a collar of stone, with aluminum cap mkd. MS39 POL PLS 9475 2011, as recorded in Storey County, Nevada, File No. 116315.</p> <p>From this same cor., a position determined by John S. Parrish, Nevada Professional Land Surveyor No. 9475, in 2012, bears N. 0°42'50" W., 16.704 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with aluminum cap mkd. MS39 POL PLS 9475 2011, as recorded in Storey County, Nevada, File No. 116315.</p> <p>From this same cor., a position determined by John S. Parrish, Nevada Professional Land Surveyor No. 9475, in 2012, bears N. 0°42'50" W., 19.950 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, projecting 2 ins. above a collar of stone, with aluminum cap mkd. T16N R21E CN1/16 S6 PLS 9475 2011, as recorded in Storey County, Nevada, File No. 116315.</p> <p>From this same cor., the 1/4 sec. cor. of secs. 6 and 31, on the N. bdy. of the Tp., bears N. 0°42'50" W., 39.900 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 17 N., R. 21 E., executed</p>

SUBDIVISION OF SECTION 6,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

under Group No. 736, with an iron rod, 5/8 in. diam., firmly set alongside, projecting 13 ins. above the ground.

From this same cor., a position determined by person(s) unknown, bears N. 0°40'40" W., 20.187 chs. dist., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 12 ins. above the ground, with a washer, 2 3/4 ins. diam., welded to the top, mkd. 1/16.

From this same cor., a position determined by John S. Parrish, Nevada Professional Land Surveyor No. 9475, bears N. 89°26'50" W., 20.279 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, projecting 1 in. above a collar of stone, with aluminum cap mkd. T16N R21E C-W 1/16 S6 PLS9465 2011, as recorded in Storey County, Nevada, File No. 116315.

From this same cor., the 1/4 sec. cor. of secs. 1 and 6, on the W. bdy. of the Tp., determined by person(s) unknown, bears N. 89°26'50" W., 40.437 chs. dist., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 7 ins. above an embedded mound of stone, 3 ft. diam., with a washer, 2 3/4 ins. diam., welded to the top, mkd. 1/4 COR, and a steel fence post firmly set alongside. This position has been adopted by professional land surveyors and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T16N
1/4
R20E | R21E
S 1 | S 6

2014

Bury the iron rod alongside the stainless steel post.
From this 1/4 sec. cor. of secs. 1 and 6, on the W. bdy. of the Tp., the cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., hereinbefore described, bears S. 0°02'10" E., 40.295 chs. dist.

From this same 1/4 sec. cor. of secs. 1 and 6, on the W. bdy. of the Tp., the cor. of Tps. 16 and 17 N., Rs. 20 and 21 E., bears N. 0°06'40" W., 39.447 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 8 ins. above a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of the S. bdy., T. 17 N., R. 20 E., executed under Group No. 343.

from which

A juniper stump, 3 ft. high, 7 ins. diam. at top, bears N. 56 1/2° E., 61 lks. dist., with the marks T17N R21E S31 visible on a partially healed blaze.

SUBDIVISION OF SECTION 6,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p>	<p>A juniper, 9 ins. diam., bears S. 11 1/2° E., 119 lks. dist., with an open blaze, clearly mkd. T16N R21E S6 BT.</p> <p>A juniper, 9 ins. diam., bears S. 46°53' W., 115.6 lks., dist., with the marks T16N R20E S1 visible on a partially healed blaze.</p> <p>A juniper, stump, 1 1/2 ft. high, 9 ins. diam. at top, bears N. 43°00' W., 68.4 lks. dist., with a mostly healed blaze, no visible marks.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 5 and 6.</p> <p>N. 89°26'50" W., on the E-W center line of sec. 6.</p> <p>8.30 American Flat Road, maintained dirt surface, 50 lks. wide, bears S. 35° E. and N. 35° W.</p> <p>15.86 Barbed wire fence, bears N. 10° E. and S. 10° W., enter cemetery.</p> <p>23.86 Barbed wire fence, bears N. and S., exit cemetery.</p> <p>40.577 The center 1/4 sec. cor. of sec. 6.</p> <hr/> <p style="text-align: center;">METES-AND-BOUNDS SURVEY OF LOT NO. 17, BLOCK 6, RANGE C, GOLD HILL TOWNSITE, T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Note: Lot No. 17, Block 6, Range C, Gold Hill Townsite, was determined by compass rule adjustment between Angle Point No. 5, Lot No. 26 and Angle Point No. 1, unpatented Lot No. 20, identical with Angle Point No. 6, unpatented Lot No. 19, and Angle Point No. 2, unpatented Lot No. 25, Block 6, Range C, Gold Hill Townsite, utilizing the record of survey performed by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, as recorded in Storey County, Nevada, File No. 117835.</p> <hr/> <p>From the point for Angle Point No. 1, Lot No. 17, identical with Angle Point No. 4, unpatented Lot No. 16, Block 6, Range C, Gold Hill Townsite, an unmonumented position determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, as recorded in Storey County, Nevada, File No. 117835. This position is accepted as a careful and faithful determination of the position of the corner.</p> <p>POINT NOT MONUMENTED</p> <p>Point is located on cut bank.</p> <p>Thence S. 61°03'10" W., on line 1-2, Lot No. 17, identical with line 3-4, unpatented Lot No. 16, Block 6, Range C, Gold Hill Townsite.</p>
---------------	--

METES-AND-BOUNDS SURVEY OF
 LOT NO. 17, BLOCK 6, RANGE C, GOLD HILL TOWNSITE,
 T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
0.565	Intersect the E-W center line of sec. 5, at a point from which the 1/4 sec. cor. of secs. 5 and 6, hereinbefore described, bears N. 89°41'40" W., 15.558 chs. dist.
0.817	Intersect the lode line of Mineral Survey No. 49, Gold Canyon claim, at a point from which Cor. No. 1, Mineral Survey No. 49, Lot B, hereinbefore described, bears S. 15°24'30" E., 5.713 chs. dist.
3.581	Intersect line 10-11, Mineral Survey No. 117, Chonta claim, at a point from which Cor. No. 11, on line 3-4, Mineral Survey No. 51, Lady Washington claim, hereinbefore described, bears S. 15°48'50" E., 7.230 chs. dist.
4.291	<p>Point for Angle Point No. 2, Lot No. 17, identical with Angle Point No. 3, unpatented Lot No. 16, Block 6, Range C, Gold Hill Townsite, an unmonumented position determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, as recorded in Storey County, Nevada, File No. 117835. This position is accepted as a careful and faithful determination of the position of the corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="857 996 1068 1183" style="text-align: center;"> <p>MS 117 CH AP2 LOT 17 GHT</p> <p>2015</p> </div> <p>Point is located in drainage, drains S. 10° E.</p>
	<p>Thence S. 2°13'00" E., on line 2-3, Lot No. 17, Gold Hill Townsite.</p>
4.079	Intersect line 4-5, Mineral Survey No. 55, Keystone claim, identical with line 6-7, Mineral Survey No. 117, Chonta claim, at a point from which Cor. No. 5, identical with Cor. No. 7, hereinbefore described, bears N. 17°33'00" W., 1.099 chs. dist.
5.716	<p>Point for Angle Point No. 3, Lot No. 17, identical with Angle Point No. 2, unpatented Lot No. 19, Block 6, Range C, Gold Hill Townsite, an unmonumented position determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, as recorded in Storey County, Nevada, File No. 117835. This position is accepted as a careful and faithful determination of the position of the corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

METES-AND-BOUNDS SURVEY OF
 LOT NO. 17, BLOCK 6, RANGE C, GOLD HILL TOWNSITE,
 T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

GHT
 LOT 17
 AP3
 MS 55
 KE

2015

From this point, Angle Point No. 5, Lot No. 26, identical with Angle Point No. 3, unpatented Lot No. 24, Block 6, Range C, Gold Hill Townsite, hereinafter described, bears S. 15°20'40" E., 13.483 lks. dist.

Thence N. 66°33'40" E., on line 3-4, Lot No. 17, identical with line 1-2, unpatented Lot No. 19, Block 6, Range C, Gold Hill Townsite.

- 0.435 Intersect line 4-5, Mineral Survey No. 55, Keystone claim, identical with line 6-7, Mineral Survey No. 117, Chonta claim, at a point from which Cor. No. 5, identical with Cor. No. 7, hereinbefore described, bears N. 17°33'00" W., 2.633 chs. dist.
- 2.053 Intersect line 10-11, Mineral Survey No. 117, Chonta claim, at a point from which Cor. No. 11, on line 3-4, Mineral Survey No. 51, Lady Washington claim, hereinbefore described, bears S. 15°48'50" E., 1.785 chs. dist.
- 4.728 Intersect the lode line of Mineral Survey No. 49, Gold Canyon claim, at a point from which Cor. No. 1, Mineral Survey No. 49, Lot B, hereinbefore described, bears N. 15°24'30" W., 0.005 chs. dist.
- 4.763 Intersect line 1-2, Mineral Survey No. 49, Lot B, at a point from which Cor. No. 1, on the lode line of Mineral Survey No. 49, Gold Canyon claim, hereinbefore described, bears S. 74°57'20" W., 0.035 chs. dist.
- 5.182 Point for Angle Point No. 4, Lot No. 17, identical with Angle Point No. 1, unpatented Lot No. 19, Block 6, Range C, Gold Hill Townsite, an unmonumented position determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, as recorded in Storey County, Nevada, File No. 117835. This position is accepted as a careful and faithful determination of the position of the corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.

GHT
 LOT 17
 AP4
 S 5
 T16N R21E

2015



METES-AND-BOUNDS SURVEY OF
 LOT NO. 17, BLOCK 6, RANGE C, GOLD HILL TOWNSITE,
 T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p>	<p>From this point, Angle Point No. 1, Lot No. 20, identical with Angle Point No. 2, unpatented Lot No. 25, and Angle Point No. 6, unpatented Lot No. 19, Block 6, Range C, Gold Hill Townsite, hereinafter described, bears S. 12°01'40" E., 3.795 chs. dist.</p> <hr/> <p>Thence N. 12°01'50" W., on line 4-1, Lot No. 17, Block 6, Range C, Gold Hill Townsite.</p> <p>5.573 Intersect the E-W center line of sec. 5, at a point from which the 1/4 sec. cor. of secs. 5 and 6, hereinbefore described, bears N. 89°41'40" W., 16.112 chs. dist.</p> <p>5.856 The point for Angle Point No. 1, Lot No. 17, identical with Angle Point No. 4, unpatented Lot No. 16, Block 6, Range C, Gold Hill Townsite and point of beginning.</p>
<p>METES-AND-BOUNDS SURVEY OF PORTIONS OF LOT NOS. 26, 28, 30 AND 31, BLOCK 6, RANGE C, GOLD HILL TOWNSITE, T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA</p>	
<p>From Angle Point No. 1, Lot No. 26, Block 6, Range C, Gold Hill Townsite, determined by person(s) unknown, monumented with a rebar, 3/8 in. diam., 24 ins. long, firmly set, projecting 9 ins. above the ground, with a steel fence post set alongside. This position has been adopted by professional land surveyors and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div data-bbox="824 1311 1040 1543" style="text-align: center;"> <p>MS 49 LOT B</p> <p>AP1 LOT 26</p> <p>GHT</p> <p>2015</p> </div> <p>Bury the rebar alongside the stainless steel post, leave the steel fence post lying on top of the mound of stone.</p> <p>Thence S. 65°13'50" W., on line 1-2, Lot No. 26, Block 6, Range C, Gold Hill Townsite.</p> <p>4.356 A position determined by Walter G. Reid, Nevada Registered Land Surveyor No. 235, in 1982, monumented with a rebar, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with a steel fence post set alongside, as recorded in Storey County, Nevada, File No. 51883.</p>	



METES-AND-BOUNDS SURVEY OF PORTIONS OF
 LOT NOS. 26, 28, 30 AND 31, BLOCK 6, RANGE C,
 GOLD HILL TOWNSITE,
 T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
4.60	Keystone Circle, maintained dirt surface, 25 lks. wide, bears S. 20° E. and N. 20° W.
5.126	A position determined by Walter G. Reid, Nevada Registered Land Surveyor No. 235, in 1982, monumented with a rebar, 5/8 in. diam., firmly set, projecting 8 ins. above the ground, with a steel fence post set alongside, as recorded in Storey County, Nevada, File No. 51883.
5.395	Intersect line 6-7, Mineral Survey No. 49, Lot B, at a point from which Cor. No. 6, hereinbefore described, bears S. 15°21'50" E., 0.043 chs. dist.
6.339	<p>Point for Angle Point No. 2, Lot No. 26, identical with Angle Point No. 1, unpatented Lot No. 25, Block 6, Range C, Gold Hill Townsite, at proportionate distance.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div data-bbox="792 845 1057 965" style="text-align: center;"> </div> <p style="text-align: center;">2015</p>
	<p>From this point, Angle Point No. 1, unpatented Lot No. 20, identical with Angle Point No. 2, unpatented Lot No. 25, and Angle Point No. 6, unpatented Lot No. 19, Block 6, Range C, Gold Hill Townsite, determined by person(s) unknown, bears S. 65°13'50" W., 0.364 chs. dist., monumented with a rebar, 3/8 in. diam., firmly set, projecting 13 ins. above the ground, with a steel fence post set alongside. This position has been adopted by professional land surveyors and is accepted as a careful and faithful determination of the position of the corner.</p>
	CORNER NOT REMONUMENTED
	<hr/> <p>Thence S. 24°49'50" E., on line 2-3, Lot No. 26, identical with line 7-1, unpatented Lot No. 25, Block 6, Range C, Gold Hill Townsite.</p>
0.40	Powerline, bears S. 15° E. and N. 15° W.
3.916	<p>Point for Angle Point No. 3, Lot No. 26, identical with Angle Point No. 7, unpatented Lot No. 25, Block 6, Range C, Gold Hill Townsite, determined by grant boundary adjustment between Angle Point Nos. 2 and 4, Lot No. 26, using bearings derived from the angular relationships shown on the Gold Hill Townsite map.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>


METES-AND-BOUNDS SURVEY OF PORTIONS OF
 LOT NOS. 26, 28, 30 AND 31, BLOCK 6, RANGE C,
 GOLD HILL TOWNSITE,
 T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<div style="text-align: center;">  <p>MS 100 ME ——— GHT LOT 26 AP3</p> </div> <p style="text-align: center;">2015</p>
	<p>Thence S. 17°49'50" E., on line 3-4, Lot No. 26, identical with line 6-7, unpatented Lot No. 25, Block 6, Range C, Gold Hill Townsite.</p>
0.90	<p>Powerline, bears N. 75° E. and S. 75° W.</p>
7.039	<p>Angle Point No. 4, Lot No. 26, identical with Angle Point No. 6, unpatented Lot No. 25, Block 6, Range C, Gold Hill Townsite, determined by person(s) unknown, monumented with a rebar, 1/2 in. diam., 24 ins. long, firmly set, projecting 2 ins. above the ground. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, and in a collar of stone with brass cap mkd.</p>
	<div style="text-align: center;">  <p>MS 100 ME ——— GHT LOT 26 AP4</p> </div> <p style="text-align: center;">2015</p>
	<p>Insert the rebar inside the stainless steel post.</p>
	<p>Thence S. 78°25'50" W., on line 4-5, Lot No. 26, identical with line 5-6, unpatented Lot No. 25, Block 6, Range C, Gold Hill Townsite.</p>
0.705	<p>Intersect line 1-2, Mineral Survey No. 51, Lady Washington claim, identical in part with line 1-2, Mineral Survey No. 100, Memphis claim, at a point from which Cor. No. 1, Mineral Survey No. 100, Memphis claim, hereinbefore described, bears S. 28°13'30" E., 4.618 chs. dist.</p>
3.914	<p>Intersect line 5-6, Mineral Survey No. 51, Lady Washington claim, identical in part with line 13-14, Mineral Survey No. 117, Chonta claim, at a point from which Cor. No. 14, hereinbefore described, bears S. 28°13'30" E., 1.206 chs. dist.</p>
4.097	<p>Angle Point No. 5, unpatented Lot No. 25, identical with Angle Point No. 4, unpatented Lot No. 24, Block 6, Range C, Gold Hill Townsite, determined by person(s) unknown, monumented with a rebar, 3/8 in. diam., firmly set, projecting 1 in. above the ground.</p>

METES-AND-BOUNDS SURVEY OF PORTIONS OF
 LOT NOS. 26, 28, 30 AND 31, BLOCK 6, RANGE C,
 GOLD HILL TOWNSITE,
 T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p> <p>5.00</p> <p>6.234</p> <p>0.269</p>	<p>Continue measurement on line 4-5, Lot No. 26, identical with line 3-4, unpatented Lot No. 24, Block 6, Range C, Gold Hill Townsite.</p> <p>Powerline, bears S. 25° E. and N. 25° W.</p> <p>Angle Point No. 5, Lot No. 26, identical with Angle Point No. 3, unpatented Lot No. 24, Block 6, Range C, Gold Hill Townsite, determined by person(s) unknown, monumented with a rebar, 3/8 in. diam., 24 ins. long, firmly set, projecting 2 ins. above the ground, with a steel fence post set alongside. This position has been adopted by professional land surveyors and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;">  <p>MS 117 CH AP5 LOT 26 GHT</p> <p>2015</p> </div> <p>Insert the rebar inside the stainless steel post, leave the steel fence post in place.</p> <hr/> <p>Thence S. 11°50'50" E., on line 5-6, Lot No. 26, Block 6, Range C, Gold Hill Townsite.</p> <p>Point for Angle Point No. 6, Lot No. 26, Block 6, Range C, Gold Hill Townsite, an unmonumented position determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, as recorded in Storey County, Nevada, File No. 117835, determined in this survey by compass rule adjustment between Angle Point No. 5, Lot No. 26, identical with Angle Point No. 3, unpatented Lot No. 24, and Angle Point No. 7, Lot No. 26, identical with Angle Point No. 2, Lot No. 30, Block 6, Range C, Gold Hill Townsite, using Crook's record. Crook's position is accepted as a careful and faithful determination of the position of the corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. below the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;">  <p>MS 117 CH GHT LOT 26 AP6</p> <p>2015</p> </div>
---	--


METES-AND-BOUNDS SURVEY OF PORTIONS OF
 LOT NOS. 26, 28, 30 AND 31, BLOCK 6, RANGE C,
 GOLD HILL TOWNSITE,
 T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Thence S. 37°37'20" E., on line 6-7, Lot No. 26, Block 6, Range C, Gold Hill Townsite.
7.120	Intersect line 14-15, Mineral Survey No. 117, Chonta claim, at a point from which Cor. No. 15, identical with Cor. No. 3, Mineral Survey No. 48, Justice and Independent claim, hereinbefore described, bears S. 16°22'50" E., 2.416 chs. dist.
7.610	Angle Point No. 7, Lot No. 26, identical with Angle Point No. 2, Lot No. 30, Block 6, Range C, Gold Hill Townsite, determined by person(s) unknown, monumented with a rebar, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with a steel fence post firmly set alongside. This position has been adopted by professional land surveyors and is accepted as a careful and faithful determination of the position of the corner.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	 <p style="text-align: center;">2015</p>
	From this cor., Angle Point No. 1, Lot No. 30, identical with Angle Point No. 2, Lot No. 28, Block 6, Range C, Gold Hill Townsite, determined by person(s) unknown, bears N. 60°22'30" E., 4.306 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with a rebar, 1/2 in. diam., firmly set alongside, projecting 3 ins. above the ground, and a steel fence post set alongside.
	Thence S. 37°37'20" E., on line 2-3, Lot No. 30, Block 6, Range C, Gold Hill Townsite.
0.90	Powerline, bears S. 30° E. and N. 30° W.
1.50	Powerline, bears S. 50° E. and N. 50° W.
1.706	Intersect line 3-4, Mineral Survey No. 48, Justice and Independent claim, at a point from which Cor. No. 3, identical with Cor. No. 15, Mineral Survey No. 117, Chonta claim, hereinbefore described, bears S. 48°45'00" W., 0.877 chs. dist.
3.970	Point for Angle Point No. 3, Lot No. 30, Block 6, Range C, Gold Hill Townsite, determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, as recorded in Storey County, Nevada, File No. 117835, reestablished in this survey by compass rule adjustment between Angle Point No. 2 and Angle Point No. 4, Lot No. 30, Block 6, Range C, Gold Hill Townsite, utilizing Crook's record. No evidence of the rebar set by Crook in 2012

METES-AND-BOUNDS SURVEY OF PORTIONS OF
 LOT NOS. 26, 28, 30 AND 31, BLOCK 6, RANGE C,
 GOLD HILL TOWNSITE,
 T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA


<p>CHAINS</p>	<p>was found. This position is accepted as a careful and faithful determination of the position of the corner.</p> <p>Set a magnetic nail, flush with the surface of Nevada State Route 342, asphalt surface, 35 lks. wide, bears S. 45° E. and N. 45° W.</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 27 ins. in the ground, for a reference monument, bears N. 7°27'10" E., 114.7 lks. dist., with brass cap mkd. RM GHT LOT30 AP3 75.7 FT TO COR 2015, and an arrow pointing to the cor.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground, for a reference monument, bears S. 83°49'30" E., 135.0 lks. dist., with brass cap mkd. RM GHT LOT30 AP3 89.1 FT TO COR 2015, and an arrow pointing to the cor.</p> <hr/> <p>Thence S. 27°20'40" E., on line 3-4, Lot No. 30, Block 6, Range C, Gold Hill Townsite.</p> <p>2.803 Angle Point No. 4, Lot No. 30, identical with Angle Point No. 2, Lot No. 31, Block 6, Range C, Gold Hill Townsite, determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, with plastic cap mkd. TRI STATE PLS10836, as recorded in Storey County, Nevada, File No. 117835. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>CORNER NOT REMONUMENTED</p> <p>Cor. is located in entrance to active mining site.</p> <hr/> <p>Thence S. 27°20'40" E., on line 2-3, Lot No. 31, Block 6, Range C, Gold Hill Townsite.</p> <p>2.727 Point for Angle Point No. 3, Lot No. 31, identical with Angle Point No. 4, unpatented Lot No. 32, Block 6, Range C, Gold Hill Townsite, determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, as recorded in Storey County, Nevada, File No. 117835, reestablished in this survey by compass rule adjustment between Angle Point No. 2 and Angle Point No. 4, Lot No. 31, Block 6, Range C, Gold Hill Townsite, utilizing Crook's record. No evidence of the rebar set by Crook in 2012 was found. This position is accepted as a careful and faithful determination of the position of the corner.</p> <p>POINT NOT MONUMENTED</p> <p>Point is located in active mining site.</p> <hr/>
---------------	--

METES-AND-BOUNDS SURVEY OF PORTIONS OF
 LOT NOS. 26, 28, 30 AND 31, BLOCK 6, RANGE C,
 GOLD HILL TOWNSITE,
 T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	Thence N. 59°05'00" E., on line 3-4, Lot No. 31, identical with line 3-4, Lot No. 32, Block 6, Range C, Gold Hill Townsite.
0.612	Intersect line 6-7, Mineral Survey No. 48, Justice and Independent claim, at a point from which Cor. No. 6, hereinbefore described, bears N. 41°18'00" W., 2.288 chs. dist.
2.50	Nevada State Route 342, asphalt surface, 35 lks. wide, bears S. 50° E. and N. 50° W.
2.90	Powerline, bears S. 50° E. and N. 50° W.
3.455	Angle Point No. 4, Lot No. 31, identical with Angle Point No. 3, unpatented Lot No. 32, Block 6, Range C, Gold Hill Townsite, determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, flush with the surface of the ground, with plastic cap mkd. TRI STATE PLS10836, as recorded in Storey County, Nevada, File No. 117835. This is accepted as a careful and faithful determination of the position of the corner.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	 <p style="text-align: center;">2015</p>
	Insert the rebar inside the stainless steel post. From this cor., a rebar, 3/8 in. diam., firmly set, projecting 12 ins. above the ground, bears N. 57°47'00" W., 1.159 chs. dist.
	Thence N. 39°28'30" W., on line 4-1, Lot No. 31, identical with line 2-3, unpatented Lot No. 32, Block 6, Range C, Gold Hill Townsite.
2.727	Angle Point No. 1, Lot No. 31, identical with Angle Point No. 2, unpatented Lot No. 32, on line 4-5, Lot No. 30, Block 6, Range C, Gold Hill Townsite, determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, flush with the surface of the ground, with plastic cap mkd. TRI STATE PLS10836, as recorded in Storey County, Nevada, File No. 117835. This is accepted as a careful and faithful determination of the position of the corner.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush. in the ground, over a plastic-encased magnet, with brass cap mkd.

METES-AND-BOUNDS SURVEY OF PORTIONS OF
 LOT NOS. 26, 28, 30 AND 31, BLOCK 6, RANGE C,
 GOLD HILL TOWNSITE,
 T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS



2015

Insert the rebar inside the stainless steel post.

From this cor., the point for Angle Point No. 2, Lot No. 31, identical with Angle Point No. 4, Lot No. 30, Block 6, Range C, Gold Hill Townsite, bears S. 59°34'50" W., 2.879 chs. dist.


Thence N. 59°34'50" E., on a portion of line 4-5, Lot No. 30, identical with line 1-2, unpatented Lot No. 32, Block 6, Range C, Gold Hill Townsite.

1.848

Angle Point No. 5, Lot No. 30, identical with Angle Point No. 1, unpatented Lot No. 32, on line 2-3, unpatented Lot No. 29, Block 6, Range C, Gold Hill Townsite, determined by person(s) unknown, monumented with a rebar, 3/8 in. diam., 21 ins. long, firmly set, projecting 4 ins. above the ground. This position was adopted by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, as recorded in Storey County, Nevada, File No. 117835, and is accepted as a careful and faithful determination of the position of the corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.



2015

Insert the rebar inside the stainless steel post.

Thence N. 36°59'20" W., on a portion of line 5-1, Lot No. 30, identical with a portion of line 2-3, unpatented Lot No. 29, Block 6, Range C, Gold Hill Townsite.

0.420

Intersect line 5-6, Mineral Survey No. 48, Justice and Independent claim, at a point from which Cor. No. 5, hereinbefore described, bears N. 48°45'00" E., 4.625 chs. dist.


METES-AND-BOUNDS SURVEY OF PORTIONS OF
 LOT NOS. 26, 28, 30 AND 31, BLOCK 6, RANGE C,
 GOLD HILL TOWNSITE,
 T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p> <p>2.600</p>	<p>Angle Point No. 3, Lot No. 28, identical with Angle Point No. 2, unpatented Lot No. 29, Block 6, Range C, Gold Hill Townsite, determined by person(s) unknown, monumented with a rebar, 3/8 in. diam., 24 ins. long, firmly set, projecting 5 ins. above the ground. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="836 638 1063 803" data-label="Diagram"> </div> <p>2015</p> <p>Bury the rebar alongside the stainless steel post.</p> <p>From this cor., a position determined by person(s) unknown, bears N. 36°59'20" E., 0.111 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, projecting 4 ins. above the ground.</p> <hr/> <p>Thence N. 51°28'10" E., on line 3-4, Lot No. 28, identical with a portion of line 1-2, unpatented Lot No. 29, Block 6, Range C, Gold Hill Townsite.</p> <p>2.661 Intersect line 2-3, Mineral Survey No. 53, Woodville claim, at a point from which Cor. No. 3, hereinbefore described, bears N. 8°28'20" W., 3.109 chs. dist.</p> <p>4.137 Angle Point No. 4, Lot No. 28, identical with Angle Point No. 5, unpatented Lot No. 27, Block 6, Range C, Gold Hill Townsite, determined by William G. Turney, Nevada Professional Land Surveyor No. 9394, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 4 ins. above the ground, with plastic cap mkd. W N TURNEY PLS9394. This position has been adopted by other professional land surveyors and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p>
----------------------------	---


METES-AND-BOUNDS SURVEY OF PORTIONS OF
 LOT NOS. 26, 28, 30 AND 31, BLOCK 6, RANGE C,
 GOLD HILL TOWNSITE,
 T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;"> GHT LOT 28 MS 48 J-I AP4 MS 53 WO 2015 </p>
	<p>Insert the rebar inside the stainless steel post.</p> <p>From this cor., a position, determined by person(s) unknown, bears N. 53°01'50" E., 3.447 chs. dist., monumented with a rebar, 3/8 in. diam., firmly set, projecting 13 ins. above the ground, with a steel fence post firmly set alongside.</p>
	<p>Thence N. 37°34'30" W., on line 4-1, Lot No. 28 identical with line 4-5, unpatented Lot No. 27, Block 6, Range C, Gold Hill Townsite.</p>
2.626	<p>Intersect line 2-3, Mineral Survey No. 53, Woodville claim, at a point from which Cor. No. 3, hereinbefore described, bears N. 8°28'20" W., 0.076 chs. dist.</p>
3.480	<p>Angle Point No. 1, Lot No. 28, identical with Angle Point No. 4, unpatented Lot No. 27, on line 7-8, Lot No. 26, Block 6, Range C, Gold Hill Townsite and Cor. No. 4, Mineral Survey No. 48, Justice and Independent claim, hereinbefore described.</p>
	<p>From this cor., Angle Point No. 2, Lot No. 28, identical with Angle Point No. 1, Lot No. 30, Block 6, Range C, Gold Hill Townsite, bears S. 60°22'30" W., 4.137 chs. dist.</p>
	<p>Thence N. 60°22'30" E., on a portion of line 7-8, Lot No. 26, identical with line 3-4, unpatented Lot No. 27, Block 6, Range C, Gold Hill Townsite.</p>
1.064	<p>Intersect line 6-1, Mineral Survey No. 100, Memphis claim, at a point from which Cor. No. 6, on line 1-2, Mineral Survey No. 65, Alta claim, hereinbefore described, bears N. 75°41'30" E., 0.565 chs. dist.</p>
1.665	<p>Intersect line 5-6, Mineral Survey No. 100, Memphis claim, identical with a portion of line 1-2, Mineral Survey No. 65, Alta claim, monumented with a rebar, hereinbefore described, at a point from which Cor. No. 6, Mineral Survey No. 100, Memphis claim, hereinbefore described, bears S. 9°07'10" E., 0.159 chs. dist.</p>
3.170	<p>Angle Point No. 8, Lot No. 26, identical with Angle Point No. 3, unpatented Lot No. 27, Block 6, Range C, Gold Hill Townsite, determined by person(s) unknown, monumented with a rebar, 3/8 in. diam., 24 ins. long, firmly set, projecting 5 ins. above the ground, and perpetuated by William G. Turney, Nevada Professional Land Surveyor No. 9394, with a rebar, 5/8 in. diam., 19 ins. long, firmly set alongside, projecting 5 ins. above the ground, with plastic cap mkd. W TURNEY PLS9394. This position has been adopted by other professional land surveyors and is accepted as a careful and faithful determination of the position of the corner.</p>


METES-AND-BOUNDS SURVEY OF PORTIONS OF
 LOT NOS. 26, 28, 30 AND 31, BLOCK 6, RANGE C,
 GOLD HILL TOWNSITE,
 T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p>	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;">  </div> <p>2015</p> <p>Insert both rebar inside the stainless steel post.</p> <p>Cor. is located in a corner of fences, one strand cable, extending N. 25° W. and S. 60° W.</p> <hr/> <p>Thence N. 24°35'10" W., on line 8-1, Lot No. 26, identical in part with line 2-3, unpatented Lot No. 27, Block 6, Range C, Gold Hill Townsite, along a one strand cable fence.</p> <p>2.009 A position determined by Greg Hess, Nevada Professional Land Surveyor No. 3921, in 2002, monumented with a rebar, 5/8 in. diam., firmly set, projecting 4 ins. above a collar of stone, with a tag mkd. PLS3921, with a steel fence post firmly set alongside, a one strand cable fence extending S. 25° E., as recorded in Storey County, Nevada, File No. 92782.</p> <p>5.286 Intersect line 5-6, Mineral Survey No. 100, Memphis claim, identical with a portion of line 1-2, Mineral Survey No. 65, Alta claim, at a point from which Cor. No. 5, hereinbefore described, bears N. 9°07'10" W., 4.099 chs. dist.</p> <p>10.40 Powerline, bears N. 75° E. and S. 75° W.</p> <p>10.592 A position determined by Walter G. Reid, Nevada Registered Land Surveyor No. 235, in 1982, monumented with a rebar, 5/8 in. diam., firmly set, projecting 6 ins. above the ground, with a steel fence post firmly set alongside, as recorded in Storey County, Nevada, File No. 51883.</p> <p>10.728 Angle Point No. 2, unpatented Lot No. 27, Block 6, Range C, Gold Hill Townsite, determined by Greg Hess, Nevada Professional Land Surveyor No. 3921, in 2002, as recorded in Storey County, Nevada, File No. 92782, and perpetuated by William G. Turney, Nevada Professional Land Surveyor No. 9394, in 2004, monumented with a rebar, 5/8 in. diam., firmly set, projecting 1 in. above the ground, with plastic cap mkd. W TURNEY PLS9394, as recorded in Storey County, Nevada, File No. 98107.</p> <p>12.514 A position determined by Walter G. Reid, Nevada Registered Land Surveyor No. 235, in 1982, monumented with a rebar, 5/8 in. diam., firmly set, projecting 7 ins. above the ground, with a steel fence post firmly set alongside, as recorded in Storey County, Nevada, File No. 51883.</p>
---------------	---

METES-AND-BOUNDS SURVEY OF PORTIONS OF
 LOT NOS. 26, 28, 30 AND 31, BLOCK 6, RANGE C,
 GOLD HILL TOWNSITE,
 T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
15.247	Intersect line 5-6, Mineral Survey No. 49, Lot B, at a point from which Cor. No. 5, hereinbefore described, bears N. 74°35'30" E., 4.528 chs. dist.
16.180	Angle Point No. 1, Lot No. 26, Block 6, Range C, Gold Hill Townsite and point of beginning.
<p>METES-AND-BOUNDS SURVEY OF PORTIONS OF LOT NOS. 43 AND 43 1/2, BLOCK 8, RANGE D, GOLD HILL TOWNSITE, T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA</p>	
<p>From Angle Point No. 1, Lot No. 43, identical with Angle Point No. 4, unpatented Lot No. 42, Block 8, Range D, Gold Hill Townsite, determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, flush with the surface of the ground, with plastic cap mkd. TRI STATE PLS10836, as recorded in Storey County, Nevada, File No. 117835. This is accepted as a careful and faithful determination of the position of the corner.</p>	
<p>At the corner point</p>	
<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>	
 <p>T16N R21E S 5 AP1 Lot 43 GHT 2015</p>	
<p>Insert the rebar inside the stainless steel post.</p>	
<p>Thence S. 85°51'40" W., on line 1-2, Lot No. 43, identical with line 3-4, unpatented Lot No. 42, Block 8, Range D, Gold Hill Townsite.</p>	
0.112	Intersect the lode line of Mineral Survey No. 42, Front Lode Consolidated claim, at a point from which the post on the S. end of the claim, hereinbefore described, bears S. 10°44'00" E., 4.272 chs. dist.
3.273	Angle Point No. 2, Lot No. 43, identical with Angle Point No. 3, unpatented Lot No. 42, Block 8, Range D, Gold Hill Townsite, determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, flush with the surface of the ground, with plastic cap mkd. TRI STATE PLS10836, as recorded in Storey County, Nevada, File No. 117835. This is accepted as a careful and faithful determination of the position of the corner.
<p>At the corner point</p>	

METES-AND-BOUNDS SURVEY OF PORTIONS OF
 LOT NOS. 43 AND 43 1/2, BLOCK 8, RANGE D, GOLD HILL TOWNSITE,
 T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;">  <p>T16N R21E S 5 AP2 Lot 43 GHT</p> <p>2015</p> </div> <p>Insert the rebar inside the stainless steel post.</p> <hr/> <p>Thence S. 21°51'40" E., on line 2-3, Lot No. 43, Block 8, Range D, Gold Hill Townsite.</p> <p>5.452 Intersect line 1-2, Mineral Survey No. 55, Keystone claim, at a point from which Cor. No. 1, hereinbefore described, bears N. 72°27'00" E., 1.561 chs. dist.</p> <p>6.477 Point for Angle Point No. 3, Lot No. 43, identical with Angle Point No. 2, Lot No. 43 1/2, Block 8, Range D, Gold Hill Townsite, determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, as recorded in Storey County, Nevada, File No. 117835, reestablished in this survey at proportionate measurement utilizing Crook's record. No evidence of the rebar set by Crook in 2012 was found. This position is accepted as a careful and faithful determination of the position of the corner.</p> <p>POINT NOT MONUMENTED</p> <p>Point is located on reestablished hill.</p> <hr/> <p>Thence S. 21°51'40" E., on line 2-3, Lot No. 43 1/2, Block 8, Range D, Gold Hill Townsite.</p> <p>0.314 Point for Angle Point No. 3, Lot No. 43 1/2, on line 1-2, unpatented Lot No. 44, Block 8, Range D, Gold Hill Townsite, determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, as recorded in Storey County, Nevada, File No. 117835, reestablished in this survey by compass rule adjustment between Angle Point No. 2, Lot No. 43, identical with Angle Point No. 3, unpatented Lot No. 42, and Angle Point No. 4, Lot No. 43 1/2, identical with Angle Point No. 1, unpatented Lot No. 44, Block 8, Range D, Gold Hill Townsite, utilizing Crook's record. No evidence of the rebar set by Crook in 2012 was found. This position is accepted as a careful and faithful determination of the position of the corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

METES-AND-BOUNDS SURVEY OF PORTIONS OF
 LOT NOS. 43 AND 43 1/2, BLOCK 8, RANGE D, GOLD HILL TOWNSITE,
 T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

MS 55 / GHT
 KE / LOT 43 1/2
 / AP3

2015

Point is located on reestablished hill.

Thence N. 68°08'20" E., on line 3-4, Lot No. 43 1/2, identical with a portion of line 1-2, unpatented Lot No. 44, Block 8, Range D, Gold Hill Townsite.

2.682 Angle Point No. 4, Lot No. 43 1/2, identical with Angle Point No. 1, unpatented Lot No. 44, Block 8, Range D, Gold Hill Townsite, determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, flush with the surface of the ground, with plastic cap mkd. TRI STATE PLS10836, with a steel fence post firmly set alongside, as recorded in Storey County, Nevada, File No. 117835. This is accepted as a careful and faithful determination of the position of the corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

GHT
 LOT 43 1/2
 AP4

T16N R21E
 S 5

2015

Insert the rebar inside the stainless steel post.

Cor. is located 25 lks. W. of W. edge of asphalt surface of Nevada State Route 342.

Thence N. 21°51'20" W., on line 4-1, Lot No. 43 1/2, Block 8, Range D, Gold Hill Townsite.

0.314 Angle Point No. 1, Lot No. 43 1/2, identical with Angle Point No. 4, Lot No. 43, Block 8, Range D, Gold Hill Townsite, determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, monumented with a rebar, 5/8 in. diam., firmly set, 15 ins. below the surface of the ground, with plastic cap mkd. TRI STATE PLS10836, as recorded in Storey County, Nevada, File No. 117835. This is accepted as a careful and faithful determination of the position of the corner.

CORNER NOT REMONUMENTED



METES-AND-BOUNDS SURVEY OF PORTIONS OF
 LOT NOS. 43 AND 43 1/2, BLOCK 8, RANGE D, GOLD HILL TOWNSITE,
 T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From this cor., the point for Angle Point No. 3, Lot No. 43, identical with Angle Point No. 2, Lot No. 43 1/2, Block 8, Range D, Gold Hill Townsite, bears S. 68°08'20" W., 2.682 chs. dist.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Thence N. 21°51'20" W., on line 4-5, Lot No. 43, Block 8, Range D, Gold Hill Townsite.</p> <p>0.822 Intersect line 5-1, Mineral Survey No. 55, Keystone claim, at a point from which Cor. No. 8, Mineral Survey No. 117, Chonta claim, hereinbefore described, bears N. 72°27'00" E., 0.992 chs. dist.</p> <p>2.788 Angle Point No. 5, Lot No. 43, Block 8, Range D, Gold Hill Townsite, determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, flush with the surface of the ground, with plastic cap mkd. TRI STATE PLS10836, as recorded in Storey County, Nevada, File No. 117835. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <p style="margin: 0;">GHT LOT 43 / T16N AP5 / R21E S 5</p> <p style="margin: 0;">2015</p> </div> <p>Insert the rebar inside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Thence N. 12°40'40" W., on line 5-1, Lot No. 43, Block 8, Range D, Gold Hill Townsite.</p> <p>2.727 Angle Point No. 1, Lot No. 43, identical with Angle Point No. 4, unpatented Lot No. 42, Block 8, Range D, Gold Hill Townsite and point of beginning.</p> <hr style="width: 80%; margin: 10px auto;"/> <p style="text-align: center;">METES-AND-BOUNDS SURVEY OF UNPATENTED LOT NO. 51, BLOCK 8, RANGE D, GOLD HILL TOWNSITE, T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From Angle Point No. 1, unpatented Lot No. 51, Block 8, Range D, Gold Hill Townsite, determined by John E. Curran, Nevada Professional Land Surveyor No. 258, in 1988, monumented with a rebar, 5/8 in. diam., 12 ins. long, firmly set, projecting 3 ins. above the ground, as recorded in Storey County, Nevada, File No. 61319. This position was adopted by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, as recorded in Storey County, Nevada, File No. 117835, and is</p>
--------	---


METES-AND-BOUNDS SURVEY OF
 UNPATENTED LOT NO. 51, BLOCK 8, RANGE D, GOLD HILL TOWNSITE,
 T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T16N R21E S 6</p> <p>AP1 Lot 51 GHT</p> </div> <p style="text-align: center;">2015</p> <p>Insert the rebar inside the stainless steel post.</p> <p>Thence S. 15°41'50" E., on line 1-2, unpatented Lot No. 51, Block 8, Range D, Gold Hill Townsite.</p> <p>14.50 American Flat Road, maintained dirt surface, 50 lks. wide, bears N. 40° E. and S. 40° W.</p> <p>25.492 Angle Point No. 2, unpatented Lot No. 51, Block 8, Range D, Gold Hill Townsite, determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of a trail road, 12 lks. wide, bears S. 40° E. and N. 40° W., with plastic cap, no marks, as recorded in Storey County, Nevada, File No. 117835. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 8 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, for a reference monument, bears S. 30°49'20" W., 90.9 lks. dist., with brass cap mkd. RM GHT LOT51 AP2 60.0 FT TO COR 2015, and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 14 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, for a reference monument, bears N. 63°03'20" W., 107.3 lks. dist., with brass cap mkd. RM GHT LOT51 AP2 70.8 FT TO COR 2015, and an arrow pointing to the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Thence N. 57°34'40" E., on line 2-3, unpatented Lot No. 51, Block 8, Range D, Gold Hill Townsite.</p> <p>4.989 Intersect the line bet. secs. 5 and 6, at a point from which the cor. of secs. 5, 6, 7 and 8, hereinbefore described, bears S. 1°13'30" E., 18.309 chs. dist.</p>
--------	---

METES-AND-BOUNDS SURVEY OF
 UNPATENTED LOT NO. 51, BLOCK 8, RANGE D, GOLD HILL TOWNSITE,
 T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>9.289 Angle Point No. 3, unpatented Lot No. 51, Block 8, Range D, Gold Hill Townsite, determined by person(s) unknown, monumented with an x chiseled in bedrock. This position has been adopted by professional land surveyors and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, in a drill hole in bedrock, with top mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>GHT LOT 51 AP3</p>  <p>T16N R21E S 5</p> </div> <p>2015</p> <p>Cor. is located under powerline, bears N. 65° E. and S. 65° W.</p> <p>From this cor., a rebar, 5/8 in. diam., firmly set, projecting 4 ins. above the ground, bears S. 55°05'10" W., 0.203 chs. dist.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Thence N. 71°14'10" E., on line 3-4, unpatented Lot No. 51, Block 8, Range D, Gold Hill Townsite.</p> <p>4.556 Intersect line 2-3, Mineral Survey No. 55, Keystone claim, at a point from which Cor. No. 3, identical with Cor. No. 1, Mineral Survey No. 48, Justice and Independent claim, hereinbefore described, bears S. 17°33'00" E., 4.712 chs. dist.</p> <p>7.201 Angle Point No. 4, unpatented Lot No. 51, on line 3-4, unpatented Lot No. 49, Block 8, Range D, Gold Hill Townsite, determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, flush with the surface of the ground, with plastic cap mkd. TRI STATE PLS10836, as recorded in Storey County, Nevada, File No. 117835. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>GHT LOT 51 AP4</p>  <p>MS 55 KE</p> </div> <p>2015</p> <p>Bury the rebar alongside stainless steel post.</p>
--------	---



METES-AND-BOUNDS SURVEY OF
 UNPATENTED LOT NO. 51, BLOCK 8, RANGE D, GOLD HILL TOWNSITE,
 T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Cor. is located on edge of active mining site.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>Thence N. 11°51'40" W., on line 4-5 unpatented Lot No. 51, Block 8, Range D, Gold Hill Townsite, identical with a portion of line 3-4, unpatented Lot No. 49, Block 8, Range D, Gold Hill Townsite.</p> <p>0.60 Powerline, bears N. 65° E. and S. 65° W.</p> <p>0.606 Angle Point No. 5, unpatented Lot No. 51, identical with Angle Point No. 3, unpatented Lot No. 49, Block 8, Range D, Gold Hill Townsite, determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 1 in. above the ground, with plastic cap mkd. TRI STATE PLS10836, as recorded in Storey County, Nevada, File No. 117835. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;">  <p>MS 55 KE AP5 LOT 51 GHT 2015</p> </div> <p>Rebar became lost between time of recovery and time of monumentation.</p> <p>Cor. is located on reestablished hill.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>Thence N. 21°51'40" W., on line 5-6, unpatented Lot 51, identical in part with line 2-3, unpatented Lot No. 45, line 2-3, unpatented Lot No. 46, line 2-3, unpatented Lot No. 47, line 2-3, unpatented Lot No. 48, and line 2-3, unpatented Lot No. 49, Block 8, Range D, Gold Hill Townsite.</p> <p>7.379 Point for Angle Point No. 6, unpatented Lot No. 51, identical with Angle Point No. 2, unpatented Lot No. 45, on line 3-4, unpatented Lot No. 44, Block 8, Range D, Gold Hill Townsite, determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, as recorded in Storey County, Nevada, File No. 117835, reestablished in this survey by compass rule adjustment between Angle Point No. 5 and Angle Point No. 7, unpatented Lot No. 51, Block 8, Range D, Gold Hill Townsite, utilizing Crook's record. No evidence of the rebar set by Crook in 2012 was found. This position is accepted as a careful and faithful determination of the position of the corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
--------	---

METES-AND-BOUNDS SURVEY OF
 UNPATENTED LOT NO. 51, BLOCK 8, RANGE D, GOLD HILL TOWNSITE,
 T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<div data-bbox="857 300 1023 538" data-label="Diagram"> </div> <p data-bbox="438 559 1055 590">Point is located on reestablished hill.</p> <hr data-bbox="690 611 1218 621"/> <p data-bbox="438 642 1396 725">Thence S. 66°31'00" W., on line 6-7, unpatented Lot No. 51, identical with a portion of line 3-4, unpatented Lot No. 44, Block 8, Range D, Gold Hill Townsite.</p> <p data-bbox="300 745 1461 963">1.758 Angle Point No. 7, unpatented Lot No. 51, identical with Angle Point No. 3, unpatented Lot No. 44, Block 8, Range D, Gold Hill Townsite, determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, monumented with a rebar, 5/8 in. diam., firmly set, 3 ins. below the surface of the ground, with plastic cap mkd. TRI STATE PLS10836, as recorded in Storey County, Nevada, File No. 117835. This is accepted as a careful and faithful determination of the position of the corner.</p> <p data-bbox="511 984 1461 1118">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 26°57'20" W., 207.4 lks. dist., with brass cap mkd. RM GHT LOT51 AP7 136.9 FT TO COR 2015, and an arrow pointing to the cor.</p> <p data-bbox="511 1139 1461 1274">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 87°39'40" W., 248.3 lks. dist., with brass cap mkd. RM GHT LOT51 AP7 163.9 FT TO COR 2015, and an arrow pointing to the cor.</p> <p data-bbox="438 1295 1071 1336">Cor. is located on E. edge of haul road.</p> <hr data-bbox="690 1346 1218 1357"/>
	<p data-bbox="438 1377 1380 1460">Thence N. 21°50'10" W., on line 7-8, unpatented Lot No. 51, identical with line 2-3, unpatented Lot No. 44, Block 8, Range D, Gold Hill Townsite.</p> <p data-bbox="300 1481 1461 1750">2.273 Angle Point No. 8, unpatented Lot No. 51, identical with Angle Point No. 2, unpatented Lot No. 44, Block 8, Range D, Gold Hill Townsite, determined by John E. Curran, Nevada Professional Land Surveyor No. 258, in 1988, monumented with a rebar, 5/8 in. diam., 12 ins. long, firmly set, projecting 2 ins. above the ground, as recorded in Storey County, Nevada, File No. 61319. This position was adopted by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, as recorded in Storey County, Nevada, File No. 117835, and is accepted as a careful and faithful determination of the position of the corner.</p> <p data-bbox="438 1771 747 1813">At the corner point</p>

METES-AND-BOUNDS SURVEY OF
 UNPATENTED LOT NO. 51, BLOCK 8, RANGE D, GOLD HILL TOWNSITE,
 T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;">  </div> <p>Insert the rebar inside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Thence N. 58°23'40" W., on line 8-9, unpatented Lot No. 51, Block 8, Range D, Gold Hill Townsite.</p> <p>0.352 Intersect line 2-3, Mineral Survey No. 55, Keystone claim, at a point from which Cor. No. 2, hereinbefore described, bears N. 17°33'00" W., 1.284 chs. dist.</p> <p>6.431 Intersect the line bet. secs. 5 and 6, at a point from which the 1/4 sec. cor. of secs. 5 and 6, hereinbefore described, bears N. 1°13'30" W., 5.238 chs. dist.</p> <p>8.124 Angle Point No. 9, unpatented Lot No. 51, Block 8, Range D, Gold Hill Townsite, determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 1 in. above the ground, with plastic cap, mkd. TRI STATE PLS 10836, as recorded in Storey County, Nevada, File No. 117835. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;">  </div> <p>Insert the rebar inside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Thence N. 66°01'50" W., on line 9-1, unpatented Lot No. 51, Block 8, Range D, Gold Hill Townsite.</p> <p>10.185 Angle Point No. 1, unpatented Lot No. 51, Block 8, Range D, Gold Hill Townsite and point of beginning.</p>
--------	---

METES-AND-BOUNDS SURVEY OF PORTIONS OF
 LOT NOS. 53 AND 54, BLOCK 8, RANGE D, GOLD HILL TOWNSITE,
 T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Note: Lot Nos. 53 and 54, Block 8, Range D, Gold Hill Townsite, were determined from a tie to Angle Point No. 1, Lot No. 53, Block 8, Range D, Gold Hill Townsite, as shown on the record of survey performed by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, as recorded in Storey County, Nevada, File No. 117835, and Crook's record bearing and distances.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the point for Angle Point No. 1, Lot No. 53, Block 8, Range D, Gold Hill Townsite, an unmonumented position determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, as recorded in Storey County, Nevada, File No. 117835. This position is accepted as a careful and faithful determination of the position of the corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 2 ins. below the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <p style="margin: 0;">T16N R21E S 5 AP1 LOT 53 GHT 2015</p> </div> <p>Point is located 8 lks. SW. of SW. edge of asphalt, Nevada State Route 342.</p> <p>From this point, a position determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, for Cor. No. 5, Mineral Survey No. 117, Chonta claim (Not utilized in the course of this survey), hereinbefore described, bears N. 0°50'00" E., 0.493 chs. dist.</p> <p>S. 68°08'20" W., on line 1-2, Lot No. 53, Block 8, Range D, Gold Hill Townsite.</p> <p>0.983 Intersect line 2-3, Mineral Survey No. 48, Justice and Independent claim, at a point from which Cor. No. 2, on line 3-4, Mineral Survey No. 55, Keystone claim, hereinbefore described, bears N. 41°18'00" W., 0.376 chs. dist.</p> <p>4.076 Point for Angle Point No. 2, Lot No. 53, Block 8, Range D, Gold Hill Townsite, an unmonumented position determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, as recorded in Storey County, Nevada, File No. 117835. This position is accepted as a careful and faithful determination of the position of the corner.</p> <p>POINT NOT MONUMENTED</p> <p>Point is located in active mining site.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Thence S. 38°01'30" E., on line 2-3, Lot No. 53, Block 8, Range D, Gold Hill Townsite.</p>
--------	--

METES-AND-BOUNDS SURVEY OF PORTIONS OF
 LOT NOS. 53 AND 54, BLOCK 8, RANGE D, GOLD HILL TOWNSITE,
 T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
2.500	<p>Point for Angle Point No. 3, Lot No. 53, identical with Angle Point No. 2, Lot No. 54, Block 8, Range D, Gold Hill Townsite, an unmonumented position determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, as recorded in Storey County, Nevada, File No. 117835. This position is accepted as a careful and faithful determination of the position of the corner.</p>
	<p>POINT NOT MONUMENTED</p>
	<p>Point is located in active mining site.</p>
	<p>From this point, Angle Point No. 1, Lot No. 54, identical with Angle Point No. 4, Lot No. 53, Block 8, Range D, Gold Hill Townsite, bears N. 49°30'00" E., 3.900 chs. dist.</p>
	<hr/> <p>Thence S. 38°01'30" E., on line 2-3, Lot No. 54, Block 8, Range D, Gold Hill Townsite.</p>
1.106	<p>Point for Angle Point No. 3, Lot No. 54, identical with Angle Point No. 2, unpatented Lot No. 55, Block 8, Range D, Gold Hill Townsite, an unmonumented position determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, as recorded in Storey County, Nevada, File No. 117835. This position is accepted as a careful and faithful determination of the position of the corner.</p>
	<p>POINT NOT MONUMENTED</p>
	<p>Point is located in active mining site.</p>
	<hr/> <p>Thence N. 49°29'10" E., on line 3-4, Lot No. 54, identical with line 1-2, unpatented Lot No. 55, Block 8, Range D, Gold Hill Townsite.</p>
3.123	<p>Intersect line 2-3, Mineral Survey No. 48, Justice and Independent claim, at a point from which Cor. No. 4, Mineral Survey No. 117, Chonta claim, hereinbefore described, bears S. 41°18'00" E., 0.311 chs. dist.</p>
3.270	<p>Intersect line 4-5, Mineral Survey No. 117, Chonta claim, at a point from which Cor. No. 4, on line 2-3, Mineral Survey No. 48, Justice and Independent claim, hereinbefore described, bears S. 15°48'50" E., 0.342 chs. dist.</p>
3.884	<p>Point for Angle Point No. 4, Lot No. 54, identical with Angle Point No. 1, unpatented Lot No. 55, Block 8, Range D, Gold Hill Townsite, an unmonumented position determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, as recorded in Storey County, Nevada, File No. 117835. This position is accepted as a careful and faithful determination of the position of the corner.</p>
	<p>Set a magnetic nail, flush with the asphalt surface of Nevada State Route 342, 35 lks. wide, bears S. 35° E. and N. 35° W.</p> <hr/>

METES-AND-BOUNDS SURVEY OF PORTIONS OF
 LOT NOS. 53 AND 54, BLOCK 8, RANGE D, GOLD HILL TOWNSITE,
 T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Thence N. 37°09'40" W., on line 4-1, Lot No. 54, Block 8, Range D, Gold Hill Townsite.
1.106	Point for Angle Point No. 1, Lot No. 54, identical with Angle Point No. 4, Lot No. 53, Block 8, Range D, Gold Hill Townsite, an unmonumented position determined by David C. Crook, Nevada Professional Land Surveyor No. 10836, in 2012, as recorded in Storey County, Nevada, File No. 117835. This position is accepted as a careful and faithful determination of the position of the corner.
	POINT NOT MONUMENTED
	Thence N. 37°09'40" W., on line 4-1, Lot No. 53, Block 8, Range D, Gold Hill Townsite.
0.426	Intersect line 4-5, Mineral Survey No. 117, Chonta claim, at a point from which Cor. No. 5, on line 3-4, Mineral Survey No. 55, Keystone claim, hereinbefore described, bears N. 15°48'50" W., 1.133 chs. dist.
1.197	Angle Point No. 1, Lot No. 53, Block 8, Range D, Gold Hill Townsite and point of beginning.
	GENERAL DESCRIPTION
	The lands included in the survey are located in and around the community of Gold Hill, in Storey County, Nevada. Access is provided by Nevada State Route 342, and numerous dirt roads. The area is mountainous land, with vegetation consisting of sagebrush, pinion pine, juniper and various grasses. The average elevation of the area is approximately 5,800 feet above sea level.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Bradley F. Dillon	Cadastral Surveyor
David D. Morlan	Chief Cadastral Surveyor
Craig E. Wanless	Principal Analyst
Christopher S. Bourgoine	Supervisory Range Technician

CERTIFICATE OF SURVEY

We, Brock R. Clifford and Brandon G. Courtright, Cadastral Surveyors, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 18th day of August, 2014, We have dependently resurveyed a portion of the subdivisional lines and portions of certain mineral surveys, subdivided sections 5 and 6, and conducted metes-and-bounds surveys of certain Gold Hill Townsite Lots, Township 16 North, Range 21 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

APR 29 2016

(Date)

Brock R. Clifford

(Cadastral Surveyor)

APR 29 2016

(Date)

Brandon G. Courtright

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of the dependent resurvey of a portion of the subdivisional lines and portions of certain mineral surveys, the subdivision of sections 5 and 6, and metes-and-bounds surveys of certain Gold Hill Townsite Lots, Township 16 North, Range 21 East, Mount Diablo Meridian, Nevada, executed by Brock R. Clifford and Brandon G. Courtright, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

APR 29 2016

(Date)

Michael A. Hammer

(Chief Cadastral Surveyor for Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in Township 16 North, Range 21 East, Mount Diablo Meridian, Nevada, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor for Nevada)~~