

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

PORTIONS OF THE EAST AND WEST BOUNDARIES,

A PORTION OF THE SUBDIVISIONAL LINES,

AND THE MEANDERS OF CARSON LAKE,

AND

THE SURVEY OF PORTIONS OF THE EAST AND WEST BOUNDARIES,

THE METES-AND-BOUNDS SURVEY OF A PORTION OF U.S. HIGHWAY NO. 95,

AND THE SURVEY OF TRACTS 37 AND 38,

TOWNSHIP 16 NORTH, RANGE 29 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATE OF NEVADA

EXECUTED BY

Brock R. Clifford, Cadastral Surveyor

Thomas E. Casinger, Cadastral Surveyor

Under Special Instructions dated June 10, 1996,

and approved June 10, 1996,

and Supplemental Special Instructions dated April 30, 1998,

and approved April 30, 1998,

which provided for the surveys included under Group No. 763,

and Assignment Instructions dated June 10, 1996

and November 3, 1997.

Survey commenced June 12, 1996

Survey completed June 25, 1998

INDEX DIAGRAM

TOWNSHIP 16 NORTH, RANGE 29 EAST

4	6	12	5	11	4	9	3	7	2	6	1	2
	13		11		10		8		6		5	
												2
	7		8		9		10		11		12	
	18		17		16		15		14		13	
	19		20		21		22		23		24	
	30		29		28		27		26		25	
	31		32		33		34		35		36	

Dependent resurvey of the meanders of Carson Lake Pages 13-15
 Survey of a portion of the east boundary Pages 15-16
 Survey of a portion of the west boundary Page 16
 Metes-and-Bounds survey of a portion of U.S. Highway No. 95 Pages 17-19
 Survey of Tract 37 Pages 19-21
 Survey of Tract 38 Pages 21-22

039

TOWNSHIP 16 NORTH, RANGE 29 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The following field notes are those of the dependent resurvey of portions of the east and west boundaries, a portion of the subdivisional lines, and the meanders of Carson Lake, and the survey of portions of the east and west boundaries, the metes-and-bounds survey of a portion of U.S. Highway No. 95, and the survey of Tracts 37 and 38, Township 16 North, Range 29 East, Mount Diablo Meridian, Nevada.

Portions of the east and west boundaries, and a portion of the subdivisional lines and the meanders of Carson Lake were surveyed by U.S. Deputy Surveyors M.F. Reilly and T.A. Magee, in 1881, under Contract No. 108. Other surveys remote to the area are not included.

The survey of the south boundary of T. 17 N., R. 29 E., and the survey of a portion of the subdivisional lines of T. 16 N., R. 30 E., were executed concurrently under this same group.

Before restoring the corners, the lines of the original surveys were retraced and diligent search made for any evidence of the original corners and other calls of the original field note record.

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, the Special Instructions dated June 10, 1996, and the Supplemental Special Instructions date April 30, 1998.

The direction of the lines of this survey were determined by azimuth taken from U.S.C. & G.S. triangulation station "LAVA" located in section 15, supplemented with direct solar observations and by use of Global Positioning System satellite data, using the real time kinematic survey process, and refer to the true meridian. The lines were carried forward by sustained angulation throughout the progress of the survey.

The vertical angles of measurements made on the slope were ascertained with a theodolite in good adjustment; the horizontal equivalents only are entered in the field notes.

The geographic position for the cor. of secs. 1 and 12 only, on the E. bdy. of the Tp. is at Lat. 39°16'13.242" N. and Long. 118°40'12.157" W. - NAD 83 (NAD 1986), as determined by survey grade GPS receivers, in 1996, from NGS stations "WYE" and "X 46".

The 1980 mean magnetic declination is 16° E., as shown on U.S.G.S. quadrangle map "CARSON LAKE, NEV." dated 1985.

040

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 16 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>(Reestablishment of the Survey Executed by M.F. Reilly and T.A. Magee, U.S. Deputy Surveyors, in 1881)</p> <hr/> <p>From the $\frac{1}{4}$ sec. cor. of secs. 7 and 12, monumented with decayed remains of a willow post, with no visible scribing, loosely set in a mound of earth. This cor. will now function as the $\frac{1}{4}$ sec. cor. of sec. 12 only.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T16N R29E R30E 1/4 S 12 </p> <p style="text-align: center;">1996</p> <p>Reset the remains of the original wooden post and set a steel fence post, 5 ft. long, alongside the stainless steel post.</p> <p>N. $0^{\circ}27'40''$ E., on the E. bdy. of sec. 12.</p> <p>Over alkali flat.</p>
40.144	<p>Point for the cor. of secs. 1, 6, 7 and 12, at proportionate distance; there is no remaining evidence of the original corner. This cor. will now function as the cor. of secs. 1 and 12 only.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T16N R29E R30E S 1 ----- S 7 S 12 </p> <p style="text-align: center;">1996</p> <p>Set a steel fence post, 5 ft. long, alongside the stainless steel post.</p> <hr/> <p>N. $0^{\circ}27'40''$ E., on the E. bdy. of sec. 1.</p>
1.592	<p>The closing cor. of secs. 6 and 7, T. 16 N., R. 30 E., monumented with a stainless steel post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of T. 16 N., R. 30 E., executed concurrently under this same group.</p>
2.90	<p>Wash, 10 lks. wide, 1 ft. deep, drains NE.</p>

041

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 16 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 4.00</p>	<p>Fence, bears NE. and SW.</p>
<p>16.80</p>	<p>Enter bottom land.</p>
<p>40.144</p>	<p>The $\frac{1}{4}$ sec. cor. of secs. 1 and 6, monumented with a basalt stone, 12X8X5 ins., mkd. $\frac{1}{4}$ on W. face, firmly set in a mound of stone. This cor. will now function as the $\frac{1}{4}$ sec. cor. of sec. 1 only.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T16N R29E R30E 1/4 S 1 </p> <p style="text-align: center;">1996</p> <p>Deposit the original cornerstone alongside the stainless steel post and rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <hr style="width: 30%; margin: 10px auto;"/>
	<p>NORTH, beginning new measurement.</p>
<p>1.448</p>	<p>The $\frac{1}{4}$ sec. cor. of sec. 6 only, T. 16 N., R. 30 E., monumented with a stainless steel post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of T. 16 N., R. 30 E., executed concurrently under this same group.</p>
<p>11.400</p>	<p>Point for the meander cor. of secs. 1 and 6, determined at record bearing and distance; there is no remaining evidence of the original corner. This cor. will now function as the meander cor. of sec. 1 only, and also as Angle Pt. No. 15, Tract 37.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">MC S 1 R29E R30E T16N</p> <p style="text-align: center;">1996</p> <p>Set a steel fence post, 5 ft. long, alongside the stainless steel post.</p> <hr style="width: 30%; margin: 10px auto;"/>

042

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 16 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

(Reestablishment of the Survey Executed by
M.F. Reilly and T.A. Magee, U.S. Deputy Surveyors, in 1881)

From the cor. of secs. 1, 6, 7 and 12, perpetuated by Barry A. Fitzpatrick, Nevada Professional Land Surveyor No. 7809, monumented with a rebar, 2 ft. long, $\frac{5}{8}$ in. diam., firmly set in a mound of stone, with a plastic cap, 1 in. diam., mkd. "FITZPATRICK PLS 7809", with the original monument, a basalt stone, 14X9X4 ins., mkd. with 5 grooves on one face and 1 groove on opposite face, lying alongside, as shown on an unrecorded plat.

At the corner point

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

T16N	
R28E	R29E
S 1	S 6
<hr/>	
S12	S 7

1996

Deposit the original cornerstone alongside the stainless steel post, insert the rebar inside the stainless steel post and rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of cor.

N. $0^{\circ}19'20''$ W., bet. secs. 1 and 6.

Over gently rolling land, covered with scattered shadscale and greasewood.

- 16.60 Enter bottom land, covered with scattered shadscale, greasewood and native grass.
- 28.30 Canal, 30 lks. wide, 3 ft. deep, bears ESE. and WNW.
- 28.50 Bladed road, parallels canal.
- 39.757 The $\frac{1}{4}$ sec. cor. of secs. 1 and 6, monumented with a basalt stone, 18X12X8 ins., dimly mkd. $\frac{1}{4}$ on W. face, firmly set in a mound of earth.

At the corner point

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.


T16N	
R28E	R29E
1/4	
S 1	S 6

1996

Deposit the original cornerstone and set a steel fence post, 5 ft. long, alongside the stainless steel post.

043

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 16 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	NORTH, beginning new measurement.
29.000	<p>Point for the meander cor. of secs. 1 and 6, determined at record bearing and distance; there is no remaining evidence of the original corner. This cor. will now function as the meander cor. of sec. 6 only, and also as Angle Pt. No. 3, Tract 38.</p> <p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<div style="text-align: center;">  <p>MC S 6 R28E R29E T16N</p> </div> <p>1998</p> <p>Set a steel fence post, 5 ft. long, alongside the stainless steel post.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 16 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">(Reestablishment of the Survey Executed by M.F. Reilly and T.A. Magee, U.S. Deputy Surveyors, in 1881)</p> <hr/> <p>From the cor. of secs. 1 and 12 only, on the E. bdy. of the Tp. N. 89°17'10" W., bet. secs. 1 and 12.</p> <p>Over rolling land, covered with scattered shadscale, greasewood and native grass.</p>
1.70	Wash, 10 lks. wide, 1 ft. deep, drains irregularly NE.
6.20	Fence, bears ENE. and WSW.
40.194	<p>The ¹/₄ sec. cor. of secs. 1 and 12, monumented with a basalt stone, 18X8X8 ins., mkd. ¹/₄ on S. face, firmly set in a mound of stone.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<div style="text-align: center;"> <p>T16N R29E S 1 1/4 ——— S12</p> <p>1996</p> </div> <p>Deposit the original cornerstone alongside the stainless steel post and rebuild the mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <hr/>

044

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 16 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS									
39.701	<p>S. 89°05'10" W., beginning new measurement.</p> <p>The cor. of secs. 1, 2, 11 and 12, monumented with a basalt stone, 12X6X6 ins., mkd. with 1 notch on E. edge and 5 notches on S. edge, firmly set in a mound of stone.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T16N R29E</td></tr> <tr><td>S 2</td><td>S 1</td></tr> <tr><td colspan="2">-----</td></tr> <tr><td>S11</td><td>S12</td></tr> </table> <p style="text-align: center;">1996</p> <p>Deposit the original cornerstone alongside the stainless steel post and rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>	T16N R29E		S 2	S 1	-----		S11	S12
T16N R29E									
S 2	S 1								

S11	S12								
	<hr/> <p>NORTH, bet. secs. 1 and 2.</p> <p>Over gently rolling land, covered with scattered shadscale and greasewood.</p>								
15.60	<p>Enter bottom land, covered with greasewood, shadscale and native grass.</p>								
37.000	<p>Point for the meander cor. of secs. 1 and 2, determined at record bearing and distance; there is no remaining evidence of the original corner. This cor. will now also function as Angle Pt. No. 13, Tract 37.</p> <p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">MC</td></tr> <tr><td colspan="2">-----</td></tr> <tr><td>S 2</td><td>S 1</td></tr> <tr><td colspan="2">T16N R29E</td></tr> </table> <p style="text-align: center;">1998</p> <p>Set a steel fence post, 5 ft. long, alongside the stainless steel post.</p>	MC		-----		S 2	S 1	T16N R29E	
MC									

S 2	S 1								
T16N R29E									
	<hr/> <p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>N. 89°58'50" W., bet. secs. 2 and 11.</p> <p>Over gently rolling land, covered with scattered shadscale and greasewood.</p>								
7.40	<p>Remnants of old trail road, bears SE. and NW.</p>								
9.80	<p>Fence, bears SE. and NW.</p>								


045

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 16 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS 9.90	Trail road, parallels fence.
25.00	Ascend; enter mountainous land.
40.126	The $\frac{1}{4}$ sec. cor. of secs. 2 and 11, monumented with a basalt stone, 22X18X4 ins., mkd. $\frac{1}{4}$ on N. face, firmly set in a mound of stone. At the corner point Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 5 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 4 ft. base, to top, with brass cap mkd. <div style="text-align: center;"> T16N R29E S 2 1/4 ——— S11 1996 </div> Deposit the original cornerstone alongside the stainless steel post. <hr style="width: 20%; margin: auto;"/> N. $87^{\circ}26'40''$ W., beginning new measurement.
41.460	The cor. of secs. 2, 3, 10 and 11, monumented with a basalt stone, 40X16X12 ins., mkd. with 2 X's on E. face and 5 X's on S. face, firmly set in a mound of stone. At the corner point Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 4 ft. base, to top, with brass cap mkd. <div style="text-align: center;"> T16N R29E S 3 S 2 ——— ——— S10 S11 1996 </div> Deposit the original cornerstone alongside the stainless steel post. <hr style="width: 20%; margin: auto;"/> NORTH, bet. secs. 2 and 3. Descend over mountainous land, covered with shadscale, Brigham tea and native grass.
40.000	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, over a plastic-encased magnet and in a collar of stone, with brass cap mkd.

046

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 16 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA


CHAINS	
	<p style="text-align: center;">T16N R29E 1/4 S 3 S 2 1996</p>
40.05	Fence, bears ESE. and WNW.
40.10	Trail road, parallels fence.
53.30	Canal, 30 lks. wide, 3 ft. deep, bears ESE. and WNW.
53.50	Bladed road, parallels canal.
59.000	<p>Point for the meander cor. of secs. 2 and 3, determined at record bearing and distance; there is no remaining evidence of the original corner. This cor. will now also function as Angle Pt. No. 11, Tract 37.</p>
	<p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">MC  S 3 S 2 T16N R29E 1998</p>
	<hr/>
	<p>From the cor. of secs. 2, 3, 10 and 11.</p>
	<p>N. 89°42'50" W., bet. secs. 3 and 10.</p>
	<p>Over mountainous land, covered with shadscale, Brigham tea and native grass.</p>
0.10	Bottom of ravine, drains N.
8.70	Spur, slopes N; descend steep W. slope.
39.649	<p>The ¹/₄ sec. cor. of secs. 3 and 10, monumented with a basalt stone, 18X12X6 ins., mkd. ¹/₄ on N. face, firmly set in a mound of stone.</p>
	<p>At the corner point</p>
	<p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 20 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T16N R29E S 3 1/4 ——— S10 1996</p>

047


DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 16 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS									
	<p>Deposit the original cornerstone alongside the stainless steel post and rebuild the mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <hr/> <p>N. 89°39'40" W., beginning new measurement.</p>								
35.20	Spur, slopes NE.								
39.674	<p>The cor. of secs. 3, 4, 9 and 10, monumented with a Tufa stone, 20X12X4 ins., mkd. with 3 X's on E. face and 5 X's on S. face, firmly set in a mound of stone.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 6 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T16N</td> <td>R29E</td> </tr> <tr> <td>S 4</td> <td>S 3</td> </tr> <tr> <td colspan="2"><hr/></td> </tr> <tr> <td>S 9</td> <td>S10</td> </tr> </table> <p style="text-align: center;">1996</p>	T16N	R29E	S 4	S 3	<hr/>		S 9	S10
T16N	R29E								
S 4	S 3								
<hr/>									
S 9	S10								
	<p>Deposit the original cornerstone alongside the stainless steel post.</p> <hr/> <p>N. 0°04'00" W., bet. secs. 3 and 4.</p> <p>Descend; enter rolling land, covered with shadscale, greasewood, Brigham tea and native grass.</p>								
39.759	<p>The ¹/₄ sec. cor. of secs. 3 and 4, monumented with a trap stone, 36X16X4 ins., mkd. ¹/₄ on W. face, firmly set in a mound of stone.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T16N</td> <td>R29E</td> </tr> <tr> <td></td> <td>¹/₄</td> </tr> <tr> <td>S 4</td> <td>S 3</td> </tr> </table> <p style="text-align: center;">1996</p>	T16N	R29E		¹ / ₄	S 4	S 3		
T16N	R29E								
	¹ / ₄								
S 4	S 3								
7.90	<p>Deposit the original cornerstone alongside the stainless steel post and rebuild the mound of stone, 4 ft. base, 2 ft. high, W. of cor.</p> <hr/> <p>NORTH, beginning new measurement.</p> <p>Enter bottom land.</p>								

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 16 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 22.000</p>	<p>Point for the meander cor. of secs. 3 and 4, determined at record bearing and distance; there is no remaining evidence of the original corner. This cor. will now also function as Angle Pt. No. 9, Tract 37.</p> <p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;">  <p>MC S 4 S 3 T16N R29E</p> </div> <p>1998</p> <p>Set a steel fence post, 5 ft. long, alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>S. 89°50'50" W., bet. secs. 4 and 9.</p> <p>Descend; enter rolling land, covered with shadscale, greasewood, Brigham tea and native grass.</p>
<p>39.879</p>	<p>The ¹/₄ sec. cor. of secs. 4 and 9, monumented with a trap stone, 40X20X10 ins., mkd. ¹/₄ on N. face, firmly set in a mound of stone.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 8 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T16N R29E S 4 1/4 ——— S 9</p> </div> <p>1996</p> <p>Deposit the original cornerstone alongside the stainless steel post.</p> <hr/> <p>S. 89°59'40" W., beginning new measurement.</p>
<p>40.164</p>	<p>The cor. of secs. 4, 5, 8 and 9, monumented with a basalt stone, 18X16X16 ins., mkd. with 4 grooves on E. face and 5 grooves on S. face, firmly set in a mound of stone.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 16 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	T16N R29E S 5 S 4 <hr style="width: 50%; margin: 0 auto;"/> S 8 S 9 1996
	Deposit the original cornerstone alongside the stainless steel post and rebuild the mound of stone, 5 ft. base, 3 ft. high, W. of cor. <hr/> NORTH, bet. secs. 4 and 5. Over rolling land, covered with shadscale, greasewood, Brigham tea and native grass. 2.40 Trail road, bears NNE. and SSW. 13.00 Enter bottom land. 15.00 Trail road, bears ENE. and WSW. 17.00 Fence, parallels trail road. 30.30 Canal, 30 lks. wide, 3 ft. deep, bears ENE. and WSW. 30.50 Bladed road, parallels canal. 39.000 Point for the meander cor. of secs. 4 and 5, determined at record bearing and distance; there is no remaining evidence of the original corner. This cor. will now also function as Angle Pt. No. 7, Tract 37. Set a stainless steel post, 28 ins. long, 2 ¹ / ₂ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;"> MC  S 5 S 4 T16N R29E 1998 </div> Set a steel fence post, 5 ft. long, alongside the stainless steel post. <hr/> From the cor. of secs. 4, 5, 8 and 9. N. 89°55'40" W., bet. secs. 5 and 8. Over gently rolling land, covered with scattered greasewood and shadscale. 39.960 Point for the 1/4 sec. cor. of secs. 5 and 8, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 ¹ / ₂ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.


050

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 16 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T16N R29E S 5 1/4 <hr style="width: 50px; display: inline-block; vertical-align: middle;"/> S 8 1996</p>
79.920	<p>Set a steel fence post, 5 ft. long, alongside the stainless steel post.</p> <p>The cor. of secs. 5, 6, 7 and 8, perpetuated by Barry A. Fitzpatrick, Nevada Professional Land Surveyor No. 7809, monumented with a rebar, 2 ft. long, $\frac{5}{8}$ in. diam., firmly set in a mound of stone, with a plastic cap, 1 in. diam., mkd. "FITZPATRICK PLS 7809", with the original monument, a basalt stone, 36X20X18 ins., mkd. with 5 grooves on two faces, lying alongside, as shown on an unrecorded plat.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T16N R29E S 6 S 5 <hr style="width: 50px; display: inline-block; vertical-align: middle;"/> S 7 S 8 1996</p> <p>Deposit the original cornerstone alongside the stainless steel post, insert the rebar inside the stainless steel post and rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>
	<p>NORTH, bet. secs. 5 and 6.</p> <p>Over gently rolling land, covered with scattered greasewood and shadscale.</p>
4.60	<p>Fence, bears E. and W.; enter bottom land, covered with shadscale, greasewood and native grass.</p>
15.70	<p>Canal, 30 lks. wide, 3 ft. deep, bears ENE. and WSW.</p>
15.90	<p>Bladed road, parallels canal.</p>
27.000	<p>Point for the meander cor. of secs. 5 and 6, determined at record bearing and distance; there is no remaining evidence of the original corner. This cor. will now also function as Angle Pt. No. 5, Tract 37.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

051

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 16 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">MC</p>  <p style="text-align: center;">1998</p> <p>Set a steel fence post, 5 ft. long, alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>S. 89°41'30" W., bet. secs. 6 and 7.</p> <p>Over gently rolling land, covered with scattered greasewood and shadscale.</p>
28.60	Wash, 20 lks. wide, 2 ft. deep, drains irregularly N.
39.60	Powerline, bears S. 16° E. and N. 16° W.
39.806	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 7, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T16N R29E S 6 1/4 ——— S 7 1996</p>
42.862	<p>Set a steel fence post, 5 ft. long, alongside the stainless steel post.</p> <p>Intersect the centerline of U.S. Highway No. 95, asphalt surface, 48 lks. wide.</p> <p>Drive a PK nail flush with the surface of the asphalt.</p> <p>From this point, the point for the centerline at Sta. "B" 1274+29.98, bears S. 26°52'50" E., 23.836 chs. dist., hereinafter described.</p>
79.652	<p>The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF THE MEANDERS OF CARSON LAKE, T. 16 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">(Reestablishment of the Survey Executed by M.F. Reilly and T.A. Magee, U.S. Deputy Surveyors, in 1881)</p> <hr/> <p>From the meander cor. of sec. 6 only, on the W. bdy. of the Tp., identical with Angle Pt. No. 3, Tract 38, hereinbefore described.</p>

DEPENDENT RESURVEY OF THE MEANDERS OF CARSON LAKE,
T. 16 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>S. 80°19'00" E., 44.204 chs., the meander cor. of secs. 2 and 3, identical with Angle Pt. No. 11, Tract 37, hereinbefore described.</p>
	<p>Thence southeasterly with the adjusted original meanders of sec. 2, identical with the bdy. bet. sec. 2 and a portion of Tract 37, describing a fixed and limiting boundary.</p>
	<p>S. 68°07'10" E., 54.129 chs., Point for the adjusted position of Angle Pt. No. 1, and will now also function as Angle Pt. No. 12, Tract 37. Point not monumented.</p>
	<p>S. 83°16'20" E., 31.523 chs., the meander cor. of secs. 1 and 2, identical with Angle Pt. No. 13, Tract 37, hereinbefore described.</p>
	<p>Thence easterly with the adjusted original meanders of sec. 1, identical with the bdy. bet. sec. 1 and a portion of Tract 37, describing a fixed and limiting boundary.</p>
	<p>N. 81°48'50" E., 62.802 chs., Point for the adjusted position of Angle Pt. No. 1, and will now also function as Angle Pt. No. 14, Tract 37. Point not monumented.</p>
	<p>N. 72°22'20" E., 18.927 chs., the meander cor. of sec. 1 only, on the E. bdy. of the Tp., identical with Angle Pt. No. 15, Tract 37, hereinbefore described.</p>
<p>SURVEY OF A PORTION OF THE EAST BOUNDARY, T. 16 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA</p>	
	<p>From the meander cor. of sec. 1 only, on the E. bdy. of the Tp., identical with Angle Pt. No. 15, Tract 37, hereinbefore described.</p>
	<p>NORTH, on the E. bdy. of the Tp., identical with line 15-1, Tract 37.</p>
	<p>Over nearly level land.</p>
30.048	<p>The 80 $\frac{1}{16}$ sec. cor. of sec. 6 only, T. 16 N., R. 30 E., monumented with a stainless steel post, 2$\frac{1}{2}$ ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of T. 16 N., R. 30 E., executed concurrently under this same group.</p>
36.103	<p>Point for the cor. of Tps. 16 and 17 N., Rs. 29 and 30 E., determined latitudinally WEST from the meander cor. of sec. 31 only, T. 17 N., R. 30 E. This cor. will also function as Angle Pt. No. 1, Tract 37, and Angle Pt. No. 10, Tract 37, T. 17 N., R. 29 E. and Angle Pt. No. 2, Tract 37, T. 17 N., R. 30 E.</p> <p>Set a stainless steel post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

054

SURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 16 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

T17N	
R29E R30E	
TR 37	TR 37
AP 10	AP 2

AP 1	S 6
TR 37	
T16N	

1998

Set a plastic sign post, 5 ft. long, alongside the stainless steel post.

Land, nearly level.

Soil, sand and clay.

Vegetation, native grass and scattered greasewood.

SURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 16 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

From the meander cor. of sec. 6 only, on the W. bdy. of the Tp., identical with Angle Pt. No. 3, Tract 38, hereinbefore described.

NORTH, on the W. bdy. of the Tp., identical with line 3-2, Tract 38.

Over nearly level land.

9.438

Point for the cor. of Tps. 16 and 17 N., Rs. 28 and 29 E., falls in U.S. Highway No. 95, 48 lks. wide, on curve, bears N. and SSE., determined latitudinally EAST from the meander cor. of secs. 1 and 36, Tps. 16 and 17 N., R. 28 E. This cor. will also function as Angle Pt. No. 2, Tract 38, and Angle Pt. No. 5, Tract 40, T. 17 N., R. 28 E. and Angle Pt. No. 9, Tract 37, T. 17 N., R. 29 E.

Drive a PK nail flush with the surface of the asphalt
from which

A stainless steel post, 28 ins. long, 2¹/₂ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 32°55' W., 1.312 chs. dist., with brass cap mkd. RM T16NR28E SEC 1 86.6 FT TO COR 1998 and an arrow pointing to the cor.

A stainless steel post, 28 ins. long, 2¹/₂ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 64°05' W., 1.194 chs. dist., with brass cap mkd. RM T17NR28E AP5 TR40 78.8 FT TO COR 1998 and an arrow pointing to the cor.

Land, nearly level.

Soil, sand and clay.

Vegetation, native grass and scattered greasewood.

055

METES-AND-BOUNDS SURVEY OF A PORTION OF U.S. HIGHWAY NO. 95,
T. 16 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Beginning at the point for the centerline of U.S. Highway No. 95, at Sta. "B" 1274+29.98, as shown on Plan and Profile Sheet No. 17, Project No. F006-4(8), obtained from the Nevada Highway Department. Point not monumented</p> <p>from which</p> <p>A reference monument, bears N. 63°07' E., 1.226 chs. dist., monumented with a brass tablet, 3¹/₄ ins. diam., seated in a concrete post, 18 ins. diam., firmly set flush with the ground, with top mkd. STA B 1274+29.99 DIST 81.00 ANGLE 90.</p> <p>A reference monument, bears S. 63°07' W., 1.092 chs. dist., monumented with a brass tablet, 3¹/₄ ins. diam., seated in a concrete post, 18 ins. diam., firmly set flush with the ground, with top mkd. STA B 1274+29.99 DIST 72.09 ANGLE 90.</p> <p>N. 26°52'50" W., on the centerline of U.S. Highway No. 95.</p> <p>Along asphalt surfaced road, 48 lks. wide.</p>
23.836	<p>Intersect the line bet. secs. 6 and 7.</p> <p>From this point, the ¹/₄ sec. cor. of secs. 6 and 7, bears N. 89°41'30" E., 3.056 chs. dist.</p>
47.090	<p>Point for the centerline at Sta. "B" 1305+37.41, as shown on Plan and Profile Sheet No. 18, Project No. F006-4(8), obtained from the Nevada Highway Department. Point not monumented</p> <p>from which</p> <p>A reference monument, bears N. 63°07' E., 0.906 chs. dist., monumented with a brass tablet, 3¹/₄ ins. diam., seated in a concrete post, 18 ins. diam., firmly set flush with the ground, with top mkd. STA B 1305+37.41 DIST 59.92 ANGLE 90.</p> <p>A reference monument, bears S. 63°07' W., 1.267 chs. dist., monumented with a brass tablet, 3¹/₄ ins. diam., seated in a concrete post, 18 ins. diam., firmly set flush with the ground, with top mkd. STA B 1305+37.41 DIST 83.75 ANGLE 90.</p> <hr/> <p>N. 26°53'10" W., on the centerline of U.S. Highway No. 95.</p> <p>Along asphalt surfaced road, 48 lks. wide.</p>
44.213	<p>Point for the centerline at Sta. "B" 1334+55.26 P.C., as shown on Plan and Profile Sheet No. 19, Project No. F006-4(8), obtained from the Nevada Highway Department. Point not monumented</p> <p>from which</p>

056

METES-AND-BOUNDS SURVEY OF A PORTION OF U.S. HIGHWAY NO. 95,
T. 16 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>A reference monument, bears N. 63°07' E., 0.888 chs. dist., monumented with a brass tablet, 3¹/₄ ins. diam., seated in a concrete post, 18 ins. diam., firmly set flush with the ground, with top mkd. STA B 1334+55.26 PT DIST 58.75 ANGLE 90.</p> <p>A reference monument, bears S. 63°07' W., 0.587 chs. dist., monumented with a brass tablet, 3¹/₄ ins. diam., seated in a concrete post, 18 ins. diam., firmly set flush with the ground, with top mkd. STA B 1334+55.26 PT DIST 38.82 ANGLE 90.</p>
6.099	<p>Thence on the centerline of U.S. Highway No. 95, along a curve to the right having a radius of 5000.00 ft., the long chord of which bears N. 13°13'30" W., 35.782 chs. dist.</p> <p>Along asphalt surface road, 48 lks. wide.</p> <p>Intersect the adjusted original meander line of Carson Lake, sec. 6.</p> <p>Point for Angle Pt. No. 3, Tract 37 and Angle Pt. No. 4, Tract 38.</p> <p>Drive a PK nail flush with the surface of the asphalt from which</p> <p>A stainless steel post, 28 ins. long, 2¹/₂ ins. diam., set 25 ins. in the ground for a reference monument, bears N. 22°52' E., 1.280 chs. dist., with brass cap mkd. RM T16NR29E AP3 TR37 84.5 FT TO COR 1998 and an arrow pointing to the cor.</p> <p>A stainless steel post 28 ins. long, 2¹/₂ ins. diam., set 23 ins. in the ground for a reference monument, bears N. 69°31' W., 1.433 chs. dist., with brass cap mkd. RM T16NR29E AP4 TR38 94.6 FT TO COR 1998 and an arrow pointing to the cor.</p> <p>From this point, the meander cor. of sec. 6 only, on the W. bdy. of the Tp., bears N. 54°25'30" W., 4.881 chs. dist.</p> <p>Continue on the centerline of U.S. Highway No. 95, identical with line 3-2, Tract 37 and line 4-1, Tract 38.</p>
18.983	<p>Intersect the N. bdy. of the Tp.</p> <p>Point for Angle Pt. No. 2, Tract 37 and Angle Pt. No. 1, Tract 38.</p> <p>Drive a PK nail flush with the surface of the asphalt from which</p> <p>A stainless steel post, 28 ins. long, 2¹/₂ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 52°25' E., 1.429 chs. dist., with brass cap mkd. RM T16NR29E AP2 TR37 94.3 FT TO COR 1998 and an arrow pointing to the cor.</p>

057

METES-AND-BOUNDS SURVEY OF A PORTION OF U.S. HIGHWAY NO. 95,
T. 16 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From this point, the cor. of Tps. 16 and 17 N., Rs. 28 and 29 E., identical with Angle Pt. No. 2, Tract 38 and also identical with Angle Pt. No. 5, Tract 40, T. 17 N., R. 28 E. and Angle Pt. No. 9, Tract 37, T. 17 N., R. 29 E., bears S. 89°04'50" W., 0.122 chs. dist.</p> <p>Continue on the centerline of U.S. Highway No. 95.</p>
36.124	<p>Point for the centerline at Sta. "B" 1358+39.28 P.T., as shown on Plan and Profile Sheet No. 19, Project No. F006-4(8), obtained from the Nevada Highway Department. Point not monumented</p> <p>from which</p> <p>A reference monument, bears N. 89°34' W., 0.839 chs. dist., monumented with a brass tablet, 3¹/₄ ins. diam., seated in a concrete post, 18 ins. diam., firmly set flush with the ground, with top mkd. STA B 1358+39.28 POT DIST 55.36 ANGLE 90. (Note: Easterly reference monument was disturbed and laying above ground.)</p>
	<p style="text-align: center;">SURVEY OF TRACT 37, T. 16 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA</p>
480.745	<p>Beginning at Angle Pt. No. 1, Tract 37, identical with the cor. of Tps. 16 and 17 N., Rs. 29 and 30 E. and also identical with Angle Pt. No. 10, Tract 37, T. 17 N., R. 29 E. and Angle Pt. No. 2, Tract 37, T. 17 N., R. 30 E., hereinbefore described.</p> <p>S. 89°04'50" W., on line 1-2, Tract 37, identical with a portion of the N. bdy. of the Tp. and also identical with a portion of line 10-9, Tract 37, T. 17 N., R. 29 E.</p>
	<p>Angle Pt. No. 2, Tract 37, identical with Angle Pt. No. 1, Tract 38, at the intersection with the centerline of U.S. Highway No. 95, hereinbefore described.</p> <p>From this point, the point for the centerline at Sta. "B" 1358+39.28 PT is 17.141 chs. dist. along a curve to the right having a radius of 5000.00 ft., the chord of which bears N. 6°02'50" W., 17.105 chs. dist.</p>
12.884	<p>Thence on line 2-3, Tract 37, identical with the centerline of U.S. Highway No. 95, along a curve to the left having a radius of 5000.00 ft., the chord of which bears S. 17°24'00" E., 12.868 chs. dist. and also identical with line 1-4, Tract 38.</p> <p>Along asphalt surfaced road, 48 lks. wide.</p>
	<p>Angle Pt. No. 3, Tract 37, identical with Angle Pt. No. 4, Tract 38, at the intersection with the adjusted original meander line of Carson Lake, sec. 6, hereinbefore described.</p> <p>From this point, the meander cor. of sec. 6 only, on the W. bdy. of the Tp., bears N. 54°25'30" W., 4.881 chs. dist.</p>

058

SURVEY OF TRACT 37,
T. 16 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	S. 54°25'30" E., on line 3-4, Tract 37, identical with a portion of the adjusted original meanders of Carson Lake, sec. 6.
49.895	The point for Angle Pt. No. 4, Tract 37, identical with Angle Pt. No. 1 of the adjusted original meanders of Carson Lake, sec. 6, hereinbefore described.
	S. 74°59'50" E., on line 4-5, Tract 37, identical with a portion of the adjusted original meanders of Carson Lake, sec. 6.
36.549	Angle Pt. No. 5, Tract 37, identical with the meander cor. of secs. 5 and 6, hereinbefore described.
	N. 83°08'00" E., on line 5-6, Tract 37, identical with a portion of the adjusted original meanders of Carson Lake, sec. 5.
50.220	The point for Angle Pt. No. 6, Tract 37, identical with Angle Pt. No. 1 of the adjusted original meanders of Carson Lake, sec. 5, hereinbefore described.
	N. 78°54'10" E., on line 6-7, Tract 37, identical with a portion of the adjusted original meanders of Carson Lake, sec. 5.
30.628	Angle Pt. No. 7, Tract 37, identical with the meander cor. of secs. 4 and 5, hereinbefore described.
	N. 76°58'20" E., on line 7-8, Tract 37, identical with a portion of the adjusted original meanders of Carson Lake, sec. 4.
75.697	The point for Angle Pt. No. 8, Tract 37, identical with Angle Pt. No. 1 of the adjusted original meanders of Carson Lake, sec. 4, hereinbefore described.
	N. 47°03'40" E., on line 8-9, Tract 37, identical with a portion of the adjusted original meanders of Carson Lake, sec. 4.
8.521	Angle Pt. No. 9, Tract 37, identical with the meander cor. of secs. 3 and 4, hereinbefore described.
	N. 83°14'10" E., on line 9-10, Tract 37, identical with a portion of the adjusted original meanders of Carson Lake, sec. 3.
36.034	The point for Angle Pt. No. 10, Tract 37, identical with Angle Pt. No. 1 of the adjusted original meanders of Carson Lake, sec. 3, hereinbefore described.
	S. 80°19'00" E., on line 10-11, Tract 37, identical with a portion of the adjusted original meanders of Carson Lake, sec. 3.
44.204	Angle Pt. No. 11, Tract 37, identical with the meander cor. of secs. 2 and 3, hereinbefore described.

SURVEY OF TRACT 37,
T. 16 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	S. 68°07'10" E., on line 11-12, Tract 37, identical with a portion of the adjusted original meanders of Carson Lake, sec. 2.
54.129	The point for Angle Pt. No. 12, Tract 37, identical with Angle Pt. No. 1 of the adjusted original meanders of Carson Lake, sec. 2, hereinbefore described.
	S. 83°16'20" E., on line 12-13, Tract 37, identical with a portion of the adjusted original meanders of Carson Lake, sec. 2.
31.523	Angle Pt. No. 13, Tract 37, identical with the meander cor. of secs. 1 and 2, hereinbefore described.
	N. 81°48'50" E., on line 13-14, Tract 37, identical with a portion of the adjusted original meanders of Carson Lake, sec. 1.
62.802	The point for Angle Pt. No. 14, Tract 37, identical with Angle Pt. No. 1 of the adjusted original meanders of Carson Lake, sec. 1, hereinbefore described.
	N. 72°22'20" E., on line 14-15, Tract 37, identical with a portion of the adjusted original meanders of Carson Lake, sec. 1.
18.927	Angle Pt. No. 15, Tract 37, identical with the meander cor. of sec. 1 only, on the E. bdy. of the Tp., hereinbefore described.
	NORTH, on line 15-1, Tract 37, identical with a portion of the E. bdy. of the Tp.
30.048	The 80 ¹ / ₁₆ sec. cor. of sec. 6 only, T. 16 N., R. 30 E., hereinbefore described.
36.103	Angle Pt. No. 1, Tract 37, identical with the cor. of Tps. 16 and 17 N., Rs. 29 and 30 E. and also identical with Angle Pt. No. 10, Tract 37, T. 17 N., R. 29 E. and Angle Pt. No. 2, Tract 37, T. 17 N., R. 30 E. and point of beginning.
<p style="text-align: center;">SURVEY OF TRACT 38, T. 16 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA</p>	
	Beginning at Angle Pt. No. 1, Tract 38, identical with Angle Pt. No. 2, Tract 37, hereinbefore described.
	S. 89°04'50" W., on line 1-2, Tract 38, identical with a portion of the N. bdy. of the Tp. and also identical with a portion of line 10-9, Tract 37, T. 17 N., R. 29 E.
0.122	Angle Pt. No. 2, Tract 38, identical with the cor. of Tps. 16 and 17 N., Rs. 28 and 29 E. and also identical with Angle Pt. No. 5, Tract 40, T. 17 N., R. 28 E. and Angle Pt. No. 9, Tract 37, T. 17 N., R. 29 E.

SURVEY OF TRACT 38,
T. 16 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>SOUTH, on line 2-3, Tract 38, identical with a portion of the W. bdy. of the Tp.</p>
9.438	<p>Angle Pt. No. 3, Tract 38, identical with the meander cor. of sec. 6 only, hereinbefore described.</p> <hr/> <p>S. 54°25'30" E., on line 3-4, Tract 38, identical with a portion of the adjusted original meanders of Carson Lake, sec. 6.</p>
4.881	<p>Angle Pt. No. 4, Tract 38, identical with Angle Pt. No. 3, Tract 37, at the intersection with the centerline of U.S. Highway No. 95, hereinbefore described.</p> <p>From this point, the point for the centerline at Sta. "B" 1334+55.26 P.C. is 6.099 chs. dist. along a curve to the left having a radius of 5000.00 ft., the chord of which bears S. 24°34'50" E., 6.097 chs. dist.</p> <hr/> <p>Thence on line 4-1, Tract 38, identical with the centerline of U.S. Highway No. 95, along a curve to the right having a radius of 5000.00 ft., the chord of which bears N. 17°24'00" W., 12.868 chs. dist. and also identical with line 3-2, Tract 37.</p>
12.884	<p>Angle Pt. No. 1, Tract 38, identical with Angle Pt. No. 2, Tract 37 and point of beginning.</p> <hr/>
GENERAL DESCRIPTION	
<p>The area surveyed and resurveyed within Township 16 North, Range 29 East, varies from mountainous in the east and north portions remaining terrain being gently rolling to fairly flat. The elevation ranges from 3,925 to 4,475 ft. above sea level. The soil varies from sandy clay loam and gravel to sandy clay loam and rocky in the higher elevations. The vegetation consists of sagebrush, rabbitbrush, Brigham tea and native grass.</p> <p>Access is by U.S. Highway No. 95, crossing the area from the S. to the N. and by improved gravel roads and trail roads.</p> <hr/>	

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Peter F. Perazzo Surveying Technician
Clay W. Morrow Surveying Technician

CERTIFICATE OF SURVEY

We, Brock R. Clifford and Thomas E. Casinger, Cadastral Surveyors, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 10th day of June, 1996, and Supplemental Special Instruction bearing date of the 30th day of April, 1998, we have dependently resurveyed portions of the east and west boundaries, a portion of the subdivisional lines, and the meanders of Carson Lake, and surveyed portions of the east and west boundaries, surveyed by metes-and-bounds a portion of U.S. Highway No. 95, and surveyed Tracts 37 and 38, Township 16 North, Range 29 East, the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

11/23/98

(Date)

David J. Clark

For Brock R. Clifford

(Cadastral Surveyor)

11/23/98

(Date)

Thomas E. Casinger

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of the dependent resurvey of portions of the east and west boundaries, a portion of the subdivisional lines, and the meanders of Carson Lake, and the survey of portions of the east and west boundaries, the metes-and-bounds survey of a portion of U.S. Highway No. 95, and the survey Tracts 37 and 38, Township 16 North, Range 29 East, Mount Diablo Meridian, Nevada, executed by Brock R. Clifford and Thomas E. Casinger, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

11/23/98

(Date)

David J. Clark

(Chief Cadastral Surveyor, Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 16 N., R. 29 E., M.D.M., Nevada, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor, Nevada)~~