

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

A PORTION OF THE SOUTH BOUNDARY OF TOWNSHIP 18 NORTH, RANGE 26 EAST

AND A PORTION OF THE SUBDIVISIONAL LINES,

AND THE

SURVEY OF

THE EAST BOUNDARY,

A PORTION OF THE SUBDIVISIONAL LINES

AND THE SUBDIVISION OF SECTIONS 11, 14, 23, 26 AND 35,

TOWNSHIP 17 NORTH, RANGE 26 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATE OF NEVADA

EXECUTED BY

Richard J. Dieckmann, Cadastral Surveyor

Under Special Instructions dated September 21, 2023,

and approved September 21, 2023,

which provided for the surveys included under Group No. 1008,

and Assignment Instructions dated September 21, 2023.

Survey commenced September 26, 2023

Survey completed April 16, 2024

INDEX DIAGRAM

TOWNSHIP 17 NORTH, RANGE 26 EAST, MOUNT DIABLO MERIDIAN, NEVADA

					3	2
					25	18
6	5	4	3	6	25 2	17 1 11
				5	24	17
7	8	9	10		23 11	16 12 10
					22	16
18	17	16	15		22 14	15 13 9
					21	15
19	20	21	22		21 23	14 24 8
					20	14
30	29	28	27		19 26	13 25 8
					19	12
31	32	33	34		18 35	12 36 7

Subdivision of Section 11 p. 26
 Subdivision of Section 14 p. 27
 Subdivision of Section 23 pp. 27-28
 Subdivision of Section 26 pp. 29-31
 Subdivision of Section 35 pp. 31-32

TOWNSHIP 17 NORTH, RANGE 26 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The following field notes are those of the dependent resurvey of a portion of the south boundary of Township 18 North, Range 26 East and a portion of the subdivisional lines, and the survey of the east boundary, a portion of the subdivisional lines and the subdivision of sections 11, 14, 23, 26 and 35, Township 17 North, Range 26 East, Mount Diablo Meridian, Nevada.

1868 - The south, east, west, and north boundaries were surveyed by E.B. Monroe, U.S. Deputy Surveyor, under Contract No. 10.

1887 - The south boundary of section 36, Township 18 North, Range 26 East, was retraced by H.H. Bence, U.S. Deputy Surveyor, under contract No. 185.

1905 - A portion of the north and west boundaries were resurveyed and portions of the subdivisional lines were surveyed by J.B. Menardi, U.S. Deputy Surveyor, under Contract No. 244.

1923 - The north boundary of T. 16 N., R. 26 E., was independently resurveyed by G.W. Ridgway, U.S. Cadastral Engineer, under Group No. 101.

1925 - A portion of the west boundary was dependently resurveyed by C.S. Swanholm, Cadastral Engineer, under Group No. 104.

1962 - Nevada Protraction Diagram No. 32, Unit No. 52 and 53 was approved.

1967 - The south boundary of T. 17 N., R. 27 E., was independently resurveyed by J.D. Sorensen, Cadastral Surveyor, under Group No. 447.

The dependent resurvey of a portion of the north boundary of T. 16 N., R. 26 E., was executed concurrently under Group No. 1006.

Before restoring the corners, the lines of the original surveys were retraced and a diligent search made for any evidence of the position of the original corners and other calls of the original field note record.

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 2009, and the Special Instructions for Group No. 1008, dated September 21, 2023.

Measurements were made with Trimble R-12 and R-12i Global Navigation Satellite System (GNSS) receivers using the real-time kinematic (RTK) method and refer to the true meridian based on geodetic methods. The mean bearings of the lines and horizontal equivalents of ground distances only are entered in the field notes.

TOWNSHIP 17 NORTH, RANGE 26 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The NAD 83(2011)(EPOCH:2010.0000) geographic position of the following corners was determined from Global Positioning System (GPS) static observations processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS), AI8816 UPSA UPSA BRGN NV1997 ECCREF DIMPLE, DE6254 RNO1 NW RENO COOP CORS ARP, DE6260 STEA STEAD COOP CORS ARP, DG6525 COF1 FERNLEY COOP CORS ARP, DN4181 P143 INDIANCRK_CN2007 CORS GRP, and DN7529 P150 MARTISPEAKCN2008 CORS GRP, and was carried forward by RTK observations.

The corner of Townships 16 and 17 North, Range 26 East, is as follows:

Latitude: 39°17'11.639" N. Longitude: 119°00'24.490" W.

The corner of sections 2, 3, 34 and 35, on the South Boundary of Township 18 North, Range 26 East, is as follows:

Latitude: 39°22'24.628" N. Longitude: 119°02'36.574" W.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 18 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of a Portion of the Survey Executed by
E.B. Monroe, U.S. Deputy Surveyor, in 1868, the Retracement
Executed by H.H. Bence, U.S. Deputy Surveyor, in 1887 and a
Portion of the Resurvey Executed by
J.B. Menardi, U.S. Deputy Surveyor, in 1905

Beginning at the cor. of Tps. 17 and 18 N., Rs. 26 and 27 E., determined at the base of a quartz stone, 21x10x10 ins. (Record, 16x10x10 ins.), buried under 18 ins. of sand and under a large ephedra bush, lying on its side, with 6 notches on each edge. This cor. will now refer to Tps. 18 N., Rs. 26 and 27 E. only.

At the corner point

Set a stainless steel post, 2 1/2 ins. diam., firmly set, 26 ins. in the ground, over a clear plastic encased magnet, in a collar of stone, with brass cap mkd.

T18N
R26E R27E
S36 | S31
S 6
T17N R27E

2023

Bury the original stone and set a galvanized steel "U" post alongside the stainless steel post.

S. 89°47'50" W., on the S. bdy. of sec. 36.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 18 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
2.888	The cor. of Tps. 17 N., Rs. 26 and 27 E., hereinafter described.
11.50	The summit of a ridge, bears N. 45° E. and S. 45° W.
39.663	<p>Point for the 1/4 sec. cor. of secs. 1 and 36, at proportionate dist., there is no remaining evidence of the original cor. This cor. will now refer to sec. 36 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a clear plastic encased magnet, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T18N R26E 1/4 S36 ----- T17N R26E</p> <p style="text-align: center;">2023</p> <p>Set a galvanized steel "U" post alongside the stainless steel post.</p>
42.964	The N 1/4 sec. cor. of sec. 1, T. 17 N., R. 26 E., hereinafter described.
55.10	A small ridge, bears S. 20° E. and N. 20° W.
63.00	A small ravine, drains S. 20° W.
79.346	<p>The cor. of secs. 1, 2, 35 and 36, monumented with the original basalt stone, 16x13x10 ins. (Record, 15x8x4 ins.), firmly set, projecting 12 ins. above ground, mkd. with 3 horizontal grooves on the W. face and 1 horizontal groove on the S. face. This cor. will now refer to secs. 35 and 36 only.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a clear plastic encased magnet, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T18N R26E S35 S36 ----- S 1 T17N R26E</p> <p style="text-align: center;">2023</p> <p>Bury the original stone along the N. side and set a galvanized steel "U" post alongside the stainless steel post.</p> <hr/> <p>S. 89°54'20" W., on the S. bdy. of sec. 35.</p>
2.00	Ravine, drains S. 25° W.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 18 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
3.695	The cor. of. secs. 1 and 2, T. 17 N., R. 26 E., hereinafter described.
7.15	Double track dirt road, 18 lks. wide, bears N. 40° E. and S. 40° W.
40.315	The 1/4 sec. cor. of secs. 2 and 35, monumented with the original vesicular basalt stone, 16x13x8 ins. (Record, 18x12x5 ins.), firmly set, projecting 12 ins. above the ground, in the northerly edge of an embedded mound of stone, 2 ft. diam., 1/2 ft. high, mkd. 1/4 on the N. face. This cor. will now refer to sec. 35 only.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a clear plastic encased magnet, in a collar of stone, with brass cap mkd.
	T18N R26E <u>1/4 S35</u>
	T17N R26E
	2023
	Bury the original stone along the W. side and set a galvanized steel "U" post alongside the stainless steel post.
	N. 86°08'10" W., beginning new measurement.
3.388	The N 1/4 sec. cor. of sec. 2, T. 17 N., R. 26 E., hereinafter described.
16.20	Ravine, drains S. 35° W.
34.70	Ravine, drains S.
40.514	The cor. of secs. 2, 3, 34 and 35, monumented with a basalt stone, 18x12x9 ins., (1905 Record, 25x10x8 ins.), firmly set, projecting 12 ins. above the ground, mkd. with 2 horizontal grooves on the W. face and 4 horizontal grooves on the E. face, with a mound of stone, 3 ft. diam., 1 1/4 ft. high, W. of cor.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a clear plastic encased magnet, in a collar of stone, with brass cap mkd.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 18 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T18N R26E S34 S35 S 3 S 2 T17N 2023</p> <p>Bury the stone along the E. side of the stainless steel post.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 17 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of a Portion of the Survey Executed by John B. Menardi, U.S. Deputy Surveyor, in 1905</p> <hr/> <p>From the 1/4 sec. cor. of secs. 3 and 10, monumented with the original basalt stone, 24x20x9 ins. (Record, 26x14x10 ins.), firmly set, projecting 12 ins. above the ground, mkd. 1/4 on the N. face, with a mound of stone, 2 ft. diam., 1 1/4 ft. high, N. of the cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a clear plastic encased magnet, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T17N R26E S 3 1/4 — S10 2023</p> <p>Bury the original stone along the S. side of the stainless steel post.</p> <p>S. 89°47'10" E., on the S. bdy. of sec. 3.</p>
25.45	Overhead power transmission lines, extend S. 20° E. and N. 20° W.
31.00	Ravine, drains S.
37.40	The summit of a basalt ridge, bears N. and S.
37.719	The cor. of secs. 2 and 10, hereinafter described.
39.934	The cor. of secs. 2, 3, 10 and 11, monumented with the original basalt stone, 34x13x8 ins. (Record, 30x14x8 ins.), loosely set, projecting 30 ins. above ground, mkd. with 5 horizontal grooves on S. face and 2 horizontal grooves on E. face, with a mound of stone, 4 ft. diam., 1 1/2 ft. high, W. of the cor.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 17 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>This cor. will now refer to the SE. cor. of sec. 3.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a clear plastic encased magnet, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T17N R26E S 3 S 2</p> <p style="text-align: center;">2023</p> <p>The original stone was incorporated into the original reference mound of stone along the S. side of its base and a galvanized steel "U" post was set alongside the stainless steel post within the mound.</p> <hr/> <p>N. 0°21'30" E., on the E. bdy. of sec. 3.</p>
19.40	Double track dirt road, 18 lks. wide, at the bottom of a broad draw, bears N. 65° E. and S. 65° W.
39.304	The W 1/4 sec. cor. of sec. 2, hereinafter described.
40.013	<p>The 1/4 sec. cor. of secs. 2 and 3, monumented with the original vesicular basalt stone, 16x11x5 ins. (Record, 16x8x6 ins.), firmly set, projecting 8 ins. above the ground, mkd. 1/4 on the W. face, with a mound of stone, 3 ft. diam., 1 1/2 ft. high, W. of the cor.</p> <p>This cor. will now refer to the 1/4 sec. cor. of sec. 3 only.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a clear plastic encased magnet, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T17N R26E 1/4 S 3 </p> <p style="text-align: center;">2023</p> <p>Bury the original stone along the S. side of the stainless steel post.</p> <hr/> <p>N. 0°21'30" E., beginning new measurement.</p>
38.584	The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., hereinbefore described.

SURVEY OF THE EAST BOUNDARY,
T. 17 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">This Survey Supersedes the 1868 Survey of the East Boundary, Executed by E.B. Monroe, U.S. Deputy Surveyor, under Contract No. 10, in conformance with the abandonment, as shown on Nevada Protraction Diagram No. 32, Unit No. 52 and 53, approved May 16, 1962.</p> <hr style="width: 20%; margin: auto;"/> <p>From the cor. of Tps. 16 and 17 N., R. 26 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 6 ins. above a mound of stone, 4 ft. diam., 1 ft. high, with brass cap marked as described in the field notes of the independent resurvey of the south boundary, T. 17 N., R. 27 E., executed under Group No. 447.</p>
	<p>NORTH, on the E. bdy. of sec. 36.</p>
40.000	<p>Point for the E 1/4 sec. cor. of sec. 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a clear plastic encased magnet, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T17N R26E R27E 1/4 S36 </p> <p style="text-align: center;">2024</p> <p>From this corner, the original 1/4 sec. cor. of secs. 31 and 36, bears S. 21°46'47" E., 3.528 chs. dist., monumented with the original basalt stone, 14x14x8 ins. (Record, 14x10x8 ins.), firmly set, projecting 12 ins. above an embedded mound of stone, 3 ft. diam., mkd. 1/4 on the W. face. Hereafter this cor. will now become an amended monument, reset in place, buried 18 ins. in ground, added the marks AM on the E. face and rebuild stones from original mound, 3 ft. base, 1/2 ft. high, over the top of the monument.</p>
80.000	<p>Point for the cor. of secs. 25 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, over a clear plastic encased magnet, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T17N R26E R27E <u>S25</u> S36 </p> <p style="text-align: center;">2023</p> <p>From this corner, the original cor. of secs. 25, 30, 31 and 36, bears S. 24°20'00" E., 3.560 chs. dist., monumented with the original vesicular basalt stone, 22x12x10 ins. (Record, 20x10x10 ins.), loosely set, leaning on its N. edge in a mound of stone, 2 ft. diam., 1 ft. high, mkd. with 5 notches on N. edge and 1 notch on S. edge. Hereafter this cor. will now become an amended monument, reset in place, 20 ins. in ground,</p>

SURVEY OF THE EAST BOUNDARY,
T. 17 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>added the marks AM on the W. face and rebuild stones from original mound, 3 ft. base, 1 ft. high, over the top of the monument.</p> <hr/> <p>NORTH, on the E. bdy. of sec. 25.</p>
40.000	<p>Point for the E 1/4 sec. cor. of sec. 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a clear plastic encased magnet, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T17N R26E R27E 1/4 S25 </p> <p style="text-align: center;">2024</p> <p>From this corner, the original 1/4 sec. cor. of secs. 25 and 30, bears S. 23°15'48" E., 3.566 chs. dist., monumented with the original basalt stone, 16x12x7 ins. (Record, 14x8x6 ins.), firmly set, projecting 6 ins. above a mound of stone, 3 ft. diam., 1/2 ft. high, mkd. 1/4 on the W. face. Hereafter this cor. will now become an amended monument, reset in place, buried 19 ins. in ground, added the marks AM on the W. face above original marks and rebuild stones from original mound, 3 ft. base, 1/2 ft. high, over the top of the monument.</p>
80.000	<p>Point for the cor. of secs. 24 and 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a clear plastic encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T17N R26E R27E <u>S24</u> S25 </p> <p style="text-align: center;">2023</p> <p>From this corner, the original cor. of secs. 19, 24, 25 and 30, bears S. 25°46'03" E., 3.548 chs. dist., monumented with the original vesicular basalt stone, 30x12x10 ins. (Record, 34x12x10 ins.), loosely set, leaning on its E. face in an embedded mound of stone, 3 ft. diam., mkd. with 4 notches on N. edge and 2 notches on S. edge. Hereafter this cor. will now become an amended monument, reset in place, 25 ins. in ground, added the marks AM on the E. face and rebuild stones from original mound, 3 ft. base, 1 ft. high, over the top of the monument.</p> <hr/> <p>NORTH, on the E. bdy. of sec. 24.</p>

SURVEY OF THE EAST BOUNDARY,
T. 17 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
35.50	Double track dirt road, 18 lks. wide, bears N. 60° E. and S. 60° W.
40.000	Point for the E 1/4 sec. cor. of sec. 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a clear plastic encased magnet, in a collar of stone, with brass cap mkd. <div style="text-align: center;"> T17N R26E R27E 1/4 S24 2023 </div>
80.000	Point for the cor. of secs. 13 and 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a clear plastic encased magnet, with brass cap mkd. <div style="text-align: center;"> T17N R26E R27E S13 S24 2023 </div> <p>From this corner, the original cor. of secs. 13, 18, 19 and 24, bears S. 28°00'11" E., 3.411 chs. dist., monumented with the original basalt stone, 21x10x6 ins. (Record, 15x8x6 ins.), firmly set, projecting 12 ins. above an embedded mound of stone, 3 ft. diam., mkd. with 3 notches on the N. edge and 3 horizontal grooves on the S. face. Hereafter this cor. will now become an amended monument, reset in place, 25 ins. in ground, added the marks AM on the E. face, grooves now on the N. face and notches now on the S. face, and rebuild stones from original mound, 2 ft. base, 1/2 ft. high, over the top of the monument.</p> <hr/> <p>NORTH, on the E. bdy. of sec. 13.</p>
3.70	Double track dirt road, 18 lks. wide, bears N. 50° E. and S. 50° W.
40.000	Point for the E 1/4 sec. cor. of sec. 13. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a clear plastic encased magnet, with brass cap mkd. <div style="text-align: center;"> T17N R26E R27E 1/4 S13 2023 </div>

SURVEY OF THE EAST BOUNDARY,
T. 17 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From this corner, the original 1/4 sec. cor. of secs. 13 and 18, bears S. 33°25'03" E., 3.448 chs. dist., monumented with the original basalt stone, 18x16x5 ins. (Record, 14x10x8 ins.), firmly set on its side, buried 7 ins. below the ground/sand, mkd. 1/4 on the face facing down. Hereafter this cor. will now become an amended monument, turned upright and reset in place, buried 20 ins. in ground, added the marks AM on the W. face alongside the original marks.</p>
80.000	<p>Point for the cor. of secs. 12 and 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a clear plastic encased magnet, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T17N R26E R27E S12 S13 </p> <p style="text-align: center;">2023</p> <p>From this corner, the original cor. of secs. 7, 12, 13 and 18, bears S. 38°12'57" E., 3.545 chs. dist., monumented with the original vesicular basalt stone, 18x12x11 ins. (Record, 12x10x10 ins.), firmly set, lying on its E. face, buried 10 ins. below the ground/sand, mkd. with 2 notches on N. edge and 4 notches on S. edge. Hereafter this cor. will now become an amended monument, reset in place, 20 ins. in ground, added the marks AM on the SE. face alongside the notches on the S. edge.</p> <hr/> <p>NORTH, on the E. bdy. of sec. 12.</p>
40.000	<p>Point for the E 1/4 sec. cor. of sec. 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a clear plastic encased magnet, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T17N R26E R27E 1/4 S12 </p> <p style="text-align: center;">2023</p> <p>From this corner, the original 1/4 sec. cor. of secs. 7 and 12, bears S. 40°16'45" E., 3.735 chs. dist., monumented with the original vesicular basalt stone, 18x15x6 ins. (Record, 12x10x6 ins.), firmly set, projecting 10 ins. above ground, mkd. 1/4 on the W. face. Hereafter this cor. will now become an amended monument, reset in place, buried 22 ins. in ground, added the marks AM on the E. face.</p>
70.00	<p>Double track dirt road, 18 lks. wide, bears S. 40° E. and N. 40° W.</p>

SURVEY OF THE EAST BOUNDARY,
T. 17 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS 80.000	<p>Point for the cor. of secs. 1 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a clear plastic encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T17N R26E R27E <u> S 1 </u> S12</p> <p style="text-align: center;">2023</p> <p>From this corner, the original cor. of secs. 1, 6, 7 and 12, bears S. 43°50'32" E., 3.673 chs. dist., monumented with the original vesicular basalt stone, 26x12x10 ins. (Record, 12x10x10 ins.), firmly set, projecting 18 ins. above ground, mkd. with 1 notch on N. edge and 5 notches on S. edge. Hereafter this cor. will now become an amended monument, reset in place, 31 ins. in ground, added the marks AM on the W. face.</p> <hr/> <p>NORTH, on the E. bdy. of sec. 1.</p>
38.10	Double track dirt road, 18 lks. wide, bears N. 55° E. and S. 55° W.
40.000	<p>Point for the E 1/4 sec. cor. of sec. 1.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 13 ins. in the ground, over a clear plastic encased magnet, in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T17N R26E R27E 1/4 S 1</p> <p style="text-align: center;">2023</p> <p>From this corner, the original 1/4 sec. cor. of secs. 1 and 6, bears S. 46°53'20" E., 3.806 chs. dist., monumented with the original basalt stone, 17x10x8 ins. (Record, 14x10x8 ins.), loosely set, lying on its side, mkd. 1/4 on the W. face. Hereafter this cor. will now become an amended monument, reset in place, buried 24 ins. in ground, added the marks AM on the W. face above original marks.</p>
77.526	<p>Intersect the S. bdy. of sec. 36, T. 18 N., R. 26 E.</p> <p>Point for the cor. of T. 17 N., Rs. 26 and 27 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a clear plastic encased magnet, with brass cap mkd.</p>

SURVEY OF THE EAST BOUNDARY,
T. 17 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T18N R26E <u> S36</u> S 1 S 6 R26E R27E T17N 2023
	From this point, the cor. of Tps. 18 N., R. 26 and 27 E., hereinbefore described, bears N. 89°47'50" E., 2.888 chs. dist.
	<hr/> SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 17 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA <hr/>
	From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 11 ins. above the ground, with brass cap mkd. as described in the field notes of the independent resurvey of the north boundary, T. 16 N., R. 26 E., executed under Group No. 101, with a mound of stone, 3 ft. diam., 1 1/2 ft. high, 6 lks. SW. of cor.
	N. 0°00'40" W., bet. secs. 35 and 36.
40.000	Point for the 1/4 sec. cor. of secs. 35 and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a clear plastic encased magnet, in a collar of stone, with brass cap mkd.
	T17N R26E 1/4 S35 S36 2024
80.000	Point for the cor. of secs. 25, 26, 35 and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a clear plastic encased magnet, in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	T17N R26E <u> S26 S25</u> S35 S36 2024
	From the cor. of secs. 25 and 36, on the E. bdy. of the Tp., hereinbefore described.
	N. 89°47'30" W., bet. secs. 25 and 36.
40.076	Point for the 1/4 sec. cor. of secs. 25 and 36.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 17 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a clear plastic encased magnet, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T17N R26E S25 1/4 — S36 2024</p>
80.152	The cor. of secs. 25, 26, 35 and 36.
	<hr/> <p>N. 0°00'40" W., bet. secs. 25 and 26.</p>
20.000	Point for the S 1/16 sec. cor. of secs. 25 and 26.
	POINT NOT MONUMENTED
38.40	Double track dirt road, 18 lks. wide, bears N. and S. 10° W.
40.000	Point for the 1/4 sec. cor. of secs. 25 and 26.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. below the surface of a double track dirt road, 18 lks. wide, bears N. and S., with brass cap mkd.</p> <p style="text-align: center;">T17N R26E 1/4 S26 S25 2024</p>
	from which
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a clear plastic encased magnet, in a collar of stone, for a reference monument, bears N. 45°00' E., 50.0 lks. dist., with brass cap mkd. RM 1/4 33.0 FT TO COR S 25 2024 and an arrow pointing to the cor.</p>
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground, over a clear plastic encased magnet, in a collar of stone, for a reference monument, bears N. 45°00' W., 50.0 lks. dist., with brass cap mkd. RM 1/4 33.0 FT TO COR S 26 2024 and an arrow pointing to the cor.</p>
43.90	Double track dirt road, 18 lks. wide, bears N. 5° E. and S.
59.60	Double track dirt road, 18 lks. wide, bears N. 35° E. and S. 35° W.
80.000	Point for the cor. of secs. 23, 24, 25 and 26.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 17 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a clear plastic encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T17N R26E <u>S23 S24</u> S26 S25</p> <p style="text-align: center;">2023</p>
	<p>From the cor. of secs. 24 and 25, on the E. bdy. of the Tp. hereinbefore described.</p> <p>N. 89°47'30" W., bet. secs. 24 and 25.</p>
40.076	<p>Point for the 1/4 sec. cor. of secs. 24 and 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a clear plastic encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T17N R26E S24 1/4 — S25</p> <p style="text-align: center;">2023</p>
53.25	<p>Double track dirt road, 18 lks. wide, bears N. 55° E. and S. 55° W.</p>
80.152	<p>The cor. of secs. 23, 24, 25 and 26.</p>
	<p>N. 0°00'40" W., bet. secs. 23 and 24.</p>
40.000	<p>Point for the 1/4 sec. cor. of secs. 23 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a clear plastic encased magnet, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T17N R26E 1/4 S23 S24</p> <p style="text-align: center;">2023</p>
53.70	<p>Double track dirt road, 18 lks. wide, bears S. 80° E. and N. 80° W.</p>
80.000	<p>Point for the cor. of secs. 13, 14, 23 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a clear plastic encased magnet, in a collar of stone, with brass cap mkd.</p>

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 17 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T17N R26E S14 S13 S23 S24 2023
	<hr/> From the cor. of secs. 13 and 24, on the E. bdy. of the Tp., hereinbefore described. N. 89°47'30" W., bet. secs. 13 and 24.
4.10	Double track dirt road, 18 lks. wide, bears N. 50° E. and S. 50° W.
40.076	Point for the 1/4 sec. cor. of secs. 13 and 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a clear plastic encased magnet, in a mound of stone, 4 1/2 ft. base, to top, with brass cap mkd.
	T17N R26E S13 1/4 — S24 2023
80.152	The cor. of secs. 13, 14, 23 and 24.
	<hr/> N. 0°00'40" W., bet. secs. 13 and 14.
40.000	Point for the 1/4 sec. cor. of secs. 13 and 14. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a clear plastic encased magnet, with brass cap mkd.
	T17N R26E 1/4 S14 S13 2023
80.000	Point for the cor. of secs. 11, 12, 13 and 14. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a clear plastic encased magnet, in a mound of stone, 5 ft. base, to top, with brass cap mkd.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 17 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T17N R26E $\frac{S11 S12}{S14 S13}$ 2023</p> <hr/> <p>From the cor. of secs. 12 and 13, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°47'30" W., bet. secs. 12 and 13.</p>
40.076	<p>Point for the 1/4 sec. cor. of secs. 12 and 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a clear plastic encased magnet, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T17N R26E S12 1/4 — S13 2023</p>
80.152	<p>The cor. of secs. 11, 12, 13 and 14.</p> <hr/> <p>N. 0°00'40" W., bet. secs. 11 and 12.</p>
40.000	<p>Point for the 1/4 sec. cor. of secs. 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a clear plastic encased magnet, in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T17N R26E 1/4 S11 S12 2023</p>
75.60	<p>Double track dirt road, 18 lks. wide, bears S. 85° E. and N. 85° W.</p>
80.000	<p>Point for the cor. of secs. 1, 2, 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a clear plastic encased magnet, in a collar of stone, with brass cap mkd.</p>

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 17 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T17N R26E S 2 S 1 ----- S11 S12</p> <p style="text-align: center;">2023</p> <hr/> <p>From the cor. of secs. 1 and 12, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°47'30" W., bet. secs. 1 and 12.</p>
26.60	Double track dirt road, 18 lks. wide, bears S. 50° E. and N. 50° W.
40.076	Point for the 1/4 sec. cor. of secs. 1 and 12. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a clear plastic encased magnet, with brass cap mkd.
	<p style="text-align: center;">T17N R26E S 1 1/4 ——— S12</p> <p style="text-align: center;">2023</p>
46.05	Double track dirt road, 18 lks. wide, bears N. 80° E. and S. 80° W.
57.50	Double track dirt road, 18 lks. wide, bears N. 50° E. and S. 50° W.
80.152	The cor. of secs. 1, 2, 11 and 12.
	<hr/> <p>N. 0°00'40" W., bet. secs. 1 and 2.</p>
40.000	Point for the 1/4 sec. cor. of secs. 1 and 2. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a clear plastic encased magnet, in a collar of stone, with brass cap mkd.
	<p style="text-align: center;">T17N R26E 1/4 S 2 S 1</p> <p style="text-align: center;">2023</p>
76.957	Intersect the S. bdy. of sec. 35, T. 18 N., R. 26 E. Point for the cor. of secs. 1 and 2.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 17 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a clear plastic encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T18N R26E S35 <hr/>S 2 S 1 T17N R26E</p> <p style="text-align: center;">2023</p> <p>From this point, the cor. of secs. 35 and 36, T. 18 N., R. 26 E., hereinbefore described, bears N. 89°54'20" E., 3.695 chs. dist.</p>
	<p>The point for the N 1/4 sec. cor. of sec. 1 is on the S. bdy. of T. 18 N., R. 26 E. and at midpoint in departure on the N. bdy. of sec. 1.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a clear plastic encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T18N R26E <hr/>1/4 S 1 T17N R26E</p> <p style="text-align: center;">2023</p> <p>Set a galvanized steel "U" post alongside the stainless steel post.</p> <p>From this point, the 1/4 sec. cor. of secs. 36, T. 18 N., R. 26 E., hereinbefore described, bears N. 89°47'50" E., 3.301 chs. dist.</p>
	<p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above a mound of stone, 3 ft. diam., 1 1/2 ft. high, with brass cap mkd. as described in the field notes of the independent resurvey of the north boundary, T. 16 N., R. 26 E., executed under Group No. 101, with a 4 x 4 ins. wood post with no visible marks, lying loose alongside. This cor. is also referenced as National Geodetic Survey KR1608 Hooten.</p> <p>N. 0°01'30" W., bet. secs. 34 and 35.</p>
25.85	<p>Double track dirt road, 18 lks. wide, bears N. 30° E. and S. 30° W.</p>
40.000	<p>Point for the 1/4 sec. cor. of secs. 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a clear plastic encased magnet, with brass cap mkd.</p>

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 17 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T17N R26E 1/4 S34 S35 2024
80.000	Point for the cor. of secs. 26, 27, 34 and 35. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a clear plastic encased magnet, with brass cap mkd.
	T17N R26E S27 S26 S34 S35 2024
	From the cor. of secs. 25, 26, 35 and 36. N. 89°45'40" W., bet. secs. 26 and 35.
9.75	Double track dirt road, 18 lks. wide, bears S. 10° E. and N. 10° W.
19.945	Point for the E 1/16 sec. cor. of secs. 26 and 35. POINT NOT MONUMENTED
39.890	Point for the 1/4 sec. cor. of secs. 26 and 35. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a clear plastic encased magnet, with brass cap mkd.
	T17N R26E S26 1/4 ——— S35 2024
43.00	Overhead power transmission lines, extend N. 5° E. and S. 5° W.
44.40	Double track dirt road, 18 lks. wide, bears N. 5° E. and S. 5° W.
45.60	Double track dirt road, 18 lks. wide, bears N. 55° E. and S. 55° W.
79.780	The cor. of secs. 26, 27, 34 and 35. N. 0°01'30" W., bet. secs. 26 and 27.
40.000	Point for the 1/4 sec. cor. of secs. 26 and 27.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 17 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a clear plastic encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T17N R26E 1/4 S27 S26</p> <p style="text-align: center;">2024</p>
80.000	<p>Point for the cor. of secs. 22, 23, 26 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a clear plastic encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T17N R26E <u>S22 S23</u> S27 S26</p> <p style="text-align: center;">2024</p>
	<p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>N. 89°45'40" W., bet. secs. 23 and 26.</p>
19.945	<p>Point for the E 1/16 sec. cor. of secs. 23 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a clear plastic encased magnet, with brass cap mkd.</p> <p style="text-align: center;">E 1/16 $\frac{S23}{S26}$</p> <p style="text-align: center;">2023</p>
35.10	<p>Set a galvanized steel "U" post alongside the stainless steel post.</p> <p>Overhead power transmission lines, extend N. 5° E. and S. 5° W.</p>
36.30	<p>Double track dirt road, 18 lks. wide, bears N. 5° E. and S. 5° W.</p>
39.890	<p>Point for the 1/4 sec. cor. of secs. 23 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a clear plastic encased magnet, with brass cap mkd.</p>

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 17 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T17N R26E S23 1/4 — S26 2023
79.780	The cor. of secs. 22, 23, 26 and 27.
	N. 0°01'30" W., bet. secs. 22 and 23.
40.000	Point for the 1/4 sec. cor. of secs. 22 and 23. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a clear plastic encased magnet, with brass cap mkd.
	T17N R26E 1/4 S22 S23 2024
80.000	Point for the cor. of secs. 14, 15, 22 and 23. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a clear plastic encased magnet, with brass cap mkd.
	T17N R26E S15 S14 S22 S23 2024
	From the cor. of secs. 13, 14, 23 and 24. N. 89°45'40" W., bet. secs. 14 and 23.
19.945	Point for the E 1/16 sec. cor. of secs. 14 and 23. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a clear plastic encased magnet, in a collar of stone, with brass cap mkd.
	S14 E 1/16 — S23 2023
	Set a galvanized steel "U" post alongside the stainless steel post.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 17 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
35.75	Overhead power transmission lines, extend S. 20° E. and N. 20° W.
36.85	Double track dirt road, 18 lks. wide, bears S. 20° E. and N. 20° W.
39.890	Point for the 1/4 sec. cor. of secs. 14 and 23.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a clear plastic encased magnet, in a collar of stone, with brass cap mkd.
	<p style="text-align: center;">T17N R26E S14 1/4 — S23</p>
	2023
	Set a galvanized steel "U" post alongside the stainless steel post.
79.780	The cor. of secs. 14, 15, 22 and 23.
	N. 0°01'30" W., bet. secs. 14 and 15.
40.000	Point for the 1/4 sec. cor. of secs. 14 and 15.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a clear plastic encased magnet, in a collar of stone, with brass cap mkd.
	<p style="text-align: center;">T17N R26E 1/4 S15 S14</p>
	2024
75.60	Double track dirt road, 18 lks. wide, bears S. 40° E. and N. 40° W.
80.000	Point for the cor. of secs. 10, 11, 14 and 15.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 9 ins. in the ground, over a clear plastic encased magnet, in a mound of stone, 5 ft. base, to top, with brass cap mkd.
	<p style="text-align: center;">T17N R26E S10 S11 S15 S14</p>
	2024
	From the cor. of secs. 11, 12, 13 and 14.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 17 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	N. 89°45'40" W., bet. secs. 11 and 14.
39.890	Point for the 1/4 sec. cor. of secs. 11 and 14. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, over a clear plastic encased magnet, in a mound of stone, 4 1/2 ft. base, to top, with brass cap mkd. T17N R26E S11 1/4 — S14 2023 Set a galvanized steel "U" post alongside the stainless steel post.
59.835	Point for the W 1/16 sec. cor. of secs. 11 and 14. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a clear plastic encased magnet, in a collar of stone, with brass cap mkd. S11 W 1/16 — S14 2023 Set a galvanized steel "U" post alongside the stainless steel post.
63.80	Overhead power transmission lines, extend S. 20° E. and N. 20° W.
65.40	Double track dirt road, 18 lks. wide, bears N. 30° E. and S. 30° W.
79.780	The cor. of secs. 10, 11, 14 and 15.
	N. 0°01'30" W., bet. secs. 10 and 11.
1.70	Double track dirt road, 18 lks. wide, bears N. 40° E. and S. 40° W.
30.60	Double track dirt road, 18 lks. wide, bears S. 45° E. and N. 45° W.
31.00	Double track dirt road, 18 lks. wide, bears S. 80° E. and N. 80° W.
40.000	Point for the 1/4 sec. cor. of secs. 10 and 11. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a clear plastic encased magnet, with brass cap mkd.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 17 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T17N R26E 1/4 S10 S11 2023. Set a galvanized steel "U" post alongside the stainless steel post.
43.30	Double track dirt road, 18 lks. wide, bears S. 20° E. and N. 20° W.
45.65	Overhead power transmission lines, extend S. 20° E. and N. 20° W.
57.75	Double track dirt road, 18 lks. wide, bears N. 55° E. and S. 55° W.
58.80	Double track dirt road, 18 lks. wide, bears E. and W.
80.000	Point for the cor. of secs. 2 and 11. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, over a clear plastic encased magnet, in a mound of stone, 4 ft. base, to top, with brass cap mkd. T17N R26E S10 S 2 S11 2023 Set a galvanized steel "U" post alongside the stainless steel post.
	From the cor. of secs. 1, 2, 11 and 12. N. 89°45'40" W., bet. secs. 2 and 11.
9.70	Double track dirt road, 18 lks. wide, bears S. 60° E. and N. 60° W.
39.890	Point for the 1/4 sec. cor. of secs. 2 and 11. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a clear plastic encased magnet, with brass cap mkd. T17N R26E S 2 1/4 — S11 2023
79.780	The cor. of secs. 2 and 11.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 17 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
0.705	<p>N. 0°01'30" W., bet. secs. 2 and 10.</p> <p>Intersect the line bet. secs. 3 and 10.</p> <p>Point for the cor. of secs. 2 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, over a clear plastic encased magnet, in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T17N R26E S 3 S10 S 2</p> <p style="text-align: center;">2023</p> <p>Set a galvanized steel "U" post alongside the stainless steel post.</p> <hr/> <p>The point for the N 1/4 sec. cor. of sec. 2 is on the S. bdy. of T. 18 N., R. 26 E. and at 40 chs. in departure from the cor. of secs. 1 and 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a clear plastic encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T18N R26E <u>1/4 S 2</u> T17N R26E 2023</p> <p>From this point, the 1/4 sec. cor. of sec. 35, T. 18 N., R. 26 E., hereinbefore described, bears S. 86°08'10" E., 3.388 chs. dist.</p> <hr/> <p>The point for the W 1/4 sec. cor. of sec. 2 is on the E. bdy. of sec. 3 and at 40 chs. in latitude from the cor. of secs. 2 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a clear plastic encased magnet, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T17N R26E 1/4 S 2</p> <p style="text-align: center;">2023</p> <p>From this point, the 1/4 sec. cor. of sec. 3, hereinbefore described, bears N. 0°21'30" E., 0.709 chs. dist.</p> <hr/>

THE SUBDIVISION OF SECTION 11,
T. 17 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	From the 1/4 sec. cor. of secs. 11 and 14.
	N. 0°01'00" W., on the N-S center line of sec. 11.
40.000	Point for the center 1/4 sec. cor. of sec. 11, at intersection with the E-W center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a clear plastic encased magnet, in a collar of stone, with brass cap mkd.
	T17N R26E C 1/4 S11
	2023
53.05	Double track dirt road, 18 lks. wide, bears E. and W.
80.000	The 1/4 sec. cor. of secs. 2 and 11.
	From the 1/4 sec. cor. of secs. 11 and 12.
	N. 89°45'40" W., on the E-W center line of sec. 11.
39.890	The center 1/4 sec. cor. of sec. 11.
59.835	Point for the C-W 1/16 sec. cor. of sec. 11.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a clear plastic encased magnet, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	W 1/16 C — C S11
	2023
	Set a galvanized steel "U" post alongside the stainless steel post.
77.80	Overhead power transmission lines, extend S. 20° E. and N. 20° W.
78.65	Double track dirt road, 18 lks. wide, bears S. 20° E. and N. 20° W.
79.780	The 1/4 sec. cor. of secs. 10 and 11.
	From the W 1/16 sec. cor. of secs. 11 and 14.
	N. 0°01'20" W., on the N-S center line of the SW1/4 of sec. 11.
40.000	The C-W 1/16 sec. cor. of sec. 11.

THE SUBDIVISION OF SECTION 14,
T. 17 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	From the 1/4 sec. cor. of secs. 14 and 23.
	N. 0°01'00" W., on the N-S center line of sec. 14.
8.80	Double track dirt road, 18 lks. wide, bears S. 20° E. and N. 20° W.
11.80	Overhead power transmission lines, extend S. 20° E. and N. 20° W.
40.000	Point for the center 1/4 sec. cor. of sec. 14, at intersection with the E-W center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a clear plastic encased magnet, in a collar of stone, with brass cap mkd.
	T17N R26E C 1/4 S14
	2023
	Set a galvanized steel "U" post alongside the stainless steel post.
80.000	The 1/4 sec. cor. of secs. 11 and 14.
<hr/>	
	From the 1/4 sec. cor. of secs. 13 and 14.
	N. 89°45'40" W., on the E-W center line of sec. 14.
39.890	The center 1/4 sec. cor. of sec. 14.
49.75	Overhead power transmission lines, extend S. 20° E. and N. 20° W.
52.35	Double track dirt road, 18 lks. wide, bears S. 10° E. and N. 10° W.
79.780	The 1/4 sec. cor. of secs. 14 and 15.
<hr/>	
THE SUBDIVISION OF SECTION 23, T. 17 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA	
<hr/>	
	From the 1/4 sec. cor. of secs. 23 and 26.
	N. 0°01'00" W., on the N-S center line of sec. 23.
40.000	Point for the center 1/4 sec. cor. of sec. 23 at intersection with the E-W center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a clear plastic encased magnet, with brass cap mkd.

THE SUBDIVISION OF SECTION 23,
T. 17 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T17N R26E C 1/4 S23 2023
80.000	The 1/4 sec. cor. of secs. 14 and 23.
	<hr/> From the 1/4 sec. cor. of secs. 23 and 24. N. 89°45'40" W., on the E-W center line of sec. 23.
19.945	Point for the C-E 1/16 sec. cor. of sec. 23.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a clear plastic encased magnet, in a collar of stone, with brass cap mkd.
	E 1/16 C — C S23 2023
	Set a galvanized steel "U" post alongside the stainless steel post.
31.30	Overhead power transmission lines, extend N. 5° E. and S. 5° W.
32.35	Double track dirt road, 18 lks. wide, bears N. 5° E. and S. 5° W.
39.890	The center 1/4 sec. cor. of sec. 23.
79.780	The 1/4 sec. cor. of secs. 22 and 23.
	<hr/> From the C-E 1/16 sec. cor. of sec. 23. N. 0°00'50" W., on the N-S center line of the NE1/4 of sec. 23.
17.15	Double track dirt road, 18 lks. wide, bears S. 80° E. and N. 80° W.
40.000	The E 1/16 sec. cor. of secs. 14 and 23.
	<hr/> From the E 1/16 sec. cor. of secs. 23 and 26. N. 0°00'50" W., on the N-S center line of the SE1/4 of sec. 23.
40.000	The C-E 1/16 sec. cor. of sec. 23.
	<hr/>

THE SUBDIVISION OF SECTION 26,
T. 17 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	From the 1/4 sec. cor. of secs. 26 and 35.
	N. 0°01'00" W., on the N-S center line of sec. 26.
4.75	Double track dirt road, 18 lks. wide, bears N. 50° E. and S. 50° W.
20.000	Point for the C-S 1/16 sec. cor. of sec. 26.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a clear plastic encased magnet, with brass cap mkd.
	<p style="text-align: center;">C S 1/16 S26 C</p> <p style="text-align: center;">2024</p>
	Set a galvanized steel "U" post alongside the stainless steel post.
31.80	Overhead power transmission lines, extend N. 5° E. and S. 5° W.
40.000	Point for the center 1/4 sec. cor. of sec. 26, at intersection with the E-W center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a clear plastic encased magnet, in a collar of stone, with brass cap mkd.
	<p style="text-align: center;">T17N R26E C 1/4 S26</p> <p style="text-align: center;">2023</p>
	from which
	<p style="text-align: center;">The NW. guy anchor of transmission tower No. 382-2, bears N. 19°12' E., 57.7 lks. dist.</p>
	<p style="text-align: center;">The SW. guy anchor of transmission tower No. 382-2, bears S. 0°01' W., 109.4 lks. dist.</p>
40.90	Double track dirt road, 18 lks. wide, bears N. 10° E. and S. 10° W.
80.000	The 1/4 sec. cor. of secs. 23 and 26.
	From the 1/4 sec. cor. of secs. 25 and 26.
	N. 89°45'40" W., on the E-W center line of sec. 26.
16.55	Double track dirt road, 18 lks. wide, bears N. 30° E. and S. 30° W.
19.945	Point for the C-E 1/16 sec. cor. of sec. 26.

THE SUBDIVISION OF SECTION 26,
T. 17 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a clear plastic encased magnet, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">E 1/16 C — C S26</p> <p style="text-align: center;">2023</p>
	<p>Set a galvanized steel "U" post alongside the stainless steel post.</p>
39.05	Overhead power transmission lines, extend N. 5° E. and S. 5° W.
39.890	The center 1/4 sec. cor. of sec. 26.
40.05	Double track dirt road, 18 lks. wide, bears N. 10° E. and S. 10° W.
79.780	The 1/4 sec. cor. of secs. 26 and 27.
	<hr/> <p>From the C-E 1/16 sec. cor. of sec. 26.</p> <p>N. 0°00'50" W., on the N-S center line of the NE1/4 of sec. 26.</p>
40.000	The E 1/16 sec. cor. of secs. 23 and 26.
	<hr/> <p>From the point for the E 1/16 sec. cor. of secs. 26 and 35.</p> <p>N. 0°00'50" W., on the N-S center line of the SE1/4 of sec. 26.</p>
20.000	Point for the SE 1/16 sec. cor. of sec. 26, at intersection with the E-W center line of the SE1/4.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a clear plastic encased magnet, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S26</p> <p style="text-align: center;">2023</p>
	<p>Set a galvanized steel "U" post alongside the stainless steel post.</p>
31.65	Double track dirt road, 18 lks. wide, bears N. 10° E. and S. 10° W.
40.000	The C-E 1/16 sec. cor. of sec. 26.
	<hr/> <p>From the point for the S 1/16 sec. cor. of secs. 25 and 26.</p> <p>N. 89°45'40" W., on the E-W center line of the SE1/4 of sec. 26.</p>

THE SUBDIVISION OF SECTION 26,
T. 17 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
6.15	Double track dirt road, 18 lks. wide, bears N. 30° E. and S. 30° W.
19.945	The SE 1/16 sec. cor. of sec. 26.
27.70	Double track dirt road, 18 lks. wide, bears N. 50° E. and S. 50° W.
39.890	The C-S 1/16 sec. cor. of sec. 26.
<hr/> <p>THE SUBDIVISION OF SECTION 35, T. 17 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>	
	<p>From the 1/4 sec. cor. of secs. 2 and 35, on the S. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above a mound of stone, 3 ft. diam., 1 1/2 ft. high, with brass cap mkd. as described in the field notes of the independent resurvey of a portion of the N. bdy. of T. 16 N., R. 27 E., executed under Group No. 101.</p> <p>N. 0°09'50" W., on the N-S center line of sec. 35.</p>
20.40	Double track dirt road, 18 lks. wide, bears N. 40° E. and S. 40° W.
40.080	Point for the center 1/4 sec. cor. of sec. 35, at intersection with the E-W center line.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a clear plastic encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T17N R26E C 1/4 S35</p> <p style="text-align: center;">2024</p>
80.081	<p>Set a galvanized steel "U" post alongside the stainless steel post.</p> <p>The 1/4 sec. cor. of secs. 26 and 35.</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 35 and 36.</p> <p>N. 89°45'40" W., on the E-W center line of sec. 35.</p>
24.55	Double track dirt road, 18 lks. wide, bears N. 30° E. and S. 30° W.
39.788	The center 1/4 sec. cor. of sec. 35.
47.00	Overhead power transmission lines, extend N. 5° E. and S. 5° W.
48.05	Double track dirt road, 18 lks. wide, bears N. and S.

THE SUBDIVISION OF SECTION 35,
T. 17 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
71.85	Double track dirt road, 18 lks. wide, bears N. 30° E. and S. 30° W.
79.780	The 1/4 sec. cor. of secs. 34 and 35.
GENERAL DESCRIPTION	
<p>Land in the northerly and southeasterly portions of this survey within sections 1, 2, 11, 12, and 13 is broken and hilly, ranging from 4,200 to 4,650 ft. above sea level. The remainder of the surveyed areas are nearly level with areas of alkali flats and generally sloping to the west. The reported distances herein were calculated at an average elevation of 4400 US Ft. above mean sea level.</p>	
<p>Soils range from gravelly, sandy loam in those areas supporting vegetation to silty clay loam and saline alkali in the sparsely vegetated and more level areas within sections 23, 26 and 35. During snow melt and inclement weather these level areas will become considerably muddy, as witnessed by our crews. Vegetation consists of Ephedra, Russian Thistle, Rabbit brush, Sparse Sage and grasses. The land within the surveyed area does not support timber.</p>	
<p>Springs or other sources of flowing water were not identified during the execution of this survey.</p>	
<p>Evidence of human activity within the surveyed area includes the numerous roads and the transmission line (N-001018) located and described within the field note record and the presence of an old fence corral within in the NW1/4 of section 24. Indicators of current or historical mining activity were not observed during the execution of this survey.</p>	
<p>Access is provided by numerous dirt roads by way of Lahontan Dam Road and US Highway 50.</p>	

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Lee T. Wilson	Cadastral Surveyor
Robert S. Hollis	Survey Technician
Mark G. Petrosine	Survey Technician
Jeremy J. Oster	Forestry Technician
Vincenzio C. Tartaglia	Forestry Technician

CERTIFICATE OF SURVEY

I, Richard J. Dieckmann, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing the date of the 21st day of September, 2023, I have dependently resurveyed a portion of the south boundary of Township 18 North, Range 26 East, and a portion of the subdivisional lines, and surveyed the east boundary, a portion of the subdivisional lines and subdivided sections 11, 14, 23, 26 and 35, Township 17 North, Range 26 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

SEP 23 2024

(Date)

Richard J. Dieckmann
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of the dependent resurvey of a portion of the south boundary of Township 18 North, Range 26 East, and a portion of the subdivisional lines, and the survey the east boundary, a portion of the subdivisional lines and the subdivision of sections 11, 14, 23, 26 and 35, Township 17 North, Range 26 East, of the Mount Diablo Meridian, Nevada, executed by Richard J. Dieckmann, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

SEP 23 2024

(Date)

Clarence D. Stickland
(Chief Cadastral Surveyor for Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above described surveys in Township 17 North, Range 26 East, Mount Diablo Meridian, Nevada, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor for Nevada)~~