

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

009

Original

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

A PORTION OF THE SOUTH BOUNDARY,  
A PORTION OF THE SUBDIVISIONAL LINES,  
AND THE MEANDERS OF CARSON LAKE,

AND

THE DETERMINATION OF A PARTITION LINE  
IN THE RELICTED LANDS OF CARSON LAKE,  
THE COMPLETION SURVEY OF THE SOUTH BOUNDARY,  
THE SUBDIVISION OF FRACTIONAL SECTIONS 25 AND 36,  
THE METES-AND-BOUNDS SURVEY OF PARCEL A,  
AND THE SURVEY OF TRACTS 37, 38, 39 AND 40,  
TOWNSHIP 17 NORTH, RANGE 28 EAST,  
OF THE MOUNT DIABLO MERIDIAN,  
IN THE STATE OF NEVADA

EXECUTED BY

Brock R. Clifford, Cadastral Surveyor  
Thomas E. Casinger, Cadastral Surveyor

Under Special Instructions dated June 10, 1996,  
and approved June 10, 1996,  
and Supplemental Special Instructions dated April 30, 1998,  
and approved April 30, 1998,  
which provided for the surveys included under Group No. 763,  
and Assignment Instructions dated June 10, 1996  
and November 3, 1997.

Survey commenced June 12, 1996

Survey completed June 8, 1998

## INDEX DIAGRAM

TOWNSHIP 17 NORTH, RANGE 28 EAST

<b>6</b>	<b>5</b>	<b>4</b>	<b>3</b>	<b>2</b>	<b>1</b>
<b>7</b>	<b>8</b>	<b>9</b>	<b>10</b>	<b>11</b>	<b>12</b>
<b>18</b>	<b>17</b>	<b>16</b>	<b>15</b>	<b>14</b>	<b>13</b>
				10	8
<b>19</b>	<b>20</b>	<b>21</b>	<b>22</b>	<b>23</b>	<b>24</b>
				9	6
<b>30</b>	<b>29</b>	<b>28</b>	<b>27</b>	<b>26</b>	<b>25</b>
					4
<b>31</b>	<b>32</b>	<b>33</b>	<b>34</b>	<b>35</b>	<b>36</b>
					2

Dependent resurvey of the meanders of Carson Lake.....Pages 11-13  
 Survey of the relicted lands of Carson Lake.....Page 13  
 Completion survey of the south boundary.....Pages 13-14  
 Subdivision of fractional section 25.....Pages 14-16  
 Subdivision of fractional section 36.....Pages 16-17  
 Metes-and-Bounds survey of Parcel A.....Pages 17-19  
 Metes-and-Bounds survey of Tract 37.....Pages 19-20  
 Metes-and-Bounds survey of Tract 38.....Pages 21-22  
 Metes-and-Bounds survey of Tract 39.....Pages 22-23  
 Metes-and-Bounds survey of Tract 40.....Pages 23-24

## TOWNSHIP 17 NORTH, RANGE 28 EAST, MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

The following field notes are those of the dependent resurvey of a portion of the south boundary, a portion of the subdivisional lines, and the meanders of Carson Lake, and the determination of a partition line in the relicited lands of Carson Lake, the completion survey of the south boundary, the subdivision of fractional sections 25 and 36, the metes-and-bounds survey of Parcel A, and the survey of Tracts 37, 38, 39 and 40, Township 17 North, Range 28 East, Mount Diablo Meridian, Nevada.

The west and north boundaries and portions of the south and east boundaries were surveyed by U.S. Deputy Surveyor E.B. Monroe, in 1868, under Contract No. 10. A portion of the subdivisional lines were surveyed by U.S. Deputy Surveyors E.B. Monroe and A.G. Bateman, in 1874, under Contract No. 63. The north boundary and portions of the south and east boundaries and subdivisional lines were resurveyed, and portions of the south and east boundaries and subdivisional lines, and the meanders of Carson Lake were surveyed by U.S. Deputy Surveyors M.F. Reilly and T.A. Magee, in 1881, under Contract No. 108. The southwest cor. of the township was remonumented by Cadastral Surveyor J.D. Sorenson, in 1967, under Group No. 447. A portion of the south boundary, the west boundary, and portions of north boundary and subdivisional lines were resurveyed by Cadastral Surveyor T.B. O'Toole, in 1990-91, under Group No. 694.

The dependent resurvey of a portion of the west boundary, and the completion survey of the west boundary of T. 17 N., R. 29 E., were executed concurrently under this same group.

Before restoring the corners, the lines of the original surveys were retraced and diligent search made for any evidence of the original corners and other calls of the original field note record.

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, the Special Instructions dated June 10, 1996, and the Supplemental Special Instructions dated April 30, 1998.

The direction of the lines of this survey were determined by azimuth taken from GPS positions at the cor. of secs. 1, 2, 35 and 36, Tps. 16 and 17 N., R. 28 E., and the cor. of secs. 1, 6, 7 and 12, T. 16 N., Rs. 28 and 29 E., and by use of Global Positioning System satellite data, using the real time kinematic survey process, and refer to the true meridian. The lines were carried forward by sustained angulation throughout the progress of the survey.

The vertical angles of measurements made on the slope were ascertained with a theodolite in good adjustment; the horizontal equivalents only are entered in the field notes.

012

## TOWNSHIP 17 NORTH, RANGE 28 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>The geographic position for the cor. of secs. 1, 2, 35 and 36, Tps. 16 and 17 N., R. 28 E., is at Lat. 39°17'05.801" N., and Long. 118°48'04.145" W. - NAD 83 (1986), as determined by survey grade GPS receivers, in 1996, from NGS stations "WYE" and "X 46".</p> <p>The 1980 mean magnetic declination is 16° E., as shown on U.S.G.S. quadrangle map "SOUTH OF FALLON, NEV." dated 1985.</p> <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY, T. 17 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>(Reestablishment of the Survey Executed by E.B. Monroe, U.S. Deputy Surveyor, in 1868, and the Resurvey Executed by M.F. Reilly and T.A. Magee, U.S. Deputy Surveyors, in 1881)</p> <hr/> <p>From the cor. of secs. 1, 2, 35 and 36, monumented with a basalt stone, 16x10x8 ins., mkd. with 6 grooves on the S. face, firmly set in a mound of stone. This is accepted as the best available evidence of the 1881 corner position. (Record, wood post)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <table border="1" data-bbox="876 1029 1023 1165"> <tr> <td>T17N</td><td>R28E</td></tr> <tr> <td>S35</td><td>S36</td></tr> <tr> <td>S 2</td><td>S 1</td></tr> <tr> <td colspan="2">T16N</td></tr> </table> <p>1996</p> <p>Deposit the basalt stone alongside the stainless steel post.</p> <p>S. 89°26'10" E., bet. secs. 1 and 36.</p> <p>Over alkali flat.</p> <p>17.00 Canal, bears SE. and NW.</p> <p>17.30 Bladed road, parallels canal.</p> <p>20.700 Point for the 1868 meander cor. of secs. 1 and 36, at record distance; there is no remaining evidence of the original corner. This will no longer function as a corner.</p> <p>40.150 The ¼ sec. cor. of secs. 1 and 36, monumented with a basalt stone, 11x7x6 ins., mkd. ¼ on N. face, firmly set in a mound of stone. This is accepted as the best available evidence of the original corner position. (Record, wood post)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>	T17N	R28E	S35	S36	S 2	S 1	T16N	
T17N	R28E								
S35	S36								
S 2	S 1								
T16N									

013

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 17 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T17N R28E S36 1/4 ——— S1 T16N  1996</p>
	<p>Deposit the basalt stone alongside the stainless steel post and rebuild the mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <hr/>
	<p>S. 89°23'30" E., beginning new measurement.</p>
25.060	<p>The meander cor. of secs. 1 and 36, monumented with a granite stone, 16x12x9 ins., mkd. S36 on the N. face, MC on the E. face, R27 S1 on the S. face and S36 on the N. face, firmly set in a mound of stone. This is accepted as the best available evidence of the original corner position. (Record, wood post) This cor. will now function as the meander cor. of sec. 36 only, and also as Angle Pt. No. 4, Tract 40.</p>
	<p>At the corner point</p>
	<p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T17N S36 R28E ——— MC T16N  1998</p>
	<p>Deposit the granite stone alongside the stainless steel post and rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <hr/>
	<p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 17 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>
	<p style="text-align: center;">(Reestablishment of the Survey Executed by E.B. Monroe and A.G. Bateman, U.S. Deputy Surveyors, in 1874, and the Resurvey and Survey Executed by M.F. Reilly and T.A. Magee, U.S. Deputy Surveyors, in 1881)</p> <hr/>
	<p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp. N. 0°25'20" E., bet. secs. 35 and 36.</p>
	<p>Over alkali flat.</p>
18.40	<p>Canal, bears SE. and NW.</p>
18.70	<p>Bladed road, bears SE. and NW.</p>
38.80	<p>Bladed road, bears E. and W.</p>
39.90	<p>Fence, bears E. and W.</p>

014

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 17 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 40.545</p>	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T17N R28E <math>\frac{1}{4}</math> S35   S36</p> <p style="text-align: center;">1997</p>
<p>81.090</p>	<p>The cor. of secs. 25, 26, 35 and 36, at intersection of old fences bearing N., S., E., and W. This is accepted as the best available evidence of the original corner position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T17N R28E S26   S25 ----- S35   S36</p> <p style="text-align: center;">1998</p> <p>From this corner, the cor. of secs. 26, 27, 34 and 35 bears N. <math>89^{\circ}34'40''</math> W., 80.460 chs. dist., monumented with a basalt stone, 12X10X8 ins., firmly set in the ground, mkd. with 1 groove on the S. face and 2 grooves on the E. face. This is accepted as the best available evidence of the original corner position. (Record, wood post)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T17N R28E S27   S26 ----- S34   S35</p> <p style="text-align: center;">1997</p> <p>Deposit the basalt stone alongside the stainless steel post.</p> <hr/> <p>N. <math>89^{\circ}51'00''</math> E., bet. secs. 25 and 36.</p> <p>Over level bottom land.</p>
<p>40.090</p>	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 25 and 36, monumented with a granite stone, 11x5x4 ins., firmly set, mkd. <math>\frac{1}{4}</math> on S. face and an "x" on top. This is accepted as the best available evidence of the original corner position. (Record, wood post)</p> <p>At the corner point</p>

015

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 17 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T17N R28E S25 1/4 ——— S36  1996</p> <p>Deposit the granite stone alongside the stainless steel post and set a steel fence post, 5 ft. long, alongside.</p> <hr/> <p>N. 89°50'10" E., beginning new measurement.</p> <p>Over level bottom land.</p>
15.039	<p>The meander cor. of secs. 25 and 36, monumented with a granite stone, 12x9x4 ins., firmly set, mkd. MC on the E. face and 1 groove on the S. face. This is accepted as the best available evidence of the original corner position. (Record, wood post) This cor. will now also function as Angle Pt. No. 4, Tract 39.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T17N S25 ——— S36 R28E</p> <p style="text-align: right;">MC</p> <p style="text-align: center;">1998</p> <p>Deposit the granite stone alongside the stainless steel post and set a steel fence post, 5 ft. long, alongside.</p> <hr/>
	<p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>N. 0°05'00" W., bet. secs. 25 and 26.</p> <p>Over level bottom land.</p>
20.10	Fence, bears E. and W.
20.350	<p>Point for the S <math>\frac{1}{16}</math> sec. cor. of secs. 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S26   S25  1997</p> <p>Set steel fence post, 5 ft. long, alongside.</p>

016

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 17 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS 40.700	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> T17N R28E  <math>\frac{1}{4}</math>  S26   S25    1997 </div> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>
81.400	<p>Point for the cor. of secs. 23, 24, 25 and 26, determined latitudinally by proportionate distance and longitudinally at record distance from the <math>\frac{1}{4}</math> sec. cor. of secs. 23 and 26; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> T17N R28E  S23   S24  <hr style="width: 50%; margin: 0 auto;"/> S26   S25    1996 </div> <p>From this point, a rebar monumented by Byron E. Johnson, Nevada Land Surveyor No. 9390, bears S. <math>65^{\circ}48'</math> E., 0.357 chs. dist., <math>\frac{5}{8}</math> in. diam., set flush with ground, with an aluminum cap, <math>1\frac{1}{2}</math> ins. diam., mkd. "B JOHNSON PLS 9390". This position is not utilized in the course of this survey.</p> <hr/> <p>EAST, bet. secs. 24 and 25.</p> <p>Over level bottom land.</p>
15.30	Wash, 8 lks. wide, 2 ft. deep, drains N. $30^{\circ}$ E.
21.90	Wash, 12 lks. wide, 2 ft. deep, drains S. $70^{\circ}$ E.
23.50	Fence, bears S. $50^{\circ}$ E. and N. $50^{\circ}$ W.
40.000	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> T17N R28E  S24  <math>\frac{1}{4}</math> ———  S25    1997 </div>



DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 17 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a steel fence post, 5<math>\frac{1}{2}</math> ft. long, alongside the stainless steel post.</p>
60.000	<p>Point for the meander cor. of secs. 24 and 25, determined at record bearing and distance; there is no remaining evidence of the original corner. This cor. will now also function as Angle Pt. No. 4, Tract 37 and Angle Pt. No. 2, Tract 38.</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>1998</p> </div> <p>Set a steel fence post, 5 ft. long, alongside the stainless steel post.</p> <p>From this point, the cor. of fences extending E., W. and NW., bears S. 41<math>\frac{1}{2}</math>° E., 1.36 chs. dist.</p> <hr/> <p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>N. 0°37'00" E., bet. secs. 23 and 24.</p> <p>Over level bottom land.</p>
40.753	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 23 and 24, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>1997</p> </div>
73.50	Bladed road, bears N. and S.
74.40	Canal, parallels bladed road.
81.506	<p>Point for the cor. of secs. 13, 14, 23 and 24, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 23 ins. in the ground, over a plastic-encased magnet and in a collar of stone, with brass cap mkd.</p>

018

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 17 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<div style="text-align: center;"> T17N R28E  S14   S13  <hr style="width: 50%; margin: 0 auto;"/> S23   S24    1997 </div> <p>From this point, a rebar monumented by Byron E. Johnson, Nevada Land Surveyor No. 9390, bears S. 0°08' W., 0.589 chs. dist., <math>\frac{5}{8}</math> in. diam., set flush with the ground, with an aluminum cap, <math>1\frac{1}{2}</math> ins. diam., mkd. "B JOHNSON PLS 9390". This position is not utilized in the course of this survey.</p> <p>From this same point, the cor. of secs. 11, 12, 13 and 14, bears N. 0°23'50" E., 81.402 chs. dist., monumented by Barry A. Fitzpatrick, Nevada Land Surveyor No. 7809, with a plastic pipe, filled with concrete, 4 ins. diam., firmly set, projecting 10 ins. above the ground, with a brass disk mkd. "11 12 13 14 T17N R28E 1993 PLS 7809" and a cross. This is accepted as the best available evidence of the original corner position.</p> <hr/> <p>S. 89°34'30" E., bet. secs. 13 and 24.</p> <p>Across pasture land.</p>
20.196	<p>Point for the W <math>\frac{1}{16}</math> sec. cor. of secs. 13 and 24.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> S13  W <math>\frac{1}{16}</math> ———  S24    1998 </div> <p>Set carsonite post, 5 ft. long, alongside the stainless steel post.</p> <p>From this point, the cor. of fences extending SE. and W. bears S. 69° W., 0.80 chs. dist. and the cor. of fences extending E. and NW. bears S. <math>26\frac{1}{2}</math>° E., 1.20 chs. dist. A canal, 18 lks. wide, parallels southerly of fences at 0.30 chs. dist.</p>
39.392	<p>Point selected for the witness cor. to the <math>\frac{1}{4}</math> sec. cor. of secs. 13 and 24.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> WC  T17N R28E  S13  1/4 ———&gt;  S24    1998 </div> <p>Set carsonite post, 5 ft. long, alongside the stainless steel post.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 17 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	From this point, a canal, 23 lks. wide, extending N. and S., bears E. at 1.00 chs., a fence extending N. and S. bears E. at 2.00 chs., a fence extending W. bears S. at 0.70 chs. dist., a canal, 20 lks. wide, extending E. and W., bears S. at 1.20 chs., and a fence extending E. (wanders), bears S. at 1.50 chs. dist.
40.392	Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 24, at proportionate distance, falls in canal where it is impractical to establish a permanent monument; there is no remaining evidence of the original corner.
41.40	Fence, bears N. and S.
79.796	Angle Pt. No. 2, Parcel A, hereinafter described.
	Continue bet. secs. 13 and 24, identical with line 2-1, Parcel A, hereinafter described.
80.554	Centerline of U.S. Highway No. 95, 48 lks. wide, bears N. $0^{\circ} 26'$ E. and S. $0^{\circ} 26'$ W.
80.784	The cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., identical with Angle Pt. No. 1, Parcel A, monumented with a rebar, $\frac{5}{8}$ in. diam., firmly set 2 ins. below asphalt surface, with plastic cap mkd. as described in the field notes of T. 17 N., R. 29 E., executed concurrently under this same group.
	From the cor. of secs. 23, 24, 25 and 26.
	S. $89^{\circ} 57' 40''$ W., bet. secs. 23 and 26.
	Over level bottom land.
19.800	Point for the E $\frac{1}{16}$ sec. cor. of secs. 23 and 26.
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<div style="text-align: center;">           S23            E <math>\frac{1}{16}</math> ———            S26            1997         </div>
	Set a steel fence post, 5 ft. long, alongside the stainless steel post.
	From this point, a rebar monumented by Byron E. Johnson, Nevada Land Surveyor No. 9390, bears S. $65^{\circ} 48'$ E, 0.179 chs. dist., $\frac{5}{8}$ in. diam., set flush with the ground, with an aluminum cap, $1\frac{1}{2}$ ins. diam., mkd. "B JOHNSON PLS 9390". This position is not utilized in the course of this survey.
23.20	Bladed road on curve, bears NNE. and SSE.
23.50	Canal, parallels bladed road.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 17 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 39.600</p>	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 23 and 26, monumented with a basalt stone, 12X10X9 ins., firmly set, projecting 5 ins. above the ground, dimly mkd. <math>\frac{1}{4}</math> on N. face. This is accepted as the best available evidence of the original corner position. (Record, wood post)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T17N R28E S23 <math>\frac{1}{4}</math> ——— S26  1998</p> </div> <p>Deposit the basalt stone and set a steel fence post, 5 ft. long, alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>S. <math>89^{\circ}08'30''</math> W., bet. secs. 14 and 23.</p> <p>Over level bottom land.</p>
<p>19.971</p>	<p>Point for the E <math>\frac{1}{16}</math> sec. cor. of secs. 14 and 23.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>S14 E <math>\frac{1}{16}</math> ——— S23  1997</p> </div> <p>Set a steel fence post, 5 ft. long, alongside the stainless steel post.</p> <p>From this point, a rebar monumented by Byron E. Johnson, Nevada Land Surveyor No. 9390, bears S. <math>0^{\circ}08'</math> W., 0.294 chs. dist., <math>\frac{5}{8}</math> in. diam., set flush with the surface of the ground, with an aluminum cap, <math>1\frac{1}{2}</math> ins. diam., mkd. "B JOHNSON PLS 9390". This position is not utilized in the course of this survey.</p>
<p>39.942</p>	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 14 and 23, monumented with a granite stone, 12X11X4 ins., firmly set, projecting 5 ins. above the ground, dimly mkd. <math>\frac{1}{4}</math> on N. face. This is accepted as the best available evidence of the original corner position. (Record, wood post)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

021

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 17 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">T17N R28E S14 1/4 ——— S23  1998</p> <p>Deposit the granite stone and set a steel fence post, 5 ft. long, alongside the stainless steel post.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF THE MEANDERS OF CARSON LAKE, T. 17 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">(Reestablishment of the Survey Executed by M.F. Reilly and T.A. Magee, U.S. Deputy Surveyors, in 1881)</p> <hr/> <p>From the meander cor. of sec. 36 only, on the S. bdy. of the Tp., identical with Angle Pt. No. 4, Tract 40, hereinbefore described.</p> <p>Thence northerly with the adjusted original meanders of sec. 36, identical with the bdy. bet. sec. 36 and Tract 40 and a portion of Tract 39, describing a fixed and limiting boundary.</p> <p>N. 8°26'20" W., 31.510 chs.,      Point for the adjusted position of Angle Pt. No. 1, and will now also function as Angle Pt. No. 3, Tract 40. Point not monumented.</p> <p>N. 5°16'40" E., 9.818 chs.,      the special meander cor. on the E-W center line of sec. 36, hereinafter described. This cor. will now also function as Angle Pt. No. 6, Tract 39 and Angle Pt. No. 2, Tract 40.</p> <p>20.226 chs.,      Point for the adjusted position of Angle Pt. No. 2, and will now also function as Angle Pt. No. 5, Tract 39.</p> <p style="text-align: right;">Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: right;">T17N S36      AP2 R28E</p> <p style="text-align: right;">1998</p> <p>N. 12°21'40" W., 31.314 chs.,      the meander cor. of secs. 25 and 36, identical with Angle Pt. No. 4, Tract 39, hereinbefore described.</p> <hr/>
--------	---

022

DEPENDENT RESURVEY OF THE MEANDERS OF CARSON LAKE,  
T. 17 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	Thence northerly with the adjusted original meanders of sec. 25, identical with the bdy. bet. sec. 25 and Tract 38 and a portion of Tract 39, describing a fixed and limiting boundary.
N. 9°52'30" E., 20.208 chs.,	Point for the adjusted position of Angle Pt. No. 1, and will now also function as Angle Pt. No. 3, Tract 39.
	Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<div style="text-align: right;"> T17N /  S25 / AP1  R28E / </div>
	1998
	Cor. is located in a fence, bears E. and W.
N. 8°23'30" E. 0.412 chs.,	the special meander cor. on the E-W center line of the SE $\frac{1}{4}$ of sec. 25, hereinafter described. This cor. will now also function as Angle Pt. No. 4, Tract 38 and Angle Pt. No. 2, Tract 39.
20.947 chs.,	the special meander cor. on the E-W center line of sec. 25, hereinafter described.
33.352 chs.,	Point for the adjusted position of Angle Pt. No. 2, and will now also function as Angle Pt. No. 3, Tract 38. Point not monumented.
N. 7°10'20" W., 28.571 chs.,	the meander cor. of secs. 24 and 25, identical with Angle Pt. No. 4, Tract 37 and Angle Pt. No. 2, Tract 38, hereinbefore described.
	<hr/> Thence northerly with the adjusted original meanders of sec. 24, identical with the bdy. bet. sec. 24 and Tract 37, describing a fixed and limiting boundary.
N. 22°45'10" W., 32.452 chs.,	Point for the adjusted position of Angle Pt. No. 1, and will now also function as Angle Pt. No. 3, Tract 37. Point not monumented.
N. 28°31'50" E., 26.241 chs.,	Point for the adjusted position of Angle Pt. No. 2, and will now also function as Angle Pt. No. 2, Tract 37. Point not monumented.

DEPENDENT RESURVEY OF THE MEANDERS OF CARSON LAKE,  
T. 17 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>N. 54°14'50" E., 25.388 chs., Angle Pt. No. 3, Parcel A, hereinafter described.</p> <p>26.727 chs., the meander cor. of secs. 19 and 24, on the E. bdy. of the Tp., identical with Angle Pt. No. 1, Tract 37 and Angle Pt. No. 4, Parcel A and also identical with Angle Pt. No. 9, Tract 40, T. 17 N., R. 29 E., monumented with a railroad spike, firmly set flush with surface of the ground, with top mkd. as described in the field notes of T. 17 N., R. 29 E., executed concurrently under this same group.</p> <hr/> <p>SURVEY OF THE RELICTED LAND OF CARSON LAKE, T. 17 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the meander cor. of secs. 24 and 25, identical with Angle Pt. No. 4, Tract 37 and Angle Pt. No. 2, Tract 38, hereinbefore described.</p> <p>N. 84°36'50" E., on the partition line between Tracts 37 and 38.</p> <p>Over nearly level land.</p> <p>21.697 The crossing closing cor. on the E. bdy. of the Tp., identical with Angle Pt. No. 5, Tract 37 and Angle Pt. No. 1, Tract 38 and also identical with Angle Pt. No. 8, Tract 37, T. 17 N., R. 29 E., and Angle Pt. No. 10, Tract 40, T. 17 N., R. 29 E., monumented with a stainless steel post, 2½ ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of T. 17 N., R. 29 E., executed concurrently under this same group.</p> <p>From this point, the point for the centroid of Carson Lake, identical with Angle Pt. No. 7, Tract 37, Angle Pt. No. 13, Tract 38 and Angle Pt. No. 11, Tract 40, all of T. 17 N., R. 29 E., bears N. 84°36'50" E., 296.274 chs. dist., as described in the field notes of T. 17 N., R. 29 E., executed concurrently under this same group.</p> <p>Land, nearly level. Soil, sandy clay loam. Undergrowth, native grasses.</p> <hr/> <p>COMPLETION SURVEY OF THE SOUTH BOUNDARY, T. 17 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the meander cor. of sec. 36 only, on the S. bdy. of the Tp., identical with Angle Pt. No. 4, Tract 40, hereinbefore described.</p>
--------	--

024

COMPLETION SURVEY OF THE SOUTH BOUNDARY,  
T. 17 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>EAST, on the S. bdy. of the Tp., identical with line 4-5, Tract 40.</p> <p>Over nearly level land.</p>
16.713	<p>The cor. of Tps. 16 and 17 N., Rs. 28 and 29 E., identical with Angle Pt. No. 5, Tract 40 and also identical with Angle Pt. No. 2, Tract 38, T. 16 N., R. 29 E. and Angle Pt. No. 9, Tract 37, T. 17 N., R. 29 E., monumented with a PK nail, set flush with asphalt surfaced road, as described in the field notes of T. 16 N., R. 29 E., executed concurrently under this same group.</p> <p>Land, nearly level. Soil, sand and clay. Vegetation, natural grasses and scattered greasewood.</p> <hr/> <p>SUBDIVISION OF FRACTIONAL SECTION 25, T. 17 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 25 and 36.</p> <p>N. <math>0^{\circ}08'30''</math> W., on the N-S center line of sec. 25.</p> <p>Over level bottom land.</p>
20.10	Fence, bears E. and W.
20.323	<p>Point for the C-S <math>\frac{1}{16}</math> sec. cor. of sec. 25.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <math display="block">\begin{array}{c} C \\ S\ 1/16 \left  S25 \\ C \end{array}</math> <p>1998</p> </div> <p>Set a steel fence post, 5 ft. long, alongside the stainless steel post.</p>
40.646	<p>Point for the center <math>\frac{1}{4}</math> sec. cor. of sec. 25, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T17N R28E</p> <math display="block">C\ 1/4\ S25</math> <p>1998</p> </div> <p>Set a steel fence post, 5 ft. long, alongside the stainless steel post.</p>
81.294	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 24 and 25.</p> <hr/>



025

SUBDIVISION OF FRACTIONAL SECTION 25,  
T. 17 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 25 and 26.</p> <p>N. <math>89^{\circ}55'30''</math> E., on the E-W center line of sec. 25, determined by the weighted mean bearing of the N. and S. bdys. of sec. 25.</p> <p>Over level bottom land.</p>
40.045	<p>The center <math>\frac{1}{4}</math> sec. cor. of sec. 25.</p>
61.704	<p>Point for the special meander cor., on the E-W center line of sec. 25, at intersection with the adjusted original meanders of Carson Lake.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T17N S25 C ——— C SMC R28E</p> <p>1998</p> </div> <p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <p>From this point, Angle Pt. No. 2 of the adjusted original meanders of Carson Lake, sec. 25, identical with Angle Pt. No. 3, Tract 38, hereinbefore described, bears N. <math>8^{\circ}23'30''</math> E., 12.405 chs. dist.</p>
18.614	<p>From the C-S <math>\frac{1}{16}</math> sec. cor. of sec. 25.</p> <p>N. <math>89^{\circ}53'20''</math> E., on the E-W center line of the <math>SE\frac{1}{4}</math> of sec. 25., determined by the weighted mean bearing of the N. and S. bdys. of the <math>SE\frac{1}{4}</math> of sec. 25.</p> <p>Over level bottom land.</p> <p>Point for a special meander cor., on the E-W center line of the <math>SE\frac{1}{4}</math> of sec. 24, at intersection with the adjusted original meanders of Carson Lake.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T17N S25 S ——— S SMC R28E</p> <p>1998</p> </div> <p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <p>From this point, Angle Pt. No. 1 of the adjusted original meanders of Carson Lake, sec. 25, identical with Angle Pt. No. 3, Tract 39, hereinbefore described, bears S. <math>8^{\circ}23'30''</math> W., 0.412 chs. dist.</p>

026


SUBDIVISION OF FRACTIONAL SECTION 25,  
T. 17 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the C-S <math>\frac{1}{16}</math> sec. cor. of sec. 25.</p> <p>S. <math>89^{\circ}53'20''</math> W., on the E-W center line of the SW<math>\frac{1}{4}</math> of sec. 25.</p> <p>Over level bottom land.</p>
40.067	<p>The S <math>\frac{1}{16}</math> sec. cor. of secs. 25 and 26.</p> <hr/> <p>SUBDIVISION OF FRACTIONAL SECTION 36, T. 17 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 1 and 36, on the S. bdy. of the Tp.</p> <p>N. <math>0^{\circ}23'10''</math> E., on the N-S center line of sec. 36.</p> <p>Over level bottom land.</p>
38.35	Bladed road, 36 lks. wide, bears E. and W.
40.20	Fence, bears E. and W.
40.770	<p>Point for the center <math>\frac{1}{4}</math> sec. cor. of sec. 36, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T17N R28E</p> <p style="text-align: center;">C <math>\frac{1}{4}</math> S36</p> <p style="text-align: center;">1998</p> <p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p>
81.590	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 25 and 36.</p> <hr/> <p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 35 and 36.</p> <p>S. <math>89^{\circ}45'20''</math> E. on the E-W center line of sec. 36., determined by the weighted mean bearing of the N. and S. bdys. of sec. 36.</p> <p>Over level bottom land.</p>
40.119	The center $\frac{1}{4}$ sec. cor. of sec. 36.
61.181	<p>Point for a special meander cor., on the E-W center line of sec. 36, at intersection with the adjusted original meanders of Carson Lake.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

027

SUBDIVISION OF FRACTIONAL SECTION 36,  
T. 17 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div data-bbox="883 264 1117 369"> <table> <tr><td>T17N</td><td></td></tr> <tr><td>S36</td><td></td></tr> <tr><td>C</td><td>C SMC</td></tr> <tr><td>R28E</td><td></td></tr> </table> </div> <div data-bbox="922 394 987 420">1998</div> <p data-bbox="440 447 1471 506">Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <p data-bbox="440 527 1471 609">From this point, Angle Pt. No. 1 of the adjusted original meanders of Carson Lake, sec. 36, identical with Angle Pt. No. 3, Tract 40, hereinbefore described, bears S. 5°16'40" W., 9.818 chs. dist.</p> <hr/> <p data-bbox="565 661 1352 714">METES-AND-BOUNDS SURVEY OF PARCEL A, T. 17 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p data-bbox="440 764 1471 846">Beginning at Angle Pt. No. 1, Parcel A, identical with the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., hereinbefore described.</p> <p data-bbox="440 869 1471 928">N. 89°34'30" W., on line 1-2, Parcel A, identical with a portion of the line bet. secs. 13 and 24.</p> <p data-bbox="440 951 873 980">Over asphalt surfaced road.</p> <p data-bbox="305 1003 1403 1033">0.23 Center of U.S. Highway No. 95, 48 lks. wide, bears N. and S.</p> <p data-bbox="305 1056 1289 1085">0.45 W. edge of asphalt pavement, enter nearly level land.</p> <p data-bbox="305 1108 1471 1190">0.988 Point for Angle Pt. No. 2, Parcel A, determined at the intersection of the line bet. secs. 13 and 24 and the westerly right-of-way of U.S. Highway No. 95.</p> <p data-bbox="440 1213 1471 1272">Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="883 1297 1097 1455"> <table> <tr><td>T17N</td><td>R28E</td></tr> <tr><td>S13</td><td></td></tr> <tr><td>S24</td><td>AP 2</td></tr> <tr><td></td><td>PARCEL A</td></tr> <tr><td></td><td>1998</td></tr> </table> </div> <p data-bbox="440 1482 1471 1564">Cor. is located in right-of-way fence bearing S., 33 lks. S. of a canal, 30 lks. wide, bears W. and on extension of a canal, 30 lks. wide, bears N.</p> <p data-bbox="440 1587 1471 1696">From this point, the point for the centerline of U.S. Highway No. 95 at Sta. B 1431+07.66, as shown on Plan and Profile Sheet No. 22, Project No. F006-4(8), obtained from the Nevada Highway No. 95 Department, bears N. 17°53'20" E., 2.542 chs. dist.</p> <p data-bbox="440 1722 607 1751">from which</p>	T17N		S36		C	C SMC	R28E		T17N	R28E	S13		S24	AP 2		PARCEL A		1998
T17N																			
S36																			
C	C SMC																		
R28E																			
T17N	R28E																		
S13																			
S24	AP 2																		
	PARCEL A																		
	1998																		

CHAINS	<p>A reference monument, bears S. 89°34' E., 0.701 chs. dist., monumented with a brass tablet, 3<sup>1</sup>/<sub>4</sub> ins. diam., seated in a concrete post, 18 ins. diam., firmly set 3 ins. below the surface of the ground, with top mkd. STA B 1431+07.6 DIST 46.13 ANGLE 90.</p> <p>A reference monument, bears N. 89°34' W., 0.604 chs. dist., monumented with a brass tablet, 3<sup>1</sup>/<sub>4</sub> ins. diam., seated in a concrete post, 18 ins. diam., firmly set 3 ins. below the surface of the ground, with top mkd. STA B 1431+07.6 DIST 39.75 ANGLE 90.</p> <p>From this same point, the true point for the 1/4 sec. cor. of secs. 13 and 24, bears N. 89°34'30" W., 39.404 chs. dist.</p> <hr/> <p>S. 0°26'00" W., on line 2-3, Parcel A, identical with a portion of the westerly right-of-way of U.S. Highway No. 95.</p> <p>13.090 Point for Angle Pt. No. 3, Parcel A, determined at the intersection of the westerly right-of-way of U.S. Highway No. 95 and the adjusted original meanders of Carson Lake, sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2<sup>1</sup>/<sub>2</sub> ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T17N R28E S24 AP 3 TR 37 1998</p>  </div> <p>Cor. is located in gate of westerly right-of-way fence, bears N. and S., 0.09 chs. S. of fences bearing N., S., and S. 54° W.</p> <p>From this point, the point for the centerline of U.S. Highway No. 95 at Sta. B 1478+55.61, as shown on Plan and Profile Sheet No. 22, Project No. F006-4(8), obtained from the Nevada Highway No. 95 Department, bears S. 0°55'30" E., 31.883 chs. dist.</p> <p>from which</p> <p>A reference monument, bears S. 89°35' E., 0.833 chs. dist., monumented with a brass tablet, 3<sup>1</sup>/<sub>4</sub> ins. diam., seated in a concrete post, 18 ins. diam., firmly set 3 ins. below the surface of the ground, with top mkd. STA B 1478+55.61 DIST 54.96 ANGLE 90.</p> <p>A reference monument, bears N. 89°35' W., 0.653 chs. dist., monumented with a brass tablet, 3<sup>1</sup>/<sub>4</sub> ins. diam., seated in a concrete post, 18 ins. diam., firmly set 3 ins. below the surface of the ground, with top mkd. STA B 1478+55.61 DIST 43.02 ANGLE 90.</p> <p>From this same point, Angle Pt. No. 2 of the adjusted original meanders of Carson Lake, sec. 24, identical with Angle Pt. No. 2,</p>
--------	--

029

METES-AND-BOUNDS SURVEY OF PARCEL A,  
T. 17 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Tract 37, hereinbefore described, bears S. 54°14'50" W., 25.388 chs. dist.</p>
	<p>From this same point, a rebar monumented by Byron E. Johnson, Nevada Land Surveyor No. 9390, bears S. 2°51' E., 0.066 chs. dist., <math>\frac{5}{8}</math> in. diam., set 1 in. below the surface of the ground, with an aluminum cap, <math>1\frac{1}{2}</math> ins. diam., mkd. illegibly. This position is not utilized in the course of this survey.</p>
	<p>N. 54°14'50" E., on line 3-4, Parcel A, identical with a portion of the adjusted original meanders of Carson Lake, sec. 24, and also identical with a portion of line 2-1, Tract 37.</p>
0.94	<p>Center of U.S. Highway No. 95, 48 lks. wide, bears N. and S.</p>
1.339	<p>Point for Angle Pt. No. 4, Parcel A, identical with the meander cor. of secs. 19 and 24, on the E. bdy. of the Tp. and Angle Pt. No. 1, Tract 37, and also identical with Angle Pt. No. 9, Tract 40, T. 17 N., R. 29 E., hereinbefore described.</p>
	<p>NORTH, on line 4-1, Parcel A, identical with a portion of the E. bdy. of the Tp.</p>
12.300	<p>Angle Pt. No. 1, Parcel A, identical with the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp. and point of beginning.</p>
	<p style="text-align: center;">SURVEY OF TRACT 37, T. 17 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA</p>
	<p>Beginning at Angle Pt. No. 1, Tract 37, identical with the meander cor. of secs. 19 and 24, on the E. bdy. of the Tp. and Angle Pt. No. 4, Parcel A and also identical with Angle Pt. No. 9, Tract 40, T. 17 N., R. 29 E., hereinbefore described.</p>
	<p>S. 54°14'50" W., on line 1-2, Tract 37, identical with a portion of line 4-3, Parcel A and also identical with a portion of the adjusted original meanders of Carson Lake, sec. 24.</p>
0.40	<p>Center of U.S. Highway No. 95, 48 lks. wide, bears N. and S.</p>
1.339	<p>Angle Pt. No. 3, Parcel A, hereinbefore described.</p>
	<p>Continue on line 1-2, Tract 37, identical with a portion of the adjusted original meanders of Carson Lake, sec. 24.</p>
26.727	<p>Angle Pt. No. 2, Tract 37, identical with Angle Pt. No. 2 of the adjusted original meanders of Carson Lake, sec. 24, hereinbefore described.</p>
	<p>From this point, a rebar monumented by Byron E. Johnson, Nevada Land Surveyor No. 9390, bears S. 42°16' E, 0.158 chs. dist., <math>\frac{5}{8}</math> in. diam., set 2 ins. below the surface of the ground, with an aluminum cap, <math>1\frac{1}{2}</math> ins. diam., mkd. "B JOHNSON PLS 9390". This position is not utilized in the course of this survey.</p>

030

SURVEY OF TRACT 37,  
T. 17 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From this same point, the cor. of fences extending SE., W. and NW., bears S. 26°46' W., 14.088 chs. dist. and the cor. of fences extending N. 45° E. and S. 30° W., bears N. 39<sup>1</sup>/<sub>4</sub>° W., 0.135 chs. dist.</p>
	<p>S. 28°31'50" W., on line 2-3, Tract 37, identical with a portion of the adjusted original meanders of Carson Lake, sec. 24.</p>
26.241	<p>Angle Pt. No. 3, Tract 37, identical with Angle Pt. No. 1 of the adjusted original meanders of Carson Lake, sec. 24, hereinbefore described.</p> <p>From this point, a rebar monumented by Byron E. Johnson, Nevada Land Surveyor No. 9390, bears S. 57° 56 'E, 0.380 chs. dist., <sup>5</sup>/<sub>8</sub> in. diam., set flush with the ground, with an aluminum cap, 1<sup>1</sup>/<sub>2</sub> ins. diam., mkd. "B JOHNSON PLS 9390". This position is not utilized in the course of this survey.</p> <p>From this same point, the cor. of fences extending SE. and NW., bears S. 37° E., 1.07 chs. dist.</p>
	<p>S. 22°45'10" E., on line 3-4, Tract 37, identical with a portion of the adjusted original meanders of Carson Lake, sec. 24.</p>
32.452	<p>Angle Pt. No. 4, Tract 37, identical with Angle Pt. No. 2, Tract 38 and also identical with the meander cor. of secs. 24 and 25, hereinbefore described.</p>
	<p>N. 84°36'50" E., on line 4-5, Tract 37, identical with a partition line of Carson Lake, and also identical with line 2-1, Tract 38.</p>
20.90	<p>Center of U.S. Highway No. 95, 48 lks. wide, bears N. and S.</p>
21.697	<p>Angle Pt. No. 5, Tract 37, on the E. bdy. of the Tp., identical with Angle Pt. No. 1, Tract 38 and the crossing closing cor. on the E. bdy. of the Tp. and also identical with Angle Pt. No. 8, Tract 37, T. 17 N., R. 29 E. and Angle Pt. No. 10, Tract 40, T. 17 N., R. 29 E., monumented with a stainless steel post, 2<sup>1</sup>/<sub>2</sub> ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of T. 17 N., R. 29 E., executed concurrently under this same group.</p>
	<p>N. 0°04'00" E., on line 5-1, Tract 37, identical with a portion of the E. bdy. of the Tp. and also identical with line 10-9, Tract 40, T. 17 N., R. 29 E.</p>
66.562	<p>Angle Pt. No. 1, Tract 37, identical with the meander cor. of secs. 19 and 24, on the E. bdy. of the Tp. and Angle Pt. No. 4, Parcel A, and also identical with Angle Pt. No. 9, Tract 40, T. 17 N., R. 29 E. and point of beginning.</p>

031

SURVEY OF TRACT 38,  
T. 17 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	Beginning at Angle Pt. No. 1, Tract 38, on the E. bdy. of the Tp., identical with Angle Pt. No. 5, Tract 37 and the crossing closing cor. on the E. bdy. of the Tp. and also identical with Angle Pt. No. 8, Tract 37, T. 17 N., R. 29 E. and Angle Pt. No. 10, Tract 40, T. 17 N., R. 29 E., hereinbefore described.
	S. 84°36'40" W., on line 1-2, Tract 38, identical with a partition line of Carson Lake, and also identical with line 5-4, Tract 37.
0.79	Center of U.S. Highway No. 95, 48 lks. wide, bears N. and S.
21.697	Angle Pt. No. 2, Tract 38, identical with Angle Pt. No. 4, Tract 37 and the meander cor. of secs. 24 and 25, hereinbefore described.
	S. 7°10'20" E., on line 2-3, Tract 38, identical with a portion of the adjusted original meanders of Carson Lake, sec. 25.
28.571	Angle Pt. No. 3, Tract 38, identical with Angle Pt. No. 2 of the adjusted original meanders of Carson Lake, sec. 25, hereinbefore described.
	S. 8°23'30" W., on line 3-4, Tract 38, identical with a portion of the adjusted original meanders of Carson Lake, sec. 25.
12.405	The special meander cor. on the E-W center line of sec. 25, hereinbefore described.
32.940	Angle Pt. No. 4, Tract 38, identical with Angle Pt. No. 2, Tract 39 and also identical with the special meander cor. on the E-W center line of the SE <sup>1</sup> / <sub>4</sub> of sec. 25, hereinbefore described.
	EAST, on line 4-5, Tract 38, identical with line 2-1, Tract 39.
21.60	Center of U.S. Highway No. 95, 48 lks. wide, bears N. and S.
22.768	Intersect the E. bdy. of the Tp.
	Point for Angle Pt. No. 5, Tract 38 and Angle Pt. No. 1, Tract 39.
	Set a stainless steel post, 28 ins. long, 2 <sup>1</sup> / <sub>2</sub> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<div style="text-align: center;"> T17N  TR38  AP 5  <hr/> AP 1  TR39  R28E R29E    1998 </div>

032

SURVEY OF TRACT 38,  
T. 17 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From this point, the cor. of Tps. 16 and 17 N., Rs. 28 and 29 E., identical with Angle Pt. No. 5, Tract 40 and also identical with Angle Pt. No. 2, Tract 38, T. 16 N., R. 29 E. and Angle Pt. No. 9, Tract 37, T. 17 N., R. 29 E., bears S. 0°04'00" W., 102.215 chs. dist., hereinbefore described.</p> <hr/>
62.971	<p>N. 0°04'00" E., on line 5-1, Tract 38, identical with a portion of the E. bdy. of the Tp. and also identical with a portion of line 9-8, Tract 37, T. 17 N., R. 29 E.</p> <p>Angle Pt. No. 1, Tract 38, on the E. bdy. of the Tp., identical with Angle Pt. No. 5, Tract 37 and also identical with Angle Pt. No. 8, Tract 37, T. 17 N., R. 29 E., and Angle Pt. No. 10, Tract 40, T. 17 N., R. 29 E. and point of beginning.</p> <hr/>
	<p style="text-align: center;">SURVEY OF TRACT 39, T. 17 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>
1.17	<p>Beginning at Angle Pt. No. 1, Tract 39, on the E. bdy. of the Tp., identical with Angle Pt. No. 5, Tract 38, hereinbefore described.</p> <p>WEST, on line 1-2, Tract 39, identical with line 5-4, Tract 38.</p> <p>Center of U.S. Highway No. 95, 48 lks. wide, bears N. and S.</p>
22.768	<p>Angle Pt. No. 2, Tract 39, identical with Angle Pt. No. 4, Tract 38 and also identical with the special meander cor. on the E-W center line of the SE<sup>1</sup>/<sub>4</sub> of sec. 25, hereinbefore described.</p> <hr/>
0.412	<p>S. 8°23'30" W., on line 2-3, Tract 39, identical with a portion of the adjusted original meanders of Carson Lake, sec. 25.</p> <p>Angle Pt. No. 3, Tract 39, identical with Angle Pt. No. 1 of the adjusted original meanders of Carson Lake, sec. 25, hereinbefore described.</p> <hr/>
20.208	<p>S. 9°52'30" W., on line 3-4, Tract 39, identical with a portion of the adjusted original meanders of Carson Lake, sec. 25.</p> <p>Angle Pt. No. 4, Tract 39, identical with the meander cor. of secs. 25 and 36, hereinbefore described.</p> <hr/>
31.314	<p>S. 12°21'40" E., on line 4-5, Tract 39, identical with a portion of the adjusted original meanders of Carson Lake, sec. 36.</p> <p>Angle Pt. No. 5, Tract 39, identical with Angle Pt. No. 2 of the adjusted original meanders of Carson Lake, sec. 25, hereinbefore described.</p> <hr/>
	<p>S. 5°16'40" W., on line 5-6, Tract 39, identical with a portion of the adjusted original meanders of Carson Lake, sec. 36.</p>



033

SURVEY OF TRACT 39,  
T. 17 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS 10.408	Angle Pt. No. 6, Tract 39, identical with the special meander cor. on the E-W center line of sec. 36 and Angle Pt. No. 2, Tract 40, hereinbefore described.
	<hr/>
	EAST, on line 6-7, Tract 39, identical with line 2-1, Tract 40.
18.93	Center of U.S. Highway No. 95, 48 lks. wide, bears N. and S.
20.482	Intersect the E. bdy. of the Tp.
	Point for Angle Pt. No. 7, Tract 39 and Angle Pt. No. 1, Tract 40.
	Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<div style="display: inline-block; vertical-align: middle;"> T17N  TR39  AP 7  <hr style="width: 100px;"/> AP 1  TR40  R28E R29E </div>
	1998
	From this point, the cor. of Tps. 16 and 17 N., Rs. 28 and 29 E., identical with Angle Pt. No. 5, Tract 40 and also identical with Angle Pt. No. 2, Tract 38, T. 16 N., R. 29 E. and Angle Pt. No. 9, Tract 37, T. 17 N., R. 29 E., bears S. 0°04'00" W., 40.939 chs. dist., hereinbefore described.
	<hr/>
	N. 0°04'00" E., on line 7-1, Tract 39, identical with a portion of the E. bdy. and also identical with a portion of line 9-8, Tract 37, T. 17 N., R. 29 E.
61.276	Angle Pt. No. 1, Tract 39, on the E. bdy. of the Tp., identical with Angle Pt. No. 5, Tract 38 and point of beginning.
	<hr/>
	SURVEY OF TRACT 40, T. 17 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA
	<hr/>
	Beginning at Angle Pt. No. 1, Tract 40, on the E. bdy. of the Tp., identical with Angle Pt. No. 7, Tract 39, hereinbefore described.
	WEST, on line 1-2, Tract 40, identical with line 7-6, Tract 39.
1.55	Center of U.S. Highway No. 95, 48 lks. wide, bears N. and S.
20.482	Angle Pt. No. 2, Tract 40, identical with Angle Pt. No. 6, Tract 39 and the special meander cor. on the E-W center line of sec. 36, hereinbefore described.
	<hr/>
	S. 5°16'40" W., on line 2-3, Tract 40, identical with a portion of the adjusted original meanders of Carson Lake, sec. 36.
0.50	Fence, bears E. and W.

034

SURVEY OF TRACT 40,  
T. 17 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS 1.70	Bladed road, bears E. and W.
9.818	Angle Pt. No. 3, Tract 40, identical with Angle Pt. No. 1 of the adjusted original meanders of Carson Lake, sec. 36, hereinbefore described.
	S. 8°26'20" E., on line 3-4, Tract 40, identical with a portion of the adjusted original meanders of Carson Lake, sec. 36.
31.510	Angle Pt. No. 4, Tract 40, identical with the meander cor. of sec. 36 only, on the S. bdy. of the Tp., hereinbefore described.
	EAST, on line 4-5, Tract 40, identical with a portion of the S. bdy. of the Tp.
16.713	Angle Pt. No. 5, Tract 40, identical with the cor. of Tps. 16 and 17 N., Rs. 28 and 29 E., and also identical with Angle Pt. No. 2, Tract 38, T. 16 N., R. 29 E. and Angle Pt. No. 9, Tract 37, T. 17 N., R. 29 E., hereinbefore described.
	N. 0°04'00" E., on line 5-1, Tract 40, identical with a portion of the E. bdy. and also identical with a portion of line 9-8, Tract 37, T. 17 N., R. 29 E.
0.54	Center of U.S. Highway No. 95, 48 lks. wide, on curve, bears N. and SSE.
40.939	Angle Pt. No. 1, Tract 40, identical with Angle Pt. No. 7, Tract 39 and point of beginning.
GENERAL DESCRIPTION	
The area surveyed and resurveyed within Township 17 North, Range 28 East, is fairly level terrain and alkali flats. The elevation ranges from about 3,910 to 3,920 ft. above sea level. The soil is sandy clay loam. The vegetation consists of sagebrush, rabbitbrush, Brigham tea and native grasses.	
Access is by U.S. Highway No. 95, crossing the area from the S. to the N. and by improved gravel roads and trail roads.	

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Peter F. Perazzo . . . . . Surveying Technician

Clay W. Morrow . . . . . Surveying Technician

## CERTIFICATE OF SURVEY

We, Brock R. Clifford and Thomas E. Casinger, Cadastral Surveyors, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 10th day of June, 1996, and Supplemental Special Instructions bearing date of the 30th day of April, 1998, we have dependently resurveyed a portion of the south boundary, a portion of the subdivisional lines, and the meanders of Carson Lake, and determined a partition line in the rellicted lands of Carson Lake, completed the survey of the south boundary, subdivided fractional sections 25 and 36, surveyed by metes-and-bounds Parcel A, and surveyed Tracts 37, 38, 39 and 40, Township 17 North, Range 28 East, Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

11/23/98

(Date)

David J. Clark

/For Brock R. Clifford

(Cadastral Surveyor)

11/23/98

(Date)

Thomas E. Casinger

(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Reno, Nevada

The foregoing field notes of the dependent resurvey of a portion of the south boundary, a portion of the subdivisional lines, and the meanders of Carson Lake, and the determination of a partition line in the rellicted lands of Carson Lake, the completion survey of the south boundary, the subdivision of fractional sections 25 and 36, the metes-and-bounds survey of Parcel A, and the survey of Tracts 37, 38, 39 and 40, Township 17 North, Range 28 East, Mount Diablo Meridian, Nevada, executed by Brock R. Clifford and Thomas E. Casinger, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

11/23/98

(Date)

David J. Clark

(Chief Cadastral Surveyor, Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 17 N., R. 28 E., M.D.M., Nevada, is a true copy of the original field notes.~~

~~(Date)~~~~(Chief Cadastral Surveyor, Nevada)~~