

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Original
FIELD NOTES
OF THE
DEPENDENT RESURVEY
OF
PORTIONS OF THE SOUTH AND EAST BOUNDARIES
AND
A PORTION OF THE SUBDIVISIONAL LINES,
AND
THE SUBDIVISION OF CERTAIN SECTIONS,
TOWNSHIP 17 SOUTH, RANGE 50 EAST,
OF THE MOUNT DIABLO MERIDIAN,
IN THE STATE OF NEVADA

EXECUTED BY
Douglas A. Potts, Cadastral Surveyor
Clay W. Morrow, Surveying Technician

Under Special Instructions dated February 2, 2006,
approved February 2, 2006,
which provided for the surveys included under Group No. 832,
and Assignment Instructions dated February 2, 2006.

Survey commenced February 9, 2006
Survey completed July 26, 2007

INDEX DIAGRAM

TOWNSHIP 17 SOUTH, RANGE 50 EAST, MOUNT DIABLO MERIDIAN, NEVADA

6	5	4	3	2	1
			12		6
7	8	11 9	10	6 11	5 12
	22	16	11	9	
18	17	16	15	14	13
	21	15	10 ⁹	9	
19 20	20	21	22 8	23	24
20	15	13	10		
30 19	29	28	27	26	25
18	16 ¹³			7	
31	32	33	7 34	35	36
	2				4 2

Subdivision of Section 9	pp 23 - 24.
Subdivision of Section 10	pp 24 - 25.
Subdivision of Section 12	pp 25 - 27.
Subdivision of Section 14	pp 27 - 29.
Subdivision of Section 17	pp 29 - 30.
Subdivision of Section 19	pp 30 - 32.
Subdivision of Section 20	pp 32 - 34.
Subdivision of Section 21	pp 34 - 37.
Subdivision of Section 22	pp 37 - 39.
Subdivision of Section 23	pp 40 - 41.
Subdivision of Section 26	pp 41 - 42.
Subdivision of Section 28	pp 42 - 44.
Subdivision of Section 29	pp 44 - 46.
Subdivision of Section 30	pp 46 - 47.
Subdivision of Section 32	pp 47 - 48.
Subdivision of Section 35	pp 49 - 51.
Subdivision of Section 36	pp 51 - 53.

TOWNSHIP 17 SOUTH, RANGE 50 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>The following field notes are those of the dependent resurvey of portions of the south and east boundaries and a portion of the subdivisional lines, and the subdivision of certain sections, Township 17 South, Range 50 East, Mount Diablo Meridian, Nevada.</p> <p>The Fourth Standard Parallel South, the west, east and south boundaries and subdivisional lines were surveyed by U.S. Deputy Surveyor E.A. Carter in 1881 under Contract No. 128. The south three miles of the west boundary and the west four miles of the south boundary were retraced and the west and south boundaries of section 31 were dependently resurveyed by U.S. Surveyor R.C. Yundt and U.S. Transitman R.F. Wilson in 1934 under California Group No. 259. The Fourth Standard Parallel South, the east boundary, the north five miles of the west boundary, the east five miles of the south boundary and the subdivisional lines were dependently resurveyed by Cadastral Surveyor H.G. Parker in 1963 under Group No. 408.</p> <p>Before restoring the corners, the lines of the original surveys were retraced and diligent search made for any evidence of the original corners and other calls of the original field note record.</p> <p>The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.</p> <p>The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 832, dated February 2, 2006.</p> <p>Measurements were made with Trimble 5700 Global Positioning System (GPS) receivers using the real-time kinematic (RTK) method and refer to the true meridian based on geodetic methods. The mean bearings of the lines and horizontal equivalents of ground distances only are entered in the field notes.</p> <p>The NAD 83 geographic position of the cor. of Tps. 17 and 18 S., Rs. 50 and 51 E., determined from Global Positioning System (GPS) static observations processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) TROPICANA CORS ARP, LAS VAGAS VALLEY CORS. ARP AND CARLTON SQUARE CORS ARP, in 2006, and carried forward by RTK observations is as follows:</p> <p>Latitude: 36°25'28.142" N. Longitude: 116°17'00.824" W.</p> <p>The January 1, 2007, mean magnetic declination was determined to be 13°08' E., from the National Oceanic and Atmospheric Administration's National Geophysical Data Center declination calculator.</p> <hr/>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Reestablishment of a Portion of the Survey Executed by E.A. Carter, U.S. Deputy Surveyor, in 1881, a Portion of the Dependent Resurvey Executed by R.C. Yundt, U.S. Surveyor and R.F. Wilson, U.S. Transitman, in 1933-34, and a Portion of the Dependent Resurvey Executed by H.G. Parker, Cadastral Surveyor, in 1963</p> <hr/> <p>Beginning at the cor. of Tps. 17 and 18 S., Rs. 50 and 51 E., monumented with an iron post, 2 1/2 ins. diam., firmly set on a rock ledge, in a mound of stone, 5 ft. diam., to top, with brass cap mkd. as described in the field notes of the dependent resurvey of the east boundary of T. 17 S., R. 50 E., executed under Group No. 408.</p> <p>N. 88°30'50" W., bet. secs. 1 and 36.</p> <p>Over nearly level land.</p> <p>21.061 The E 1/16 sec. cor. of secs. 1 and 36, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the south boundary of T. 17 S., R. 50 E., executed under Group No. 408, with a wooden post, 4 ins. square, mkd. US BOUNDARY NPS, firmly set alongside.</p> <hr/> <p>N. 88°30'00" W., beginning new measurement.</p> <p>21.121 The 1/4 sec. cor. of secs. 1 and 36, monumented with an iron post, 2 1/2 ins. diam., cemented in a mound of stone, 5 ft. diam., with brass cap mkd. as described in the field notes of the dependent resurvey of the south boundary of T. 17 S., R. 50 E., executed under Group No. 408, with a wooden post, 4 ins. square, mkd. US BOUNDARY NPS, firmly set alongside.</p> <hr/> <p>From the cor. of secs. 4, 5, 32 and 33, determined by person(s) unknown, monumented with a rebar, 5/8 in. diam., firmly set 10 ins. below the surface an improved gravel road, with a plastic cap not legible. This monument is locally recognized as the position of the original corner, is harmoniously related to other existing original and local corners and is accepted as the best available evidence of the position of the original corner.</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic- encased magnet, for a reference monument, bears N. 43°33' E., 70.3 lks. dist., with brass cap mkd. RM T17S R50E 46.4 FT TO COR S33 2007 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic- encased magnet, for a reference monument, bears N. 43°27' W., 78.2 lks. dist., with brass cap mkd. RM T17S R50E 51.6 FT TO COR S32 2007 and an arrow pointing to the corner.</p>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>N. 89°19'20" W., bet. secs. 5 and 32.</p> <p>Along bladed gravel road.</p>
40.184	<p>The 1/4 sec. cor. of secs. 5 and 32, determined by person(s) unknown, monumented with a rebar, 1/2 in. diam., firmly set 10 ins. below the surface of an improved gravel road. This monument is locally recognized as the position of the original corner, is harmoniously related to other existing original and local corners, and is accepted as the best available evidence of the position of the original corner.</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 49°14' E., 87.6 lks. dist., with brass cap mkd. RM 1/4 S32 57.8 FT TO COR 2007 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 50°34' W., 92.4 lks. dist., with brass cap mkd. RM 1/4 S32 61.0 FT TO COR 2007 and an arrow pointing to the corner.</p> <hr/> <p>N. 89°19'50" W., beginning new measurement.</p>
16.60	<p>Leave gravel road; continue along asphalt road.</p>
20.082	<p>The W 1/16 sec. cor. of secs. 5 and 32, determined by person(s) unknown, monumented with a rebar, 5/8 in. diam., firmly set flush with the surface of an asphalt road, with plastic cap not legible. This monument is locally recognized as the position of the corner point, and is accepted as a careful and faithful determination of the position of the corner.</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 37°03' E., 94.1 lks. dist., with brass cap mkd. RM W 1/16 S32 62.1 FT TO COR 2007 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 38°46' W., 99.7 lks. dist., with brass cap mkd. RM W 1/16 S32 65.8 FT TO COR 2007 and an arrow pointing to the corner.</p> <hr/> <p>N. 89°20'00" W., beginning new measurement.</p> <p>Continue along asphalt road.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p> <p>20.084</p>	<p>The cor. of secs. 5, 6, 31 and 32, determined by person(s) unknown, monumented with a rebar, 5/8 in. diam., firmly set flush with the surface of an asphalt road, with remains of a plastic cap not legible. This monument is locally recognized as the position of the original corner, is harmoniously related to other existing original and local corners, and is accepted as the best available evidence of the position of the original corner.</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 37°16' E., 88.0 lks. dist., with brass cap mkd. RM T17S R50E 58.1 FT TO COR S32 2007 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 49°50' W., 109.2 lks. dist., with brass cap mkd. RM T17S R50E 72.1 FT TO COR S31 2007 and an arrow pointing to the corner.</p> <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY, T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of a Portion of the Survey Executed by E.A. Carter, U.S. Deputy Surveyor, in 1881, and a Portion of the Dependent Resurvey Executed by H.G. Parker, Cadastral Surveyor, in 1963</p> <hr/> <p>From the cor. of Tps. 17 and 18 S., Rs. 50 and 51 E., hereinbefore described.</p> <p>N. 2°28'50" W., bet. secs. 31 and 36.</p> <p>Over low mountainous land.</p> <p>19.442 Point for the S 1/16 sec. cor. of secs. 31 and 36, falls on rocky ledge where it is impractical to establish a permanent monumented.</p> <p>From this point, the point selected for the witness corner to the S 1/16 sec. cor. of secs. 31 and 36, bears S. 89°20'10" E., 0.127 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground to solid rock, over a plastic-encased magnet and in a mound of stone, 4 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC</p> <p>S 1/16</p> <p>← S36 S31</p> <p>2007</p> </div>
-----------------------------	--

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Cor. is located 10 ft. E. of the top of a rocky, razorback ridge.
31.20	Trail road, bears NW. and SE.
38.884	The 1/4 sec. cor. of secs. 31 and 36, monumented with an iron post, 2 1/2 ins. diam., firmly set in a collar of stone, 2 1/2 ft. diam., with brass cap mkd. as described in the field notes of the dependent resurvey of the east boundary of T. 17 S., R. 50 E., executed under Group No. 408, with a mound of stone, 3 ft. diam., 1 ft. high, W. of cor.
	<p>From the 1/4 sec. cor. of secs. 7 and 12, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the east boundary of T. 17 S., R. 50 E., executed under Group No. 408, with a wooden post, 4 ins. square, firmly set alongside, projecting 2 ft. above the ground.</p> <p>N. 2°17'10" W., bet. secs. 7 and 12.</p> <p>Over nearly level land</p>
19.441	<p>The N 1/16 sec. cor. of secs. 7 and 12, determined by Richard H. Hafen, Nevada professional Land Surveyor No. 4428, monumented with a rebar, 5/8 in. diam., 12 ins. long, firmly set flush with the ground, with aluminum cap mkd. RL HAFEN RLS 4428. This monument is locally recognized as the position of the corner point, and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S12 S 7 2006</p> <p>Insert the rebar inside the stainless steel post, and set a steel boundary post, 8 ft. long, alongside the stainless steel post.</p> <p>N. 2°17'10" W., beginning new measurement.</p>
19.441	The cor. of secs. 1, 6, 7 and 12, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the east boundary of T. 17 S., R. 50 E., executed under Group No. 408, with an iron pipe, 2 ins. diam., firmly set alongside, projecting 4 ft. above the ground.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Reestablishment of a Portion of the Survey Executed by E.A. Carter, U.S. Deputy Surveyor, in 1881, and a Portion of the Dependent Resurvey Executed by H.G. Parker, Cadastral Surveyor, in 1963</p> <hr/> <p>From the 1/4 sec. cor. of secs. 11 and 12, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408, with a mound of stone 2 ft. diam., 1/2 ft. high, W. of cor.</p> <p>N. 3°53'20" W., bet. secs. 11 and 12.</p> <p>Over gently rolling land.</p> <p>37.808 The cor. of secs. 1, 2, 11 and 12, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408, with a mound of stone, 2 1/2 ft. diam., 1 ft. high, W. of cor.</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 88°54'40" W., bet. secs. 1 and 12.</p> <p>Over gently rolling land.</p> <p>20.045 The E 1/16 sec. cor. of secs. 1 and 12, determined by Richard L. Hafen, Nevada Professional Land Surveyor No. 4428, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set flush with the ground, with aluminum cap mkd. RL HAFEN RLS 4428. This monument is locally recognized as the position of the corner point and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{r} \text{E } 1/16 \quad \frac{\text{S } 1}{\text{S } 12} \\ 2006 \end{array}$ </div> <p>Insert the rebar inside the stainless steel post, and set a steel boundary post, 8 ft. long, alongside the stainless steel post.</p> <hr/> <p>N. 88°54'40" W., beginning new measurement.</p>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.045	<p>The 1/4 sec. cor. of secs. 1 and 12, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408, with a mound of stone, 2 ft. diam., 1 ft. high, N. of cor.</p> <hr/> <p>S. 89°56'10" W., beginning new measurement.</p>
39.880	<p>The cor. of secs. 1, 2, 11 and 12.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 34 and 35, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408, with a carsonite post firmly set alongside, projecting 4 ft. above the ground.</p> <p>N. 0°59'40" E., bet. secs. 34 and 35.</p> <p>Over nearly level land.</p>
4.60	Trail road, bears NE. and SW.
20.056	<p>Point for the N 1/16 sec. cor. of secs. 34 and 35.</p> <p>POINT NOT MONUMENTED.</p>
40.112	<p>The cor. of secs. 26, 27, 34 and 35, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408, with a mound of stone, 3 ft. diam., 2 ft. high, W. of the cor.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 26 and 35, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408, with a mound of stone, 2 ft. diam., 1 ft. high, N., and a carsonite post firmly set alongside of cor., projecting 4 ft. above the ground.</p> <p>S. 89°58'30" W., bet. secs. 26 and 35.</p> <p>Over nearly level land.</p>
20.082	<p>Point for the W 1/16 sec. cor. of secs. 26 and 35.</p> <p>POINT NOT MONUMENTED.</p>
22.30	Trail road, bears NW. and SE.
40.164	<p>The cor. of secs. 26, 27, 34 and 35.</p> <hr/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the cor. of secs. 22, 23, 26 and 27, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408, with a mound of stone, 4 ft. diam., 2 ft. high, W. of cor.</p> <p>N. 0°34'00" E., bet. secs. 22 and 23.</p> <p>Over nearly rolling bench land.</p>
20.098	<p>Point for the S 1/16 sec. cor. of secs. 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S22 S23 2006</p> <p>Set a steel boundary post, 8 ft. long, alongside the stainless steel post.</p>
40.196	<p>The 1/4 sec. cor. of secs. 22 and 23, monumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stone, 3 ft. diam., to top, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408, with a carsonite post firmly set alongside.</p> <hr/> <p>N. 6°15'00" W., beginning new measurement.</p> <p>Over nearly level land.</p>
9.214	<p>Point for the S-N 1/64 sec. cor. of secs. 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S-N 1/64 S22 S23 2007</p> <p>Set a steel boundary post, 8 ft. long, alongside the stainless steel post.</p>
18.428	<p>Point for the N 1/16 sec. cor. of secs. 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S22 S23 2006</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Set a steel boundary post, 8 ft. long, alongside the stainless steel post.
36.856	<p>The cor. of secs. 14, 15, 22 and 23, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408, with two carsonite posts firmly set alongside, each projecting 4 ft. above the ground.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 14 and 23, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408.</p> <p>N. 88°47'20" W., bet. secs. 14 and 23.</p> <p>Descend rocky N. slope.</p>
19.917	<p>Point for the W 1/16 sec. cor. of secs. 14 and 23.</p> <p>POINT NOT MONUMENTED.</p> <p>Enter rolling land.</p>
39.834	<p>The cor. of secs. 14, 15, 22 and 23.</p> <hr/> <p>N. 2°53'40" W., bet. secs. 14 and 15.</p> <p>Along old track road.</p>
18.420	<p>Point for the S 1/16 sec. cor. of secs. 14 and 15.</p> <p>POINT NOT MONUMENTED.</p>
36.840	<p>The 1/4 sec. cor. of secs. 14 and 15, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408, with two carsonite posts firmly set alongside, each projecting 4 ft. above the ground.</p> <hr/> <p>From the cor. of secs. 11, 12, 13 and 14, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408.</p> <p>S. 89°32'20" W., bet. secs. 11 and 14.</p> <p>Over nearly level land.</p>
39.135	<p>Point for the 1/4 sec. cor. of secs. 11 and 14, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 3 ft. diam., with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>T17S R50E S11 1/4 <u> </u> S14</p> <p>2006</p> <p>Cor. is located in a draw, drains N.</p>
78.270	<p>The cor. of secs. 10, 11, 14 and 15, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408, with two carsonite posts firmly set alongside, each projecting 4 ft. above the ground.</p> <hr/> <p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>N. 89°07'00" W., bet. secs. 22 and 27.</p> <p>Over gently rolling land.</p>
20.152	<p>Point for the E 1/16 sec. cor. of secs. 22 and 27.</p> <p>POINT NOT MONUMENTED.</p>
32.00	<p>Bladed dirt road, bears NE. and SW.</p>
40.304	<p>The 1/4 sec. cor. of secs. 22 and 27, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408.</p> <hr/> <p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>S. 87°31'00" W., bet. secs. 15 and 22.</p> <p>Over gently rolling land.</p>
17.30	<p>Bladed dirt road, bears N. and S.; enter abandoned cultivated fields.</p>
20.016	<p>Point for the E 1/16 sec. cor. of secs. 15 and 22.</p> <p>POINT NOT MONUMENTED.</p>
40.032	<p>The 1/4 sec. cor. of secs. 15 and 22, monumented with an iron post, 2 1/2 ins. diam., loosely set 12 ins. below the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408. The 1963 iron post has been disturbed and damaged. Accepted base of iron post as the best available evidence of the 1963 position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div data-bbox="862 279 1024 375"> <p>T17S R50E S15 1/4 <u>S22</u></p> </div> <div data-bbox="919 401 984 426">2007</div> <div data-bbox="449 455 1440 510"> <p>Bury the 1963 iron post below the surface of the ground, along the W. side of the stainless steel post.</p> </div> <hr/> <div data-bbox="449 564 1101 590"> <p>From the cor. of secs. 10, 11, 14 and 15.</p> </div> <div data-bbox="449 617 1053 642"> <p>N. 85°41'00" W., bet. secs. 10 and 15.</p> </div> <div data-bbox="449 669 846 695"> <p>Over gently rolling land.</p> </div> <div data-bbox="305 724 911 749"> <p>40.50 Trail road, bears NW. and SE.</p> </div> <div data-bbox="305 777 1456 936"> <p>40.719 The 1/4 sec. cor. of secs. 10 and 15, monumented with an iron post, 2 1/2 ins. diam., firmly set flush with the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408, with a steel post set alongside, projecting 4 ft. above the ground.</p> </div> <hr/> <div data-bbox="449 993 1133 1018"> <p>N. 85°41'40" W., beginning new measurement.</p> </div> <div data-bbox="449 1045 688 1071"> <p>Across meadows.</p> </div> <div data-bbox="305 1098 1459 1232"> <p>40.711 The cor. of secs. 9, 10, 15 and 16, established by person(s) unknown, monumented with a steel fence post, 5 ft. long, firmly set. This steel fence post correlates well with other existing corners and is accepted as the best available evidence of the position of the original corner.</p> </div> <div data-bbox="449 1260 756 1285"> <p>At the corner point</p> </div> <div data-bbox="449 1312 1459 1392"> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, encircled in a collar of stone, with brass cap mkd.</p> </div> <div data-bbox="881 1417 1027 1509"> <p>T17S R50E S 9 S10 <u>S16 S15</u></p> </div> <div data-bbox="919 1535 984 1560">2007</div> <div data-bbox="449 1587 1294 1612"> <p>Reset steel fence alongside the stainless steel post.</p> </div> <hr/> <div data-bbox="449 1669 1459 1854"> <p>From the 1/4 sec. cor. of secs. 9 and 10, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408, with two carsonite posts firmly set alongside, each projecting 4 ft. above the ground.</p> </div>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Cor. is located in meadow.</p> <p>N. 4°39'40" W., bet. secs. 9 and 10.</p> <p>Over nearly level land.</p>
11.70	Fence, bears, ENE. and WSW.
12.30	Mine haul road, bears ENE. and WSW.; enter rolling land.
18.226	<p>The N 1/16 sec. cor. of secs. 9 and 10, determined by Richard L. Hafen, Nevada Professional Land Surveyor No. 4428, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 8 ins. above the ground, with plastic cap mkd. RLS 4428. This monument is locally recognized as the position of the corner point, and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S 9 S10</p> <p style="text-align: center;">2006</p> <p>Insert the rebar inside the stainless steel post, and set a steel boundary post, 8 ft. long, alongside the stainless steel post.</p> <p>From this cor., a rebar, 1/4 in. diam., firmly set, projecting 4 ins. above the ground, bears NORTH, 0.03 chs. dist. This position cannot be reconciled with proper procedures, is not harmoniously related to surrounding corners and is not utilized during the course of this survey.</p> <hr/> <p>N. 4°39'40" W., beginning new measurement.</p>
16.60	Trail road, bears E. and W.
18.226	<p>The cor. of secs. 3, 4, 9 and 10, monumented with an iron post, 2 1/2 ins. diam., firmly set in a small collar of stone, projecting 8 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408, with a carsonite post firmly set alongside, projecting 4 ft. above the ground.</p> <hr/> <p>From the cor. of secs. 2, 3, 10 and 11, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408, with two carsonite posts firmly set alongside, each projecting 4 ft. above the ground.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 87°51'20" W., bet. secs. 3 and 10. Over rolling land.
20.90	Mine haul road, bears NE. and SW.
40.125	The 1/4 sec. cor. of secs. 3 and 10, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408, with a mound of stone, 3 ft. diam., 1 ft. high, N., and a wood post, 4x6 ins. diam., set alongside of cor. N. 87°50'30" W., beginning new measurement.
40.097	The cor. of secs. 3, 4, 9 and 10. From the cor. of secs. 28, 29, 32 and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408, with a mound of stone, 2 1/2 ft. diam., 1 ft. high, N. of cor. N. 0°10'50" E., bet. secs. 28 and 29. Over nearly level land.
19.856	Point for the S 1/16 sec. cor. of secs. 28 and 29. POINT NOT MONUMENTED.
39.712	The 1/4 sec. cor. of secs. 28 and 29, monumented with an iron post, 2 1/2 ins. diam., firmly set 8 ins. below the surface of the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408. From the cor. of secs. 21, 22, 27 and 28, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408. S. 89°20'10" W., bet. secs. 21 and 28. Over gently rolling land.
20.135	The E 1/16 sec. cor. of secs. 21 and 28, determined by Wallace T. Boundy, Nevada Professional Land Surveyor No. 2518, in 1991, monumented with a rebar, 5/8 in. diam., 12 ins. long, firmly set flush with the ground, with plastic cap mkd. BOUNDY RLS 2518, as recorded in Nye County, Nevada, Record of Survey No. 292624. This monument is locally recognized as the position of the corner point, and is accepted as a careful and faithful determination of the position of the corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> $\begin{array}{r} \text{E } 1/16 \quad \frac{\text{S21}}{\text{S28}} \\ 2007 \end{array}$ <p>Insert the rebar inside the stainless steel post, and set a steel boundary post, 8 ft. long, alongside the stainless steel post.</p> <hr/> <p>S. 89°20'20" W., beginning new measurement.</p> <p>20.143 The 1/4 sec. cor. of secs. 21 and 28, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408.</p> <hr/> <p>S. 89°22'00" W., beginning new measurement.</p> <p>0.50 Powerline, bears N. and S.</p> <p>0.70 Bladed road, bears N. and S.</p> <p>20.164 The W 1/16 sec. cor. of secs. 21 and 28, determined by Lisle Lowe, Nevada Professional Land Surveyor No. 8423, in 1996, monumented with a rebar, 5/8 in. diam., 12 ins. long, firmly set flush with the ground, with plastic cap not legible, as recorded in Nye County, Nevada, Record of Survey No. 395085. This monument is locally recognized as the position of the corner point, and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> $\begin{array}{r} \text{W } 1/16 \quad \frac{\text{S21}}{\text{S28}} \\ 2007 \end{array}$ <p>Insert the rebar inside the stainless steel post, and set a steel boundary post, 8 ft. long, alongside the stainless steel post.</p> <p>Cor. is located at S. end of fence, bearing N.</p> <hr/>
--------	---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	S. 89°20'00" W., beginning new measurement.
20.168	<p>The cor. of secs. 20, 21, 28 and 29, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408, with carsonite and steel posts firmly set alongside, each projecting 4 ft. above the ground.</p> <hr/> <p>N. 2°47'10" W., bet. secs. 20 and 21.</p> <p>Along fence, over nearly level land.</p>
19.862	<p>The S 1/16 sec. cor. of secs. 20 and 21, determined by Lisle Lowe, Nevada Professional Land Surveyor No. 8423, in 1996, monumented with a rebar, 5/8 in. diam., 12 ins. long, firmly set flush with the ground, with plastic cap mkd. PLS 8423, as recorded in Nye County, Nevada, Record of Survey No. 395085. This monument is locally recognized as the position of the corner point, and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>S 1/16 S20 S21</p> <p>2007</p> </div> <p>Insert the rebar inside the stainless steel post, and set a steel boundary post, 8 ft. long, alongside the stainless steel post.</p> <p>Cor. is located in a fence, bearing N. and S.</p> <hr/> <p>N. 2°47'10" W., beginning new measurement.</p>
0.50	Fence ends, bears S.
19.862	<p>The 1/4 sec. cor. of secs. 20 and 21, monumented with an iron post, 2 1/2 ins. diam., firmly set flush with the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408, with a carsonite post firmly set alongside, projecting 4 ft. above the ground.</p> <hr/> <p>From the cor. of secs. 15, 16, 21 and 22, determined by person(s) unknown, monumented with a rebar, 5/8 in. diam., 20 ins. long, firmly set 2 ins. below the ground, with remains of plastic cap not legible. This monument is locally recognized as the position of the corner point, and is accepted as a careful and faithful determination of the position of the corner.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{r} \text{T17S R50E} \\ \text{S16} \mid \text{S15} \\ \hline \text{S21} \mid \text{S22} \end{array}$ <p>2007</p> </div> <p>Insert the rebar inside the stainless steel post.</p> <p>Cor. is located in wet marsh area.</p> <p>N. 86°12'20" W., bet. secs. 16 and 21.</p> <p>Through wet marsh land.</p> <p>40.710 Point for the 1/4 sec. cor. of secs. 16 and 21, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{r} \text{T17S R50E} \\ \text{S16} \\ 1/4 \mid \hline \text{S21} \end{array}$ <p>2007</p> </div> <p>Cor. is located on levee, bears E. and W.</p> <p>81.420 The cor. of secs. 16, 17, 20 and 21, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408.</p> <hr/> <p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>S. 89°37'10 W., bet. secs. 9 and 16.</p> <p>Across rolling land.</p> <p>40.036 The 1/4 sec. cor. of secs. 9 and 16, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408.</p> <hr/> <p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>N. 89°36'40" W., bet. secs. 29 and 32.</p>
--------	---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Over nearly level land.
20.590	<p>The E 1/16 sec. cor. of secs. 29 and 32, determined by person(s) unknown, monumented with a rebar, 1/2 in. diam., 20 ins. long, firmly set flush with the ground, with a carsonite post firmly set alongside, projecting 4 ft. above the ground. This monument is locally recognized as the position of the corner point, and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{r} \text{E } 1/16 \quad \text{S29} \\ \hline \text{S32} \end{array}$ <p>2007</p> </div> <p>Insert the rebar inside the stainless steel post, and set a steel boundary post, 8 ft. long, alongside the stainless steel post.</p> <hr/> <p>N. 89°37'10" W., beginning new measurement.</p>
17.819	<p>The 1963 witness cor. for the 1/4 sec. cor. of secs. 29 and 32, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408.</p> <hr/> <p>N. 89°42'00" W., beginning new measurement.</p>
2.780	<p>The 1/4 sec. cor. of secs. 29 and 32, determined by person(s) unknown, monumented with a rebar, 1/2 in. diam., 20 ins. long, firmly set flush with the ground, with a carsonite post firmly set alongside, projecting 4 ft. above the ground. This monument is locally recognized as the position of the original corner, is harmoniously related to other existing original and local corners, and is accepted as a careful and faithful reestablishment of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{r} \text{T17S R50E} \\ \text{S29} \\ 1/4 \quad \hline \text{S32} \end{array}$ <p>2007</p> </div>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Bury the rebar alongside the stainless steel post, and set a steel boundary post, 8 ft. long, alongside the stainless steel post.</p>
	<hr/> <p>N. 89°42'00" W., beginning new measurement.</p>
20.495	<p>The W 1/16 sec. cor. of secs. 29 and 32, determined by person(s) unknown, monumented with a rebar, 1/2 in. diam., 20 ins. long, firmly set flush with the ground. This monument is locally recognized as the position of the corner point, and is accepted as a careful and faithful determination of the position of the corner.</p>
	<p>At the corner point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">W 1/16 $\frac{S29}{S32}$</p>
	<p style="text-align: center;">2007</p>
	<p>Bury the rebar alongside the stainless steel post, and set a steel boundary post, 8 ft. long, alongside the stainless steel post.</p>
	<p>Cor. is located 2 ft. N. of fence cor., fences extending S. and W.</p>
	<hr/> <p>N. 89°42'00" W., beginning new measurement.</p>
	<p>Along fence, over gently rolling land.</p>
20.495	<p>The cor. of secs. 29, 30, 31 and 32, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408.</p>
	<p>Cor. is located 1 1/2 ft. N. of fence, bearing E. and W.</p>
	<hr/> <p>N. 89°59'40" W., bet. secs. 30 and 31.</p>
	<p>Over nearly level land.</p>
20.520	<p>The E 1/16 sec. cor. of secs. 30 and 31, determined by person(s) unknown, monumented with a rebar, 1/2 in. diam., 20 ins. long, firmly set flush with the ground. This monument is locally recognized as the position of the corner point, and is accepted as a careful and faithful determination of the position of the corner.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{r} \text{E } 1/16 \quad \text{S30} \\ \hline \text{S31} \end{array}$ <p>2007</p> </div> <p>Bury the rebar alongside the stainless steel post, and set a steel boundary post, 8 ft. long, alongside the stainless steel post.</p> <p>Cor. is located 5 ft. SW. of fence cor., fences bearing N. and E.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 89°59'40" W., beginning new measurement.</p> <p>Over nearly level land.</p> <p>20.520 The 1/4 sec. cor. of secs. 30 and 31, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408, with a carsonite post firmly set alongside, projecting 4 ft. above the ground.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 1°23'20" E., bet. secs. 29 and 30.</p> <p>Over nearly level land.</p> <p>39.747 Point for the 1/4 sec. cor. of secs. 29 and 30, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T17S R50E</p> $\begin{array}{r} 1/4 \\ \text{S30} \mid \text{S29} \end{array}$ <p>2007</p> </div> <p>Set a carsonite post, 4 ft. long, alongside the stainless steel post.</p> <p>From this cor., the 1963 witness cor. to the 1/4 sec. cor. of secs. 29 and 30, an iron post, 28 ins. long, 2 1/2 in. diam., lying loose on the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408, bears S. 24°33' E., 0.72 chs. dist. This iron post has been disturbed due to farming activity and the true location is undeterminable. I destroy the iron post.</p>
--------	---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
79.494	<p>The cor. of secs. 19, 20, 29 and 30, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408, with a mound of stone, 3 ft. diam., 2 ft. high, W. of cor.</p> <hr/> <p>S. 89°24'40" W., bet. secs. 19 and 30.</p> <p>Over nearly level land.</p>
21.688	<p>The E 1/16 sec. cor. of secs. 19 and 30, determined by person(s) unknown, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 2 ins. above the ground. This monument is locally recognized as the position of the corner point, and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{r} \text{E } 1/16 \quad \text{S19} \\ \hline \text{S30} \end{array}$ <p>2007</p> </div> <p>Insert the rebar inside the stainless steel post, and set a steel boundary post, 8 ft. long, alongside the stainless steel post.</p> <p>Cor. is located in fence, bears N. and S.</p> <hr/> <p>S. 89°24'40" W., beginning new measurement.</p> <p>Over nearly level land.</p>
21.688	<p>The 1/4 sec. cor. of secs. 19 and 30, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408, with a carsonite post firmly set alongside, projecting 4 ft. above the ground.</p> <hr/> <p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 3°22'10" W., bet. secs. 19 and 20.</p> <p>Over nearly level land.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.122	<p>The S 1/16 sec. cor. of secs. 19 and 20, determined by person(s) unknown, monumented with a rebar, 1/2 in. diam., 20 ins. long, firmly set, projecting 4 ins. above the ground. This monument is locally recognized as the position of the corner point, and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S19 S20 2007</p> <p>Insert the rebar inside the stainless steel post, and set a steel boundary post, 8 ft. long, alongside the stainless steel post.</p> <hr/> <p>N. 3°22'10" W., beginning new measurement.</p> <p>Over rolling land.</p>
0.10	Fence, bears NE. and SW.
20.122	<p>The 1/4 sec. cor. of secs. 19 and 20, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408, with a mound of stone, 3 ft. diam., 2 ft. high, W. of cor.</p> <hr/> <p>N. 3°11'00" W., beginning new measurement.</p> <p>Over gently rolling land.</p>
38.884	<p>The cor. of secs. 17, 18, 19 and 20, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408.</p> <p>This cor. is located 5 ft. ESE. of fence cor., fences extending S. and ENE.</p> <hr/> <p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>N. 89°13'40" W., bet. secs. 17 and 20.</p> <p>Over nearly level land.</p>
20.336	Point for the E 1/16 sec. cor. of secs. 17 and 20.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	$\begin{array}{r} \text{E } 1/16 \quad \frac{\text{S17}}{\text{S20}} \\ 2006 \end{array}$
40.672	<p>The 1/4 sec. cor. of secs. 17 and 20, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, in a collar of stone, 3 ft. diam., with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408.</p>
	<hr/> <p>From the cor. of secs. 8, 9, 16 and 17, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408, with a steel fence post firmly set alongside.</p> <p>N. 89°53'30" W., bet. secs. 8 and 17.</p> <p>Over gently rolling land.</p>
20.091	<p>The E 1/16 sec. cor. of secs. 8 and 17, determined by the U.S. Fish and Wildlife Service, monumented with a rebar, 5/8 in. diam., 24 ins. long, firmly set, projecting 5 ins. above the ground, with aluminum cap erroneously mkd. D.O.I. FW W 1/16 S 8 S17. This monument is locally recognized as the position of the corner point, and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> $\begin{array}{r} \text{E } 1/16 \quad \frac{\text{S } 8}{\text{S17}} \\ 2006 \end{array}$ <p>Bury the rebar alongside the stainless steel post.</p> <hr/> <p>N. 89°53'30" W., beginning new measurement.</p> <p>Continue over gently rolling land.</p>
20.091	<p>The 1/4 sec. cor. of secs. 8 and 17, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, encircled in a collar of stone, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408.</p>

SUBDIVISION OF SECTION 9,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the 1/4 sec. cor. of secs. 9 and 16.</p> <p>N. 4°37'40" W., on the N-S center line of sec. 9.</p> <p>Over nearly level land.</p>
18.20	Fence, bears NE. and SW.
20.10	Mine haul road, bears NE. and SW.; enter rolling land.
36.536	<p>The center 1/4 sec. cor. of sec. 9, determined by person(s) unknown, monumented with a rebar, 1/4 in. diam., 10 ins. long, firmly set, projecting 2 ins. above the ground. This monument is locally recognized as the position of the corner point, and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T17S R50E</p> <p style="text-align: center;">C 1/4 S 9</p> <p style="text-align: center;">2006</p> <p>Bury the rebar alongside the stainless steel post.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/> <p>N. 4°37'40" W., beginning new measurement.</p> <p>Over rolling land.</p>
18.181	<p>The center N 1/16 sec. cor. of sec. 9, established by person(s) unknown, monumented with a rebar, 1/4 in. diam., firmly set, projecting 5 ins. above the ground, with a carsonite post firmly set alongside. This monument is locally recognized as the position of the corner point, and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;"> $\begin{array}{c} C \\ N\ 1/16 \left S\ 9 \\ C \end{array}$ </p> <p style="text-align: center;">2006</p> <p>Insert the rebar inside the stainless steel post, and set a steel boundary post, 8 ft. long, alongside the stainless steel post.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/>

SUBDIVISION OF SECTION 9,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 4°37'40" W., beginning new measurement. Continue over rolling land.
18.181	The 1/4 sec. cor. of secs. 4 and 9, monumented with an iron post, 2 1/2 ins. diam., firmly set in a collar of stone, projecting 10 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408, with a mound of stone, 2 1/2 ft. diam., 1 1/2 ft. high, N., and a carsonite post firmly set alongside of cor., projecting 4 ft. above the ground.
	From the 1/4 sec. cor. of secs. 9 and 10. S. 89°33'50" W., on the E-W center line of sec. 9. Over rolling land.
12.40	Bladed road, N. and S.
18.40	Fence, bears NE. and SW.
25.60	Mine haul road, bears NE. and SW.
39.996	The center 1/4 sec. cor. of sec. 9. S. 89°33'50" W., beginning new measurement. Over rolling land.
39.990	The 1/4 sec. cor. of secs. 8 and 9, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408, with a carsonite post firmly set alongside, projecting 4 ft. above the ground.
	From the N 1/16 sec. cor. of secs. 9 and 10. S. 89°30'00" W., on the E-W center line of the NE1/4 of sec. 9. Over rolling land.
39.981	The center N 1/16 sec. cor. of sec. 9.
	SUBDIVISION OF SECTION 10, T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA
	From the 1/4 sec. cor. of secs. 10 and 11, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 14 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 17 S., 50 E., executed under Group No. 408.

SUBDIVISION OF SECTION 10,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 86°42'50" W., on the E-W center line of sec. 10.
	Over rolling land.
80.830	The 1/4 sec. cor. of secs. 9 and 10.
	<p style="text-align: center;">SUBDIVISION OF SECTION 12, T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA</p>
	<p>From the 1/4 sec. cor. of secs. 12 and 13, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408, with a mound of stone, 2 ft. diam., 1 ft. high, N. of cor.</p>
	N. 3°06'30" W., on the N-S center line of sec. 12.
	Over rolling land.
38.464	<p>The center 1/4 sec. cor. of sec. 12, determined by person(s) unknown, monumented with a rebar, 5/8 in. diam., firmly set flush with the ground, with aluminum cap not legible. This monument is locally recognized as the position of the corner point, and is accepted as a careful and faithful determination of the position of the corner.</p>
	At the corner point
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	T17S R50E
	C 1/4 S12
	2006
	<p>Insert the rebar inside the stainless steel post, and set a steel boundary post, 8 ft. long, alongside the stainless steel post.</p>
	Cor. falls in wash, drains irregularly W.
	N. 3°06'30" W., beginning new measurement.
19.372	<p>The center N 1/16 sec. cor. of sec. 12, determined by Richard L. Hafen, Nevada Professional Land Surveyor No. 4428, monumented with a rebar, 5/8 in. diam., firmly set flush with the ground, with aluminum cap mkd. RL HAFEN RLS 4428. This monument is locally recognized as the position of the corner point, and is accepted as a careful and faithful determination of the position of the corner.</p>

SUBDIVISION OF SECTION 12,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 3°06'30" W., beginning new measurement.
19.372	The 1/4 sec. cor. of secs. 1 and 12.
	<hr/> <p>From the 1/4 sec. cor. of secs. 7 and 12, on the E. bdy. of the Tp.</p> <p>N. 88°39'30" W., on the E-W center line of sec. 12.</p> <p>Over rolling land.</p>
19.774	<p>The center E 1/16 sec. cor. of sec. 12, determined by Richard L. Hafen, Nevada Professional Land Surveyor No. 4428, monumented with a rebar, 5/8 in. diam., firmly set flush with the ground, with aluminum cap mkd. RL HAFEN RLS 4428. This monument is locally recognized as the position of the corner point, and is accepted as a careful and faithful determination of the position of the corner.</p> <hr/> <p>N. 88°39'30" W., beginning new measurement.</p>
19.774	<p>The center 1/4 sec. cor. of sec. 12.</p> <hr/> <p>N. 88°39'30" W., beginning new measurement.</p>
39.430	<p>The 1/4 sec. cor. of secs. 11 and 12.</p> <hr/> <p>From the center E 1/16 sec. cor. of sec. 12.</p> <p>N. 2°41'50" W., on the N-S center line of the NE1/4 of sec. 12.</p> <p>Over rolling land.</p>
19.406	<p>The NE 1/16 sec. cor. of sec. 12, determined by Richard L. Hafen, Nevada Professional Land Surveyor No. 4428, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set flush with the ground, with aluminum cap mkd. RL HAFEN RLS 4428. This monument is locally recognized as the position of the corner point, and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S12</p> <p style="text-align: center;">2006</p> <p>Insert the rebar inside the stainless steel post, and set a steel boundary post, 8 ft. long, alongside the stainless steel post.</p> <hr/>

SUBDIVISION OF SECTION 12,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 2°41'50" W., beginning new measurement.
19.406	The E 1/16 sec. cor. of secs. 1 and 12.
	<hr/> <p>From the N 1/16 sec. cor. of secs. 7 and 12, on the E. bdy. of the Tp.</p> <p>N. 88°47'00" W., on the E-W center line of the NE1/4 of sec. 12.</p> <p>Over rolling land.</p>
19.909	The NE 1/16 sec. cor. of sec. 12.
	<hr/> <p>N. 88°47'00" W., beginning new measurement.</p>
19.909	The center N 1/16 sec. cor. of sec. 12.
	<hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 14, T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 14 and 23.</p> <p>N. 3°21'10" W., on the N-S center line of sec. 14.</p> <p>Over gently rolling land.</p>
18.723	Point for the center S 1/16 sec. cor. of sec. 14.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<div style="text-align: center;"> $\begin{array}{c} C \\ S\ 1/16\ S14 \\ C \end{array}$ <p>2006</p> </div>
	Set a steel boundary post, 8 ft. long, alongside the stainless steel post.
37.446	Point for the center 1/4 sec. cor. of sec. 14, at intersection with the E-W center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<div style="text-align: center;"> <p>T17S R50E</p> <p>C 1/4 S14</p> <p>2006</p> </div>

SUBDIVISION OF SECTION 14,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Set a steel boundary post, 8 ft. long, alongside the stainless steel post.
74.875	<p>The 1/4 sec. cor. of secs. 11 and 14.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 13 and 14, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408, with a mound of stone, 2 ft. diam., 1 ft. high, W. of the cor.</p> <p>N. 89°37'50" W., on the E-W center line of sec. 14.</p> <p>Over gently rolling land.</p>
39.502	The center 1/4 sec. cor. of sec. 14.
59.248	<p>Point for the center W 1/16 sec. cor. of sec. 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \text{W } 1/16 \\ \text{C } \frac{\quad}{\quad} \text{C} \\ \text{S14} \end{array}$ <p>2006</p> </div> <p>Set a steel boundary post, 8 ft. long, alongside the stainless steel post.</p>
78.994	<p>The 1/4 sec. cor. of secs. 14 and 15.</p> <hr/> <p>From the point for the W 1/16 sec. cor. of secs. 14 and 23.</p> <p>N. 3°07'30" W., on the N-S center line of the SW1/4 of sec. 14.</p> <p>Over gently rolling land.</p>
18.572	<p>Point for the SW 1/16 sec. cor. of sec. 14, at intersection with the E-W center line of the SW1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \text{SW } 1/16 \text{ S14} \\ \\ 2006 \end{array}$ </div> <p>Set a steel boundary post, 8 ft. long, alongside the stainless steel post.</p>
37.144	<p>The center W 1/16 sec. cor. of sec. 14.</p> <hr/>

SUBDIVISION OF SECTION 14,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the center S 1/16 sec. cor. of sec. 14.</p> <p>N. 89°12'40" W., on the E-W center line of the SW1/4 of sec. 14.</p> <p>Over gently rolling land.</p>
19.831	The SW 1/16 sec. cor. of sec. 14.
39.662	The point for the S 1/16 sec. cor. of secs. 14 and 15.
<p style="text-align: center;">SUBDIVISION OF SECTION 17, T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA</p>	
	<p>From the 1/4 sec. cor. of secs. 17 and 20.</p> <p>N. 2°28'30" W., on the N-S center line of sec. 17.</p> <p>Over gently rolling land.</p>
20.40	Fence, bears NE. and SW.
34.90	Mine haul road, bears NE. and SW.
38.590	<p>Point for the center 1/4 sec. cor. of sec. 17, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T17S R50E</p> <p style="text-align: center;">C 1/4 S17</p> <p style="text-align: center;">2006</p> <p>Set a steel boundary post, 8 ft. long, alongside the stainless steel post.</p>
77.116	The 1/4 sec. cor. of secs. 8 and 17.
	<p>From the 1/4 sec. cor. of secs. 16 and 17, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408, with a carsonite post firmly set alongside, projecting 4 ft. above the ground.</p> <p>N. 89°31'50" W., on the E-W center line of sec. 17.</p> <p>Over gently rolling land.</p>
20.210	Point for the center E 1/16 sec. cor. of sec. 17.

SUBDIVISION OF SECTION 17,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">E 1/16 C $\frac{\quad}{S17}$ C S17</p> <p style="text-align: center;">2006</p> <p>Set a steel boundary post, 8 ft. long, alongside the stainless steel post.</p>
27.10	Fence, bears NE. and SW.
35.80	Mine haul road, bears NE. and SW.
40.420	The center 1/4 sec. cor. of sec. 17.
80.848	<p>The 1/4 sec. cor. of secs. 17 and 18, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408, with a mound of stone, 3 ft. diam., 2 ft. high, W. of cor.</p> <hr/> <p>From the center E 1/16 sec. cor. of sec. 17.</p> <p>N. 2°38'10" W., on the N-S center line of the NE1/4 of sec. 17.</p> <p>Over gently rolling land.</p>
12.35	Mine haul road, bears NE. and SW.
38.658	<p>The E 1/16 sec. cor. of secs. 8 and 17.</p> <hr/> <p>From the E 1/16 sec. cor. of secs. 17 and 20.</p> <p>N. 2°39'00" W., on the N-S center line of the SE1/4 of sec. 17.</p> <p>Over gently rolling land.</p>
38.705	<p>The center E 1/16 sec. cor. of sec. 17.</p> <hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 19, T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 19 and 30.</p> <p>N. 2°33'50" W., on the N-S center line of sec. 19.</p> <p>Over rolling land.</p>
19.860	<p>Point for the center S 1/16 sec. cor. of sec. 19.</p> <p>POINT NOT MONUMENTED.</p>

SUBDIVISION OF SECTION 19,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.720	<p>Point for the center 1/4 sec. cor. of sec. 19, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 1 ft. diam., with brass cap mkd.</p> <p style="text-align: center;">T17S R50E</p> <p style="text-align: center;">C 1/4 S19</p> <p style="text-align: center;">2006</p>
49.00	Mine haul road, bears NE. and SW.
78.790	<p>The 1/4 sec. cor. of secs. 18 and 19, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408, with a mound of stone, 2 ft. diam., W. of cor.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 19 and 20.</p> <p>S. 88°44'20" W., on the E-W center line of sec. 19.</p> <p>Over rolling land.</p>
5.50	Fence, bears NE. and SW.
21.396	<p>Point for the center E 1/16 sec. cor. of sec. 19.</p> <p>POINT NOT MONUMENTED.</p>
42.792	The center 1/4 sec. cor. of sec. 19.
55.00	Mine haul road, bears NE. and SW.
83.735	<p>The 1/4 sec. cor. of secs. 19 and 24, on the W. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the west boundary of T. 17 S., R. 50 E., executed under Group No. 408, with a carsonite post firmly set alongside, projecting 4 ft. above the ground.</p> <hr/> <p>From the E 1/16 sec. cor. of secs. 19 and 30.</p> <p>N. 2°58'10" W., on the N-S center line of the SE1/4 of sec. 19.</p> <p>Along fence, over rolling land.</p>
19.990	<p>The SE 1/16 sec. cor. of sec. 19, determined by U.S. Fish and Wildlife Service, monumented with a rebar, 3/4 in. diam., 30 ins. long, firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. SE 1/16 S19 1987. This monument is locally recognized as the position of the corner point, and is accepted as a careful and faithful determination of the position of the corner.</p>

SUBDIVISION OF SECTION 19,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S19</p> <p style="text-align: center;">2007</p> <p>Bury the rebar alongside the stainless steel post.</p> <hr/> <p>N. 2°58'10" W., beginning new measurement.</p>
0.11	Fence, bears NE. and SW.
19.990	<p>The point for the center E 1/16 sec. cor. of sec. 19.</p> <hr/> <p>From the S 1/16 sec. cor. of secs. 19 and 20.</p> <p>S. 89°04'40" W., on the E-W center line of the SE1/4 of sec. 19.</p> <p>Over rolling land.</p>
21.542	<p>The SE 1/16 sec. cor. of sec. 19.</p> <hr/> <p>S. 89°04'40" W., beginning new measurement.</p>
0.06	Fence, bears N. and S.
21.542	<p>The point for the center S 1/16 sec. cor. of sec. 19.</p> <hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 20, T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 20 and 29, determined by person(s) unknown, monumented with a rebar, 1/2 in. diam., 20 ins. long, firmly set, projecting 4 ins. above the ground. This monument is locally recognized as the position of the original corner, is harmoniously related to other existing original and local corners, and is accepted as the best available evidence of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T17S R50E S20 1/4 <u> </u> S29</p> <p style="text-align: center;">2007</p> <p>Insert the rebar in the stainless steel post.</p>

SUBDIVISION OF SECTION 20,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 2°59'00" W., on the N-S center line of sec. 20.
	Over nearly level land.
19.990	The center S 1/16 sec. cor. of sec. 20, determined by
	Richard L. Hafen, Nevada Professional Land Surveyor No. 4428,
	monumented with a rebar, 1/2 in. diam., 30 ins. long, firmly
	set, projecting 4 ins. above the ground, with plastic cap mkd.
	RLS 4428. This monument is locally recognized as the position
	of the corner point, and is accepted as a careful and faithful
	determination of the position of the corner.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
	24 ins. in the ground, over a plastic-encased magnet, with brass
	cap mkd.
	<div style="text-align: center;"> $\begin{array}{c} C \\ S\ 1/16 \left S20 \\ C \end{array}$ </div>
	2007
	Bury the rebar alongside the stainless steel post, and set a
	steel boundary post, 8 ft. long, alongside the stainless steel
	post.
	<hr/>
	N. 2°59'00" W., beginning new measurement.
19.990	The center 1/4 sec. cor. of sec. 20, determined by person(s)
	unknown, monumented with a rebar, 5/8 in. diam., firmly set,
	projecting 4 ins. above the ground, with aluminum cap mkd. T17S
	R50E C 1/4 S20. This monument is locally recognized as the
	position of the corner point, and is accepted as a careful and
	faithful determination of the position of the corner.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
	24 ins. in the ground, over a plastic-encased magnet, with brass
	cap mkd.
	<div style="text-align: center;">T17S R50E</div>
	<div style="text-align: center;">C 1/4 S20</div>
	2007
	Bury the rebar alongside the stainless steel post, and set a
	steel boundary post, 8 ft. long, alongside the stainless steel
	post.
	<hr/>
	N. 2°59'00" W., beginning new measurement.
38.818	The 1/4 sec. cor. of secs. 17 and 20.
	<hr/>

SUBDIVISION OF SECTION 20,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the 1/4 sec. cor. of secs. 20 and 21.</p> <p>N. 89°12'20" W., on the E-W center line of sec. 20.</p> <p>Over nearly level land.</p>
40.396	<p>The center 1/4 sec. cor. of sec. 20.</p> <hr/> <p>N. 89°12'20" W., beginning new measurement.</p>
40.530	<p>The 1/4 sec. cor. of secs. 19 and 20.</p> <hr/> <p>From the center S 1/16 sec. cor. of sec. 20.</p> <p>N. 89°22'50" W., on the E-W center line of the SW1/4 of sec. 20.</p> <p>Over gently rolling land.</p>
40.388	<p>The S 1/16 sec. cor. of secs. 19 and 20.</p> <hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 21, T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 21 and 28.</p> <p>N. 2°36'30" W., on the N-S center line of sec. 21.</p> <p>Over nearly level land.</p>
9.60	Powerline, bears N. and S.
16.50	Bladed road, bears N. and S.; thence along bladed road.
18.938	<p>Point for the center S 1/16 sec. cor. of sec. 21.</p> <p>POINT NOT MONUMENTED.</p>
37.10	Leave bladed road, on curve, bears S. and E; enter wet marsh land.
37.876	<p>The center 1/4 sec. cor. of sec. 21, determined by Wallace T. Boundy, Nevada Professional Land Surveyor No. 2518, in 1991, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 1 in. above the ground, with plastic cap not legible, as recorded in Nye County, Nevada, Record of Survey No. 292624. This monument is locally recognized as the position of the corner point, and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

SUBDIVISION OF SECTION 21,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">T17S R50E</p> <p style="text-align: center;">C 1/4 S21</p> <p style="text-align: center;">2007</p> <p>Insert the rebar inside the stainless steel post, and set a steel boundary post, 8 ft. long, alongside the stainless steel post.</p> <hr/> <p>N. 2°31'20" W., beginning new measurement.</p>
37.500	<p>The 1/4 sec. cor. of secs. 16 and 21.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 21 and 22, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408, with a carsonite post firmly set alongside.</p> <p>N. 88°04'50" W., on the E-W center line of sec. 21.</p> <p>Over gently rolling land.</p>
20.228	<p>The center E 1/16 sec. cor. of sec. 21, determined by Wallace T. Boundy, Nevada Professional Land Surveyor No. 2518, in 1991, monumented with a rebar, 5/8 in. diam., 12 ins. long, firmly set, projecting 1 in. above the ground, with plastic cap mkd. Boundy RLS 2518, as recorded in Nye County, Nevada, Record of Survey No. 292624, with a carsonite post firmly set alongside. This monument is locally recognized as the position of the corner point, and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">E 1/16 C $\frac{\quad}{\quad}$ C S21</p> <p style="text-align: center;">2007</p> <p>Insert the rebar inside the stainless steel post, and set a steel boundary post, 8 ft. long, alongside the stainless steel post.</p> <hr/> <p>N. 88°07'00" W., beginning new measurement.</p>
7.50	Bladed road, bears ENE. and WSW.
18.90	Powerline, bears N. and S.
20.232	The center 1/4 sec. cor. of sec. 21.

SUBDIVISION OF SECTION 21,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 88°02'50" W., beginning new measurement. Across marsh land.
20.279	Point for the center W 1/16 sec. cor. of sec. 21. POINT NOT MONUMENTED.
40.558	The 1/4 sec. cor. of secs. 20 and 21. <hr/>
	From the E 1/16 sec. cor. of secs. 21 and 28. N. 2°32'50" W., on the N-S center line of the SE1/4 of sec. 21. Over gently rolling land.
36.978	The center E 1/16 sec. cor. of sec. 21. <hr/>
	From the W 1/16 sec. cor. of secs. 21 and 28. N. 2°41'10" W., on the N-S center line of the SW1/4 of sec. 21. Over nearly level land.
11.30	Private access gravel road, bears E. and W.
19.405	The SW 1/16 sec. cor. of sec. 21, determined by person(s) unknown, monumented with a rebar, 5/8 in. diam., 15 ins. long, firmly set, projecting 4 ins. above the ground, at cor. of fences, extending S. and W. This monument is locally recognized as the position of the corner point, and is accepted as a careful and faithful determination of the position of the corner. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. SW 1/16 S21 2007 Insert the rebar inside the stainless steel post, and set a steel boundary post, 8 ft. long, alongside the stainless steel post. <hr/>
19.390	N. 2°43'10" W., beginning new measurement. The point for the center W 1/16 sec. cor. of sec. 21. <hr/>
	From the point for the center S 1/16 sec. cor. of sec. 21. N. 89°18'50" W., on the E-W center line of the SW1/4 of sec. 21.

SUBDIVISION OF SECTION 21,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Over nearly level land.
20.211	The SW 1/16 sec. cor. of sec. 21.
	N. 89°22'40" W., beginning new measurement.
20.223	The S 1/16 sec. cor. of secs. 20 and 21.
	<p style="text-align: center;">SUBDIVISION OF SECTION 22, T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA</p>
	From the 1/4 sec. cor. of secs. 22 and 27.
	N. 2°33'00" W., on the N-S center line of sec. 22.
	Over gently rolling land.
19.049	Point for the center S 1/16 sec. cor. of sec. 22.
	POINT NOT MONUMENTED.
38.098	Point for the center 1/4 sec. cor. of sec. 22, at intersection with the E-W center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T17S R50E
	C 1/4 S22
	2007
	Set a steel fence post, 4 ft. long, alongside the stainless steel post.
46.10	Bladed road, bears ENE. and WSW.
56.323	Point for the center N 1/16 sec. cor. of sec. 22.
	POINT NOT MONUMENTED.
74.548	The 1/4 sec. cor. of secs. 15 and 22.
	From the 1/4 sec. cor. of secs. 22 and 23.
	S. 87°57'40" W., on the E-W center line of sec. 22.
	Over nearly level land.
21.208	Point for the center E 1/16 sec. cor. of sec. 22.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

SUBDIVISION OF SECTION 22,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div style="text-align: center;"> $\begin{array}{c} E \ 1/16 \\ C \ \hline S22 \end{array} C$ </div>
	<div style="text-align: center;">2007</div>
	<p>Set a steel boundary post, 4 ft. long, alongside the stainless steel post.</p>
21.508	Bladed dirt road, bears N. and S.
42.416	The center 1/4 sec. cor. of sec. 22.
82.600	The 1/4 sec. cor. of secs. 21 and 22.
	<hr/>
	<p>From the center E 1/16 sec. cor. of sec. 22.</p>
	<p>N. 4°24'40" W., on the N-S center line of the NE1/4 of sec. 22.</p>
	<p>Over nearly level land.</p>
1.20	Bladed dirt road, bears N. and S.
8.90	Bladed dirt road, bears E. and W.
9.159	Point for the C-S-NE 1/64 sec. cor. of sec. 22.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<div style="text-align: center;"> $\begin{array}{c} S22 \\ C-S-NE \ 1/64 \end{array}$ </div>
	<div style="text-align: center;">2007</div>
	<p>Set carsonite and steel boundary posts alongside the stainless steel post.</p>
18.318	Point for the NE 1/16 sec. cor. of sec. 22, at intersection with the E-W center line of the NE1/4.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<div style="text-align: center;">NE 1/16 S22</div>
	<div style="text-align: center;">2007</div>
	<p>Set a steel boundary post, 8 ft. long, alongside the stainless steel post.</p>
36.636	The point for the E 1/16 sec. cor. of secs. 15 and 22.
	<hr/>

SUBDIVISION OF SECTION 22,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the N 1/16 sec. cor. of secs. 22 and 23.</p> <p>S. 87°44'40" W., on the E-W center line of the NE1/4 of sec. 22.</p> <p>Over nearly level land.</p>
17.50	Bladed dirt road, N. and S.
20.612	The NE 1/16 sec. cor. of sec. 22.
41.224	The point for the center N 1/16 sec. cor. of sec. 22.
	<hr/> <p>From the S-N 1/64 sec. cor. of secs. 22 and 23.</p> <p>S. 87°51'10" W., on the E-W center line of the SE1/4 of the NE1/4 of sec. 22.</p> <p>Over nearly level land.</p>
17.80	Bladed dirt road, bears N. and S.
20.910	The C-S-NE 1/64 sec. cor. of sec. 22.
	<hr/> <p>From the point for the E 1/16 sec. cor. of secs. 22 and 27.</p> <p>N. 0°57'00" W., on the N-S center line of the SE1/4 of sec. 22.</p> <p>Over nearly level land.</p>
18.60	Bladed dirt road, bears NE. and SW.
19.566	<p>Point for the SE 1/16 sec. cor. of sec. 22, at intersection with the E-W center line of the SE1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S22</p> <p style="text-align: center;">2007</p> <p>Set a steel boundary post alongside the stainless steel post.</p>
39.132	The center E 1/16 sec. cor. of sec. 22.
	<hr/> <p>From the S 1/16 sec. cor. of secs. 22 and 23.</p> <p>S. 89°23'00" W., on the E-W center line of the SE1/4 of sec. 22.</p> <p>Over nearly level land.</p>
20.20	Bladed dirt road, bears NE. and SW.
20.673	The SE 1/16 sec. cor. of sec. 22.
41.346	The point for the center S 1/16 sec. cor. of sec. 22.

SUBDIVISION OF SECTION 23,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the 1/4 sec. cor. of secs. 23 and 26, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408, with a mound of stone, 4 ft. diam., 2 ft. high, N., and a carsonite post firmly set alongside of cor.</p> <p>N. 2°49'00" W., on the N-S center line of sec. 23.</p> <p>Ascend rocky hills.</p>
38.812	<p>Point for the center 1/4 sec. cor. of sec. 23, at intersection with the E-W center line.</p> <p>Point falls on a rocky ledge.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, in drill hole, encased in concrete, with top mkd.</p> <p style="text-align: center;">T17S R50E</p> <p style="text-align: center;">C 1/4 S23</p> <p style="text-align: center;">2006</p> <p>Continue along steep E. slope of rocky hill.</p>
57.448	<p>Point for the center N 1/16 sec. cor. of sec. 23.</p> <p>POINT NOT MONUMENTED.</p>
76.084	<p>The 1/4 sec. cor. of secs. 14 and 23.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 23 and 24, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408, with a mound of stone, 3 ft. diam., 2 ft. high, W. of cor.</p> <p>N. 87°49'30" W., on the E-W center line of sec. 23.</p> <p>Ascend rocky hill.</p>
37.50	Saddle of rocky hill, bears N. and S.; descend.
40.182	The center 1/4 sec. cor. of sec. 23.
59.020	<p>Point for the center W 1/16 sec. cor. of sec. 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, encircled in a collar of stone, 3 ft. diam., with brass cap mkd.</p>

SUBDIVISION OF SECTION 23,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">W 1/16 C — C S23</p> <p style="text-align: center;">2006</p>
77.858	<p>The 1/4 sec. cor. of secs. 22 and 23.</p> <hr/> <p>From the center W 1/16 sec. cor. of sec. 23.</p> <p>N. 4°31'30" W., on the N-S center line of the NW1/4 of sec. 23.</p> <p>Along base of W. slope of rocky hill.</p>
18.524	<p>Point for the NW 1/16 sec. cor. of sec. 23, at intersection with the E-W center line of the NW1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S23</p> <p style="text-align: center;">2006</p>
37.048	<p>The point for the W 1/16 sec. cor. of secs. 14 and 23.</p> <hr/> <p>From the point for the center N 1/16 sec. cor. of sec. 23.</p> <p>N. 88°19'10" W., on the E-W center line of the NW1/4 of sec. 23.</p> <p>Ascend steep, rocky E. slope.</p>
6.50	Top of rocky hill; descend.
19.377	The NW 1/16 sec. cor. of sec. 23.
38.754	The N 1/16 sec. cor. of secs. 22 and 23.
	<p style="text-align: center;">SUBDIVISION OF SECTION 26, T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 26 and 35.</p> <p>N. 0°34'10" E., on the N-S center line of sec. 26.</p> <p>Over gently rolling land.</p>
40.085	<p>The center 1/4 sec. cor. of sec. 26, determined by Mark Chilton, Nevada Professional Engineer and Land Surveyor No. 1404, monumented with an iron pipe, 1 1/2 ins. diam., firmly set in a collar of stone, with brass cap mkd. T17S R50E C 1/4 S26 1973 CHILTON ENGINEERING ELKO NEVADA RLS 1404, as recorded in Nye County, Nevada, Record of Survey No. 37466. This monument is locally recognized as the position of the corner point, and is accepted as a careful and faithful determination of the position of the corner.</p> <hr/>

SUBDIVISION OF SECTION 26,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°33'30" E., beginning new measurement.
40.550	The 1/4 sec. cor. of secs. 23 and 26.
	<hr/> <p>From the 1/4 sec. cor. of secs. 25 and 26, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408, with a mound of stone, 3 ft. diam., 2 ft. high, W. of cor.</p> <p>N. 89°35'20" W., on the E-W center line of sec. 26.</p> <p>Over mountainous land.</p>
23.00	Enter rolling land.
40.286	The center 1/4 sec. cor. of sec. 26.
	<hr/> <p>N. 89°35'50" W., beginning new measurement.</p>
39.377	The 1/4 sec. cor. of secs. 26 and 27, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408, with a mound of stone, 2 ft. diam., 1 ft. high, W. of cor.
	<hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 28, T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 28 and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set flush with the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408, with a steel fence post set alongside.</p> <p>N. 0°25'20" E., on the N-S center line of sec. 28.</p> <p>Over rolling land.</p>
15.10	Bladed dirt road, bears N. and S.
39.912	The center 1/4 sec. cor. of sec. 28, determined by Wallace T. Boundy, Nevada Professional Land Surveyor No. 2518, monumented with a rebar, 5/8 in. diam., 12 ins. long, firmly set, projecting 2 ins. above the ground, with plastic cap mkd. BOUNDY RLS 2518, as recorded in Nye County, Nevada, Record of Survey No. 292624. This monument is locally recognized as the position of the corner point, and is accepted as a careful and faithful determination of the position of the corner.

SUBDIVISION OF SECTION 28,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T17S R50E</p> <p style="text-align: center;">C 1/4 S28</p> <p style="text-align: center;">2007</p> <p>Insert the rebar inside the stainless steel post, and set a steel boundary post, 8 ft. long, alongside the stainless steel post.</p> <hr/> <p>N. 0°24'50" E., beginning new measurement.</p>
39.902	<p>The 1/4 sec. cor. of secs. 21 and 28.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 27 and 28, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408.</p> <p>S. 89°41'20" W., on the E-W center line of sec. 28.</p> <p>Over rolling land.</p>
20.069	<p>The center E 1/16 sec. cor. of sec. 28, determined by Wallace T. Boundy, Nevada Professional Land Surveyor No. 2518, monumented with a rebar, 5/8 in. diam., 12 ins. long, firmly set, projecting 1 in. above the ground, with plastic cap mkd. BOUNDY RLS 2518, as recorded in Nye County, Nevada, Record of Survey No. 292624. This monument is locally recognized as the position of the corner point, and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">E 1/16 C $\frac{\quad}{\quad}$ C S28</p> <p style="text-align: center;">2007</p> <p>Insert the rebar inside the stainless steel post, and set a steel boundary post, 8 ft. long, alongside the stainless steel post.</p> <hr/> <p>S. 89°41'30" W., beginning new measurement.</p>
20.076	<p>The center 1/4 sec. cor. of sec. 28.</p> <hr/>

SUBDIVISION OF SECTION 28,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	S. 89°44'30" W., beginning new measurement.
0.50	Bladed dirt road, bears N. and S.
40.178	The 1/4 sec. cor. of secs. 28 and 29.
	<hr/> <p>From the center E 1/16 sec. cor. of sec. 28.</p> <p>N. 0°30'30" E., on the N-S center line of the NE1/4 of sec. 28.</p> <p>Over rolling land.</p>
40.028	The E 1/16 sec. cor. of secs. 21 and 28.
	<hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 29, T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 29 and 32.</p> <p>N. 0°52'00" E., on the N-S center line of sec. 29.</p> <p>Over gently rolling land.</p>
19.846	<p>The center S 1/16 sec. cor. of sec. 29, determined by person(s) unknown, monumented with a rebar, 1/2 in. diam., 20 ins. long, firmly set, projecting 1 in. above the ground. This monument is locally recognized as the position of the corner point, and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>C</p> <p>S 1/16 S29</p> <p>C</p> <p>2007</p> </div> <p>Insert the rebar inside the stainless steel post, and set a steel boundary post, 8 ft. long, alongside the stainless steel post.</p> <hr/> <p>N. 0°51'30" E., beginning new measurement.</p>
19.850	<p>Point for the center 1/4 sec. cor. of sec. 29, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

SUBDIVISION OF SECTION 29,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T17S R50E
	C 1/4 S29
	2007
59.534	The 1/4 sec. cor. of secs. 20 and 29.
	<hr/> <p>From the 1/4 sec. cor. of secs. 28 and 29.</p> <p>N. 89°38'20" W., on the E-W center line of sec. 29.</p> <p>Over nearly level land.</p>
20.356	Point for the center E 1/16 sec. cor. of sec. 29.
	POINT NOT MONUMENTED.
40.712	The center 1/4 sec. cor. of sec. 29.
81.332	The 1/4 sec. cor. of secs. 29 and 30.
	<hr/> <p>From the E 1/16 sec. cor. of secs. 29 and 32.</p> <p>N. 0°31'30" E., on the N-S center line of the SE1/4 of sec. 29.</p> <p>Over nearly level land.</p>
19.850	<p>The SE 1/16 sec. cor. of sec. 29, determined by person(s) unknown, monumented with a rebar, 1/2 in. diam., 20 ins. long, firmly set, projecting 2 ins. above the ground. This monument is locally recognized as the position of the corner point, and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S29</p> <p style="text-align: center;">2007</p> <p>Bury the rebar alongside the stainless steel post, and set a carsonite post alongside the stainless steel post.</p> <hr/> <p>N. 0°30'10" E., beginning new measurement.</p>
19.852	<p>The point for the center E 1/16 sec. cor. of sec. 29.</p> <hr/> <p>From the point for the S 1/16 sec. cor. of secs. 28 and 29.</p> <p>N. 89°37'40" W., on the E-W center line of the SE1/4 of sec. 29.</p>

SUBDIVISION OF SECTION 29,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Over nearly level land.
20.469	The SE 1/16 sec. cor. of sec. 29. <hr/>
	N. 89°38'40" W., beginning new measurement.
20.479	The center S 1/16 sec. cor. of sec. 29. <hr/>
	SUBDIVISION OF SECTION 30, T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA <hr/>
	From the 1/4 sec. cor. of secs. 30 and 31.
	N. 0°18'00" W., on the N-S center line of sec. 30.
	Over gently rolling land.
39.480	Point for the center 1/4 sec. cor. of sec. 30, at intersection with the E-W center line. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins., over a plastic-encased magnet, with brass cap mkd. T17S R50E C 1/4 S30 2007
79.022	The 1/4 sec. cor. of secs. 19 and 30. <hr/>
	From the 1/4 sec. cor. of secs. 29 and 30.
	S. 89°39'30" W., on the E-W center line of sec. 30.
	Over nearly level land.
21.104	Point for the center E 1/16 sec. cor. of sec. 30. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. E 1/16 C $\frac{\quad}{\quad}$ C S30 2007
	Cor. is located 4 ft. W. of fence, bears N. and S.
42.208	The center 1/4 sec. cor. of sec. 30.

SUBDIVISION OF SECTION 30,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
82.814	<p>The 1/4 sec. cor. of secs. 25 and 30, on the W. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the west boundary of T. 17 S., R. 50 E., executed under Group No. 408, with a carsonite post firmly set alongside.</p> <hr/> <p>From the center E 1/16 sec. cor. of sec. 30.</p> <p>N. 0°32'50" E., on the N-S center line of the NE1/4 of sec. 30.</p> <p>Over rolling land.</p>
39.641	<p>The E 1/16 sec. cor. of secs. 19 and 30.</p> <hr/> <p>From the E 1/16 sec. cor. of secs. 30 and 31.</p> <p>N. 0°32'50" E., on the N-S center line of the SE1/4 of sec. 30.</p> <p>Over rolling land.</p>
39.609	<p>The center E 1/16 sec. cor. of sec. 30.</p> <hr/>
	<p style="text-align: center;">SUBDIVISION OF SECTION 32, T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>
39.854	<p>From the 1/4 sec. cor. of secs. 5 and 32, on the S. bdy. of the Tp.</p> <p>N. 0°21'30" E., on the N-S center line of sec. 32.</p> <p>Over nearly level land.</p> <p>Point for the center 1/4 sec. cor. of sec. 32, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T17S R50E</p> <p style="text-align: center;">C 1/4 S32</p> <p style="text-align: center;">2007</p>
79.728	<p>The 1/4 sec. cor. of secs. 29 and 32.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 32 and 33, at the cor. of fences, extending N. and E. This position is locally recognized as the cor., and is accepted as the best available evidence of the position of the original corner.</p>

SUBDIVISION OF SECTION 32,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins., over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T17S R50E 1/4 S32 S33 2007</p> <p>Set a carsonite post alongside of the stainless steel post.</p> <p>N. 89°30'20" W., on the E-W center line of sec. 32.</p> <p>Over nearly level land.</p>
40.668	The center 1/4 sec. cor. of sec. 32.
60.920	<p>Point for the center W 1/16 sec. cor. of sec. 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">W 1/16 C — C S32 2007</p> <p>Set a carsonite post alongside the stainless steel post.</p> <p>Cor. is located in a fence, bearing N. and S. and 1 ft. S. of a steel fence post.</p>
81.172	<p>The 1/4 sec. cor. of secs. 31 and 32, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408.</p> <hr/> <p>From the W 1/16 sec. cor. of secs. 5 and 32, on the S. bdy. of the Tp.</p> <p>N. 0°06'30" E., on the N-S center line of the SW1/4 of sec. 32.</p> <p>Over gently rolling land.</p>
39.794	<p>The center W 1/16 sec. cor. of sec. 32.</p> <hr/> <p>N. 0°00'20" E., on the N-S center line of the NW1/4 of sec. 32.</p> <p>Over gently rolling land.</p>
39.806	<p>The W 1/16 sec. cor. of secs. 29 and 32.</p> <hr/>

SUBDIVISION OF SECTION 35,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the 1/4 sec. cor. of secs. 2 and 35, on the S. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the south boundary of T. 17 S., R. 50 E., executed under Group No. 408, with a carsonite post and a steel fence post firmly set alongside.</p> <p>N. 0°39'50" E., on the N-S center line of sec. 35.</p> <p>Over nearly level land.</p> <p>40.212 Point for the center 1/4 sec. cor. of sec. 35, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T17S R50E</p> <p style="text-align: center;">C 1/4 S35</p> <p style="text-align: center;">2006</p> <p>60.195 Point for the center N 1/16 sec. cor. of sec. 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;"> $\begin{array}{c} C \\ N\ 1/16 \left S35 \\ C \end{array}$ </p> <p style="text-align: center;">2006</p> <p>From this cor., a position determined by the U.S. Fish and Wildlife Service, monumented with a rebar, 5/8 in. diam., firmly set, projecting 8 ins. above the ground, with aluminum cap, 3 ins. diam., mkd. CN 1/16 S35 1991, bears N. 12°35'20" W., 2.845 chs. dist. This position cannot be reconciled with proper procedures, is not harmoniously related to surrounding corners and is not utilized during the course of this survey.</p> <p>80.178 The 1/4 sec. cor. of secs. 26 and 35.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 35 and 36, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 24 ins. above ground, in a mound of stone, 3 ft. diam., to top, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408, with a carsonite post firmly set alongside.</p> <p>S. 89°46'30" W., on the E-W center line of sec. 35.</p>
--------	---

SUBDIVISION OF SECTION 35,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Over nearly level land.
40.418	The center 1/4 sec. cor. of sec. 35.
60.620	Point for the center W 1/16 sec. cor. of sec. 35. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;"> W 1/16 C — C S35 2006 </div> Set a steel boundary post, 8 ft. long, alongside the stainless steel post.
80.822	The 1/4 sec. cor. of secs. 34 and 35. <hr/> From the center W 1/16 sec. cor. of sec. 35. N. 0°49'50" E., on the N-S center line of the NW1/4 of sec. 35. Over nearly level land.
20.020	The NW 1/16 sec. cor. of sec. 35, determined by the U.S. Fish and Wildlife Service, monumented with a rebar, 5/8 in. diam., 20 ins. long, firmly set, projecting 8 ins. above the ground, with aluminum cap mkd. NW 1/16 S35 1991, with a carsonite post and a rusted drill bit firmly set alongside. This monument is locally recognized as the position of the corner point, and is accepted as a careful and faithful determination of the position of the corner. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, encircled in a collar of stone, 3 ft. diam., with brass cap mkd. <div style="text-align: center;"> NW 1/16 S35 2006 </div> Bury the rebar alongside the stainless steel post. <hr/> N. 0°49'50" E., beginning new measurement.
20.020	The point for the W 1/16 sec. cor. of secs. 26 and 35. <hr/> From the center N 1/16 sec. cor. of sec. 35. S. 89°52'20" W., on the E-W center line of the NW1/4 of sec. 35.

SUBDIVISION OF SECTION 35,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Over nearly level land.
20.142	The NW 1/16 sec. cor. of sec. 35. <hr/>
	S. 89°52'20" W., beginning new measurement.
20.142	The point for the N 1/16 sec. cor. of secs. 34 and 35. <hr/>
	SUBDIVISION OF SECTION 36, T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA
	From the 1/4 sec. cor. of secs. 1 and 36, on the S. bdy. of the Tp. N. 0°26'00" W., on the N-S center line of sec. 36. Ascend steep, rocky mountain.
2.683	An iron pipe, 1 in. diam., set by L.M. Bobeau, Nevada Professional Engineer and Land Surveyor No. 675, loosely set in a mound of stone, 2 1/2 ft. diam., with brass cap, 2 ins. diam., mkd. NPS WC RE 675 DEVILS HOLE, as recorded in Nye County, Nevada, Record of Survey No. 49270.
6.458	A witness cor. established by the National Park Service, monumented with an aluminum pipe, 1 in. diam., firmly set, concreted in a mound of stone, 3 ft. diam., with an aluminum tablet, 3 ins. diam., mkd. H4 WC DEVILS HOLE and a wood post, 4 ins. square, 3 ft. high, set alongside, as shown on a Boundary Survey Map of Devils Hole, dated 8/81, on file with the United States Department of the Interior Park Service, Denver Service Center. <hr/>
	N. 0°18'50" W., beginning new measurement. Ascend steep, rocky S. slope.
13.220	True point for the center S 1/16 sec. cor. of sec. 36, determined at record distance from the witness cor. on the N-S center line of sec. 36 and record distance from the witness cor. on the E-W center line of the SE1/14 of sec. 36, as shown on a Boundary Survey Map of Devils Hole, on file with the United States Department of the Interior Park Service, Denver Service Center, falls on ledge rock face, where it is impractical to establish a permanent monument. <hr/>
	N. 0°25'50" W., beginning new measurement. Descend steep, rocky E. slope.
19.669	Point for the center 1/4 sec. cor. of sec. 36, at intersection with the E-W center line.

SUBDIVISION OF SECTION 36,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, over a plastic-encased magnet, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T17S R50E</p> <p style="text-align: center;">C 1/4 S36</p> <p style="text-align: center;">2006</p>
58.927	<p>The 1/4 sec. cor. of secs. 25 and 36, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 24 ins. above ground, in a mound of stone, 6 ft. diam., to top, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 31 and 36, on the E. bdy. of the Tp.</p> <p>N. 87°45'40" W., on the E-W center line of sec. 36.</p> <p>Over rolling land.</p>
20.391	<p>Point for the center E 1/16 sec. cor. of sec. 36.</p> <p>POINT NOT MONUMENTED.</p>
40.782	<p>The center 1/4 sec. cor. of sec. 36.</p>
80.832	<p>The 1/4 sec. cor. of secs. 35 and 36.</p> <hr/> <p>From the E 1/16 sec. cor. of secs. 1 and 36, on the S. bdy. of the Tp.</p> <p>N. 1°29'10" W., on the N-S center line of the SE1/4 of sec. 36.</p>
9.50	<p>Improved gravel road, NNE. and SSW.</p>
19.558	<p>The SE 1/16 sec. cor. of sec. 36, determined by the National Park Service, monumented with an aluminum pipe, 1 in. diam., firmly set in concrete, projecting 2 ins. above the ground, with aluminum cap, 3 ins. diam., mkd. NE CORNER DEVILS HOLE, as shown on Boundary Survey Map, dated 8/81, on file with the United States Department of the Interior Park Service, Denver Service Center, and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S36</p> <p style="text-align: center;">2007</p>

SUBDIVISION OF SECTION 36,
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Bury the iron pipe and concrete alongside the stainless steel post.</p> <p>From this cor., a position determined by L.M. Bobeau, Nevada Professional Engineer and Land Surveyor No. 675, monumented with an iron pipe, 1 in. diam., firmly set flush with the ground, encircled in a collar of stone, with brass cap, 2 ins. diam., mkd. NPS RE675 DEVILS HOLE, as recorded in Nye County, Nevada, Record of Survey No. 49270, bears N. 70°40' E., 11.9 lks. dist. This position cannot be reconciled with proper procedures, is not harmoniously related to surrounding corners and is not utilized during the course of this survey.</p> <hr/> <p>N. 1°27'50" W., beginning new measurement.</p>
19.555	<p>The point for the center E 1/16 sec. cor. of sec. 36.</p> <hr/> <p>From the true point for the S 1/16 sec. cor. of secs. 31 and 36, on the E. bdy. of the Tp.</p> <p>N. 88°08'10" W., on the E-W center line of the SE1/4 of sec. 36. Over rolling land.</p>
20.729	<p>The SE 1/16 sec. cor. of sec. 36.</p> <hr/> <p>N. 88°07'10" W., beginning new measurement.</p>
7.941	<p>A position established by L.M. Bobeau, Nevada Professional Engineer and Land Surveyor No. 675, monumented with an iron pipe, 1 in. diam., firmly set flush with the ground, in a mound of stone, 3 ft. diam., 1/2 ft. high, with a wood post, 4 ins. square, set alongside, with brass cap, 2 ins. diam., mkd. NPS WC RE 675 DEVILS HOLE, bears North, 0.051 chs. dist. This position cannot be reconciled with proper procedures, is not harmoniously related to surrounding corners and is not utilized during the course of this survey.</p> <p>Ascend steep, rocky E. slope.</p>
20.097	<p>A witness cor. for the center S 1/16 sec. cor. of sec. 36, established by the National Park Service, monumented with an aluminum pipe, 1 in. diam., firmly set in concrete, with aluminum cap, 3 ins. diam., mkd. H2 WC DEVILS HOLE, as shown on Boundary Survey Map, dated 8/81, on file with the United States Department of the Interior Park Service, Denver Service Center. This position is accepted as a careful and faithful establishment of the position of the witness corner.</p> <hr/> <p>N. 88°19'20" W., beginning new measurement.</p>
0.643	<p>The true point for the center S 1/16 sec. cor. of sec. 36.</p> <hr/>

T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	GENERAL DESCRIPTION
	<p>The lands dependently resurveyed and subdivided within Township 17 South, Range 50 East are part of the Ash Meadows National Wildlife Refuge located in the Amargosa Desert, and ranges from about 2,100 to 3,100 ft. above sea level. The terrain is nearly level to low mountainous. The soil is sandy clay loam in the lower elevations to rocky in the higher elevations and vegetation consists of scattered mesquite and native grass.</p> <p>Access to the area is provided by numerous improved roads, unimproved roads, and trail roads. Carson Slough drains the area from north to south leaving in section 32. There are numerous springs in the area, and the Death Valley National Monument is located in section 36.</p> <hr/>

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Lance A. Barney	Cadastral Surveyor
Michelle E. Martin	Supervisory Range Technician
Derrick J. Rader	Supervisory Range Technician
David R. Rodriguez	Survey Aid

CERTIFICATE OF SURVEY

WE, Douglas A. Potts, Cadastral Surveyor and Clay W. Morrow, Surveying Technician, HEREBY CERTIFY upon honor, that in pursuance of Special Instructions bearing the date of the 2nd day of February, 2006, We have dependently resurveyed portions of the south and east boundaries and a portion of the subdivisional lines, and subdivided certain sections, Township 17 South, Range 50 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

August 2, 2007

(Date)

Douglas A. Potts

/ For Douglas A. Potts
(Cadastral Surveyor)

August 1, 2007

(Date)

Clay W. Morrow

(Surveying Technician)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of the dependent resurvey of portions of the south and east boundaries and a portion of the subdivisional lines, and the subdivision of certain sections, Township 17 South, Range 50 East, Mount Diablo Meridian, Nevada, executed by Douglas A. Potts, Cadastral Surveyor, and Clay W. Morrow, Surveying Technician, having been critically examined and found correct, are hereby approved.

August 2, 2007

(Date)

Douglas A. Potts

(Chief Cadastral Surveyor, Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 17 S., R. 50 E., M.D.M., Nevada, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor, Nevada)~~