

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF

A PORTION OF THE SOUTH BOUNDARY, TOWNSHIP 17 SOUTH, RANGE 49 EAST

AND

THE DEPENDENT RESURVEY OF

A PORTION OF THE SUBDIVISIONAL LINES,

THE SUBDIVISION OF SECTION 1,

AND

METES-AND-BOUNDS SURVEYS IN SECTION 1,

TOWNSHIP 18 SOUTH, RANGE 49 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATE OF NEVADA

EXECUTED BY

Kelly R. Totten, Cadastral Surveyor

Under Special Instructions dated April 6, 2022,

and approved April 6, 2022,

which provided for the surveys included under Group No. 1000,

and Assignment Instructions dated April 5, 2022.

Survey commenced June 2, 2022

Survey completed April 27, 2023

INDEX DIAGRAM

TOWNSHIP 18 SOUTH, RANGE 49 EAST, MOUNT DIABLO MERIDIAN, NEVADA

6	5	4	3	2	4 2 1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

SUBDIVISION OF SECTION 1..... pp 6 - 10
 METES-AND-BOUNDS SURVEYS IN SECTION 1..... pp 10 - 12

TOWNSHIP 18 SOUTH, RANGE 49 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The following field notes are those of the dependent resurvey of a portion of the south boundary, Township 17 South, Range 49 East, and the dependent resurvey of a portion of the subdivisional lines, the subdivision of section 1, and metes-and-bounds surveys in section 1, Township 18 South, Range 49 East, Mount Diablo Meridian, Nevada.

1873 - The Eastern Boundary of the State of California (former oblique boundary line between California and Nevada) was surveyed by A.W. Von Schmidt, U.S. Astronomer and Surveyor, under contract dated July 1872.

1881-1882 - The boundary between California and Nevada (former oblique boundary line between California and Nevada) was retraced from mile post 464 to mile post 499 and the exterior lines of T. 17 S., R. 49 E. and T. 18 S., R. 50 E. were surveyed by E.A. Carter, U.S. Deputy Surveyor under contract No. 128.

1893-1899 - The Oblique Boundary Line between California and Nevada (present oblique boundary line between California and Nevada) was surveyed by the U.S. Coast and Geodetic Survey.

1926 - The corner of Tps. 17 and 18 S., Rs. 49 and 50 E. was remonumented by E.H. Kimmell, U.S. Surveyor and W. Mussetter, United States Coast and Geodetic Survey in 1926.

1933 - The portion of the Von Schmidt California - Nevada Boundary (former oblique boundary between California and Nevada) between mile post 467 and mile post 484 was dependently resurveyed by R.C. Yundt, U.S. Surveyor under California Group No. 259.

1933-1934 - The U.S. Coast and Geodetic Survey Boundary Line between California and Nevada (present oblique boundary line between California and Nevada) from Monument 98 1/2 to Monument 104 was dependently resurveyed by A. Nelson, U.S. Cadastral Engineer and R.F. Wilson, U.S. Transitman under California Group No. 259.

1933-1934 - The South Boundary of T. 17 S., R. 49 E., and the West Boundary of T. 18 S., R. 50 E., was resurveyed and surveyed by R.C. Yundt, U.S. Surveyor and R.F. Wilson, U.S. Transitman under California Group No. 259..

1934 - The subdivisional lines of Fractional T. 18 S., R. 49 E. were surveyed and resurveyed by R.F. Wilson, U.S. Transitman under California Group No. 259.

Before restoring the corners, the lines of the original surveys were retraced and a diligent search made for any evidence of the position of the original corners and other calls of the original field note record.

In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 2009, and the Special Instructions for Group No. 1000, dated April 6, 2022.

TOWNSHIP 18 SOUTH, RANGE 49 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

Measurements were made with Trimble R-10 Global Navigation Satellite System (GNSS) receivers using the real-time kinematic (RTK) method and refer to the true meridian based on geodetic methods. The mean bearings of the lines and horizontal equivalents of ground distances only are entered in the field notes.

The NAD 83(2011)(EPOCH:2010.0000) geographic positions of the following corners were determined from Global Positioning System (GPS) static observations processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) DJ3669 NVCA CARLTON SQUARE 2 CORS ARP, DN7449 P619 SILURIANHICS2008 CORS ARP, and DR3059 NVAG NVAG AMARGOSAVALL CORS ARP, and carried forward by RTK observations.

The 1/4 section corner of sections 1 and 12 is as follows:

Latitude: 36°24'36.612" N. Longitude: 116°24'03.982" W.

The corner of sections 35 and 36 on the S. bdy. of T. 17 S., R. 49 E., is as follows:

Latitude: 36°25'31.751" N. Longitude: 116°24'39.516" W.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 17 S., R. 49 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of a Portion of the Survey Executed by E.A. Carter in 1881 and a Portion of the Resurvey and Survey executed by R.C. Yundt, U.S. Surveyor, and R.F. Wilson, U.S. Transitman, in 1933-34

Beginning at the cor. of Tps. 17 and 18 S., Rs. 49 and 50 E., determined by person(s) unknown, monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of an asphalt road. This position is harmoniously related to surrounding corners, has been adopted by numerous professional land surveyors, and is accepted as the best available evidence of the position of the original corner.

from which

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 23 ins. in the ground, over a plastic encased magnet, for a reference monument, bears N. 47°24'50" E., 200.0 lks. dist., with brass cap mkd. RM T17S R50E S31 132.0 FT TO COR 2022 and an arrow pointing to the corner.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 17 S., R. 49 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 23 ins. in the ground, over a plastic encased magnet, for a reference monument, bears S. 41°10'20" E., 200.0 lks. dist., with brass cap mkd. RM T18S R50E S6 132.0 FT TO COR 2022 and an arrow pointing to the corner.</p> <p>Cor. is located in "Spring Meadows Road", bears E. and W. N. 89°43'40" W., on the S. bdy. of sec. 36.</p> <p>Along asphalt road.</p>
7.15	"Spring Meadows Road" curves to NW. Depart asphalt road and continue on graded dirt road.
20.258	From this point, a position determined by person(s) unknown, monumented with a nail, 5/8 in. diam. head, firmly set, flush with the surface of a graded dirt road, no record found, bears SOUTH, 0.017 chs. dist., not utilized in the course of this survey.
20.263	From this point, a position determined by person(s) unknown, monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of a graded dirt road, as recorded in Nye County, Nevada, Record of Survey No. 671481 bears SOUTH, 0.004 chs. dist., not utilized in the course of this survey.
40.534	<p>Point for the 1/4 sec. cor. of secs. 1 and 36, determined by irregular boundary adjustment; there is no remaining evidence of the 1933-34 corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T17S R49E</p> <p>S36</p> <p>1/4 ———</p> <p>S 1</p> <p>T18S</p> <p>2022</p> </div> <p>from which</p> <p>A PK nail, 2 ins. long, 3/8 ins. diam., set flush with the surface of a power pole, facing the corner, for a reference monument, bears S. 2°29'00" E., 17.7 lks. dist., with underlying aluminum washer, 2 ins. diam., mkd. BLM CADASTRAL SURVEY RM 2022.</p> <p>A PK nail, 2 ins. long, 3/8 ins. diam., set flush with the surface of a power pole, facing the corner, for a reference monument, bears S. 88°00'50" W., 407.3 lks. dist., with underlying aluminum washer, 2 ins. diam., mkd. BLM CADASTRAL SURVEY RM 2022.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 17 S., R. 49 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 89°59'40" W., beginning new measurement.
19.905	Point for the W 1/16 sec. cor. of sec. 1 only, T. 18 S., R. 49 E.
	POINT NOT MONUMENTED
39.810	The closing cor. of secs. 1 and 2, T. 18 S., R. 49 E., hereinafter described.
43.853	The cor. of secs. 35 and 36, T. 17 S., R. 49 E., monumented with an iron post, 2 ins. diam, firmly set, projecting 7 ins. above the ground, with brass cap mkd. as described in the field notes of the resurvey and survey of the south boundary of fractional T. 17 S., R. 49 E., executed under California Group No. 259.
	From this cor., an iron pipe, 1 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, bears N. 89°59'00" W., 0.956 chs. dist.
<hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 18 S., R. 49 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of a Portion of the Survey and Resurvey executed by R.F. Wilson, U.S. Transitman, in 1934</p> <hr/> <p>From the 1/4 sec. cor. of secs. 1 and 2, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. as described in the field notes of the survey and resurvey of subdivisional lines of fractional T. 18 S., R. 49 E., executed under California Group No. 259, with a wooden post, 3 ins. square, firmly set, projecting 36 ins. above the ground, south of the cor. Remark the brass cap to read as follows:</p> <p style="text-align: center;">T18S R49E 1/4 S 2 S 1</p> <p style="text-align: center;">2023 1934</p> <p>N. 0°01'10" E., bet. secs. 1 and 2.</p>	
4.996	Point for the S-S-N 1/256 sec. cor. of secs. 1 and 2, occupied by a spike, 1/4 in. diam, with 5/8 in. diam. head, 6 ins. long, firmly set 1 in. below the surface of the ground, as recorded in Nye County, Nevada, as Mining Map No. 25145.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 18 S., R. 49 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>S-S-N 1/256 S 2 S 1</p> <p>2023</p> <p>Insert spike inside the stainless steel post.</p>
9.992	<p>Point for the S-N 1/64 sec. cor. of secs. 1 and 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <p>S-N 1/64 S 2 S 1</p> <p>2023</p>
14.988	<p>Point for the N-S-N 1/256 sec. cor. of secs. 1 and 2, occupied by an iron pipe of unknown origin, 2 ins. diam., 24 ins. long, firmly set, projecting 4 ins. above the ground.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <p>N-S-N 1/256 S 2 S 1</p> <p>2023</p>
	<p>Insert iron pipe inside the stainless steel post.</p> <p>From this cor., a rebar, 1/2 in. diam., firmly set, projecting 7 ins. above the ground, bears S. 16°54'40" W., 0.020 chs. dist.</p>
19.984	<p>Point for the N 1/16 sec. cor. of secs. 1 and 2.</p> <p>POINT NOT MONUMENTED</p>
26.65	<p>Record distance for the 1934 closing cor. on the Von Schmidt California-Nevada Boundary; there is no remaining evidence of the 1934 corner.</p>
31.10	<p>Intersect southerly edge of graded dirt road, bears N. and SW.; continue along graded dirt road.</p>
37.55	<p>Steel gate, bears E. and W.</p>
40.55	<p>Intersect northerly edge of graded dirt road, bears NE. and S.; depart graded dirt road.</p>
42.70	<p>Power line, bears E. and W.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 18 S., R. 49 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS
44.504

Intersect the south boundary of T. 17 S., R. 49 E.

The closing cor. of secs. 1 and 2, T. 18 S., R. 49 E., monumented with an iron post, 2 ins. diam., firmly set, projecting 9 ins. above the ground, with exposed portion bent flush with the ground, with brass cap mkd. as described in the field notes of the survey and resurvey of subdivisional lines of fractional T. 18 S., R. 49 E., executed under California Group No. 259, with a rebar 1/2 in. diam., 12 ins. long, firmly set, projecting 7 ins. above the ground, alongside.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.

T17S R49E
S36

S 2 | S 1
T18S R49E
CC

2022

Insert rebar inside the stainless steel post and bury the iron post alongside.

From this cor., the cor. of secs. 35 and 36, T. 17 S., R. 49 E., hereinbefore described, bears N. 89°59'40" W., 4.043 chs. dist.

SUBDIVISION OF SECTION 1,
T. 18 S., R. 49 E., MOUNT DIABLO MERIDIAN, NEVADA

From the 1/4 sec. cor. of secs. 1 and 12, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd.

S 1
1/ ———
S12

1934

Added marks to the cap to read

T18S R49E
S 1
1/4 ———
S12

2023
1934

SUBDIVISION OF SECTION 1,
T. 18 S., R. 49 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°06'30" W., on the N-S center line of sec. 1.
21.107	From this point, a rebar, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, bears EAST, 0.523 chs. dist. This position is not utilized in the course of this survey.
41.100	<p>The center 1/4 sec. cor. of sec. 1, determined by person(s) unknown, monumented with a rebar, 5/8 in. diam., firmly set, projecting 3 1/2 ins. above the ground, with an iron pipe, 2 ins. diam., 24 ins. long, lying loose alongside, with brass cap mkd. LS 3654 CENTER SEC 1, as recorded in Nye County, Nevada, Record of Survey No. 671481. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T18S R49E C 1/4 S 1</p> <p style="text-align: center;">2022</p> <p>Insert the iron pipe inside the stainless steel post and bury the rebar alongside.</p> <hr/> <p>N. 0°05'50" W., beginning new measurement.</p>
10.848	<p>Point for the C-S-N 1/64 sec. cor. of sec. 1.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">S 1 C-S-N 1/64</p> <p style="text-align: center;">2022</p>
21.696	<p>Point for the C-N 1/16 sec. cor. of sec. 1.</p> <p>POINT NOT MONUMENTED</p>
43.20	Power line, bears E. and W.
43.392	<p>The 1/4 sec. cor. of secs. 1 and 36, on the S. bdy. of sec. 36, T. 17 S., R. 49 E.</p> <hr/>

SUBDIVISION OF SECTION 1,
T. 18 S., R. 49 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From the 1/4 sec. cor. of secs. 1 and 6, on the E. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. as described in the field notes of the survey and resurvey of the west boundary of fractional T. 18 S., R. 50 E., executed under California Group No. 259. Remark the brass cap to read as follows:</p> <p style="text-align: center;">T18S R49E R50E 1/4 S 1 S 6</p> <p style="text-align: center;">2023 1934</p>
10.023	<p>S. 88°24'40" W., on the E-W center line of sec. 1.</p> <p>The C-E-E 1/64 sec. cor. of sec. 1, determined by person(s) unknown, monumented with a rebar, 5/8 in. diam., 12 ins. long, firmly set, projecting 4 ins. above the ground, no record found. This monument is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">E-E 1/64 C ——— C S 1</p> <p style="text-align: center;">2023</p> <p>Insert rebar inside the stainless steel post.</p> <p>Cor. is located 1.5 lks. S. of a barbed wire fence, bears E. and W.</p> <p>From this cor., a rebar, 5/8 in. diam., firmly set, projecting 9 ins. above the ground, bears N. 88°05'10" E., 0.453 chs. dist.</p> <p>From this same cor., a rebar, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, bears S. 88°34'30" W., 0.454 chs. dist.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S.88°24'40" W., beginning new measurement.</p>
10.023	<p>The C-E 1/16 sec. cor. of sec. 1, determined by person(s) unknown, monumented with a rebar, 5/8 in. diam., firmly set, 2 ins. below the surface of the ground, as recorded in Nye County, Nevada, Record of Survey No. 671481. This monument is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p>




SUBDIVISION OF SECTION 1,
T. 18 S., R. 49 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">E 1/16 C ——— C S 1 2023</p> <p>Insert rebar inside the stainless steel post.</p> <p>Cor. is located 1.5 lks. S. of the corner of a barbed wire fence, with fence extending N. and E.</p> <hr/> <p>S. 88°24'40" W., beginning new measurement.</p>
20.046	<p>The center 1/4 sec. cor. of sec. 1.</p> <hr/> <p>S. 88°24'20" W., beginning new measurement.</p>
18.186	Point for Angle Point No. 1, of the metes-and-bounds surveys in sec. 1, hereinafter described.
19.959	<p>Point for the C-W 1/16 sec. cor. of sec. 1.</p> <p>POINT NOT MOUNUMENTED</p> <p>From this point a rebar, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, set by person(s) unknown, bears S. 88°07'20" W., 0.035 chs. dist., and is not utilized in the course of this survey.</p>
27.80	Post and cable fence, bears NW. and SE.
30.293	Point for Angle Point No. 3, of the metes-and-bounds surveys in sec. 1, hereinafter described.
39.918	<p>The 1/4 sec. cor. of secs. 1 and 2.</p> <hr/> <p>From the point for the C-W 1/16 sec. cor. of sec. 1.</p> <p>N. 0°02'10" W. on the N-S center line of the NW1/4 of sec. 1.</p>
1.10	Barbed wire fence, bears E. and W. Enter disturbed area.
10.420	<p>Point for the C-S-NW 1/64 sec. cor. of sec. 1.</p> <p>POINT NOT MONUMENTED</p>
11.80	Barbed wire fence, bears E. and W. Leave disturbed area.
20.840	<p>Point for the NW 1/16 sec. cor. of sec. 1 at intersection with the E-W center line of the NW1/4.</p> <p>POINT NOT MONUMENTED</p>


SUBDIVISION OF SECTION 1,
T. 18 S., R. 49 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
41.35	Power line, bears E. and W.
43.948	The point for the W 1/16 sec. cor. of sec. 1 only, on the S. bdy. of sec. 36, T. 17 S., R. 49 E.
	From the point for the C-N 1/16 sec. cor. of sec. 1. S. 85°57'00" W. on the E-W center line of the NW1/4 of sec. 1
19.977	The point for the NW 1/16 sec. cor. of sec. 1.
36.60	Westerly edge of tailings dam. Descend 20 ft.
39.956	The point for the N 1/16 sec. cor. of secs. 1 and 2.
	From the point for the C-S-N 1/64 sec. cor. of sec. 1. S. 87°10'40" W. on the E-W center line of the SE1/4NW1/4 of sec. 1.
17.581	Point for Angle Point No. 2, of the metes-and-bounds surveys in sec. 1, hereinafter described.
17.734	Barbed wire fence, bears N. and S. Enter disturbed area.
19.963	The point for the C-S-NW 1/64 sec. cor. of sec. 1.
	From the point for the C-S-NW 1/64 sec. cor. of sec. 1. S. 87°10'40" W. on the E-W center line of the SW1/4NW1/4 of sec. 1.
9.184	Barbed wire fence, bears N. and S. Leave disturbed area.
9.337	Point for Angle Point No. 4, of the metes-and-bounds surveys in sec. 1, hereinafter described.
19.965	The S-N 1/64 sec. cor. of secs. 1 and 2.
METES-AND-BOUNDS SURVEYS IN SECTION 1, T. 18 S., R. 49 E., MOUNT DIABLO MERIDIAN, NEVADA	
MEMORANDUM	
The following metes-and-bounds surveys were executed to identify certain lands for direct sale.	
From the point for Angle Point No. 1 on the E-W center line of sec. 1. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.	

METES-AND-BOUNDS SURVEYS IN SECTION 1
T. 18 S., R. 49 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
10.507	<p style="text-align: center;">T18S R49E S1 AP 1</p>  <p style="text-align: center;">2022</p> <p>N. 3°16'30" E., in sec. 1.</p> <p>The point for Angle Point No. 2 on the E-W center line of the SE1/4NW1/4 sec. 1.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T18S R49E S1 AP 2</p>  <p style="text-align: center;">2022</p>
10.300	<p>From the point for Angle Point No. 3 on the E-W center line of sec. 1.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T18S R49E S1 AP 3</p>  <p style="text-align: center;">2022</p> <p>N. 5°33'30" E., in sec. 1.</p> <p>The point for Angle Point No. 4 on the E-W center line of the SW1/4NW1/4 sec. 1.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p>

METES-AND-BOUNDS SURVEYS IN SECTION 1
T. 18 S., R. 49 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div data-bbox="873 273 1026 509"><p>T18S R49E S1 AP 4 SN—SN  2022</p></div> <div data-bbox="435 567 1464 857"><hr/><p>GENERAL DESCRIPTION</p><p>The land contained in this survey is level or nearly level; general drainage is westerly, and the average elevation is 2,100 ft. above sea level. The vegetation in the undisturbed areas is sagebrush and creosote. The area has a history of mining, but no active mining activity was observed in the course of the survey.</p><p>Access is provided by numerous paved and dirt roads by way of Nevada State Route 373.</p><hr/></div>
--------	---

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Carlos Gil Mendoza


Cadastral Surveyor

CERTIFICATE OF SURVEY

I, Kelly R. Totten, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 6th day of April, 2022, I have dependently resurveyed a portion of the south boundary, Township 17 South, Range 49 East, and dependently resurveyed a portion of the subdivisional lines, subdivided section 1, and performed the metes-and-bounds surveys in section 1, Township 18 South, Range 49 East, Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

JUN 20 2023

(Date)


(Cadastral Surveyor)


CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of the dependent resurvey of a portion of the south boundary, Township 17 South, Range 49 East, and the dependent resurvey of a portion of the subdivisional lines, the subdivision of section 1 and metes-and-bounds surveys in section 1, Township 18 South, Range 49 East, Mount Diablo Meridian, Nevada, executed by Kelly R. Totten, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

JUN 29 2023

(Date)


(Chief Cadastral Surveyor for Nevada)~~CERTIFICATE OF TRANSCRIPT~~

I CERTIFY that the foregoing transcript of the field notes of the above described surveys in Townships 17 and 18 South, Range 49 East, Mount Diablo Meridian, Nevada, is a true copy of the original field notes.

~~(Date)~~~~(Chief Cadastral Surveyor for Nevada)~~