

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL
FIELD NOTES

OF THE
DEPENDENT RESURVEY
OF

A PORTION OF THE WEST BOUNDARY
AND A PORTION OF THE SUBDIVISIONAL LINES,
THE SUBDIVISION OF CERTAIN SECTIONS,
A METES-AND-BOUNDS SURVEY OF THE
EASTERLY RIGHT-OF-WAY LINE OF U.S. HIGHWAY NO. 95,
THROUGH SECTIONS 6 AND 7, AND A PORTION OF SECTION 8,
AND
A METES-AND-BOUNDS SURVEY OF
THE RED ROCK CANYON NATIONAL CONSERVATION AREA BOUNDARY,
THROUGH A PORTION OF SECTION 7, AND THROUGH SECTIONS 8, 16, 17 AND 21,
TOWNSHIP 18 SOUTH, RANGE 59 EAST,
OF THE MOUNT DIABLO MERIDIAN,
IN THE STATE OF NEVADA.

EXECUTED BY

Brandon G. Courtright, Cadastral Surveyor

Under Special Instructions dated May 6, 2015,
and approved May 6, 2015,
and Supplemental Special Instructions dated July 10, 2015,
and approved July 10, 2015,
which provided for the surveys included under Group No. 945,
and Assignment Instructions dated May 6, 2015, and July 13, 2015.

Survey commenced June 6, 2015

Survey completed June 3, 2020

INDEX DIAGRAM

TOWNSHIP 18 SOUTH, RANGE 59 EAST, MOUNT DIABLO MERIDIAN, NEVADA

4 6 27	28 5 27	22 4 21	15 3	2	1
4 7 25	26 8 24	20 9 19	14 10 13	11 11	12
3 18	24 17 23	18 16 17	12 15 12	9 14 8	7 13 7
2 19	20	17 21 16	11 22	23	6 24 5
30	29	28	27	26	25
31	32	33	34	35	36

Subdivision of Section 4	pp 28 - 32
Subdivision of Section 7	pp 32 - 33
Subdivision of Section 8	pp 33 - 37
Subdivision of Section 9	pp 38 - 42
Subdivision of Section 14	pp 42 - 45
Subdivision of Section 15	pp 45 - 51
Subdivision of Section 23	pp 51 - 53
Subdivision of Section 24	pp 53 - 58
Metes-and-bounds Survey of the Easterly Right-of-Way line of U.S. Highway No. 95	pp 58 - 63
Metes-and-bounds Survey of the Red Rock Canyon National Conservation Area boundary	pp 63 - 66

TOWNSHIP 18 SOUTH, RANGE 59 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The following field notes are those of the dependent resurvey of a portion of the west boundary and a portion of the subdivisional lines, the subdivision of certain sections, a metes-and-bounds survey of the easterly right-of-way line of U.S. Highway No. 95, through sections 6 and 7, and a portion of section 8, and a metes-and-bounds survey of the Red Rock Canyon National Conservation Area boundary, through a portion of section 7 and through sections 8, 16, 17 and 21, Township 18 South, Range 59 East, Mount Diablo Meridian, Nevada.

The south boundary was surveyed by U.S. Deputy Surveyors J.M. Brunt and W.H. Proctor in 1881 under Contract No. 127. The north, east and west boundaries, and the subdivisional lines were surveyed by U.S. Deputy Surveyor E.A. Carter in 1881 under Contract No. 128. A portion of the south boundary was dependently resurveyed by Cartographic Survey Aid P.K. Russell in 1956 under Group No. 362. Portions of the south and east boundaries, and a portion of the subdivisional lines were dependently resurveyed by Cadastral Surveyor J.A. Mack in 1984 under Group No. 612. A portion of the south boundary was dependently resurveyed by Cadastral Surveyor R.E. Williams in 1991 under Group No. 698. Portions of the east and north boundaries were dependently resurveyed by Cadastral Surveyors S.E. Dagitz and B.R. Clifford in 2009-2011 under Group No. 881.

Before restoring the corners, the lines of the original surveys were retraced and a diligent search made for any evidence of the original corners and other calls of the original field note record.

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 2009, and the Special Instructions for Group No. 945, dated May 6, 2015, and the Supplemental Special Instructions dated July 10, 2015.

Measurements were made with Trimble R8 and 5800 Global Positioning System (GPS) receivers using the real-time kinematic (RTK) method and refer to the true meridian based on geodetic methods. The mean bearings of lines and horizontal equivalent of ground distances only are entered in the field notes.

The NAD 1983 (2011) (Epoch:2010.0000) geographic position of the following corners were determined by GPS static observations processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuous Operating Reference Stations (CORS), DJ8973 NVBM BERMUDA CORS ARP, DI4038 NVPO MT. POTOSI CORS ARP, DI1079 NVLM AMS WT FACILITY CORS ARP, and carried forward by RTK observations.

The corner of Townships 17 and 18 South, Ranges 58 and 59 East, is as follows:

Latitude: 36°25'30.414" N. Longitude: 115°25'25.594" W.

TOWNSHIP 18 SOUTH, RANGE 59 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The 1/4 section corner of sections 24 and 25 is as follows:

Latitude: 36°21'55.940" N. Longitude: 115°19'25.227" W.

The May 7, 2015 mean magnetic declination was determined to be 12°01' E., as obtained from the National Oceanic and Atmospheric Administration's National Geophysical Data Center declination calculator.

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of a Portion of the Survey Executed by
U.S. Deputy Surveyor E.A. Carter in 1881

Beginning at the cor. of secs. 19, 24, 25 and 30, monumented with a sandstone, 16x10x4 ins. (Record: limestone, 16x11x10 ins.), lying loose in a mound of stone, 3 ft. diam., 1/2 ft. high, mkd. with 4 notches on an edge and 2 notches on the opposite edge, with a nail set beneath.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T18S	
R58E	R59E
S24	S19
<hr/>	
S25	S30

2015

Bury mkd. stone alongside stainless steel post.

N. 0°09'30" E., bet. secs. 19 and 24.

34.70 Spur, slopes N. 75° E.

41.322 Point for the 1/4 sec. cor. of secs. 19 and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.

T18S	
1/4	
R58E	R59E
S24	S19

2015

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Cor. is located 23 lks. dist., N. of small wash, 8 lks. wide, drains N. 80° E.														
82.644	<p>Point for the cor. of secs. 13, 18, 19 and 24, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T18S</td></tr> <tr><td>R58E</td><td>R59E</td></tr> <tr><td>S13</td><td>S18</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S24</td><td>S19</td></tr> </table> <p>2015</p> </div> <p>Cor. is located on SE. edge of wash, 20 lks. wide, drains N. 40° E.</p>	T18S		R58E	R59E	S13	S18	<hr/>		S24	S19				
T18S															
R58E	R59E														
S13	S18														
<hr/>															
S24	S19														
41.322	<p>N. 0°09'30" E., bet. secs. 13 and 18.</p> <p>Point for the 1/4 sec. cor. of secs. 13 and 18, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T18S</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>R58E</td><td>R59E</td></tr> <tr><td>S13</td><td>S18</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td colspan="2">2015</td></tr> </table> </div>	T18S		1/4		R58E	R59E	S13	S18	<hr/>		2015			
T18S															
1/4															
R58E	R59E														
S13	S18														
<hr/>															
2015															
82.644	<p>Point for the cor. of. secs. 7, 12, 13 and 18, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T18S</td></tr> <tr><td>R58E</td><td>R59E</td></tr> <tr><td>S12</td><td>S 7</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S13</td><td>S18</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td colspan="2">2015</td></tr> </table> </div>	T18S		R58E	R59E	S12	S 7	<hr/>		S13	S18	<hr/>		2015	
T18S															
R58E	R59E														
S12	S 7														
<hr/>															
S13	S18														
<hr/>															
2015															

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	N. 0°09'30" E., bet. secs. 7 and 12.
41.322	Point for the 1/4 sec. cor. of secs. 7 and 12, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd. <div style="text-align: center;"> T18S 1/4 R58E R59E S12 S 7 2015 </div>
82.644	Point for the cor. of secs. 1, 6, 7 and 12, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd. <div style="text-align: center;"> T18S R58E R59E S 1 S 6 <hr style="width: 50%; margin: 0 auto;"/> S12 S 7 2015 </div>
	N. 0°09'30" E., bet. secs. 1 and 6.
31.50	Powerline, bears S. 44° E. and N. 44° W.
31.70	Dirt road, 12 lks. wide, bears S. 44° E. and N. 44° W.
38.80	Powerline, bears S. 44° E. and N. 44° W.
41.322	Point for the 1/4 sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd. <div style="text-align: center;"> T18S 1/4 R58E R59E S 1 S 6 2015 </div>

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
82.644	<p>The cor. of Tps. 17 and 18 S., Rs. 58 and 59 E., monumented with a stainless steel post, firmly set, flush in a mound of stone, 3 ft. diam., 1/2 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the E. bdy., T. 17 S., R. 58 E., executed concurrently under this same Group, with a steel fence post firmly set alongside.</p> <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor E.A. Carter in 1881 and a Portion of the Dependent Resurvey Executed by Cadastral Surveyor J.A. Mack in 1984</p> <hr/> <p>From the 1/4 sec. cor. of secs. 24 and 25, monumented with an iron post, 2 1/2 ins. diam., firmly set, 2 ins. below the surface of the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 18 S., R. 59 E., executed under Group No. 612, with a steel fence post firmly set alongside.</p> <p>Cor. is located on N. edge of gravel road, 15 lks. wide, bears E. and W., and alongside a chain link fence, bears E. and W.</p> <p>S. 86°12'40" W., bet. secs. 24 and 25.</p> <p>Along N. edge of gravel road and a chain link fence.</p>
20.398	<p>Point for the W 1/16 sec. cor. of secs. 24 and 25.</p> <p>POINT NOT MONUMENTED</p>
30.597	<p>Point for the W-W 1/64 sec. cor. of secs. 24 and 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>S24</p> <p>W-W 1/64 —</p> <p>S25</p> <p>2015</p> </div>
40.796	<p>Cor. is located on N. edge of gravel road, 15 lks. wide, bears E. and W., and alongside a chain link fence, bears E. and W.</p> <p>The cor. of secs. 23, 24, 25 and 26, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 18 S., R. 59 E., executed under Group No. 612.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Cor. is located on N. edge of gravel road, 15 lks. wide, bears E. and W., and alongside a chain link fence, bears E. and W.
	N. 0°00'40" E., bet. secs. 23 and 24.
20.455	Point for the S 1/16 sec. cor. of secs. 23 and 24. POINT NOT MONUMENTED
40.910	The 1/4 sec. cor. of secs. 23 and 24, perpetuated by Rita M. Lumos, Nevada Professional Land Surveyor No. 5094, in 2004, monumented with an aluminum cap, 3 1/4 ins. diam., firmly set in concrete flush with the ground, with top mkd. CITY OF LAS VEGAS 1/4 T18S 23 24 R59E PLS 5094 2003, as recorded in Clark County, Nevada, File 135, Page 67 of Surveys, with the original monument, a limestone, 10x8x7 ins. (Record: granite, 18x10x8 ins.), lying loose alongside, mkd. 1/4 on a face, and a steel fence post firmly set alongside. This is accepted as a careful and faithful perpetuation of the position of the original corner.
	N. 0°03'00" E., beginning new measurement.
4.90	Dirt road, 12 lks. wide, bears S. 45° E. and N. 45° W.
5.15	Powerline, bears S. 45° E. and N. 45° W.
19.30	Trail road, 12 lks. wide, bears S. 70° E. and N. 70° W.
20.408	Point for the N 1/16 sec. cor. of secs. 23 and 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. N 1/16 S23 S24 2015
30.612	Point for the N-N 1/64 sec. cor. of secs. 23 and 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. N-N 1/64 S23 S24 2015

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.816	<p>The cor. of secs. 13, 14, 23 and 24, perpetuated by Rita M. Lumos, Nevada Professional Land Surveyor No. 5094, in 2004, monumented with an aluminum cap, 3 1/4 ins. diam., firmly set in concrete flush with the ground, with top mkd. CITY OF LAS VEGAS T18S 13 14 23 24 R59E PLS 5094 2003, as recorded in Clark County, Nevada, File 135, Page 67 of Surveys, with the original monument, a limestone, 12x10x7 ins. (Record: granite, 20x10x7 ins.), loosely set alongside, mkd. with 1 notch on E. edge and 3 notches on S. edge. This is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <hr/> <p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., monumented with an aluminum cap, 3 1/4 ins. diam., firmly set in concrete flush with the ground, with top mkd. as described in the field notes of the dependent resurvey of a portion of the E. bdy., T. 18 S., R. 59 E., executed under Group No. 881.</p> <p>From this cor., a corner of cable fences extending N. and E., bears N. 47°41'00" E., 0.084 chs. dist.</p> <p>S. 86°26'00" W., bet. secs. 13 and 24.</p>
41.040	<p>The 1/4 sec. cor. of secs. 13 and 24, reestablished by Rita M. Lumos, Nevada Professional Land Surveyor No. 5094, in 2004, monumented with an aluminum cap, 3 1/4 ins. diam., firmly set in concrete flush with the ground, with top mkd. CITY OF LAS VEGAS T18S R59E 1/4 13 24 PLS 5094 2004, as recorded in Clark County, Nevada, File 135, Page 67 of Surveys, with a steel fence post firmly set alongside. This is accepted as a careful and faithful reestablishment of the position of the original corner.</p> <hr/> <p>S. 86°26'00" W., beginning new measurement.</p>
20.520	<p>Point for the W 1/16 sec. cor. of secs. 13 and 24.</p> <p>POINT NOT MONUMENTED</p>
32.20	Wash, 240 lks. wide, drains S. 20° E.
33.80	Trail road, 12 lks. wide, bears S. 25° E. and N. 25° W.
41.040	<p>The cor. of secs. 13, 14, 23 and 24.</p> <hr/> <p>N. 1°27'20" E., bet. secs. 13 and 14.</p>
10.10	Trail road, 12 lks. wide, bears S. 45° E. and N. 45° W.
14.90	Wash, 120 lks. wide, drains S. 30° E.
43.288	<p>Point for the 1/4 sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>T18S R59E 1/4 S14 S13</p> <p>2015</p> <p>From this point, a mound of stone, 3 ft. diam., 1 ft. high, bears N. 17°09'50" W., 11.669 chs. dist.</p>
86.576	<p>The cor. of secs. 11, 12, 13 and 14, monumented with a limestone, 15x9x7 ins. (Record: 15x12x7 ins.), firmly set, projecting 11 ins. above a mound of earth, 2 ft. diam., 4 ins. high, mkd. with 1 notch on E. edge and 4 notches on S. edge, with the remains of pits 8 ft. NE., SE., SW. and NW.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p>T18S R59E S11 S12 —+— S14 S13</p> <p>2015</p> <p>Bury mkd. stone alongside stainless steel post.</p>
	<p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>N. 89°34'10" W., bet. secs. 14 and 23.</p>
8.20	Trail road, 12 lks. wide, bears S. 10° E. and N. 10° W.
10.215	<p>Point for the E-E 1/64 sec. cor. of secs. 14 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p>S14 E-E 1/64 — S23</p> <p>2015</p>
20.430	<p>Point for the E 1/16 sec. cor. of secs. 14 and 23.</p> <p>POINT NOT MONUMENTED</p>
34.70	Powerline, bears S. 45° E. and N. 45° W.
35.00	Dirt road, 15 lks. wide, bears S. 45° E. and N. 45° W.
35.70	Dirt road, 15 lks. wide, bears N. 40° E. and S. 40° W.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.860	<p>The 1/4 sec. cor. of secs. 14 and 23, reestablished by Rita M. Lumos, Nevada Professional Land Surveyor No. 5094, in 2004, monumented with an aluminum cap, 3 1/4 ins. diam., firmly set in concrete flush with the ground, with top mkd. CITY OF LAS VEGAS T18S R59E 1/4 14 23 PLS 5094 2004, as recorded in Clark County, Nevada, File 135, Page 67 of Surveys, with an aluminum washer and nail, 1 1/2 ins. diam., firmly set alongside in concrete, mkd. CITY OF LAS VEGAS 5LV8932N4 BM NO., and a steel fence post firmly set alongside. This is accepted as a careful and faithful reestablishment of the position of the original corner.</p>
	<hr/> <p>N. 89°34'10" W., beginning new measurement.</p>
20.430	<p>Point for the W 1/16 sec. cor. of secs. 14 and 23.</p> <p>POINT NOT MONUMENTED</p>
40.860	<p>The cor. of secs. 14, 15, 22 and 23, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 18 S., R. 59 E., executed under Group No. 612, with a mound of stone, 3 ft. diam., 2 ft. high, W. of cor., and a steel fence post firmly set alongside.</p>
	<hr/> <p>N. 1°05'10" E., bet. secs. 14 and 15.</p>
14.20	<p>Enter communication tower site, edge bears N. 69° E. and S. 69° W.</p>
19.818	<p>Point for the S 1/16 sec. cor. of secs. 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S15 S14</p> <p style="text-align: center;">2015</p>
20.85	<p>Exit communication tower site, edge bears S. 21° E. and N. 21° W.</p>
29.727	<p>Point for the N-S 1/64 sec. cor. of secs. 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>N-S 1/64 S15 S14 2015</p>
39.636	<p>Point for the 1/4 sec. cor. of secs. 14 and 15, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p>T18S R59E 1/4 S15 S14 2015</p> <p>From this point, a limestone, 13x10x7 ins., lying loose on the ground, no marks visible, bears S. 27°18'10" W., 4.124 chs. dist.</p>
47.20	Dirt road, 15 lks. wide, bears S. 45° W. and N. 45° E.
47.45	Powerline, bears S. 45° E. and N. 45° W.
59.454	<p>Point for the N 1/16 sec. cor. of secs. 14 and 15.</p> <p>POINT NOT MONUMENTED</p>
79.272	<p>Point for the cor. of secs. 10, 11, 14 and 15, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p>T18S R59E S10 S11 ----- S15 S14 2015</p> <p>From this point, the 1/4 sec. cor. of secs. 10 and 11 bears N. 0°15'10" W., 39.629 chs. dist., determined at the center of a mound of earth and stone, 2 ft. diam., 4 ins. high. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>T18S R59E 1/4 S10 S11 2015</p> <hr/> <p>From the cor. of secs. 11, 12, 13 and 14. S. 85°21'50" W., bet. secs. 11 and 14.</p>
41.334	<p>Point for the 1/4 sec. cor. of secs. 11 and 14, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p>T18S R59E S11 1/4 — S14 2015</p>
49.40	Trail road, 12 lks. wide, bears N. 10° E. and S. 10° W.
82.668	The cor. of secs. 10, 11, 14 and 15.
	<hr/> <p>From the cor. of secs. 21, 22, 27 and 28, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 18 S., R. 59 E., executed under Group No. 612.</p> <p>Cor. is located on W. side of wash, 20 lks. wide, drains N. 35° E.</p> <p>N. 0°31'00" E., bet. secs. 21 and 22.</p>
28.810	A monument set for the beginning point of the northeasterly boundary of the Red Rock Canyon National Conservation Area, hereinafter described.
31.30	Powerline, bears S. 44° E. and N. 44° W.
31.40	Dirt road, 12 lks. wide, bears S. 44° E. and N. 44° W.
36.30	Powerline, bears S. 44° E. and N. 44° W.
40.991	The 1/4 sec. cor. of secs. 21 and 22, reestablished by Rita M. Lumos, Nevada Professional Land Surveyor No. 5094, in 2004, monumented with an aluminum cap, 3 1/4 ins. diam., firmly set in concrete flush with the ground, and in a collar of stone, with top mkd. CITY OF LAS VEGAS T18S R59E 1/4 21 22 PLS 5094 2004, as recorded in Clark County, Nevada, File 135, Page 67 of Surveys.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>This is accepted as a careful and faithful reestablishment of the position of the original corner.</p> <hr/> <p>N. 0°31'00" E., beginning new measurement.</p>
23.40	Southbound lane, U.S. Highway No. 95, bears S. 44° E. and N. 44° W.
25.70	Northbound lane, U.S. Highway No. 95, bears S. 44° E. and N. 44° W.
40.991	<p>The cor. of secs. 15, 16, 21 and 22, perpetuated by Rita M. Lumos, Nevada Professional Land Surveyor No. 5094, in 2004, monumented with an aluminum cap, 3 1/4 ins. diam., firmly set in concrete flush with the ground, and in a collar of stone, with top mkd. CITY OF LAS VEGAS T18S R59E 15 16 21 22 PLS 5094 2004, as recorded in Clark County, Nevada, File 135, Page 67 of Surveys, with a limestone, 16x10x5 ins., lying loose alongside, no marks visible, and a steel fence post firmly set alongside. This is accepted as the best available evidence of the position of the original corner.</p> <hr/> <p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>N. 89°52'00" W., bet. secs. 15 and 22.</p>
20.257	<p>Point for the E 1/16 sec. cor. of secs. 15 and 22.</p> <p>POINT NOT MONUMENTED</p>
40.514	<p>The 1/4 sec. cor. of secs. 15 and 22, reestablished by Rita M. Lumos, Nevada Professional Land Surveyor No. 5094, in 2004, monumented with an aluminum cap, 3 1/4 ins. diam., firmly set in concrete flush with the ground, and in a collar of stone, with top mkd. CITY OF LAS VEGAS T18S R59E 1/4 15 22 PLS 5094 2004, as recorded in Clark County, Nevada, File 135, Page 67 of Surveys, with a steel fence post firmly set alongside. This is accepted as a careful and faithful reestablishment of the position of the original corner.</p> <hr/> <p>N. 89°52'00" W., beginning new measurement.</p>
40.514	<p>The cor. of secs. 15, 16, 21 and 22.</p> <hr/> <p>N. 0°36'20" E., bet. secs. 15 and 16.</p>
39.463	<p>The 1/4 sec. cor. of secs. 15 and 16, monumented with a limestone, 16x9x6 ins. (Record: granite, 19x12x8 ins.), lying loose in a mound of stone, 2 ft. diam., 1 ft. high, no marks visible. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T18S R59E 1/4 S16 S15</p> <p style="text-align: center;">2015</p> <p>Bury unmarked stone alongside stainless steel post.</p> <hr/> <p>N. 0°41'50" W., beginning new measurement.</p>
19.884	<p>Point for the N 1/16 sec. cor. of secs. 15 and 16.</p> <p>POINT NOT MONUMENTED</p>
39.768	<p>The cor. of secs. 9, 10, 15 and 16, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 18 S., R. 59 E., executed under Group No. 612, with a mound of stone, 3 ft. diam., 2 ft. high, W. of the cor., and a steel fence post firmly set alongside.</p> <hr/> <p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>N. 89°53'20" W., bet. secs. 10 and 15.</p>
20.646	<p>Point for the E 1/16 sec. cor. of secs. 10 and 15.</p> <p>POINT NOT MONUMENTED</p>
28.70	Powerline, bears S. 35° E. and N. 35° W.
28.90	Dirt road, 15 lks. wide, bears S. 35° E. and N. 35° W.
41.292	<p>Point for the 1/4 sec. cor. of secs. 10 and 15, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T18S R59E S10 1/4 — S15</p> <p style="text-align: center;">2015</p> <p>From this point, a wood stake, firmly set at the center of a scattered mound of stone, 2 1/2 ft. diam., 1 ft. high, bears S. 1°05'00" W., 0.680 chs. dist.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
61.938	Point for the W 1/16 sec. cor. of secs. 10 and 15. POINT NOT MONUMENTED
74.842	Point for the E-W-W-W 1/1024 sec. cor. of secs. 10 and 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;">1 — 1024 2015</div>
78.40	Dirt road, 15 lks. wide, bears S. 70° E. and N. 70° W.
82.584	The cor. of secs. 9, 10, 15 and 16. <hr/>
	N. 0°40'20" W., bet. secs. 9 and 10.
1.40	Dirt road, 15 lks. wide, bears S. 70° E. and N. 70° W.
21.845	Point for the S 1/16 sec. cor. of secs. 9 and 10. POINT NOT MONUMENTED
43.690	Point for the 1/4 sec. cor. of secs. 9 and 10, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;">T18S R59E 1/4 S 9 S10 2015</div>
87.380	Point for the cor. of secs. 3, 4, 9 and 10, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;">T18S R59E S 4 S 3 — S 9 S10 2015</div>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From this point, the cor. of secs. 1, 2, 11 and 12 bears N. 89°32'40" E., 165.369 chs. dist., monumented with a limestone, 8x6x4 ins. (Record: sandstone, 18x14x8 ins.), firmly set, projecting 6 ins. above a collar of stone, mkd. with 1 notch on E. edge and 5 notches on S. edge.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T18S R59E</p> <table style="margin: auto;"> <tr> <td>S 2</td> <td>S 1</td> </tr> <tr> <td colspan="2"><hr/></td> </tr> <tr> <td>S11</td> <td>S12</td> </tr> </table> <p>2015</p> </div> <p>Bury mkd. stone alongside stainless steel post.</p> <p>The control line was fully retraced, and no evidence of the intervening corners was found.</p> <hr/> <p>N. 3°11'50" E., bet. secs. 3 and 4.</p> <p>43.755 The 1/4 sec. cor. of secs. 3 and 4, determined at the center of a mound of earth and stone, 2 ft. diam., 3 ins. high, occupied by a nail. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T18S R59E</p> <p>1/4</p> <table style="margin: auto;"> <tr> <td>S 4</td> <td>S 3</td> </tr> </table> <p>2015</p> </div> <p>From this point, a limestone, 16x13x7 ins., lying loose on the ground, no marks visible, bears S. 9°25'10" W., 16.354 chs. dist.</p> <hr/> <p>N. 0°11'40" W., beginning new measurement.</p> <p>40.98 Barbed wire fence, bears E. and W.</p>	S 2	S 1	<hr/>		S11	S12	S 4	S 3
S 2	S 1								
<hr/>									
S11	S12								
S 4	S 3								

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 41.034</p>	<p>The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set in a mound of broken concrete, 3 ft. base, 4 ins. high, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the N. bdy., T. 18 S., R. 59 E., executed under Group No. 881.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 21 and 28, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 18 S., R. 59 E., executed under Group No. 612, with a mound of stone, 2 1/2 ft. diam., 1 1/2 ft. high, N. of cor.</p> <p>N. 88°34'00" W., bet. secs. 21 and 28.</p> <p>41.245 Point for the cor. of secs. 20, 21, 28 and 29, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T18S R59E</p> <table border="1"> <tr> <td>S20</td> <td>S21</td> </tr> <tr> <td>S29</td> <td>S28</td> </tr> </table> <p>2015</p> </div> <p>From this point, the cor. of secs. 28, 29, 32 and 33 bears S. 0°50'00" E., 81.214 chs. dist., perpetuated by person(s) unknown, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 3 ins. above a mound of earth and stone, 2 ft. diam., 6 ins. high, with the original monument, a limestone, 13x9x7 ins. (Record: 18x10x7 ins.), lying loose alongside, mkd. with 4 notches on an edge and 1 notch on another, and a steel fence post firmly set alongside. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T18S R59E</p> <table border="1"> <tr> <td>S29</td> <td>S28</td> </tr> <tr> <td>S32</td> <td>S33</td> </tr> </table> <p>2015</p> </div> <p>Insert rebar inside, and bury mkd. stone alongside stainless steel post, leave steel fence post in place.</p>	S20	S21	S29	S28	S29	S28	S32	S33
S20	S21								
S29	S28								
S29	S28								
S32	S33								

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From this same point, the cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., bears S. 89°42'00" W., 161.174 chs. dist., hereinbefore described.</p> <p>The control lines were fully retraced, and no evidence of the intervening corners was found.</p>
	<p>N. 0°20'10" E., bet. secs. 20 and 21.</p>
40.603	<p>Point for the 1/4 sec. cor. of secs. 20 and 21, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T18S R59E 1/4 S20 S21</p> <p style="text-align: center;">2015</p>
81.206	<p>Point for the cor. of secs. 16, 17, 20 and 21, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T18S R59E S17 S16 — — S20 S21</p> <p style="text-align: center;">2015</p> <p>From this point, a sandstone, 16x15x8 ins., lying loose on the ground, no marks visible, with a nail set beneath, bears S. 0°06'20" E., 2.802 chs. dist.</p>
	<p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>N. 89°47'00" W., bet. secs. 16 and 21.</p>
15.10	<p>Northbound lane, U.S. Highway No. 95, bears S. 44° E. and N. 44° W.</p>
17.40	<p>Southbound lane, U.S. Highway No. 95, bears S. 44° E. and N. 44° W.</p>
41.227	<p>Point for the 1/4 sec. cor. of secs. 16 and 21, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>T18S R59E S16 1/4 — S21 2015</p>
45.30	Powerline, bears S. 44° E. and N. 44° W.
49.70	Dirt road, 12 lks. wide, bears S. 44° E. and N. 44° W.
50.20	Powerline, bears S. 44° E. and N. 44° W.
52.559	The witness point, at the intersection of the Red Rock Canyon National Conservation Area boundary, with the line bet. secs. 16 and 21, hereinafter described.
82.454	The cor. of secs. 16, 17, 20 and 21.
	<hr/> <p>N. 0°07'10" W., bet. secs. 16 and 17.</p>
30.578	The witness point, at the intersection of the Red Rock Canyon National Conservation Area boundary, with the line bet. secs. 16 and 17, hereinafter described.
32.90	Powerline, bears S. 44° E. and N. 44° W.
33.40	Dirt road, 12 lks. wide, bears S. 44° E. and N. 44° W.
38.10	Powerline, bears S. 44° E. and N. 44° W.
40.603	<p>Point for the 1/4 sec. cor. of secs. 16 and 17, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p>T18S R59E 1/4 S17 S16 2015</p>
66.55	Southbound lane, U.S. Highway No. 95, bears S. 44° E. and N. 44° W.
68.90	Northbound lane, U.S. Highway No. 95, bears S. 44° E. and N. 44° W.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 81.206</p>	<p>The cor. of secs. 8, 9, 16 and 17, determined by Rita M. Lumos, Nevada Professional Land Surveyor No. 5094, monumented with an aluminum cap, 3 1/4 ins. diam., firmly set in concrete flush with the ground, and in a scattered mound of stone, 3 ft. diam., 1/2 ft. high, with top mkd. CITY OF LAS VEGAS T18S 8 9 16 17 R59E PLS 5094 2003, with a steel fence post firmly set alongside. This is accepted as the best available evidence of the position of the original corner.</p> <p>From this cor., the SE. cor. of a gravel pit bears N. 0°16'30" E., 10.282 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, projecting 7 ins. above the ground, with aluminum cap mkd. NEV TRANS DEPT AP2 1221010A PIT COR 2012, alongside a cor. of chain link fences extending N. and W.</p> <p>From this same cor., the SW. cor. of a gravel pit bears N. 62°32'40" W., 22.741 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, with aluminum cap mkd. NEV TRANS DEPT AP3 1221011A PIT COR 2012, alongside a cor. of chain link fences extending N. and E.</p>
<p>20.997</p>	<p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>N. 87°32'30" W., bet. secs. 9 and 16.</p> <p>Point for the E 1/16 sec. cor. of secs. 9 and 16.</p> <p>POINT NOT MONUMENTED</p>
<p>23.622</p>	<p>Point for the E-E-W-E 1/1024 sec. cor. of secs. 9 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>1</p> <hr/> <p>1024</p> <p>2015</p> </div>
<p>41.994</p>	<p>The 1/4 sec. cor. of secs. 9 and 16, perpetuated by the Nevada Department of Transportation, monumented with a rebar, 5/8 in. diam., 24 ins. long, firmly set, flush in a mound of earth, 4 ft. diam., 4 ins. high, with aluminum cap mkd. NEV TRANS DEP T18S R59E S9 S16 1221002L 2011, with the original monument, a sandstone, 15x12x9 ins. (Record: 23x13x12 ins.), lying loose alongside, mkd. 1/4 on a face, a mound of stone, 3 ft. diam., 1 1/2 ft. high N. of cor., and a steel fence post firmly set alongside. This is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>T18S R59E S 9 1/4 — S16 2015</p> <p>Bury rebar and mkd. stone alongside stainless steel post, leave mound of stone and steel fence post in place.</p> <hr/> <p>N. 89°18'20" W., beginning new measurement.</p>
20.294	<p>Point for the W 1/16 sec. cor. of secs. 9 and 16.</p> <p>POINT NOT MONUMENTED</p>
40.588	<p>The cor. of secs. 8, 9, 16 and 17.</p> <hr/> <p>N. 1°00'50" W., bet. secs. 8 and 9.</p>
10.20	Dirt road, 12 lks. wide, bears E. and W.
10.30	Chain link fence, bears E. and W., enter gravel pit.
19.490	<p>Point for the S 1/16 sec. cor. of secs. 8 and 9.</p> <p>POINT NOT MONUMENTED</p>
30.10	Chain link fence, bears E. and W., exit gravel pit.
30.20	Dirt road, 12 lks. wide, bears E. and W.
31.671	<p>Point for the S-N-N-S 1/1024 sec. cor. of secs. 8 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p>1 — 1024 2015</p>
	<p>From this point, the NE. cor. of a gravel pit bears S. 11°10'00" E., 1.634 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, projecting 5 ins. above the ground, with aluminum cap mkd. NEV TRANS DEPT AP5 1221013A PIT COR 2012, alongside a cor. of chain link fences extending S. and W.</p> <p>From this same point, the NW. cor. of a gravel pit bears S. 85°55'00" W., 19.497 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with aluminum cap mkd. NEV TRANS DEPT AP4 1221012A PIT COR 2012, alongside a cor. of chain link fences extending S. and W.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
38.980	<p>Point for the 1/4 sec. cor. of secs. 8 and 9, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T18S R59E 1/4 S 8 S 9</p> <p style="text-align: center;">2015</p>
77.960	<p>The cor. of secs. 4, 5, 8 and 9, determined at the center of a mound of stones, 2 1/2 ft. diam., 1/2 ft. high. This is accepted as the best available evidence of the position of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T18S R59E S 5 S 4 —+— S 8 S 9</p> <p style="text-align: center;">2015</p>
	<p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>S. 85°04'50" W., bet. secs. 4 and 9.</p>
8.65	Dirt road, 15 lks. wide, bears S. 35° E. and N. 35° W.
18.00	Wash, 6 lks. wide, drains S. 30° E.
41.593	<p>Point for the 1/4 sec. cor. of secs. 4 and 9, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T18S R59E S 4 1/4 — S 9</p> <p style="text-align: center;">2015</p>
83.186	<p>The cor. of secs. 4, 5, 8 and 9.</p> <hr/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 4°50'20" E., bet. secs. 4 and 5.
52.473	The 1/4 sec. cor. of secs. 4 and 5, determined by Russell Avery, Nevada Professional Land Surveyor No. 2002, and Linda L. Miller, Nevada Professional Land Surveyor No. 10843, in 2002, monumented with an iron pipe, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. AVERY-MILLER T18S R59E 1/4 S5 S4 2002 PLS 10843, as recorded in Clark County, Nevada, File 123, Page 64 of Surveys, with an iron pipe, 1 in. diam., firmly set alongside, projecting 1 in. above the ground, and a fence post firmly set 1 ft. S., with hog wire fences extending N. and E. This position has been adopted by adjacent landowners and professional land surveyors and is accepted as the best available evidence of the position of the original corner.
	N. 1°01'10" E., beginning new measurement.
	Along a hog wire fence and Landy Street, dirt surface, 15 lks. wide.
4.99	Hog wire fence, bears E. and W.
	From this point, a cor. of hog wire fences extending N., E., and S., bears WEST, 0.01 chs. dist.
	Continue along hog wire fence and Landy Street.
9.994	From this point, a position established by person(s) unknown bears WEST, 0.003 chs. dist., monumented with an iron pipe, 1 in. diam., firmly set, projecting 4 ins. above the ground, as recorded in Clark County, Nevada, File 123, Page 64 of Surveys.
10.42	Cor. of hog wire fences extending E. and S.
19.963	From this point, a position established by David F. Causey, Nevada Professional Land Surveyor No. 1811, in 1975, bears WEST, 0.005 chs. dist., monumented with an iron pipe, 1 in. diam., firmly set, projecting 4 ins. above the ground, as recorded in Clark County, Nevada, File 5, Page 62 of Parcel Maps.
24.96	From this point, a cor. of chain link fence extending E., bears EAST, 0.17 chs. dist.
29.82	From this point, a cor. of chain link fences extending N. and E., bears EAST, 0.11 chs. dist.
29.974	From this point, a position established by person(s) unknown, bears WEST, 0.006 chs. dist., monumented with an iron pipe, firmly set, bent over and buried 5 ins. below the surface of Landy Street.
34.95	From this point, a cor. of hog wire fences extending N. and E., bears EAST, 0.14 chs. dist.
34.970	A position established by person(s) unknown, monumented with a rebar, firmly set, flush with the surface of Landy Street, with damaged and illegible plastic cap.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
37.77	From this point, a cor. of fences bears EAST, 0.14 chs. dist., with chain link fences extending N. and E., hog wire fence extending S.
39.44	From this point, a cor. of chain link fences extending E. and S., bears EAST, 0.15 chs. dist.
39.70	Leave Landy Street.
39.961	The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., monumented with an iron pipe, 2 1/2 ins. diam., firmly set, flush in a collar of stone, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the N. bdy., T. 18 S., R. 59 E., executed under Group No. 881.
	From the cor. of secs. 16, 17, 20 and 21.
	N. 88°18'40" W., bet. secs. 17 and 20.
41.039	Point for the 1/4 sec. cor. of secs. 17 and 20, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base to top, with brass cap mkd.
	<div style="text-align: center;"> T18S R59E S17 1/4 — S20 2015 </div>
82.078	Point for the cor. of secs. 17, 18, 19 and 20, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	<div style="text-align: center;"> T18S R59E S18 S17 — — S19 S20 2015 </div>
	From this point, the cor. of secs. 29, 30, 31 and 32 bears S. 0°23'10" E., 164.582 chs. dist., monumented with a sandstone, 16x11x9 ins. (Record: limestone, 14x8x7 ins.), firmly set, projecting 8 ins. above a mound of earth, 2 1/2 ft. diam., 3 ins. high, mkd. with 5 grooves on E. face and 1 groove on S. face, with the remains of pits 5 ft. NW. and SE. of cor.
	At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T18S R59E</p> <table style="margin: auto;"> <tr> <td>S30</td><td>S29</td></tr> <tr> <td colspan="2"><hr/></td></tr> <tr> <td>S31</td><td>S32</td></tr> </table> <p>2015</p> </div> <p>Bury mkd. stone alongside stainless steel post.</p> <p>From this same point, a mound of stone, 3 ft. diam., 1 ft. high, bears S. 0°14'10" E., 47.337 chs. dist.</p> <p>From this same point, the cor. of secs. 18, 19, 24 and 25, on the W. bdy. of the Tp., bears S. 88°41'00" W., 79.369 chs. dist., hereinbefore described.</p> <p>The control lines were fully retraced, and no evidence of the intervening corners was found.</p> <hr/> <p>N. 0°00'30" E., bet. secs. 17 and 18.</p> <p>41.145 Point for the 1/4 sec. cor. of secs. 17 and 18, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T18S R59E</p> <p>1/4</p> <p>S18 S17</p> <p>2015</p> </div> <p>82.290 Point for the cor. of secs. 7, 8, 17 and 18, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T18S R59E</p> <table style="margin: auto;"> <tr> <td>S 7</td><td>S 8</td></tr> <tr> <td colspan="2"><hr/></td></tr> <tr> <td>S18</td><td>S17</td></tr> </table> <p>2015</p> </div> <hr/> <p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>N. 87°33'00" W., bet. secs. 8 and 17.</p>	S30	S29	<hr/>		S31	S32	S 7	S 8	<hr/>		S18	S17
S30	S29												
<hr/>													
S31	S32												
S 7	S 8												
<hr/>													
S18	S17												

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
12.60	Northbound lane, U.S. Highway No. 95, bears S. 44° E. and N. 44° W.
14.90	Southbound lane, U.S. Highway No. 95, bears S. 44° E. and N. 44° W.
20.481	Point for the E 1/16 sec. cor. of secs. 8 and 17. POINT NOT MONUMENTED
40.962	Point for the 1/4 sec. cor. of secs. 8 and 17, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd. <div style="text-align: center;"> T18S R59E S 8 1/4 — S17 2015 </div>
44.00	Powerline, bears S. 44° E. and N. 44° W.
49.10	Dirt road, 12 lks. wide, bears S. 44° E. and N. 44° W.
49.15	Powerline, bears S. 44° E. and N. 44° W.
51.517	The witness point, at the intersection of the Red Rock Canyon National Conservation Area boundary, with the line bet. secs. 8 and 17, hereinafter described.
61.443	Point for the W 1/16 sec. cor. of secs. 8 and 17. POINT NOT MONUMENTED
81.924	The cor. of secs. 7, 8, 17 and 18 <hr/>
	S. 88°56'10" W., bet. secs. 7 and 18.
40.972	Point for the 1/4 sec. cor. of secs. 7 and 18, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd. <div style="text-align: center;"> T18S R59E S 7 1/4 — S18 2015 </div>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
79.127	The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., hereinbefore described.
	From the cor. of secs. 7, 8, 17 and 18.
	N. 0°24'50" W., bet. secs. 7 and 8.
20.573	Point for the S 1/16 sec. cor. of secs. 7 and 8.
	POINT NOT MONUMENTED
30.034	The witness point, at the intersection of the Red Rock Canyon National Conservation Area boundary, with the line bet. secs. 7 and 8, hereinafter described.
32.40	Powerline, bears S. 44° E. and N. 44° W.
32.50	Dirt road, 12 lks. wide, bears S. 44° E. and N. 44° W.
37.50	Powerline, bears S. 44° E. and N. 44° W.
41.146	Point for the 1/4 sec. cor. of secs. 7 and 8, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.
	T18S R59E 1/4 S 7 S 8 2015
66.10	Southbound lane, U.S. Highway No. 95, bears S. 44° E. and N. 44° W.
68.50	Northbound lane, U.S. Highway No. 95, bears S. 44° E. and N. 44° W.
70.241	The witness point at the intersection of the easterly right-of- way line of U.S. Highway No. 95, with the line bet. secs. 7 and 8, hereinafter described.
82.292	Point for the cor. of secs. 5, 6, 7 and 8, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<div style="text-align: center;"> T18S R59E S 6 S 5 <hr style="width: 50%; margin: 0 auto;"/> S 7 S 8 2015 </div> <p>From this point, an embedded mound of stone, 2 1/2 ft. diam., bears S. 45°30'40" E., 3.804 chs. dist.</p> <p>From this same point, an embedded mound of stone, 3 1/2 ft. diam., bears S. 3°07'50" E., 9.869 chs. dist.</p> <hr/> <p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>N. 84°28'20" W., bet. secs. 5 and 8.</p> <p>27.00 Trail road, 12 lks. wide, bears N. 40° E. and S. 40° W.</p> <p>40.713 Point for the 1/4 sec. cor. of secs. 5 and 8, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> T18S R59E S 5 1/4 ——— S 8 2015 </div> <p>81.426 The cor. of secs. 5, 6, 7 and 8.</p> <hr/> <p>S. 89°11'10" W., bet. secs. 6 and 7.</p> <p>11.525 The witness point, at the intersection of the easterly right-of-way line of U.S. Highway No. 95, with the line bet. secs. 6 and 7, hereinafter described.</p> <p>13.20 Northbound lane, U.S. Highway No. 95, bears S. 44° E. and N. 44° W.</p> <p>15.45 Southbound lane, U.S. Highway No. 95, bears S. 44° E. and N. 44° W.</p> <p>40.468 Point for the 1/4 sec. cor. of secs. 6 and 7, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>T18S R59E S 6 1/4 — S 7 2015</p>
42.90	Powerline, bears S. 44° E. and N. 44° W.
47.65	Trail road, 12 lks. wide, bears S. 44° E. and N. 44° W.
47.80	Powerline, bears S. 44° E. and N. 44° W.
78.285	The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., hereinbefore described.
	<hr/> <p>From the cor. of secs. 5, 6, 7 and 8. N. 2°23'20" E., bet. secs. 5 and 6.</p>
41.180	<p>Point for the 1/4 sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p>T18S R59E 1/4 S 6 S 5 2015</p>
82.494	<p>The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, flush in a collar of stone, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the S. bdy., T. 17 S., R. 59 E., executed concurrently under this same Group.</p> <hr/> <p>SUBDIVISION OF SECTION 4, T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 4 and 9. N. 3°30'00" E., on the N-S center line of sec. 4.</p>
42.45	Rosencrantz Avenue, dirt surface, 12 lks. wide, bears S. 80° E. and N. 80° W.
45.50	Dirt road, 12 lks. wide, bears S. 50° E. and N. 50° W.
47.50	Dirt road, 15 lks. wide, bears E. and W.

SUBDIVISION OF SECTION 4,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 48.546</p>	<p>The center 1/4 sec. cor. of sec. 4, established by person(s) unknown, monumented with a rebar, 1/2 in. diam., firmly set, projecting 2 ins. above the ground, with a steel fence post set alongside, with chain link fences extending N. and W. This position agrees with distances reported from the 1/4 sec. cor. of secs. 4 and 5 on multiple records of survey and is accepted as a careful and faithful determination of the position of the corner.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 27 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 45°07'30" E., 2.000 chs. dist., with brass cap mkd. RM T18S R59E S4 132.0 FT TO COR 2015, and an arrow pointing to the corner.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 44°52'50" E., 2.000 chs. dist., with brass cap mkd. RM T18S R59E S4 132.0 FT TO COR 2015, and an arrow pointing to the corner.</p> <p>From this point, a position established by Russell Avery, Nevada Professional Land Surveyor No. 2002, and Linda L. Miller, Nevada Professional Land Surveyor No. 10843, in 2002, bears S. 48°39'50" E., 0.015 chs. dist., monumented with an iron pipe, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. AVERY-MILLER T18S R59E C 1/4 S4 2002 PLS2002-10843, as recorded in Clark County, Nevada, File 123, Page 64 of Surveys. This position was established by using a position established by Russell Avery and Linda Miller for the 1/4 sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp., which was not utilized during the course of the dependent resurvey of a portion of the N. bdy., T. 18 S., R. 59 E., executed under Group No. 881.</p> <hr style="width: 30%; margin-left: 0;"/> <p>N. 0°59'50" E., beginning new measurement.</p> <p>Along chain link fence.</p> <p>5.00 Chain link fence, bears E. and W.</p> <p>From this point, a cor. of chain link fences extending N., S. and W., bears EAST, 0.01 chs. dist.</p> <p>Continue along chain link fence.</p> <p>9.50 Chain link fence, bears E. and W.</p> <p>From this point, a cor. of hog wire fences extending S. and W., bears EAST, 0.01 chs. dist.</p>
--------------------------	---

SUBDIVISION OF SECTION 4,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
9.998	From this point, a position established by person(s) unknown bears WEST, 0.003 chs. dist., monumented with a rebar, 1/2 in. diam., firmly set, flush with the surface of a Grover Avenue, gravel surface, 15 lks. wide, extends W., as recorded in Clark County, Nevada, File 169, Page 80 of Surveys.
10.50	Hog wire fence, bears E. and W. From this point, a cor. of fences bears EAST, 0.01 chs. dist., with chain link fence extending N., and hog wire fence extending W. Continue along chain link fence.
15.00	Chain link fence, bears E. and W. From this point, a cor. of chain link fences extending N., S., and W., bears EAST, 0.01 chs. dist. Continue along chain link fence.
17.00	Hog wire fence, bears E. and W. From this point, a cor. of fences bears EAST, 0.01 chs. dist., with hog wire fences extending N. and W., and chain link fence extending S. Continue along hog wire fence.
19.50	Hog wire fence, bears E. and W. From this point, a cor. of hog wire fences extending S. and W., bears EAST, 0.01 chs. dist.
19.90	Gelber Avenue, gravel surface, 15 lks. wide, extends W.
20.029	From this point, a position established by Richard L. Hafen, Nevada Professional Land Surveyor No. 4428, in 2001, bears EAST, 0.004 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of Gelber Avenue, with aluminum cap mkd. R.L. Hafen RLS4428, as recorded in Clark County, Nevada, File 116, Page 80 of Surveys, with a rebar, 1/2 in. diam., firmly set alongside, flush with the surface of Gelber Avenue.
24.80	Cor. of electric fences extending N. and W. Continue along electric fence.
25.10	Cor. of barbed wire fences extending N. and W., and electric fence extending S. Continue along barbed wire fence.
29.30	Barbed wire fence, bears E. and W. From this point, a cor. of barbed wire fences extending S. and W., bears EAST, 0.01 chs. dist.

SUBDIVISION OF SECTION 4,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
30.038	From this point, a position established by Richard L. Hafen, Nevada Professional Land Surveyor No. 4428, in 2001, bears EAST, 0.003 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, 2 ins. below the surface of Bunghero Avenue, dirt surface, 15 lks. wide, extends W., with aluminum cap mkd. R.L. Hafen RLS4428, as recorded in Clark County, Nevada, File 116, Page 80 of Surveys.
30.50	From this point, a cor. of hog wire fences extending N. and W., bears WEST, 0.07 chs. dist. Continue along hog wire fence.
35.00	From this point, a cor. of hog wire fences extending N., S. and W., bears WEST, 0.04 chs. dist. Continue along hog wire fence.
40.03	Cor. of hog wire fences extending S. and W., and barbed wire fence extending E.
40.048	The 1/4 sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the N. bdy., T. 18 S., R. 59 E., executed under Group No. 881. From this cor., a position established by Russell Avery, Nevada Professional Land Surveyor No. 2002, and Linda L. Miller, Nevada Professional Land Surveyor No. 10843, in 2002, monumented with an iron pipe, 2 ins. diam., firmly set flush with the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the N. bdy., T. 18 S., R. 59 E., executed under Group No. 881, bears S. 20°00'10" E., 0.022 chs. dist.
	From the 1/4 sec. cor. of secs. 3 and 4. N. 88°19'00" W., on the E-W center line of sec. 4.
28.90	Trail road, 12 lks. wide, bears S. 15° E. and N. 15° W.
40.30	Domingo Road, dirt surface, 12 lks. wide, bears N. and S.
40.930	The center 1/4 sec. cor. of sec. 4. N. 89°37'20" W., beginning new measurement. Along chain link fence.
5.004	A position established by person(s) unknown, monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, alongside fence post, with chain link fences extending N. and E., and hog wire fence extending W. Continue along hog wire fence.

SUBDIVISION OF SECTION 4,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
9.993	From this point, a position established by person(s) unknown, bears NORTH, 0.004 chs. dist., monumented with a rebar, 1/2 in. diam., firmly set, bent over and 5 ins. below the surface of the ground.
10.35	Hog wire fence, bears N. and S. From this point, a cor. of hog wire fences extending N. and E., bears SOUTH, 0.06 chs. dist.
19.980	A position established by David F. Causey, Nevada Professional Land Surveyor No. 1811, in 1975, monumented with an iron pipe, 1 in. diam., firmly set, projecting 4 ins. above the ground, as recorded in Clark County, Nevada, File 5, Page 62 of Parcel Maps.
29.90	Intersection of dirt road, 12 lks. wide, bearing N. 35° E. and S. 35° W., with Pugatz Street, dirt surface, 12 lks. wide, bearing N. and S.
35.011	Hog wire fence, bears N. and S. From this point, a position established by person(s) unknown, bears SOUTH, 0.75 chs. dist., monumented with a rebar, 5/8 in. diam., loosely set, projecting 18 ins. above the ground, with a fence cor. alongside, with hog wire fences extending N., N. 85° E. and S. 85° W.
39.973	The 1/4 sec. cor. of secs. 4 and 5.
<p>SUBDIVISION OF SECTION 7, T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA</p>	
	From the 1/4 sec. cor. of secs. 7 and 18. N. 0°04'10" W., on the N-S center line of sec. 7.
41.237	Point for the center 1/4 sec. cor. of sec. 7, at intersection with the E-W center line. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T18S R59E C 1/4 S 7 2015
74.85	Powerline, bears S. 44° E. and N. 44° W.
75.00	Dirt road, 12 lks. wide, bears S. 44° E. and N. 44° W.
79.90	Powerline, bears S. 44° E. and N. 44° W.
82.474	The 1/4 sec. cor. of secs. 6 and 7.

SUBDIVISION OF SECTION 7,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	From the 1/4 sec. cor. of secs. 7 and 8. S. 89°03'40" W., on the E-W center line of sec. 7.
3.50	Powerline, bears S. 44° E. and N. 44° W.
8.25	Dirt road, 12 lks. wide, bears S. 44° E. and N. 44° W.
8.40	Powerline, bears S. 44° E. and N. 44° W.
10.603	The witness point, at the intersection of the Red Rock Canyon National Conservation Area boundary, with the E-W center line of sec. 7, hereinafter described.
40.720	The center 1/4 sec. cor. of sec. 7.
78.706	The 1/4 sec. cor. of secs. 7 and 12, on the W. bdy. of the Tp.
SUBDIVISION OF SECTION 8 T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA	
	From the 1/4 sec. cor. of secs. 8 and 17. N. 0°42'20" W., on the N-S center line of sec. 8.
20.031	Point for the C-S 1/16 sec. cor. of sec. 8. POINT NOT MONUMENTED
25.80	Southbound lane, U.S. Highway No. 95, bears S. 44° E. and N. 44° W.
28.20	Northbound lane, U.S. Highway No. 95, bears S. 44° E. and N. 44° W.
32.550	Point for the C-S-N-N-S 1/1024 sec. cor. of sec. 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd. <div style="text-align: right;">1 —— 1024 2015</div>
38.60	Trail road, 15 lks. wide, bears S. 70° E. and N. 70° W.
40.062	Point for the center 1/4 sec. cor. of sec. 8, at intersection with the E-W center line. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

SUBDIVISION OF SECTION 8,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T18S R59E C 1/4 S 8</p>
	<p style="text-align: center;">2015</p>
63.00	Trail road, 12 lks. wide, bears N. 40° E. and S. 40° W.
80.124	The 1/4 sec. cor. of secs. 5 and 8.
	<hr/> <p>From the 1/4 sec. cor. of secs. 8 and 9.</p>
	<p>N. 86°00'50" W., on the E-W center line of sec. 8.</p>
20.411	Point for the C-E 1/16 sec. cor. of sec. 8.
	<p>POINT NOT MONUMENTED</p>
40.822	The center 1/4 sec. cor. of sec. 8.
46.60	Trail road, 15 lks. wide, bears S. 70° E. and N. 70° W.
51.302	The witness point, at the intersection of the easterly right-of-way line of U.S. Highway No. 95, with the E-W center line of sec. 8, hereinafter described.
53.10	Northbound lane, U.S. Highway No. 95, bears S. 44° E. and N. 44° W.
55.60	Southbound lane, U.S. Highway No. 95, bears S. 44° E. and N. 44° W.
61.233	Point for the C-W 1/16 sec. cor. of sec. 8.
	<p>POINT NOT MONUMENTED</p>
81.644	The 1/4 sec. cor. of secs. 7 and 8.
	<hr/> <p>From the point for the E 1/16 sec. cor. of secs. 8 and 17.</p>
	<p>N. 0°51'30" W., on the N-S center line of the SE1/4 of sec. 8.</p>
19.761	Point for the SE 1/16 sec. cor. of sec. 8, at intersection with the E-W center line of the SE1/4.
	<p>POINT NOT MONUMENTED</p>
32.112	Point for the C-S-N-N-SE 1/1024 sec. cor. of sec. 8.
	<p>POINT NOT MONUMENTED</p>
39.522	The point for the C-E 1/16 sec. cor. of sec. 8.
	<hr/> <p>From the point for the S 1/16 sec. cor. of secs. 8 and 9.</p>
	<p>N. 86°47'00" W., on the E-W center line of the SE1/4 of sec. 8.</p>

SUBDIVISION OF SECTION 8,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.444	The point for the SE 1/16 sec. cor. of sec. 8.
40.888	The point for the C-S 1/16 sec. cor. of sec. 8.
	<hr/>
	From the S-N-N-S 1/1024 sec. cor. of secs. 8 and 9.
	N. 86°18'10" W., on the computed E-W center line of the SE1/4 of the NE1/4 of the NE1/4 of the SE1/4 of sec. 8.
5.106	Point for the C-S-NE-NE-SE 1/1024 sec. cor. of sec. 8, at its computed position.
	POINT NOT MONUMENTED
	<hr/>
	N. 86°18'10" W., on the computed E-W center line of the SW1/4 of the NE1/4 of the NE1/4 of the SE1/4 of sec. 8.
5.106	Point for the C-S-N-NE-SE 1/1024 sec. cor. of sec. 8, at its computed position.
	POINT NOT MONUMENTED
	<hr/>
	N. 86°18'10" W., on the computed E-W center line of the SE1/4 of the NW1/4 of the NE1/4 of the SE1/4 of sec. 8.
5.106	Point for the C-S-NW-NE-SE 1/1024 sec. cor. of sec. 8, at its computed position.
	POINT NOT MONUMENTED
	<hr/>
	N. 86°18'10" W., on the E-W center line of the SW1/4 of the NW1/4 of the NE1/4 of the SE1/4 of sec. 8.
2.40	Trail road, 15 lks. wide, bears S. 70° E. and N. 70° W.
5.106	The point for the C-S-N-N-SE 1/1024 sec. cor. of sec. 8.
	<hr/>
	N. 86°18'10" W., on the computed E-W center line of the SE1/4 of the NE1/4 of the NW1/4 of the SE1/4 of sec. 8.
5.106	Point for the C-S-NE-NW-SE 1/1024 sec. cor. of sec. 8, at its computed position.
	POINT NOT MONUMENTED
	<hr/>
	N. 86°18'10" W., on the computed E-W center line of the SW1/4 of the NE1/4 of the NW1/4 of the SE1/4 of sec. 8.

SUBDIVISION OF SECTION 8,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
5.106	Point for the C-S-N-NW-SE 1/1024 sec. cor. of sec. 8, at its computed position. POINT NOT MONUMENTED
	<hr/>
	N. 86°18'10" W., on the computed E-W center line of the SE1/4 of the NW1/4 of the NW1/4 of the SE1/4 of sec. 8.
5.106	Point for the C-S-NW-NW-SE 1/1024 sec. cor. of sec. 8, at its computed position. POINT NOT MONUMENTED
	<hr/>
	N. 86°18'10" W., on the E-W center line of the SW1/4 of the NW1/4 of the NW1/4 of the SE1/4 of sec. 8.
5.106	The C-S-N-N-S 1/1024 sec. cor. of sec. 8. From the point for the W 1/16 sec. cor. of secs. 8 and 17. N. 0°33'30" W., on the N-S center line of the SW1/4 of sec. 8.
9.831	The point of intersection of the Red Rock Canyon National Conservation Area boundary, with the N-S center line of the SW1/4 of sec. 8.
12.20	Powerline, bears S. 44° E. and N. 44° W.
12.30	Dirt road, 12 lks. wide, bears S. 44° E. and N. 44° W.
17.30	Powerline, bears S. 44° E. and N. 44° W.
20.302	Point for the SW 1/16 sec. cor. of sec. 8, at intersection with the E-W center line of the SW1/4. POINT NOT MONUMENTED
32.991	Point for the C-S-N-N-SW 1/1024 sec. cor. of sec. 8. POINT NOT MONUMENTED
40.604	The point for the C-W 1/16 sec. cor. of sec. 8. From the point for the C-S 1/16 sec. cor. of sec. 8. N. 86°47'00" W., on the E-W center line of the SW1/4 of sec. 8.
20.444	The point for the SW 1/16 sec. cor. of sec. 8.
23.50	Powerline, bears S. 44° E. and N. 44° W.
28.70	Dirt road, 12 lks. wide, bears S. 44° E. and N. 44° W.
28.80	Powerline, bears S. 44° E. and N. 44° W.

SUBDIVISION OF SECTION 8,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
31.171	The point of intersection of the Red Rock Canyon National Conservation Area boundary, with the E-W center line of the SW1/4 of sec. 8.
40.888	The point for the S 1/16 sec. cor. of secs. 7 and 8.
	From the C-S-N-N-S 1/1024 sec. cor. of sec. 8.
	N. 86°18'10" W., on the computed E-W center line of the SE1/4 of the NE1/4 of the NE1/4 of the SW1/4 of sec. 8.
2.673	The witness point, at the intersection of the easterly right-of-way line of U.S. Highway No. 95, with the E-W center line of the SE1/4 of the NE1/4 of the NE1/4 of the SW1/4 of sec. 8, hereinafter described.
4.50	Northbound lane, U.S. Highway No. 95, bears S. 44° E. and N. 44° W.
5.106	Point for the C-S-NE-NE-SW 1/1024 sec. cor. of sec. 8, at its computed position.
	POINT NOT MONUMENTED
	N. 86°18'10" W., on the computed E-W center line of the SW1/4 of the NE1/4 of the NE1/4 of the SW1/4 of sec. 8.
1.826	Southbound lane, U.S. Highway No. 95, bears S. 44° E. and N. 44° W.
5.106	Point for the C-S-N-NE-SW 1/1024 sec. cor. of sec. 8, at its computed position.
	POINT NOT MONUMENTED
	N. 86°18'10" W., on the E-W center line of the SE1/4 of the NW1/4 of the NE1/4 of the SW1/4 of sec. 8.
5.106	Point for the C-S-NW-NE-SW 1/1024 sec. cor. of sec. 8, at its computed position.
	POINT NOT MONUMENTED
	N. 86°18'10" W., on the E-W center line of the SW1/4 of the NW1/4 of the NE1/4 of the SW1/4 of sec. 8.
5.106	The point for the C-S-N-N-SW 1/1024 sec. cor. of sec. 8.

SUBDIVISION OF SECTION 9,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the 1/4 sec. cor. of secs. 9 and 16.</p> <p>N. 0°21'40" W., on the N-S center line of sec. 9.</p>
10.167	<p>Point for the C-S-S 1/64 sec. cor. of sec. 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 9 C-S-S 1/64 2015</p>
13.80	Dirt road, 15 lks. wide, bears S. 70° E. and N. 70° W.
20.334	<p>Point for the C-S 1/16 sec. cor. of sec. 9.</p> <p>POINT NOT MONUMENTED</p>
22.876	<p>Point for the C-S-S-N-S 1/1024 sec. cor. of sec. 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">1 ----- 1024 2015</p>
40.668	<p>Point for the center 1/4 sec. cor. of sec. 9, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T18S R59E C 1/4 S 9 2015</p>
82.008	<p>The 1/4 sec. cor. of secs. 4 and 9.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 9 and 10.</p> <p>S. 88°19'30" W., on the E-W center line of sec. 9.</p>
20.857	<p>Point for the C-E 1/16 sec. cor. of sec. 9.</p> <p>POINT NOT MONUMENTED</p>
41.714	The center 1/4 sec. cor. of sec. 9.

SUBDIVISION OF SECTION 9,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
62.230	Point for the C-W 1/16 sec. cor. of sec. 9. POINT NOT MONUMENTED
82.746	The 1/4 sec. cor. of secs. 8 and 9. <hr/>
	From the point for the E 1/16 sec. cor. of secs. 9 and 16. N. 0°31'20" W., on the N-S center line of the SE1/4 of sec. 9
7.60	Dirt road, 15 lks. wide, bears S. 70° E. and N. 70° W.
21.089	Point for the SE 1/16 sec. cor. of sec. 9, at intersection with the E-W center line of the SE1/4. POINT NOT MONUMENTED
42.178	The point for the C-E 1/16 sec. cor. of sec. 9. <hr/>
	From the point for the S 1/16 sec. cor. of secs. 9 and 10. N. 89°36'10" W., on the E-W center line of the SE1/4 of sec. 9.
20.913	The point for the SE 1/16 sec. cor. of sec. 9.
41.826	The C-S 1/16 sec. cor. of sec. 9. <hr/>
	From the E-E-W-E 1/1024 sec. cor. of secs. 9 and 16. N. 0°30'10" W., on the computed N-S center line of the SE1/4 of the SE1/4 of the SW1/4 of the SE1/4 of sec. 9.
5.249	Point for the C-E-SE-SW-SE 1/1024 sec. cor. of sec. 9, at its computed position. POINT NOT MONUMENTED
	N. 0°30'10" W., on the computed N-S center line of the NE1/4 of the SE1/4 of the SW1/4 of the SE1/4 of sec. 9.
3.20	Dirt road, 15 lks. wide, bears S. 70° E. and N. 70° W.
5.249	Point for the C-E-E-SW-SE 1/1024 sec. cor. of sec. 9, at its computed position. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

SUBDIVISION OF SECTION 9,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<div style="text-align: center;">1</div> <hr/> <div style="text-align: center;">1024</div> <div style="text-align: center;">2015</div>
	N. 88°34'10" W., on a portion of the E-W center line of the SW1/4 of the SE1/4 of sec. 9.
6.75	Dirt road, 15 lks. wide, bears S. 70° E. and N. 70° W.
18.333	The C-S-S 1/64 sec. cor. of sec. 9.
	<hr/> <p>From the point for the W 1/16 sec. cor. of secs. 9 and 16.</p> <p>N. 0°40'50" W., on the N-S center line of the SW1/4 of sec. 9.</p>
19.912	Point for the SW 1/16 sec. cor. of sec. 9, at intersection with the E-W center line of the SW1/4.
	POINT NOT MONUMENTED
20.30	Dirt road, 15 lks. wide, bears S. 70° E. and N. 70° W.
22.401	Point for the C-S-S-N-SW 1/1024 sec. cor. of sec. 9.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<div style="text-align: center;">1</div> <hr/> <div style="text-align: center;">1024</div> <div style="text-align: center;">2015</div>
32.357	Point for the C-S-N-N-SW 1/1024 sec. cor. of sec. 9.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<div style="text-align: center;">1</div> <hr/> <div style="text-align: center;">1024</div> <div style="text-align: center;">2015</div>
39.824	The point for the C-W 1/16 sec. cor. of sec. 9.
	<hr/> <p>From the C-S 1/16 sec. cor. of sec. 9.</p> <p>S. 89°30'10" W., on the E-W center line of the SW1/4 of sec. 9.</p>

SUBDIVISION OF SECTION 9,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
19.20	Dirt road, 15 lks. wide, bears S. 70° E. and N. 70° W.
20.401	The point for the SW 1/16 sec. cor. of sec. 9.
40.40	Dirt road, 12 lks. wide, bears N. and S.
40.50	Chain link fence, bears N. and S., enter gravel pit.
40.802	The point for the S 1/16 sec. cor. of secs. 8 and 9.
	<hr/>
	From the C-S-S-N-S 1/1024 sec. cor. of sec. 9.
	S. 89°21'20" W., on the computed E-W center line of the SE1/4 of the SE1/4 of the NE1/4 of the SW1/4 of sec. 9.
5.104	Point for the C-S-SE-NE-SW 1/1024 sec. cor. of sec. 9, at its computed position.
	POINT NOT MONUMENTED
	<hr/>
	S. 89°21'20" W., on the computed E-W center line of the SW1/4 of the SE1/4 of the NE1/4 of the SW1/4 of sec. 9.
5.104	Point for the C-S-S-NE-SW 1/1024 sec. cor. of sec. 9, at its computed position.
	POINT NOT MONUMENTED
	<hr/>
	S. 89°21'20" W., on the computed E-W center line of the SE1/4 of the SW1/4 of the NE1/4 of the SW1/4 of sec. 9.
5.104	Point for the C-S-SW-NE-SW 1/1024 sec. cor. of sec. 9, at its computed position.
	POINT NOT MONUMENTED
	<hr/>
	S. 89°21'20" W., on the E-W center line of the SW1/4 of the SW1/4 of the NE1/4 of the SW1/4 of sec. 9.
5.104	The C-S-S-N-SW 1/1024 sec. cor. of sec. 9.
	<hr/>
	From the C-S-N-N-SW 1/1024 sec. cor. of sec. 9.
	S. 88°45'50" W., on the computed E-W center line of the SE1/4 of the NE1/4 of the NW1/4 of the SW1/4 of sec. 9.
5.118	Point for the C-S-NE-NW-SW 1/1024 sec. cor. of sec. 9, at its computed position.
	POINT NOT MONUMENTED
	<hr/>

SUBDIVISION OF SECTION 9,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>S. 88°45'50" W., on the computed E-W center line of the SW1/4 of the NE1/4 of the NW1/4 of the SW1/4 of sec. 9.</p>
5.118	<p>Point for the C-S-N-NW-SW 1/1024 sec. cor. of sec. 9, at its computed position.</p> <p>POINT NOT MONUMENTED</p>
5.118	<p>S. 88°45'50" W., on the computed E-W center line of the SE1/4 of the NW1/4 of the NW1/4 of the SW1/4 of sec. 9.</p> <p>Point for the C-S-NW-NW-SW 1/1024 sec. cor. of sec. 9, at its computed position.</p> <p>POINT NOT MONUMENTED</p>
5.118	<p>S. 88°45'50" W., on the E-W center line of the SW1/4 of the NW1/4 of the NW1/4 of the SW1/4 of sec. 9.</p> <p>The S-N-N-S 1/1024 sec. cor. of secs. 8 and 9.</p>
<p style="text-align: center;">SUBDIVISION OF SECTION 14, T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA</p>	
	<p>From the 1/4 sec. cor. of secs. 14 and 23.</p> <p>N. 1°16'40" E., on the N-S center line of sec. 14.</p>
5.90	Dirt road, 15 lks. wide, bears S. 45° E. and N. 45° W.
6.20	Powerline, bears S. 45° E. and N. 45° W.
10.365	<p>Point for the C-S-S 1/64 sec. cor. of sec. 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S14 C-S-S 1/64 2015</p>
20.730	<p>Point for the C-S 1/16 sec. cor. of sec. 14.</p> <p>POINT NOT MONUMENTED</p>
30.10	Trail road, 12 lks. wide, bears S. 60° E. and N. 60° W.
37.55	Trail road, 12 lks. wide, bears S. 40° E. and N. 40° W.
41.460	Point for the center 1/4 sec. cor. of sec. 14, at intersection with the E-W center line.

SUBDIVISION OF SECTION 14,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T18S R59E C 1/4 S14 2015
82.920	The 1/4 sec. cor. of secs. 11 and 14.
	From the 1/4 sec. cor. of secs. 13 and 14. S. 87°53'00" W., on the E-W center line of sec. 14.
40.90	Trail road, 12 lks. wide, bears N. 15° E. and S. 20° W.
41.056	The center 1/4 sec. cor. of sec. 14.
44.40	Trail road, 12 lks. wide, bears S. 40° E. and N. 40° W.
61.584	Point for the C-W 1/16 sec. cor. of sec. 14. POINT NOT MONUMENTED
74.70	Powerline, bears S. 45° E. and N. 45° W.
74.90	Dirt road, 15 lks. wide, bears S. 45° E. and N. 45° W.
82.112	The 1/4 sec. cor. of secs. 14 and 15.
	From the point for the W 1/16 sec. cor. of secs. 14 and 23. N. 1°11'00" E., on the N-S center line of the SW1/4 of sec. 14.
10.137	Point for the C-S-SW 1/64 sec. cor. of sec. 14. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	S14 C-S-SW 1/64 2015
20.274	Point for the SW 1/16 sec. cor. of sec. 14, at intersection with the E-W center line of the SW1/4. POINT NOT MONUMENTED
26.50	Dirt road, 15 lks. wide, bears S. 45° E. and N. 45° E.
26.80	Powerline, bears S. 45° E. and N. 45° W.

SUBDIVISION OF SECTION 14,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.548	The point for the C-W 1/16 sec. cor. of sec. 14.
	From the point for the C-S 1/16 sec. cor. of sec. 14.
	S. 89°09'10" W., on the E-W center line of the SW1/4 of sec. 14.
14.10	Powerline, bears S. 45° E. and N. 45° W.
14.40	Dirt road, 15 lks. wide, bears S. 45° E. and N. 45° W.
20.474	The point for the SW 1/16 sec. cor. of sec. 14.
30.711	Point for the C-W-SW 1/64 sec. cor. of sec. 14.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	S14 C-W-SW 1/64 2015
40.50	Enter communication tower site, edge bears S. 21° E. and N. 21° W.
40.948	The S 1/16 sec. cor. of secs. 14 and 15.
	From the C-S-S 1/64 sec. cor. of sec. 14.
	S. 89°47'30" W., on the E-W center line of the SE1/4 of the SW1/4 of sec. 14.
4.10	Powerline, bears S. 45° E. and N. 45° W.
4.40	Dirt road, 15 lks. wide, bears S. 45° E. and N. 45° W.
20.452	The C-S-SW 1/64 sec. cor. of sec. 14.
	S. 89°47'30" W., on a portion of the computed E-W center line of the SW1/4 of the SW1/4 of sec. 14.
10.226	Point for the SW-SW 1/64 sec. cor. of sec. 14, at its computed position.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

SUBDIVISION OF SECTION 14,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">S14 SW-SW 1/64 2015</p>
10.023	<p>N. 1°08'10" E., on a portion of the N-S center line of the SW1/4 of the SW1/4 of sec. 14.</p> <p>The C-W-SW 1/64 sec. cor. of sec. 14.</p>
	<p style="text-align: center;">SUBDIVISION OF SECTION 15, T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA</p>
19.773	<p>From the 1/4 sec. cor. of secs. 15 and 22.</p> <p>N. 0°31'10" E., on the N-S center line of sec. 15.</p> <p>Point for the C-S 1/16 sec. cor. of sec. 15.</p>
39.546	<p>POINT NOT MONUMENTED</p> <p>Point for the center 1/4 sec. cor. of sec. 15, at intersection with the E-W center line.</p>
49.470	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T18S R59E C 1/4 S15 2015</p> <p>Point for the C-S-N 1/64 sec. cor. of sec. 15.</p>
59.394	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S15 C-S-N 1/64 2015</p> <p>Point for the C-N 1/16 sec. cor. of sec. 15.</p>
61.875	<p>POINT NOT MONUMENTED</p> <p>Point for the C-S-S-N-N 1/1024 sec. cor. of sec. 15.</p>

SUBDIVISION OF SECTION 15,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">1 — 1024 2015</p>
66.70	Dirt road, 15 lks. wide, bears S. 70° E. and N. 70° W.
79.242	The 1/4 sec. cor. of secs. 10 and 15.
	<hr/> <p>From the 1/4 sec. cor. of secs. 14 and 15.</p> <p>N. 89°59'00" W., on the E-W center line of sec. 15.</p>
10.226	<p>Point for the C-E-E 1/64 sec. cor. of sec. 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S15 C-E-E 1/64 2015</p>
20.452	<p>Point for the C-E 1/16 sec. cor. of sec. 15.</p> <p>POINT NOT MONUMENTED</p>
30.678	<p>Point for the C-W-E 1/64 sec. cor. of sec. 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S15 C-W-E 1/64 2015</p>
40.904	The center 1/4 sec. cor. of sec. 15.
61.130	<p>Point for the C-W 1/16 sec. cor. of sec. 15.</p> <p>POINT NOT MONUMENTED</p>
81.356	<p>The 1/4 sec. cor. of secs. 15 and 16.</p> <hr/> <p>From the point for the C-E 1/16 sec. cor. of sec. 15.</p>

SUBDIVISION OF SECTION 15,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°48'10" E., on the N-S center line of the NE1/4 of sec. 15.
19.833	Point for the NE 1/16 sec. cor. of sec. 15, at intersection with the E-W center line of the NE1/4.
	POINT NOT MONUMENTED
20.20	Dirt road, 15 lks. wide, bears S. 70° E. and N. 70° W.
28.90	Powerline, bears S. 35° E. and N. 35° W.
29.30	Dirt road, 15 lks. wide, bears S. 35° E. and N. 35° W.
39.666	The point for the E 1/16 sec. cor. of secs. 10 and 15.
	From the point for the N 1/16 sec. cor. of secs. 14 and 15.
	N. 89°56'10" W., on the E-W center line of the NE1/4 of sec. 15.
11.80	Powerline, bears S. 45° E. and N. 45° W.
12.00	Dirt road, 15 lks. wide, bears S. 45° E. and N. 45° W.
19.50	Dirt road, 15 lks. wide, bears S. 70° E. and N. 70° W.
20.549	The point for the NE 1/16 sec. cor. of sec. 15.
41.098	The point for the C-N 1/16 sec. cor. of sec. 15.
	From the C-W-E 1/64 sec. cor. of sec. 15.
	N. 0°39'40" E., on a portion of the computed N-S center line of the SW1/4 of the NE1/4 of sec. 15.
9.920	Point for the SW-NE 1/64 sec. cor. of sec. 15, at its computed position.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	S15 SW-NE 1/64 2015
	N. 89°57'30" W., on a portion of the E-W center line of the SW1/4 of the NE1/4 of sec. 15.
10.250	The C-S-N 1/64 sec. cor. of sec. 15.
	From the point for the E 1/16 sec. cor. of secs. 15 and 22.
	N. 0°48'10" E., on the N-S center line of the SE1/4 of sec. 15.

SUBDIVISION OF SECTION 15,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
19.795	Point for the SE 1/16 sec. cor. of sec. 15, at intersection with the E-W center line of the SE1/4.
	POINT NOT MONUMENTED
39.590	The point for the C-E 1/16 sec. cor. of sec. 15.
	From the S 1/16 sec. cor. of secs. 14 and 15.
	N. 89°55'30" W., on the E-W center line of the SE1/4 of sec. 15.
8.10	Exit communication tower site, edge bears N. 21° W. and S. 21° E.
20.355	The point for the SE 1/16 sec. cor. of sec. 15.
40.710	The point for the C-S 1/16 sec. cor. of sec. 15.
	From the N-S 1/64 sec. cor. of secs. 14 and 15.
	N. 89°57'20" W., on a portion of the computed E-W center line of the NE1/4 of the SE1/4 of sec. 15.
2.90	Dirt road, 15 lks. wide, bears N. 50° E. and S. 50° W.
3.55	Enter communication tower site, edge bears S. 21° E. and N. 21° W.
10.202	Point for the NE-SE 1/64 sec. cor. of sec. 15, at its computed position.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	S15 NE-SE 1/64 2015
	N. 0°56'40" E., on a portion of the N-S center line of the NE1/4 of the SE1/4 of sec. 15.
3.10	Exit communication tower site, edge bears N. 69° E. and S. 69° W.
9.903	The C-E-E 1/64 sec. cor. of sec. 15.
	From the point for the C-W 1/16 sec. cor. of sec. 15.
	N. 0°05'20" W., on the N-S center line of the NW1/4 of sec. 15.

SUBDIVISION OF SECTION 15,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
19.865	Point for the NW 1/16 sec. cor. of sec. 15, at the intersection with the E-W center line of the NW1/4. POINT NOT MONUMENTED
22.348	Point for the C-S-S-N-NW 1/1024 sec. cor. of sec. 15. POINT NOT MONUMENTED
34.10	Dirt road, 15 lks. wide, bears S. 70° E. and N. 70° W.
39.730	The point for the W 1/16 sec. cor. of secs. 10 and 15. <hr/>
	From the point for the C-N 1/16 sec. cor. of sec. 15. N. 89°56'10" W., on the E-W center line of the NW1/4 of sec. 15.
20.436	The point for the NW 1/16 sec. cor. of sec. 15.
40.872	The point for the N 1/16 sec. cor. of secs. 15 and 16. <hr/>
	From the C-S-S-N-N 1/1024 sec. cor. of sec. 15. N. 89°55'50" W., on the computed E-W center line of the SE1/4 of the NE1/4 of the NW1/4 of sec. 15.
5.116	Point for the C-S-SE-NE-NW 1/1024 sec. cor. of sec. 15, at its computed position. POINT NOT MONUMENTED <hr/>
	N. 89°55'50" W., on the computed E-W center line of the SW1/4 of the SE1/4 of the NE1/4 of the NW1/4 of sec. 15.
5.116	Point for the C-S-S-NE-NW 1/1024 sec. cor. of sec. 15, at its computed position. POINT NOT MONUMENTED <hr/>
	N. 89°55'50" W., on the computed E-W center line of the SE1/4 of the SW1/4 of the NE1/4 of the NW1/4 of sec. 15.
5.116	Point for the C-S-SW-NE-NW 1/1024 sec. cor. of sec. 15, at its computed position. POINT NOT MONUMENTED <hr/>
	N. 89°55'50" W., on the E-W center line of the SW1/4 of the SW1/4 of the NE1/4 of the NW1/4 of sec. 15.
5.116	The point for the C-S-S-N-NW 1/1024 sec. cor. of sec. 15. <hr/>

SUBDIVISION OF SECTION 15,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
2.558	<p>N. 89°55'50" W., on a portion of the computed E-W center line of the SE1/4 of the SE1/4 of the NW1/4 of the NW1/4 of sec. 15.</p> <p>Point for the SE-SE-NW-NW 1/1024 sec. cor. of sec. 15, at its computed position.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: right;"> $\frac{1}{1024}$ 2015 </div>
2.484	<p>N. 0°09'50" W., on a portion of the computed N-S center line of the SE1/4 of the SE1/4 of the NW1/4 of the NW1/4 of sec. 15.</p> <p>Point for the C-E-SE-NW-NW 1/1024 sec. cor. of sec. 15, at its computed position.</p> <p>POINT NOT MONUMENTED</p>
4.967	<p>N. 0°09'50" W., on the computed N-S center line of the NE1/4 of the SE1/4 of the NW1/4 of the NW1/4 of sec. 15.</p> <p>Point for the C-E-E-NW-NW 1/1024 sec. cor. of sec. 15, at its computed position.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: right;"> $\frac{1}{1024}$ 2015 </div>
10.270	<p>N. 89°54'40" W, on a portion of the computed E-W center line of the NW1/4 of the NW1/4 of sec. 15.</p> <p>Point for the C-E-W-NW-NW 1/1024 sec. cor. of sec. 15, at its computed position.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

SUBDIVISION OF SECTION 15,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<div>1</div> <hr/> <div>1024</div> <div>2015</div>
	<hr/> <p>N. 0°28'10" W, on the computed N-S center line of the SE1/4 of the NW1/4 of the NW1/4 of the NW1/4 of sec. 15.</p>
4.969	<p>Point for the C-E-NW-NW-NW 1/1024 sec. cor. of sec. 15, at its computed position.</p> <p>POINT NOT MONUMENTED</p>
	<hr/> <p>N. 0°28'10" W, on the N-S center line of the NE1/4 of the NW1/4 of the NW1/4 of the NW1/4 of sec. 15.</p>
3.70	Dirt road, 15 lks. wide, bears S. 70° E. and N. 70° W.
4.969	The E-W-W-W 1/1024 sec. cor. of secs. 10 and 15.
	<hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 23, T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 23 and 26, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 18 S., R. 59 E., executed under Group No. 612.</p> <p>Cor. is located on N. edge of gravel road, 15 lks. wide, and alongside chain link fence, both bear E. and W.</p> <p>N. 0°09'00" E., on the N-S center line of sec. 23.</p>
40.863	<p>The center 1/4 sec. cor. of sec. 23, determined by Rita M. Lumos, Nevada Professional Land Surveyor No. 5094, in 2004, monumented with an aluminum cap, 3 1/4 ins. diam., firmly set in concrete flush with the ground, and in a collar of stone, with top mkd. CITY OF LAS VEGAS T18S R59E C 1/4 S23 PLS 5094 2004, as recorded in Clark County, Nevada, File 135, Page 67 of Surveys, with a steel fence post firmly set alongside. This is accepted as a careful and faithful determination of the position of the corner.</p>
	<hr/> <p>N. 0°09'00" E., beginning new measurement.</p>
20.408	<p>Point for the C-N 1/16 sec. cor. of sec. 23.</p> <p>POINT NOT MONUMENTED</p>
35.10	Dirt road, 15 lks. wide, bears N. 40° E. and S. 40° W.

SUBDIVISION OF SECTION 23,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.816	The 1/4 sec. cor. of secs. 14 and 23.
	From the 1/4 sec. cor. of secs. 23 and 24.
	N. 89°34'10" W., on the E-W center line of sec. 23.
20.467	Point for the C-E 1/16 sec. cor. of sec. 23.
	POINT NOT MONUMENTED
40.934	The center 1/4 sec. cor. of sec. 23.
	N. 89°34'10" W., beginning new measurement.
31.60	Dirt road, 15 lks. wide, bears N. 40° E. and S. 40° W.
40.945	The 1/4 sec. cor. of secs. 22 and 23, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 18 S., R. 59 E., executed under Group No. 612, with a mound of stone, 2 1/2 ft. diam., 1 1/2 ft. high, W. of cor.
	From the point for the C-E 1/16 sec. cor. of sec. 23.
	N. 0°06'00" E., on the N-S center line of the NE1/4 of sec. 23.
20.408	Point for the NE 1/16 sec. cor. of sec. 23, at intersection with the E-W center line of the NE1/4.
	POINT NOT MONUMENTED
25.90	Dirt road, 15 lks. wide, bears S. 45° E. and N. 45° W.
26.20	Powerline, bears S. 45° E. and N. 45° W.
40.816	The point for the E 1/16 sec. cor. of secs. 14 and 23.
	From the N 1/16 sec. cor. of secs. 23 and 24.
	N. 89°34'10" W., on the E-W center line of the NE1/4 of sec. 23.
2.50	Trail road, 12 lks. wide, bears S. 50° E. and N. 50° W.
14.80	Powerline, bears S. 45° E. and N. 45° W.
15.10	Dirt road, 15 lks. wide, bears S. 45° E. and N. 45° W.
20.448	The point for the NE 1/16 sec. cor. of sec. 23.
40.896	The point for the C-N 1/16 sec. cor. of sec. 23.

SUBDIVISION OF SECTION 23,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	From the N-N 1/64 sec. cor. of secs. 23 and 24. N. 89°34'10" W., on a portion of the computed E-W center line of the NE1/4 of the NE1/4 of sec. 23.
6.40	Trail road, 12 lks. wide, bears S. 10° E. and N. 10° W.
10.220	Point for the NE-NE 1/64 sec. cor. of sec. 23, at its computed position. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. S23 NE-NE 1/64 2015
10.204	N. 0°04'30" E., on a portion of the N-S center line of the NE1/4 of the NE1/4 of sec. 23. The E-E 1/64 sec. cor. of secs. 14 and 23.
SUBDIVISION OF SECTION 24 T. 18 S., R. 59E., MOUNT DIABLO MERIDIAN, NEVADA	
	From the 1/4 sec. cor. of secs. 24 and 25. N. 0°12'50" E., on the N-S center line of sec. 24.
0.90	Dirt road, 15 lks. wide, bears S. 45° E. and N. 45° W.
1.10	Powerline, bears S. 45° E. and N. 45° W.
10.40	Trail road, 12 lks. wide, bears S. 35° E. and N. 35° W.
20.407	Point for the C-S 1/16 sec. cor. of sec. 24. POINT NOT MONUMENTED
40.814	The center 1/4 sec. cor. of sec. 24, determined by Rita M. Lumos, Nevada Professional Land Surveyor No. 5094, in 2004, monumented with an aluminum cap, 3 1/4 ins. diam., firmly set in concrete flush with the ground, and in a collar of stone, with top mkd. CITY OF LAS VEGAS T18S R59E C 1/4 24 PLS 5094 2004, as recorded in Clark County, Nevada, File 135, Page 67 of Surveys, with a steel fence post firmly set alongside. This is accepted as a careful and faithful determination of the position of the corner.
8.40	N. 0°12'50" E., beginning new measurement. Trail road, 12 lks. wide, bears S. 50° E. and N. 50° W.

SUBDIVISION OF SECTION 24,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
12.70	Wash, 2 chs. wide, drains S. 70° E.
20.386	Point for the C-N 1/16 sec. cor. of sec. 24.
	POINT NOT MONUMENTED
40.772	The 1/4 sec. cor. of secs. 13 and 24.
	<hr/> <p>From the 1/4 sec. cor. of secs. 19 and 24, on the E. bdy. of the Tp., monumented with an aluminum cap, 3 1/4 ins. diam., firmly set in concrete flush with the ground, with top mkd. as described in the field notes of the dependent resurvey of a portion of the E. bdy., T. 18 S., R. 59 E., executed under Group No. 881, with a steel fence post firmly set alongside.</p> <p>S. 86°21'30" W., on the E-W center line of sec. 24.</p>
4.80	Wash, 2 chs. wide, drains S. 30° W.
26.60	Wash, 2 chs. wide, drains S. 40° E.
32.70	Trail road, 12 lks. wide, bears S. 45° E. and N. 45° W.
40.921	The center 1/4 sec. cor. of sec. 24.
	<hr/> <p>S. 86°21'30" W., beginning new measurement.</p>
10.233	Point for the C-E-W 1/64 sec. cor. of sec. 24.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S24 C-E-W 1/64</p> <p style="text-align: center;">2015</p>
20.466	Point for the C-W 1/16 sec. cor. of sec. 24.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">W 1/16 C——C S24</p> <p style="text-align: center;">2015</p>
22.00	Trail road, 12 lks. wide, bears S. 35° E. and N. 50° W.
36.20	Powerline, bears S. 45° E. and N. 45° W.
36.50	Dirt road, 15 lks. wide, bears S. 45° E. and N. 45° W.

SUBDIVISION OF SECTION 24,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.932	The 1/4 sec. cor. of secs. 23 and 24.
	From the point for the W 1/16 sec. cor. of secs. 24 and 25. N. 0°06'40" E., on the N-S center line of the SW1/4 of sec. 24.
10.216	Point for the C-S-SW 1/64 sec. cor. of sec. 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;">S24 C-S-SW 1/64 2015</div>
20.432	Point for the SW 1/16 sec. cor. of sec. 24 at intersection with the E-W center line of the SW1/4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;">SW 1/16 S24 2015</div>
23.30	Dirt road, 15 lks. wide, bears S. 45° E. and N. 45° W.
23.60	Powerline, bears S. 45° E. and N. 45° W.
38.55	Trail road, 12 lks. wide, bears S. 35° E. and N. 35° W.
40.864	The C-W 1/16 sec. cor. of sec. 24.
	From the point for the C-S 1/16 sec. cor. of sec. 24. S. 86°17'10" W., on the E-W center line of the SW1/4 of sec. 24.
8.00	Trail road, 12 lks. wide, bears S. 40° E. and N. 30° W.
10.216	Point for the C-E-SW 1/64 sec. cor. of sec. 24. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;">S24 C-E-SW 1/64 2015</div>
17.60	Powerline, bears S. 45° E. and N. 45° W.

SUBDIVISION OF SECTION 24,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
17.80	Dirt road, 15 lks. wide, bears S. 45° E. and N. 45° W.
20.432	The SW 1/16 sec. cor. of sec. 24.
40.864	The point for the S 1/16 sec. cor. of secs. 23 and 24.
	<hr/> <p>From the C-E-SW 1/64 sec. cor. of sec. 24.</p> <p>N. 0°09'50" E., on the N-S center line of the NE1/4 of the SW1/4 of sec. 24.</p>
4.50	Trail road, 12 lks. wide, bears S. 40° E. and N. 40° W.
20.419	The C-E-W 1/64 sec. cor. of sec. 24.
	<hr/> <p>From the W-W 1/64 sec. cor. of secs. 24 and 25.</p> <p>N. 0°03'40" E., on a portion of the computed N-S center line of the SW1/4 of the SW1/4 of sec. 24.</p>
10.222	<p>Point for the SW-SW 1/64 sec. cor. of sec. 24, at its computed position.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S24 SW-SW 1/64</p> <p style="text-align: center;">2015</p>
	<hr/> <p>N. 86°14'50" E., on a portion of the E-W center line of the SW1/4 of the SW1/4 of sec. 24.</p>
10.208	The C-S-SW 1/64 sec. cor. of sec. 24.
	<hr/> <p>From the C-W 1/16 sec. cor. of sec. 24.</p> <p>N. 0°07'50" E., on the N-S center line of the NW1/4 of sec. 24.</p>
10.199	<p>Point for the C-S-NW 1/64 sec. cor. of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>


SUBDIVISION OF SECTION 24,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">S24 C-S-NW 1/64</p> <p style="text-align: center;">2015</p>
19.80	Trail road, 12 lks. wide, bears S. 50° E. and N. 50° W.
20.398	Point for the NW 1/16 sec. cor. of sec. 24, at intersection with the E-W center line of the NW1/4.
	POINT NOT MONUMENTED
21.80	Wash, 3 chs. wide, drains S. 60° E.
40.796	The point for the W 1/16 sec. cor. of secs. 13 and 24.
	<hr/> <p>From the point for the C-N 1/16 sec. cor. of sec. 24. S. 86°23'50" W., on the E-W center line of the NW1/4 of sec. 24.</p>
18.30	Wash, 3 chs. wide, drains S. 60° E.
20.492	The point for the NW 1/16 sec. cor. of sec. 24.
21.10	Trail road, 12 lks. wide, bears S. 50° E. and N. 50° W.
30.738	Point for the C-W-NW 1/64 sec. cor. of sec. 24.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<p style="text-align: center;">S24 C-W-NW 1/64</p> <p style="text-align: center;">2015</p>
40.984	The N 1/16 sec. cor. of secs. 23 and 24.
	<hr/> <p>From the C-S-NW 1/64 sec. cor. of sec. 24. S. 86°22'40" W., on a portion of the computed E-W center line of the SW1/4 of the NW1/4 of sec. 24.</p>
10.239	Point for the SW-NW 1/64 sec. cor. of sec. 24, at its computed position.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.



SUBDIVISION OF SECTION 24,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div style="text-align: center;">S24 SW-NW 1/64 2015</div> <hr/> <p>N. 0°05'30" E., on a portion of the N-S center line of the SW1/4 of the NW1/4 of sec. 24.</p> <p>10.201 The C-W-NW 1/64 sec. cor. of sec. 24.</p> <hr/> <p style="text-align: center;">METES-AND-BOUNDS SURVEY OF THE EASTERLY RIGHT-OF-WAY LINE OF U.S. HIGHWAY NO. 95, THROUGH SECTIONS 6 AND 7, AND A PORTION OF SECTION 8, T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">MEMORANDUM</p> <p>The following metes-and-bounds survey identifies the easterly right-of-way line of U.S. Highway No. 95, through sections 6 and 7 and a portion of section 8, as shown on sheets 16 through 18 of State of Nevada, Department of Highways, Right-of-Way Division Property Schedule Map Supplement to Application CC-018191. It begins at the E-W center line of the SE1/4 of the NE1/4 of the NE1/4 of the SW1/4 of section 8 and ends at the intersection with the north boundary of the township.</p> <hr/> <p>From the point for a witness point, at the intersection of the easterly right-of-way line of U.S. Highway No. 95, with the E-W center line of the SE1/4 of the NE1/4 of the NE1/4 of the SW1/4 of sec. 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p style="margin-left: 100px;">WP T18S R59E S S-N-N-S — 8 — S-N-N-S</p> </div> <p style="text-align: center;">2015</p> <p>From this point, the C-S-N-N-S 1/1024 sec. cor. of sec. 8, hereinbefore described, bears S. 86°18'10" E., 2.673 chs. dist.</p> <p>From this same point, Nevada Department of Transportation highway station 1093093, utilized to determine the easterly right-of-way line, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA N 291+01.35 POT DIST 76.63 1093093H, with a steel fence post firmly set alongside, bears S. 44°17'27" E., 101.302 chs. dist.</p>
--------	--

METES-AND-BOUNDS SURVEY OF
THE EASTERLY RIGHT-OF-WAY LINE OF U.S. HIGHWAY NO. 95,
THROUGH SECTIONS 6 AND 7, AND A PORTION OF SECTION 8,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From this same point, Nevada Department of Transportation highway station 1093095, not utilized to determine the easterly right-of-way line, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA N 338+79.35 DIST 83.16 1093095H, with steel fence post firmly set alongside, bears S. 44°13'40" E., 28.898 chs. dist.</p> <p>From this same point, Nevada Department of Transportation highway station 1093092, utilized to determine the easterly right-of-way line, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA S 291+01.35 POT DIST 58.37 1093092H, with a steel fence post firmly set alongside, bears S. 42°12'35" E., 101.372 chs. dist.</p> <p>From this same point, Nevada Department of Transportation highway station 1093094, utilized to determine the easterly right-of-way line, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA S 338+79.35 DIST 59.17 1093094H, with a steel fence post firmly set alongside, bears S. 36°56'20" E., 29.138 chs. dist.</p> <p>N. 44°19'40" W., on the easterly right-of-way line of U.S. Highway No. 95, through a portion of sec. 8.</p>
11.276	<p>Point for a witness point, at the intersection of the easterly right-of-way line of U.S. Highway No. 95, with the E-W center line of sec. 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>WP</p> <p>T18S R59E</p>  <p>2015</p> </div>
13.90	<p>From this point, the point for the C-W 1/16 sec. cor. of sec. 8, hereinbefore described, bears N. 86°00'50" W., 9.931 chs. dist.</p>
28.897	<p>Trail road, 15 lks. wide, bears S. 70° E. and N. 45° W.</p>
	<p>Wood post, 4x4 ins., firmly set, projecting 3 1/2 ft. above the ground.</p> <p>From this point, Nevada Department of Transportation highway station 1093097, utilized to determine the easterly right-of-way line, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA N 376+93.44 DIST 60.05 1093097H, bears S. 45°40'20" W., 0.302 chs. dist.</p>

METES-AND-BOUNDS SURVEY OF
THE EASTERLY RIGHT-OF-WAY LINE OF U.S. HIGHWAY NO. 95,
THROUGH SECTIONS 6 AND 7, AND A PORTION OF SECTION 8,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From this same point, Nevada Department of Transportation highway station 1093096, utilized to determine the easterly right-of-way line, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA S 376+93.44 DIST 109.96 1093096H, with a steel fence post firmly set alongside, bears S. 45°40'20" W., 4.515 chs. dist.</p>
41.121	<p>Wood post, 4x4 ins., firmly set, projecting 3 1/2 ft. above the ground.</p>
	<p>From this point, a Nevada Department of Transportation highway station, not utilized to determine the easterly right-of-way line monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA NS 402+72.38 DIST 70.04, with a steel fence post firmly set alongside, bears S. 45°40'20" W., 0.155 chs. dist.</p>
54.895	<p>Point for a witness point, at the intersection of the easterly right-of-way line of U.S. Highway No. 95, with the line bet. secs. 7 and 8.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<div style="text-align: center;"> <p>WP T18S R59E</p>  <p>2015</p> </div>
	<p>From this point, the cor. of secs. 5, 6, 7 and 8, hereinbefore described, bears N. 0°24'50" W., 12.051 chs. dist.</p>
	<p>N. 44°19'50" W., on the easterly right-of-way line of U.S. Highway No. 95, through sec. 7.</p>
13.082	<p>Wood post, 4x4 ins., firmly set, projecting 3 1/2 ft. above the ground.</p>
16.617	<p>Point for a witness point, at the intersection of the easterly right-of-way line of U.S. Highway No. 95, with the line bet. secs. 6 and 7.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<div style="text-align: center;"> <p>WP T18S R59E</p>  <p>2015</p> </div>

METES-AND-BOUNDS SURVEY OF
THE EASTERLY RIGHT-OF-WAY LINE OF U.S. HIGHWAY NO. 95,
THROUGH SECTIONS 6 AND 7, AND A PORTION OF SECTION 8,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From this point, the cor. of secs. 5, 6, 7 and 8, hereinbefore described, bears N. 89°11'10" E., 11.525 chs. dist.</p> <hr/> <p>N. 44°20'10" W., on the easterly right-of-way line of U.S. Highway No. 95, through sec. 6.</p>
25.808	Wood post, 4x4 ins., firmly set, projecting 3 1/2 ft. above the ground.
39.761	<p>Point for a witness point, at point of curvature, monumented with a wood post, 4x4 ins., firmly set, projecting 3 1/2 ft. above the ground.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 2°42'30" E., 1.644 chs. dist., with brass cap mkd. RM T18S R59E WP S6 108.5 FT TO COR 2015, and an arrow pointing to the corner.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 83°37'30" E., 1.529 chs. dist., with brass cap mkd. RM T18S R59E WP S6 100.9 FT TO COR 2015, and an arrow pointing to the corner.</p> <p>From this point, Nevada Department of Transportation highway station 1093099, utilized to determine the easterly right-of-way line, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA NC 431+30.46 DIST 70.07 1093099H, with a steel fence post firmly set alongside, bears S. 45°39'50" W., 0.150 chs. dist.</p> <p>From this same point, Nevada Department of Transportation highway station 1093098, utilized to determine the easterly right-of-way line, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA SC 431+30.46 DIST 70.22 1093098H, with a steel fence post firmly set alongside, bears S. 45°39'50" W., 3.912 chs. dist.</p> <hr/> <p>Thence along the arc of a circular curve to the right; having a radius of 9812.00 ft.; the chord of said arc bearing N. 35°16'43" W., 46.808 chs. dist.</p>
12.974	<p>Wood post, 4x4 ins., firmly set, projecting 3 1/2 ft. above the ground.</p> <p>From this point, a Nevada Department of Transportation highway station, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA NC 439+95.70 DIST 70.00, bears S. 50°39'50" W., 0.152 chs. dist.</p>
25.016	Wood post, 4x4 ins., firmly set, projecting 3 1/2 ft. above the ground.

METES-AND-BOUNDS SURVEY OF
THE EASTERLY RIGHT-OF-WAY LINE OF U.S. HIGHWAY NO. 95,
THROUGH SECTIONS 6 AND 7, AND A PORTION OF SECTION 8,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From this point, a Nevada Department of Transportation highway station, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA NC 447+94.48 DIST 70.02, bears S. 55°18'20" W., 0.151 chs. dist.</p> <p>37.046 Wood post, 4x4 ins., firmly set, projecting 3 1/2 ft. above the ground.</p> <p>From this point, a Nevada Department of Transportation highway station, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA NC 455+95.25 DIST 69.96, with a steel fence post firmly set alongside, bears S. 59°56'30" W., 0.152 chs. dist.</p> <p>47.004 Point for a witness point on curve.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">WP T18S R59E</p> <p style="text-align: center;">S \ 6</p> <p style="text-align: center;">2020</p> <p>From this point, point of tangency bears N. 25°38'35" W., 3.013 chs. dist., monumented with a wood post, 4x4 ins., firmly set, projecting 3 1/2 ft. above the ground.</p> <p>From this point of tangency, Nevada Department of Transportation highway station 1093101, utilized to determine the easterly right-of-way line, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA NC 464+94.82 DIST 70.04 1093101H, with a steel fence post firmly set alongside, bears S. 64°56'20" W., 0.151 chs. dist.</p> <p>From this same point of tangency, Nevada Department of Transportation highway station 1093100, utilized to determine the easterly right-of-way line, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA SC 464+94.82 DIST 69.99, bears S. 64°56'20" W., 3.909 chs. dist.</p> <p>From this same point of tangency, a concrete pillar, 6x6 ins., firmly set, projecting 8 ins. above the ground, with a nail set on top, bears N. 31°29'30" W., 0.027 chs. dist.</p> <hr/> <p>N. 12°05'20" W., continuing on the easterly right-of-way line of U.S. Highway No. 95, through sec. 6.</p>
--------	---

METES-AND-BOUNDS SURVEY OF
THE EASTERLY RIGHT-OF-WAY LINE OF U.S. HIGHWAY NO. 95,
THROUGH SECTIONS 6 AND 7, AND A PORTION OF SECTION 8,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 15.431</p>	<p>The witness point, at the intersection of the easterly right-of-way line of U.S. Highway No. 95, with the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, flush in a collar of stone, with brass cap mkd. as described in the field notes of the metes-and-bounds survey of the easterly right-of-way line of U.S. Highway No. 95, through sec. 36, T. 17 S., R. 59 E., executed concurrently under this same Group.</p> <p>From this point, the cor. of Tps. 17 and 18 S., Rs. 58 and 59 E., bears S. 89°41'30" W., 8.466 chs. dist.</p> <hr/> <p style="text-align: center;">METES-AND-BOUNDS SURVEY OF THE RED ROCK CANYON NATIONAL CONSERVATION AREA BOUNDARY, THROUGH A PORTION OF SECTION 7, AND THROUGH SECTIONS 8, 16, 17 AND 21, T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">MEMORANDUM</p> <p>The following metes-and-bounds survey identifies a portion of the Red Rock Canyon National Conservation Area boundary as determined by an Administrative Survey of the Red Rock Canyon National Conservation Area boundary executed concurrently with this survey.</p> <hr/> <p>From the beginning point of the northeasterly boundary of the Red Rock Canyon National Conservation Area, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap, 3 1/4 ins. diam., mkd. T18S R59E S21 S22 RRCNCA 1 2020.</p> <p>From this point, the 1/4 sec. cor. of secs. 21 and 22, hereinbefore described, bears N. 0°31'00" E., 12.181 chs. dist.</p> <p>N. 44°18'10" W., on the Red Rock Canyon National Conservation Area boundary through sec. 21.</p> <p>37.285 Point for a witness point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>WP T18S R59E S 21 2020</p> </div> <p>74.570 Point for a witness point, at the intersection of the Red Rock Canyon National Conservation Area boundary, with the line bet. secs. 16 and 21.</p>
--------------------------	---

METES-AND-BOUNDS SURVEY OF THE RED ROCK CANYON NATIONAL
CONSERVATION AREA BOUNDARY, THROUGH A PORTION OF SECTION 7,
AND THROUGH SECTIONS 8, 16, 17 AND 21,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA


CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="876 383 1031 528"> <p>WP T18S R59E S 16 S 21</p> </div> <p>2020</p> <p>From this point, the 1/4 sec. cor. of secs. 16 and 21, hereinbefore described, bears S. 89°47'00" E., 11.332 chs. dist.</p>
42.888	<p>N. 44°18'20" W., on the Red Rock Canyon National Conservation Area boundary through sec. 16.</p> <p>Point for a witness point, at the intersection of the Red Rock Canyon National Conservation Area boundary, with the line bet. secs. 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="876 984 1031 1160"> <p>WP T18S R59E S 17 S 16</p> </div> <p>2020</p> <p>From this point, the 1/4 sec. cor. of secs. 16 and 17, hereinbefore described, bears N. 0°07'10" W., 10.025 chs. dist.</p>
36.916	<p>N. 44°18'40" W., on the Red Rock Canyon National Conservation Area boundary through sec. 17.</p> <p>Point for a witness point.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

METES-AND-BOUNDS SURVEY OF THE RED ROCK CANYON NATIONAL
CONSERVATION AREA BOUNDARY, THROUGH A PORTION OF SECTION 7,
AND THROUGH SECTIONS 8, 16, 17 AND 21,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
73.832	<div data-bbox="878 277 1024 451" data-label="Diagram"> </div> <p>Point for a witness point, at the intersection of the Red Rock Canyon National Conservation Area boundary, with the line bet. secs. 8 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="878 696 1024 895" data-label="Diagram"> </div> <p>From this point, the 1/4 sec. cor. of secs. 8 and 17, hereinbefore described, bears S. 87°33'00" E., 10.555 chs. dist.</p> <hr/> <p>N. 44°19'00" W., on the Red Rock Canyon National Conservation Area boundary through sec. 8.</p>
14.332	<p>Point for a witness point, at the intersection of the Red Rock Canyon National Conservation Area boundary, with the N-S center line of the SW1/4 of sec. 8.</p> <p>POINT NOT MONUMENTED</p> <p>From this point, the W 1/16 sec. cor. of secs. 8 and 17, hereinbefore described, bears S. 0°33'30" E., 9.831 chs. dist.</p>
29.808	<p>Point for a witness point, at the intersection of the Red Rock Canyon National Conservation Area boundary, with the E-W center line of the SW1/4 of sec. 8.</p> <p>POINT NOT MOMUMENTED</p> <p>From this point, the point for the S 1/16 sec. cor. of secs. 7 and 8, hereinbefore described, bears N. 86°47'00" W., 9.717 chs. dist.</p>
43.793	<p>Point for a witness point, at the intersection of the Red Rock Canyon National Conservation Area boundary, with the line bet. secs. 7 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

METES-AND-BOUNDS SURVEY OF THE RED ROCK CANYON NATIONAL
CONSERVATION AREA BOUNDARY, THROUGH A PORTION OF SECTION 7,
AND THROUGH SECTIONS 8, 16, 17 AND 21,
T. 18 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS



2020


From this point, the point for the S 1/16 sec. cor. of secs. 7 and 8, hereinbefore described, bears S. $0^{\circ}24'50''$ E., 9.461 chs. dist.

N. $44^{\circ}19'10''$ W., on the Red Rock Canyon National Conservation Area boundary through a portion of sec. 7.

15.289

Point for a witness point, at the intersection of the Red Rock Canyon National Conservation Area boundary, with the E-W center line of sec. 7.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.



2020

From this point, an angle point in the northeasterly boundary of the Red Rock Canyon National Conservation Area, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap, 3 1/4 ins. diam., mkd. T18S R58E RRCNCA 1 2020, bears N. $44^{\circ}19'30''$ W., 100.244 chs. dist.

From this same point, the 1/4 sec. cor. of secs. 7 and 8, hereinbefore described, bears N. $89^{\circ}03'40''$ E., 10.603 chs. dist.

GENERAL DESCRIPTION

The lands included in this survey are located approximately 5 miles north of the northern edge of North Las Vegas, in Clark County, Nevada. Access is provided by U.S. Highway No. 95, and numerous dirt roads. The area is fairly level. Vegetation consists of various grasses, greasewood, sagebrush, Joshua trees, and various cacti. The average elevation of the area is approximately 3,000 ft. above sea level.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Brock R. Clifford	Supervisory Cadastral Surveyor
Carlos Gil-Mendoza	Cadastral Surveyor
Joseph J. Johnson	Cadastral Surveyor
Lucas T. Beauchamp	Student Trainee (Land Surveyor)
Wyatt B. Butler	Student Trainee (Land Surveyor)
Austin D. Garner	Student Trainee (Land Surveyor)

CERTIFICATE OF SURVEY

I, Brandon G. Courtright, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing the date of the 6th day of May, 2015, and supplemental special instructions bearing the date of the 10th day of July, 2015, I have dependently resurveyed a portion of the west boundary, a portion of the subdivisional lines, subdivided certain sections, executed a metes-and-bounds survey of the easterly right-of-way line of U.S. Highway No. 95, through sections 6 and 7 and a portion of section 8, and executed a metes-and-bounds survey of the Red Rock Canyon National Conservation Area boundary, through a portion of section 7 and through sections 8, 16, 17 and 21, Township 18 South, Range 59 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

AUG 10 2020

(Date)

Michael O. Hammer

/For Brandon G. Courtright
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of the dependent resurvey of a portion of the west boundary, a portion of the subdivisional lines, the subdivision of certain sections, a metes-and-bounds survey of the easterly right-of-way line of U.S. Highway No. 95 through sections 6 and 7, and a portion of section 8, and a metes-and-bounds survey of the Red Rock Canyon National Conservation Area boundary, through a portion of section 7 and through sections 8, 16, 17 and 21, Township 18 South, Range 59 East, of the Mount Diablo Meridian, Nevada, executed by Brandon G. Courtright, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

AUG 10 2020

(Date)

Michael O. Hammer
(Chief Cadastral Surveyor for Nevada)

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above described surveys in Township 18 South, Range 59 East, Mount Diablo Meridian, Nevada, is a true copy of the original field notes.

(Date)

(Chief Cadastral Surveyor for Nevada)