

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

OF THE

DEPENDENDT RESURVEY

OF

A PORTION OF THE EAST BOUNDARY

AND

A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF SECTIONS 25, 26 and 27,

TOWNSHIP 18 SOUTH, RANGE 60 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATE OF NEVADA

EXECUTED BY

Steven E. Dagitz, Cadastral Surveyor

Brock R. Clifford, Cadastral Surveyor

Under Special Instructions dated July 16, 2009,

and approved July 16, 2009,

which provided for the surveys included under Group No. 881,

and Assignment Instructions dated July 21, 2009.

Survey commenced July 21, 2009

Survey completed February 12, 2010

INDEX DIAGRAM

TOWNSHIP 18 SOUTH, RANGE 60 EAST, MOUNT DIABLO MERIDIAN, NEVADA

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
9	9	8			
19	20	21	8 22	23	24
30	29	28	7 27	6 26	5 25
				6	5 3
31	32	33	34	35	4 36 2

Subdivision of Section 25 p. 10.
 Subdivision of Section 26 p. 10.
 Subdivision of Section 27..... p. 10.

TOWNSHIP 18 SOUTH, RANGE 60 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>The following field notes are those of the dependent resurvey of a portion of the east boundary and a portion of the subdivisional lines, and the subdivision of sections 25, 26 and 27, Township 18 South, Range 60 East, Mount Diablo Meridian, Nevada.</p> <p>The west boundary was surveyed by U.S. Deputy Surveyor E. A. Carter in 1881 under Contract No. 128. The north, south and east boundaries and the subdivisional lines were surveyed by U.S. Deputy Surveyors R.H. Woods and W.H Myrick in 1882 under Contract No. 111. A portion of the south boundary was dependently resurveyed by Cartographic Survey Aid P.K. Russell in 1956 under Group No. 357. The cor. of Tps. 18 and 19 S., Rs. 60 and 61 E., was remonumented by Cadastral Surveyor N.R. Forsyth in 1990 under Group No. 683. A portion of the west boundary was dependently resurveyed by Cadastral Surveyor J.A. Mack in 1984 under Group No. 612. A portion of the south boundary was dependently resurveyed by Cadastral Surveyor R.A. Pratt in 1990 under Group No. 688.</p> <p>A dependent resurvey of a portion of the west boundary was executed concurrently under T. 18 S., R. 59 E., of this same group.</p> <p>Before restoring the corners, the lines of the original surveys were retraced and a diligent search made for any evidence of the original corners and other calls of the original field note record.</p> <p>The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.</p> <p>The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 881, dated July 16, 2009.</p> <p>Measurements were made with Trimble R8-2 and 5800 Global Positioning System (GPS) receivers using the real-time kinematic (RTK) method and refer to the true meridian based on geodetic methods. The mean bearings of the lines and horizontal equivalents of ground distances only are entered in the field notes.</p> <p>The NAD 83 (CORS 96) geographic position of the cor. of Tps. 18 and 19 S., Rs. 60 and 61 E., determined from GPS static observations processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) TROPICANA CORS ARP, CARLTON SQUARE 2 CORS ARP, and BERMUDA CORS ARP, in 2009, and carried forward by RTK observations is as follows:</p> <p>Latitude: 36°20'07.138" N. Longitude: 115°12'25.144" W.</p>
--------	--

TOWNSHIP 18 SOUTH, RANGE 60 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>The 1974 mean magnetic declination is 15° E., as shown on U.S.G.S. 7 1/2 minute quadrangle map "CORN CREEK SPRINGS, NEV.", dated 1974.</p> <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY, T. 18 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of the Survey Executed By U.S. Deputy Surveyors R.H. Woods and W.H. Myrick in 1882</p> <hr/> <p>Beginning at the cor. of Tps. 18 and 19 S., Rs. 60 and 61 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. as described in the field notes of T. 19 S., R. 61 E., executed under Group No. 683, from which the remaining 1990 accessory</p> <p>A cross (X) etched on a steel plate, 4 ins. square, mkd. PWF414 77299 112 57914, firmly attached to a powerline pole, bears S. 43°20' W., 1.476 chs. dist.</p> <p>N. 0°59'50" E., bet. secs. 31 and 36.</p> <p>Ascend gradual SW slope, with scattered yucca and greasewood.</p> <p>40.696 The 1/4 sec. cor. of secs. 31 and 36, perpetuated by person(s) unknown, monumented with a rebar, 5/8 in. diam., 12 ins. long, firmly set, projecting 4 ins. above the ground, with a limestone, 18x11x6 ins., lying alongside, mkd. 1/4 on one face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T18S R60E R61E 1/4 S36 S31 2009</p> <p>Insert the rebar inside the stainless steel post and bury the mkd. stone alongside.</p> <p>Cor. is located E., 30 lks. of a concrete flood canal, bears N. and S.</p> <hr/> <p>N. 0°03'30" E., beginning new measurement.</p> <p>40.553 The cor. of secs. 25, 30, 31 and 36, perpetuated by Robert L. Pounds, Nevada Professional Land Surveyor No. 13867, monumented with a rebar, 5/8 in. diam., 12 ins. long, firmly set, projecting 6 ins. above the ground, in a mound of stone,</p>
--------	---

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 18 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>4 ft. base, 1 ft. high, with a limestone, 14x10x9 ins., lying alongside, mkd. with 1 notch on one edge and 5 notches on opposite edge, as recorded in Clark County, Nevada, File 142, Page 30 of Surveys.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td>T18S</td><td></td></tr> <tr><td>R60E</td><td>R61E</td></tr> <tr><td>S25</td><td>S30</td></tr> <tr><td>S36</td><td>S31</td></tr> </table> <p>2009</p> </div> <p>Insert the rebar inside the stainless steel post and bury the mkd. stone alongside.</p> <p>Cor. is located E., 30 lks. of a concrete flood canal, bears N. and S.</p> <hr/> <p>N. 0°29'40" E., bet. secs. 25 and 30.</p> <p>Ascend gradual SW slope, with scattered barrel cacti and greasewood.</p> <p>40.542 The 1/4 sec. cor. of secs. 25 and 30, perpetuated by Robert L. Pounds, Nevada Professional Land Surveyor No. 13867, monumented with a rebar, 5/8 in. diam., firmly set, projecting 4 ins. above the ground, in a mound of stone, 3 ft. base, 1 ft. high, with a limestone, 13x9x8 ins., lying alongside, mkd. 1/4 on one face, as recorded in Clark County, Nevada, File 142, Page 30 of Surveys.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td>T18S</td><td></td></tr> <tr><td>R60E</td><td>R61E</td></tr> <tr><td>1/4</td><td></td></tr> <tr><td>S25</td><td>S30</td></tr> </table> <p>2009</p> </div> <p>Insert the rebar inside the stainless steel post and bury the mkd. stone alongside.</p> <hr/>	T18S		R60E	R61E	S25	S30	S36	S31	T18S		R60E	R61E	1/4		S25	S30
T18S																	
R60E	R61E																
S25	S30																
S36	S31																
T18S																	
R60E	R61E																
1/4																	
S25	S30																

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 18 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Reestablishment of the Survey Executed By U.S. Deputy Surveyors R.H. Woods and W.H. Myrick in 1882</p> <hr/> <p>From the 1/4 sec. cor. of secs. 35 and 36, perpetuated by Robert L. Pounds, Nevada Professional Land Surveyor No. 3687, in 2004, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 4 ins. above the ground, as recorded in Clark County, Nevada, File 142, Page 30 of Surveys. This rebar was subsequently recovered by Frederick W. Orban, Nevada Professional Land Surveyor No. 4541, in 2007, as recorded in Clark County, Nevada, File 167, Page 33 of Surveys. This is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T18S R60E 1/4 S35 S36 2009</p> </div> <p>Insert the rebar inside the stainless steel post.</p> <p>N. 2°53'00" W., bet. secs. 35 and 36.</p> <p>Ascend gradual SW slope, with scattered yucca and greasewood.</p> <p>39.138 Point for the cor. of secs. 25, 26, 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T18S R60E S26 S25 S35 S36 2009</p> </div> <p>From this point, a position determined by Frederick W. Orban, Nevada Professional Land Surveyor No. 4541, in 2007, monumented with a rebar, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with an aluminum cap mkd. FW ORBAN T18S R60E 25 26 35 36 PLS 4541, as recorded in Clark County, Nevada, File 167, Page 33 of Surveys, bears S. 78°47' E., 0.051 chs. dist. This point previously determined by Robert L. Pounds, Nevada Professional Land Surveyor No. 3687, in 2004, as recorded in Clark County, Nevada, File 142, Page 30 of Surveys, was established using incorrect record data and was not utilized during the course of this survey.</p> <hr/>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 18 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 88°06'20" W., bet. secs. 25 and 36.</p> <p>Ascend gradual SW slope, with scattered greasewood, yucca and sage.</p>
41.440	<p>Point for the 1/4 sec. cor. of secs. 26 and 35, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>POINT NOT MONUMENTED</p>
82.880	<p>The cor. of secs. 25, 26, 35 and 36.</p> <hr/> <p>N. 0°53'40" W., bet. secs. 25 and 26.</p> <p>Ascend gradual SW slope, with scattered greasewood, yucca and sage.</p>
39.093	<p>Point for the 1/4 sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T18S R60E 1/4 S26 S25 2009</p>
78.186	<p>From this point, a position determined by Frederick W. Orban, Nevada Professional Land Surveyor No. 4541, monumented with a rebar, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with an aluminum cap mkd. FW ORBAN T18S R60E 1/4 S25 S26 PLS 4541, as recorded in Clark County, Nevada, File 167, Page 33 of Surveys, bears S. 81°00' E., 0.026 chs. dist. The information related to this point as depicted on maps recorded in Clark County, Nevada, File 142, Page 30 of Surveys and File 167, Page 33 of Surveys is deficient on proper procedures and is not utilized during the course of this survey.</p> <p>The cor. of secs. 23, 24, 25 and 26, monumented with a limestone, 13x11x5 ins., firmly set in a mound of stone, 3 ft. base, 1 ft. high, mkd. with 2 notches on S. edge and 1 notch on E. edge.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 18 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div data-bbox="878 268 1024 369"> T18S R60E S23 S24 ----- S26 S25 </div> <div data-bbox="919 401 984 426">2009</div> <div data-bbox="435 455 1308 480">Bury the mkd. stone alongside the stainless steel post.</div> <hr/> <div data-bbox="435 541 1088 567">From the cor. of secs. 25, 26, 35 and 36.</div> <div data-bbox="435 600 1039 625">N. 89°24'20" W., bet. secs. 26 and 35.</div> <div data-bbox="435 659 1276 684">Ascend SW slope, with scattered greasewood and yucca.</div> <div data-bbox="297 714 1455 766">41.778 Point for the 1/4 sec. cor. of secs. 26 and 35, at proportionate distance; there is no remaining evidence of the original corner.</div> <div data-bbox="435 793 756 819">POINT NOT MONUMENTED</div> <div data-bbox="297 846 1455 1031">83.556 The cor. of secs. 26, 27, 34 and 35, perpetuated by Rita M. Lumos, Nevada Professional Land Surveyor No. 5094, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 2 ins. above the ground, and in a collar of stone, as recorded in Clark County, Nevada, File 135, Page 67 of Surveys. This is accepted as a careful and faithful perpetuation of the position of the original corner.</div> <div data-bbox="435 1058 737 1083">At the corner point</div> <div data-bbox="435 1113 1406 1190">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</div> <div data-bbox="878 1220 1024 1320"> T18S R60E S27 S26 ----- S34 S35 </div> <div data-bbox="919 1348 984 1373">2009</div> <div data-bbox="435 1400 1227 1425">Bury the rebar alongside the stainless steel post.</div> <hr/> <div data-bbox="435 1486 1023 1512">N. 0°20'00" W., bet. secs. 26 and 27.</div> <div data-bbox="435 1539 1260 1564">Across SW slope with scattered greasewood and yucca.</div> <div data-bbox="297 1591 1455 1803">40.887 The 1/4 sec. cor. of secs. 26 and 27, most recently reestablished by Frederick W. Orban, Nevada Professional Land Surveyor No. 4541, monumented with a rebar, 5/8 in. diam., 30 ins. long, firmly set flush with the ground, with an aluminum cap mkd. FW ORBAN T18S R60E 1/4 S26 S27 PLS 4541, as recorded in Clark County, Nevada, File 167, Page 33 of Surveys. This is accepted as a careful and faithful reestablishment of the position of the original corner.</div> <div data-bbox="435 1831 737 1856">At the corner point</div>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 18 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T18S R60E 1/4 S27 S26 2009</p> <p>Bury the rebar alongside the stainless steel post.</p> <hr/> <p>N. 0°20'00" W., beginning new measurement.</p>
40.887	<p>The cor. of secs. 22, 23, 26 and 27, perpetuated by Rita M. Lumos, Nevada Professional Land Surveyor No. 5094, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 3 ins. above the ground, with a limestone, 19x11x6 ins., lying alongside, mkd. with 2 notches on one edge and 2 notches on another edge, as recorded in Clark County, Nevada, File 135, Page 67 of Surveys.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T18S R60E S22 S23 S27 S26 2009</p> <p>Bury the rebar and the mkd. stone alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34, perpetuated by Rita M. Lumos, Nevada Professional Land Surveyor No. 5094, monumented with an aluminum cap, 3 1/4 ins. diam., set in concrete flush with the ground, mkd. CITY OF LAS VEGAS T18S R60E 27 28 33 34 PLS 5094 2003, in a mound of stone, 3 ft. base, 1 ft. high, as recorded in Clark County, Nevada, File 135, Page 67 of Surveys, bears S. 0°13'30" E., 40.490 chs. dist. This is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>N. 0°13'30" W., bet. secs. 27 and 28.</p> <p>Ascend S slope, with scattered greasewood and yucca.</p>
40.490	<p>The 1/4 sec. cor. of secs. 27 and 28, reestablished by Rita M. Lumos, Nevada Professional Land Surveyor No. 5094, monumented with an aluminum cap, 3 1/4 ins. diam., set in concrete flush with the ground, mkd. CITY OF LAS VEGAS T18S R60E 1/4 27 28 PLS 5094, as recorded in Clark County, Nevada, File 135, Page 67 of Surveys. This is accepted as a careful and faithful reestablishment of the position of the original corner.</p> <hr/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 18 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°13'30" W., beginning new measurement.
40.490	The cor. of secs. 21, 22, 27 and 28, perpetuated by Rita M. Lumos, Nevada Professional Land Surveyor No. 5094, monumented with an aluminum cap, 3 1/4 ins. diam., set in concrete flush with the ground, mkd. CITY OF LAS VEGAS T18S R60E 21 22 27 28 PLS 5094 2003, as recorded in Clark County, Nevada, File 135, Page 67 of Surveys. This is accepted as a careful and faithful perpetuation of the position of the original corner.
	N. 0°24'40" E., bet. secs. 21 and 22.
	Ascend S slope, with scattered greasewood and yucca.
38.710	The 1/4 sec. cor. of secs. 21 and 22, reestablished by Rita M. Lumos, Nevada Professional Land Surveyor No. 5094, monumented with an aluminum cap, 3 1/4 ins. diam., set in concrete flush with the ground, mkd. CITY OF LAS VEGAS T18S R60E 1/4 21 22 PLS 5094 2003, as recorded in Clark County, Nevada, File 135, Page 67 of Surveys. This is accepted as a careful and faithful reestablishment of the position of the original corner.
	N. 0°24'40" E., beginning new measurement.
38.710	The cor. of secs. 15, 16, 21 and 22, determined by Rita M. Lumos, Nevada Professional Land Surveyor No. 5094, monumented with an aluminum cap, 3 1/4 ins. diam., set in concrete flush with the ground, mkd. CITY OF LAS VEGAS T18S R60E 15 16 21 22 PLS 5094 2003, as recorded in Clark County, Nevada, File 135, Page 67 of Surveys, with an unmarked stone lying loose alongside. This is accepted as the best available evidence of the position of the original corner.
	N. 86°30'00" W., bet. secs. 16 and 21.
	Over S slope, with scattered greasewood and yucca.
40.593	The 1/4 sec. cor. of secs. 16 and 21, reestablished by Rita M. Lumos, Nevada Professional Land Surveyor No. 5094, monumented with an aluminum cap, 3 1/4 ins. diam., set in concrete flush with the ground, mkd. CITY OF LAS VEGAS T18S R60E 1/4 16 21 PLS 5094 2004, as recorded in Clark County, Nevada, File 135, Page 67 of Surveys. This is accepted as a careful and faithful reestablishment of the position of the original corner.
	N. 86°30'00" W., beginning new measurement.
40.593	The cor. of secs. 16, 17, 20 and 21, perpetuated by Rita M. Lumos, Nevada Professional Land Surveyor No. 5094, monumented with an aluminum cap, 3 1/4 ins. diam., set in concrete flush with the ground, mkd. CITY OF LAS VEGAS T18S R60E 16 17 20 21 PLS 5094 200, as recorded in Clark County, Nevada, File 135, Page 67 of Surveys, with a limestone, 15x9x6 ins., lying loose alongside, mkd. with 3 notches on one edge and 4 notches on another edge.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 18 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>N. 89°51'10" W., bet. secs. 17 and 20.</p> <p>Over S slope, with scattered greasewood and yucca.</p>
41.320	<p>The 1/4 sec. cor. of secs. 17 and 20, reestablished by Rita M. Lumos, Nevada Professional Land Surveyor No. 5094, monumented with an aluminum cap, 3 1/4 ins. diam., set in concrete flush with the ground, mkd. CITY OF LAS VEGAS T18S R60E 1/4 17 20 PLS 5094 200, as recorded in Clark County, Nevada, File 135, Page 67 of Surveys. This is accepted as a careful and faithful reestablishment of the position of the original corner.</p> <p>From this cor., an aluminum rod, 5/8 in. diam., firmly set in concrete, projecting 1 in. above ground, bears S. 84°36' W., 2.389 chs. dist.</p>
	<p>N. 89°51'10" W., beginning new measurement.</p>
41.320	<p>The cor. of secs. 17, 18, 19 and 20, perpetuated by Rita M. Lumos, Nevada Professional Land Surveyor No. 5094, monumented with an aluminum cap, 3 1/4 ins. diam., set in concrete flush with the ground, mkd. CITY OF LAS VEGAS T18S R60E 17 18 19 20 PLS 5094 200, as recorded in Clark County, Nevada, File 135, Page 67 of Surveys. This is accepted as a careful and faithful perpetuation of the position of the original corner.</p>
	<p>N. 83°23'50" W., bet. secs. 18 and 19.</p> <p>Over SW slope, with scattered greasewood and yucca.</p>
34.507	<p>An aluminum cap set by Rita M. Lumos, Nevada Professional Land Surveyor No. 5094, 3 1/4 ins. diam., set in concrete flush with the ground, mkd. CITY OF LAS VEGAS T18S R60E 1/4 18 19 PLS 5094 2004, as recorded in Clark County, Nevada, File No. 135, Page 67 of Surveys. This was established using improper methods of restoration of a lost corner and was not utilized during the course of this survey.</p>
35.002	<p>Point for the 1/4 sec. cor. of secs 18 and 19, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T18S R60E S18 1/4 ——— S19 2010</p>
69.015	<p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented with a local monument, an aluminum cap, 3 1/4 ins. diam., set in concrete, mkd. as described in the field notes of the dependent resurvey of the E. bdy. of T. 18 S., R. 59 E., executed concurrently under this same group.</p>

SUBDIVISION OF SECTION 25,
T. 18 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the 1/4 sec. cor. of secs. 25 and 30, on the E. bdy. of the Tp.</p> <p>S. 87°08'10" W., on the E-W center line of sec. 25.</p> <p>83.891 The 1/4 sec. cor. of secs. 25 and 26.</p> <hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 26, T. 18 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 25 and 26.</p> <p>N. 88°09'50" W., on the E-W center line of sec. 26.</p> <p>83.217 The 1/4 sec. cor. of secs. 26 and 27.</p> <hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 27, T. 18 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 26 and 27.</p> <p>S. 89°43'00" W., on the E-W center line of sec. 27.</p> <p>81.669 The 1/4 sec. cor. of secs. 27 and 28.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The area resurveyed and subdivided is situated north of Las Vegas along the southerly boundary of the Desert National Wildlife Refuge. The land is mostly gently rolling. The elevation ranges from about 2,400 to 2,900 ft. above sea level. The soil is sandy and gravelly throughout the township. The vegetation consist of greasewood, creosote, shadscale and cacti.</p> <p>Access into the area is provided by many desert trail roads.</p> <p>No mineral formations of consequence were noted during the survey.</p> <hr/>
--------	---

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS


Joseph J. Johnson	Student Trainee (Land Surveyor)
Michael C. Lambeth	Surveying Technician

CERTIFICATE OF SURVEY


We, Steven E. Dagitz and Brock R. Clifford, Cadastral Surveyors, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 16th day of July, 2009, we have dependently resurveyed a portion of the east boundary and a portion of the subdivisional lines, and subdivided sections 25, 26 and 27, Township 18 South, Range 60 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

January 21, 2011

(Date)

/For Steven E. Dagitz
(Cadastral Surveyor)January 19, 2011

(Date)

(Cadastral Surveyor)


CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of the dependent resurvey of a portion of the east boundary and a portion of the subdivisional lines, and the subdivision of sections 25, 26 and 27, Township 18 South, Range 60 East, Mount Diablo Meridian, Nevada, executed by Steven E. Dagitz and Brock R. Clifford, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

January 21, 2011

(Date)


(Chief Cadastral Surveyor, Nevada)~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 18 S., R. 60 E., Mount Diablo Meridian, Nevada, is a true copy of the original field notes.~~

~~(Date)~~~~(Chief Cadastral Surveyor, Nevada)~~