

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
A PORTION OF THE SUBDIVISIONAL LINES AND PORTIONS OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 32,

AND

THE FURTHER SUBDIVISION OF SECTION 32,
TOWNSHIP 18 SOUTH, RANGE 60 EAST,
OF THE MOUNT DIABLO MERIDIAN,
IN THE STATE OF NEVADA

EXECUTED BY

Carlos Gil Mendoza, Cadastral Surveyor

Under Special Instructions dated March 10, 2020

and approved March 10, 2020,

which provided for the surveys included under Group No. 994,

and Assignment Instructions dated April 22, 2020.

Survey commenced May 27, 2020

Survey completed September 4, 2020

INDEX DIAGRAM

TOWNSHIP 18 SOUTH, RANGE 60 EAST, MOUNT DIABLO MERIDIAN, NEVADA

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	3 2	33	34	35	36

Dependent Resurvey of Portions of the Subdivision-of-Section
 Lines of Section 32 pp 5-11
 Further Subdivision of Section 32 pp 11-12

TOWNSHIP 18 SOUTH, RANGE 60 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The following field notes are those of the dependent resurvey of a portion of the south boundary, a portion of the subdivisional lines and portions of the subdivision-of-section lines of section 32, and the further subdivision of section 32, Township 18 South, Range 60 East, Mount Diablo Meridian, Nevada.

The west boundary was surveyed by U.S. Deputy Surveyor E.A. Carter in 1881, under Contract No. 128. The north, south and east boundaries, and the subdivisional lines were surveyed by U.S. Deputy Surveyors R.H. Woods and W.H. Myrick in 1881-1882, under Contract No. 111. A portion of the south boundary was dependently resurveyed by Cartographic Survey Aid P.K. Russell in 1956, under Group No. 357. A portion of the west boundary was dependently resurveyed by Cadastral Surveyor J.A. Mack in 1984, under Group No. 612. The corner of Tps. 18 and 19 S., Rs. 60 and 61 E. was remonumented by Cadastral Surveyor N.R. Forsyth in 1990, under Group No. 683. A portion of the south boundary was dependently resurveyed by Cadastral Surveyor R.A. Pratt in 1990, under Group No. 688. Portions of the east and west boundaries, and a portion of the subdivisional lines were dependently resurveyed and certain sections were subdivided by Cadastral Surveyors S.E. Dagitz and B.R. Clifford in 2009-2011, under Group No. 881. Portions of the south and west boundaries, and a portion of the subdivisional lines were dependently resurveyed and certain sections were subdivided by Cadastral Surveyor C.S. Dukart in 2015, under Group No. 945.

Before restoring the corners, the lines of the original surveys were retraced and a diligent search made for any evidence of the original corners and other calls of the original field note record.

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 2009, and the Special Instructions for Group No. 994, dated March 10, 2020.

Measurements were made with Trimble R-10 Global Navigation Satellite System (GNSS) receivers using the real-time kinematic (RTK) method and refer to the true meridian based on geodetic methods. The mean bearings of the lines and horizontal equivalents of ground distances only are entered in the field notes.

The NAD 1983(2011) (EPOCH: 2010.0000) geographic position, of the following corners were determined from GNSS static observations processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) DJ3669 NVCA CARLTON SQUARE 2 CORS ARP, DJ8973 NVBM BERMUDA CORS ARP, and DI1079 NVLM AMS WT FACILITY CORS ARP, and carried forward by RTK observations.

The 1/4 sec. cor. of secs. 5 and 32, on the S. bdy. of the Tp., is as follows:

Latitude: 36°20'09.881" N. Longitude: 115°17'15.338" W.

TOWNSHIP 18 SOUTH, RANGE 60 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>The cor. of secs. 29, 30, 31, and 32, is as follows:</p> <p>Latitude: 36°20'58.749" N. Longitude: 115°17'56.509" W.</p> <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY, T. 18 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of a portion of the Survey executed by U.S. Deputy Surveyors R.H. Woods and W.H. Myrick in 1881, a Portion of the Dependent Resurvey Executed by Cadastral Surveyor R.A. Pratt in 1990 and a Portion of the Dependent Resurvey Executed by Cadastral Surveyor C.S. Dukart in 2015</p> <hr/> <p>From the 1/4 sec. cor. of secs. 5 and 32, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the surface of the ground, in a collar of stone, with brass cap mkd. as described in the field notes of the 2015 dependent resurvey of a portion of the north boundary, T. 19 S., R. 60 E., executed under Group No. 945, with a brass washer, 2 ins. diam., mkd. CITY OF LAS VEGAS 1LV905N4 BM NO, wired to it.</p> <p>N. 89°20'50" W., bet. secs. 5 and 32.</p> <p>9.999 The E-W 1/64 sec. cor. of secs. 5 and 32, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the surface of the ground, with brass cap mkd. as described in the field notes of the 2015 dependent resurvey of a portion of the north boundary, T. 19 S., R. 60 E., executed under Group No. 945, with a steel "T-post" fence post N. of the cor.</p> <hr/> <p>N. 89°20'50" W., beginning new measurement.</p> <p>9.999 Point for the W 1/16 sec. cor. of secs. 5 and 32, at proportionate distance.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>S32</p> <p>W1/16 —————</p> <p>S 5</p> <p>2020</p> </div> <p>From this cor., a rivet in a brass washer, 2 ins. diam., firmly set in concrete base, 6 ins. diam., flush with the surface of the ground, mkd. CITY OF LAS VEGAS OLV90 5NNW6 BM NO, bears N. 80°34'30" E., 0.198 chs. dist., with a steel "T-post" fence post set alongside.</p> <p>12.65 Power line, 2 wire, bears S. 32° E. and N. 32° W.</p>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 18 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
12.85	Dirt road, 18 lks. wide, bears S. 32° E. and N. 32° W.
29.997	<p>The cor. of secs. 5, 6, 31, and 32, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the surface of the ground, with brass cap mkd. as described in the field notes of the 2015 dependent resurvey of a portion of the north boundary, T. 19 S., R. 60 E., executed under Group No. 945, and with a brass washer, 2 ins. diam., mkd. CITY OF LAS VEGAS OLV90 5NWS BM NO, wired to it.</p> <p>from which reference monuments set by Danny E. Hill, Nevada Professional Land Surveyor No. 9389, in 2007, as recorded in Clark County, Nevada, Corner Record, Instrument No. 20070828-0001612</p> <p>A rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, with aluminum cap, 1 1/2 ins. diam., mkd. D. HILL RM 92.85 PLS 9389, bears N. 51°44'40" E., 140.7 lks. dist.</p> <p>A rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, with aluminum cap, 1 1/2 ins. diam., mkd. D. HILL RM 91.72 PLS 9389, bears S. 59°57'50" E., 139.0 lks. dist.</p> <p>An aluminum cap, 2 ins. diam. (2015 Record: 1 1/2 ins. diam.), firmly set in a concrete pad, mkd. RM 80.80 PLS 9389, bears S. 54°34'30" W., 122.4 lks. dist.</p> <p>From this cor., a position determined by persons unknown, monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, bears N. 63°52'00" W., 0.492 chs. dist.</p> <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 18 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of a Portion of the Survey executed by U.S. Deputy Surveyors R.H. Woods and W.H. Myrick in 1882 and a Portion of the Dependent Resurvey Executed by Cadastral Surveyor C.S. Dukart in 2015</p> <hr/> <p>From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 8°26'40" W., bet secs. 31 and 32.</p>
1.10	Wood post and cable fence, 2 strand, bears E. and W.
18.812	<p>Point for the S 1/16 sec. cor. of secs. 31 and 32, at proportionate distance.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 18 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">S1/16</p> <p style="text-align: center;">S31 S32</p> <p style="text-align: center;">2020</p>
33.00	Dirt road, 18 lks. wide, bears S. 45° E. and N. 45° W.
33.40	Power line, 2 wire, bears S. 38° E. and N. 38° W.
37.624	<p>The 1/4 sec. cor. of secs. 31 and 32, monumented with an aluminum cap, 3 1/4 ins. diam., firmly set in concrete base, 12 ins. diam., flush with the ground, mkd. as described in the field notes of the 2015 dependent resurvey of a portion of the subdivisional lines, T. 18 S., R. 60 E., executed under Group No. 945, and as recorded in Clark County, Nevada, File 135, Page 67 of Surveys, with a steel "T-post" fence post set alongside.</p> <p>From this cor., a rivet in a brass washer, 2 ins. diam., firmly set in same concrete base, 12 ins. diam. (2015 Record: 6 ins. diam.), flush with the surface of the ground, mkd. CITY OF LAS VEGAS 5LV 8031E4 PLS XXX, bears S. 6°01'30" E., 0.004 chs. dist.</p> <hr/> <p>N. 8°26'40" W., beginning new measurement.</p>
9.406	<p>Point for the S-N 1/64 sec. cor. of secs. 31 and 32, at proportionate distance.</p> <p>POINT NOT MONUMENTED</p>
18.812	<p>Point for the N 1/16 sec. cor. of secs. 31 and 32, at proportionate distance.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">N1/16</p> <p style="text-align: center;">S31 S32</p> <p style="text-align: center;">2020</p>
28.218	<p>The N-N 1/64 sec. cor. of secs. 31 and 32, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the surface of the ground, with brass cap mkd. as described in the field notes of the 2015 dependent resurvey of a portion of the subdivisional lines, T. 18 S., R. 60 E., executed under Group No. 945, with a steel "T-post" fence post W. of the cor.</p> <hr/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 18 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>N. 8°26'40" W., beginning new measurement.</p> <p>9.406 The cor. of secs. 29, 30, 31, and 32, monumented with an aluminum cap, 3 1/4 ins. diam., set in concrete base, 12 ins. diam., flush with the surface of the ground, mkd. as described in the field notes of the 2015 dependent resurvey of a portion of the subdivisional lines, T. 18 S., R. 60 E., executed under Group No. 945, and as recorded in Clark County, Nevada, File 135, Page 67 of Surveys, with a steel "T-post" fence post set alongside, and with a stone, 12 x 11 x 8 ins., (Record: limestone, 16 x 14 x 9 ins.), with 1 notch on one edge and 5 notches on another edge, lying loose on a mound of stone, 2 ft. base, 1 ft. high, SW. of the cor.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 29 and 32, monumented with an aluminum cap, 3 1/4 ins. diam., firmly set in concrete base, 12 ins. diam., flush with the surface of the ground, mkd. as described in the field notes of the 2015 dependent resurvey of a portion of the subdivisional lines, T. 18 S., R. 60 E., executed under Group No. 945, and as recorded in Clark County, Nevada, File 162, Page 35 of Surveys, with a steel "T-post" fence post set alongside.</p> <p>S. 89°45'30" W., bet secs. 29 and 32.</p>
20.424	<p>Point for the W 1/16 sec. cor. of secs. 29 and 32, at proportionate distance.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>S29</p> <hr style="width: 100px; margin: 0 auto;"/> <p>W1/16 S32</p> <p>2020</p> </div>
30.636	<p>Point for the W-W 1/64 sec. cor. of secs. 29 and 32, at proportionate distance.</p> <p>POINT NOT MONUMENTED</p>
40.848	<p>The cor. of secs. 29, 30, 31, and 32.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF PORTIONS OF THE SUBDIVISION-OF-SECTION LINES OF SECTION 32, T. 18 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of a Portion of the Subdivision Executed by Cadastral Surveyor C.S. Dukart in 2015</p> <hr/> <p>From the 1/4 sec. cor. of secs. 5 and 32, on the S. bdy. of the Tp.</p>

DEPENDENT RESURVEY OF PORTIONS OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 32,
T. 18 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 7°43'50" W., on the N-S center line of sec. 32.
0.90	Wood post and cable fence, 2 strand, bears E. and W.
7.60	Dirt road, 12 lks. wide, bears E. and W.
16.85	Dirt road, 12 lks. wide, bears N. 70° E. and W.
18.938	Point for the C-S 1/16 sec. cor. of sec. 32, at proportionate distance. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;"> C S1/16 S32 C 2020 </div>
28.407	Point for the C-N-S 1/64 sec. cor. of sec. 32, at proportionate distance. POINT NOT MONUMENTED
37.876	The center 1/4 sec. cor. of sec. 32, monumented with an aluminum cap, 3 1/4 ins. diam., firmly set in concrete base, 12 ins. diam., flush with the surface of the ground, mkd. as described in the field notes of the 2015 subdivision of section 32, T. 18 S., R. 60 E., executed under Group No. 945, and as recorded in Clark County, Nevada, File 162, Page 35 of Surveys, with a steel "T-post" fence post set alongside. <hr style="width: 20%; margin: 10px auto;"/> N. 7°43'50" W., beginning new measurement.
9.469	Point for the C-S-N 1/64 sec. cor. of sec. 32. POINT NOT MONUMENTED
17.802	Wash, 113 lks. wide, drains. NE.
18.938	Point for the C-N 1/16 sec. cor. of sec. 32, at proportionate distance. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

DEPENDENT RESURVEY OF PORTIONS OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 32,
T. 18 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<div style="text-align: center;"> C N1/16 S32 C 2020 </div>
37.876	<p>The 1/4 sec. cor. of secs. 29 and 32.</p> <hr/> <p>From the center 1/4 sec. cor. of sec. 32.</p> <p>N. 89°47'50" W., on a portion of the E-W center line of sec. 32.</p>
10.106	<p>Point for the C-E-W 1/64 sec. cor. of sec. 32, at proportionate distance.</p> <p>POINT NOT MONUMENTED</p>
15.159	<p>The C-W-E-W 1/256 sec. cor. of sec. 32, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the surface of the ground, in a collar of stone, with brass cap mkd. as described in the field notes of the 2015 subdivision of section 32, T. 18 S., R. 60 E., executed under Group No. 945, with a steel "T-post" fence post N. of the cor.</p> <hr/> <p>From the W 1/16 sec. cor. of secs. 5 and 32, on the S. bdy. of the Tp.</p> <p>N. 8°05'10" W., on the N-S center line of the SW1/4 of sec. 32.</p>
0.95	Wood post and cable fence, 2 strand, bears E. and W.
10.25	Dirt road, 12 lks. wide, bears N. 50° E. and S. 70° W.
18.874	<p>Point for the SW 1/16 sec. cor. of sec. 32, at intersection with the E-W center line of the SW1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> SW1/16 S32 2020 </div>
28.310	<p>Point for the C-N-SW 1/64 sec. cor. of sec. 32, at proportionate distance.</p> <p>POINT NOT MONUMENTED</p>
33.028	<p>Point for the C-N-N-SW 1/256 sec. cor. of sec. 32.</p> <p>POINT NOT MONUMENTED</p>

DEPENDENT RESURVEY OF PORTIONS OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 32,
T. 18 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
37.746	The C-W 1/16 sec. cor. of sec. 32, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the surface of the ground, in a collar of stone, with brass cap mkd. as described in the field notes of the 2015 subdivision of section 32, T. 18 S., R. 60 E., executed under Group No. 945, with a steel "T-post" fence post N. of the cor.
	From the C-S 1/16 sec. cor. of sec. 32.
	N. 89°34'30" W., on the E-W center line of the SW1/4 of sec. 32.
5.026	Point for the C-E-E-SW 1/256 sec. cor. of sec. 32.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.
	S32
	C-E-E-SW
	1/256
	2020
10.052	Point for the C-E-SW 1/64 sec. cor. of sec. 32, at proportionate distance.
	POINT NOT MONUMENTED
20.104	The SW 1/16 sec. cor. of sec. 32.
31.95	Power line, 2 wire, bears S. 32° E. and N. 32° W.
32.25	Dirt road, 18 lks. wide, bears S. 32° E. and N. 32° W.
40.208	The S 1/16 sec. cor. of secs. 31 and 32.
	From the NE-SW 1/64 sec. cor. of sec. 32, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the surface of the ground, in a collar of stone, with brass cap mkd. as described in the field notes of the 2015 subdivision of section 32, T. 18 S., R. 60 E., executed under Group No. 945, with a steel "T-post" fence post W. of the cor.
	N. 7°54'30" W., on a portion of the N-S center line of the NE1/4SW1/4 of sec. 32.
4.727	Point for the C-N-NE-SW 1/256 sec. cor. of sec. 32.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.

DEPENDENT RESURVEY OF PORTIONS OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 32,
T. 18 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>S32</p> <p>C-N-NE-SW 1/256</p> <p>2020</p>
9.454	<p>The point for the C-E-W 1/64 sec. cor. of sec. 32.</p> <hr/> <p>From the point for the C-N-S 1/64 sec cor. of sec. 32</p> <p>N. 89°41'10" W., on a portion of the E-W center line of the NE1/4SW1/4 of sec. 32.</p>
5.039	<p>Point for the C-E-NE-SW 1/256 sec. cor. of sec. 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p>S32</p> <p>C-E-NE-SW 1/256</p> <p>2020</p>
10.078	<p>The NE-SW 1/64 sec. cor. of sec. 32.</p> <hr/> <p>From the C-W-NE-SW 1/256 sec. cor. of sec. 32, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the surface of the ground, in a collar of stone, with brass cap mkd. as described in the field notes of the 2015 subdivision of section 32, T. 18 S., R. 60 E., executed under Group No. 945, with a steel "T-post" fence post N. of the cor.</p> <p>N. 7°59'40" W., on the N-S center line of the NW1/4NE1/4SW1/4 of sec. 32.</p>
4.722	<p>Point for the NW-NE-SW 1/256 sec. cor. of sec. 32, at intersection with the E-W center line of the NW1/4NE1/4SW1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p>S32</p> <p>NW-NE-SW 1/256</p> <p>2020</p>
9.444	<p>The C-W-E-W 1/256 sec. cor. of sec. 32.</p> <hr/>

DEPENDENT RESURVEY OF PORTIONS OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 32,
T. 18 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From the C-S-NW 1/64 sec. cor. of sec. 32, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the surface of the ground, in a collar of stone, with brass cap mkd. as described in the field notes of the 2015 subdivision of section 32, T. 18 S., R. 60 E., executed under Group No. 945, with a steel "T-post" fence post W. of the cor.</p> <p>N. 8°05'20" W., on a portion of the N-S center line of the NW1/4 of sec. 32.</p>
9.437	<p>Point for the NW 1/16 sec. cor. of sec. 32, at intersection with the E-W center line of the NW1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S32</p> <p style="text-align: center;">2020</p>
18.874	<p>Point for the C-N-NW 1/64 sec. cor. of sec. 32, at proportionate distance.</p> <p>POINT NOT MONUMENTED</p>
28.311	<p>The W 1/16 sec. cor. of secs. 29 and 32.</p> <hr/> <p>From the C-N 1/16 sec. cor. of sec. 32.</p> <p>S. 89°58'30" W., on the E-W center line of the NW1/4 of sec. 32.</p>
10.159	<p>Point for the C-E-NW 1/64 sec. cor. of sec. 32.</p> <p>POINT NOT MONUMENTED</p>
20.318	<p>The NW 1/16 sec. cor. of secs. 32.</p>
25.397	<p>Point for the C-E-W-NW 1/256 sec. cor. of sec. 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 17 ins. in the ground to solid rock, over a plastic-encased magnet, and in a supporting mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">S32</p> <p style="text-align: center;">C-E-W-NW</p> <p style="text-align: center;">1/256</p> <p style="text-align: center;">2020</p>
30.476	<p>Point for the C-W-NW 1/64 sec. cor. of sec. 32, at proportionate distance.</p>

DEPENDENT RESURVEY OF PORTIONS OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 32,
T. 18 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 17 ins. in the ground to solid rock, over a plastic-encased magnet, and in a supporting mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">S32</p> <p style="text-align: center;">C-W-NW 1/64</p> <p style="text-align: center;">2020</p>
40.634	<p>The N 1/16 sec. cor. of secs. 31 and 32.</p> <hr/> <p>From the C-S-NW 1/64 sec. cor. of sec. 32.</p> <p>N. 89°54'50" W., on a portion of the E-W center line of the SW1/4NW1/4 of sec. 32.</p>
5.066	<p>Point for the C-E-SW-NW 1/256 sec. cor. of sec. 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">S32</p> <p style="text-align: center;">C-E-SW-NW 1/256</p> <p style="text-align: center;">2020</p>
10.132	<p>The SW-NW 1/64 sec. cor. of sec. 32, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the surface of the ground, in a collar of stone, with brass cap mkd. as described in the field notes of the 2015 subdivision of section 32, T. 18 S., R. 60 E., executed under Group No. 945, with a steel "T-post" fence post W. of the cor.</p> <hr/> <p style="text-align: center;">FURTHER SUBDIVISION OF SECTION 32, T. 18 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the C-E-E-SW 1/256 sec. cor. of sec. 32.</p> <p>N. 7°49'10" W., on the N-S center line of the SE1/4NE1/4SW1/4 of sec. 32.</p>
9.460	<p>The C-E-NE-SW 1/256 sec. cor. of sec. 32.</p> <hr/> <p>From the C-N-NE-SW 1/256 sec. cor. of sec. 32.</p> <p>N. 89°44'30" W., on the E-W center line of the NW1/4NE1/4SW1/4 of sec. 32.</p>

FURTHER SUBDIVISION OF SECTION 32,
T. 18 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
5.046	The NW-NE-SW 1/256 sec. cor. of sec. 32
10.092	The point for the C-N-N-SW 1/256 sec. cor. of sec. 32.
	<hr/> <p>From the point for the C-E-W 1/64 sec. cor. of sec. 32.</p> <p>N. 7°54'40" W., on the N-S center line of the SE1/4NW1/4 of sec. 32.</p>
9.453	Point for the SE-NW 1/64 sec. cor. of sec. 32, at intersection with the E-W center line of the SE1/4NW1/4.
	POINT NOT MONUMENTED
18.906	The point for the C-E-NW 1/64 sec. cor. of sec. 32.
	<hr/> <p>From the point for the C-S-N 1/64 sec. cor. of sec. 32.</p> <p>N. 89°54'40" W., on the E-W center line of the SE1/4NW1/4 of sec. 32.</p>
10.132	The point for the SE-NW 1/64 sec. cor. of sec. 32.
15.198	Point for the C-W-SE-NW 1/256 sec. cor. of sec. 32.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.
	S32
	C-W-SE-NW 1/256
	2020
20.264	The C-S-NW 1/64 sec. cor. of sec. 32.
	<hr/> <p>From the C-W-E-W 1/256 sec. cor. of sec. 32.</p> <p>N. 8°00'00" W., on the N-S center line of the SW1/4SE1/4NW1/4 of sec. 32.</p>
9.446	The C-W-SE-NW 1/256 sec. cor. of sec. 32.
	<hr/> <p>From the C-E-SW-NW 1/256 sec. cor. of sec. 32.</p> <p>N. 8°10'40" W., on the N-S center line of the NE1/4SW1/4NW1/4 of sec. 32.</p>
9.429	The C-E-W-NW 1/256 sec. cor. of sec. 32.
	<hr/>

TOWNSHIP 18 SOUTH, RANGE 60 EAST, MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p>	<p>GENERAL DESCRIPTION</p> <p>The area included in this survey is situated at the northerly edge of Las Vegas, Nevada. The average elevation of the area surveyed is approximately 2600 feet above sea level and generally drains to the south and the east. Vegetation mainly consists of creosote and other native grasses.</p> <hr/>
---------------	---

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Lee T. Wilson

Cadastral Surveyor

Kelly R. Totten

Student Trainee (Survey)

CERTIFICATE OF SURVEY

I, Carlos Gil Mendoza, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 10th day of March, 2020, I have dependently resurveyed a portion of the south boundary, a portion of the subdivisional lines and portions of the subdivision-of-section lines of section 32, and further subdivided section 32, Township 18 South, Range 60 East, of the Mount Diablo Meridian, in the state of Nevada, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

SEP 15 2020

(Date)

Carlos G. Mendoza

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of the dependent resurvey of a portion of the south boundary, a portion of the subdivisional lines and portions of the subdivision-of-section lines of section 32, and the further subdivision of section 32, Township 18 South, Range 60 East, of the Mount Diablo Meridian, Nevada, executed by Carlos Gil Mendoza, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

SEP 15 2020

(Date)

Michael O. Hummer

(Chief Cadastral Surveyor for Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

I CERTIFY that the foregoing transcript of the field notes of the above described surveys in Township 18 South, Range 60 East, Mount Diablo Meridian, Nevada, is a true copy of the original field notes.

~~(Date)~~~~(Chief Cadastral Surveyor for Nevada)~~