

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF

PORTIONS OF THE CALIFORNIA-NEVADA STATE LINE

FROM MILE POST 168 TO MILE POST 171,

AND FROM MILE POST 173 TO MILE POST 175,

PORTIONS OF THE OLD CALIFORNIA-NEVADA STATE LINE,

PORTIONS OF THE SOUTH, EAST, AND NORTH BOUNDARIES,

A PORTION OF THE SUBDIVISIONAL LINES,

THE SUBDIVISION OF

SECTIONS 6, 7, 10, 14, 22, 23, 24, 29, 30, 31, AND 32,

AND METES-AND-BOUNDS SURVEYS IN CERTAIN SECTIONS,

TOWNSHIP 19 NORTH, RANGE 18 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATES OF NEVADA AND CALIFORNIA

EXECUTED BY

David L. Dukleth, Cadastral Surveyor

Under Special Instructions dated August 22, 1997,

and approved August 22, 1997 and August 25, 1997,

which provided for the surveys included under Group No. 768, Nevada,

and Group No. 1280, California,

and Assignment Instructions dated August 29, 1997, and January 29, 1998.

Survey commenced July 29, 1997

Survey completed March 10, 2003

CA NV

3

111

[illegible]

CA NV

Subdivision of sec. 6, Pg. 55-60
Subdivision of sec. 7, Pg. 60-65
Subdivision of sec. 10, Pg. 65-68
Subdivision of sec. 14, Pg. 68-70
Subdivision of sec. 22, Pg. 70-73
Subdivision of sec. 23, Pg. 74-76
Subdivision of sec. 24, Pg. 76-77
Subdivision of sec. 29, Pg. 77-81
Subdivision of sec. 30, Pg. 81-85
Subdivision of sec. 31, Pg. 85-90
Subdivision of sec. 32, Pg. 90-93

Metes-and-bounds survey in sec. 21, pg.	94-95
Metes-and-bounds survey in sec. 22, pg.	95-99
Metes-and-bounds survey in sec. 23, pg.	99-104
Metes-and-bounds survey in sec. 24, pg.	104-107

TOWNSHIP 19 NORTH, RANGE 18 EAST,
MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	<p>The following field notes are those of the dependent resurvey of portions of the California-Nevada State Line, from Mile Post 168 to Mile Post 171, and from Mile Post 173 to Mile Post 175, portions of the old California-Nevada State Line, portions of the south, east, and north boundaries, a portion of the subdivisional lines, the subdivision of sections 6, 7, 10, 14, 22, 23, 24, 29, 30, 31, and 32, and metes-and-bounds surveys in certain sections, Township 19 North, Range 18 East, of the Mount Diablo Meridian, in the States of Nevada and California.</p> <p>History of prior surveys</p> <p>1863 U.S. Deputy Surveyor, E.H. Dyer surveyed the east boundary under Contract "D".</p> <p>1865 U.S. Deputy Surveyor, S.W. Foreman surveyed the south and north boundaries, the old California-Nevada State Line, and the subdivisional lines under Contract "H".</p> <p>1866 U.S. Deputy Surveyor, R.A. Chase surveyed the U.S. Timber Reserve under Contract "L".</p> <p>1872-73 U.S. Astronomer, A.W. Von Schmidt surveyed the new (present) California-Nevada State Line, under Contract dated July 20, 1872.</p> <p>1874 U.S. Deputy Surveyor, D.D. Brown resurveyed a portion of the north boundary of T. 18 N., R. 18 E., to close against the new California-Nevada State Line, which is a portion of the south boundary of T. 19 N., R. 18 E., under contract dated June 17, 1874.</p> <p>1877 U.S. Deputy Surveyor, W.F. Benson resurveyed a portion of the south boundary of T. 20 N., R. 18 E., to close against the new California-Nevada State Line, which is a portion of the north boundary of T. 19 N., R. 18 E., under contract dated May 25, 1877.</p> <p>1913-14 U.S. Surveyor, W.J. Lightfoot, retraced and dependently resurveyed a portion of the old California-Nevada State Line, a portion of the new California-Nevada State Line, and a portion of the subdivisional lines under Group No. 18.</p> <p>1918 U.S. Transitman, E. Voigt, retraced and dependently resurveyed a portion of the old California-Nevada State Line, a portion of the new California-Nevada State Line, portions of the north and south boundaries, and a portion of the subdivisional lines under Group No. 35.</p> <p>1943-45 Cadastral Engineer, C.S. Swanholm, dependently resurveyed a portion of the north boundary under Group No. 312, Nevada.</p> <p>1966 Cadastral Surveyors, R.A. Pratt and W.L. Jepson remonumented certain corners under Group No. 393, Nevada.</p>
--------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

113

TOWNSHIP 19 NORTH, RANGE 18 EAST,
MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS

Before restoring the corners, the lines of the original surveys were retraced and diligent search made for any evidence of the original corners and other calls of the original field note record.

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and Special Instructions dated August 22, 1997, which provided for the surveys included under Group No. 768, Nevada, and Group No. 1280, California.

The direction of the lines were determined by direct solar and polaris observations. The lines were carried forward by sustained angulation being supplemented by other observations of the sun and polaris taken throughout the progress of the survey.

All measurements were made on the slope with electronic distance measuring devices and reduced to their horizontal equivalents which are entered in the field notes.

The geographic position for the 1/4 sec. cor. of secs. 19 and 24, on the E. bdy. of the Tp., is at Lat. $39^{\circ}29'51.177''$ N., Long. $119^{\circ}54'00.831''$ W. (NAD83), as calculated from National Geodetic Survey control (formerly U.S.C. and G.S. triangulation) station "HUNTER", located in sec. 19, T. 19 N., R. 19 E.

The geographic position for the cor. of secs. 20, 21, 28, and 29, is at Lat. $39^{\circ}29'27.294''$ N., Long. $119^{\circ}58'21.716''$ W. (NAD83), as calculated from National Geodetic Survey control (formerly U.S.C. and G.S. triangulation) station "BENDER", located in sec. 28.

The geographic position for the 1/4 sec. cor. of secs. 7 and 8, is at Lat. $39^{\circ}31'37.845''$ N., Long. $119^{\circ}59'32.280''$ W. (NAD83), as calculated from National Geodetic Survey control (formerly U.S.C. and G.S. triangulation) station "VERDI BLUFF", located in sec. 17.

The mean magnetic declination is $16\frac{1}{2}^{\circ}$ E., as shown on U.S.G.S. quadrangle map "VERDI, NEV." dated 1967 and photorevised in 1982.

DEPENDENT RESURVEY OF PORTIONS OF THE CALIFORNIA-NEVADA STATE LINE,
FROM MILE POST 168 TO MILE POST 171,
AND FROM MILE POST 173 TO MILE POST 175,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

<p>CHAINS</p>	<p>Reestablishment of Portions of the Survey Executed by A.W. Von Schmidt, U.S. Astronomer, in 1872-73, Portions of the Retracement and Resurvey Executed by W.J. Lightfoot, U.S. Surveyor, in 1913-1914, and the Dependent Resurvey Executed by E. Voigt, U.S. Transitman, in 1918</p> <hr/> <p>Beginning at the point for Mile Post 168 at proportionate measurement. A down and decayed pine snag, 10 ins. diam., 14 ft. long, on rocky ground, with 2 open blazes on opposite sides with faint scribe marks, illegible, was found nearby. The stump hole could not be determined from the tree remains.</p> <p>Not monumented.</p> <p>From this point, Mile Post 167, bears N. 0°01'20" W., 79.588 chs. dist., determined by person(s) unknown, for the U.S. Forest Service, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 16 ins. above ground, with USFS aluminum cap mkd. MP167 CAL NEV 1988, and in a mound of stone, 4 ft. diam., 1 ft. high. This is accepted as the best available evidence of the position of the original corner.</p> <p>S. 0°01'50" W., on the 169th mile.</p> <p>73.306 The point for the closing cor. of Tps. 19 and 20 N., R. 18 E., hereinafter described.</p> <p>80.364 Mile Post 169, monumented with the remains of the original cor. tree, a decayed pine stump, 3 ft. diam., with burnt snag lying down slope, no marks visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">169M CAL NEV 1999</p> <p>from which</p> <p>A granite boulder, 7 x 7 x 4 ft. high, bears S. 16°20' E., 90.2 lks. dist., mkd. BXO on top, 4 ft. from S. edge.</p> <p>A granite boulder, 7 x 4 x 3 ft. high, bears S. 67°10' W., 50.9 lks. dist., mkd. BXO on top.</p> <p>Cor. is located on moderate S. slope with pine and sagebrush.</p> <hr/> <p>S. 0°11'50" W., on the 170th mile.</p> <p>12.914 Intersection of the E. and W. center line of the NE1/4 of sec. 6, with the California-Nevada State Line, hereinafter described.</p>
---------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

DEPENDENT RESURVEY OF PORTIONS OF THE CALIFORNIA-NEVADA STATE LINE,
 FROM MILE POST 168 TO MILE POST 171,
 AND FROM MILE POST 173 TO MILE POST 175,
 T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	
15.957	<p>The original point at the Record 16.11 ch. call: "Pass between two Pine Trees each 5 links from line". Point determined at midpoint between remains of original trees</p> <p>A pine stump, 16 ins. diam., bears S. 86 1/2° E., 5.0 lks. dist., with scribe marks NEV visible on W. face of blaze.</p> <p>A pine stump, 16 ins. diam., bears N. 86 1/2° W., 5.0 lks. dist., no marks visible on decayed remains.</p> <p>This point now functions as an Angle Point.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">AP T19NR18E CAL NEV S6 1999</p> <p>from which new accessories</p> <p>A granite boulder, 6 x 6 x 4 ft. high, bears S. 48°00' E., 40.5 lks. dist., mkd. BXO on top.</p> <p>A granite boulder, 8 x 4 x 3 ft. high, bears N. 2°20' W., 62.8 lks. dist., mkd. BXO on top.</p> <p>Cor. is located on a gradual W. slope in pine timber with scattered sagebrush and granite boulders, 19 lks. E. of fence, bears N. and S., 4 strand barbed wire, metal and wood posts.</p> <p>S. 0°48'00" W., beginning new measurement.</p>
16.882	Point of intersection of the E. and W. center line of sec. 6, with the California-Nevada State Line, hereinafter described.
17.816	<p>The original point at the Record 34.10 ch. call: "Pass between two Pine Trees each 4 links from line". Point determined at record dist. from original east tree remains</p> <p>A pine stump, 23 ins. diam., bears East, 4.0 lks. dist., with scribe marks NEV visible on W. face of blaze.</p> <p>This point now functions as an Angle Point.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground over a plastic-encased magnet, and in a collar of stone, 2 ft. diam., with brass cap mkd.</p>

116

DEPENDENT RESURVEY OF PORTIONS OF THE CALIFORNIA-NEVADA STATE LINE,
 FROM MILE POST 168 TO MILE POST 171,
 AND FROM MILE POST 173 TO MILE POST 175,
 T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	AP T19NR18E CAL NEV S6 1999
	<p>from which a new accessory</p> <p>A granite boulder, 8 x 6 x 3 ft. high, bears S. 33°00' E., 176.6 lks. dist., mkd. BXO on W. face, 2 1/2 ft. above ground.</p> <p>Cor. is located on a gradual S. slope with pine timber, 10 lks. East of fence, bears N. and S., 4 strand, barbed wire, metal and wood posts.</p> <hr/> <p>S. 0°40'50" W., beginning new measurement.</p>
23.078	Point of intersection of the N. and S. center line of sec. 6, with the California-Nevada State Line, hereinafter described.
38.171	The point for the closing cor. of secs. 6 and 7, hereinafter described.
45.945	<p>Mile Post 170, monumented with an iron post, 3 ins. diam., firmly set, concrete filled, projecting 21 ins., in scattered mound of stone, 8 ft. diam., 1 ft. high, without the cap described in the field notes of the 1918 resurvey, from which the remains of the original bearing trees</p> <p>A pine stump remains, 2 1/2 ft. diam., burned off at ground level, with burned and weathered snag remains alongside, bears S. 41 1/2° E., 3.72 chs. dist., no marks visible. (1873 Record, S. 42°00' E., 3.70 chs.)</p> <p>A Jeffrey pine, 43 ins. diam., bears S. 52° W., 2.61 chs. dist., with healed blaze. (1873 Record, S. 50°50' W., 2.62 chs.)</p> <p>and new bearing trees</p> <p>A Jeffrey pine, 28 ins. diam., bears N. 16° E., 59 lks. dist., mkd. MP170.</p> <p>A Jeffrey pine, 28 ins. diam., bears S. 70 1/2° E., 108 lks. dist., mkd. MP170.</p> <p>Cor. is located on level ground in fence line, 4 strand, wood and metal posts, bears N. and S.</p> <hr/> <p>S. 0°44'10" W., on the 171st mile.</p>
12.571	Point of intersection of the E. and W. center line of the NW1/4 of sec. 7, with the California-Nevada State Line, hereinafter described.
32.910	Point of intersection of the E. and W. center line of sec. 7, hereinafter described.

DEPENDENT RESURVEY OF PORTIONS OF THE CALIFORNIA-NEVADA STATE LINE,
FROM MILE POST 168 TO MILE POST 171,
AND FROM MILE POST 173 TO MILE POST 175,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	
47.385	<p>Mile Post 170+47, monumented with a cast iron monument, 12 ins. sq. at base, 6 ins. sq. at top, 6 ft. above ground, mkd. as described in the field notes of the 1873 survey.</p> <p>from which a local accessory</p> <p>An iron rod, 5/8 in. diam., firmly set, bears N. 0°31'20" E., 101.7 lks. dist., as recorded in Washoe County, Subdivision Tract Map Nos. 2205A and 2284A, with a copper coated steel cap, 1 1/2 ins. diam., mkd. RLS 2170, 5 1/2 ins. below surface, in survey monument well (mkd. 'WATER' on cover), 8 ins. diam., in center of Dog Valley Road, paved surface, 26 ft. wide, bears E. and W.</p> <p>Cor. is located on level ground, inside chain link fence enclosure, 6 x 4 1/2 ft., 6 ft. high.</p> <hr/> <p>S. 0°38'40" W., beginning new measurement.</p>
5.307	<p>Point of intersection of the E. and W. center line of the SW1/4 of sec. 7, with the California-Nevada State Line, hereinafter described.</p>
25.089	<p>The point for the closing cor. of secs. 7 and 18, hereinafter described.</p>
32.682	<p>Mile Post 171, monumented with a granite stone, 15 x 15 x 10 ins. (Record, 17 x 15 x 12 ins.), projecting 2 ins. above ground. Exposed to reveal chisel marks NEV visible on E. side and CAL visible on W. side, as described in the field notes of the 1913 resurvey, from which the remaining 1913 accessory</p> <p>A granite boulder, 5 1/2 x 5 1/2 x 5 ft., bears S. 83°15' E., 219.0 lks. dist., mkd. at top with chiseled 6 in. X.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground over a plastic encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>171M CAL NEV 1999</p> </div> <p>from which a new accessory</p> <p>A power pole, bears S. 44 3/4° E., 218 lks. dist., with tags mkd. 52542 and J9489, lines bear S. and N. 55° E.</p> <p>Bury the mkd. stone, upside down on N. side of stainless steel post.</p> <p>Cor. is located on level ground in open field.</p> <hr/>

DEPENDENT RESURVEY OF PORTIONS OF THE CALIFORNIA-NEVADA STATE LINE,
FROM MILE POST 168 TO MILE POST 171,
AND FROM MILE POST 173 TO MILE POST 175,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	<p>From Mile Post 173, an unrecorded perpetuation by William Grimm, California Registered Land Surveyor No. 2712 and Nevada Professional Land Surveyor No. 737, monumented with a copper coated steel rod, 7/8 in. diam., firmly set, projecting 8 ins. above ground, with copper cap, 1 1/2 ins. diam., mkd. MP173 CAL LS2712 NEV LS737 1981 and in a mound of stone, 4 ft. diam., with stone, 17 x 20 x 8 ins. (1913 Record, 18 x 15 x 9 ins.), with chisel marks NEV on one side.</p> <p>No new accessories taken due to proximity to private residence.</p> <p>Not remonumented.</p> <p>Cor. is located on E. slope with pine and mountain mahogany.</p> <p>S. 0°47'10" W., on the 174th mile.</p> <p>32.103 Point of intersection of the E. and W. center line of sec. 30, with the California-Nevada State Line, hereinafter described.</p> <p>52.245 Intersection of the E. and W. center line of the SW1/4 of sec. 30, with the California-Nevada State Line, hereinafter described.</p> <p>72.400 The closing cor. of secs. 30 and 31, hereinafter described.</p> <p>79.321 Mile Post 174, monumented with the original cor. tree, a Jeffrey pine, 31 ins. diam., with partial scribe marks and chaining notch visible on mostly healed blaze on N. side.</p> <p>from which</p> <p>An iron post, 3 ins. diam., firmly set, bears N. 8 1/2° W., 4.4 lks. dist., projecting 12 ins. above ground, in a mound of stone, 2 ft. diam., 1 ft. high, with brass cap mkd. as described in the field notes of the 1918 resurvey. Note: This monument was set to preserve the original cor. tree, described as "decaying". Since cor. tree is very healthy, this monument is remarked as a reference monument with an arrow pointing to the cor.</p> <p>and a new accessory</p> <p>A Jeffrey pine, 34 ins. diam., bears N. 35 3/4° E., 151 lks. dist., mkd. MP174 BT.</p> <p>Cor. tree is located on steep S. slope, with sagebrush.</p> <hr/> <p>S. 0°32'50" W., on the 175th mile.</p> <p>13.025 Intersection of the E. and W. center line of the NW1/4 of sec. 31, with the California-Nevada State Line, hereinafter described.</p> <p>32.984 Point of intersection of the E. and W. center line of sec. 31, with the California-Nevada State Line, hereinafter described.</p> <p>45.868 Point for Mile Post 174+44, at proportionate measurement, falls on cut bank along jeep trail and railroad tracks.</p>
--------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

DEPENDENT RESURVEY OF PORTIONS OF THE CALIFORNIA-NEVADA STATE LINE,
 FROM MILE POST 168 TO MILE POST 171,
 AND FROM MILE POST 173 TO MILE POST 175,
 T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	<p>From this point, the cast iron monument, 12 ins. sq. at base, 6 ins. sq. at top, 6 ft. above ground, mkd. as described in the field notes of the 1873 survey for the 174+44 Mile Post, bears S. 5°50' E., 0.787 chs. dist. This monument is located on level ground (Record, rising ground to NW) and appears to have been moved after it was established in order to lay additional railroad tracks and to provide road access alongside the tracks.</p> <p>Point for Mile Post 174+44 not monumented.</p> <hr/> <p>S. 1°08'50" W., beginning new measurement.</p> <p>26.771 The point for the closing cor. of Tps. 18 and 19 N., R. 18 E., hereinafter described.</p> <p>37.229 Mile Post 175, monumented with an iron post, 3 ins. diam., firmly set, projecting 13 ins. above ground, in mound of stone, 3 ft. diam., 6 ins. high, with brass cap mkd. as described in the field notes of the 1918 resurvey, from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A decayed pine stump, 40 ins. diam., bears N. 20° E., 112 lks. dist., no marks visible. (Record, N. 17°20' E., 114 lks.)</p> <p style="padding-left: 40px;">A decayed pine stump, 30 ins. diam., bears S. 77° E., 113 lks. dist., no marks visible. (Record, S. 79°15' E., 112 lks.)</p> <p style="padding-left: 40px;">A decayed pine stump, 20 ins. diam., bears N. 85 1/4° W., 87 lks. dist., no marks visible. (Record, N. 84°30' W., 94 lks.)</p> <p>and the 1918 bearing trees</p> <p style="padding-left: 40px;">A Jeffrey pine, 24 ins. diam., bears N. 42°30' E., 214 lks. dist., with healed blaze. (Record, 260 lks.)</p> <p style="padding-left: 40px;">A Jeffrey pine, 16 ins. diam., bears S. 75 1/4° E., 124 lks. dist., with healed blaze. (Record, S. 76°00' E.)</p> <p style="padding-left: 40px;">A stump hole, 2 ft. diam., with remains of pine snag alongside, bears S. 60°30' W., 110 lks. dist., with partial illegible scribe marks visible.</p> <p style="padding-left: 40px;">A Jeffrey pine, 16 ins. diam., bears N. 41°00' W., 132 lks. dist., with healed blaze. (Record, 130 lks.)</p> <p>Cor. is located on NW slope with mountain mahogany and pine timber.</p> <hr/>
--------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

DEPENDENT RESURVEY OF PORTIONS OF THE
OLD CALIFORNIA-NEVADA STATE LINE,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, CALIFORNIA

CHAINS	<p>Reestablishment of Portions of the Survey Executed by S.W. Foreman, U.S. Deputy Surveyor, in 1865, Portions of the Retracement Executed by W.J. Lightfoot, U.S. Surveyor, in 1913-1914 and the Dependent Resurvey Executed by E. Voigt, U.S. Transitman, in 1918</p> <hr/> <p>From the cor. of secs. 6, 6, 31, and 31, on the S. bdy. of the Tp., monumented with an iron post, 3 ins. diam., loosely set, projecting 22 ins. above ground, with brass cap mkd. as described in the field notes of the 1918 resurvey from which the original bearing trees</p> <p>A cedar, 36 ins. diam., bears N. 8° E., 34 lks. dist., with scribe marks T19N 18RE BT visible on partially healed blaze. (1865 and 1918 Records, 36 lks.)</p> <p>A stump hole with pine bark remains, 3 ft. diam., bears N. 78 1/2° W., 48 lks. dist., with remains of decayed snag alongside, 29 ins. diam., with weathered blaze with illegible scribe marks. (1865 and 1918 Records, 57 lks.)</p> <p>and a new bearing tree</p> <p>A Jeffrey pine, 22 ins. diam., bears S. 54° E., 56.5 lks. dist., mkd. X BT on the southerly fork, 22 ins. diam., of a double forked tree.</p> <p>Rehabilitate monument.</p> <p>Cor. is located on a steep S. slope with pine, cedar and mountain mahogany in rocky soil.</p> <p>N. 0°01'10" W., on the old California-Nevada State Line bet. secs. 31 and 31.</p> <p>40.195 The 1/4 sec. cor. of secs. 31 and 31, monumented with an iron post, 1 in. diam., loosely set, projecting 25 ins. above ground, with brass cap mkd. as described in the field notes of the 1918 resurvey, from which the original bearing tree</p> <p>A ponderosa pine, 37 ins. diam., bears S. 60° E., 60 lks. dist., with chopped open blaze, no marks visible. (1865 Record, S. 65° E., 1918 Record, S. 65°30' E.)</p> <p>and a tree not of record</p> <p>A white fir snag, 38 ins. diam., bears N. 62° W., 128 lks. dist., with open blaze and ax marks, no scribe marks visible.</p> <p>and a new accessory</p> <p>A granite boulder, 6 x 7 x 4 ft. high, bears N. 82°00' W., 29.5 lks. dist., mkd. BXO on SE face, 2 ft. above ground.</p> <p>Rehabilitate monument.</p>
--------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

121

DEPENDENT RESURVEY OF PORTIONS OF THE
 OLD CALIFORNIA-NEVADA STATE LINE,
 T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, CALIFORNIA

CHAINS	<p>Cor. is located on a steep NE slope with pine, fir, birch, and tobacco brush.</p> <hr/> <p>N. 0°10'50" E., beginning new measurement.</p>
20.142	<p>Point for the N 1/16 sec. cor. of secs. 31 and 31.</p> <p>Not monumented.</p>
40.284	<p>The cor. of secs. 30, 30, 31, and 31, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. as described in the field notes of the 1918 resurvey.</p> <p>from which new bearing trees</p> <p>A Jeffrey pine, 15 ins. diam., bears N. 42° E., 116 lks. dist., mkd. T19NR18E S30 BT.</p> <p>A Jeffrey pine, 16 1/2 ins. diam., bears S. 80 1/2° W., 78 lks. dist., mkd. T19NR18E S31 BT.</p> <p>A Jeffrey pine, 16 1/2 ins. diam., bears N. 29° W., 86 lks. dist., mkd. T19NR18E S30 BT.</p> <p>Cor. is located on a steep brush covered NE slope with scattered pine and fir.</p> <hr/> <p>N. 0°02'20" W., on the old California-Nevada State Line bet. secs. 30 and 30.</p>
1.40	<p>Center of graded dirt road, 15 lks. wide, bears N. 52° W. and S. 31° E. in curve.</p>
20.065	<p>Point for the S 1/16 sec. cor. of secs. 30 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S30 S30 1999</p> <p>from which</p> <p>An igneous boulder, 3 x 5 x 4 ft. high, bears N. 49°00' E., 72.2 lks. dist., mkd. BXO on top.</p> <p>An igneous boulder, 6 x 4 x 4 ft. high, bears S. 74°10' E., 101.2 lks. dist., mkd. BXO on top face, 1 ft. from S. edge.</p>
40.130	<p>The 1/4 sec. cor. of secs. 30 and 30, monumented with an iron post, 1 in. diam., loosely set, projecting 25 ins. above ground, with brass cap mkd. as described in the field notes of the 1918 resurvey. Alongside the iron post, an igneous stone, 15 x 8 ins., projecting 10 ins. above the ground, mkd. 1/4 on a face.</p>

DEPENDENT RESURVEY OF PORTIONS OF THE
OLD CALIFORNIA-NEVADA STATE LINE,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, CALIFORNIA

CHAINS	<p>from which new accessories</p> <p>A cedar, 5 ins. diam., bears N. 50 3/4° E., 63 lks. dist., mkd. X BT.</p> <p>An igneous boulder, 6 x 7 x 5 ft. high, bears S. 80°20' E., 487.5 lks. dist., mkd. BXO on NW face, 4 ft. above ground.</p> <p>Bury mkd. stone alongside iron post and rehabilitate monument.</p> <p>Cor. is located on moderate NE slope in heavy brush and scattered pine.</p> <hr/> <p>N. 0°00'10" E., beginning new measurement.</p> <p>19.671 The N 1/16 sec. cor. of secs. 30 and 30, determined by Dale D. Kulm, California Registered Civil Engineer No. 16895, monumented with an iron rod, 3/4 in. diam., firmly set, projecting 6 ins. above ground, and in a mound of stone, 3 ft. diam., 2 ft. high, as shown on an unrecorded survey obtained from Mr. Kulm. Monument was set as part of the resurvey and subdivision of sec. 30. This is accepted as a careful determination of the position of the corner.</p> <p>Not remonumented.</p> <hr/> <p>N. 0°01'50" W., beginning new measurement.</p> <p>19.731 The cor. of secs. 19, 19, 30, and 30, monumented with an iron post, 2 ins. diam., firmly set, projecting 2 ins. above a mound of stone, 2 ft. base, 10 ins. high, with brass cap mkd. as described in the field notes of the 1918 resurvey. Alongside the iron post, a granite stone, 13 x 6 ins., projecting 14 ins. above the ground, mkd. with 2 notches on S. edge and 5 notches on N. edge, and in a mound of stone, 2 1/2 ft. diam., 6 ins. high, from which the remains of the 1918 bearing tree</p> <p>A stump hole, 2 ft. diam., bears S. 65 1/2° E., 54.5 lks. dist., with burnt root crown and fallen pine snag, 21 ins. diam., lying alongside. (Record, S. 56°25' E., 46 lks.)</p> <p>and new accessories</p> <p>A Jeffrey pine, 18 ins. diam., bears N. 60° E., 60 lks. dist., mkd. T19N R18E S19 BT.</p> <p>A granite boulder, 3 x 2 x 1 ft. high, bears S. 85°10' E., 89.7 lks. dist., mkd. BXO on top.</p> <p>Cor. is located on a moderate N. slope with fir, pine, and heavy brush on rocky soil.</p> <hr/> <p>From the cor. of secs. 7, 7, 18, and 18, monumented by Theodore A. Fox, California Registered Land Surveyor No. 4035, for the U.S. Forest Service, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 15 ins. above ground, and in a scattered mound of stone, 4 ft. base, 1 ft. high, with brass cap mkd. USFS T19N R18E S7 S7 S18 S18 LS 4035.</p>
--------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

DEPENDENT RESURVEY OF PORTIONS OF THE
OLD CALIFORNIA-NEVADA STATE LINE,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, CALIFORNIA

CHAINS	<p>This monument falls at the position of a marked stone recovered by Dale D. Kulm, California Registered Civil Engineer No. 16895, as recorded in Sierra County, Book 3, of Maps and Surveys, Page 97, and is accepted as the best available evidence of the position of the original corner.</p> <p>from which new accessories</p> <p>An igneous boulder, 7 x 7 x 6 1/2 ft. high, bears S. 20°50' E., 22.0 lks. dist., mkd. BXO on N. face, 3 ft. above ground.</p> <p>An igneous boulder, 4 x 3 x 2 1/2 ft. high, bears N. 3°30' W., 38.5 lks. dist., mkd. BXO on S. face, 2 ft. above ground.</p> <p>Rebuild mound of stone, 4 ft. base to top.</p> <p>Cor. is located on rocky WSW slope in burn area.</p> <p>N. 0°38'00" E., on the old California-Nevada State Line bet. secs. 7 and 7.</p>
1.514	<p>The point on line, established by Dale D. Kulm, California Registered Civil Engineer No. 16895, in 1971, an iron pipe, 1 in. diam., firmly set, projecting 3 ins. above ground, in a collar of stone, 2 ft. diam., as recorded in Sierra County, Book 3, of Maps and Surveys, Page 97, set for a Sierra Pacific Power Co. right-of-way.</p>
19.800	<p>The S 1/16 sec. cor. of secs. 7 and 7, monumented by Theodore A. Fox, California Registered Land Surveyor No. 4035, for the U.S. Forest Service, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above ground, and in a scattered collar of stone, 2 ft. base, with brass cap mkd. USFS 1/16 S7 S7 1973 LS 4035. This monument falls at the position originally determined and monumented by Dale D. Kulm, California Registered Civil Engineer No. 16895, in 1971, as recorded in Sierra County, Book 3, of Maps and Surveys, Page 97 and Book 4, Maps and Surveys, Page 93, and is accepted as a careful and faithful determination of the position of the corner.</p> <p>Cor. is located on SE slope with scattered pine.</p>
19.800	<p>N. 0°38'10" E., beginning new measurement.</p> <p>The 1/4 sec. cor. of secs. 7 and 7, perpetuated by Theodore A. Fox, California Registered Land Surveyor No. 4035, for the U.S. Forest Service, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap, 3 1/2 ins. diam., mkd. USFS T19N R18E 1/4 S7 S7 LS 4035, and in a collar of stone, 1 1/2 ft. base, with igneous stone, 17 x 9 x 6 ins., 4 ft. down slope from pipe, among scattered grouping of stones, 4 ft. diam., with chisel marks 1/4 on face (1913 Record, trachyte 18 x 14 x 12 ins.), from which the remains of an original bearing tree</p>

DEPENDENT RESURVEY OF PORTIONS OF THE
OLD CALIFORNIA-NEVADA STATE LINE,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, CALIFORNIA

CHAINS	<p>A burned pine stump, with snag alongside, 30 ins. diam., bears N. 78° E., 35 lks. dist., no marks visible (matches 1913 Record), (1865 Record, N. 78 1/2° E., 24 lks.)</p> <p>Deposit mkd. stone alongside iron post.</p> <p>Cor. is located on steep WSW slope.</p> <hr/> <p>N. 0°19'20" W., beginning new measurement.</p>
20.045	<p>The N 1/16 sec. cor. of secs. 7 and 7, determined by Dale D. Kulm, California Registered Civil Engineer No. 16895, monumented with an iron pipe, 1 in. diam., firmly set, projecting 2 ins. above ground, and in a mound of stone, 2 ft. diam., with brass cap, 2 ins. diam., punch mkd. 15 and a brass washer attached, mkd. RCE 16895, an unrecorded monument set as part of the subdivision of sec. 7. This is accepted as a careful and faithful determination of the cor. position.</p> <p>Not remonumented.</p> <p>From this corner, the lot corner established by John E. Curran, California Registered Land Surveyor No. 2356, a galvanized iron pipe, 3/4 ins. diam., loosely set, projecting 3 1/2 ins. above ground, and in a collar of stone, 1 ft. diam., no marks, bears N. 26°00' E., 9.1 lks. dist., matches monument set by John E. Curran, L.S. No. 2356, in 1948, as recorded in Sierra County, Book 1, of Maps and Surveys, Page 20, and is not utilized in this resurvey.</p> <p>From this same corner, the lot corner established by Richard W. Arden, California Registered Civil Engineer No. 13156, in 1968, an iron rod, 1/2 in. diam., loosely set, projecting 8 ins. above ground, with tag mkd. RCE 13156, bears N. 4°31' W., 22.6 lks. dist., as recorded in Sierra County, Book 2, of Maps and Surveys, Page 91, and is not utilized in this resurvey.</p> <p>Cor. is located on E. slope of spur, slopes NW.</p> <hr/> <p>N. 0°25'20" W., beginning new measurement.</p>
20.039	<p>The cor. of secs. 6, 6, 7, and 7, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 24 ins. above ground, and in a mound of stone, 2 1/2 ft. base, with brass cap mkd. as described in the field notes of the 1918 resurvey.</p> <p>from which</p> <p>A ponderosa pine, 26 ins. diam., bears S. 63° E., 248 lks. dist., mkd. T19N R18E S7 BT.</p> <p>An igneous boulder, 2 1/2 x 1 1/2 x 3/4 ft. high, bears N. 74°50' W., 158.2 lks. dist., mkd. BXO on SE face, 1/2 ft. above ground.</p>

DEPENDENT RESURVEY OF PORTIONS OF THE
OLD CALIFORNIA-NEVADA STATE LINE,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, CALIFORNIA

CHAINS	<p>Rebuild mound of stone, 3 ft. base, to top.</p> <p>Cor. is located on open rocky NE slope in burn area.</p> <hr/> <p>N. 0°04'50" W., on the old California-Nevada State Line bet. secs. 6 and 6.</p> <p>19.861 Point for the S 1/16 sec. cor. of secs. 6 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 5 ins. in the ground over a plastic-encased magnet, and in a mound of stone, 6 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S6 S6 1999</p> <p>from which</p> <p style="padding-left: 40px;">An igneous boulder, 2 x 2 1/2 x 2 ft. high, bears N. 81°40' E., 106.1 lks. dist., mkd. BXO on SW face, 1 ft. above ground.</p> <p style="padding-left: 40px;">A Jeffrey pine, 20 ins. diam., bears S. 5 1/2° W., 46 lks. dist., mkd. S1/16 S6 BT.</p> <p>Cor. is located on a steep SE slope with pine, mountain mahogany, and sage in a rocky soil, N., 2.12 chs. of a deep ravine, 6 lks. wide, drains S. 66° E.</p> <p>39.722 The 1/4 sec. cor. of secs. 6 and 6, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, and in a collar of stone, 2 ft. base, 6 ins. high, with brass cap mkd. as described in the field notes of the 1918 resurvey, from which the 1918 bearing trees</p> <p style="padding-left: 40px;">A pine, 23 ins. diam., bears S. 53 3/4° E., 108 lks. dist., with healed blaze. (Record, S. 42°45' E.)</p> <p style="padding-left: 40px;">A pine, 30 ins. diam., bears S. 67 1/2° W., 71 lks. dist., with healed blaze. (Record, S. 72°30' W.)</p> <hr/> <p>N. 0°05'50" W., beginning new measurement.</p> <p>39.628 The cor. of secs. 6, 6, 31, and 31, on the N. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 13 ins. above ground, with brass cap mkd. as described in the field notes of the 1918 resurvey, with igneous stone, 21 x 15 x 7 ins., lying alongside, no marks visible, from which the remains of the 1918 bearing trees</p> <p style="padding-left: 40px;">A root hole, 2 ft. diam., with decayed pine remains alongside bears S. 33 1/4° E., 67 lks. dist., no marks visible. (Record, S. 31°45' E.)</p> <p style="padding-left: 40px;">A Jeffrey pine, 23 ins. diam., bears N. 77°50' W., 95 lks. dist., with healed blaze. (Record, 96 lks.)</p>
--------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

DEPENDENT RESURVEY OF PORTIONS OF THE
OLD CALIFORNIA-NEVADA STATE LINE,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, CALIFORNIA

CHAINS

and new accessories

A granite boulder, 5 x 5 x 3 ft. high, bears
S. 4°00' E., 66.0 lks. dist., mkd. BXO on top face.

A granite boulder, 5 x 3 x 2 1/2 ft. high, bears
S. 36°30' W., 77.8 lks. dist., mkd. BXO on NE face,
1 ft. above ground.

A Jeffrey pine, 28 ins. diam., bears N. 35° W.,
154 lks. dist., mkd. T20N R18E S31 BT.

Cor. is located on level ground with pine, fir, and sage, a
sandy soil in wash area on SW side of Dog Creek.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

Reestablishment of a Portion of the Survey Executed by
S.W. Foreman, U.S. Deputy Surveyor, in 1865,
the Dependent Resurvey Executed by
E. Voigt, U.S. Transitman, in 1918,
and the Remonumentation Executed by
R.A. Pratt and W.L. Jepson, Cadastral Surveyors, in 1966

From the cor. of secs. 4, 5, 32, and 33, monumented with an iron
post, 2 1/2 ins. diam., firmly set in a mound of stone, 5 ft.
base, 4 ft. high, to top, with brass cap mkd. as described in
the field notes of the 1966 remonumentation, from which the
remains of the original bearing trees

A Jeffrey pine, 5 ft. diam., bears S. 1 3/4° E.,
118 lks. dist., with scribe marks 18E S5 visible on
partially healed blaze. (1865 and 1966 Records,
S. 3 1/2° W., 125 lks.)

A pine snag, 7 ft. diam., bears N. 59 1/2° W., 118 lks.
dist., with healed blaze. (1865 and 1966 Records,
N. 66 1/2° W., 123 lks.)

and the 1966 bearing trees

A Jeffrey pine, 25 ins. diam., bears S. 43° E.,
36.3 lks. dist., with healed blaze. (1966 Record,
S. 44° E., 37 lks.)

A Jeffrey pine, 25 ins. diam., bears N. 36 1/2° W.,
80 lks. dist., with healed blaze. (1966 Record,
N. 36° W.)

Cor. is located on a WSW slope, with Jeffrey pine, fir, and
mountain mahogany.

N. 89°52'10" W., bet. secs. 5 and 32.

20.114

Point for the E 1/16 sec. cor. of secs. 5 and 32.

Not monumented.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	
40.228	<p>The 1/4 sec. cor. of secs. 5 and 32, monumented with an igneous stone, 15 x 12 x 19 ins. (Record, 20 x 12 x 12 ins.), no marks visible, set in center of an embedded mound of stone, 3 x 2 ft., 12 ins. high from which a small rock pinnacle, 4 x 5 ft., 10 ft. high, bears S. 28° E., 40 lks. dist., (Record, "A high rock 50 lks. South of cor.")</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T19N R18E</p> <p>S32</p> <p>1/4 —</p> <p>S 5</p> <p>T18N</p> <p>1999</p> </div> <p>from which</p> <p style="padding-left: 40px;">An igneous rock face, 1 ch. wide, bears S. 2°20' E., 12.2 lks. dist., mkd. BXO on W. face.</p> <p>Deposit stone alongside the stainless steel post.</p> <p>Cor. is located on top of rock spur, 1 ch. wide, slopes N. 30° W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°57'00" W., beginning new measurement.</p>
40.369	<p>The cor. of secs. 5, 6, 31, and 32, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd. as described in the field notes of the 1966 remonumentation, from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A pine snag, 17 ins. diam., bears N. 84° W., 37 lks. dist., with partial scribe marks 8N R18E S31 BT visible on deep weathered blaze.</p> <p style="padding-left: 40px;">A pine snag, 31 ins. diam., bears N. 45° W., 47 lks. dist., with partial scribe marks XXX I visible on weathered chopped open blaze. (1865 Record, N. 46° W.)</p> <p>and the 1966 bearing trees</p> <p style="padding-left: 40px;">A pine snag, 28 ins. diam., bears N. 7° E., 80 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A mountain mahogany, 7 ins. diam., bears S. 15° E., 14 lks. dist., with scribe marks BT S6 visible on partially healed blaze.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	<p>Note: The 1918 Resurvey Record reports setting an iron post alongside a mkd. granite stone, and ties to the original bearing trees of S. 64°15' W., 49 lks., and S. 45° W., 72 lks. dist. There are additional ties to 3 new bearing trees.</p> <p>The 1966 Remonumentation Record reports finding a mound of stone which matches the record bearings and distances to the original bearing trees, however it does not document recovery of the 1918 monument or its accessories. The 1918 record position bears N. 13°26' E., 61.2 lks. dist. from the 1966 monument based on the recovered original bearing trees.</p> <p>A scattered grouping of stones including one stone, 21 x 18 x 5 ins. (1918 Record, 22 x 16 x 4 ins.), with no definite marks, was recovered at the 1918 Record position. No evidence of the iron pipe was found. The remains of the 1918 record bearing trees, all snag remains, were recovered down slope from the 1918 record bearings and distances, but the stump holes were not clearly defined. The NE tree is 2 ft. diam., with weathered face, and faint illegible scribe marks. The other two snags were well weathered with ax marks visible.</p> <p>from the 1966 accepted position, add new bearing trees</p> <p>A Jeffrey pine, 10 ins. diam., bears N. 45° E., 43.5 lks. dist., mkd. S32 BT.</p> <p>A Jeffrey pine, 11 ins. diam., bears S. 23° W., 13 lks. dist., mkd. S6 BT.</p> <p>Cor. is located on a steep N. slope, with Jeffrey pine and mountain mahogany.</p> <p>From this corner, an iron pipe, 1 in. diam., loosely set, projecting 22 ins. above ground, bears S. 80° E., 5.1 lks. dist., no marks. This monument is not utilized in this survey.</p>
39.845	<p>N. 89°15'10" W., bet. secs. 6 and 31.</p> <p>The 1/4 sec. cor. of secs. 6 and 31, monumented with an iron post, 1 in. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd. as described in the field notes of the 1918 resurvey, from which the remains of the original bearing trees</p> <p>A stump hole with pine bark remains, 2 ft. diam., bears S. 20° W., 39 lks. dist., no marks visible.</p> <p>A pine snag, 30 ins. diam., 6 ft. high, bears N. 38° W., 15 lks. dist., mkd. 1/4 S on open blaze and reverse scribe marks visible on fallen remains. (1865 and 1918 Records, 22 lks.)</p> <p>and the 1918 bearing trees</p> <p>A ponderosa pine, 23 ins. diam., bears N. 37°10' E., 77 lks. dist., with healed blaze.</p> <p>A ponderosa pine, 21 ins. diam., bears S. 11°50' W., 67 lks. dist., with healed blaze.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	<p>and an unrecorded accessory</p> <p>A concrete cylinder, 4 ins. diam., firmly set, projecting 5 ins. above ground, bears N. 35° W., 2.4 lks. dist., with iron cap, 4 1/2 ins. diam., with Stone and Webster cap markings.</p> <p>Cor. is located on gradual WNW slope, pine, scattered cedar, and mountain mahogany.</p> <hr/> <p>S. 89°44'40" W., beginning new measurement.</p> <p>4.665 The 1918 closing cor. of secs. 6, 6, 31, and 31, monumented with an iron post, 3 ins. diam., firmly set, projecting 13 ins. above ground, and in a mound of stone, 3 ft. diam., to top, with brass cap mkd. as described in the field notes of the 1918 resurvey, from which the remains of the 1918 bearing trees</p> <p>A ponderosa pine, 40 ins. diam., bears N. 64°45' E., 102 lks. dist., with partial scribe marks visible on mostly healed blaze. (Record, N. 65°40' E.)</p> <p>A ponderosa pine, 34 ins. diam., bears S. 36°10' E., 85 lks. dist., with scribe marks T18NR18E S6 visible on partially healed blaze. (Record, S. 34°30' E.)</p> <p>A pine stump hole, 2 ft. diam., bears S. 54°30' W., 119 lks. dist. (Record, S. 55°30' E.)</p> <p>A pine stump hole, 2 ft. diam., bears N. 23°40' W., 75 lks. dist. (Record, N. 22°15' W.)</p> <p>and new bearing trees</p> <p>A ponderosa pine, 17 ins. diam., bears S. 63 1/2° W., 107.5 lks. dist., mkd. CC T18NR18E S6 BT.</p> <p>A ponderosa pine, 15 ins. diam., bears N. 46 1/2° W., 81.5 lks. dist., mkd. CC T19NR18E S31 BT.</p> <p>Cor. is located on gradual NW slope, 36 lks. E. of jeep trail, 15 lks. wide, bears S. 23° W. and N. 23° E. also 74 lks. S. of same jeep trail, bears S. 27° W. and N. 27° E.</p> <hr/> <p>S. 89°42'40" W., beginning new measurement.</p> <p>0.051 Intersect the California-Nevada State Line.</p> <p>Point for the closing cor. of Tps. 18 and 19 N., R. 18 E.</p> <p>Not monumented.</p> <p>From this point, Mile Post 175, bears S. 1°08'30" W., 10.458 chs. dist., hereinbefore described.</p> <p>57.149 The cor. of secs. 6, 6, 31, and 31, on the old California-Nevada State Line, hereinbefore described.</p> <hr/>
--------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Reestablishment of a Portion of the Survey Executed by E.H. Dyer, U.S. Deputy Surveyor, in 1863</p> <hr/> <p>From the 1/4 sec. cor. of secs. 19 and 24, monumented with a stone, 11 x 7 x 9 ins. (Record, 12 x 5 x 5 ins.), no marks visible, set in center depression of an embedded mound of stone, 3 1/2 ft. diam., 6 ins. high.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T19N R18E R19E 1/4 S24 S19 1998</p> <p>from which</p> <p style="padding-left: 40px;">An embedded igneous boulder, 5 x 2 x 1 1/4 ft. high, bears S. 29°10' W., 47.2 lks. dist., mkd. BXO on NNE face, 1 ft. above ground.</p> <p>Deposit stone along W. side of stainless steel post.</p> <p>Cor. is located on open rocky mesa with grasses.</p> <p>From this corner, the locally accepted 1/4 sec. cor. of secs. 19 and 24, determined by Alan Means, Nevada Registered Land Surveyor No. 3573 and California Registered Civil Engineer No. 23112, in 1979, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 2 ins. above ground, and in a mound of stone, 3 ft. diam., 1/2 ft. high, bears S. 31°00' E., 4.30 chs. dist., with metal tag attached mkd. CE 23112, as recorded in Washoe County, Land Map No. 43B. This monument is not utilized in this resurvey.</p> <p>From this same corner, National Geodetic Survey control (formerly U.S.C. & G.S. triangulation) station "HUNTER", evidenced with the stem remains of the Record brass tablet cemented in a drill hole in an igneous rock formation, bears S. 47°14'40" E., 57.564 chs. dist., and verified with ties to the identifiable Reference Mark remains. Only the brass tablet for the SE Reference Mark is found in place.</p> <p>N. 0°25'30" W., bet. secs. 19 and 24.</p> <p>18.808 The point for Angle Point No. 1, of the metes-and-bounds survey in sec. 24, hereinafter described.</p> <p>26.50 Ravine, 10 lks. wide, drains E. of NE.</p>
--------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
34.436	<p>Point for the original meander cor. of secs. 19 and 24, for the right bank of the Truckee River, at proportionate dist., there is no remaining evidence of the original cor.</p> <p>Not monumented.</p>
35.85	<p>Right bank of the Truckee River, bears S. 50° E.</p>
37.044	<p>Point for the original meander cor. of secs. 19 and 24, for the left bank of the Truckee River, at proportionate dist., there is no remaining evidence of the original cor. tree.</p> <p>Not monumented.</p>
37.50	<p>Left bank of the Truckee River, bears S. 43° E.</p>
41.740	<p>Point for the cor. of secs. 13, 18, 19, and 24, reestablished from ties to private survey monuments, falls in paved parking lot, there is no remaining evidence of the original monument, from which</p> <p>A lot corner, established by Don M. McHarg, Nevada Professional Land Surveyor No. 4787, in 1995, an iron rod, 5/8 in. diam., firmly set, flush with surface, bears S. 41°44' E., 350.7 lks. dist., with plastic cap, 1 1/4 ins. diam., mkd. SUMMIT ENGRG PLS4787, as recorded in Washoe County, Record of Survey Map Nos. 2858 and 2865. Note: The Record of Survey shows the tie incorrectly.</p> <p>A lot corner, established by Don M. McHarg, Nevada Professional Land Surveyor No. 4787, in 1995, an iron rod, 5/8 in. diam., firmly set, 3 ins. below surface, bears S. 44°53' E., 725.1 lks. dist., with plastic cap, 1 1/4 ins. diam., marks illegible, as recorded in Washoe County, Record of Survey Map No. 2865. Correct tie as recorded in Washoe County, Subdivision Tract Map No. 2771A. Note: tie made to verify error on Record of Surveys.</p> <p>A reference object, established by person(s) unknown, a chiseled X on top face of downward sloping concrete bridge wall, 1 ft. wide, bears N. 50°21' W., 859.8 lks. dist., used as tie, as recorded in Washoe County, Record of Survey Map Nos. 2858, 2865, and 3014. Concrete wall bears E. and W., with marks located East, 19.15 ft., measured on slope from level top of wall, at the NE end of White Fir Street bridge over the Truckee River.</p> <p>The above iron rods are in danger of destruction by new development.</p> <p>At the corner point</p> <p>Set an asphalt nail flush with pavement.</p>

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

from which more permanent local survey monuments

A copper coated steel rod, with unmarked cap, 1 1/2 ins. diam., bears S. 70°41' E., 848.1 lks. dist., 5 ins. below surface of Sugar Pine cul-de-sac, paved surface, in survey monument casing, 8 ins. diam., as recorded in Washoe County, Subdivision Tract Map No. Map 2771A.

A copper coated steel rod, with cap, 1 1/2 ins. diam., mkd. PLS 4043, bears N. 48°19' W., 902.3 lks. dist., 4 ins. below surface of White Fir Street, paved surface and at N. end of bridge over Truckee River, in survey monument casing, 8 ins. diam., as recorded in Washoe County, Subdivision Tract Map No. 2771A.

Cor. is located on level paved parking lot of Patagonia Store, 10 ft. North of concrete curb, bears NE and SW.

From this corner, the 1/4 sec. cor. of secs. 13 and 18, determined by person(s) unknown, bears N. 0°12'10" W., 39.904 chs. dist., monumented with a concrete cylinder, firmly set, 4 ins. diam., projecting 4 ins. above ground, with iron rod, 5/8 in. sq., set flush in center, mkd. with an X on top, accepted by local surveyors, as recorded in Washoe County, Record of Survey Map Nos. 648, 695A and 2017. This is accepted as the best available evidence of the position of the original corner.

Not remonumented.

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

Reestablishment of a Portion of the Survey Executed by
S.W. Foreman, Deputy Surveyor, in 1865,
and a Portion of the Dependent Resurvey Executed by
E. Voigt, U.S. Transitman, in 1918

From the cor. of secs. 5, 6, 31, and 32, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. as described in the field notes of the 1918 resurvey, alongside of which is a granite stone, 20 x 13 x 8 ins. (Record, 30 x 10 x 8 ins.), with faint marks and in a mound of stone, 3 ft. base, 12 ins. high, from which the remains of a 1918 bearing tree

A burned pine snag base, 21 ins. diam., bears S. 18° W., 176 lks. dist., no marks visible. (Record, 1.80 chs.)

and new bearing trees

A Jeffrey pine, 13 ins. diam., bears N. 54° E., 82 lks. dist., mkd. T20N R18E S32 BT.

A Jeffrey pine, 8 ins. diam., bears S. 10° W., 110 lks. dist., mkd. X BT.

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	<p>A Jeffrey pine, 30 ins. diam., bears N. 81° W., 36 lks. dist., mkd. T20N R18E S31 BT.</p> <p>Cor. is located on steep SE sage slope with scattered Jeffrey pine.</p> <p>S. 89°35'00" W., bet. secs. 6 and 31.</p> <p>21.930 Point for the E 1/16 sec. cor. of secs. 6 and 31.</p> <p>Not monumented.</p> <p>42.149 The 1918 closing cor. of secs. 6, 6, 31, and 31, monumented with an iron post, 2 ins. diam., firmly set, projecting 17 ins. above ground, and in a mound of stone, 3 1/2 ft. diam., to top, with brass cap mkd. as described in the field notes of the 1918 resurvey.</p> <p>Cor. is located on open SE rocky sagebrush slope with scattered pine, 1/2 ch. E. of a fence, 4 wire, bears N. and S.</p> <hr/> <p>N. 89°09'00" W., beginning new measurement.</p> <p>0.071 Intersect the California-Nevada State Line.</p> <p>Point for the closing cor. of Tps. 19 and 20 N., R. 18 E.</p> <p>Not monumented.</p> <p>From this point, Mile Post 169, bears S. 0°01'50" W., 7.058 chs. dist., hereinbefore described.</p> <p>2.038 The 1/4 sec. cor. of secs. 6 and 31, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd. as described in the field notes of the 1918 resurvey, from which a 1918 bearing tree</p> <p>A mountain mahogany, 6 ins. diam., bears S. 2 1/2° E., 51 lks. dist., with illegible scribe marks visible on partially healed blaze. (Record, South, 50 lks.)</p> <p>and new bearing tree</p> <p>A Jeffrey pine, double trunks, each 8 ins. diam., bears S. 55° E., 52 lks. dist., mkd. 1/4 S6 BT on westerly trunk.</p> <p>Cor. is located on open rocky SSE sagebrush slope with scattered pine.</p> <p>From this corner, the cor. of secs. 6, 6, 31, and 31, on the old California-Nevada State Line and the N. bdy. of the Tp., bears S. 89°12'20" W., 60.599 chs. dist., hereinbefore described.</p> <hr/>
--------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

<p>CHAINS</p>	<p>Reestablishment of a Portion of the Survey Executed by S.W. Foreman, U.S. Deputy Surveyor, in 1865, Portions of the Retracement Executed by W.J. Lightfoot, U.S. Surveyor, in 1913-1914, and Portions of the Retracement and Dependent Resurvey Executed by E. Voigt, U.S. Transitman, in 1918</p> <hr/> <p>From the 1/4 sec. cor. of secs. 24 and 25, perpetuated by Alan Means, Nevada Registered Land Surveyor No. 3573, in 1979, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 2 ins. above ground, with partially melted plastic cap mkd. RLS 3573, and in a collar of stone, 2 1/2 ft. diam., with faint chisel marks on one stone, 22 x 9 x 7 ins. (Record, 20 x 9 x 8 ins.) The iron rod is a remonumentation of a rock mound as recorded in Washoe County, Land Map No. 43B, and is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T19N R18E S24 1/4 — S25 1998</p> <p>No accessories available.</p> <p>Deposit iron rod, 19 ins. long, inside the stainless steel post.</p> <p>Deposit the stone alongside the stainless steel post.</p> <p>Cor. is located on open level rocky ground.</p> <p>N. 89°22'10" W., bet. secs. 24 and 25.</p> <p>39.643 The cor. of secs. 23, 24, 25, and 26, perpetuated by Alan Means, Nevada Registered Land Surveyor No. 3573, in 1979, monumented with an iron rod, 5/8 in. diam., loosely set, projecting 10 ins. above ground, with metal tag attached mkd. RLS 3573, and in a mound of stone, 4 ft. diam., 15 ins. high, and one stone, 24 x 14 x 9 ins. in mound with faint notches. The iron rod is a remonumentation of a rock mound as recorded in Washoe County, Land Map Nos. 43A and 43B, and is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>Not remonumented.</p> <p>Rehabilitate monument.</p> <p>Cor. is located on open rocky W. slope 50 lks. E. of jeep trail, 9 ft. wide, bears N. 10° W., and S. 15° E. in curve.</p> <hr/>
---------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

135

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	N. 0°40'30" E., bet. secs. 23 and 24.
39.800	<p>The 1/4 sec. cor. of secs. 23 and 24, perpetuated by Alan Means, Nevada Registered Land Surveyor No. 3573, in 1979, monumented with an iron rod, 5/8 in. diam., loosely set, projecting 8 ins. above ground, with metal tag attached mkd. RLS 3573, with stone alongside, 19 x 13 x 5 ins., no marks visible and in a mound of stone, 3 ft. diam., 12 ins. high. The iron rod is a remonumentation of a rock mound as recorded in Washoe County, Land Map No. 43A, and is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T19N R18E 1/4 S23 S24 1998</p> </div> <p>Deposit iron rod, 17 ins. long, inside the stainless steel post.</p> <p>Deposit the stone alongside the stainless steel post.</p> <p>Cor. is located on open rocky W. slope.</p> <hr/> <p>N. 0°58'00" E., beginning new measurement.</p>
39.799	<p>Point for the cor. of secs. 13, 14, 23, and 24, at proportionate dist. bet. the 1/4 sec. cors. to the N., S. and W., and the W 1/16 sec. cor. of secs. 13 and 24, based on local survey information, falls on slope affected by land slide, there is no remaining evidence of the original cor. or of the local survey perpetuation of a rock mound as recorded in Washoe County, Land Map Nos. 43A and 43B.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T19N R18E S14 S13 ----- S23 S24 1998</p> </div> <p>from which</p> <p>An embedded igneous boulder, 6 x 4 x 5 ft. high, bears N. 31°40' E., 397.6 lks. dist., mkd. BXO on WSW face, 1 1/2 ft. above ground.</p> <p>A Jeffrey pine, 27 ins. diam., bears S. 34 3/4° W., 303 lks. dist., mkd. 1/4 S23 BT.</p>

136

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

<p>CHAINS</p>	<p>Raise a mound of stone, 2 1/2 ft. diam., 3/4 ft. high, 2 1/2 ft. to W.</p> <p>Cor. is located on an open E. slope.</p> <hr/> <p>From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°23'50" W., bet. secs. 13 and 24.</p> <p>34.002 The 1/4 sec. cor. of secs. 13 and 24, at proportionate dist., bet. sec. cors. to the E. and the W 1/16 sec. cor. of secs. 13 and 24, based on local survey information, there is no remaining evidence of the original cor. or local monument as recorded in Washoe County, Land Map No. 43B.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T19N R18E</p> <p>S13</p> <p>1/4 —</p> <p>S24</p> <p>1998</p> </div> <p>from which</p> <p style="padding-left: 40px;">A copper coated steel rod, with unmarked cap, 1 1/2 ins. diam., bears S. 85°13'40" E., 504.2 lks. dist., 6 1/2 ins. below surface of White Fir Court, paved surface, in survey monument casing, 8 ins. diam., as recorded in Washoe County, Subdivision Tract Map No. 2991B.</p> <p style="padding-left: 40px;">An aluminum disk, 1 1/2 ins. diam., set flush in concrete, mkd. PLS 5666, bears S. 48°12'06" E., 387.4 lks. dist., as recorded in Washoe County, Subdivision Tract Map No. 2991B, located at S. edge of wood post fence cor., metal fence 4 1/2 ft. tall, bears S. 74° E. and N. 19° W., and wood fence, 5 1/2 ft. tall bears N. 48° E.</p> <p>Cor. is located in open pasture on gradual ENE slope.</p> <p>53.998 The W 1/16 sec. cor. of secs. 13 and 24, determined Alan Means, Nevada Registered Land Surveyor No. 3573, in 1979, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 3 ins. above ground, with melted plastic cap, with illegible marks. This monument matches other monuments set by Mr. Means in sec. 24, in 1979, as recorded in Washoe County, Land Map No. 43B, and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
---------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

137

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	<div data-bbox="839 260 1001 338"> <p>S13 W 1/16 — S24</p> </div> <div data-bbox="946 365 1009 390"> <p>1998</p> </div> <div data-bbox="450 417 1488 472"> <p>Deposit the iron rod, 18 ins. long, inside the stainless steel post.</p> </div> <div data-bbox="450 499 1093 525"> <p>Cor. is located on open grassy NW slope.</p> </div> <hr data-bbox="702 546 1235 550"/> <div data-bbox="450 581 1141 606"> <p>S. 89°23'20" W., beginning new measurement.</p> </div> <div data-bbox="294 634 1044 659"> <p>19.992 The cor. of secs. 13, 14, 23, and 24.</p> </div> <hr data-bbox="450 682 1483 686"/> <div data-bbox="450 718 1044 743"> <p>N. 0°57'50" E., bet. secs. 13 and 14.</p> </div> <div data-bbox="294 770 1488 1035"> <p>39.798 The 1/4 sec. cor. of secs. 13 and 14, perpetuated by Alan Means, Nevada Registered Land Surveyor No. 3573, in 1979, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 5 ins. above ground, with metal tag attached mkd. RLS 3573, with an igneous stone alongside, 15 x 14 x 9 ins., no marks visible. The iron rod is a remonumentation of a found rock mound as recorded in Washoe County, Land Map No. 43B. A well weathered wood post, 4 ins. square, 5 ft. long laying down slope, no marks visible. This is accepted as a careful and faithful perpetuation of the position of the original corner.</p> </div> <div data-bbox="450 1062 756 1087"> <p>At the corner point</p> </div> <div data-bbox="450 1115 1488 1194"> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> </div> <div data-bbox="893 1222 1040 1299"> <p>T19N R18E 1/4 S14 S13</p> </div> <div data-bbox="933 1327 997 1352"> <p>1998</p> </div> <div data-bbox="450 1379 611 1404"> <p>from which</p> </div> <div data-bbox="525 1432 1417 1512"> <p>An embedded granite boulder, 10 1/2 x 6 1/2 x 4 ft. high, bears N. 73°36' E., 190.0 lks. dist., mkd. BXO on W. face, 3 ft. above ground.</p> </div> <div data-bbox="525 1539 1417 1619"> <p>An embedded granite boulder, 7 x 5 x 2 1/2 ft. high, bears S. 66°31' W., 136.4 lks. dist., mkd. BXO on E. face, 2 ft. above ground.</p> </div> <div data-bbox="450 1646 1488 1701"> <p>Deposit iron rod, 15 1/2 ins. long, inside the stainless steel post.</p> </div> <div data-bbox="450 1728 1412 1753"> <p>Cor. is located on open rocky steep N. slope with low brush.</p> </div> <hr data-bbox="702 1774 1235 1778"/>
--------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	N. 1°08'20" E., beginning new measurement.								
39.572	<p>The cor. of secs. 11, 12, 13, and 14, perpetuated by Alan Means, Nevada Registered Land Surveyor No. 3573, in 1975, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 2 ins. above ground, with metal tag attached mkd. RLS 3573, as recorded in Washoe County, Record of Survey Map No. 1104. This is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr> <td>T19N</td><td>R18E</td></tr> <tr> <td>S11</td><td>S12</td></tr> <tr> <td colspan="2"><hr/></td></tr> <tr> <td>S14</td><td>S13</td></tr> </table> <p>1997</p> </div> <p>from which</p> <p>An embedded granite boulder, 15 x 13 x 10 ft. high, bears N. 5°40' E., 59.5 lks. dist., mkd. BXO on SE face, 5 ft. above ground.</p> <p>An embedded granite boulder, 8 x 5 1/2 x 5 ft. high, bears S. 40°00' E., 1.4 lks. dist., mkd. BXO on W. face, 4 ft. above ground.</p> <p>An embedded granite boulder, 6 1/2 x 4 1/2 x 3 1/2 ft. high, bears S. 85°30' W., 13.4 lks. dist., mkd. BXO on top.</p> <p>An embedded granite boulder, 16 x 13 x 10 ft. high, bears N. 45°40' W., 46.9 lks. dist., mkd. BXO on S. face, 5 1/2 ft. above ground.</p> <p>Deposit iron rod, 17 ins. long, inside the stainless steel post.</p> <p>Cor. is located on SW slope, 1 1/2 ft. W. of base boulder, among many large granite boulders and brush.</p> <p>From this corner, National Geodetic Survey control (formerly U.S.C. & G.S. triangulation) station "DARK", monumented with a standard brass tablet, 3 1/2 ins. diam. cemented in drill hole, in an igneous rock formation, bears N. 23°51'10" E., 39.754 chs. dist.</p> <hr/> <p>From the cor. of secs. 23, 24, 25, and 26.</p> <p>S. 86°58'40" W., bet. secs. 23 and 26.</p>	T19N	R18E	S11	S12	<hr/>		S14	S13
T19N	R18E								
S11	S12								
<hr/>									
S14	S13								
39.342	<p>The 1/4 sec. cor. of secs. 23 and 26, monumented with an igneous stone, 19 x 13 x 8 ins. (Record, 17 x 12 x 9 ins.), mkd. 1/4 on a face, lying in an embedded mound of stone, 3 ft. diam., 12 ins. high.</p>								

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

<p>CHAINS</p>	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T19N R18E</p> <p>S23</p> <p>1/4 ———</p> <p>S26</p> <p>1998</p> </div> <p>from which</p> <p>An embedded igneous boulder, 4 x 3 x 4 ft. high, bears N. 38°00' E., 85.0 lks. dist., mkd. BXO on top of SW sloping face.</p> <p>A Jeffrey pine, 18 ins. diam., bears S. 64 1/2° W., 87 lks. dist., mkd. 1/4 S26 BT.</p> <p>Deposit stone in mound alongside the stainless steel post.</p> <p>Cor. is located on open rocky E. slope.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 88°55'00" W., beginning new measurement.</p> <p>39.297 The cor. of secs. 22, 23, 26, and 27, perpetuated by Alan Means, Nevada Registered Land Surveyor No. 3573, in 1979, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 4 ins. above ground, with melted plastic cap, marks obliterated, with stone, 14 x 10 x 8 ins. (Record, 24 x 10 x 10 ins.) mkd. with 2 notches on S. and E. edges, and in a mound of stone, 2 1/2 ft. diam., 6 ins. high, as recorded in Washoe County, Land Map No. 43A. This is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T19N R18E</p> <table border="1" style="margin: auto;"> <tr> <td>S22</td><td>S23</td></tr> <tr> <td>S27</td><td>S26</td></tr> </table> <p>1997</p> </div> <p>Deposit iron rod, 16 ins. long, inside the stainless steel post.</p> <p>Deposit the mkd. stone on the W. side of the stainless steel post.</p> <p>Cor. is located on gradual NW slope, 80 lks. W. of jeep trail, 10 ft. wide, bears S. 12° W. and N. 12° E.</p>	S22	S23	S27	S26
S22	S23				
S27	S26				

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	<p>From this corner, a mound of stone, 3 1/2 ft. diam., 6 ins. high, bears N. 16°27' E., 296.1 lks. dist., and is of unknown origin, and not utilized in the course of this resurvey.</p>
39.961	<p>N. 0°17'40" E., bet. secs. 22 and 23.</p> <p>The 1/4 sec. cor. of secs. 22 and 23, monumented with an igneous stone, 18 x 7 x 7 ins. (Record, 18 x 6 x 6 ins.), mkd. 1/4 on W. face, set in an embedded mound of stone, 3 ft. x 3 1/2 ft. x 6 ins. high.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T19N R18E 1/4 S22 S23 1997</p> </div> <p>No accessories available.</p> <p>Deposit the stone in the mound of stone, alongside the stainless steel post.</p> <p>Cor. is located 1.30 chs. N. of crest on top of open mesa gradually sloping to the N.</p>
20.019	<p>N. 1°19'10" E., beginning new measurement.</p> <p>Point for the N 1/16 sec. cor. of secs. 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>N 1/16 S22 S23 1998</p> </div> <p>from which</p> <p>An embedded igneous boulder, 5 1/2 x 3 x 2 ft. high, bears N. 67°30' E., 48.2 lks. dist., mkd. BXO on top at NW end.</p> <p>An embedded igneous boulder, 3 x 3 x 2 ft. high, bears N. 72°20' W., 63.7 lks. dist., mkd. BXO on NNW face, 1 1/2 ft. above ground.</p> <p>Cor. is located on steep rocky open N. slope, 1 ft. S. of fence line, 4-strand, metal and wood posts, mostly down, bears E. and W. Fence cor. bears S. 89°35' E., 143.3 lks. dist., fence line bears W. and N. 38° E.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	<p>From this corner, an iron rod, 5/8 in. diam., firmly set, projecting 2 ins. above ground, with melted plastic cap, marks obliterated, matching monuments set by Alan Means, Nevada Registered Land Surveyor No. 3573, bears N. 82°49'30" E., 17.9 lks. dist., recorded in Washoe County, Land Map No. 43A, and which did not recover and use evidence of the original survey and thus is not utilized in this resurvey. Mr. Means was contacted in Reno concerning this and other unrecorded monuments in sections 22, 23, and 24, but he did not offer any information or records for his work. This point becomes Angle Point No. 12, of the metes-and-bounds survey in sec. 23, hereinafter described.</p>
40.038	<p>The cor. of secs. 14, 15, 22, and 23, determined by person(s) unknown, monumented with an iron shaft, 3 x 2 ins., firmly set, 10 ins. below surface, no marks visible, accepted by local land surveyors, as recorded in Washoe County, Land Map No. 43A, and Parcel Map No. 612 and is accepted as the best available evidence of the position of the original corner. Along the SE side of the shaft is an iron pipe, 1 in. diam., firmly set, 2 ins. below surface, no marks visible. Along the NNW side of the shaft is an iron rod, 5/8 in. diam., firmly set, 1 in. below surface, with plastic cap mkd. RLS 1643, established by Richard W. Arden, Nevada Professional Land Surveyor No. 1643.</p> <p>from the iron shaft,</p> <p>An iron rod, 5/8 in. diam., firmly set, projecting 4 ins. above ground, bears S. 55°10' E., 1.5 lks. dist., at the N. side of fence post cor., 10 ins. diam., fences bear S. and E., wood posts, 5-strand wire. Origin of monument unknown.</p> <p>An iron shaft, 4 ins. diam., firmly set, concrete filled, nail in center, 2 ins. below surface, bears N. 3°49' W., 175.4 lks. dist., at S. edge of gravel road, 10 ft. wide, bears E. and W. This monument was set as part of a Sierra Pacific Power Co. survey, on file with the Washoe Map Office, on Land Identification Map No. 147-11-069.</p> <p>An iron rod, 5/8 in. diam., firmly set, 4 ins. below surface, with plastic cap mkd. RLS 1643, bears N. 0°02' W., 118.5 lks. dist. Monument set by Richard W. Arden, as part of the Belli Ranch Estates Subdivision, recorded in Washoe County, Subdivision Tract Map No. 2097.</p> <p>Not remonumented.</p>
19.395	<p>From the cor. of secs. 13, 14, 23, and 24.</p> <p>S. 88°40'50" W., bet. secs. 14 and 23.</p> <p>Point for the E 1/16 sec. cor. of secs. 14 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	<div data-bbox="839 262 1011 394" style="text-align: right;"> S14 E 1/16 — S23 1998 </div> <p>from which</p> <p>An embedded igneous boulder, 2 1/2 x 2 1/2 x 3/4 ft. high, bears S. 87°30' E., 106.3 lks. dist., mkd. BXO on top.</p> <p>An unrecorded scattered mound of stone, 5 ft. diam., 6 ins. high, bears S. 58°25' E., 93.9 lks. dist, with well weathered wood post alongside, 3 x 4 ins., 5 ft. long, no marks visible.</p> <p>An embedded igneous boulder, 2 1/2 x 2 x 1 ft. high, bears S. 5°40' E., 57.8 lks. dist., mkd. BXO on NE face, 3/4 ft. above ground.</p> <p>Cor. is located on rocky open NE slope of mesa.</p> <p>38.790 The 1/4 sec. cor. of secs. 14 and 23, perpetuated by Alan Means, Nevada Registered Land Surveyor No. 3573, in 1979, monumented with an iron rod, 5/8 in. diam., loosely set, projecting 7 ins. above ground, with metal tag attached, mkd. RLS 3573, alongside of which is an igneous stone, 21 x 12 x 9 ins. (Record, 24 x 12 x 10 ins.), mkd. 1/4 on a face, and a decayed wood post, 4 ins. square, 5 ft. long, loosely set, no marks visible, in an embedded mound of stone, 3 ft. diam., 2 ft. high, as recorded in Washoe County, Land Map No. 43A.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div data-bbox="880 1297 1049 1455" style="text-align: right;"> T19N R18E S14 1/4 — S23 1998 </div> <p>from which</p> <p>An embedded igneous boulder, 4 1/2 x 3 x 1 ft. high, bears N. 66°10' E., 114.3 lks. dist., mkd. BXO on top.</p> <p>An embedded igneous boulder, 5 x 3 x 1 1/2 ft. high, bears S. 16°00' E., 37.1 lks. dist., mkd. BXO on NW face, 1 ft. above ground.</p> <p>Deposit iron rod, 14 ins. long, inside stainless steel post.</p> <p>Deposit mkd. stone along the N. side of the stainless steel post.</p> <p>Cor. is located on open N. slope.</p>
--------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

143

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	<p>From this corner, National Geodetic Survey control (formerly U.S.C. & G.S. triangulation) station "RANCH HILL", monumented with a standard brass tablet, 3 1/2 ins. diam. cemented in drill hole, in an igneous rock formation, bears S. 18°41'50" E., 27.249 chs. dist.</p> <hr/> <p>S. 89°55'30" W., beginning new measurement.</p>
16.531	Angle Point No. 1, of the metes-and-bounds survey in sec. 23, hereinafter described.
19.900	<p>The W 1/16 sec. cor. of secs. 14 and 23, determined by Peter G. Guisti, Nevada Registered Professional Engineer No. 335, in 1947, monumented with an iron bar, 1/2 in. sq., firmly set, 2 ins. below surface, as recorded in Washoe County Record of Survey Map No. 53. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>from which</p> <p style="padding-left: 40px;">An iron rod, 5/8 in. diam., firmly set 1 in. below surface, with plastic cap mkd. OSGOOD 3917, bears N. 17° E., 0.6 lks. dist., set as part of the metes-and-bounds survey in sec. 14, as recorded in Washoe County, Record of Survey Map No. 2497.</p> <p>Iron bar not remonumented.</p> <p>Cor. is located in level pasture, wet during most of the year, 17 lks. E. of barbed wire fence, bears N. and S.</p> <hr/> <p>S. 89°57'20" W., beginning new measurement.</p>
14.468	A parcel corner, established by Richard W. Arden, Registered Civil Engineer No. 13156, an iron rod, 5/8 in. diam., firmly set, 2 ins. below surface, with plastic cap mkd. LS 1643 ARDEN, as recorded in Washoe County, Record of Survey Map No. 1359.
14.713	A parcel corner, established by Don M. McHarg, Nevada Professional Land Surveyor No. 4787, an iron rod, 5/8 in. diam., flush with surface, with plastic cap mkd. SUMMIT ENG PLS 4787, as recorded in Washoe County, Record of Survey Map No. 2420.
14.717	A monument established by Richard W. Arden, Registered Civil Engineer No. 13156, an iron rod, 5/8 in. diam., firmly set, flush with surface, with plastic cap mkd. RLS 1643, set by Richard W. Arden, no record recovered.
19.892	The cor. of secs. 14, 15, 22, and 23.
	<hr/> <p>N. 0°08'10" W., bet. secs. 14 and 15.</p>
39.985	The 1/4 sec. cor. of secs. 14 and 15, determined by Alan Means, Nevada Registered Land Surveyor No. 3573, in 1978, monumented with an iron rod, 5/8 in. diam., firmly set, 3 ins. below surface, with aluminum cap mkd. 1/4 COR. 15 14 RLS 3573, a perpetuation of a 'found bolt in mound of rock' as recorded in Washoe County, Parcel Map No. 612. This is accepted as the best available evidence of the position of the original corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	<p>Not remonumented.</p> <p>From this corner, National Geodetic Survey control (formerly U.S.C. & G.S. triangulation) station "TRASH", monumented with a standard brass tablet, 3 1/2 ins. diam. cemented in drill hole, in an igneous rock formation, bears S. 78°48'20" W., 23.612 chs. dist.</p> <hr/> <p>N. 0°06'30" W., beginning new measurement.</p>						
40.105	<p>The cor. of secs. 10, 11, 14, and 15, reestablished by John R. Brooke, Nevada Registered Land Surveyor No. 1554, in 1989, monumented with an iron rod, 5/8 in. diam., firmly set, flush with surface of ground, with plastic cap mkd. BROOKE PLS 1554, as recorded in Washoe County, Parcel Map No. 2426, and Land Map No. 136 and was set at the former location of a monument set by Alan Means, Nevada Registered Land Surveyor No. 3573, recovered by Paul D. Higginbotham, Nevada Registered Land Surveyor No. 6200, in 1990, as recorded in Washoe County Record of Survey Map No. 2232. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p> <table border="1" data-bbox="888 1060 1037 1171"> <tr> <td>T19N</td><td>R18E</td></tr> <tr> <td>S10</td><td>S11</td></tr> <tr> <td>S15</td><td>S14</td></tr> </table> <p>1997</p> <p>Deposit iron rod, 18 ins. long, inside the stainless steel post.</p> <p>Cor. is located on SE slope, 2 lks. W. of wire fence, bears N. and S. Fence cor. bears S. 6 1/4° E., 21 lks. dist.; wire fences bear N. and W.</p> <p>From this corner, a control point, established by Alan Means, Nevada Registered Land Surveyor No. 3573, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 1 1/2 ins. above ground, bears N. 43°40' W., 1.217 chs. dist., with metal tag mkd. RLS 3573, metal fence post alongside. This monument is erroneously depicted as the cor. of secs. 10, 11, 14, and 15, as recorded in Washoe County, Record of Survey Map No. 1061, and is not utilized in this resurvey.</p> <hr/> <p>From the cor. of secs. 11, 12, 13, and 14.</p> <p>S. 89°51'20" W., bet. secs. 11 and 14.</p>	T19N	R18E	S10	S11	S15	S14
T19N	R18E						
S10	S11						
S15	S14						
40.092	<p>Point for the 1/4 sec. cor. of secs. 11 and 14, at proportionate dist., falls in housing subdivision; there is no remaining evidence of the original cor., or local survey monumentation.</p> <p>Not monumented.</p>						

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	
80.184	The cor. of secs. 10, 11, 14, and 15.
	<p>N. 2°52'00" W., bet. secs. 10 and 11.</p> <p>The S 1/16 sec. cor. of secs. 10 and 11, determined by Robert L. Fisher, Nevada Registered Land Surveyor No. 3922, monumented with an iron rod, 5/8 in. diam., firmly set, flush with ground, with plastic cap mkd. PLS 3922, falls at the position previously used and accepted by local surveys as recorded in Washoe County, Parcel Map No. 2426 and Record of Survey Map No. 2946. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S10 S11</p> <p style="text-align: center;">1998</p> <p>Deposit iron rod, 19 ins. long, inside the stainless steel post.</p> <p>Cor. is located on SSW slope, N. 40° W., 1.5 lks. from wood post cor. of fences. Metal post, 5 wire fences bear S. and E.</p>
20.881	<p>N. 2°54'40" W., beginning new measurement.</p> <p>The 1/4 sec. cor. of secs. 10 and 11, reestablished by John R. Brooke, Nevada Registered Land Surveyor No. 1554, in 1991, monumented with an iron rod, 5/8 in. diam., firmly set, flush with ground, with plastic cap mkd. PLS 1554, as recorded in Washoe County, Land Map No. 136 and Record of Survey Map No. 2946. Mr. Brooke reestablished an unrecorded determination by Alan Means, Nevada Registered Land Surveyor No. 3573, recovered and accepted by other Land Surveyors as recorded in Washoe County, Record of Survey Map Nos. 1061, 1341, and 2232. This is accepted as a careful and faithful reestablishment of the position of the original corner.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument bears S. 60°04' E., 108.2 lks. dist., mkd. RM 1/4 S11 71.4 FT TO COR 1998, and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument bears S. 37°20' W., 100.1 lks. dist., mkd. RM 1/4 S10 66.0 FT TO COR 1998 and an arrow pointing to the cor.</p> <p>Cor. is located on open steep S. slope, 4 lks. from E. edge of jeep trail, 22 lks. wide, bears N. and S, and 60 lks. S. of crest of hill.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	<p>Not remonumented.</p> <hr/> <p>From the cor. of secs. 22, 23, 26, and 27.</p> <p>N. 89°39'30" W., bet. secs. 22 and 27.</p> <p>41.499 The 1/4 sec. cor. of secs. 22 and 27, perpetuated by Alan Means, Nevada Registered Land Surveyor No. 3573, in 1979, monumented with an iron rod, 1/2 in. diam., loosely set, projecting 12 ins. above ground, with plastic cap mkd. MEANS RLS 3573, alongside of which is an igneous stone, 19 x 10 x 5 ins. (Record, 16 x 10 x 7 ins.), mkd. 1/4 on a face, and in a mound of stone, 4 ft. diam., 9 ins. high. A rock mound was recovered for this cor. by Mr. Means, as recorded in Washoe County, Land Map No. 43A. A second iron rod, 1/2 in. diam., firmly set, projecting 5 ins. above ground, with plastic cap mkd. MEANS RLS 3573, bears N. 67°50' W., 22.2 lks. dist., no information available.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T19N R18E</p> <p>S22</p> <p>1/4 —</p> <p>S27</p> <p>1998</p> </div> <p>No available accessories.</p> <p>Deposit iron rod, 18 ins. long, inside stainless steel post.</p> <p>Deposit mkd. stone along the N. side of the stainless steel post.</p> <p>Cor. is located on open rocky NNE slope.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 21 and 22, perpetuated by Alan Means, Nevada Registered Land Surveyor No. 3573, in 1979, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 6 ins. above ground, with plastic cap mkd. RLS 3573, alongside of which is an igneous stone, 20 x 18 x 8 ins. (Record, 24 x 16 x 12 ins.), mkd. 1/4 on a face, and in a mound of stone, 3 1/2 ft. diam., 9 ins. high. A rock mound was recovered for this cor. by Mr. Means, as recorded in Washoe County, Land Map No. 43A.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p>
--------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	
	<p>T19N R18E 1/4 S21 S22 1998</p>
	<p>from which</p> <p>An embedded igneous boulder, 4 x 4 x 2 ft. high, bears N. 60°30' E., 90.4 lks. dist., mkd. BXO on NW face, 1 ft. above ground.</p> <p>An embedded igneous boulder, 2 1/2 x 2 1/2 x 1 1/2 ft. high, bears S. 73°30' W., 119.1 lks. dist., mkd. BXO on E. face, 1/2 ft. above ground.</p> <p>Deposit iron rod, 19 ins. long, inside stainless steel post.</p> <p>Deposit mkd. stone along the N. side of the stainless steel post.</p> <p>Cor. is located on open gradual NW slope.</p> <p>From this corner, a mound of stone, 5 x 3 ft., with burned lath remains in center, bears N. 7°00' W., 188.5 lks., dist.</p> <p>N. 0°32'30" E., bet. secs. 21 and 22.</p>
35.205	The point for Angle Point No. 10, of the metes-and-bounds survey in sec. 22, hereinafter described.
35.414	The point for Angle Point No. 1, of the metes-and-bounds survey in sec. 21, hereinafter described.
35.546	An iron rod, 5/8 in. diam., buried 2 ins. below surface of access road along Steamboat Ditch, with unreadable damaged plastic cap. This monument occupies the position of a cor. of lots 33 and 34, Block A, as shown on Subdivision Tract Map No. 2097B, as recorded in Washoe County, Nevada
39.870	<p>The cor. of secs. 15, 16, 21, and 22, determined by person(s) unknown, monumented with an iron pipe, 2 1/2 ins. diam., firmly set, projecting 1 in. above ground, 1/2 lk. W. of chain link fence, 6 ft. high, bears N. and S. and in a wire fence, bears E. and W., and locally accepted as recorded in Washoe County, Land Map Nos. 43 and 43A. This is accepted as the best available evidence of the position of the original corner.</p> <p>Not remonumented.</p> <p>Cor. is located on level ground at E. side of pasture.</p> <hr/> <p>From the cor. of secs. 14, 15, 22, and 23.</p> <p>N. 89°51'50" W., bet. secs. 15 and 22.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	
40.628	<p>The 1/4 sec. cor. of secs. 15 and 22, determined by person(s) unknown, monumented with an iron rod, 1 in. diam., firmly set, 4 ins. below ground surface, and locally accepted as recorded in Washoe County, Land Map No. 43A, Parcel Map Nos. 612 and 707, and Subdivision Tract Map No. 2097B. This is accepted as the best available evidence of the position of the corner.</p> <p>Not remonumented.</p> <p>Cor. is located in rocky pasture, N. 50° E., 10.5 lks., from cor. of low animal shed, 16 x 13 ft., long side, bears S. 30° W.</p> <p>From this corner, National Geodetic Survey control (formerly U.S.C. & G.S. triangulation) station "TRASH", hereinbefore described, bears N. 26°11'40" E., 39.344 chs. dist.</p> <hr/> <p>N. 89°50'10" W., beginning new measurement.</p>
20.293	<p>Point for the W 1/16 sec. cor. of secs. 15 and 22, falls on developed private lot.</p> <p>Not monumented.</p> <p>From this point, an iron rod, 5/8 in. diam., firmly set, bears S. 70°20' E., 2.136 chs. dist., as depicted on the map for Belli Ranch Estates, recorded in Washoe County, Subdivision Tract Map No. 2097B, with a copper coated steel cap, 1 1/2 ins. diam., mkd. RLS 1647, 7 ins. below surface, in survey monument well, 7 ins. diam., in center of Leventina Canyon Road, paved surface, 42 ft. wide, bears N. 25° E. and S. 10° W. into curve.</p>
40.586	<p>The cor. of secs. 15, 16, 21, and 22.</p> <hr/> <p>From the cor. of secs. 10, 11, 14, and 15.</p> <p>N. 89°57'20" W., bet. secs. 10 and 15.</p>
13.526	<p>At a point 0.3 lks. S. of an iron rod, 5/8 in. diam., firmly set, projecting 2 ins. above ground, with plastic cap, 1 1/4 ins. diam., mkd. PLS 3922, and set by Robert L. Fisher, Nevada Professional Land Surveyor No. 3922, for housing subdivisions to the south.</p>
20.024	<p>The E 1/16 sec. cor. of secs. 10 and 15, determined by Alan Means, Nevada Registered Land Surveyor No. 3573, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 1 in. above ground, with metal tag attached, mkd. RLS 3573, as recorded in Washoe County, Record of Survey Map No. 2946, and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	<div data-bbox="818 260 985 390" data-label="Text"> <p>S10 E 1/16 — S15 1998</p> </div> <div data-bbox="435 420 594 445" data-label="Text"> <p>from which</p> </div> <div data-bbox="509 474 1399 554" data-label="Text"> <p>A fence cor. bears S. 2°40' E., 22.5 lks. dist., fences bear E. and S., metal posts, pig wire bottom, 3 strands barbed wire on top.</p> </div> <div data-bbox="509 579 1399 684" data-label="Text"> <p>An iron rod, 5/8 in. diam., firmly set, projecting 3 ins. above ground, bears S. 29°00' W., 25.2 lks. dist., with plastic cap, 1 1/4 ins. diam., mkd. SUMMIT ENGINEERING CONTROL POINT.</p> </div> <div data-bbox="431 711 1443 739" data-label="Text"> <p>Deposit the iron rod, 18 in. long, inside stainless steel post.</p> </div> <div data-bbox="428 764 1138 791" data-label="Text"> <p>Cor. is located on a moderate open SE slope.</p> </div> <hr data-bbox="683 814 1214 821"/> <div data-bbox="428 848 1122 875" data-label="Text"> <p>N. 89°58'50" W., beginning new measurement.</p> </div> <div data-bbox="274 900 371 926" data-label="Text"> <p>20.021</p> </div> <div data-bbox="428 900 1468 1140" data-label="Text"> <p>The 1/4 sec. cor. of secs. 10 and 15, an unrecorded perpetuation by Alan Means, Nevada Registered Land Surveyor No. 3573 and California Registered Civil Engineer No. 23112, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 2 ins. above ground, with metal tag attached mkd. CE 23112, alongside of which is an igneous stone, 15 x 10 x 7 ins. (Record, 16 x 10 x 10 ins.) mkd. 1/4 on a face, and in a mound of stone, 3 ft. diam., 9 ins. high, accepted by local Land Surveyors, as recorded in Washoe County, Record of Survey Map No. 2946.</p> </div> <div data-bbox="425 1165 737 1190" data-label="Text"> <p>At the corner point</p> </div> <div data-bbox="425 1215 1468 1297" data-label="Text"> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> </div> <div data-bbox="857 1325 1029 1482" data-label="Text"> <p>T19N R18E S10 1/4 — S15 1998</p> </div> <div data-bbox="425 1509 594 1535" data-label="Text"> <p>from which</p> </div> <div data-bbox="501 1562 1370 1642" data-label="Text"> <p>An iron well casing, 6 1/2 ins. diam., firmly set, projecting 8 ins. above ground, bears S. 84°30' E., 397.4 lks. dist., no marks.</p> </div> <div data-bbox="501 1669 1373 1749" data-label="Text"> <p>An embedded igneous boulder, 2 x 1 1/2 x 3/4 ft. high, bears S. 79°40' E., 35.1 lks. dist., mkd. BXO on W. face.</p> </div> <div data-bbox="501 1776 1373 1856" data-label="Text"> <p>An embedded igneous boulder, 2 1/2 x 2 x 1 ft. high, bears S. 38°10' W., 60.8 lks. dist., mkd. BXO on NE face.</p> </div>
--------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	<p>Deposit iron rod, 18 ins. long, inside stainless steel post.</p> <p>Deposit mkd. stone along the N. side of the stainless steel post.</p> <p>Cor. is located on gradual open NNW slope, 85 lks. N. of jeep trail, 8 ft. wide, bears S. 75° E. and N. 80° W. in curve.</p> <hr/> <p>From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 2°02'50" E., bet. secs. 32 and 33.</p> <p>19.737 Point for the S 1/16 sec. cor. of secs. 32 and 33.</p> <p>Not monumented.</p> <p>39.474 Point for the 1/4 sec. cor. of secs. 32 and 33, at proportionate dist., there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T19N R18E 1/4 S32 S33 1998</p> <p>from which</p> <p style="padding-left: 40px;">A meta-volcanic boulder, 4 x 3 x 2 1/2 ft. high, bears S. 84°20' E., 55.7 lks. dist., mkd. BXO on top.</p> <p style="padding-left: 40px;">A meta-volcanic boulder, 7 x 5 x 5 ft. high, bears S. 16°40' E., 43.6 lks. dist., mkd. BXO on top. Rock is lower portion of outcrop along spur, sloping to NW.</p> <p>Cor. is located on brushy N. slope with few young fir.</p> <p>59.211 Point for the N 1/16 sec. cor. of secs. 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S32 S33 1998</p> <p>from which</p> <p style="padding-left: 40px;">An igneous boulder, 6 x 4 x 4 ft. high, bears S. 85°40' E., 26.8 lks. dist., mkd. BXO on WNW face, 3 3/4 ft. above ground.</p>
--------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	<p>An igneous boulder, 5 1/2 x 2 1/2 x 1 1/2 ft. high, bears S. 70°00' W., 11.1 lks. dist., mkd. BXO on top.</p>						
	<p>Cor. is located on open rocky NE slope, 38 lks. N. of fence remains, fallen posts, 3-wire, bears N. 50° W. and S. 50° E.</p>						
78.948	<p>The cor. of secs. 28, 29, 32, and 33, monumented with a mound of stone, 3 ft. diam., 1 ft. high, with stone, fallen out of mound, 18 x 11 x 6 ins. (Record, 18 x 12 x 8 ins.), mkd. with 5 notches on an edge and 4 notches on an adjacent edge. Also remains of decayed wood stake in center of mound, no marks visible, from which the remains of the original bearing tree</p>						
	<p>A burned base of pine, 3 ft. diam., bears S. 61° E., 81 lks. dist., no marks. A Fiberboard Paper Products Corporation corner record, found in the files of the U.S. Forest Service notes 30 to 40 ins. double pine windfall, with hack marks.</p>						
	<p>At the corner point</p>						
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>						
	<table border="1"> <tr> <td>T19N</td><td>R18E</td></tr> <tr> <td>S29</td><td>S28</td></tr> <tr> <td>S32</td><td>S33</td></tr> </table>	T19N	R18E	S29	S28	S32	S33
T19N	R18E						
S29	S28						
S32	S33						
	<p>1998</p>						
	<p>from which new accessories</p>						
	<p>An igneous boulder, 3 x 2 x 3 ft. high, bears N. 42°40' E., 69.0 lks. dist., mkd. BXO on SW face, 2 ft. above ground.</p>						
	<p>A mountain mahogany, triple trunk, bears S. 27° E., 70 lks. dist., mkd. X BT on east fork, 6 ins. diam.</p>						
	<p>An igneous boulder, 7 x 7 x 5 ft. high, bears S. 80°40' W., 45.5 lks. dist., mkd. BXO on NE face, 4 ft. above ground.</p>						
	<p>Deposit the mkd. stone on the west side of the stainless steel post.</p>						
	<p>Cor. is located on open rocky SSW slope.</p>						
	<p>N. 0°20'00" E., bet. secs. 28 and 29.</p>						
20.566	<p>Point for the S 1/16 sec. cor. of secs. 28 and 29.</p>						
	<p>Not monumented.</p>						
41.132	<p>The 1/4 sec. cor. of secs. 28 and 29, monumented with a scattered mound of stone, 3 1/2 ft. diam., 1 ft. high, from which the remains of the original bearing tree</p>						

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

<p>CHAINS</p>	<p>A stump hole, 2 ft. diam., with pine snag remains alongside, bears S. 6° E., 145 lks. dist., no marks. A Fiberboard Paper Products Corporation corner record found in the files of the U.S. Forest Service notes "orig. 36 in. pine windfall, scribing visible 1/4 SXX."</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T19N R18E 1/4 S29 S28</p> <p style="text-align: center;">1998</p> <p>from which new accessories</p> <p>A volcanic boulder, 3 x 2 x 1 1/2 ft. high, bears S. 76°20' E., 48.1 lks. dist., mkd. BXO on W. end, 1 ft. above ground.</p> <p>A volcanic boulder, 3 1/2 x 3 x 2 1/2 ft. high, bears N. 22°30' W., 45.6 lks. dist., mkd. BXO on SE face, 2 ft. above ground.</p> <p>Cor. is located on very rocky W. slope.</p> <hr/> <p>N. 1°19'40" E., beginning new measurement.</p> <p>19.740 Point for the N 1/16 sec. cor. of secs. 29 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S29 S28</p> <p style="text-align: center;">1998</p> <p>from which</p> <p>An embedded igneous boulder, 4 x 3 x 3 ft. high, bears N. 28°30' E., 93.9 lks. dist., mkd. BXO on SW face, 1/2 ft. above ground.</p> <p>An embedded igneous boulder, 4 1/2 x 3 1/2 x 2 ft. high, bears S. 75°40' W., 81.0 lks. dist., mkd. BXO on E. face, 1/2 ft. above ground.</p> <p>Cor. is located on N. slope.</p>
---------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	
39.480	<p>The cor. of secs. 20, 21, 28, and 29, monumented with an iron post, 2 1/2 ins. diam., firmly set, with stone, 30 x 14 x 12 ins. (Record, 30 x 16 x 16 ins.), mkd. with 2 notches on S. edge and 4 notches on E. edge set on W. side of post and in a mound of stone, 3 ft. base, with brass cap mkd. as described in the field notes of the 1966 remonumentation.</p> <p>Cor. is located on rocky NNW slope, 2 lks. N. of barbed wire fence, metal posts, bears E. and W.</p> <p>From this corner, National Geodetic Survey control (formerly U.S.C. & G.S. triangulation) station "BENDER", monumented with a standard brass tablet, 3 1/2 ins. diam. cemented in drill hole, in an igneous rock formation, bears S. 67°56'50" E., 43.665 chs. dist.</p>
40.046	<p>N. 2°32'50" W., bet. secs. 20 and 21.</p> <p>Point for the 1/4 sec. cor. of secs. 20 and 21, at proportionate dist., there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T19N R18E 1/4 S20 S21 1998</p> </div> <p>Cor. is located in open burn area on gradual NW slope.</p>
80.092	<p>The cor. of secs. 16, 17, 20, and 21, monumented with a stone, 22 x 10 x 5 ins. (Record, 30 x 10 x 8 ins.), firmly set, projecting 10 ins. above ground, mkd. with 3 notches on S. edge and 4 notches on E. edge and in a scattered mound of stone, 4 ft. diam., 1 ft. high.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T19N R18E S17 S16 S20 S21 1998</p> </div> <p>Deposit the mkd. stone, alongside the stainless steel post.</p> <p>Cor. is located on gradual SE slope, 2 ft. E. of fence cor. with 4 wire fences and metal posts, bear W. and N.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	<p>From this corner, National Geodetic Survey control (formerly U.S.C. & G.S. triangulation) station "KNOLL", monumented with a standard brass tablet, 3 1/2 ins. diam. cemented in drill hole, in an igneous rock formation, bears N. 37°15'10" W., 13.287 chs. dist.</p> <hr/> <p>From the cor. of secs. 15, 16, 21, and 22.</p> <p>N. 87°56'50" W., bet. secs. 16 and 21.</p>
9.197	The point for Angle Point No. 9, of the metes-and-bounds survey in sec. 21, hereinafter described.
39.699	<p>The 1/4 sec. cor. of secs. 16 and 21, an unrecorded determination by Eugene B. Longfield, Nevada Professional Land Surveyor No. 886, monumented with an iron pipe, 1 in. diam., firmly set, projecting 6 ins. above ground, with metal tag mkd. LS RE 886, and in a mound of stone, 2 1/2 ft. diam., 3 ins. high, and locally accepted as recorded in Washoe County, Land Map No. 43, and Record of Survey Map No. 1267, and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T19N R18E</p> <p>S16</p> <p>1/4 ———</p> <p>S21</p> <p>1999</p> </div> <p>Deposit iron pipe, 27 ins. long, inside stainless steel post.</p> <p>Cor. is located 3 lks. S. of barbed wire fence, bears E. and W.</p> <hr/> <p>N. 87°30'30" W., beginning new measurement.</p>
2.266	At a point 0.6 lks. N. of a lot corner, an unrecorded establishment by Eugene B. Longfield, Nevada Professional Land Surveyor No. 886, an iron pipe, 7/8 ins. diam., firmly set, projecting 8 ins. above ground, with metal tag mkd. LS RE 886, in a mound of stone, 3 ft. diam., recovered by local Land Surveyors as recorded in Washoe County, Land Map No. 43, and Record of Survey Map No. 1267.
19.84	At a point 1.5 lks. N. of a wood post fence cor., metal post, 4-wire fences bears E. and N. No evidence recovered for the 3/4 in. iron rod at record distance of 19.870 chs., recovered by local Land Surveyors as recorded in Washoe County, Land Map No. 43, and Record of Survey Map No. 1267.
39.754	The cor. of secs. 16, 17, 20, and 21.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	<p>From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp., hereinbefore described.</p>
	<p>N. 0°01'30" E., bet. secs. 31 and 32.</p>
39.952	<p>The 1/4 sec. cor. of secs. 31 and 32, monumented with an iron post, 1 in. diam., firmly set, and in a mound of stone, 2 1/2 ft. base, 1 ft. high, with brass cap mkd. as described in the field notes of the 1918 resurvey, from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A pine snag stump remains, 30 ins. diam., bears N. 48 1/2° E., 72 lks. dist., with fallen remains alongside, with chopped open blaze, no marks visible. (1865 Record, N. 48 1/2° W.; 1918 Record N. 49° E.)</p> <p style="padding-left: 40px;">A pine stump with burned-out remains, 30 ins. diam., bears S. 71 1/2° W., 56 lks. dist., with fallen remains alongside, no marks visible. (1865 Record, 52 lks.)</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 18 ins. diam., bears S. 6 1/2° W., 30 lks. dist., with location tag.</p> <p style="padding-left: 40px;">An incense cedar, 17 ins. diam., bears N. 21 1/2° W., 45 lks. dist. with location tag.</p> <p>Cor. is located on NE slope with pine timber and mountain mahogany.</p>
	<p>N. 3°23'30" E., beginning new measurement.</p>
19.993	<p>Point for the N 1/16 sec. cor. of secs. 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> <p>N 1/16</p> <p>S31 S32</p> <p>1998</p> </div> <p>from which</p> <p style="padding-left: 40px;">A volcanic boulder, 2 x 2 1/2 x 3 ft. high, bears N. 50°20' E., 9.4 lks. dist., mkd. BXO on S. face, 2 ft. above ground. Boulder is welded into volcanic mud flow.</p> <p style="padding-left: 40px;">A ponderosa pine, 30 ins., diam., bears S. 28° W., 311 lks. dist., mkd. N1/16 S31 BT.</p> <p>Cor. is located on steep open SW slope. Volcanic mud flow terrain.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	
39.986	<p>The cor. of secs. 29, 30, 31, and 32, monumented with an iron post, 2 ins. diam., loosely set, and in a mound of stone, 2 ft. base, 1 ft. high, with brass cap mkd. as described in the field notes of the 1918 resurvey,</p> <p>from which</p> <p style="padding-left: 40px;">A volcanic mud flow, 15 x 15 x 5 ft. high, bears S. 83°00' E., 5.5 lks. dist., mkd. BXO on SW face, 5 ft. above ledge.</p> <p>Rehabilitate monument.</p> <p>Cor. is located on a narrow ledge, 2 1/2 ft. wide, of very steep W. facing spur.</p> <hr/> <p>From the cor. of secs. 28, 29, 32, and 33.</p> <p>N. 89°24'00" W., bet. secs. 29 and 32.</p>
19.886	<p>Point for the E 1/16 sec. cor. of secs. 29 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> $\begin{array}{r} \text{S29} \\ \text{E 1/16} \text{ --- } \\ \text{S32} \\ 1998 \end{array}$ </div> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 37 ins. diam., bears N. 45 1/2° E., 109 lks. dist., mkd. E1/16 S29 BT.</p> <p style="padding-left: 40px;">An incense cedar, 21 ins. diam., bears S. 88 1/2° W., 83 1/2 lks. dist., mkd. E1/16 S32 BT.</p> <p style="padding-left: 40px;">An igneous boulder, 3 x 2 x 2 1/2 ft. high, bears N. 20°40' W., 8.8 lks. dist., mkd. BXO on SE face, 2 ft. above ground.</p> <p>Cor. is located 48 lks. S. of jeep trail, 12 ft. wide, bears S. 42° E. and N. 34° W. in curve. Falls in low drainage.</p>
39.772	<p>The 1/4 sec. cor. of secs. 29 and 32, an unrecorded perpetuation monumented with an iron rod, 5/8 in. diam., firmly set, projecting 12 ins. above ground, and alongside of which is an igneous stone, 15 x 10 x 12 ins. (Record, 14 x 10 x 10 ins.), mkd. 1/4 on a face, and in a mound of stone, 3 1/2 ft. diam., 1 ft. high, from which the remains of the original bearing tree</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

<p>CHAINS</p>	<p>A pine stump remains, 24 ins. diam., bears S. $7\frac{1}{2}^{\circ}$ E., 129 lks. dist., with remains of chopped open blaze, no marks visible.</p> <p>and an unrecorded tree</p> <p>A Jeffrey pine, 29 ins. diam., bears N. $76\frac{1}{2}^{\circ}$ W., 92 lks. dist., with healed blazes. Sawed open upper blaze to reveal scribe marks 29. Ring count dates blaze with scribe marks back to the 1918 GLO era resurveys in this area.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 25 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T19N R18E</p> <p>S29</p> <p>1/4 —</p> <p>S32</p> <p>1998</p> </div> <p>from which new accessories</p> <p>The NW cor. of concrete block building, 24 x 16 ft., bears S. $48^{\circ}20'$ E., 196.0 lks. dist., long side bears N. $43\frac{1}{2}^{\circ}$ W.</p> <p>An igneous boulder, 4 x 3 x 3 ft. high, bears S. $34^{\circ}30'$ E., 50.8 lks. dist., mkd. BXO on W. face, 2 ft. above ground.</p> <p>Deposit iron rod, 31 ins. long, inside stainless steel post.</p> <p>Deposit mkd. stone along the SE side of the stainless steel post.</p> <p>Cor. is located on gradual WNW slope with pine and mountain mahogany.</p> <hr style="width: 30%; margin-left: auto; margin-right: auto;"/> <p>N. $89^{\circ}03'00''$ W., beginning new measurement.</p> <p>20.628 Point for the W 1/16 sec. cor. of secs. 29 and 32.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground to rock, over a plastic-encased magnet, and in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>S29</p> <p>W 1/16 —</p> <p>S32</p> <p>1998</p> </div>
---------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	<p>from which</p> <p>An igneous boulder, 5 x 2 1/2 x 3 ft. high, bears N. 26°10' E., 84.9 lks. dist., mkd. BXO on S. face, 2 ft. above ground.</p> <p>A Jeffrey pine, 17 ins. diam., bears S. 67 1/4° E., 200 lks. dist., with location tag.</p> <p>Cor. is located in open on gentle S. slope and in the saddle of a spur, slopes NNW.</p> <p>41.256 The cor. of secs. 29, 30, 31, and 32.</p> <hr/> <p>N. 89°47'40" W., bet. secs. 30 and 31.</p> <p>20.825 Point for the E 1/16 sec. cor. of secs. 30 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>S30 E 1/16 — S31 1999</p> </div> <p>from which</p> <p>A Jeffrey pine, 19 ins. diam., bears S. 41° W., 14 1/2 lks. dist., mkd. E1/16 S31 BT.</p> <p>Cor. is located on gradual NE slope in burn area with scattered pine.</p> <p>41.650 The 1/4 sec. cor. of secs. 30 and 31, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, along side of which is an igneous stone, 22 x 20 x 6 ins. (1865 Record, 18 x 6 x 8 ins.; 1918 Record, 18 x 10 x 8 ins.), mkd. 1/4 on a face, in a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd. as described in the field notes of the 1918 resurvey, from which the 1918 accessory</p> <p>A Jeffrey pine, 22 ins. diam., bears N. 70°35' E., 173 lks. dist., with healed blaze. (Record, 171 lks.)</p> <p>and a new accessory</p> <p>An igneous boulder, 7 1/2 x 4 x 4 ft. high, bears S. 20°00' E., 229.7 lks. dist., mkd. BXO on NW face, 2 ft. above ground near northern end.</p> <p>Cor. is located on steep S. slope.</p> <hr/> <p>N. 89°33'50" W., beginning new measurement.</p>
--------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	
4.213	<p>Intersect the California-Nevada State Line.</p> <p>Point for the closing cor. of secs. 30 and 31.</p> <p>Not Monumented.</p> <p>Cor. is located on open steep rocky S. slope.</p> <p>From this corner, Mile Post 174, on the California-Nevada State Line, bears S. $0^{\circ}47'10''$ W., 6.921 chs. dist., hereinbefore described.</p>
4.248	<p>The 1918 closing cor. of secs. 30, 30, 31, and 31, monumented with an iron post, 2 ins. diam., firmly set, projecting 18 ins. above ground, and in a mound of stone, 2 1/2 ft. diam., to top, with brass cap mkd. as described in the field notes of the 1918 resurvey.</p> <p>from which</p> <p style="padding-left: 40px;">An igneous boulder, 4 x 2 x 2 ft. high, bears N. $48^{\circ}16'$ E., 82.0 lks. dist., mkd. BXO on WSW face, 1 ft. above ground.</p> <p style="padding-left: 40px;">A Jeffrey pine, 28 ins. diam., bears N. $2\frac{1}{2}^{\circ}$ W., 112 lks. dist., mkd. T19NR18E S30 BT.</p> <hr style="width: 20%; margin-left: 40px;"/> <p>N. $89^{\circ}22'10''$ W., beginning new measurement.</p>
13.640	<p>Point selected for the witness cor. to the W 1/16 sec. cor. of secs. 30 and 31.</p> <p>Set a brass tablet, 3 1/2 ins. diam., 3 ins. stem., in an iron pipe, 1 in. diam., 14 ins. long in drill hole top of small rock outcrop, and cemented into place, with brass cap mkd.</p> <div style="text-align: center; margin-top: 20px;"> <p>WC</p> <p>S30</p> <p>W 1/16 <—</p> <p>S31</p> <p>1999</p> </div> <p>from which</p> <p style="padding-left: 40px;">A Jeffrey pine, 14 ins., diam., bears S. $79\frac{3}{4}^{\circ}$ E., 45 lks. dist., mkd. XBT.</p> <p style="padding-left: 40px;">A Jeffrey pine, 18 ins., diam., bears S. $36\frac{1}{2}^{\circ}$ W., 157 lks. dist., mkd. XBT.</p> <p>Rock outcrop is located on SW slope.</p>
16.500	<p>True point for the W 1/16 sec. cor. of secs. 30 and 31, falls on unstable right bank of a creek, 5 lks. wide, drains ESE, where it is impractical to establish a permanent monument.</p>

160

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	
37.244	<p>Point for the 80 1/16 sec. cor. of secs. 30 and 31.</p> <p>Not monumented.</p>
56.96	<p>Center of graded dirt road, 15 lks. wide, bears N. 30° W. and S. 27° E.</p>
58.009	<p>The cor. of secs. 30, 30, 31, and 31, on the old California-Nevada State Line, hereinbefore described.</p> <hr/>
	<p>From the cor. of secs. 29, 30, 31, and 32.</p> <p>N. 3°19'40" W., bet. secs. 29 and 30.</p>
20.097	<p>Point for the S 1/16 sec. cor. of secs. 29 and 30.</p> <p>Not monumented.</p>
40.194	<p>The 1/4 sec. cor. of secs. 29 and 30, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above the ground, and in a mound of stone, 4 ft. diam., 1 ft. high, with brass cap mkd. as described in the field notes of the 1918 resurvey. The brass cap is also erroneously mkd. WC below the record marks. Remove the marks WC from the brass cap.</p> <p>from which new accessories</p> <p>A Jeffrey pine, 24 ins. diam., bears S. 15 1/2° E., 98 lks. dist., mkd. 1/4 S29 BT.</p> <p>A vertical rock cliff, bears S. 42°20' W., 57.9 lks. dist., mkd. BXO on ENE face, 5 ft. above ground. Face of cliff bears N. and S.</p> <p>A Jeffrey pine, 25 ins. diam., bears N. 73 1/4° W., 55 lks. dist., mkd. XBT. Tree is at base of cliff.</p> <p>Cor. is located on level rocky ground.</p> <hr/> <p>N. 3°03'50" W., beginning new measurement.</p>
39.679	<p>The cor. of secs. 19, 20, 29, and 30, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, and in a collar of stone, 1 1/2 ft. diam., with brass cap mkd. as described in the field notes of the 1918 resurvey. The marked stone recovered in 1913, was not recovered by this resurvey.</p> <p>Cor. is located under a wood rail fence, bears E. and W., also 2.2 ft. S. of a 4 wire barbed wire fence, bears E. and W., 63 1/2 lks. E. of fence cor., with fences, bearing E. and N. A chain link dog enclosure parallels the S. side of the rail fence.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	
	<p>From this corner, a concrete cylinder, 4 ins. diam., firmly set, 5 ins. below surface, bears N. 89°18' E., 2.625 chs. dist., with iron cap, 4 1/2 ins. diam., with Stone and Webster cap markings, described by Thomas J. Welsh, RPE & LS No. 47, on unrecorded Record of Survey for a portion of sec. 19, on file in the County Engineers/Surveyor Office in Reno, Nevada, file No. 19181912. Mr. Welsh reports that the monument was established in 1910 for the cor. of secs. 19, 20, 29, and 30. Copies of field notebook, County File No. 19181122 Field Book No. 628 dated 11-17-11 show that the monument was established as a Deed corner and not as a perpetuation of the original 1865 Record monument. The position monumented by the GLO has been recognized since 1913 by local Land Surveyors, including Mr. Welsh. Other Stone & Webster monuments were recovered by Mr. Welsh and rejected to subdivide sec. 19.</p> <p>The Stone and Webster monument is not utilized due to its method of establishment and is disputed by the 1865 record evidence recovered by the 1913 and 1918 resurveys.</p> <hr/> <p>From the cor. of secs. 20, 21, 28, and 29.</p> <p>S. 89°53'50" W., bet. secs. 20 and 29.</p>
22.181	<p>Point for the E 1/16 sec. cor. of secs. 20 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground to rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>S20 E 1/16 — S29 1998</p> </div> <p>from which</p> <p>An igneous boulder, 7 x 7 x 2 1/2 ft. high, bears N. 61°30' E., 225.9 lks. dist., mkd. BXO on WSW face, 2 1/2 ft. above ground.</p> <p>An igneous boulder, 6 x 4 1/2 x 1 ft. high, bears S. 84°10' E., 264.1 lks. dist., mkd. BXO on WNW face, 1 ft. above ground.</p> <p>Cor. is located on open gentle NW slope.</p>
44.362	<p>The 1/4 sec. cor. of secs. 20 and 29, monumented with an upright stone, 21 x 9 x 8 ins. (Record, 16 x 10 x 10 ins.), no marks visible, set in the center of an embedded mound of stone, 4 ft. diam.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

162

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	
	<p>T19N R18E S20 1/4 <u> </u> S29 1998</p>
	<p>from which</p> <p>An igneous boulder, 5 x 4 x 4 ft. high, bears N. 45°10' E., 399.7 lks. dist., mkd. BXO on W. face, 3 ft. above ground.</p> <p>An igneous rock face, 7 x 5 ft. high, bears N. 75°00' E., 422.4 lks. dist., mkd. BXO on top.</p> <p>Deposit stone along the N. side of the stainless steel post.</p> <p>Cor. is located on gradual NE slope.</p> <hr/> <p>N. 89°33'30" W., beginning new measurement.</p>
42.253	<p>The cor. of secs. 19, 20, 29, and 30.</p> <hr/> <p>N. 89°07'20" W., bet. secs. 19 and 30.</p>
2.10	<p>Truckee River, 1.5 chs. wide, drains N. 10° W. (1865 Record, 4.37 chs., 1913 Record, 6.83 chs.)</p>
37.192	<p>The 1/4 sec. cor. of secs. 19 and 30, an unrecorded perpetuation by William W. Grimm, Nevada Registered Land Surveyor No. 737, monumented with a copper coated steel rod, 7/8 in. diam., firmly set, projecting 10 ins. above ground, with copper cap, 1 1/2 ins. diam., mkd. 1981 1/4 S19 S30 LS737 and in a mound of stone, 4 ft. diam., with stone, 18 x 11 x 9 ins. (1913 Record, 20 x 12 x 10 ins.), mkd. 1/4 on a face.</p> <p>Not remonumented.</p> <p>Cor. is located on NNE slope with pine and mountain mahogany.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 7 and 18, perpetuated by Theodore A. Fox, Nevada Registered Land Surveyor No. 2456, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. USFS T19N R18E 1/4 S7 S18 RLS 2456, alongside of which is a stone 16 x 11 x 10 ins., mkd. 1/4 on a face and in a mound of stone, 2 1/2 ft. base, 1 ft. high.</p> <p>from which new accessories</p> <p>A copper coated steel rod, with cap, 2 ins. diam., mkd. RLS 2170, firmly set, bears N. 3°38' E., 144.4 lks. dist., 8 ins. below surface of Sylvan Circle, paved surface, in survey monument casing, 8 ins. diam., as recorded in Washoe County, Sunrise Creek Subdivision Tract Map No. 2128A.</p>

163

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	
	<p>An iron pipe, 3 ins. diam., firmly set, bears N. 88°00' E., 41.4 lks. dist., concrete filled, projecting 5 ins. above ground, with iron rod in center, 1 in. diam., no marks or other information recovered. Similar to monuments set by Thomas J. Welsh, RPE & LS No. 47, as shown on unrecorded maps supplied by Sierra Pacific Power Company.</p> <p>A copper coated steel rod, with cap, 2 ins. diam., mkd. RLS 2170, firmly set, bears N. 55°58' W., 119.7 lks. dist., 8 ins. below surface of Sylvan Circle, paved surface, in survey monument casing, 8 ins. diam., as recorded in Washoe County, Sunrise Creek Subdivision Tract Map No. 2128A.</p>
	<p>Cor. is located on level ground, 3 lks. S. of barbed wire fence, wood posts, bears E. and W.</p> <p>S. 89°26'00" W., bet. secs. 7 and 18.</p>
0.988	<p>Point for the 1913 closing cor. of secs. 7 and 18, at proportionate dist.; there is no remaining evidence of the 1913 closing cor., or local perpetuations by private surveyors. Falls in intersection of two paved streets.</p> <p>Not monumented.</p>
0.997	<p>Intersect the California-Nevada State Line.</p> <p>Point for the closing cor. of secs. 7 and 18.</p> <p>Not monumented.</p> <p>From this point, Mile Post 171, bears S. 0°38'40" W., 7.593 chs. dist., hereinbefore described.</p>
43.208	<p>Point for the 80 1/16 sec. cor. of secs. 7 and 18.</p> <p>Not monumented.</p>
61.896	<p>The cor. of secs. 7, 7, 18, and 18, on the old California-Nevada State Line, hereinbefore described.</p>
	<hr/> <p>From the 1/4 sec. cor. of secs. 6 and 7, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above ground, in a mound of stone, 4 ft. diam., 1 ft. high, with brass cap mkd. as described in the field notes of the 1918 resurvey, alongside of which is an igneous rock, 18 x 12 x 6 ins. (1865 Record, 14 x 10 x 18 ins.; 1913 and 1918 Records, 10 x 8 x 4 ins. above ground), mkd. 1/4 on a face.</p> <p>from which</p> <p>A ponderosa pine, 22 ins. diam., bears N. 3 1/4° E., 56 lks. dist., mkd. T19N R18E S6 BT.</p> <p>An igneous boulder, 3 1/2 x 2 1/2 x 1 ft. high, bears N. 54°20' E., 109.6 lks. dist., mkd. BXO on top.</p>

164

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	<p>Cor. is located on gradual W. slope with scattered pine and sage.</p> <p>S. 89°33'00" W., bet. secs. 6 and 7.</p>
0.506	<p>Intersect the California-Nevada State Line.</p> <p>Point for the closing cor. of secs. 6 and 7.</p> <p>Not monumented.</p> <p>From this point, Mile Post 170, bears S. 0°40'50" W., 7.774 chs. dist., hereinbefore described.</p>
0.588	<p>The 1918 closing cor. of secs. 6, 6, 7, and 7, monumented with an iron post, 2 ins. diam., firmly set, projecting 17 ins. above ground, in a mound of stone, 3 ft. diam., 1 ft. high, with brass cap mkd. as described in the field notes of the 1918 resurvey, alongside of which is an igneous rock, 12 x 12 x 10 ins. (1913 Record, 16 x 12 x 10 ins.), mkd. with 5 grooves, 1 groove, and CC on adjacent faces.</p> <hr/> <p>S. 88°54'20" W., beginning new measurement.</p>
21.497	<p>The W 1/16 sec. cor. of secs. 6 and 7, determined by Thomas J. Welsh, Nevada Registered Civil Engineer and Land Surveyor No. 47, recovered by Peter D. Rabbon, California Registered Civil Engineer No. 29617, in 1985, monumented with an iron rod, 3/4 in. diam., firmly set, projecting 13 ins. above ground, with tag mkd. LS 47, alongside of which is another iron rod, 3/4 in. diam., firmly set, projecting 17 ins. above ground, no marks, as recorded in Sierra County, Book 7, of Maps and Surveys, Page 75. This position is accepted as a careful and faithful determination of the position of the corner.</p> <p>Not remonumented.</p> <hr/> <p>S. 88°58'00" W., beginning new measurement.</p>
22.034	<p>The 80 1/16 sec. cor. of secs. 6 and 7, determined by Dale D. Kulm, California Registered Civil Engineer No. 16895, in 1979, monumented with an iron rod, 1/2 in. diam., firmly set, projecting 6 ins. above ground, with tag mkd. RCE 16895, and in a mound of stone, 2 ft. diam., as recorded in Sierra County, Book 6, of Maps and Surveys, Page 49. Note: The local survey record indicates that this monument was intended to be set 10 ft. west of the 80 1/16 sec. cor. of secs 6 and 7 and at a distance of 1184.01 ft. from the cor. of secs. 6, 6, 7, and 7, but was recovered 1193.82 ft. or about 10 ft. too far east of where intended and is now located at the proper location for the 80 1/16 sec. cor. This position is accepted as the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p>

165

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	<p style="text-align: center;">S 6 1/16 — 80 S 7</p> <p style="text-align: center;">1999</p> <p>from which</p> <p>An igneous boulder, 11 1/2 x 6 1/4 x 3 1/2 ft. high, bears N. 81°00' E., 43.4 lks. dist., mkd. BXO on W. end, 1 1/2 ft. above ground.</p> <p>An igneous boulder, 20 x 15 x 7 ft. high, bears S. 2°00' W., 51.2 lks. dist., mkd. BXO on NNW face, 3 ft. above ground.</p> <p>Cor. is located on gradual E. slope in rocky burn area.</p> <p>From this corner, an iron rod, 5/8 in. diam., firmly set, projecting 4 ins. above ground, set by Peter D. Rabbon, California Registered Civil Engineer No. 29617, in 1985, bears S. 86°10' E., 15.3 lks. dist., with aluminum cap, 1 1/2 ins. diam., mkd. RCE 29617, and in a mound of stone, 2 1/2 ft. diam., as recorded in Sierra County, Book 7, of Maps and Surveys, Page 75. Based on this plat, the monument set by Mr. Rabbon was intended to be set at 1194.01 ft. from the cor. of secs. 6, 6, 7, and 7, or 10 ft. easterly of Mr. Kulm's monument. Mr. Rabbon's monument was recovered 10.1 ft. easterly of Mr. Kulm's, but since Mr. Kulm's location is 10 ft. easterly of where shown on his plat, Mr. Rabbon's monument is also 10 ft. too far E. and thus is not utilized in the course of this resurvey.</p>
18.087	<p>S. 88°52'50" W., beginning new measurement.</p> <p>The cor. of secs. 6, 6, 7, and 7, on the old California-Nevada State Line, hereinbefore described.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 5 and 6, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above ground, and in a scattered collar of stone, 2 ft. base, 1/2 ft. high, with brass cap mkd. as described in the field notes of the 1918 resurvey. Alongside of which is a granite stone, 12 x 11 x 8 ins. (1865 Record, 18 x 8 x 8 ins.; 1918 Record, 6 x 8 x 8 ins.), no marks visible.</p> <p>from which</p> <p>A granite boulder, 4 x 3 1/2 x 3 ft. high, bears N. 55°40' E., 125.1 lks. dist., mkd. BXO on top.</p> <p>A Jeffrey pine, 9 ins. diam., bears N. 21° W., 35 1/2 lks. dist., mkd. X BT.</p> <p>Cor. is located on open SE slope with sage and bitterbrush.</p> <p>N. 3°29'00" E., bet. secs. 5 and 6.</p>
19.883	<p>Point for the N 1/16 sec. cor. of secs. 5 and 6.</p>

166

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S6 S5 1999</p> <p>from which</p> <p style="padding-left: 40px;">A granite boulder, 3 x 5 x 2 ft. high, bears S. 70°20' E., 35.1 lks. dist., mkd. BXO on W. face, 1 ft. above ground.</p> <p style="padding-left: 40px;">A granite boulder, 4 1/2 x 2 x 2 1/2 ft. high, bears S. 1°00' W., 6.6 lks. dist., mkd. BXO on N. face, 1 1/2 ft. above ground.</p> <p>Cor. is located on steep N. slope with granite boulders, pine, mountain mahogany, bitterbrush, and sage.</p>
39.926	<p>The cor. of secs. 5, 6, 31, and 32, on the N. bdy. of the Tp., hereinbefore described.</p> <hr/> <p style="text-align: center;">SUBDIVISION OF ELONGATED SECTION 6, T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 6 and 7.</p> <p>N. 1°14'30" W., on the N. and S. center line of sec. 6.</p>
15.091	<p>Intersect the California-Nevada State Line.</p> <p>Not monumented.</p> <p>From this point an Angle Point on the California-Nevada State Line bears N. 0°40'50" E., 23.078 chs. dist., hereinbefore described.</p>
19.550	<p>Point for the center south 1/16 sec. cor. of sec. 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">C S 1/16 S6 C 1999</p> <p>from which</p> <p style="padding-left: 40px;">An igneous boulder, 3 1/2 x 3 1/2 x 2 ft. high, bears N. 42°40' E., 116 lks. dist., mkd. BXO on the top.</p> <p style="padding-left: 40px;">A Jeffrey pine, 33 ins. diam., bears N. 89 3/4° E., 199 lks. dist., mkd. CS 1/16 S6 BT.</p>

SUBDIVISION OF ELONGATED SECTION 6,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

<p>CHAINS</p>	<p>From this corner, an iron rod, 3/4 in. diam., firmly set, projecting 9 ins. above ground, established by Peter D. Rabbon, California Registered Civil Engineer No. 29617, in 1985, with aluminum cap, 1 1/2 ins. diam., mkd. RCE 29617, bears N. 9°10' E., 44.0 lks. dist., as recorded in Sierra County, Book 7, of Maps and Surveys, Page 75, and is not utilized in the course of this resurvey due to the use of improper control for the subdivision of the section.</p> <p>Cor. is located on a steep S. slope with sage, bitterbrush, and scattered pine in rocky and sandy soil, 6 lks. W. of a barbed wire fence, bears N. and S. Also 45 lks. S. of a barbed wire fence which bears W. and intersects N. and S. fence.</p> <p>39.100 Point for the center 1/4 sec. cor. of sec. 6, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T19N R18E C 1/4 S6 1999</p> <p>from which</p> <p style="padding-left: 40px;">A granite boulder, 3 x 2 1/2 x 1 ft. high, bears S. 12°10' W., 33.3 lks., dist., mkd. BXO on the top.</p> <p style="padding-left: 40px;">A granite boulder, 3 x 2 x 1 ft. high, bears S. 66°20' W., 32.0 lks. dist., mkd. BXO on the top.</p> <p>Cor. is located on a moderate S. slope with pine, mountain mahogany, bitterbrush, and sage and 71 lks. W. of a barbed wire fence, bears N. and S.</p> <p>59.026 Point for the center north 1/16 sec. cor. of sec. 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">C N 1/16 S6 C</p> <p style="text-align: center;">1999</p> <p>from which</p> <p style="padding-left: 40px;">A Jeffrey pine, 9 ins. diam., bears S. 11 1/4° E., 109 1/2 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A Jeffrey pine, 19 ins. diam., bears S. 31° W., 54 lks. dist., mkd. CN 1/16 S6 BT.</p>
---------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

168

SUBDIVISION OF ELONGATED SECTION 6,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	Cor. is located on a moderate NW slope with pine, mountain mahogany, and sage, 134 lks. W. of a barbed wire fence bears N. and S.
79.042	The 1/4 sec. cor. of secs. 6 and 31, on the N. bdy. of the Tp.
	From the 1/4 sec. cor. of secs. 5 and 6.
	S. 89°30'00" W., on the E. and W. center line of sec. 6.
20.450	Point for the center east 1/16 sec. cor. of sec. 6.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	E 1/16 C ——— C S6 1999
	from which
	A granitic boulder, 5 x 3 x 4 ft. high, bears N. 42°20' E., 31.6 lks. dist., mkd. BXO on the SW face, 3 ft. above ground.
	A granitic boulder, 5 x 4 x 2 ft. high, bears N. 82°50' E., 38.8 lks. dist., mkd. BXO on top.
	Cor. is located on a moderate SW slope with scattered pine, mountain mahogany, and sage with large boulders.
40.092	Intersect the California-Nevada State Line.
	Not monumented.
	From this point, an Angle Point on the California-Nevada State Line bears S. 0°48'00" W., 0.934 chs. dist., hereinbefore described.
40.900	The center 1/4 sec. cor. of sec. 6.
62.996	Point for the center west 1/16 sec. cor. of sec. 6.
	Not monumented.
85.092	Point for the center 80 1/16 sec. cor. of sec. 6.
	Not monumented.
	Point is located on moderate SW slope with scattered pine, bitterbrush, and sage.
102.300	The 1/4 sec. cor. of secs. 6 and 6, on the old California-Nevada State Line.

169

SUBDIVISION OF ELONGATED SECTION 6,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	<p>From the center east 1/16 sec. cor. of sec. 6.</p>
	<p>N. 1°21'20" E., on the N. and S. center line of the NE1/4 of sec. 6.</p>
19.890	<p>Point for the NE 1/16 sec. cor. of sec. 6, at intersection with the E. and W. center line of the NE1/4.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">NE 1/16 S6</p>
	<p style="text-align: center;">1999</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A granitic boulder, 8 x 9 x 4 ft. high, bears N. 58°00' E., 59.4 lks. dist., mkd. BXO on the top.</p>
	<p style="padding-left: 40px;">A granitic boulder, 10 x 10 x 10 ft. high, bears N. 48°40' W., 31.4 lks. dist., mkd. BXO on the SE face, 4 ft. above ground.</p>
	<p>Cor. is located on moderate SW slope with scattered pine, bitterbrush, and sage.</p>
39.882	<p>The point for the E 1/16 sec. cor. of secs. 6 and 31, on the N. bdy. of the Tp.</p>
	<hr/>
	<p>From the N 1/16 sec. cor. of secs. 5 and 6.</p>
	<p>S. 89°37'20" W., on the E. and W. center line of the NE1/4 of sec. 6.</p>
21.186	<p>The NE 1/16 sec. cor. of sec. 6.</p>
41.053	<p>Intersect the California-Nevada State Line.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground over a plastic encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	<div style="text-align: center;"> <p>CAL NEV</p> <p>N ——— N</p> <p> </p> <p> S 6</p> </div>
	<p style="text-align: center;">1999</p>
	<p>Cor. is located 10.8 ft. E. of fence, 4-wire with metal posts on a gradual NW slope with Jeffrey pine timber.</p>
	<p>From this corner, an Angle Point on the California-Nevada State Line, bears S. 0°11'50" W., 3.043 chs. dist., hereinbefore described.</p>
42.538	<p>The center north 1/16 sec. cor. of sec. 6.</p> <hr/>

170

SUBDIVISION OF ELONGATED SECTION 6,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	<p>From the center south 1/16 sec. cor. of sec. 6.</p> <p>S. 89°12'40" W., on the E. and W. center line of SW1/4 of sec. 6.</p>
22.026	<p>At a point, 28.5 lks. S. of an iron rod, 3/4 in. diam., firmly set, projecting 6 ins. above ground, set by Peter D. Rabbon, California Registered Civil Engineer No. 29617, in 1985, as recorded in Sierra County, Book 7, of Maps and Surveys, Page 75, with aluminum cap, 1 1/2 ins. diam., mkd. RCE 29617. Due to the use of improper control for the subdivision of the section, this monument is not utilized in the course of this resurvey.</p>
44.155	<p>Point for the south 80 1/16 sec. cor. of sec. 6, at intersection with the N. and S. 80 line of the SW1/4 of sec. 6, falls on unstable talus slope.</p> <p>Not monumented.</p> <p>From this point, an iron rod, 3/4 in. diam., loosely set in rock talus, set by Peter D. Rabbon, California Registered Civil Engineer No. 29617, in 1985, as recorded in Sierra County, Book 7, of Maps and Surveys, Page 75, with aluminum cap, 1 1/2 ins. diam., mkd. RCE 29617. Due to the use of improper control for the subdivision of the section, this monument is not utilized in the course of this resurvey.</p>
61.802	<p>The S 1/16 sec. cor. of secs. 6 and 6, on the old California-Nevada State Line.</p> <hr/> <p>From the 80 1/16 sec. cor. of secs. 6 and 7.</p> <p>N. 1°21'00" W., on the N. and S. 80 line of the SW1/4 of sec. 6.</p>
19.756	<p>True point for the south 80 1/16 sec. cor. of sec. 6.</p>
20.374	<p>Point selected for the witness cor. to the south 80 1/16 sec. cor. of sec. 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC</p> <p>↓</p> <p>1/16</p> <p>S $\frac{1}{16}$ 80</p> <p>S 6</p> <p>1999</p> </div> <p>from which</p> <p>A Jeffrey pine, 8 ins. diam., bears N. 41° W., 54 1/2 lks. dist., mkd. X BT.</p> <p>A granite boulder, 6 x 3 1/2 x 3 ft. high, bears N. 10°40' W., 42.4 lks. dist., mkd. BXO on the top.</p>

171

SUBDIVISION OF ELONGATED SECTION 6,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	Cor. is located on steep rocky NE slope.
39.530	The point for the center 80 1/16 sec. cor. of sec. 6.
	<p>SUBDIVISION OF ELONGATED SECTION 7, T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA</p> <p>From the 1/4 sec. cor. of secs. 7 and 18.</p> <p>N. 0°21'10" E., on the N. and S. center line of sec. 7.</p>
19.780	Point for the center south 1/16 sec. cor. of sec. 7.
	Not monumented.
39.560	<p>The center 1/4 sec. cor. of sec. 7, determined by Richard W. Arden, California Registered Professional Engineer No. 13156, in 1968, monumented with a concrete cylinder, 6 ins. diam., loosely set, leaning to N., with brass disk in center, 2 ins. diam., mkd. RE 13156 SE COR LOT 13 EC 7, as recorded in Sierra County, Book 2, of Maps and Surveys, Page 91, (local record monument description is 1/2 in. pin). This is accepted as a careful and faithful determination of the position of the corner.</p> <p>Not remonumented.</p> <p>from which</p> <p>A monument of unknown usage, established by Richard W. Arden, California Registered Professional Engineer No. 13156, monumented with an iron rod, 1/2 in. diam., loosely set, projecting 3 ins. above ground, bears S. 0°21'10" W., 4.3 lks. dist., with metal tag mkd. RCE 13156.</p> <p>Cor. is located on N. slope under fence line, partially down, bears N. and S.</p>
	N. 0°21'10" E., beginning new measurement.
20.339	Point for the center north 1/16 sec. cor. of sec. 7.
	Not monumented.
40.678	The 1/4 sec. cor. of secs. 6 and 7.
	<p>From the 1/4 sec. cor. of secs. 7 and 8, determined from ties to local survey monuments, set by Dale E. Kulm, Nevada Professional Land Surveyor No. 2170, as recorded in Washoe County, Subdivision Tract Map No. 2500A. The monument was not recovered, it was reported by Mr. Kulm as having been destroyed by home construction.</p> <p>Not remonumented.</p>

SUBDIVISION OF ELONGATED SECTION 7,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	<p>from which</p> <p>A survey monument, established by Dale E. Kulm, Nevada Professional Land Surveyor No. 2170, an iron rod, 5/8 in. diam., firmly set, with an aluminum cap, 1 1/2 ins. diam., mkd. RLS 2170, bears N. 35°43'50" E., 727.9 lks. dist., 7 1/2 ins. below surface, in survey monument well, 8 ins. diam., in center of Riverdale Circle, paved surface, 26 ft. wide.</p> <p>A survey monument, established by Dale E. Kulm, Nevada Professional Land Surveyor No. 2170, an iron rod, 5/8 in. diam., firmly set, with an aluminum cap, 1 1/2 ins. diam., mkd. RLS 2170, bears N. 63°26'30" W., 329.7 lks. dist., 7 1/2 ins. below surface, in survey monument well, 8 ins. diam., in center of Riverdale Circle, paved surface, 26 ft. wide. Record bearing is rotated 9'30" clockwise and record distances multiplied by 0.9997 based on ties made in this resurvey.</p> <p>From this corner, National Geodetic Survey control (formerly U.S.C. & G.S. triangulation) station "VERDI BLUFF", monumented with a standard brass tablet, 3 1/2 ins. diam. cemented in drill hole, in an igneous rock formation, bears S. 40°27'50" E., 65.873 chs. dist.</p> <p>S. 89°28'40" W., on the E. and W. center line of sec. 7.</p> <p>39.856 The center 1/4 sec. cor. of sec. 7.</p> <hr/> <p>S. 89°28'40" W., beginning new measurement.</p> <p>0.771 Intersect the California-Nevada State Line.</p> <p>Not monumented.</p> <p>From this point, Mile Post 170+47, on the California-Nevada State Line, bears S. 0°44'10" W., 14.475 chs. dist., hereinbefore described.</p> <p>21.709 The center west 1/16 sec. cor. of sec. 7, determined by Richard W. Arden, California Registered Civil Engineer No. 13156, monumented with a concrete cylinder, 6 ins. diam., firmly set, with brass disk in center, 2 ins. diam., mkd. RE 13156 SE COR LOT 2 SEC 7, as recorded in Sierra County, Book 2, of Maps and Surveys, Page 91, and is accepted as an careful and faithful determination of the position of the corner.</p> <p>from which</p> <p>The SW corner lot 1, Verdi-Sierra Pines Subdivision, Unit No. 2, established by Dale E. Kulm, California Registered Civil Engineer No. 16895, an iron rod, 1/2 in. diam., firmly set, projecting 1 in. above ground, bears S. 88°50' E., 14.6 lks. dist., set in concrete, at corner of fences, bears N. and E., as recorded in Sierra County, Book 3, of Maps and Surveys, Pages 88-89.</p>
--------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

SUBDIVISION OF ELONGATED SECTION 7,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	<p>Not remonumented.</p> <hr/> <p>S. 89°27'20" W., beginning new measurement.</p>
0.757	A street right-of-way monument, Verdi-Sierra Pines Subdivision, Unit No. 2, established by Richard W. Arden, California Registered Civil Engineer No. 13156, an iron rod, 1/2 in. diam., firmly set, projecting 1 1/2 ins. above ground, as recorded in Sierra County, Book 3, of Maps and Surveys, Pages 22-23.
9.120	An iron rod, 5/8 in. diam., firmly set, projecting 3 1/2 ins. above ground, with tag mkd. RCE 16895, set by Dale D. Kulm, as recorded in Sierra County, Book 4, of Maps and Surveys, Page 13.
9.174	An iron rod, 1/2 in. diam., firmly set, projecting 4 1/2 ins. above ground, no tag. This monument matches the local record of Dale D. Kulm, as recorded in Sierra County, Book 4, of Maps and Surveys, Pages 13.
21.694	<p>The center 80 1/16 sec. cor. of sec. 7, determined by Richard W. Arden, California Registered Civil Engineer No. 13156, in 1968, monumented with a concrete cylinder, 6 ins. diam., firmly set, with brass disk in center, 2 ins. diam., mkd. RE 13156 SW COR TEMP, and in a scattered collar of stone, 1 1/2 ft. diam., as recorded in Sierra County, Book 2, of Maps and Surveys, Page 91, (local record monument description is 1/2 in. pin). This is accepted as a careful and faithful determination of the position of the corner.</p> <p>from which</p> <p style="padding-left: 40px;">A Jeffrey pine, 23 ins. diam., bears S. 3 1/2° W., 19 lks. dist., mkd. C-80 1/16 S7 BT.</p> <p style="padding-left: 40px;">A vertical pipe, 6.7 ins. diam., projecting 6 ft. above ground, bears S. 28 1/2° W., 55 1/2 lks. dist., no marks. Pipe is set for buried pipeline.</p> <p>Cor. is located on SE slope at edge of burn area.</p> <hr/> <p>S. 89°28'30" W., beginning new measurement.</p>
18.291	<p>The 1/4 sec. cor. of secs. 7 and 7, on the old California-Nevada State Line.</p> <hr/> <p>From the point for the center south 1/16 sec. cor. of sec. 7.</p> <p>S. 89°27'10" W., on the E. and W. center line of SW1/4 of sec. 7.</p>
0.896	<p>Intersect the California-Nevada State Line.</p> <p>Not monumented.</p> <p>From this point, Mile Post 170+47, on the California-Nevada State Line, bears N. 0°38'40" E., 5.307 chs. dist., hereinbefore described.</p>

174

SUBDIVISION OF ELONGATED SECTION 7,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

<p>CHAINS</p> <p>43.307</p>	<p>The south 80 1/16 sec. cor. of sec. 7, determined by Richard W. Arden, California Registered Civil Engineer No. 13156 and Nevada Professional Land Surveyor No. 1643, monumented with an iron rod, 1/2 in. diam., firmly set, projecting 2 ins. above ground, with tag mkd. LS 1643. Matches other monuments set by Arden as recorded in Sierra County, Book 2, of Maps and Surveys, Page 91. Alongside of which is an iron pipe, 1 in. diam., firmly set, projecting 3 1/2 ins. above ground, with brass cap, 2 ins. diam., mkd. RCE 16895, set by Dale D. Kulm, as recorded in Sierra County, Book 9, of Maps and Surveys, Page 53. This is accepted as a careful and faithful determination of the cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{r} 1/16 \\ S \frac{\quad}{\quad} 80 \\ S \quad 7 \\ 1999 \end{array}$ </div> <p>from which</p> <p style="padding-left: 40px;">A power pole, bears S. 72° W., 13 1/2 lks. dist., tagged 185456 and J69855.</p> <p style="padding-left: 40px;">A Jeffrey pine, 21 ins. diam., bears N. 52° W., 145 1/2 lks. dist., mkd. S-80 1/16 S7 BT.</p> <p>Deposit the iron rod, 18 ins. long, inside the stainless steel post.</p> <hr style="width: 30%; margin-left: 0;"/> <p>S. 89°27'10" W., beginning new measurement.</p>
<p>18.488</p>	<p>The S 1/16 sec. cor. of secs. 7 and 7, on the old California-Nevada State Line.</p> <hr/> <p>From the point for the 80 1/16 sec. cor. of secs. 7 and 18.</p> <p>N. 0°03'30" E., on the N. and S. 80 line of the SW1/4 of sec. 7.</p>
<p>19.791</p>	<p>The south 80 1/16 sec. cor. of sec. 7.</p> <hr/> <p>N. 0°04'10" E., beginning new measurement.</p>
<p>19.790</p>	<p>The center 80 1/16 sec. cor. of sec. 7.</p> <hr/> <p>From the point for the center north 1/16 sec. cor. of sec. 7.</p> <p>S. 89°12'00" W., on the E. and W. center line of NW1/4 of sec. 7.</p>

175

SUBDIVISION OF ELONGATED SECTION 7,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	
0.635	<p>Intersect the California-Nevada State Line.</p> <p>Not monumented.</p> <p>From this point, Mile Post 170, on the California-Nevada State Line, bears N. 0°44'10" E., 12.571 chs. dist., hereinbefore described.</p>
43.764	<p>The north 80 1/16 sec. cor. of sec. 7, determined by Richard W. Arden, California Registered Civil Engineer No. 13156, monumented with an iron rod, 1/2 in. diam., firmly set, projecting 1 in. above ground, no tag. This monument matches the local record of Richard W. Arden, California RCE 13156 as recorded in Sierra County, Book 2, of Maps and Surveys, Page 91. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} 1/16 \\ N \frac{\quad}{\quad} 80 \\ S \quad 7 \end{array}$ <p>1999</p> </div> <p>from which</p> <p style="padding-left: 40px;">An igneous boulder, 3 1/2 x 2 1/2 x 2 ft. high, bears N. 32°00' E., 48.9 lks. dist., mkd. BXO on top face.</p> <p style="padding-left: 40px;">An igneous boulder, 3 x 3 1/2 x 3 ft. high, bears N. 69°40' W., 89.0 lks. dist., mkd. BXO on S. face, 2 ft. above ground.</p> <p>Deposit the iron rod, 18 ins. long, inside the stainless steel post.</p> <p>Cor. is located on open burned over rocky S. slope.</p> <hr style="width: 30%; margin-left: 0;"/> <p>S. 89°12'00" W., beginning new measurement.</p>
18.168	<p>The N 1/16 sec. cor. of secs. 7 and 7, on the old California-Nevada State Line.</p> <hr style="width: 80%; margin-left: 0;"/> <p>From the center 80 1/16 sec. cor. of sec. 7.</p> <p>N. 0°40'20" W., on the N. and S. 80 line of the NW1/4 of sec. 7.</p>
20.132	<p>The north 80 1/16 sec. cor. of sec. 7.</p> <hr style="width: 30%; margin-left: 0;"/>

176

SUBDIVISION OF ELONGATED SECTION 7,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	N. 0°39'00" W., beginning new measurement.
20.140	The 80 1/16 sec. cor. of secs. 6 and 7.
	<p style="text-align: center;">SUBDIVISION OF SECTION 10, T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA</p>
	From the 1/4 sec. cor. of secs. 10 and 15.
	N. 1°43'50" W., on the N. and S. center line of sec. 10.
20.469	Point for the center south 1/16 sec. cor. of sec. 10.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.
	<p style="text-align: center;">C S 1/16 S10 C</p>
	1998
	Cor. is located on level ground.
40.938	The center 1/4 sec. cor. of sec. 10, determined by Don M. McHarg, Nevada Professional Land Surveyor No. 4787, in 1996, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 1 in. above ground, with plastic cap mkd. PLS 4787, as recorded in Washoe County, Record of Survey Map No. 3121. This is accepted as a careful and faithful determination of the position of the corner.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 2 ft. base, to top, with brass cap mkd.
	<p style="text-align: center;">T19N R18E C 1/4 S10</p>
	1998
	Deposit iron rod, 18 ins. long inside stainless steel post.
	Cor. is located on level ground with sage.
	N. 1°43'40" W., beginning new measurement.
38.886	The 1/4 sec. cor. of secs. 3 and 10, matching other unrecorded perpetuations by Alan Means, Nevada Professional Land Surveyor No. 3573, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 5 ins. above ground, no marks, with stone, 16 x 12 x 6 ins. alongside, with faint marks. This position has been accepted by local Land Surveyors as recorded in Washoe County, Record of Survey Map Nos. 1341, 2946, and 3121, and is accepted as the best available evidence of the position of the original corner.

SUBDIVISION OF SECTION 10,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T19N R18E</p> <p>S 3</p> <p>1/4 —</p> <p>S10</p> <p>1998</p> </div> <p>Deposit iron rod, 18 ins. long, inside the stainless steel post.</p> <p>Deposit the mkd. stone on the W. side of the stainless steel post.</p> <p>Cor. is located on open WSW slope 10 lks. N. of jeep trail, 9 ft. wide, bears N. 80° W. and S. 80° E.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 10 and 11.</p> <p>S. 88°53'40" W., on the E. and W. center line of sec. 10.</p> <p>19.590 The center east 1/16 sec. cor. of sec. 10, determined by Don M. McHarg, Nevada Professional Land Surveyor No. 4787, in 1996, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 1 in. above ground, with plastic cap mkd. PLS 4787, as recorded in Washoe County, Record of Survey Map No. 3121, and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>E 1/16</p> <p>C — C</p> <p>S10</p> <p>1998</p> </div> <p>from which</p> <div style="margin-left: 40px;"> <p>An iron rod, 3/4 in. diam., firmly set, projecting 1 in. above ground, bears N. 87° E., 8.2 lks. dist., mkd. HIGG-N-SONS PLS 6200, as recorded in Washoe County, Record of Survey Map No. 2232.</p> </div> <p>Deposit iron rod, 18 ins. long, inside the stainless steel post.</p> <p>Cor. is located on gradual SW slope, 25 lks. E. of bladed road, 14 ft. wide, bears N. 30° E. and S. 22° W. in curve.</p> <hr/>
--------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

SUBDIVISION OF SECTION 10,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	S. 88°53'40" W., beginning new measurement.
19.591	The center 1/4 sec. cor. of sec. 10. <hr/>
	S. 88°57'50" W., beginning new measurement.
18.444	<p>The center west 1/16 sec. cor. of sec. 10, determined by Don M. McHarg, Nevada Professional Land Surveyor No. 4787, in 1996, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 1 in. above ground, with plastic cap, mkd. SUMMIT ENG PLS 4787, as recorded in Washoe County, Record of Survey Map No. 3121, and is accepted as a careful and faithful determination of the position of the corner.</p> <p>Not remonumented.</p> <p>Cor. is located on gradual E. slope in sage.</p> <hr/>
	S. 88°48'50" W., beginning new measurement.
18.447	<p>The 1/4 sec. cor. of secs. 9 and 10, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 24 ins. above ground, with aluminum cap, 2 ins. diam., mkd. NEV TRANS DEPT 233058L. This position has been accepted by local surveyors, as recorded in Washoe County, Record of Survey Map Nos. 1341, 2946, and 3121, and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T19N R18E 1/4 S9 S10 1998</p> <p>Deposit iron rod, 18 ins. long, inside the stainless steel post.</p> <p>Cor. is located at W. edge of jeep trail, 8 ft. wide, bears N. and S.</p> <p>From this corner, National Geodetic Survey control (formerly U.S.C. & G.S. triangulation) station "STICKY", monumented with a standard brass tablet, 3 1/2 ins. diam., cemented in drill hole, in an igneous rock formation, bears N. 51°30'40" W., 9.529 chs. dist.</p> <hr/> <p>From the E 1/16 sec. cor. of secs. 10 and 15.</p> <p>N. 2°18'50" W., on the N. and S. center line of the SE1/4 of sec. 10.</p>
20.663	Point for the SE 1/16 sec. cor. of sec. 10, at intersection with the E. and W. center line of the SE1/4.

179

SUBDIVISION OF SECTION 10,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set an iron rod, 1/2 in. sq., 24 ins. long, 6 ins. below surface.</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, for a reference monument bears S. 79°20' E., 100.0 lks. dist., with brass cap mkd. RM SE 1/16 S10 66.0 FT TO COR 1998 and an arrow pointing to the cor.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, for a reference monument bears S. 14°23' W., 100.0 lks. dist., with brass cap mkd. RM SE 1/16 S10 66.0 FT TO COR 1998 and an arrow pointing to the cor.</p> <p>Cor. is located on gradual NW slope in sage, at N. edge of bladed road, 18 lks. wide, bears N. 53° W. and S. 61° E.</p>
41.337	<p>The center east 1/16 sec. cor. of sec. 10.</p> <hr/> <p>From the S 1/16 sec. cor. of secs. 10 and 11.</p> <p>S. 89°28'40" W., on the E. and W. center line of the SE1/4 of sec. 10.</p>
19.814	<p>The SE 1/16 sec. cor. of sec. 10.</p>
39.619	<p>The center south 1/16 sec. cor. of sec. 10.</p> <hr/>
	<p style="text-align: center;">SUBDIVISION OF SECTION 14, T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 14 and 23.</p> <p>N. 0°05'50" E., on the N. and S. center line of sec. 14.</p> <p>40.316 Point for the center 1/4 sec. cor. of sec. 14, at intersection with the E. and W. center line, falls on railroad tie.</p> <p>Set an iron spike flush with tie, 1.1 ft. SE of southerly rail, tracks, 5 ft. wide, bears N. 45° E. and S. 45° W.</p> <p>from which</p> <p>An embedded granite boulder, 7 x 6 x 5 ft. high, bears S. 57°20' W., 208.4 lks. dist., mkd. BXO on top.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, for a reference monument bears N. 72°30' W., 273.8 lks. dist., with brass cap mkd. RM T19N R18E S14 180.7 FT C1/4 1998 and an arrow pointing to the cor.</p>

180

SUBDIVISION OF SECTION 14,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
80.148	The point for the 1/4 sec. cor. of secs. 11 and 14.
	<p>From the 1/4 sec. cor. of secs. 13 and 14.</p> <p>S. 89°27'50" W., on the E. and W. center line of sec. 14.</p>
19.690	Point for the center east 1/16 sec. cor. of sec. 14.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>E 1/16</p> <p>C ——— C</p> <p>S14</p> <p>1998</p> </div>
	<p>from which</p> <p>An embedded granite boulder, 6 x 4 x 6 ft. high, bears S. 27°00' W., 332.1 lks. dist., mkd. BXO on NE face, 3 ft. above ground.</p> <p>An embedded granite boulder, 6 x 4 x 2 ft. high, bears N. 85°00' W., 196.3 lks. dist., mkd. BXO on E. end, 1 ft. above ground.</p> <p>Cor. is located on steep westerly slope with sage and bitterbrush.</p>
	The following Lot Corners and monuments on line;
30.054	An iron pin, 1/2 in. diam., firmly set, projecting 2 ins. above ground with nut on top, 1 in. sq., described by Thomas J. Welsh, RPE & LS No. 47, on unrecorded Record of Survey, on file in the County Engineers/Surveyor Office in Reno, Nevada, file No. 19181413 and as recorded in Washoe County, Record of Survey Map Nos. 1497 and 2959.
32.494	A granite boulder, 5 x 5 x 2 1/2 ft. high, mkd. with X on top, 1 ft. from N. edge as described by Thomas J. Welsh, RPE & LS No. 47, on unrecorded Record of Survey, on file in the County Engineers/Surveyor Office in Reno, Nevada, file No. 19181413 and as recorded in Washoe County, Record of Survey Map Nos. 1497 and 2959.
35.457	A chiseled X on concrete step as mkd. and described by Thomas J. Welsh, RPE & LS No. 47, on unrecorded Record of Survey, on file in the County Engineers/Surveyor Office in Reno, Nevada, file No. 19181413 and as recorded in Washoe County, Record of Survey Map Nos. 1497 and 2959.
35.785	An iron pin, 1 in. diam., firmly set, flush with ground described by Thomas J. Welsh, RPE & LS No. 47, on unrecorded Record of Survey, on file in the County Engineers/Surveyor Office in Reno, Nevada, file No. 19181413 and as recorded in Washoe County, Record of Survey Map No. 2959.

181

SUBDIVISION OF SECTION 14,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
38.569	A lot corner, established by Michael S. Smith, Nevada Professional Land Surveyor No. 6642, monumented with a brass disk, 1 3/8 ins. diam., mkd. PLS 6642, set flush in concrete, 1 1/2 ft. diam., and flush with ground, as recorded in Washoe County, Record of Survey Map Nos. 1497 and 2959. Described by Thomas J. Welsh, RPE & LS No. 47, as an iron pin, 1 in. diam., on unrecorded Record of Survey, on file in the County Engineers/Surveyor Office in Reno, Nevada, file No. 19181413.
39.262	A chiseled X on top of concrete drainage structure, 7 1/2 x 1 3/4 ft. wide, described by Thomas J. Welsh, RPE & LS No. 47, described on unrecorded Record of Survey, on file in the County Engineers/Surveyor Office in Reno, Nevada, file No. 19181413 and as recorded in Washoe County, Record of Survey Map Nos. 1497 and 2959.
39.380	The center 1/4 sec. cor. of sec. 14.
79.333	The 1/4 sec. cor. of secs. 14 and 15.
	<hr/> <p>From the E 1/16 sec. cor. of secs. 14 and 23.</p> <p>N. 0°31'40" E., on the N. and S. center line of the SE1/4 of sec. 14.</p>
40.056	The center east 1/16 sec. cor. of sec. 14.
	<hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 22, T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 22 and 27.</p> <p>N. 1°25'40" E., on the N. and S. center line of sec. 22.</p>
39.913	<p>Point for the center 1/4 sec. cor. of sec. 22, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T19N R18E C 1/4 S22</p> <p style="text-align: center;">1998</p> <p>from which</p> <p>An igneous boulder, 5 1/2 x 4 x 1 ft. high, bears N. 45°00' E., 93.9 lks. dist., mkd. BXO on top.</p> <p>An igneous boulder, 5 1/2 x 3 x 3 ft. high, bears S. 3°10' E., 117.6 lks. dist., mkd. BXO on N. face, 1 1/2 ft. above ground.</p>

SUBDIVISION OF SECTION 22,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>also from which</p> <p>The local center 1/4 sec. cor. of sec. 22, established by George G. Lindesmith, Nevada Professional Land Surveyor No. 6306, monumented with an iron rod, 5/8 in. diam., projecting 5 ins. above ground, with melted cap, bears N. 27°20' E., 3.2 lks. dist., as recorded in Washoe County, Parcel Map No. 2935 and based on a survey by Alan Means, Nevada Registered Land Surveyor No. 3573, as recorded in Washoe County, Parcel Map No. 612. The local position did not use evidence of the original survey to properly subdivide the section and is not utilized in this resurvey.</p> <p>Cor. is located on N. slope with burned mountain mahogany.</p> <p>49.925 At a point 1.2 lks. E. of a parcel corner, established by George G. Lindesmith, Nevada Professional Land Surveyor No. 6306, an iron rod, 5/8 in. diam., firmly set, projecting 6 ins. above ground with melted plastic cap, and in a collar of stone, 2 ft. diam., as recorded in Washoe County, Parcel Map No. 2935. Position was not used in the course of this resurvey due to use of improper control to subdivide the section.</p> <p>59.888 Point for the center north 1/16 sec. cor. of sec. 22.</p> <p>Set a stainless steel post, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 1 1/2 ft. base, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} C \\ N\ 1/16 \left S22 \\ C \end{array}$ <p>1998</p> </div> <p>from which</p> <p>An igneous boulder, 7 x 3 x 3 ft. high, bears N. 21°30' E., 163.0 lks. dist., mkd. BXO on SW face, 1 ft. above ground.</p> <p>An igneous boulder, 7 x 5 x 2 1/2 ft. high, bears S. 15°00' W., 242.6 lks. dist., mkd. BXO on N. face, 1 3/4 ft. above ground.</p> <p>An iron rod, 5/8 in. diam., firmly set, projecting 1 in. above ground, bears S. 34°00' W., 9.8 lks. dist., with no marks. Alongside of which is a fence cor., 4 wire, metal and burned wood posts, bears E. and S.</p> <p>Cor. is located on steep rocky W. slope in burn area.</p> <p>From this corner, the local center north 1/16 sec. cor. of sec. 22, established by George G. Lindesmith, Nevada Professional Land Surveyor No. 6306, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 1 in. above ground, with melted cap, bears N. 15° E., 1.7 lks. dist., as recorded in Washoe County, Parcel Map No. 2935 and based on a survey by Alan Means, Nevada Registered Land Surveyor No. 3573, as recorded in Washoe County, Parcel Map No. 612.</p>
--------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

183

SUBDIVISION OF SECTION 22,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Local position did not use evidence of the original survey to properly subdivide the section and is not used in this resurvey.</p>
79.863	<p>The 1/4 sec. cor. of secs. 15 and 22.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 22 and 23.</p> <p>N. 89°44'10" W., on the E. and W. center line of sec. 22.</p>
40.706	<p>The center 1/4 sec. cor. of sec. 22.</p>
50.686	<p>At a point 2.1 lks. S. of a parcel corner, established by George G. Lindesmith, Nevada Professional Land Surveyor No. 6306, an iron rod, 5/8 in. diam., firmly set, projecting 3 ins. above ground, with melted plastic cap, as recorded in Washoe County, Parcel Map No. 2935. Position was not used in the course of this resurvey due to use of improper control to subdivide the section.</p>
60.692	<p>Point for the center west 1/16 sec. cor. of sec. 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 2 ft. diam., with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} W \ 1/16 \\ C \ \hline S22 \\ C \end{array}$ <p>1998</p> </div> <p>from which</p> <p style="padding-left: 40px;">An igneous boulder, 5 1/2 x 4 x 2 ft. high, bears S. 11°30' W., 32.9 lks. dist., mkd. BXO on N. face, 3/4 ft. above ground.</p> <p style="padding-left: 40px;">An igneous boulder, 4 x 2 1/2 x 2ft. high, bears N. 14°50' W., 18.1 lks. dist., mkd. BXO on S. face, 1 ft. above ground.</p> <p>Cor. is located on SE slope.</p> <p>From this corner, the local center west 1/16 sec. cor. of sec. 22, established by George G. Lindesmith, Nevada Professional Land Surveyor No. 6306, an iron rod, 5/8 in. diam., projecting 4 ins. above ground, with melted cap, bears N. 55° E., 1.8 lks. dist., and in a mound of stone, 3 ft. diam., as recorded in Washoe County, Parcel Map No. 2935, and based on a survey by Alan Means, Nevada Registered Land Surveyor No. 3573, as recorded in Washoe County, Parcel Map No. 612. Local position did not use evidence of the original survey to properly subdivide the section and is not used in this resurvey.</p>
80.678	<p>The 1/4 sec. cor. of secs. 21 and 22.</p> <hr/> <p>From the N 1/16 sec. cor. of secs. 22 and 23.</p>

184

SUBDIVISION OF SECTION 22,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 89°48'00" W., on the E. and W. center line of the NE1/4 of sec. 22.
40.667	The center north 1/16 sec. cor. of sec. 22. <hr/>
	From the center west 1/16 sec. cor. of sec. 22.
	N. 0°59'10" E., on the N. and S. center line of the NW1/4 of sec. 22.
9.983	At a point, 0.7 lks. W. of a parcel corner, established by George G. Lindesmith, Nevada Professional Land Surveyor No. 6306, an iron rod, 5/8 in. diam., firmly set, projecting 4 ins. above ground, with melted plastic cap, and in a collar of stone, 2 ft. diam., as recorded in Washoe County, Parcel Map No. 2935. Position was not used in the course of this resurvey due to use of improper control to subdivide the section.
15.349	At a point, 0.7 lks. W. of a parcel corner, established by George G. Lindesmith, Nevada Professional Land Surveyor No. 6306, an iron rod, 5/8 in. diam., firmly set, projecting 3 ins. above ground, with melted plastic cap, and in a collar of stone, 2 ft. diam., as recorded in Washoe County, Parcel Map No. 2935. Position was not used in the course of this resurvey due to use of improper control to subdivide the section. Also 0.6 lks. W. of an iron rod, 1/2 in. diam., firmly set, projecting 12 ins. above ground, unmarked and of unknown origin.
33.582	A lot corner, established by Richard W. Arden, Nevada Professional Land Surveyor No. 1643, an iron rod, 5/8 in. diam., firmly set, projecting 1 in. above ground with melted plastic cap, as recorded in Washoe County, Subdivision Tract Map No. 2097B. Also 0.8 lks. E. of an iron rod, 5/8 in. diam., firmly set, flush with ground, with plastic cap mkd. PLS 1643.
37.907	At a point, 0.3 lks. W. of a lot corner, established by Richard W. Arden, Nevada Professional Land Surveyor No. 1643, an iron rod, 5/8 in. diam., firmly set, projecting 8 ins. above ground, with plastic cap, mkd. RLS 1643, cemented into ground at end of chain link fence, bears N. 60° E., as recorded in Washoe County, Subdivision Tract Map No. 2097B.
38.10	Top of bank, at S. edge of canal, 20 ft. wide, bears N. 70° E. and S. 60° W. in curve.
38.404	Point for Angle Point No. 1 of the metes-and-bounds survey in the W1/2 of the NW1/4 of sec. 22, hereinafter described. From this point, an iron rod, 5/8 in. diam., established by Richard W. Arden, Nevada Professional Land Surveyor No. 1643, firmly set, projecting 2 ins. above ground, with plastic cap mkd. RLS 1643, bears N. 30°00' W., 7.6 lks. dist., and in a collar of stone, 1 ft. diam., on the edge of the northern bank of Steamboat Ditch. Ditch bears N. 75° E. and S. 60° W. in curve.
39.908	The point for the W 1/16 sec. cor. of secs. 15 and 22. <hr/>

185

SUBDIVISION OF SECTION 23,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the 1/4 sec. cor. of secs. 23 and 26.</p>
	<p>N. 1°09'40" E., on the N. and S. center line of sec. 23.</p>
41.304	<p>Point for the center 1/4 sec. cor. of sec. 23, at intersection with the E. and W. center line.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar stone, 1 1/2 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T19N R18E C 1/4 S23</p>
	<p style="text-align: center;">1998</p>
	<p>from which</p>
	<p style="padding-left: 40px;">An igneous boulder, 5 x 4 x 2 1/2 ft. high, bears S. 29°20' W., 34.5 lks. dist., mkd. BXO on NNE face, 2 ft. above ground.</p>
	<p>Cor. is located in dry drainage, drains N. 30° E., with sage.</p>
61.047	<p>Point for the center north 1/16 sec. cor. of sec. 23.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;"> $\begin{array}{c} C \\ N\ 1/16 \left S23 \\ C \end{array}$ </p>
	<p style="text-align: center;">1998</p>
	<p>from which</p>
	<p style="padding-left: 40px;">An igneous boulder, 7 x 6 x 4 ft. high, bears N. 61°30' E., 95.7 lks. dist., mkd. BXO on W. sloping face near top.</p>
	<p style="padding-left: 40px;">An igneous boulder, 4 1/2 x 3 x 2 1/2 ft. high, bears N. 19°40' W., 48.8 lks. dist., mkd. BXO on top.</p>
	<p>Cor. is located on steep open WNW slope.</p>
80.790	<p>The 1/4 sec. cor. of secs. 14 and 23.</p>
	<hr/>
	<p>From the 1/4 sec. cor. of secs. 23 and 24.</p>
	<p>S. 89°09'00" W., on the E. and W. center line of sec. 23.</p>
38.918	<p>The center 1/4 sec. cor. of sec. 23.</p>
58.879	<p>Point for the center west 1/16 sec. cor. of sec. 23, falls on unstable slope.</p>
	<p>At the true point, chisel an X on embedded rock, 18 x 9 ins., 7 ins. below surface.</p>

186

SUBDIVISION OF SECTION 23,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 18 ins. in the ground, over a plastic-encased magnet, for a reference monument bears N. 88°40' E., 55.5 lks. dist., mkd. RM CW 1/16 S23 36.6 FT 1998 and an arrow pointing to the cor.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground, over a plastic-encased magnet, for a reference monument bears S. 31°00' W., 110.4 lks. dist., mkd. RM CW 1/16 S23 72.8 FT 1998 and an arrow pointing to the cor.</p> <p>Cor. is located on steep open NNW slope.</p> <p>78.840 The 1/4 sec. cor. of secs. 22 and 23.</p> <hr/> <p>From the center west 1/16 sec. cor. of sec. 23.</p> <p>N. 1°14'10" E., on the N. and S. center line of the NW1/4 of sec. 23.</p> <p>19.881 Point for the NW 1/16 sec. cor. of sec. 23, at intersection with the E. and W. center line of the NW1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S23</p> <p style="text-align: center;">1998</p> <p>from which</p> <p>An igneous boulder, 2 1/2 x 2 x 2 ft. high, bears S. 1°00' W., 71.4 lks. dist., mkd. BXO on top.</p> <p>An igneous boulder, 2 1/2 x 1 1/2 x 2 ft. high, bears N. 26°00' W., 5.7 lks. dist., mkd. BXO on top.</p> <p>Cor. is located on steep open NNW slope.</p> <p>19.892 Intersect line bet. Angle Point No. 11 and Angle Point No. 12, of the metes-and-bounds survey in sec. 23, from which Angle Point No. 11 bears N. 89°34'20" E., 0.087 chs. dist., hereinafter described.</p> <p>39.757 The W 1/16 sec. cor. of secs. 14 and 23.</p> <hr/> <p>From the center north 1/16 sec. cor. of sec. 23.</p> <p>S. 89°32'40" W., on the E. and W. center line of the NW1/4 of sec. 23.</p> <p>19.930 The NW 1/16 sec. cor. of sec. 23.</p>
--------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

187

SUBDIVISION OF SECTION 23,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.678	Intersect line bet. Angle Point No. 12 of the metes-and-bounds survey in sec. 23, and the 1/4 sec. cor. of secs. 22 and 23, from which Angle Point No. 12 bears N. 1°49'30" E., 0.021 chs. dist., hereinafter described.
39.856	The N 1/16 sec. cor. of secs. 22 and 23.
<p style="margin: 0;">SUBDIVISION OF SECTION 24, T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA</p>	
<p style="margin: 0;">From the 1/4 sec. cor. of secs. 24 and 25. N. 1°03'50" E., on the N. and S. center line of sec. 24.</p>	
37.732	Angle point No. 4, of the metes-and-bounds survey in sec. 24, hereinafter described. From this point, a locally established control point bears S. 86°24'10" E., 37.390 chs. dist., hereinbefore described.
39.620	Point for the center 1/4 sec. cor. of sec. 24, at intersection with the E. and W. center line. Set a stainless steel post, 2 1/2 ins. diam., 22 ins. in the ground over a plastic-encased magnet, and in a collar of stone, 2 ft. base, to top, with brass cap mkd.
<p style="margin: 0;">T19N R18E C 1/4 S24 1998</p>	
<p style="margin: 0;">Cor. is located on open grassy NNE slope. From this corner, an iron rod, 5/8 ins. diam., firmly set, projecting 2 ins. above ground with melted plastic cap, set by Alan Means, Nevada Registered Land Surveyor No. 3573, in 1979, bears S. 1°00' W., 188.8 lks. dist., as recorded in Washoe County, Land Map No. 43B. This position is not accepted for section subdivision due to use of improper control. This cor. is remonumented as Angle Point No. 4, hereinafter described.</p>	
63.460	Angle Point No. 3, of the metes-and-bounds survey in sec. 24, hereinafter described.
80.463	The 1/4 sec. cor. of secs. 13 and 24.
<p style="margin: 0;">From the 1/4 sec. cor. of secs. 19 and 24, on the E. bdy. of the Tp. N. 89°06'30" W., on the E. and W. center line of sec. 24.</p>	
35.073	The center 1/4 sec. cor. of sec. 24.

188

SUBDIVISION OF SECTION 24,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
55.025	Intersect line bet. Angle Point No. 5 of the metes-and-bounds survey in sec. 24, and the W 1/16 sec. cor. of secs. 13 and 24, from which Angle Point No. 5 bears S. 1°00'20" W., 0.945 chs. dist., hereinafter described.
55.028	<p>Point for the center west 1/16 sec. cor. of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 2 ft. diam., with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \text{W } 1/16 \\ \text{C} \text{ --- } \text{C} \\ \text{S24} \\ 1998 \end{array}$ </div> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 21 ins. in the ground, over a plastic-encased magnet, for a reference monument bears N. 88°20' E., 100.6 lks. dist., mkd. RM CW 1/16 S24 66.4 FT 1998 and an arrow pointing to the cor.</p> <p>Cor. is located on brushy NNE slope 3 lks. S. of S. bank of Steamboat ditch, 10 ft. wide, bank bears N. 50° W. and E. Steamboat Ditch drains N. 70° E. from N. 20° W. A lone willow, 2 ft. diam., bears N. 80° W., 30 lks. dist., partially decayed.</p>
74.983	<p>The 1/4 sec. cor. of secs. 23 and 24.</p> <hr/> <p>From the center west 1/16 sec. cor. of sec. 24.</p> <p>N. 1°00'40" E., on the N. and S. center line of the NW1/4 of sec. 24.</p>
40.323	<p>The W 1/16 sec. cor. of secs. 13 and 24.</p> <hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 29, T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>
20.400	<p>From the 1/4 sec. cor. of secs. 29 and 32.</p> <p>N. 2°27'40" W., on the N. and S. center line of sec. 29.</p> <p>Point for the center south 1/16 sec. cor. of sec. 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \text{C} \\ \text{S } 1/16 \text{ --- } \text{S29} \\ \text{C} \\ 1998 \end{array}$ </div>

SUBDIVISION OF SECTION 29,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 40 ins. diam., bears N. 2 1/2° E., 111 lks. dist., mkd. CS 1/16 S29 BT.</p> <p>Cor. is located on steep N. slope with pine timber to N.</p> <p>40.800 Point for the center 1/4 sec. cor. of sec. 29, at intersection with the E. and W. center line.</p> <p style="padding-left: 40px;">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T19N R18E C 1/4 S29</p> <p style="text-align: center;">1998</p> <p>from which</p> <p style="padding-left: 40px;">An igneous boulder, 4 x 2 1/2 x 1 1/2 ft. high, bears N. 54°50' E., 52.1 lks. dist., mkd. BXO on WSW face, 1 ft. above ground.</p> <p style="padding-left: 40px;">An igneous boulder, 3 x 1 1/2 x 2 ft. high, bears N. 47°30' W., 86.3 lks. dist., mkd. BXO on S. face, 1 ft. above ground.</p> <p>Cor. is located on open rocky S. slope with sage.</p> <p>60.490 Point for the center north 1/16 sec. cor. of sec. 29.</p> <p>Not monumented.</p> <p>80.180 The 1/4 sec. cor. of secs. 20 and 29.</p> <hr/> <p style="padding-left: 40px;">From the 1/4 sec. cor. of secs. 28 and 29.</p> <p style="padding-left: 40px;">N. 89°56'10" W., on the E. and W. center line of sec. 29.</p> <p>20.879 Point for the center east 1/16 sec. cor. of sec. 29.</p> <p style="padding-left: 40px;">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. diam., with brass cap mkd.</p> <p style="text-align: center;">E 1/16 C ——— C S29</p> <p style="text-align: center;">1998</p> <p>from which</p> <p style="padding-left: 40px;">An igneous boulder, 2 1/2 x 2 x 2 ft. high, bears S. 6°10' E., 52.5 lks. dist., mkd. BXO on top.</p>
--------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

190

SUBDIVISION OF SECTION 29,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>An igneous boulder, 2 x 2 x 2 1/2 ft. high, bears N. 70°50' W., 19.6 lks. dist., mkd. BXO on SE. face, 6 ins. above ground.</p> <p>Cor. is located on moderate NW open slope with burned mountain mahogany.</p>
41.758	The center 1/4 sec. cor. of sec. 29.
62.671	<p>Point for the center west 1/16 sec. cor. of sec. 29.</p> <p>Not monumented.</p>
83.584	<p>The 1/4 sec. cor. of secs. 29 and 30.</p> <hr/> <p>From the center east 1/16 sec. cor. of sec. 29.</p> <p>N. 0°33'50" W., on the N. and S. center line of the NE1/4 of sec. 29.</p>
19.704	<p>Point for the NE 1/16 sec. cor. of sec. 29, at intersection with the E. and W. center line of the NE1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S29</p> <p style="text-align: center;">1998</p> <p>from which</p> <p>An igneous boulder, 3 x 2 x 2 1/2 ft. high, bears S. 55°30' E., 61.5 lks. dist., mkd. BXO on NW face, 1 1/2 ft. above ground.</p> <p>An igneous boulder, 4 1/2 x 4 x 2 1/2 ft. high, bears S. 31°00' W., 75.2 lks. dist., mkd. BXO on N. face, 2 ft. above ground.</p> <p>Cor. is located on moderate open rocky NNW slope with sage.</p>
39.408	<p>The E 1/16 sec. cor. of secs. 20 and 29.</p> <hr/> <p>From the N 1/16 sec. cor. of secs. 28 and 29.</p> <p>S. 89°58'40" W., on the E. and W. center line of the NE1/4 of sec. 29.</p>
21.530	The NE 1/16 sec. cor. of sec. 29.
43.060	<p>The point for the center north 1/16 sec. cor. of sec. 29.</p> <hr/>

SUBDIVISION OF SECTION 29,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the E 1/16 sec. cor. of secs. 29 and 32.</p>
	<p>N. 1°03'30" W., on the N. and S. center line of the SE1/4 of sec. 29.</p>
20.477	<p>Point for the SE 1/16 sec. cor. of sec. 29, at intersection with the E. and W. center line of the SE1/4.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">SE 1/16 S29</p>
	<p style="text-align: center;">1998</p>
	<p>from which</p>
	<p>An igneous boulder, 4 x 3 x 3 ft. high, bears S. 49°20' W., 93.1 lks. dist., mkd. BXO on NE face, 2 ft. above ground.</p>
	<p>An igneous boulder, 3 x 2 1/2 x 2 ft. high, bears N. 23°10' W., 32.6 lks. dist., mkd. BXO on SE face, 1 ft. above ground.</p>
	<p>Cor. is located on gradual open N. slope 1/2 ch. N. of small rocky knoll. Pine to NE in burn.</p>
40.954	<p>The center east 1/16 sec. cor. of sec. 29.</p>
	<hr/>
	<p>From the point for the S 1/16 sec. cor. of secs. 28 and 29.</p>
	<p>N. 89°40'30" W., on the E. and W. center line of the SE1/4 of sec. 29.</p>
20.383	<p>The SE 1/16 sec. cor. of sec. 29.</p>
40.766	<p>The center south 1/16 sec. cor. of sec. 29.</p>
	<hr/>
	<p>From the W 1/16 sec. cor. of secs. 29 and 32.</p>
	<p>N. 2°53'30" W., on the N. and S. center line of the SW1/4 of sec. 29.</p>
20.248	<p>Point for the SW 1/16 sec. cor. of sec. 29, at intersection with the E. and W. center line of the SW1/4.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">SW 1/16 S29</p>
	<p style="text-align: center;">1998</p>

192

SUBDIVISION OF SECTION 29,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>from which</p> <p>A meta-volcanic boulder, 5 x 2 x 3 ft. high, bears S. 62°50' E., 29.5 lks. dist., mkd. BXO on top.</p> <p>A ponderosa pine, 26 ins. diam., bears N. 29 1/2° W., 166 lks. dist., mkd. SW 1/16 S29 BT.</p> <p>Cor. is located on steep NNE slope, scattered pine and cedar to N. in ravine.</p>
40.496	<p>The point for the center west 1/16 sec. cor. of sec. 29.</p> <hr/>
	<p>From the center south 1/16 sec. cor. of sec. 29.</p> <p>N. 89°29'50" W., on the E. and W. center line of the SW1/4 of sec. 29.</p>
20.770	<p>The SW 1/16 sec. cor. of sec. 29.</p>
41.540	<p>The point for the S 1/16 sec. cor. of secs. 29 and 30.</p> <hr/>
	<p style="text-align: center;">SUBDIVISION OF ELONGATED SECTION 30, T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 30 and 31.</p> <p>North, on the N. and S. center line of sec. 30.</p> <p>20.148 Point for the center south 1/16 sec. cor. of sec. 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} C \\ S\ 1/16 \left S30 \\ C \end{array}$ <p>1999</p> </div>
40.296	<p>from which</p> <p>An incense cedar, 23 ins. diam., bears S. 87° E., 27 lks. dist., mkd. CS 1/16 S30 BT.</p> <p>A ponderosa pine, 27 ins. diam., bears S. 20° W., 67 lks. dist., mkd. CS 1/16 S30 BT.</p> <p>Cor. is located on steep ESE slope with scattered pine and cedar timber.</p> <p>Point for the center 1/4 sec. cor. of sec. 30, at intersection with the E. and W. center line.</p>

193

SUBDIVISION OF ELONGATED SECTION 30,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T19N R18E C 1/4 S30</p> <p style="text-align: center;">1999</p> <p>from which</p> <p style="padding-left: 40px;">A Jeffrey pine, 12 ins. diam., bears S. 88° W., 50 lks. dist., mkd. C 1/4 S30 BT.</p> <p style="padding-left: 40px;">A Jeffrey pine, 11 ins. diam., bears N. 22° W., 45 lks. dist., mkd. C 1/4 S30 BT.</p> <p>Cor. is located on a NNW slope with mountain mahogany and bitterbrush with scattered pine.</p> <p>80.168 The 1/4 sec. cor. of secs. 19 and 30.</p> <hr/> <p>From the 1/4 cor. of secs. 29 and 30.</p> <p>N. 89°32'10" W., on the E. and W. center line of sec. 30.</p> <p>19.657 Point for the center east 1/16 sec. cor. of sec. 30.</p> <p>Not monumented.</p> <p>39.314 The center 1/4 sec. cor. of sec. 30.</p> <p>42.974 Intersect the California-Nevada State Line.</p> <p>Not monumented.</p> <p>From this point, Mile Post 173, on the California-Nevada State Line, bears N. 0°47'10" E., 32.103 chs. dist., hereinbefore described.</p> <p>60.203 Point for the center west 1/16 sec. cor. of sec. 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">W 1/16 C ——— C S30</p> <p style="text-align: center;">1999</p> <p>from which</p> <p style="padding-left: 40px;">A cedar, 11 ins. diam., bears S. 3° E., 42 lks., dist., mkd. CW 1/16 S30 BT.</p> <p style="padding-left: 40px;">A Jeffrey pine, 12 ins. diam., bears S. 54 1/4° W., 24 lks. dist., mkd. CW 1/16 S30 BT.</p>
--------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

194

SUBDIVISION OF ELONGATED SECTION 30,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	Cor. is located on gradual NE slope with pine, cedar, and mountain mahogany in rocky soil.
81.093	<p>Point for the center 80 1/16 sec. cor. of sec. 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> $C \frac{1/16}{S30} 80$ <p>1999</p> <p>from which</p> <p>A cedar, 5 ins. diam., bears N. 22 1/4° E., 103 1/2 lks., dist., mkd. X BT.</p> <p>A cedar, 11 ins. diam., bears N. 67° E., 93 lks. dist., mkd. C80 1/16 S30 BT.</p> <p>Cor. is located on moderate NE slope with dense brush in rocky soil.</p>
101.591	<p>The 1/4 sec. cor. of secs. 30 and 30, on the old California-Nevada State Line.</p> <hr/> <p>From the E 1/16 sec. cor. of secs. 30 and 31.</p> <p>N. 1°39'40" W., on the N. and S. center line of the SE1/4 of sec. 30.</p>
20.114	<p>Point for the SE 1/16 sec. cor. of sec. 30, at intersection with the E. and W. center line of the SE1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> $SE \frac{1/16}{S30}$ <p>1999</p> <p>from which</p> <p>A Jeffrey pine, 30 ins. diam., bears N. 72 1/4° E., 150 lks. dist., mkd. SE 1/16 S30 BT.</p>
40.228	<p>Cor. is located on a moderate open E. slope with sagebrush and scattered pine and cedar.</p> <p>The point for the center east 1/16 sec. cor. of sec. 30.</p> <hr/>

195

SUBDIVISION OF ELONGATED SECTION 30,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	<p>From the point for the S 1/16 sec. cor. of secs. 29 and 30.</p> <p>N. 89°40'00" W., on the E. and W. center line of the SE1/4 of sec. 30.</p>
20.241	The SE 1/16 sec. cor. of sec. 30.
40.482	The center south 1/16 sec. cor. of sec. 30.
	<hr/> <p>From the true point for the W 1/16 sec. cor. of secs. 30 and 31.</p> <p>N. 0°12'20" W., on the N. and S. center line of the SW1/4 of sec. 30.</p>
20.130	<p>Point for the SW 1/16 sec. cor. of sec. 30, at intersection with the E. and W. center line of the SW1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">SW 1/16 S30</p> <p style="text-align: center;">1999</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 22 ins. diam., bears S. 74 1/2° E., 98 lks. dist., mkd. SW 1/16 S30 BT.</p> <p>Cor. is located on steep S. slope with sagebrush, mountain mahogany, bitterbrush, and scattered pine.</p>
40.250	<p>The center west 1/16 sec. cor. of sec. 30.</p> <hr/> <p>From the center south 1/16 sec. cor. of sec. 30.</p> <p>N. 89°27'30" W., on the E. and W. center line of the SW1/4 of sec. 30.</p>
3.936	<p>Intersect the California-Nevada State Line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>CAL NEV</p> <p>—+—</p> <p> </p> <p>S S</p> <p> </p> <p> S30</p> <p> 1999</p> </div> <p>from which</p> <p style="padding-left: 40px;">A Jeffrey pine, 13 ins. diam., bears N. 29 1/2° E., 135 lks. dist., mkd. X BT.</p>

196

SUBDIVISION OF ELONGATED SECTION 30,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	<p>A Jeffrey pine, 22 ins. diam., bears N. 78° E., 87 1/2 lks. dist., mkd. X BT.</p> <p>Cor. is located on E. slope with sagebrush, bitterbrush, and pine to NE.</p> <p>From this corner, Mile Post 174, on the California-Nevada State Line, bears S. 0°47'10" W., 27.076 chs. dist., hereinbefore described.</p>
20.819	The SW 1/16 sec. cor. of sec. 30.
41.636	<p>Point for the south 80 1/16 sec. cor. of sec. 30, at intersection with the N. and S. 80 line of the SW1/4 of sec. 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>1/16</p> <p>S $\frac{\quad}{\quad}$ 80</p> <p>S 30</p> <p>1999</p> </div> <p>Cor. is located on steep SW slope, 27 lks. E. of ravine, 1 ch. wide, drains S. 40° W. with pine, cedar, and bitterbrush in rocky soil.</p>
62.267	<p>The S 1/16 sec. cor. of secs. 30 and 30, on the old California-Nevada State Line.</p> <hr/> <p>From the point for the 80 1/16 sec. cor. of secs. 30 and 31.</p> <p>N. 0°25'00" W., on the N. and S. 80 line of the SW1/4 of sec. 30.</p>
20.099	The south 80 1/16 sec. cor. of sec. 30.
40.193	The center 80 1/16 sec. cor. of sec. 30.
	<hr/> <p style="text-align: center;">SUBDIVISION OF ELONGATED SECTION 31, T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 6 and 31, on the S. bdy. of the Tp.</p> <p>N. 0°24'30" E., on the N. and S. center line of sec. 31.</p>
39.610	<p>Point for center 1/4 sec. cor. of sec. 31, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p>

197

SUBDIVISION OF ELONGATED SECTION 31,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	<p>T19N R18E C 1/4 S31</p> <p>1999</p> <p>from which</p> <p>A granite boulder, 14 x 7 x 8 ft. high, bears N. 70°00' E., 70.0 lks. dist., mkd. BXO on SW face, 8 ft. above ground and under fence paralleling highway.</p> <p>A Jeffrey pine, 14 ins. diam., bears S. 18 3/4° W., 208 lks. dist., mkd. C 1/4 S31 BT.</p> <p>Cor. is located on a steep SE sage covered slope, 33 lks. S. and 22 lks. E. of E. edge of pavement of Interstate Highway 80.</p> <p>59.555 Point for the center north 1/16 sec. cor. of sec. 31.</p> <p>Set a brass tablet, 3 1/2 ins. diam., 3 in. stem., cemented into an iron pipe, 1 1/8 in. diam., 16 ins. long, cemented into drill hole, projecting 5 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">C N 1/16 S31 C</p> <p>1999</p> <p>from which</p> <p>A granite boulder, 3 x 2 x 1 ft. high, bears S. 37°50' W., 45.3 lks. dist., mkd. BXO, 3 ins. below top on northern portion. Boulder is on crest of narrow ridge, bears S. 60° E. and N. 60° W.</p> <p>Cor. is located on steep NE slope with bitterbrush, mountain mahogany, and sage.</p> <p>79.500 The 1/4 sec. cor. of secs. 30 and 31.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 31 and 32.</p> <p>N. 89°44'40" W., on the E. and W. center line of sec. 31.</p> <p>19.786 Point for the center east 1/16 sec. cor. of sec. 31.</p> <p>Not monumented.</p> <p>39.572 The center 1/4 sec. cor. of sec. 31.</p> <p>43.911 Intersect the California-Nevada State Line.</p> <p>Not monumented.</p> <p>From this point, the point for Mile Post 174+44, on the California-Nevada State Line, bears S. 0°32'50" W., 12.884 chs. dist., hereinbefore described.</p>
--------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

198

SUBDIVISION OF ELONGATED SECTION 31,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

<p>CHAINS</p> <p>60.184</p>	<p>Point for the center west 1/16 sec. cor. of sec. 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> $\begin{array}{c} \text{W } 1/16 \\ \text{C } \frac{\quad}{\quad} \text{C} \\ \text{S31} \end{array}$ <p>1999</p> <p>from which a local bearing tree</p> <p>A Jeffrey pine, 33 ins. diam., bears N. 23° E., 41 lks., dist., with attn. sign.</p> <p>from which new accessories</p> <p>A granite boulder, 20 x 12 x 6 ft. high, bears S. 54°30' E., 272.6 lks. dist., mkd. BXO on top, 5 ft. from W. end.</p> <p>An igneous boulder, 6 x 4 x 1 1/2 ft. high, bears S. 8°20' W., 35.5 lks. dist., mkd. BXO on NE face, 1 ft. above ground.</p> <p>Cor. is located on steep SE slope with pine timber.</p>
<p>80.796</p>	<p>Point for the center 80 1/16 sec. cor. of sec. 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> $\begin{array}{c} 1/16 \\ \text{C } \frac{\quad}{\quad} 80 \\ \text{S31} \end{array}$ <p>1999</p> <p>from which</p> <p>A cedar, 12 ins. diam., bears N. 28 1/2° E., 34 lks., dist., mkd. C80 1/16 S31 BT.</p> <p>A granite boulder, 10 x 10 x 6 ft. high, bears S. 27°20' E., 131.1 lks. dist., mkd. BXO on NW face, 2 ft. above ground.</p> <p>Cor. is located on steep E. slope with pine, fir, mountain mahogany, and manzanita.</p>
<p>101.676</p>	<p>The 1/4 sec. cor. of secs. 31 and 31, on the old California-Nevada State Line.</p> <hr/>

SUBDIVISION OF ELONGATED SECTION 31,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	From the point for the center east 1/16 sec. cor. of sec. 31.
	N. 1°54'00" E., on the N. and S. center line of the NE1/4 of sec. 31.
19.962	Point for the NE 1/16 sec. cor. of sec. 31, at intersection with the E. and W. center line of the NE1/4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 3 ft. base, to top, with brass cap mkd.
	NE 1/16 S31
	1999
	from which
	A granite boulder, 4 1/2 x 4 x 4 1/2 ft. high, bears N. 15°00' E., 133.4 lks. dist., mkd. BXO on SSE face, 1 ft. from top.
	A granite boulder, 6 1/2 x 5 x 3 ft. high, bears N. 57°30' W., 69.7 lks. dist., mkd. BXO on SE face, 1/2 ft. from top.
	Cor. is located on open level ground at E. side of jeep trail and buried fiber optic cable line, bears S. 32° W. and N. 32° E.
39.924	The E 1/16 sec. cor. of secs. 30 and 31.
	<hr/>
	From the N 1/16 sec. cor. of secs. 31 and 32.
	N. 89°46'10" W., on the E. and W. center line of the NE1/4 of sec. 31.
20.306	The NE 1/16 sec. cor. of sec. 31.
40.612	The center north 1/16 sec. cor. of sec. 31.
	<hr/>
	From the center west 1/16 sec. cor. of sec. 31.
	N. 0°12'30" E., on the N. and S. center line of the NW1/4 of sec. 31.
20.010	Point for the NW 1/16 sec. cor. of sec. 31, at intersection of E. and W. center line of the NW1/4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 5 ins. in the ground, over a plastic-encased magnet, set into chiseled out rock in place and in a mound of stone, 5 ft. base, to top, with brass cap mkd.
	NW 1/16 S31
	1999

200

SUBDIVISION OF ELONGATED SECTION 31,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	<p>from which</p> <p>A Jeffrey pine, 29 ins. diam., bears N. 58° E., 135 lks. dist., mkd. NW 1/16 S31 BT.</p> <p>An igneous boulder, 7 x 4 x 4 ft. high, bears N. 39°20' W., 71.2 lks. dist., mkd. BXO on SE face, 2 ft. above ground.</p> <p>Cor. is located on steep E. slope with scattered pine and mountain mahogany.</p> <p>40.011 The true point for the W 1/16 sec. cor. of secs. 30 and 31.</p> <hr/> <p>From the center north 1/16 sec. cor. of sec. 31.</p> <p>N. 89°33'50" W., on the E. and W. center line of the NW1/4 of sec. 31.</p> <p>4.290 Intersect the California-Nevada State Line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>CAL NEV</p> <p>— —</p> <p>N — — N</p> <p> </p> <p> S31</p> <p> 1999</p> </div> <p>from which</p> <p>An igneous rock face, 6 ft. wide x 3 ft. high, bears S. 88°50' E., 90.0 lks. dist., mkd. BXO on W. face, 4 ft. above ground.</p> <p>Point is located on steep SE slope with sagebrush, 23 lks. above base of slope.</p> <p>From this point, Mile Post 174, on the California-Nevada State Line, bears N. 0°32'50" E., 13.025 chs. dist., hereinbefore described.</p> <p>20.680 The NW 1/16 sec. cor. of sec. 31.</p> <p>41.358 Point for the north 80 1/16 sec. cor. of sec. 31, at intersection with the N. and S. 80 line of the NW1/4 of sec. 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft., base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>1/16</p> <p>N ——— 80</p> <p> S31</p> <p> 1999</p> </div>
--------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

201

SUBDIVISION OF ELONGATED SECTION 31,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA

CHAINS	<p>from which</p> <p>An igneous boulder, 4 x 6 x 3 ft. high, bears N. 89°00' E., 65.7 lks. dist., mkd. BXO on top.</p> <p>An igneous boulder, 4 x 5 x 3 ft. high, bears N. 15°40' W., 25.8 lks. dist., mkd. BXO on S. face, 2 1/2 ft. above ground.</p> <p>Cor. is located on steep S. slope with scattered pine and sage in rocky soil.</p> <p>62.180 The point for the N 1/16 sec. cor. of secs. 31 and 31, on the old California-Nevada State Line.</p> <hr/> <p>From the center 80 1/16 sec. cor. of sec. 31.</p> <p>N. 0°01'00" E., on the N. and S. 80 line of the NW1/4 of sec. 31.</p> <p>20.076 The north 80 1/16 sec. cor. of sec. 31.</p> <p>40.148 The point for the 80 1/16 sec. cor. of secs. 30 and 31.</p> <hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 32, T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 5 and 32, on the S. bdy. of the Tp.</p> <p>N. 2°21'50" E., on the N. and S. center line of sec. 32.</p> <p>19.850 Point for the center south 1/16 sec. cor. of sec. 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} C \\ S\ 1/16 \left S32 \\ C \end{array}$ <p>1999</p> </div> <p>from which</p> <p>An igneous boulder, 6 x 4 1/2 x 2 1/2 ft. high, bears N. 32°20' E., 59.1 lks. dist., mkd. BXO on top.</p> <p>A Jeffrey pine, 25 ins. diam., bears S. 85 3/4° E., 84 lks. dist., mkd. CS 1/16 S32 BT.</p> <p>Cor. is located on rocky E. slope with mountain mahogany and scattered pine.</p>
--------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

202

SUBDIVISION OF SECTION 32,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.700	<p>Point for the center 1/4 sec. cor. of sec. 32, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T19N R18E C 1/4 S32</p> <p style="text-align: center;">1999</p> <p>from which</p> <p style="padding-left: 40px;">An igneous boulder, 3 x 3 x 3 ft. high, bears S. 51°00' E., 105.6 lks. dist., mkd. BXO on NW face, 2 1/2 ft. above ground.</p> <p style="padding-left: 40px;">An igneous boulder, 8 x 4 x 6 ft. high, bears S. 55°40' W., 123.7 lks. dist., mkd. BXO on NE face, 5 ft. above ground.</p> <p>Cor. is located on steep rocky NW slope with scattered pine and mountain mahogany.</p>
59.495	<p>Point for the center north 1/16 sec. cor. of sec. 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">C N 1/16 S32 C</p> <p style="text-align: center;">1999</p> <p>from which</p> <p style="padding-left: 40px;">A Jeffrey pine, 12 ins. diam., bears N. 46° E., 40 lks. dist., mkd. CN 1/16 S32 BT.</p> <p style="padding-left: 40px;">A Jeffrey pine, 16 ins. diam., bears N. 40° W., 44 lks. dist., mkd. CN 1/16 S32 BT.</p> <p>Cor. is located on steep rocky SW slope with scattered pine and mountain mahogany.</p>
79.290	<p>The 1/4 sec. cor. of secs. 29 and 32.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 32 and 33.</p> <p>N. 89°33'30" W., on the E. and W. center line of sec. 32.</p>
19.999	<p>Point for the center east 1/16 sec. cor. of sec. 32.</p>

203

SUBDIVISION OF SECTION 32,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. diam., with brass cap mkd.</p> <p style="text-align: center;">E 1/16 C ——— C S32</p> <p style="text-align: center;">1999</p> <p>from which</p> <p style="padding-left: 40px;">An igneous boulder, 2 x 1 1/2 x 1 ft. high, bears S. 49°00' W., 41.0 lks. dist., mkd. BXO on E. face, 1/2 ft. above ground.</p> <p style="padding-left: 40px;">An igneous boulder, 3 1/2 x 2 1/2 x 2 1/2 ft. high, bears N. 64°10' W., 114.3 lks. dist., mkd. BXO on SE. face, 1 1/2 ft. above ground,</p> <p>Cor. is located on moderate NW open slope with burned mountain mahogany.</p> <p>39.998 The center 1/4 sec. cor. of sec. 32.</p> <p>81.986 The 1/4 sec. cor. of secs. 31 and 32.</p> <hr/> <p>From the center east 1/16 sec. cor. of sec. 32.</p> <p>N. 2°12'20" E., on the N. and S. center line of the NE1/4 of sec. 32.</p> <p>19.766 Point for the NE 1/16 sec. cor. of sec. 32, at intersection with the E. and W. center line of the NE1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S32</p> <p style="text-align: center;">1999</p> <p>from which</p> <p style="padding-left: 40px;">A Jeffrey pine, 30 ins. diam., bears N. 8° E., 74 lks. dist., mkd. NE 1/16 S32 BT.</p> <p style="padding-left: 40px;">An igneous boulder, 3 x 2 x 2 ft. high, bears S. 83°10' E., 7.9 lks. dist., mkd. BXO on top.</p> <p>Cor. is located on E. slope with mountain mahogany and Jeffrey pine.</p> <p>39.532 The E 1/16 sec. cor. of secs. 29 and 32.</p> <hr/>
--------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

204

SUBDIVISION OF SECTION 32,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the N 1/16 sec. cor. of secs. 32 and 33.</p> <p>N. 89°28'50" W., on the E. and W. center line of the NE1/4 of sec. 32.</p>
19.943	The NE 1/16 sec. cor. of sec. 32.
39.886	The center north 1/16 sec. cor. of sec. 32.
	<hr/> <p>From the point for the E 1/16 sec. cor. of secs. 5 and 32, on the S. bdy. of the Tp.</p> <p>N. 2°12'30" E., on the N. and S. center line of the SE1/4 of sec. 32.</p>
19.793	<p>Point for the SE 1/16 sec. cor. of sec. 32, at intersection with the E. and W. center line of the SE1/4, falls at N. edge of a tree.</p> <p>At true point, set spike in cutout near base, 4 ins. into N. side of white fir, 16 ins. diam., and mkd. N. side, SE1/16.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 21 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, for a reference monument bears N. 53°30' E., 47.2 lks. dist., with brass cap mkd. RM SE 1/16 31.1 FT. S32 1999. RM and an arrow pointing to the cor., is located at W. edge of skid road, bears. S. 10° W. and N. with pine and fir timber.</p> <p style="padding-left: 40px;">An igneous boulder, 8 x 5 x 2 ft. high, bears S. 35°20' E., 75.3 lks. dist., mkd. BXO on top. Rock is at E. side of skid trail.</p>
39.586	The center east 1/16 sec. cor. of sec. 32.
	<hr/> <p>From the point for the S 1/16 sec. cor. of secs. 32 and 33.</p> <p>N. 89°42'50" W., on the E. and W. center line of the SE1/4 of sec. 32.</p>
20.057	The SE 1/16 sec. cor. of sec. 32.
40.114	The center south 1/16 sec. cor. of sec. 32.
	<hr/> <p>From the center north 1/16 sec. cor. of sec. 32.</p> <p>N. 89°18'30" W., on the E. and W. center line of the NW1/4 of sec. 32.</p>
41.622	The N 1/16 sec. cor. of secs. 31 and 32.

205

METES-AND-BOUNDS SURVEY IN SECTION 21,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>The following metes-and-bounds survey represents a Grant Boundary restoration of a portion of the boundary of Parcel 7, as shown on Land Division Map No. 43, recorded in Washoe County, Nevada, in 1979 and is based on Document No. 393665, as recorded in Washoe County, Nevada, Book 705 of Deeds, Pages 151-153.</p> <p>From the point for Angle Point No. 1, on the line bet. secs. 21 and 22, determined at record distance from the cor. of secs. 15, 16, 21, and 22, falls in maintenance road along N. side of Steamboat Ditch.</p> <p>Not monumented.</p> <p>From this point, the cor. of secs. 15, 16, 21, and 22, bears N. 0°32'30" E., 4.456 chs. dist., hereinbefore described.</p> <p>From this same point, the point for Angle Point No. 10, of the metes-and-bounds survey in sec. 22 bears S. 0°32'30" W., 0.209 chs. dist., hereinafter described.</p> <p>S. 75°01'50" W., 0.590 chs. Point for Angle Point No. 2, falls at S. edge of maintenance road along Steamboat Ditch.</p> <p>Not monumented.</p> <p>N. 34°06'00" W., 1.089 chs. Point for Angle Point No. 3, falls at N. edge of maintenance road along Steamboat Ditch.</p> <p>Not monumented.</p> <p>N. 47°13'00" W., 2.809 chs. Point for Angle Point No. 4, falls at N. edge of maintenance road along Steamboat Ditch.</p> <p>Not monumented.</p> <p>N. 65°06'00" W., 1.867 chs. Point for Angle Point No. 5, falls at N. edge of maintenance road along Steamboat Ditch.</p> <p>Not monumented.</p> <p>N. 74°54'10" W., 1.289 chs. Point for Angle Point No. 6, falls at N. edge of maintenance road along Steamboat Ditch.</p> <p>Not monumented.</p>
--------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

206

METES-AND-BOUNDS SURVEY IN SECTION 21,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>S. 61°35'50" W., 1.103 chs. Point for Angle Point No. 7, falls at S. edge of maintenance road along Steamboat Ditch.</p> <p>Not monumented.</p> <p>N. 58°21'20" W., 2.359 chs. Point for Angle Point No. 8, falls in center of maintenance road along Steamboat Ditch.</p> <p>Not monumented.</p> <p>N. 2°04'50" E., 0.293 chs. Point for Angle Point No. 9, on the line bet. secs. 16 and 21, determined at record distance from the cor. of secs. 15, 16, 21, and 22, falls in fence line, bears E. and W.</p> <p>Not monumented.</p> <p>From this point, the cor. of secs. 15, 16, 21, and 22, bears S. 87°56'50" E., 9.197 chs. dist., hereinbefore described.</p> <hr/> <p>METES-AND-BOUNDS SURVEY IN SECTION 22, T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>The following metes-and-bounds survey represents the northerly line of the Steamboat Ditch through the W1/2 of the NW1/4 of section 22, T. 19 N., R. 18 E., M.D.M., Nevada, as shown on Parcel Map No. 612 and Subdivision Tract Map No. 2097B, and is based on Book 112 of Deeds, Pages 540-545, Document No. 480326, as recorded in Washoe County, Nevada.</p> <hr/> <p>Most of the local survey monuments along Steamboat Ditch were found to have been set at convenient points on stable ground northerly of the ditch and some along lot lines as depicted on the map for Belli Ranch Estates, Subdivision Tract Map No. 2097B, recorded in Washoe County, Nevada.</p> <p>Additional monuments along the ditch, some at acceptable record positions, are hereinafter described in the metes-and-bounds survey. The Grant Boundary method of adjustment was used to restore the position of missing corners.</p> <p>From the point for Angle Point No. 1, on the N. and S. center line of the NW1/4 of sec. 22. Point at proportionate measure based on Belli Ranch Estates, recorded in Washoe County, Nevada, Subdivision Tract Map No. 2097B. Point falls in Steamboat Ditch where it is impractical to establish a permanent monument.</p>
--------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

207

METES-AND-BOUNDS SURVEY IN SECTION 22,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Not monumented.</p> <p>From this point, the point for the W 1/16 sec. cor. of secs. 15 and 22, bears N. 0°59'10" E., 1.504 chs. dist., hereinbefore described.</p> <p>S. 53°59'30" W., 1.589 chs. Point for the SE cor. of Lot 37, identical to the SW cor. of Lot 38, Belli Ranch Estates, as recorded in Washoe County, Nevada, Subdivision Tract Map No. 2097B. Point falls in Steamboat Ditch.</p> <p>From this point, an offset position, determined by Elmer J. Plummer, Nevada Professional Land Surveyor No. 5095, monumented with an iron rod, 3/4 in. diam., firmly set, projecting 6 ins. above ground, with plastic cap mkd. RLS 5095, bears N. 33°30' W., 7.4 lks. dist., fence bears N.</p> <p>Not monumented.</p> <p>3.222 chs. Point for Angle Point No. 2. Point falls in Steamboat Ditch where it is impractical to establish a permanent monument.</p> <p>From this point, an offset position, determined by Richard W. Arden, Nevada Professional Land Surveyor No. 1643, monumented with an iron rod, 5/8 in. diam., firmly set, 1 in. below surface, with plastic cap mkd. RLS 1643, bears N. 35°00' W., 7.5 lks. dist., on the edge of the northern bank of Steamboat Ditch. Ditch bears N. 55° E. and S. 55° W.</p> <p>Not monumented.</p> <p>S. 57°32'40" W., 2.008 chs. Point for the SE cor. of Lot 36, identical to the SW cor. of Lot 37, Belli Ranch Estates, as recorded in Washoe County, Nevada, Subdivision Tract Map No. 2097B. Point falls in Steamboat Ditch where it is impractical to establish a permanent monument.</p> <p>From this point, an offset position, determined by Elmer J. Plummer, Nevada Professional Land Surveyor No. 5095, monumented with, an iron rod, 5/8 in. diam.,</p>
--------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

208

METES-AND-BOUNDS SURVEY IN SECTION 22,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>firmly set, flush with ground, with plastic cap mkd. RLS 5095, bears N. 36°30' W., 7.3 lks. dist., on the edge of the northern bank of Steamboat Ditch. Ditch bears N. 55° E. and S. 55° W.</p> <p>Not monumented.</p> <p>2.782 chs. Angle Point No. 3, determined by Richard W. Arden, Nevada Professional Land Surveyor No. 1643, monumented with an iron rod, 5/8 in. diam., loosely set leaning towards Steamboat Ditch, with plastic cap mkd. RLS 1643.</p> <p>Not remonumented.</p> <p>S. 44°57'30" W., 2.973 chs. Angle Point No. 4, determined by Richard W. Arden, Nevada Professional Land Surveyor No. 1643, monumented with an iron rod, 5/8 in. diam., loosely set leaning towards Steamboat Ditch, with plastic cap mkd. RLS 1643.</p> <p>Not remonumented.</p> <p>S. 30°08'20" W., 3.369 chs. Point for Angle Point No. 5. Point falls in Steamboat Ditch where it is impractical to establish a permanent monument.</p> <p>From this point, an offset position, determined by, Richard W. Arden, Nevada Professional Land Surveyor No. 1643, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 2 ins. above ground, with plastic cap mkd. RLS 1643, bears N. 22°50' W., 19.1 lks. dist., on the edge of the northern bank of Steamboat Ditch. Ditch bears N. 30° E. and N. 75° W. in curve.</p> <p>Not monumented.</p> <p>N. 75°34'10" W., 2.102 chs. The SE cor. of Lot 35, identical to the SW cor. of Lot 36, determined by Richard W. Arden, Nevada Professional Land Surveyor No. 1643, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 1 in. above ground at edge of Steamboat Ditch, with plastic cap mkd. RLS 1643.</p>
--------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

209

METES-AND-BOUNDS SURVEY IN SECTION 22,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Not remonumented.</p> <p>3.434 chs. Point for Angle Point No. 6. Point falls in Steamboat Ditch where it is impractical to establish a permanent monument.</p> <p>From this point, an offset position, determined by Richard W. Arden, Nevada Professional Land Surveyor No. 1643, monumented with an iron rod, 5/8 in. diam., firmly set, 4 ins. below surface, with plastic cap mkd. ARDEN RLS 1643, bears N. 23°10' E., 15.0 lks. dist., on the edge of the northern bank of Steamboat Ditch. Ditch bears S. 75° E. and N. 50° W. in curve.</p> <p>Not monumented.</p> <p>N. 48°18'20" W., 5.028 chs. Point for Angle Point No. 7. Point falls in Steamboat Ditch where it is impractical to establish a permanent monument.</p> <p>From this point, an offset position, determined by Richard W. Arden, Nevada Professional Land Surveyor No. 1643, monumented with an iron rod, 5/8 in. diam., firmly set, 1 in. below surface, with plastic cap mkd. ARDEN RLS 1643, bears N. 24°30' E., 7.4 lks. dist., on the edge of the northern bank of Steamboat Ditch. Ditch bears S. 50° E. and N. 60° W. in curve.</p> <p>Not monumented.</p> <p>N. 56°25'50" W., 1.941 chs. Angle Point No. 8, determined by Richard W. Arden, Nevada Professional Land Surveyor No. 1643, monumented with an iron rod, 5/8 in. diam., loosely set, leaning towards Steamboat Ditch, with plastic cap mkd. RLS 1643. Northern bank of ditch bears S. 60° E. and N. 70° W. in curve.</p> <p>Not remonumented.</p>
--------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

METES-AND-BOUNDS SURVEY IN SECTION 22,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

N. 69°39'00" W., 1.794 chs. Point for Angle Point No. 9, falls in Steamboat Ditch where it is impractical to establish a permanent monument. Private survey monument recovered found laying loose in ditch. Ditch bears S. 70° E. and S. 65° W. in curve.

Not monumented.

S. 63°17'50" W., 1.329 chs. Point for Angle Point No. 10, on the line bet. secs. 21 and 22, determined at record distance from a monument occupying the position of a cor. of lots 33 and 34, as shown on Subdivision Tract Map No. 2097B, as recorded in Washoe County, Nevada, hereinbefore described. Point falls in Steamboat Ditch where it is impractical to establish a permanent monument.

From this point, an offset position, determined by Elmer J. Plummer, Nevada Professional Land Surveyor No. 5095, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 2 ins. above ground, with melted plastic cap, matching other monuments set by Mr. Plummer, bears N. 1°20' E., 7.6 lks. dist., on the edge of the northern bank of Steamboat Ditch. Ditch bears N. 70° E. and S. 80° W. in curve.

From this same point, Angle Point No. 1, of the metes-and-bounds survey in sec. 21, bears N. 0°32'30" E., 0.209 chs. dist., hereinbefore described.

METES-AND-BOUNDS SURVEY IN SECTION 23,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA

The following metes-and-bounds survey represents portions of the boundaries of Parcels 46, 47 and 57, as shown on Land Division Map No. 43A, as recorded in Washoe County, Nevada, in 1979, and is based in part on Document No. 155423, Book 203 of Deeds, Pages 254 and 255, as recorded in Washoe County, Nevada. The Grant Boundary method of adjustment was used to restore the position of missing corners.


METES-AND-BOUNDS SURVEY IN SECTION 23,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

From Angle Point No. 1, on the line bet. secs. 14 and 23, determined by Peter G. Guisti, Nevada Professional Land Surveyor No. 335, monumented with an iron bar, 1/2 in. square, firmly set, projecting 1 in. above ground, as recorded in Washoe County Record of Survey Map No. 53.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 2 ft. base, to top, with brass cap mkd.



Deposit iron rod, 14 ins. long, inside stainless steel post.

Angle Point is located on E. side of level pasture, 1/2 lk. W. of fence, bears N. and S.

From this point, the Angle Point determined by Alan Means, Nevada Professional Land Surveyor No. 3573, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 1 in. above ground, bears N. 60° E., 1.2 lks. dist., with plastic cap mkd. MEANS RLS 3573.

From this same point, the W 1/16 sec. cor. of secs. 14 and 23, bears S. 89°55'30" W., 3.369 chs. dist., hereinbefore described.

S. 4°14'40" E., 5.752 chs.

Angle Point No. 2, determined by Peter G. Guisti, Nevada Professional Land Surveyor No. 335, monumented with an iron bar, 1/2 in. square, firmly set, projecting 1 in. above ground, as recorded in Washoe County, Nevada, Record of Survey Map No. 53.


212

METES-AND-BOUNDS SURVEY IN SECTION 23,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 2 ft. base, to top, with brass cap mkd.</p> <div data-bbox="1090 504 1247 640"> <p>S23 AP2</p> <p>1999</p> </div> <p>Deposit iron bar, 14 ins. long, inside stainless steel post.</p> <p>Angle Point is located on E. side of level pasture, 1/2 lk. W. of fence, bears N. and S.</p> <p>From this point, the Angle Point determined by Alan Means, Nevada Professional Land Surveyor No. 3573, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 2 ins. above ground, bears N. 60° E., 1.0 lks. dist., with plastic cap mkd. MEANS RLS 3573.</p> <p>S. 18°11'40" E., 2.992 chs. Angle Point No. 3, determined by Peter G. Guisti, Nevada Professional Land Surveyor No. 335, monumented with an iron bar, 1/2 in. square, firmly set, projecting 1 in. above ground, as recorded in Washoe County, Nevada, Record of Survey Map No. 53.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 2 ft. base, to top, with brass cap mkd.</p> <div data-bbox="1090 1617 1247 1753"> <p>S23 AP3</p> <p>1999</p> </div> <p>Deposit iron bar, 14 ins. long, inside stainless steel post.</p>
--------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

213

METES-AND-BOUNDS SURVEY IN SECTION 23,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Angle Point is located on E. side of level pasture, 1/2 lk. W. of fence, bears N. and S.</p> <p>From this point, an iron rod, 5/8 in. diam., firmly set, projecting 2 ins. above ground, bears N. 20° E., 1.9 lks. dist., with melted plastic cap and matches unrecorded monuments set by Alan Means, RLS 3573 along fence line to the N., some with readable caps mkd. RLS 3573.</p> <p>S. 37°50'10" E., 5.839 chs. Point for Angle Point No. 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;">  <p>S23 ——— AP4</p> <p>1999</p> </div> <p>Angle Point is located on NW slope in ditch access road fill.</p> <p>From this point, an iron rod, 5/8 in. diam., firmly set, 2 ins. below surface, no cap, bears N. 30° E., 2.1 lks. dist., and matches unrecorded monuments set by Alan Means, RLS 3573 along fence line to the N., some with readable caps mkd. RLS 3573.</p> <p>S. 41°42'00" W., 0.863 chs. Point for Angle Point No. 5.</p> <p>Not monumented.</p> <p>S. 74°03'00" W., 2.008 chs. Point for Angle Point No. 6.</p> <p>Not monumented.</p> <p>N. 82°07'40" W., 1.831 chs. Point for Angle Point No. 7.</p> <p>Not monumented.</p> <p>S. 83°46'20" W., 1.423 chs. Point for Angle Point No. 8.</p> <p>Not monumented.</p> <p>S. 51°19'40" W., 1.430 chs. Point for Angle Point No. 9.</p> <p>Not monumented.</p>

METES-AND-BOUNDS SURVEY IN SECTION 23,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>S. 82°58'40" W., 1.452 chs. Point for Angle Point No. 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S23 / AP10 1999</p> <p>From this point, an iron rod, 5/8 in. diam., 18 ins. long, laying loose, no cap, bears N. 50° E., 1.3 lks. dist., and matches unrecorded monuments set by Alan Means, RLS 3573 along fence line to the NE., some with readable caps mkd. RLS 3573.</p> <p>From this same point, the W 1/16 sec. cor. of secs. 14 and 23, bears N. 0°04'40" W., 15.357 chs. dist., hereinbefore described.</p> <p>S. 4°36'30" W., 4.517 chs. Angle Point No. 11, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 1 in. above ground, with melted plastic cap and matches unrecorded monuments set by Alan Means, RLS 3573, as recorded in Washoe County, Land Map No. 43, with readable caps mkd. RLS 3573.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S23 / AP11 1999</p> <p>Deposit iron rod, 14 ins. long, inside stainless steel post.</p> <p>Angle Point is located on open rocky N. slope.</p>
--------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

215

METES-AND-BOUNDS SURVEY IN SECTION 23,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

S. $89^{\circ}34'20''$ W., 0.087 chs. Intersect the N. and S. center line of the NW1/4 sec. 23, from which the NW 1/16 sec. cor. of sec. 23, bears S. $1^{\circ}14'10''$ W., 0.011 chs. dist., hereinbefore described.

19.835 chs. Angle Point No. 12, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 2 ins. above ground, with melted plastic cap and matches unrecorded monuments set by Alan Means, RLS 3573, as recorded in Washoe County, Land Map No. 43, with readable caps mkd. RLS 3573.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

S23

AP12

1999

Deposit iron rod, 16 ins. long, along S. side of stainless steel post.

Angle Point is located on steep rocky N. slope.

S. $1^{\circ}49'30''$ W., 0.021 chs. Intersect the E. and W. center line of sec. 23, from which the N 1/16 sec. cor. of secs. 22 and 23 bears S. $89^{\circ}32'40''$ W., 0.178 chs. dist., hereinbefore described.

20.046 chs. The 1/4 sec. cor. of secs. 22 and 23, hereinbefore described.

METES-AND-BOUNDS SURVEY IN SECTION 24,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA

The following metes-and-bounds survey represents portions of the boundaries of certain Parcels, as shown on Land Map No. 43B, recorded in Washoe County, Nevada, in 1979, and described in document No. 781361, as recorded in Washoe County, Nevada, Book 1717 of Deeds, Pages 404-410.

216

METES-AND-BOUNDS SURVEY IN SECTION 24,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

From the point for Angle Point No. 1, determined at intersection of the north line of Parcel 52 with the line bet. secs. 19 and 24 on the E. bdy. of the Tp.

Not monumented.

Angle Point is located on steep NNW slope on open burn area.

From this point, the NE corner of Parcel 52, monumented with an iron rod, 5/8 in. diam., firmly set, 8 in. below ground, with cap mkd. MEANS RLS 3573, as recorded in Washoe County, Nevada, Land Map No. 43B, bears N. 78°26'20" E., 1.110 chs. dist.

From this same point, the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of Tp., bears N. 0°25'30" W., 22.932 chs. dist.

S. 78°26'20" W., 26.323 chs.

Angle Point No. 2, determined by Alan Means, Nevada Professional Land Surveyor No. 3573, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 2 ins. above ground, with melted plastic cap matching other monuments set by Mr. Means, as recorded in Washoe County, Nevada, Land Map No. 43B.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 2 ft. base, to top, with brass cap mkd.



1999

Deposit iron rod, 18 ins. long, inside stainless steel post.

Angle Point is located on open WNW slope on burn area.

217

METES-AND-BOUNDS SURVEY IN SECTION 24,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From this point, an iron rod, 5/8 in. diam., firmly set, projecting 1 in. above ground, bears N. 5°00' E., 21.1 lks. dist., with melted yellow cap, and matches unrecorded monuments set by Alan Means, RLS 3573 along fence line in sec. 23, some with readable caps mkd. RLS 3573.</p>
<p>N. 38°43'00" W., 13.904 chs.</p>	<p>Angle Point No. 3, on the N. and S. center line of sec. 24, determined by Alan Means, Nevada Professional Land Surveyor No. 3573, monumented with an iron rod, 5/8 in. diam., firmly set, flush with ground, with plastic cap mkd. MEANS RLS 3573, as recorded in Washoe County, Nevada, Land Map No. 43B.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 2 ft. base, to top, with brass cap mkd.</p> <div data-bbox="1148 1056 1240 1161"> </div> <p>1999</p> <p>Deposit iron rod, 16 ins. long, inside stainless steel post.</p> <p>Angle Point is located on SW slope on open burn area.</p> <p>From this point, the 1/4 sec. cor. of secs. 13 and 24, bears N. 1°03'50" E., 17.003 chs. dist., hereinbefore described.</p>
<p>S. 1°03'50" W., 23.840 chs.</p> <p>25.728 chs.</p>	<p>The center 1/4 sec. cor. of sec. 24, hereinbefore described.</p> <p>Angle Point No. 4, determined by Alan Means, Nevada Professional Land Surveyor No. 3573, on the N. and S. center line of sec. 24, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 2 ins. above ground, with melted plastic cap, matches other monuments set by Alan Means, as recorded in Washoe County, Nevada, Land Map No. 43B.</p>

218

METES-AND-BOUNDS SURVEY IN SECTION 24,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 2 ft. base, to top, with brass cap mkd.
	<div><div>S24</div><div>AP4</div></div>
	1999
	Deposit iron rod, 18 ins. long, inside stainless steel post.
	Angle Point is located on a gradual NE slope on open grass covered burn area.
N. 86°24'10" W., 19.970 chs.	Angle Point No. 5, determined by Alan Means, Nevada Professional Land Surveyor No. 3573, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 1 in. above ground, with plastic cap mkd. MEANS RLS 3573, as recorded in Washoe County, Nevada, Land Map No. 43B.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 2 ft. base, to top, with brass cap mkd.
	<div><div>S24</div><div>AP5</div></div>
	1999
	Deposit iron rod, 19 ins. long, inside stainless steel post.
	Angle Point is located on a NW slope with sage and willows.
N. 1°00'20" E., 0.945 chs.	Intersect the E. and W. center line of sec. 24, from which the center west 1/16 sec. cor. of sec. 24, bears N. 89°06'30" W., 0.003 chs. dist., hereinbefore described.
41.268 chs.	The W 1/16 sec. cor. of secs. 13 and 24, hereinbefore described.

GENERAL DESCRIPTION,
T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	GENERAL DESCRIPTION
	<p>This resurvey was made to meet the management needs of the Toiyabe National Forest and is situated in southwestern Washoe County, Nevada and southeastern Sierra County, California. The resurvey is a portion of the township in California and Nevada to the east of the old California State Line which is approximately three quarters of a mile westerly of the present State Line. The town of Verdi, Nevada is located in section 17 and the western city limits of Reno, Nevada extend into section 24. Interstate Highway 80 follows the Truckee River from section 31 through the center of the township to its eastern boundary. The present California-Nevada State Line passes along the western town limits of Verdi and through sections 6, 7, 18, 19, 30, and 31. Dog Valley Road crosses the northwestern portion of the township from Verdi. Access is by unpaved secondary roads off of Interstate 80 and Dog Valley Road. The lower slopes of Peavine Peak are to the north of Interstate 80. The south half and western portions of this township are mountainous with elevations ranging from 4700 feet at the Truckee River to 7600 feet below Verdi Peak. Land use is primarily limited to recreational uses such as four wheel drive vehicles, motorbikes, ATV's, bicycles and hiking. A portion of the Mt. Rose Wilderness lies in the southeastern portion of the township. Timber has been harvested in the past. Recent forest and brush fires have burned portions of the foothills.</p>

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANT

Mark G. Petrosine	Surveying Technician
Todd L. Burrill	Survey Aid
Susan C. Sarantopoulos	Survey Aid
Ryan L. Ming	Survey Aid
Jay W. Foley	Survey Aid
Nick R. Caple	Survey Aid
Eric Brower	Survey Aid
Joe R. Sullivan	Survey Aid

CERTIFICATE OF SURVEY

I, David L. Dukleth, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of August 22, 1997, I have dependently resurveyed portions of the California-Nevada State Line, from Mile Post 168 to Mile Post 171, and from Mile Post 173 to Mile Post 175, portions of the old California-Nevada State Line, portions of the south, east, and north boundaries, a portion of the subdivisional lines, subdivided sections 6, 7, 10, 14, 22, 23, 24, 29, 30, 31, and 32, and executed metes-and-bounds surveys in certain sections, Township 19 North, Range 18 East, of the Mount Diablo Meridian, in the States of Nevada and California, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

July 15, 2004

(Date)

David L. Dukleth

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada
Sacramento, California

The foregoing field notes of the dependent resurvey of portions of the California-Nevada State Line, from Mile Post 168 to Mile Post 171, and from Mile Post 173 to Mile Post 175, portions of the old California-Nevada State Line, portions of the south, east, and north boundaries, a portion of the subdivisional lines, the subdivision of sections 6, 7, 10, 14, 22, 23, 24, 29, 30, 31, and 32, and metes-and-bounds surveys in certain sections, Township 19 North, Range 18 East, of the Mount Diablo Meridian, in the States of Nevada and California, executed by David L. Dukleth, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

August 5, 2004

(Date)

Acting

David L. Clark
(Chief Cadastral Surveyor, Nevada)

August 5, 2004

(Date)

James G. Purkey
(Chief Cadastral Surveyor, California)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 19 N., R. 18 E., M.D.M., Nevada, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor, Nevada)~~

~~(Date)~~

~~(Chief Cadastral Surveyor, California)~~