

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

OF THE

CORRECTIVE DEPENDENT RESURVEY AND DEPENDENT RESURVEY

OF

A PORTION OF THE SOUTH BOUNDARY,

THE

CORRECTIVE DEPENDENT RESURVEY AND DEPENDENT RESURVEY

OF

A PORTION OF THE SUBDIVISIONAL LINES,

THE

DEPENDENT RESURVEY

OF

A PORTION OF THE SUBDIVISION OF SECTION 34,

THE

FURTHER SUBDIVISION OF SECTION 34,

THE

METES-AND-BOUNDS SURVEY OF TRACTS 37, 38, 39, AND 40,

AND THE

METES-AND-BOUNDS SURVEY OF LOT 7 IN SECTION 34,

TOWNSHIP 19 NORTH, RANGE 20 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATE OF NEVADA

EXECUTED BY

David D. Morlan, Cadastral Surveyor

Under Special Instructions dated January 14, 1994, approved
January 14, 1994, and Supplemental Special Instructions dated

April 22, 2002, approved April 22, 2002,

which provided for the surveys included under Group No. 741,

and Assignment Instructions dated March 28, 1994.

Survey commenced March 29, 1994

Survey completed April 25, 2002

INDEX DIAGRAM

TOWNSHIP 19 NORTH, RANGE 20 EAST

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	<div style="text-align: right;">6 6 5 4 2</div> 34	35	36

Dependent Resurvey of a Portion of the Subdivision of Section 34..pp	8 - 10
Further Subdivision of Section 34	pp 11 - 16
Metes-and-Bounds Survey of Tract 37.....	pp 16 - 18
Metes-and-Bounds Survey of Tract 38.....	pp 18 - 20
Metes-and-Bounds Survey of Tract 39.....	pp 20 - 21
Metes-and-Bounds Survey of Tract 40.....	pp 21 - 22
Metes-and-Bounds Survey of Lot 7 in Section 34.....	pp 23 - 24

TOWNSHIP 19 NORTH, RANGE 20 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The following field notes are those of the corrective dependent resurvey and dependent resurvey of a portion of the south boundary, the corrective dependent resurvey and dependent resurvey of a portion of the subdivisional lines, the dependent resurvey of a portion of the subdivision of section 34, the further subdivision of section 34, the metes-and-bounds survey of Tracts 37, 38, 39, and 40, and the metes-and-bounds survey of Lot 7 in section 34, Township 19 North, Range 20 East, Mount Diablo Meridian, Nevada.

The south boundary was surveyed by J. S. Lawson, U. S. Deputy Surveyor in 1861 under Contract "B". The subdivisional lines were surveyed by U. S. Deputy Surveyors E. H. Dyer in 1863 under Contract "D", and K. W. Taylor in 1882 under Contract No. 136. J. W. Hardison Cadastral Engineer and H. T. Brown Cadastral Surveyor, dependently resurveyed a portion of the south boundary, a portion of the subdivisional lines, and partially subdivided section 34 in 1956 under Group No. 366. Other surveys remote to the area are not included.

Professional Land Surveyor Harry R. Ericson, in a letter dated August 21, 1991, reported double corners at the cor. of secs. 2, 3, 34 and 35, and the 1/4 sec. cor. of secs. 3 and 34, both on the S. bdy. of the Tp. The Chief, Branch of Cadastral Survey, issued a Preliminary Report of Investigation dated January 10, 1994, verifying the existence of the original corner of secs. 2, 3, 34 and 35, at a different location than determined by Hardison in 1956. Existence of an original corner at a different location than the 1/4 sec. cor. of secs. 3 and 34, determined in 1956, could not be verified. Additional review of the evidence, documented by Memorandum dated May 19, 1994, resulted in determination that the original monument for the southeast corner of section 34 shall control patents issued based on the original survey, and the location of the 1956 corner shall control patents issued after the acceptance of the 1956 resurvey. The memorandum further determined the 1956 south 1/4 cor. of sec. 34 will remain as the official corner and have all the authority and significance of an identified original corner. The corrective dependent resurvey portions of this survey reflect these determinations.

Before restoring the corners, the lines of the original surveys were retraced and diligent search made for any evidence of the original corners and other calls of the original field note record.

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, Special Instructions dated January 14, 1994, and Supplemental Special Instructions dated April 22, 2002.

The direction of the lines of this survey were determined by azimuth taken from B.L.M. G.P.S. Station "GP7", located in section 32 of this township, and National Geodetic Survey control (formerly U.S.C. & G.S. triangulation) station "TRUCKEE", located near the section line between secs. 2 and 11, T. 18 N., R. 20 E.

TOWNSHIP 19 NORTH, RANGE 20 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The directions of the lines were carried forward by sustained angulation.

The vertical angles of measurements made on the slope were ascertained with a total station, in good adjustment; the horizontal equivalents only are entered in the field notes.

The geographic position of the 1/4 section corner of sections 3 and 34, on the S. bdy. of the Tp., is at latitude $39^{\circ}27'45.14''$ N. and longitude $119^{\circ}43'24.17''$ W., (NAD 83), as determined by a direct tie to National Geodetic Survey control (formerly U.S.C. & G.S. triangulation) station "TRUCKEE".

The mean magnetic declination was found to be $15 \frac{3}{4}^{\circ}$ E., as determined from U. S. Geological Survey program "Geomagnetic Fields" using Field Model USCON95.

CORRECTIVE DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 19 N., R. 20 E., MOUNT DABLO MERIDIAN, NEVADA

Reestablishment of a Portion of the Survey Executed by
J. S. Lawson, U. S. Deputy Surveyor, in 1861, and
Correction of a Portion of the Dependent Resurvey Executed by
Cadastral Engineer J. W. Hardison and Cadastral Surveyor
H. T. Brown, in 1956.

Beginning at the original 1861 sec. cor. of secs. 2, 3, 34 and 35, monumented with a stone, 20x14x7 ins., plainly mkd. with 2 notches on the E. edge and 4 notches on the W. edge, lying on a mound of stone.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to solid rock over a plastic encased magnet, and in a mound of stone, 3 ft. base to top, with brass cap mkd.

T19N	R20E
S 34	S 35
S 3	S 2
T18N	

1994

Deposit the original cornerstone alongside the stainless steel post.

From this corner, the cor. of secs. 2, 3, 34 and 35, erroneously determined by Hardison and Brown in 1956, monumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the dependent resurvey of the south boundary of T. 19 N., R. 20 E., executed under Group No. 366, bears N. $43^{\circ}50'10''$ E., 4.538 chs. dist. Add the marks AM 1994 and bury the iron post in the mound of stone.

N. $86^{\circ}13'30''$ W., bet. secs. 3 and 34.

CORRECTIVE DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 19 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Over rocky mountainous land, through scattered sagebrush and native grass.
16.682	Angle Point No. 6, Lot 7, hereinafter described.
18.399	Point for the E 1/16 sec. cor. of secs. 3 and 34, identical with Angle Point No. 5, Lot 7. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic encased magnet, and in a collar of stone, with brass cap mkd. <div style="text-align: center;"> S 34 E 1/16 S 3 2002 </div>
25.60	Enter gravel pit.
32.20	Leave gravel pit.
36.798	The 1/4 sec. cor. of secs. 3 and 34, identical with Angle Point No. 4, Lot 7, monumented with an iron post, 2 1/2 ins. diam., firmly set projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the south boundary of T. 19 N., R. 20 E., executed under Group No. 366. Add the marks 1995 to brass cap. <div style="text-align: center;"> Note: The rock ring for the 1/4 sec. cor. of secs. 3 and 34, shown on Washoe County Record of Survey No. 2146, File No. 1374274, filed by Harry R. Ericson, Nevada Professional Land Surveyor No. 1797, was searched for but not found. The rock ring position was not utilized during this survey. </div> <p>From this corner, a rebar, 5/8 in. diam., with yellow plastic cap mkd. RLS 1797, firmly set flush with the ground 0.007 chs. W. of a NW. and SE. fence, established by Harry R. Ericson, Nevada Professional Land Surveyor No. 1797, and recorded in Washoe County, Nevada, Survey Map No. 2146, File No. 1374274, bears S. 60°32'50" W., 4.339 chs. dist.</p> <p>From this same corner, a rebar, 5/8 in. diam., with yellow plastic cap mkd. RLS 2519, firmly set flush with the ground, established by Alan B. Campbell, Nevada Professional Land Surveyor No. 2519, as shown on an unrecorded survey plat for Sierra Pacific Power Company, Section 3, T. 18 N., R. 20 E., bears S. 82°09'20" E., 16.929 chs. dist.</p> <p>From this same corner, a rebar, 5/8 in. diam., with yellow plastic cap mkd. RLS 1797, firmly set projecting 1 in. above the ground, established by Harry R. Ericson, Nevada Professional Land Surveyor No. 1797, and recorded in Washoe County, Nevada, Survey Map No. 2146, File No. 1374274, bears S. 82°23'40" E., 17.268 chs. dist.</p>

CORRECTIVE DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 19 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From this same corner, National Geodetic Survey control (formerly U.S.C. & G.S. triangulation) station "TRUCKEE" bears S. 37°14'00" E., 102.536 chs. dist., monumented with a standard brass cap, 3 1/2 ins. diam., firmly cemented into a drill hole in a rock outcrop, with top mkd. TRUCKEE 1946 and a triangle.</p> <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY, T. 19 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of a Portion of the Survey Executed by J. S. Lawson, U. S. Deputy Surveyor, in 1861, and the Dependent Resurvey Executed by Cadastral Engineer J. W. Hardison and Cadastral Surveyor H. T. Brown, in 1956.</p> <hr/> <p>S. 87°23'50" W., beginning new measurement.</p> <p>Over nearly level land.</p> <p>1.90 Power line, bears northerly and southerly.</p> <p>4.20 Improved gravel road, bears NW. and SE.</p> <p>5.20 Fence, bears NW. and SE.</p> <p>5.80 Flick ditch, 30 lks. wide, 4 ft. deep, course NW.</p> <p>15.60 Steamboat Creek, 10 lks. wide, 2 ft. deep, course N. 20° W.</p> <p>21.589 Point for the W 1/16 sec. cor. of secs. 3 and 34.</p> <p>POINT NOT MONUMENTED</p> <p>25.10 Ditch, 30 lks. wide, 1 ft. deep, course NNE.</p> <p>26.30 Fence, at base of hills, bears irregularly N. and S.</p> <p>39.20 Ridge, bears N. and S.</p> <p>43.178 The cor. of secs. 3, 4, 33 and 34, monumented with an iron pipe, 3/4 in. diam., 31 ins. long, firmly set in a mound of stone; there is no remaining evidence of the marked stone recovered in the 1956 dependent resurvey. This iron pipe is locally recognized as the position of the original corner, and has been utilized by private surveyors (Washoe County Records Survey Map No. 2146, File No. 1374274, and Survey Map No. 2492, File No. 1617007).</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to solid rock over a plastic encased magnet, and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p>
--------	--

287

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 19 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

T19N R20E
S 33 | S 34
S 4 | S 3
T18N

1994

Reset the iron pipe alongside the stainless steel post.

CORRECTIVE DEPENDENT RESURVEY OF
A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of a Portion of the Survey Executed by
E. H. Dyer, U. S. Deputy Surveyor, in 1863, and
Correction of a Portion of the Dependent Resurvey Executed by
Cadastral Engineer J. W. Hardison and Cadastral Surveyor
H. T. Brown, in 1956.

From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the
Tp., hereinbefore described.

N. 0°47'20" W., bet. secs. 34 and 35.

Over rocky mountainous land, through scattered sagebrush and
native grass.

14.20 Trail road in ravine, bears NE. and SW.

19.981 Point for the S 1/16 sec. cor. of secs. 34 and 35.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
8 ins. in the ground to solid rock over a plastic encased magnet,
and in a mound of stone, 3 ft. base to top, with brass cap mkd.

S 1/16
S 34 | S 35

1994

From this corner, the S 1/16 sec. cor. of secs. 34 and 35,
erroneously determined by Hardison and Brown in 1956, monumented
with an iron post, 2 1/2 ins. diam., firmly set in a mound of
stone, with brass cap mkd. as described in the field notes of the
dependent resurvey of the subdivisional lines of T. 19 N.,
R. 20 E., executed under Group No. 366, bears N. 44°03'00" E.,
2.261 chs. dist. Add the marks AM 1994 and bury the iron post in
the mound of stone.

26.30 Spur, slopes NW.

39.962 The 1/4 sec. cor. of secs. 34 and 35, monumented with an iron
post, 2 1/2 ins. diam., firmly set in a mound of stone, with
brass cap mkd. as described in the field notes of the dependent
resurvey of the subdivisional lines of T. 19 N., R. 20 E.,
executed under Group No. 366.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Reestablishment of a Portion of the Survey Executed by E. H. Dyer, U. S. Deputy Surveyor, in 1863, and a Portion of the Dependent Resurvey Executed by Cadastral Engineer J. W. Hardison and Cadastral Surveyor H. T. Brown, in 1956.</p> <hr/> <p>From the N 1/16 sec. cor. of secs. 34 and 35, monumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 19 N., R. 20 E., executed under Group No. 366.</p> <p>N. 1°36'50" W., bet. secs. 34 and 35.</p> <p>Over steep rolling land, through scattered sagebrush and native grass.</p>
6.70	Base of hill.
9.648	<p>Point for the N-N 1/64 sec. cor. of secs. 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to solid rock over a plastic encased magnet, and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">N-N 1/64 S 34 S 35</p> <p style="text-align: center;">1994</p>
14.472	<p>The N-N-N 1/256 sec. cor. of secs. 34 and 35, determined by Elmer J. Plummer, Nevada Professional Land Surveyor No. 5095, monumented with a rebar, 5/8 in. diam., firmly set, projecting 4 ins. above the ground, with yellow plastic cap mkd. RLS 5095, as recorded in Washoe County, Nevada, Survey Map No. 2157, File No. 1383707. This rebar is accepted as a careful and faithful determination of the position of the corner.</p> <hr/> <p>N. 1°36'50" W., beginning new measurement.</p>
4.824	<p>The cor. of secs. 26, 27, 34 and 35, monumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 19 N., R. 20 E., executed under Group No. 366.</p> <hr/> <p>N. 89°38'20" W., bet. secs. 27 and 34.</p> <p>Over gently rolling land, through scattered sagebrush and native grass.</p>
17.012	<p>The 1/1024 sec. cor. of secs. 27 and 34, determined by persons unknown, monumented with a metal concrete stake, 3/4 in. diam., 30 ins. long, firmly set projecting 6 ins. above the ground, and over a rebar 5/8 in. diam., 18 ins. long, firmly set 24 ins. below the ground. This is accepted as a careful and faithful determination of the position of the corner.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic encased magnet, with brass cap mkd.</p> <p style="text-align: center;">1/1024</p> <p style="text-align: center;">1995</p> <p>Reset the stake and rebar, and set a steel fence post, 5 1/2 ft. long, alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°38'20" W., beginning new measurement.</p> <p>2.430 Point for the E 1/16 sec. cor. of secs. 27 and 34, at proportionate distance; there is no remaining evidence of the 1956 iron post.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>S 27</p> <p>E 1/16 </p> <p>S 34</p> </div> <p style="text-align: center;">2002</p> <p>Set a fiberglass post, 4 ft. long, alongside the stainless steel post.</p> <p>4.860 Point for the 1/1024 sec. cor. of secs. 27 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic encased magnet, with brass cap mkd.</p> <p style="text-align: center;">1/1024</p> <p style="text-align: center;">1995</p> <p>Set a 1 in. angle iron post, 24 ins. long, alongside the stainless steel post.</p> <p>7.290 Point for the E-W-E 1/256 sec. cor. of secs. 27 and 34, falls in an improved gravel road, bearing north and south.</p> <p>Set a nail, 8 ins. long, 1/2 in. diam., 4 ins. below the surface of the road.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 20 ins. in the ground to solid rock over a plastic encased magnet, and in a mound of stone, 3 ft. base to top, for a reference monument, bears S. 83°04'30" W., 24.3 ft. dist., with brass cap mkd. RM E-W-E 1/256 24.3 FT TO COR S34 1995 and an arrow pointing to the true point.</p>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 18 ins. in the ground to solid rock over a plastic encased magnet, and in a mound of stone, 3 ft. base to top, for a reference monument, bears S. 39°18'40" W., 45.1 ft. dist., with brass cap mkd. XRM 45.1 FT TO COR 1995 and an arrow pointing to the true point.</p>
17.011	<p>Point for the W-W-E 1/256 sec. cor. of secs. 27 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 27 W-W-E 1/256 S 34</p> <p style="text-align: center;">1995</p> <p>Set a steel fence post, 5 1/2 ft. long, alongside the stainless steel post.</p>
21.872	<p>The 1/4 sec. cor. of secs. 27 and 34, monumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 19 N., R. 20 E., executed under Group No. 366.</p> <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISION OF SECTION 34, T. 19 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of a Portion of the Survey Executed by Cadastral Engineer J. W. Hardison and Cadastral Surveyor H. T. Brown, in 1956.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 3 and 34, on the S. bdy. of the Tp.</p> <p>N. 2°50'50" W., on the N-S center line of sec. 34.</p> <p>Over gently rolling land, through scattered sagebrush and native grass.</p>
18.826	<p>The center S 1/16 sec. cor. of sec. 34, monumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the subdivision of section 34, T. 19 N., R. 20 E., executed under Group No. 366.</p> <hr/> <p>N. 2°53'10" W., beginning new measurement.</p> <p>Over gently rolling land, enter gravel pit.</p>
18.817	<p>The center 1/4 sec. cor. of sec. 34, monumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the subdivision of section 34, T. 19 N., R. 20 E., executed under Group No. 366.</p> <hr/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISION OF SECTION 34,
T. 19 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>N. 2°51'50" W., beginning new measurement.</p> <p>Over gently rolling land, leave gravel pit.</p>
0.20	Trail road, bears E. and W.
5.60	Graded road, bears NE. and SW.
8.90	Trail road, bears E. and W.
9.688	<p>The center S-N 1/64 sec. cor. of sec. 34, determined by persons unknown, monumented with a metal stake, 1 in. diam., 18 ins. long, firmly set in a mound of stone. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to solid rock over a plastic encased magnet, and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} C \\ S-N \frac{1}{64} S \ 34 \\ C \end{array}$ <p>1994</p> </div> <p>Reset the stake inside the stainless steel post.</p> <hr/> <p>N. 2°51'50" W., beginning new measurement.</p> <p>Over gently rolling land.</p>
9.678	<p>The center N 1/16 sec. cor. of sec. 34, monumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the subdivision of section 34, T. 19 N., R. 20 E., executed under Group No. 366.</p> <hr/> <p>N. 2°51'40" W., beginning new measurement.</p> <p>Over gently rolling land, ascend rocky hillside.</p>
9.690	<p>Point for the center N-N 1/64 sec. cor. of sec. 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to solid rock over a plastic encased magnet, and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} C \\ N-N \frac{1}{64} S \ 34 \\ C \end{array}$ <p>1994</p> </div> <p>Set a fiberglass post, 4 ft. long, alongside the stainless steel post.</p>
11.30	Spur, slopes E., descend.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISION OF SECTION 34,
T. 19 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
19.10	Abandoned fence, bears E. and W.
19.380	The 1/4 sec. cor. of secs. 27 and 34.
	<hr/>
	From the 1/4 sec. cor. of secs. 34 and 35.
	N. 89°54'30" W., on the E-W center line of sec. 34.
	Over mountainous land, through scattered sagebrush and native grass.
14.293	The center W-E-E 1/256 sec. cor. of sec. 34, determined by persons unknown, monumented with a rebar, 1/2 in. diam., 18 ins. long, firmly set in a mound of stone. This is accepted as a careful and faithful determination of the position of the corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to solid rock over a plastic encased magnet, and in a mound of stone, 3 ft. base to top, with brass cap mkd.
	<div style="text-align: center;"> W-E-E 1/256 C ————— C S 34 1994 </div>
	Reset the rebar and set a fiberglass post, 4 ft. long, alongside the stainless steel post.
	<hr/>
	N. 89°54'30" W., beginning new measurement.
	Over gently rolling land.
2.00	Ravine, drains SW.
4.748	The center E 1/16 sec. cor. of sec. 34, monumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the subdivision of section 34, T. 19 N., R. 20 E., executed under Group No. 366.
	<hr/>
	N. 89°54'40" W., beginning new measurement.
	Over gently rolling land.
5.20	Enter gravel pit.
17.10	Leave gravel pit.
19.000	The center 1/4 sec. cor. of sec. 34.
	<hr/>

FURTHER SUBDIVISION OF SECTION 34,
T. 19 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the center E 1/16 sec. cor. of sec. 34.</p> <p>N. 2°12'50" W., on the N-S center line of the NE1/4 of sec. 34.</p> <p>Over gently rolling land, through scattered sagebrush and native grass.</p> <p>19.296 Point for the NE 1/16 sec. cor. of sec. 34, at intersection with the E-W center line of the NE1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to solid rock over a plastic encased magnet, and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">S 34 NE 1/16 1994</p> <p>24.130 Point for the C-S-N-NE 1/256 sec. cor. of sec. 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">S 34 C-S-N-NE 1/256 2002</p> <p>33.798 Point for the C-N-N-NE 1/256 sec. cor. of sec. 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">S 34 C-N-N-NE 1/256 2002</p> <p>38.632 The E 1/16 sec. cor. of secs. 27 and 34.</p> <hr/> <p>From the N 1/16 sec. cor. of secs. 34 and 35.</p> <p>N. 89°43'20" W., on the E-W center line of the NE1/4 of sec. 34.</p> <p>Over mountainous land, through scattered sagebrush and native grass.</p> <p>9.623 The C-E-NE 1/64 sec. cor. of sec. 34, determined by Loreto M. Manuel, Nevada Professional Land Surveyor No. 4867, monumented with a rebar 5/8 in. diam., 25 ins. long, firmly set projecting 6 ins. above the ground, with yellow plastic cap mkd. RLS 4867, as recorded in Washoe County, Nevada, Survey Map No. 1687, File No. 939855. This rebar is accepted as a careful and faithful determination of the position of the corner.</p>
--------	--

FURTHER SUBDIVISION OF SECTION 34,
T. 19 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to solid rock over a plastic encased magnet, and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">S 34 C-E-NE 1/64 1994</p> <p>Reset the rebar inside the stainless steel post.</p> <hr/> <p>N. 89°44'00" W., beginning new measurement.</p> <p>Over mountainous land.</p> <p>4.805 The C-W-E-NE 1/256 sec. cor. of sec. 34, determined by Loreto M. Manuel, Nevada Professional Land Surveyor No. 4867, monumented with a rebar 5/8 in. diam., 25 ins. long, firmly set projecting 6 ins. above the ground, with yellow plastic cap mkd. RLS 4867, as recorded in Washoe County, Nevada, Survey Map No. 1697, File No. 939855. This rebar is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to solid rock over a plastic encased magnet, and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">S 34 C-W-E-NE 1/256 1994</p> <p>Reset the rebar inside the stainless steel post.</p> <hr/> <p>N. 89°44'00" W., beginning new measurement.</p> <p>4.812 The NE 1/16 sec. cor. of sec. 34.</p> <p>12.021 Point for the 1/1024 sec. cor. of sec. 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to solid rock over a plastic encased magnet, and in a mound of stone, 2 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">S34 1/1024 1994</p> <p>14.00 Trail road, bears NE. and SW.</p>
--------	--

295

FURTHER SUBDIVISION OF SECTION 34,
T. 19 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
15.00	Trail road, bears NE. and SW.
16.827	Point for the 1/1024 sec. cor. of sec. 34.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to solid rock over a plastic encased magnet, and in a mound of stone, 2 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">S34 1/1024 1994</p>
24.036	The center N 1/16 sec. cor. of sec. 34.
	<hr/> <p>From the SW-NE-NE 1/256 sec. cor. of sec. 34, determined by persons unknown, monumented with a wooden hub, 2 ins. square, 8 ins. long, firmly set projecting 2 ins. above the ground in a collar of stone. This wooden hub is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground to solid rock over a plastic encased magnet, and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">S 34 SW-NE-NE 1/256 1994</p> <p>Reset the wooden hub alongside the stainless steel post.</p> <p>N. 2°03'50" W., on the N-S center line of the SW1/4 of the NE1/4 of the NE1/4 of sec. 34.</p> <p>Over gently rolling land, through scattered sagebrush and native grass.</p>
4.836	<p>The C-W-NE-NE 1/256 sec. cor. of sec. 34, determined by Loreto M. Manuel, Nevada Professional Land Surveyor No. 4867, monumented with a rebar 5/8 in. diam., 21 ins. long, firmly set projecting 5 ins. above the ground, with yellow plastic cap mkd. RLS 4867, as recorded in Washoe County, Nevada, Survey Map No. 1687, File No. 939855. This rebar is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to solid rock over a plastic encased magnet, and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p>

FURTHER SUBDIVISION OF SECTION 34,
T. 19 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">S 34 C-W-NE-NE 1/256</p> <p style="text-align: center;">1995</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 15 ins. in the ground to solid rock over a plastic encased magnet, and in a mound of stone, 2 1/2 ft. base to top, for a reference monument, bears N. 13°34'40" E., 80.0 ft. dist., with brass cap mkd. RM C-W-NE-NE 1/256 80.0 FT TO COR S34 1998 and an arrow pointing to the corner.</p> <p>A granite boulder, 2 ft. and 4 ins. x 2 ft., projecting 10 ins. above ground, bears N. 54°12'20" E., 197.7 lks. dist., mkd. BO X on south-westerly face. The X is approximately 4 1/2 ins. from high point(top).</p> <p>Reset the rebar inside the stainless steel post.</p> <hr/> <p>From the SW-NE-NE 1/256 sec. cor. of sec. 34.</p> <p>N. 89°41'30" W., on the E-W center line of the SW1/4 of the NE1/4 of the NE1/4 of sec. 34.</p> <p>Over gently rolling land, through scattered sagebrush and native grass.</p> <p>4.821 The C-S-N-NE 1/256 sec. cor. of sec. 34.</p> <hr/> <p>From the C-W-NE-NE 1/256 sec. cor. of sec. 34.</p> <p>N. 2°02'40" W., on the N-S center line of the NW1/4 of the NE1/4 of the NE1/4 of sec. 34.</p> <p>Over gently rolling land, through scattered sagebrush and native grass.</p> <p>4.836 The NW-NE-NE 1/256 sec. cor. of sec. 34, determined by persons unknown, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set projecting 6 ins. above the ground at the corner of a rock fence, bearing N. and W., and a rebar, 5/8 in. diam., 18 ins. long, firmly set alongside. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 34 NW-NE-NE 1/256</p> <p style="text-align: center;">1994</p>
--------	--

FURTHER SUBDIVISION OF SECTION 34,
T. 19 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Reset the rebars inside the stainless steel post.</p> <hr/> <p>N. 89°38'50" W., on the E-W center line of the NW1/4 of the NE1/4 of the NE1/4 of sec. 34.</p> <p>Over gently rolling land, through scattered sagebrush and native grass.</p> <p>2.419 Point for the 1/1024 sec. cor. of sec. 34, determined by persons unknown, monumented with a rebar, 5/8 in. diam., firmly set 12 ins. below the ground at the corner of a rock fence, bearing N. and E. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>POINT NOT REMONUMENTED</p> <hr/> <p>N. 89°51'40" W., beginning new measurement.</p> <p>Over gently rolling land.</p> <p>2.429 The C-N-N-NE 1/256 sec. cor. of sec. 34.</p> <hr/> <p>From the point for the C-E-NW-NE 1/256 sec. cor. of sec. 34, at its computed position.</p> <p>POINT NOT MONUMENTED</p> <p>N. 2°22'30" W., on the N-S center line of the NE1/4 of the NW1/4 of the NE1/4 of sec. 34.</p> <p>Over gently rolling land, through scattered sagebrush and native grass.</p> <p>4.837 Point for the NE-NW-NE 1/256 sec. cor. of sec. 34, at its computed position.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to solid rock over a plastic encased magnet, and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">S 34 NE-NW-NE 1/256 1994</p> <hr/> <p>From the C-N-N-NE 1/256 sec. cor. of sec. 34.</p> <p>N. 89°39'40" W., on the E-W center line of the NE1/4 of the NW1/4 of the NE1/4 of sec. 34.</p> <p>Over gently rolling land, through scattered sagebrush and native grass.</p> <p>2.423 Point for the 1/1024 sec. cor. of sec. 34.</p>
--------	--

FURTHER SUBDIVISION OF SECTION 34,
T. 19 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to solid rock over a plastic encased magnet, and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p>1/1024</p> <p>1995</p> <p>4.846 The NE-NW-NE 1/256 sec. cor. of sec. 34.</p> <hr/> <p>From the point for the SE-NW-NE 1/256 sec. cor. of sec. 34, at its computed position.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to solid rock over a plastic encased magnet, and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p>S 34 SE-NW-NE 1/256</p> <p>1994</p> <p>N. 2°22'30" W., on the N-S center line of the SE1/4 of the NW1/4 of the NE1/4 of sec. 34.</p> <p>Over gently rolling land, through scattered sagebrush and native grass.</p> <p>4.837 The point for the C-E-NW-NE 1/256 sec. cor. of sec. 34.</p> <hr/> <p>From the C-S-N-NE 1/256 sec. cor. of sec. 34.</p> <p>N. 89°42'30" W., on the E-W center line of the SE1/4 of the NW1/4 of the NE1/4 of sec. 34.</p> <p>Over gently rolling land, through scattered sagebrush and native grass.</p> <p>4.819 The SE-NW-NE 1/256 sec. cor. of sec. 34.</p> <hr/> <p>METES-AND-BOUNDS SURVEY OF TRACT 37, T. 19 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Tract 37, identical with the E1/2 of the NE1/4 of the SW1/4 of the SE1/4 of sec. 34, as shown on the plat accepted March 22, 1957.</p> <p>This tract was located by the subdivision of sec. 34 as surveyed by J. W. Hardison, Cadastral Engineer and H. T. Brown, Cadastral Surveyor, in 1956. The field notes of the boundaries of Tract 37 only are furnished herewith.</p>
--------	---

METES-AND-BOUNDS SURVEY OF TRACT 37,
T. 19 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From Angle Point No. 1, of Tract 37, identical with the SE 1/16 sec. cor. of sec. 34, based upon the 1956 resurvey and subdivision, monumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the subdivision of the SE1/4 of section 34 of T. 19 N., R. 20 E., executed under Group No. 366.</p> <p>Remark the brass cap to read as follows:</p> <div style="text-align: center;"> <p>T19N R20E</p> <table border="1" style="margin: auto;"> <tr> <td>AP-1</td><td>S 34</td></tr> <tr> <td>TR-37</td><td></td></tr> </table> <p>1956 1994</p> </div> <p>S. 89°26'50" W., on line 1-2, Tract 37.</p> <p>Over rolling land, through scattered sagebrush and native grass.</p> <p>4.864 Point for Angle Point No. 2, Tract 37, identical with the C-E-W-SE 1/256 sec. cor. of sec. 34, based upon the 1956 resurvey and subdivision, also identical with Angle Point No. 1, Tract 38.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to solid rock over a plastic encased magnet, and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T19N R20E</p> <p>S 34</p> <table border="1" style="margin: auto;"> <tr> <td>AP-1</td><td>AP-2</td></tr> <tr> <td>TR-38</td><td>TR-37</td></tr> </table> <p>1994</p> </div> <p>From this corner, a rebar, 5/8 in. diam., firmly set projecting 2 ins. above the ground, bears SOUTH, 0.084 chs. dist.</p> <p>S. 4°08'20" E., on line 2-3, Tract 37, identical with line 1-4, Tract 38.</p> <p>9.333 Point for Angle Point No. 3, Tract 37, identical with the C-E-SW-SE 1/256 sec. cor. of sec. 34, based upon the 1956 resurvey and subdivision, also identical with Angle Point No. 4, Tract 38, Angle Point No. 1, Tract 39, and Angle Point No. 2, Tract 40, determined by persons unknown, monumented with a steel stake, 3/4 in. diam., 15 ins. long, firmly set flush with the ground. This steel stake is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to solid rock over a plastic encased magnet, and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p>	AP-1	S 34	TR-37		AP-1	AP-2	TR-38	TR-37
AP-1	S 34								
TR-37									
AP-1	AP-2								
TR-38	TR-37								

300

METES-AND-BOUNDS SURVEY OF TRACT 37,
T. 19 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<table border="1" data-bbox="873 275 1047 441"> <tr> <td>T19N</td><td>R20E</td></tr> <tr> <td>AP-4</td><td>AP-3</td></tr> <tr> <td>TR-38</td><td>TR-37</td></tr> <tr> <td>AP-1</td><td>AP-2</td></tr> <tr> <td>TR-39</td><td>TR-40</td></tr> </table> <p data-bbox="932 464 992 491">1994</p> <p data-bbox="448 516 1474 571">Reset the steel stake and set a steel fence post, 5 ft. long, alongside the stainless steel post.</p> <p data-bbox="448 598 1474 653">N. 89°05'40" E., on line 3-4, Tract 37, identical with line 2-1, Tract 40.</p> <p data-bbox="321 680 1479 863">4.896 Point for Angle Point No. 4, Tract 37, identical with the C-S-SE 1/64 sec. cor. of sec. 34, based upon the 1956 resurvey and subdivision, also identical with Angle Point No. 1, Tract 40, determined by persons unknown, monumented with a metal pipe, 2 1/2 ins. diam., 6 1/2 ft. long, firmly set in a mound of stone. This metal pipe is accepted as a careful and faithful determination of the position of the corner.</p> <p data-bbox="448 890 748 917">At the corner point</p> <p data-bbox="448 945 1479 1022">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic encased magnet, with brass cap mkd.</p> <table border="1" data-bbox="889 1050 1089 1218"> <tr> <td>T19N</td><td>R20E</td></tr> <tr> <td>AP-4</td><td></td></tr> <tr> <td>TR-37</td><td></td></tr> <tr> <td>AP-1</td><td>S 34</td></tr> <tr> <td>TR-40</td><td></td></tr> </table> <p data-bbox="932 1241 992 1268">1994</p> <p data-bbox="448 1295 1479 1350">Reset the metal pipe alongside the stainless steel post and rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p data-bbox="448 1377 1040 1404">N. 4°20'40" W., on line 4-1, Tract 37.</p> <p data-bbox="321 1432 1263 1459">9.304 Angle Point No. 1, Tract 37, and point of beginning.</p> <hr/> <p data-bbox="578 1512 1349 1566">METES-AND-BOUNDS SURVEY OF TRACT 38, T. 19 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p data-bbox="448 1614 1479 1692">Tract 38, identical with the W1/2 of the NE1/4 of the SW1/4 of the SE1/4 of sec. 34, as shown on the plat accepted March 22, 1957.</p> <p data-bbox="448 1719 1479 1824">This tract was located by the subdivision of sec. 34 as surveyed by J. W. Hardison, Cadastral Engineer and H. T. Brown, Cadastral Surveyor, in 1956. The field notes of the boundaries of Tract 38 only are furnished herewith.</p>	T19N	R20E	AP-4	AP-3	TR-38	TR-37	AP-1	AP-2	TR-39	TR-40	T19N	R20E	AP-4		TR-37		AP-1	S 34	TR-40	
T19N	R20E																				
AP-4	AP-3																				
TR-38	TR-37																				
AP-1	AP-2																				
TR-39	TR-40																				
T19N	R20E																				
AP-4																					
TR-37																					
AP-1	S 34																				
TR-40																					

301

METES-AND-BOUNDS SURVEY OF TRACT 38,
T. 19 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From Angle Point No. 1, of Tract 38, identical with the C-E-W-SE 1/256 sec. cor. of sec. 34, based upon the 1956 resurvey and subdivision, also identical with Angle Point No. 2, Tract 37, hereinbefore described.</p> <p>S. 89°26'50" W., on line 1-2, Tract 38.</p> <p>Over rolling land, through scattered sagebrush and native grass.</p> <p>4.864 Point for Angle Point No. 2, Tract 38, identical with the C-W-SE 1/64 sec. cor. of sec. 34, based upon the 1956 resurvey and subdivision, determined by persons unknown, monumented with a steel pin, 1/4 in. diam., 8 ins. long, firmly set flush with the ground. This steel pin is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to solid rock over a plastic encased magnet, and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T19N R20E</p> <p>S 34</p> <div style="border-left: 1px solid black; padding-left: 5px; margin-left: 10px;"> <p>AP-2</p> <p>TR-38</p> </div> <p>1994</p> </div> <p>Reset the steel pin alongside the stainless steel post.</p> <p>S. 3°56'10" E., on line 2-3, Tract 38.</p> <p>9.361 Point for Angle Point No. 3, Tract 38, identical with the SW-SE 1/64 sec. cor. of sec. 34, based upon the 1956 resurvey and subdivision, also identical with Angle Point No. 2, Tract 39, determined by persons unknown, monumented with a mound of stone. A metal pipe, 2 1/2 ins. diam., 6 1/2 ft. long, similar to the one at Angle Point No. 4, Tract 37, was found lying on the ground approximately 60 ft. westerly. This mound of stone is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to solid rock over a plastic encased magnet, and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T19N R20E</p> <div style="border-left: 1px solid black; padding-left: 5px; margin-left: 10px;"> <p>AP-3</p> <p>TR-38</p> </div> <p>S 34</p> <div style="border-left: 1px solid black; padding-left: 5px; margin-left: 10px;"> <p>AP-2</p> <p>TR-39</p> </div> <p>1994</p> </div>
--------	--

METES-AND-BOUNDS SURVEY OF TRACT 38,
T. 19 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Reset the metal pipe alongside the stainless steel post.</p> <p>N. 89°05'40" E., on line 3-4, Tract 38, identical with line 2-1, Tract 39.</p> <p>4.896 Angle Point No. 4, Tract 38, identical with the C-E-SW-SE 1/256 sec. cor. of sec. 34, based upon the 1956 resurvey and subdivision, also identical with Angle Point No. 3, Tract 37, Angle Point No. 1, Tract 39, and Angle Point No. 2, Tract 40, hereinbefore described.</p> <p>N. 4°08'20" W., on line 4-1, Tract 38, identical with line 3-2, Tract 37.</p> <p>9.333 Angle Point No. 1, Tract 38, and point of beginning.</p> <hr/> <p style="text-align: center;">METES-AND-BOUNDS SURVEY OF TRACT 39, T. 19 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Tract 39, identical with the W1/2 of the SE1/4 of the SW1/4 of the SE1/4 of sec. 34, as shown on the plat accepted March 22, 1957.</p> <p>This tract was located by the subdivision of sec. 34 as surveyed by J. W. Hardison, Cadastral Engineer and H. T. Brown, Cadastral Surveyor, in 1956. The field notes of the boundaries of Tract 39 only are furnished herewith.</p> <p>From Angle Point No. 1, of Tract 39, identical with the C-E-SW-SE 1/256 sec. cor. of sec. 34, based upon the 1956 resurvey and subdivision, also identical with Angle Point No. 3, Tract 37, Angle Point No. 4, Tract 38, and Angle Point No. 2, Tract 40, hereinbefore described.</p> <p>S. 89°05'40" W., on line 1-2, Tract 39, identical with line 4-3, Tract 38.</p> <p>Over rolling land, through scattered sagebrush and native grass.</p> <p>4.896 Angle Point No. 2, Tract 39, identical with the SW-SE 1/64 sec. cor. of sec. 34, based upon the 1956 resurvey and subdivision, also identical with Angle Point No. 3, Tract 38, hereinbefore described.</p> <p>S. 3°14'00" E., on line 2-3, Tract 39.</p> <p>9.355 Point for Angle Point No. 3, Tract 39, identical with the W-E 1/64 sec. cor. of secs. 3 and 34, on the S. bdy. of the Tp., based upon the 1956 resurvey and subdivision, also identical with Angle Point No. 3, Lot 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to solid rock over a plastic encased magnet, and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p>
--------	--

303

METES-AND-BOUNDS SURVEY OF TRACT 39,
T. 19 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div data-bbox="876 273 1044 367"> <table> <tr> <td>T19N</td><td>R20E</td></tr> <tr> <td>S 34</td><td>AP-3</td></tr> <tr> <td></td><td>TR-39</td></tr> </table> </div> <div data-bbox="909 378 998 436"> <p>AP-3 LOT 7</p> </div> <div data-bbox="909 457 998 487"> <p>1994</p> </div> <p data-bbox="438 514 1469 573">N. 88°45'00" E., on line 3-4, Tract 39, identical with line 3-2, Lot 7.</p> <p data-bbox="316 594 1469 808">4.985 Point for Angle Point No. 4, Tract 39, identical with the E-W-E 1/256 sec. cor. of secs. 3 and 34, on the S. bdy. of the Tp., based upon the 1956 resurvey and subdivision, also identical with Angle Point No. 3, Tract 40, and Angle Point No. 2, Lot 7, determined by persons unknown, monumented with a rebar, 1/2 in. diam., 25 ins. long, firmly set in a mound of stone. This rebar is accepted as a careful and faithful determination of the position of the corner.</p> <p data-bbox="438 829 743 861">At the corner point</p> <p data-bbox="438 882 1469 993">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to solid rock over a plastic encased magnet, and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <div data-bbox="860 1014 1044 1108"> <table> <tr> <td>T19N</td><td>R20E</td></tr> <tr> <td>AP-4</td><td>AP-3</td></tr> <tr> <td>TR-39</td><td>TR-40</td></tr> </table> </div> <div data-bbox="909 1119 998 1178"> <p>AP-2 LOT 7</p> </div> <div data-bbox="909 1199 998 1228"> <p>1995</p> </div> <p data-bbox="438 1249 1242 1281">Reset the rebar alongside the stainless steel post.</p> <p data-bbox="438 1302 1469 1365">N. 3°47'20" W., on line 4-1, Tract 39, identical with line 3-2, Tract 40.</p> <p data-bbox="316 1386 1258 1417">9.329 Angle Point No. 1, Tract 39, and point of beginning.</p> <hr/> <p data-bbox="568 1470 1347 1528"> METES-AND-BOUNDS SURVEY OF TRACT 40, T. 19 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA </p> <hr/> <p data-bbox="438 1575 1469 1654">Tract 40, identical with the E1/2 of the SE1/4 of the SW1/4 of the SE1/4 of sec. 34, as shown on the plat accepted March 22, 1957.</p> <p data-bbox="438 1675 1469 1787">This tract was located by the subdivision of sec. 34 as surveyed by J. W. Hardison, Cadastral Engineer and H. T. Brown, Cadastral Surveyor, in 1956. The field notes of the boundaries of Tract 40 only are furnished herewith.</p>	T19N	R20E	S 34	AP-3		TR-39	T19N	R20E	AP-4	AP-3	TR-39	TR-40
T19N	R20E												
S 34	AP-3												
	TR-39												
T19N	R20E												
AP-4	AP-3												
TR-39	TR-40												

METES-AND-BOUNDS SURVEY OF TRACT 40,
T. 19 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

From Angle Point No. 1, Tract 40, identical with the C-S-SE 1/64 sec. cor. of sec. 34, based upon the 1956 resurvey and subdivision, also identical with Angle Point No. 4, Tract 37, hereinbefore described.

S. 89°05'40" W., on line 1-2, Tract 40, identical with line 4-3, Tract 37.

Over rolling land, through scattered sagebrush and native grass.

4.896 Angle Point No. 2, Tract 40, identical with the C-E-SW-SE 1/256 sec. cor. of sec. 34, based upon the 1956 resurvey and subdivision, also identical with Angle Point No. 3, Tract 37, Angle Point No. 4, Tract 38, and Angle Point No. 1, Tract 39, hereinbefore described.

S. 3°47'20" E., on line 2-3, Tract 40, identical with line 1-4, Tract 39.

9.329 Angle Point No. 3, Tract 40, identical with the E-W-E 1/256 sec. cor. of secs. 3 and 34, on the S. bdy. of the Tp., based upon the 1956 resurvey and subdivision, also identical with Angle Point No. 4, Tract 39, and Angle Point No. 2, Lot 7, hereinbefore described.

N. 88°45'00" E., on line 3-4, Tract 40, identical with line 2-1, Lot 7.

4.985 Point for Angle Point No. 4, Tract 40, identical with the E 1/16 sec. cor. of secs. 3 and 34, on the S. bdy. of the Tp., based upon the 1956 resurvey and subdivision, also identical with Angle Point No. 1, Lot 7, monumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the south boundary of T. 19 N., R. 20 E., executed under Group No. 366.

Remark the brass cap to read as follows:

T19N R20E	
AP-4	S 34
TR-40	
AP-1	
LOT 7	
1956	
1995	

N. 4°20'40" W., on line 4-1, Tract 40.

9.304 Angle Point No. 1, Tract 40, and point of beginning.

305

METES-AND-BOUNDS SURVEY OF LOT 7 IN SECTION 34,
T. 19 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From Angle Point No. 1, Lot 7, identical with the E 1/16 sec. cor. of secs. 3 and 34, on the S. bdy. of the Tp., based upon the 1956 resurvey and subdivision, also identical with Angle Point No. 4, Tract 40, hereinbefore described.</p> <p>S. 89°45'00" W., on line 1-2, Lot 7, identical with line 4-3, Tract 40.</p> <p>Over rolling land, through scattered sagebrush and native grass.</p> <p>4.985 Angle Point No. 2, Lot 7, identical with the E-W-E 1/256 sec. cor. of secs. 3 and 34, on the S. bdy. of the Tp., based upon the 1956 resurvey and subdivision, also identical with Angle Point No. 3, Tract 40 and Angle Point No. 4, Tract 39, hereinbefore described.</p> <p>S. 89°45'00" W., on line 2-3, Lot 7, identical with line 4-3, Tract 39.</p> <p>4.985 Angle Point No. 3, Lot 7, identical with the W-E 1/64 sec. cor. of secs. 3 and 34, on the S. bdy. of the Tp., based upon the 1956 resurvey and subdivision, also identical with Angle Point No. 3, Tract 39, hereinbefore described.</p> <p>S. 89°45'00" W., on line 3-4, Lot 7.</p> <p>9.970 Angle Point No. 4, Lot 7, identical with the 1/4 sec. cor. of secs. 3 and 34, on the S. bdy. of the Tp., hereinbefore described.</p> <p>S. 86°13'30" E., on line 4-5, Lot 7.</p> <p>18.399 Angle Point No. 5, Lot 7, identical with the E 1/16 sec. cor. of secs. 3 and 34, hereinbefore described.</p> <p>S. 86°13'30" E., on line 5-6, Lot 7.</p> <p>1.717 Point for Angle Point No. 6, Lot 7, established at the intersection point of the extension of line 1-4, Tract 40, with the S. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to solid rock over a plastic encased magnet, and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T19N R20E</p> <table border="1"> <tr> <td>LOT 7</td> <td></td> </tr> <tr> <td>AP-6</td> <td>S 34</td> </tr> </table> <p>S 3</p> <p>T18N R20E</p> <p>1995</p> </div> <p>From this point, the original 1861 sec. cor. of secs. 2, 3, 34 and 35, on the S. Bdy. of the Tp., bears S. 86°13'30" E., 16.682 chs. dist., hereinbefore described.</p>	LOT 7		AP-6	S 34
LOT 7					
AP-6	S 34				

306

METES-AND-BOUNDS SURVEY OF LOT 7 IN SECTION 34,
T. 19 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 4°20'40" W., on line 6-1, Lot 7.
1.764	Angle Point No. 1, Lot 7, and point of beginning. <hr/>
	<p>GENERAL DESCRIPTION</p> <p>The land surveyed and resurveyed within section 34, Township 19 North, Range 20 East, situated at the southerly end of Hidden Valley, ranges from about 4,500 to 5,000 ft. above sea level, and is gently rolling to mountainous. The soil is rocky sandy clay loam and vegetation consists of sagebrush and native grass.</p> <p>Access into the area is provided by Mira Loma Road, Short Lane and numerous trail roads. Two gravel pits are located in the section, one near the center of the section and the other just crossing over the south boundary into the section. A power line, bearing NW. and SE., crosses the S. bdy. just W. of the 1/4 sec. cor. of secs. 3 and 34.</p> <p>There are several homes situated on private land in the N1/2 of the NE1/4 of the NE1/4 of the section.</p> <p>No mineral formations of consequence were noted during the survey.</p> <hr/>

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Robert H. Thompson
Gary M. Jacobs
Robert W. Crouch
Clay W. Morrow
Peter F. Perazzo

Cadastral Surveyor
Cartographic Technician
Survey Technician
Survey Technician
Survey Technician

308

CERTIFICATE OF SURVEY

I, David D. Morlan, HEREBY CERTIFY upon honor, that in pursuance of Special Instructions bearing date of the 14th day of January, 1994, and Supplemental Special Instructions bearing date of the 22nd day of August, 2002, I have correctively dependently resurveyed and dependently resurveyed a portion of the south boundary, correctively dependently resurveyed and dependently resurveyed a portion of the subdivisional lines, dependently resurveyed a portion of the subdivision of section 34, further subdivided section 34, executed the metes-and-bounds survey of Tracts 37, 38, 39, and 40, and executed the metes-and-bounds survey of Lot 7 in section 34, T. 19 N., R. 20 E., of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

June 4, 2002

(Date)

David D. Morlan
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of the corrective dependent resurvey and dependent resurvey of a portion of the south boundary, the corrective dependent resurvey and dependent resurvey of a portion of the subdivisional lines, the dependent resurvey of a portion of the subdivision of section 34, the further subdivision of section 34, the metes-and-bounds survey of Tracts 37, 38, 39, and 40, and the metes-and-bounds survey of Lot 7 in section 34, T. 19 N., R. 20 E., Mount Diablo Meridian, Nevada, executed by David D. Morlan, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

June 11, 2002

(Date)

R. M. Scum

(Chief Cadastral Surveyor, Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 19 N., R. 20 E., M.D.M., Nevada, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor, Nevada)~~