

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF

A PORTION OF THE SUBDIVISIONAL LINES

AND

THE SUBDIVISION OF SECTIONS 10, 11 AND 15,

THE SURVEY OF PORTIONS OF

THE AVULSED CHANNEL OF THE TRUCKEE RIVER IN SECTIONS 10 AND 11,
AND THE MEANDERS OF THE TRUCKEE RIVER IN SECTIONS 10, 11 AND 15,

AND

CERTAIN METES-AND-BOUNDS SURVEYS IN SECTIONS 10, 11 AND 15,

TOWNSHIP 19 NORTH, RANGE 21 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATE OF NEVADA

EXECUTED BY

Richard L. Jones, Cadastral Surveyor

Clay W. Morrow, Surveying Technician

Under Special Instructions dated April 21, 2003,
and approved April 21, 2003, and Supplemental and Amended Special
Instructions dated August 6, 2004, and approved August 6, 2004,
which provided for the surveys included under Group No. 811,
and Assignment Instructions dated April 18, 2003 and April 21, 2003

Survey commenced: April 21, 2003

Survey completed: August 24, 2004

INDEX DIAGRAM

TOWNSHIP 19 NORTH, RANGE 21 EAST, MOUNT DIABLO MERIDIAN, NEVADA

6	5	4	3	2	1
			19	9	
7	8	9	17 10	6 11	2 12
			13	5	
18	17	16	12 15	3 14	13
			11		
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Subdivision of sec. 10,	Pg. 20 - 25
Subdivision of sec. 11,	Pg. 25 - 31
Subdivision of sec. 15,	Pg. 31 - 37
Survey of avulsed channel of the Truckee River in sec. 10,	Pg. 37 - 49
Survey of right bank of avulsed channel of the Truckee River in sec. 11, ...	Pg. 49 - 51
Survey of a portion of the meanders of the right bank of the Truckee River, .	Pg. 51 - 56
Survey of a portion of the meanders of the left bank of the Truckee River, .	Pg. 56 - 61
Metes-and-bounds survey of railroad right-of-way in sec. 10,	Pg. 61 - 65
Metes-and-bounds survey parallel and concentric to railroad in sec. 15,	Pg. 65 - 68
Metes-and-bounds survey in sec. 11,	Pg. 68 - 71
Metes-and-bounds survey of 50 ft. wide strip of land in the NE1/4 of the NW1/4 of sec. 15,	Pg. 71 - 75

TOWNSHIP 19 NORTH, RANGE 21 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines and the subdivision of sections 10, 11 and 15, the survey of portions of the avulsed channel of the Truckee River in sections 10 and 11, and the meanders of the Truckee River in sections 10, 11 and 15 and certain metes-and bounds surveys in sections 10, 11 and 15, in Township 19 North, Range 21 East, Mount Diablo Meridian, Nevada.

A portion of the Carson Guide Meridian, along the west boundary was surveyed by U.S. Deputy Surveyor B. Ives in 1861 under Contract A.

The south and north boundary, a portion of the east boundary and a portion of the subdivisional lines were surveyed by U.S. Deputy Surveyor S.W. Foreman in 1865 under Contract K.

The south and north boundaries, a portion of the east boundary and a portion of the subdivisional lines were dependently resurveyed, and a portion of the east boundary and the remainder of the subdivisional lines were surveyed by U.S. Deputy Surveyor T.K. Stewart in 1903 under Contract No. 220.

Before restoring the corners, the lines of the original survey were retraced and a diligent search made for any evidence of the original corners and other calls of the original field note record.

Truckee River Avulsions

Aerial photography taken in 1959, 1964 and 1974, show two avulsions of the Truckee River occurred in sections 10 and 11. One avulsion occurred between the years 1959 and 1964 and the second occurred between the years 1964 and 1974. The positions of the avulsed channels were photo-identified and used to identify on-the-ground evidence of the mean high water line of the avulsed channel. The on-the-ground evidence was used to control angle points of the fixed and limited boundary of the avulsed channels. Where on-the-ground evidence was indeterminate, points digitized from the aerial photography were used to control the angle points of the avulsed channels.

The survey was executed in accordance with the specification set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 811, Nevada, dated April 21, 2003, and the Supplemental and Amended Special Instructions dated August 6, 2006.

The direction and distance of the lines of the survey were obtained by Trimble 5700 Global Positioning Systems(GPS) receivers using real-time kinematic methods. The mean bearings of the lines and horizontal equivalents of ground distances only are entered in these field notes.

The geographic position NAD 1983 of the corner of sections 10, 11, 14 and 15, as determined by ties made to SPANISH SPRINGS COOP CORS L1 Phase center and TANG COOP CORS L1 Phase Center, is as follows:

Latitude: 39°31'15.735" N. Longitude: 119°36'31.500" W.

The mean magnetic declination is 17° E., as shown on U.S.G.S. quadrangle map "PATRICK, NEV." Dated 1980.

247

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

Reestablishment of a Portion of the Survey Executed by
S.W. Foreman, U.S. Deputy Surveyor, in 1865

From the cor. of secs. 11 and 14 only, monumented with a basalt stone, 20x9x7 ins. (1865 Record, 17x9x5 ins.; 1903 Record, 18x13x5 ins.), firmly set, plainly mkd. with 4 grooves on S. face and 1 groove on E. face (1903 Record, notches, edges), and a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

T19N	R21E
S11	
S14	S12

2003

Deposit the original corner stone alongside the stainless steel post.

N. 0°03'20" E., bet. secs. 11 and 12.

Over rolling foothills, covered with scattered sagebrush and native grass.

40.299

The 1/4 sec. cor. of secs. 11 and 12, set by S.W. Foreman in 1865, under Contract K, monumented with a basalt stone, 20x10x6 ins. (1865 Record, 20x10x8 ins.), firmly set in a mound of stone, 3 ft. base, plainly mkd. with 1/4 on W. face, with an X on top.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

T19N	R21E
1/4	
S11	S12

2003

Deposit the original corner stone alongside the stainless steel post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From this corner, the 1/4 sec. cor. of secs. 11 and 12, set by T.K. Stewart in 1903, under Contract No. 220, monumented with a basalt stone, 12x12x6 ins. (1903 Record, 18x12x9 ins.), firmly set in a mound of stone, 3 ft. base, plainly mkd. with 1/4 on E. face, bears N. 66°45' E., 6.278 chs. dist.</p> <hr/> <p>N. 0°25'30" W., beginning new measurement.</p>						
20.030	Point for the N 1/16 sec. cor. of secs. 11 and 12, not monumented.						
40.060	<p>The cor. of secs. 1, 2, 11 and 12, monumented with a basalt stone, 23x12x6 ins. (1865 Record, 20x10x8 ins.), firmly set in a mound of stone, 3 ft. base, plainly mkd. with 5 notches on S. edge and 1 notch on E. edge.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr> <td>T19N</td><td>R21E</td></tr> <tr> <td>S 2</td><td>S 1</td></tr> <tr> <td>S11</td><td>S12</td></tr> </table> </div> <p>2003</p> <p>Deposit the original corner stone alongside the stainless steel post.</p> <p>From this corner, the cor. of secs. 1, 2, 11 and 12, set by T.K. Stewart in 1903, under Contract No. 220, monumented with a basalt stone, 16x10x4 ins. (1903 Record, 14x9x6 ins.), plainly mkd. with 5 notches on S. edge and 1 notch on E. edge, bears N. 69°02' E., 6.409 chs. dist.</p> <hr/> <p>From the cor. of secs. 14, 15, 22 and 23, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set projecting 2 ins. above the ground in a collar of stone, 3 ft. diam., with a basalt stone, 22x12x8 ins. (1865 Record, 18x12x6 ins.; 1903 Record, 18x10x9 ins.), lying alongside, mkd. with 3 notches on one edge and 2 notches on adjoining edge.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>	T19N	R21E	S 2	S 1	S11	S12
T19N	R21E						
S 2	S 1						
S11	S12						

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div data-bbox="862 262 1008 363"> <p>T19N R21E S15 S14 S22 S23</p> </div> <div data-bbox="902 394 967 422">2003</div> <div data-bbox="415 457 1446 516"> <p>Insert the rebar inside the stainless steel post and deposit the original corner stone alongside the stainless steel post.</p> </div> <div data-bbox="415 548 1003 575"> <p>N. 1°51'10" E., bet. secs. 14 and 15.</p> </div> <div data-bbox="415 606 1446 665"> <p>Over rolling foothills, covered with scattered sagebrush and native grass.</p> </div> <div data-bbox="269 697 1446 787"> <p>42.514 The 1/4 sec. cor. of secs. 14 and 15, monumented with a basalt stone, 14x8x8 ins., firmly set in a mound of stone, 3 ft. base, plainly mkd. 1/4 on E. face.</p> </div> <div data-bbox="415 819 721 846"> <p>At the corner point</p> </div> <div data-bbox="415 877 1446 968"> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, over a plastic-encased magnet and in a collar of stone, with brass cap mkd.</p> </div> <div data-bbox="862 999 1008 1087"> <p>T19N R21E 1/4 S15 S14</p> </div> <div data-bbox="902 1119 967 1146">2003</div> <div data-bbox="415 1178 1446 1236"> <p>Deposit the original corner stone alongside the stainless steel post.</p> </div> <div data-bbox="415 1297 1084 1325"> <p>N. 0°18'00" W., beginning new measurement.</p> </div> <div data-bbox="269 1356 1446 1566"> <p>20.003 The N 1/16 sec. cor. of secs. 14 and 15, monumented with an iron pipe, 2 ins. diam., 20 ins. long, firmly set projecting 12 ins. above the ground with a threaded metal cap mkd. "AZCARATE S15 S14 N 1/16 1945. This position has been adopted and recorded by various professional land surveyors as indicated on survey records recorded in Storey County, Nevada, and is accepted as the position of the corner.</p> </div> <div data-bbox="415 1598 721 1625"> <p>At the corner point</p> </div> <div data-bbox="415 1656 1446 1747"> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> </div>
--------	---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>N 1/16 S15 S14</p>
	<p>2004</p>
	<p>Insert the iron pipe inside the stainless steel post.</p>
	<p>N. 2°16'50" W., beginning new measurement.</p>
15.024	<p>The N-N-N 1/256 sec. cor. of secs. 14 and 15, monumented with a steel pipe, 10 ins. diam., firmly set projecting 7 ft. above the ground. This position has been adopted and recorded by various professional land surveyors as indicated on survey records recorded in Storey County, Nevada, and is accepted as the best available evidence of the position of the corner.</p>
	<p>N. 1°10'50" W., beginning new measurement.</p>
5.002	<p>The cor. of secs. 10, 11, 14, and 15, determined by David C. Brown, Nevada Professional Land Surveyor No. 8418, monumented with a rebar 5/8 in. diam., 18 ins. long, firmly set 2 ins. below the surface of the ground with a plastic cap, 1 1/2 ins. diam. mkd. PLS 8418, as recorded in Storey County, Nevada, File No. 77879, Record of Survey. This position has been adopted and recorded by various professional land surveyors as indicated on survey records recorded in Storey County, Nevada, and is accepted as the best available evidence of the position of the original corner.</p>
	<p>At the corner point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p>T19N R21E S10 S11 S15 S14</p>
	<p>2004</p>
	<p>Insert the rebar inside the stainless steel post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>
	<p>From the cor. of secs. 11 and 14 only.</p>
	<p>S. 89°58'00" W., bet. secs. 11 and 14.</p>
	<p>Over rolling foothills, covered with scattered sagebrush and native grass.</p>

251

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.351	<p>The 1/4 sec. cor. of secs. 11 and 14, monumented with a basalt stone, 18x10x9 ins., firmly set in a mound of stone, 3 ft. base, plainly mkd. 1/4 on N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 13 ins. in the ground, over a plastic-encased magnet in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T19N R21E S11 1/4 <u> </u> S14</p> <p>2003</p> </div> <p>Deposit the original corner stone alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°16'20" W., beginning new measurement.</p>
20.291	<p>The W 1/16 sec. cor. of secs. 11 and 14, determined by David C. Brown, Nevada Professional Land Surveyor No. 8418, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set projecting 2 ins. above the ground with a plastic cap, 1 1/2 ins. diam., mkd. PLS 8418, as recorded in Storey County, Nevada, File No. 77879, Record of Survey. This position has been adopted and recorded by various professional land surveyors as indicated on survey records recorded in Storey County, Nevada, and is accepted as a careful and faithful determination of the position of the corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>W 1/16 <u> </u> S11 S14</p> <p>2004</p> </div> <p>Insert the rebar inside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°17'00" W., beginning new measurement.</p>
20.283	<p>The cor. of secs. 10, 11, 14 and 15.</p> <hr style="width: 50%; margin: 10px auto;"/> <p>N. 0°11'40" W., bet. secs. 10 and 11.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Over bottom land, covered with scattered sagebrush, native grass and widely scattered cottonwood.
1.00	Improved gravel road, bears NE and SW.
1.748	Point for Angle Point No. 1, of a metes-and-bounds survey in sec. 11. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div data-bbox="857 606 1023 768" data-label="Diagram"> </div>
20.466	Point for the S 1/16 sec. cor. of secs. 10 and 11. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div data-bbox="873 982 992 1098" data-label="Diagram"> </div> <p>Set a steel fence post, 6 ft. long, alongside the stainless steel post.</p>
23.959	Adjusted right bank of the Truckee River, bears N. 50°14'30" E. and S. 50°14'30" W.
29.824	Present left bank of the Truckee River, at the line of mean high water, bank bears N. 78°01'10" E. and S. 78°01'10" W.
33.187	Right bank of the avulsed channel of the Truckee River, point for Angle Point No. 21, sec. 10, identical with Angle Point No. 1, sec. 11, bank bears N. 86°07'40" E. and S. 42°54'10" W. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div data-bbox="849 1671 1036 1881" data-label="Diagram"> </div>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
38.722	Union Pacific Railroad, observed centerline of main track, bears NE and SW.
40.932	<p>The 1/4 sec. cor. of secs. 10 and 11, determined by James L. Scholl Jr., Nevada Professional Land Surveyor No. 1799, monumented with an iron pin, 1/2 in. diam., 18 ins. long, firmly set in a collar of stone, as recorded in Washoe County, Nevada, File No. 50458 Record of Survey No. 559, and is accepted as a careful and faithful determination of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T19N R21E 1/4 S10 S11 2003</p> <p>Insert the iron pin inside the stainless steel post and raise a mound of stone, 3 ft. base. 2 ft. high, W. of cor.</p> <hr/> <p>N. 0°04'30" W., beginning new measurement.</p> <p>Enter rolling land.</p>
7.60	Paved road, bears NE and SW.
15.00	East bound lane I-80, on curve, bears NE and SW.
15.90	West bound lane I-80, on curve, bears NE and SW.
20.84	Telephone pole line, bears N. 57 3/4° E. and S. 57 3/4° W.
21.88	Power pole line, parallels telephone pole line.
40.468	<p>The cor. of secs. 2, 3, 10 and 11, remonumented by John R. Weber, Nevada Professional Land Surveyor No. 2522, monumented with a brass disk, 2 1/2 ins. diam., mkd. T 19 N R 21 E S2 S3 S10 S11 1971 RLS 2522, firmly set in concrete, in a collar of stone, with a basalt stone 15x10x9 ins. (1865 Record, 16x12x9 ins.), lying alongside, mkd. with 5 grooves on one face and 2 grooves on adjoining face, as described in Washoe County, Nevada Corner Record No. 235862 and is accepted as a careful and faithful determination of the position of the corner.</p> <p>Deposit the original corner stone alongside the brass disk.</p> <hr/>


254

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the cor. of secs. 1, 2, 11 and 12.</p>
	<p>N. 88°55'00" W., bet. secs. 2 and 11.</p>
	<p>Descend rolling foothills, covered with sagebrush and native grass.</p>
20.213	<p>The E 1/16 sec. cor. of secs. 2 and 11, determined by David C. Brown, Nevada Professional Land Surveyor No. 8418, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set flush with the ground, with a plastic cap, 1 1/2 ins. diam., mkd. PLS 8418, as recorded in Storey County, Nevada, File No. 77077 Record of Survey and is accepted as a careful and faithful determination of the position of the corner.</p>
	<p>At the corner point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	$\begin{array}{r} \text{E } 1/16 \quad \text{S } 2 \\ \hline \text{S11} \end{array}$
	<p>2003</p>
	<p>Insert the rebar inside the stainless steel post and set a steel fence post, 4 ft. long, alongside the stainless steel post.</p>
	<hr/>
	<p>N. 88°55'00" W., beginning new measurement.</p>
	<p>Enter bottom land.</p>
6.432	<p>A point on the line, determined by David C. Brown, Nevada Professional Land Surveyor No. 8414, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set projecting 2 ins. above the ground, with a plastic cap, 1 1/2 ins. diam., mkd. PLS 8418, as recorded in Storey County, Nevada, File No. 77879 Record of Survey in 1996. This point will now function as the witness cor. to the meander cor., on the right bank of the Truckee River.</p>
	<p>At the corner point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground over a plastic-encased magnet, with brass cap mkd.</p>

255

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<div style="text-align: center;">  </div> <p style="text-align: center;">2004</p> <p>Insert the rebar inside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 88°55'00" W., beginning new measurement.</p>
0.662	Point for the meander cor. of sec. 11 only, for the right bank of the Truckee River, bears NNE and S. 11°50'50" W., at proportionate distance, based on the position determined by David C. Brown, Nevada Professional Land Surveyor No. 8418, as recorded in Storey County, Nevada, File No. 77077 Record of Survey in 1996. This position is accepted as a careful and faithful determination of the position of the corner. Point falls on bank where it is impractical to establish a permanent monument.
3.147	Present left bank of the Truckee River, at the line of mean high water, bank bears S. 17°33'40" W. and NNE.
13.781	<p>Point for the 1/4 sec. cor. of secs. 2 and 11, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T19N R21E</p> <p>S 2</p> <p>1/4 <u> </u></p> <p>S11</p> </div> <p style="text-align: center;">2004</p> <p>Raise a mound of stone 3 ft. base, 2 ft. high, N. of cor.</p>
20.108	Union Pacific Railroad, observed centerline of main track, bears NE and SW.
25.35	Paved road, bears NE and SW, enter rolling land.
29.55	East bound lane I-80, bears N. 37 1/2° E. and S. 37 1/2° W.
30.65	West bound lane I-80, parallels east bound lane.
32.000	Nevada Department of Transportation Right-of-Way monument, a standard disc, 3 1/2 ins. diam., firmly set in concrete, 12 ins. diam., projecting 2 ins. above the ground, mkd. STAW 448+97.47 POT DIST 71.05 FT. ELV. 4387.719, bears South, 0.077 chs. dist.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
32.75	Telephone pole line, parallels I-80.
34.65	Power pole line, parallels I-80.
44.205	A brass disk, 2 1/2 ins. diam., firmly set in concrete, mkd. PLS 2522, bears North, 0.107 chs. dist.
54.207	The cor. of secs. 2, 3, 10 and 11.
	<hr/> <p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>N. 89°13'20" W., on the S. bdy. of sec. 15.</p> <p>Over rolling foothills, covered with sagebrush and native grass.</p>
40.641	<p>The 1/4 sec. cor. of secs. 15 and 22, monumented with a basalt stone, 12x9x6 ins., firmly set in a mound of stone, 3 ft. base, plainly mkd. 1/4 on N. face. This cor. will now refer to the 1/4 sec. cor. of sec. 15 only.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T19N R21E 1/4 S15 <hr/></p> <p style="text-align: center;">2003</p> <p>Deposit the original corner stone alongside the stainless steel post.</p> <hr/> <p>S. 89°17'00" W., beginning new measurement.</p>
20.353	A rebar, 5/8 in. diam., firmly set projecting 2 ins. above the ground.
38.549	The closing cor. of secs. 21 and 22 monumented with a basalt stone, 18x10x10 ins. (1903 Record, 18x8x7 ins.), set in a mound of stone, mkd. with 3 grooves and CC on S. face and 3 grooves on E. face, with a rebar, 5/8 in. diam., set alongside.
40.671	The cor. of secs. 15 and 16 only, monumented with a basalt stone, 18x10x8 ins. (1865 Record, 18x10x10 ins.; 1903 Record, 14x9x6 ins.), set in a mound of stone, 3 ft. diam., plainly mkd. with 3 notches on S. edge, no other marks visible, with a rebar, 5/8 in. diam., set alongside.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr> <td>T19N</td><td>R21E</td></tr> <tr> <td><u>S16</u></td><td><u>S15</u></td></tr> <tr> <td colspan="2">S21</td></tr> </table> </div> <p>2003</p> <p>Deposit the original corner stone alongside the stainless steel post and insert the rebar inside the stainless steel post.</p> <hr/> <p>N. 1°07'20" E., bet. secs. 15 and 16.</p> <p>Descend foothills, covered with scattered sagebrush and native grass.</p> <p>17.40 Paved road, bears E. and W., enter bottom land.</p> <p>24.40 Right bank of the Truckee River, bears E. and W.</p> <p>27.40 Left bank of the Truckee River, bears E. and W.</p> <p>42.763 The 1/4 sec. cor. of secs. 15 and 16, determined by Ronald L. Cooper, Nevada Professional Land Surveyor No. 3919, monumented with a rebar, 5/8 in. diam., firmly set 2 ins. below surface of old abandoned paved road, with an aluminum cap, 1 1/2 ins. diam., mkd. 1/4 15 16 3919, as recorded in Washoe County, Nevada, File No. 516741 Record of Survey and is accepted as a careful and faithful determination of the position of the original corner.</p> <hr/> <p>N. 0°42'50" W., beginning new measurement.</p> <p>Enter gently rolling land, covered with scattered sagebrush and native grass.</p> <p>7.026 Union Pacific Railroad, observed centerline of main track, bears E. and W.</p> <p>20.310 The N 1/16 sec. cor. of secs. 15 and 16, determined by Ronald L. Cooper, Nevada Professional Land Surveyor No. 3919, monumented with a rebar, 5/8 in. diam. firmly set projecting 2 ins. above the ground, as recorded in Washoe County, Nevada, File 516741 Record of Survey and is accepted as a careful and faithful determination of the position of the corner.</p> <hr/>	T19N	R21E	<u>S16</u>	<u>S15</u>	S21	
T19N	R21E						
<u>S16</u>	<u>S15</u>						
S21							

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°42'00" W., beginning new measurement.
12.90	Frontage road, bears N. 47 1/2° E. and S. 47 1/2° W.
16.20	East bound lane I-80, parallels frontage road.
17.40	West bound lane I-80, parallels frontage road.
20.311	<p>The cor. of secs. 9, 10, 15 and 16, determined by person(s) unknown, monumented with a steel pin, 5/8 in. diam., firmly set in concrete, 3 ins. below the surface of the ground with a steel fence post, projecting 3 ft. above the ground set alongside. This steel pin has been adopted and utilized by various Land Surveyors and is accepted as the best available evidence of the position of the original corner.</p> <p>from which</p> <p>A stainless steel post 2 1/2 ins. diam., 28 ins. long, set 18 ins. in the ground, over a plastic-encased magnet and in a collar of stone, for a reference monument, bears N. 89°08' E., 0.588 chs. dist., with brass cap mkd. RM T19N R21E S10 38.8 FT. TO COR. 2003 and an arrow pointing to the cor.</p> <p>A stainless steel post 2 1/2 ins. diam., 28 ins. long, set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 2°50' W., 0.560 chs. dist., with brass cap mkd. RM T19N R21E S16 37 FT. TO COR. 2003 and an arrow pointing to the cor.</p> <hr/> <p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>N. 89°12'40" W., bet. secs. 10 and 15.</p> <p>Over bottom land, covered with widely scattered sagebrush and native grass.</p>
1.80	Improved gravel road, bears NE and SW.
20.483	<p>Point for the E 1/16 sec. cor. of secs. 10 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: right;"> <p>S10 E 1/16 — S15</p> <p>2004</p> </div>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Set a steel fence post, 6 ft. long, alongside the stainless steel post.
35.133	<p>Intersect the adjusted meanders for the right bank of the Truckee River, bears N. $36^{\circ}32'10''$ E. and S. $36^{\circ}32'10''$ W. Point for the meander cor. of secs. 10 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="824 583 1052 772"> <p>MC</p> <p>T19N S10 S15 R21E</p> <p>2004</p> </div>
37.484	Left bank of the Truckee River, at the line of mean high water, bank bears N. $34^{\circ}44'20''$ E. and S. $34^{\circ}44'20''$ W. Point for the meander cor. of secs. 10 and 15, falls on a bank where it is impractical to establish a permanent monument.
38.124	<p>Point selected for the witness cor., to the meander cor. of secs. 10 and 15, on the left bank of the Truckee River.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div data-bbox="844 1161 1052 1402"> <p>WC</p> <p>T19N S10 S15 R21E</p> <p>MC</p> <p>2004</p> </div>
38.294	<p>Intersect the southerly right-of-way line of the Union Pacific Railroad, on a line 100 ft. right angle distance from and parallel to the observed centerline of the main track, bears N. $39^{\circ}35'30''$ E., and SW.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div data-bbox="824 1707 1019 1885"> <p>WP</p> <p>S10 S15</p> <p>2004</p> </div>




260

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.238	Union Pacific Railroad, observed centerline of main track, bears N. $39^{\circ}35'30''$ E. and S. $39^{\circ}35'30''$ W.
40.966	<p>The 1/4 sec. cor. of secs. 10 and 15, monumented with a basalt stone, 18x14x8 ins., plainly mkd. with 1/4 on N. face, set in a mound of stone, 3 ft. base, with a rebar, 5/8 in. diam., set alongside.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 5 ins. in the ground to bedrock over a plastic-encased magnet, and in a mound of stone, 5 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T19N R21E</p> <p>S10</p> <p>1/4 $\frac{\quad}{\quad}$</p> <p>S15</p> <p>2003</p> </div> <p>Deposit the original corner stone alongside the stainless steel post and insert the rebar inside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. $89^{\circ}31'00''$ W., beginning new measurement.</p>
3.174	<p>Intersect a line parallel and concentric with and 200 ft. dist. from the observed centerline of the main track of the Union Pacific Railroad, bears NE and S. $39^{\circ}35'30''$ W.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>WP</p> <p>S10</p> <p>S15 $\frac{\quad}{\quad}$</p> <p>2003</p> </div>
17.756	<p>Intersect an arc of a circular curve to the right of a line parallel and concentric with and 25 ft. dist., from the centerline of existing paved road.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

261

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>WP</p> 
18.725	<p>Intersect an arc of a circular curve to the right of a line parallel and concentric with and 25 ft. dist., from the centerline of existing paved road.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p>WP</p> 
20.278	<p>Point for the W 1/16 sec. cor. of secs. 10 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a collar of stone, with brass cap mkd.</p>
	<p>W 1/16 </p>
	<p>At this point, found a rebar, 5/8 in. diam., 18 ins. long, 1 ft. below the surface of the ground that has been disturbed, insert rebar inside the stainless steel post.</p> <p>From this same point, an iron pipe, 2 ins. diam., projecting 3 ins. above the ground, leaning easterly, of no known record, bears S. 87° 43' E., 0.011 chs. dist. This iron pipe was not utilized during the course of this survey.</p>
32.40	Frontage road, bears N. 47 1/2° E. and S. 47 1/2° W.
35.487	<p>Point for the W-W-W 1/256 sec. cor. of secs. 10 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet and in a collar of stone, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>S10 W-W-W 1/256 S15 2004</p>
36.10	East bound lane I-80, parallels frontage road.
37.35	West bound lane I-80, parallels frontage road.
40.556	The cor. of secs. 9, 10, 15 and 16.
	<hr/> <p>N. 0°07'40" W., bet. secs. 9 and 10.</p> <p>Over gently rolling land, covered with scattered sagebrush and native grass.</p>
0.40	Paved frontage road, bears N. 47 1/2° E. and S. 47 1/2° W.
5.060	<p>The S-S-S 1/256 sec. cor. of secs. 9 and 10, determined by James A. Mack, Nevada Professional Land Surveyor No. 6897, monumented with a rebar, 5/8 in. diam., firmly set projecting 10 ins., in a subsurface rectangular plastic box, 1x2x1 ft., with a plastic cap, 1 1/2 in. diam., mkd. PLS 6897, as recorded in Washoe County, Nevada, File No. 2305818 Record of Survey and is accepted as a careful and faithful determination of the position of the corner.</p> <hr/> <p>N. 0°06'40" W., beginning new measurement.</p>
5.063	Point for the S-S 1/64 sec. cor. of secs. 9 and 10, not monumented.
15.190	<p>The S 1/16 sec. cor. of secs. 9 and 10, determined by Don M. McHarg, Nevada Professional Land Surveyor No. 4787, monumented with a rebar, 5/8 in. diam., 18 ins. long, set flush with the ground with a plastic cap, 1 1/2 in. diam., mkd. PLS 4787 and a steel fence post, 6 ft. long, set alongside the rebar, as recorded in Washoe County, Nevada, File No. 1126846 Parcel Map and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

263



DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>S 1/16 S 9 S10</p> <p>2003</p> <p>Insert the rebar inside the stainless steel post and reset the fence post alongside the stainless steel post.</p> <hr/> <p>N. 0°06'30" W., beginning new measurement.</p>
9.20	Power pole line, bears S. 55 1/2° E. and N. 55 1/2° W.
13.30	Paved Road, bears NW and SE, ascend mountainous land.
20.251	<p>The 1/4 sec. cor. of secs. 9 and 10, monumented with an iron pipe, 2 ins. diam., firmly set projecting 9 ins. above the ground, in a mound of stone, with a metal washer, 3/4 in. diam., attached to the iron pipe, mkd. RE 47 and the original corner stone, a basalt stone, 22x10x7 ins. (1865 Record, 16x12x8 ins.), plainly mkd. with 1/4 on one face, lying alongside the iron pipe.</p> <p>At the corner point</p> <p>Set a brass tablet, 3 1/2 ins. diam., in concrete, on the top of existing iron pipe, mkd.</p> <p>T19N R21E 1/4 S 9 S10</p> <p>2003</p> <p>Deposit the original corner stone alongside the iron pipe.</p> <hr/> <p>N. 0°07'10" W., beginning new measurement.</p>
20.80	Double wood pole power line, bears S. 68 1/4° E. and N. 68 1/4° W.
24.10	Double metal pole power line, parallels double wood pole power line.
40.406	<p>The cor. of secs. 3, 4, 9 and 10, monumented with a basalt boulder, 2x2x3 ft. (1865 Record, stone 24x12x10 ins.), firmly set in a mound of stone, 5 ft. base, mkd. with 5 grooves on S. face and 3 grooves on E. face and an X on top.</p> <p>At the corner point</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a brass tablet, 3 1/2 ins. diam., in concrete, at X chiseled on top of the basalt boulder, mkd.</p> <div style="text-align: center;"> <p>T19N R21E</p> <table> <tr> <td>S 4</td><td>S 3</td></tr> <tr> <td>S 9</td><td>S10</td></tr> </table> <p>2003</p> </div> <hr/> <p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>N. 89°42'20" W., bet. secs. 3 and 10.</p> <p>Over mountainous land, covered with sagebrush and native grass.</p>	S 4	S 3	S 9	S10
S 4	S 3				
S 9	S10				
0.25	Paved road, bears N. and S.				
39.70	Double wood pole power line, bears N. 58 3/4° E. and S. 58 3/4° W.				
40.721	<p>The 1/4 sec. cor. of secs. 3 and 10, determined by James A. Scholl, Nevada Professional Land Surveyor No. 1799, monumented with an iron pin, 3/8 in. diam., 18 ins. long, as recorded in Washoe County, Nevada, 50458 Record of Survey and is accepted as a careful and faithful determination of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 2 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T19N R21E</p> <table> <tr> <td>S 3</td><td></td></tr> <tr> <td>1/4</td><td>S10</td></tr> </table> <p>2003</p> </div> <p>Insert the iron pin inside the stainless steel post.</p> <hr/> <p>N. 89°42'30" W., beginning new measurement.</p>	S 3		1/4	S10
S 3					
1/4	S10				
8.10	Double metal pole power line, bears N. 61 1/4° E. and S. 61 1/4° W.				
32.40	Paved road in canyon, bears NW and SE.				
40.753	The cor. of secs. 3, 4, 9 and 10.				

SUBDIVISION OF SECTION 10,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the 1/4 sec. cor. of secs. 10 and 15.</p>
	<p>N. 0°02'30" E., on the N-S center line of sec. 10.</p>
1.489	<p>Intersect the northwesterly right-of-way line of the Union Pacific Railroad, 100 ft. right angle distance from, and parallel to the observed centerline of the main track, bears N. 39°35'30" E. and SW.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	
	<p style="text-align: center;">2003</p>
20.287	<p>The C-S 1/16 sec. cor. of sec. 10, determined by Jon B. Loder, Nevada Professional Land Surveyor No. 10842, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 2 ins. above the ground, with a steel fence post, 4 ft. long set alongside the rebar, with a plastic cap, 1 1/2 ins. diam., mkd. J. LODER PLS 10842, as shown on an unrecorded plat obtained from Mr. Loder and is accepted as a careful and faithful determination of the position of the corner.</p>
	<p>At the corner point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet and in a collar of stone, with brass cap mkd.</p>
	
	<p style="text-align: center;">2003</p>
	<p>Insert the rebar inside the stainless steel post and reset the T post alongside the stainless steel post.</p>
	<hr style="width: 20%; margin: 10px auto;"/>
	<p>N. 0°02'30" E., beginning new measurement.</p>
7.40	<p>Improved gravel road, bears E and W.</p>
10.144	<p>Point for the C-N-S 1/64 sec. cor. of sec. 10.</p>

SUBDIVISION OF SECTION 10,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam, 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S10 C-N-S 1/64</p> <p style="text-align: center;">2004</p>
10.50	Telephone pole line, bears N. 43 3/4° E. and S. 43 3/4° W.
13.00	East bound lane I-80, bears N. 47 1/2° E. and S. 47 1/2° W.
14.20	West bound lane I-80, parallels east bound lane of I-80.
17.60	Paved Frontage road, parallels east bound lane of I-80.
18.60	Power pole line, bears N. 48 3/4° E. and S. 48 3/4° W.
20.287	<p>The center 1/4 sec. cor. of sec. 10, determined by James L. Scholl, Nevada Professional Land Surveyor No. 1799, monumented with an iron pin, 3/8 in. diam., firmly set projecting 2 ins. above the ground in a collar of stone, as recorded in Washoe County, Nevada, File No. 50458 Record of Survey No. 559, and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T19N R21E C 1/4 S10</p> <p style="text-align: center;">2003</p> <p>Insert the iron pin inside the stainless steel post and set a steel fence post, 4 ft. long, alongside the stainless steel post.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/> <p>N. 0°01'00" E., beginning new measurement.</p>
2.80	Paved road, bears NW and SE.
39.80	Double wood pole power line, bears N. 58 3/4° E. and S. 58 3/4° W.
40.470	The 1/4 sec. cor. of secs. 3 and 10.

267

SUBDIVISION OF SECTION 10,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the 1/4 sec. cor. of secs. 10 and 11.</p> <p>N. 89°42'30" W., on the E-W center line of sec. 10.</p>
20.395	<p>Point for the C-E 1/16 sec. cor. of sec. 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>E 1/16</p> <p>C ————— C</p> <p>S10</p> <p>2003</p> </div>
27.60	Paved road, on curve, bears NE and SW.
32.90	East bound lane I-80, bears N. 47 1/2° E. and S. 47 1/2° W.
33.574	Nevada Department of Transportation monument, an aluminum disc, 2 1/2 ins. diam., firmly set in concrete, 12 ins. diam., projecting 2 ins. above the ground, mkd. DIST 55.00 FT., STA OW 402+99.64 PC, bears South, 1.589 chs. dist.
34.10	West bound lane I-80, parallels east bound lane of I-80.
38.80	Paved frontage road, on curve, bears NW and SW.
39.60	Power pole line, bears N. 48 3/4° E. and S. 48 3/4° W.
40.790	<p>The center 1/4 sec. cor. of sec. 10.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 89°37'10" W., beginning new measurement.</p>
20.330	<p>Point for the C-W 1/16 sec. cor. of sec. 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>W 1/16</p> <p>C ————— C</p> <p>S10</p> <p>2004</p> </div>
40.660	<p>The 1/4 sec. cor. of secs. 9 and 10.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>From the E 1/16 sec. cor. of secs. 10 and 15.</p> <p>N. 0°04'40" W., on the N-S center line of the SE1/4 of sec. 10.</p>

SUBDIVISION OF SECTION 10,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Across bottom land.
13.564	Intersect the right bank of the avulsed channel of the Truckee River, from which Angle Point No. 1, sec. 10, bears N. 86°10'30" W., 0.003 chs. dist., hereinafter described.
14.529	Adjusted right bank of the Truckee River, bank bears N. 50°07'30" E. and S. 50°07'30" W.
15.745	Intersect the left bank of the avulsed channel of the Truckee River, from which the true point for a special meander cor. of sec. 10, bears S. 73°33'50" W., 2.506 chs. dist., hereinafter described.
17.137	Present left bank of the Truckee River, at the line of mean high water, bank bears N. 47°13'00" E. and S. 47°13'00" W.
17.874	Intersect the southeasterly right-of-way line of Union Pacific Railroad, on a line 100 ft. right angle distance from, and parallel to the observed centerline of the main track, bears N. 49°34'30" E. and S. 49°34'30" W., not monumented.
19.682	Union Pacific Railroad, observed centerline of main track, bears N. 49°34'30" E. and S. 49°34'30" W.
20.377	<p>The SE 1/16 sec. cor. of sec. 10, determined by Jon B. Loder, Nevada Professional Land Surveyor No. 10842, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set projecting 1 in. above the ground with a plastic cap, 1 1/2 ins. diam., mkd. LODER PLS 10842, as shown on an unrecorded plat and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S10</p> <p style="text-align: center;">2004</p> <p>Insert the rebar inside the stainless steel post.</p> <hr style="width: 20%; margin-left: 0;"/> <p>N. 0°04'40" W., beginning new measurement.</p> <p>Enter rolling land.</p>
20.376	<p>The C-E 1/16 sec. cor. of sec. 10.</p> <hr style="width: 50%; margin-left: 0;"/>



269

SUBDIVISION OF SECTION 10,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the S 1/16 sec. cor. of secs. 10 and 11.</p> <p>N. 89°27'30" W., on the E-W center line of the SE1/4 of sec. 10.</p> <p>Across bottom land.</p>
4.849	Intersect the right bank of the avulsed channel of the Truckee River, from which Angle Point No. 15, sec. 10, bears N. 1°32'20" W., 0.185 chs. dist., hereinafter described.
5.892	<p>The left bank of the avulsed channel of the Truckee River, bears N. and S. 1°39'30" W., point for Angle Point No. 14, sec. 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>S</p> <p>S ————— S</p> <p>10 / AP14</p> <p>LB</p> <p>2004</p> </div>
13.566	Adjusted right bank of the Truckee River, bank bears N. 56°59'20" E. and S. 56°59'20" W.
17.529	Intersect the southeasterly right-of-way of the Union Pacific Railroad at the end point of a line 100 ft. dist. and at right angle and parallel to the observed centerline of the main track, bears S. 49°34'30" W., falls in river, not monumented.
17.711	Present left bank of the Truckee River, at the line of mean high water, bank bears N. 45°56'20" E. and S. 45°56'20" W.
19.840	Union Pacific Railroad, observed centerline of main track, bears N. 49°34'30" E. and S. 49°34'30" W.
20.439	<p>The SE 1/16 sec. cor. of sec. 10.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°27'30" W., beginning new measurement.</p> <p>Enter rolling land.</p>
1.713	<p>Intersect the northwesterly right-of-way line of the Union Pacific Railroad, on a line 100 ft. dist. and at right angles and parallel to the observed centerline of the main track, bears N. 49°34'30" E. and S. 49°34'30" W.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a collar of stone with brass cap mkd.</p>

270

SUBDIVISION OF SECTION 10,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.439	The C-S 1/16 sec. cor. of sec. 10.
	<p style="text-align: center;">SUBDIVISION OF SECTION 11, T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 11 and 14.</p> <p>N. 0°13'50" W., on the N-S center line of sec. 11.</p> <p>Over rolling hills, covered with sagebrush and native grass.</p> <p>20.378 The C-S 1/16 sec. cor. of sec. 11, monumented with a boulder, 4x3x3 ft., with chisel marks X S 1/16 1945. This position has been adopted by adjacent land owners and professional land surveyors and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a brass tablet, 3 1/4 in. diam., with a 3 1/2 ins. stem, in a drill hole, in concrete, mkd.</p> <div style="text-align: center;">  </div> <p style="text-align: center;">2004</p> <p>An iron pipe, 2 1/2 ins. diam., 18 ins. long, with threaded metal cap mkd. AZCARATE 1/16 S11 1945 was found lying loose in a rock slide, W., 50 lks. dist.</p>
20.506	<p>N. 0°14'30" W., beginning new measurement.</p> <p>The center 1/4 sec. cor. of sec. 11, identical with Angle Point No. 11, of a metes-and-bounds survey in sec. 11, determined by David C. Brown, Nevada Professional Land Surveyor No. 8418, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set projecting 2 ins. above the ground, with a plastic cap, 1 1/2 ins. diam., mkd. PLS 8418, as recorded in Storey County, Nevada, File No. 77879, Record of Survey, in 1996 and is accepted as a careful and faithful determination of the position of the corner.</p>

271

SUBDIVISION OF SECTION 11,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, over a plastic-encased magnet, with brass
cap mkd.

T19N R21E
C 1/4 S11

2003

Insert the rebar inside the stainless steel post and raise a
mound of stone, 3 ft. base, 2 ft. high, W. of cor.

N. 0°14'20" W., beginning new measurement.

Enter bottom land.

17.868

A point on line, determined by David C. Brown, Nevada
Professional Land surveyor No. 8418, monumented with a rebar,
5/8 in. diam., 18 ins. long, firmly set projecting 2 ins. above
the ground with a plastic cap, 1 1/2 in. diam., mkd. PLS 8418,
as recorded in Storey County, Nevada, File No. 77879 Record
of Survey in 1996. This point will now function as the witness
cor. to a special meander cor. on the right bank of the Truckee
River.


At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, over a plastic-encased magnet, with brass
cap mkd.

WC

SMC

C



2004

Insert the rebar inside the stainless steel post.


N. 0°14'20" W., beginning new measurement.

SUBDIVISION OF SECTION 11,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
0.765	Point for the special meander cor. for the right bank of the Truckee River, bears NE, and S. 51°31'10" W., on the N-S center line of sec. 11, at record distance, based on the position determined by David C. Brown, Nevada Professional Land Surveyor No. 8418, as recorded in Storey County, Nevada, File No. 77077 Record of Survey in 1996. This position is accepted as a careful and faithful determination of the position of the corner. Point falls on bank where it is impractical to establish a permanent monument.
2.262	Point for the C-N 1/16 sec. cor. of sec. 11, falls in river, not monumented.
3.203	Present left bank of the Truckee River, at the line of mean high water, bank bears N. 61°49'50" E. and S. 61°49'50" W.
22.393	<p>The 1/4 sec. cor. of secs. 2 and 11.</p> <hr/> <p>From the 1/4 sec. cor. of sec. 11 and 12.</p> <p>N. 89°12'20" W., on the E-W center line of sec. 11.</p> <p>Over rolling hills covered with sagebrush and native grass.</p>
20.279	Point for the C-E 1/16 sec. cor. of sec. 11, not monumented.
40.558	<p>The center 1/4 sec. cor. of sec. 11, identical with Angle Point No. 11, of a metes-and-bounds survey in sec. 11.</p> <hr/> <p>N. 89°12'40" W., beginning new measurement.</p>
14.633	Intersect line 9-10, of a metes-and-bounds survey in sec. 11, from which Angle Point No. 9, hereinafter described, bears S. 57°23'10" W., 6.257 chs. dist.
20.270	<p>Point for the C-W 1/16 sec. cor. of sec. 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>W 1/16</p> <p>C ——— C</p> <p>S11</p> <p>2003</p> </div> <p>Set a carsonite post, 6 ft. long alongside the stainless steel post.</p>


273

SUBDIVISION OF SECTION 11,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
23.769	<p>Point selected for a witness cor. to the special meander cor. on the E-W center line of sec. 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC</p>  <p>SMC C S C 11</p> </div> <p>2004</p>
23.869	<p>Intersect the adjusted meanders for the right bank of the Truckee River, bears N. 19°30'10" E. and S. 19°30'10" W. Point for the special meander cor. on the E-W center line of sec. 11, falls on bank where it is impractical to establish a permanent monument.</p>
25.938	<p>Left bank of the Truckee River, at the line of mean high water, bank bears N. 27°34'10" E. and S. 27°34'10" W.</p>
38.63	<p>Union Pacific Railroad, observed centerline of main track, bears NE and SW.</p>
40.540	<p>The 1/4 sec. cor. of secs. 10 and 11.</p>
	<hr/> <p>From the point for the C-E 1/16 sec. cor. of sec. 11.</p> <p>N. 0°19'50" W., on the N-S center line of the NE1/4 of sec. 11.</p> <p>Over rolling hills covered with sagebrush and native grass.</p>
20.080	<p>The NE 1/16 sec. cor. of sec. 11, determined by David C. Brown, Nevada Professional Land Surveyor No. 8418, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set in a collar of stone, with a plastic cap, 1 1/2 ins. diam., mkd. PLS 8418, as recorded in Storey County Nevada, File No. 77879 and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

274

SUBDIVISION OF SECTION 11,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">NE 1/16 S11</p> <p style="text-align: center;">2003</p> <p>Insert the rebar inside the stainless steel post and raise a mound of stone, 3 ft. diam., 2 ft. high, W. of cor.</p> <hr/> <p>N. 0°19'50" W., beginning new measurement.</p> <p>20.080 The E 1/16 sec. cor. of secs. 2 and 11.</p> <hr/> <p>From the point for the N 1/16 sec. cor. of secs. 11 and 12.</p> <p>N. 89°03'40" W., on the E-W center line of the NE1/4 of sec. 11.</p> <p>Over rolling land, covered with sagebrush and native grass.</p> <p>20.246 The NE 1/16 sec. cor. of sec. 11.</p> <hr/> <p>N. 89°03'40" W., beginning new measurement.</p> <p>17.519 A point on line, determined by David C. Brown, Nevada Professional Land Surveyor No. 8418, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set 2 ins. below the surface of the ground, with a plastic cap, 1 1/2 ins. diam., mkd. PLS 8418, as recorded in Storey County, Nevada, File No. 77879, Record of Survey in 1996. This point will now function as the witness cor. to the special meander cor. on the right bank of the Truckee River.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC</p>  </div> <p style="text-align: center;">2004</p> <p>Set a carsonite post, 5 ft. long alongside the stainless steel post.</p> <hr/> <p>N. 89°03'40" W., beginning new measurement.</p>
--------	--

275

SUBDIVISION OF SECTION 11,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
0.701	<p>Point for the special meander cor. on the E-W center line of the NE1/4 of sec. 11, for the right bank of the Truckee River, bears N. 57°54'20" E. and SW, at proportionate distance, based on the position determined by David C. Brown, Nevada Professional Land Surveyor No. 8418, as recorded in Storey County, Nevada, File No. 77077, Record of Survey in 1996. This position is accepted as a careful and faithful determination of the position of the corner. Point falls on bank where it is impractical to establish a permanent monument.</p>
2.727	<p>The point for the C-N 1/16 sec. cor. of sec. 11.</p> <hr/> <p>From the W 1/16 sec. cor. of secs. 11 and 14.</p> <p>N. 0°12'40" W., on the N-S center line of the SW1/4 of sec. 11.</p> <p>Across active gravel pit.</p>
20.421	<p>The SW 1/16 sec. cor. of sec. 11, determined by David C. Brown, Nevada Professional Land Surveyor No. 8418, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set 12 ins. below the surface of the ground with a plastic cap, 1 1/2 ins. diam., mkd. PLS 8414, as recorded in Storey County, Nevada, File No. 77879, Record of Survey in 1996 and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. below the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SW 1/16 S11</p> <p style="text-align: center;">2004</p> <p>Insert the rebar inside the stainless steel post.</p> <hr/> <p>N. 0°12'40" W., beginning new measurement.</p>
7.935	<p>Intersect line 7-8, of a metes-and-bounds survey in sec. 11, from which Angle Point No. 7, hereinafter described, bears S. 41°49'20" W., 4.554 chs. dist.</p> <p>Leave active gravel pit; enter bottom land.</p>
20.485	<p>The C-W 1/16 sec. cor. of sec. 11.</p> <hr/>

276

SUBDIVISION OF SECTION 11,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA


CHAINS	<p>From the C-S 1/16 sec. cor. of sec. 11.</p> <p>N. 89°09'10" W., on the E-W center line of the SW1/4 of sec. 11.</p> <p>Across active gravel pit.</p>
20.283	<p>The SW 1/16 sec. cor. of sec. 11.</p> <hr/> <p>N. 89°09'30" W., beginning new measurement.</p>
7.026	<p>Intersect line 6-7 of a metes-and-bounds survey in sec. 11, from which Angle Point No. 6, hereinafter described, bears S. 41°44'30" W., 2.268 chs. dist.</p>
20.277	<p>The S 1/16 sec. cor. of secs. 10 and 11.</p> <hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 15, T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 15 and 22.</p> <p>N. 0°09'40" E., on the N-S center line of sec. 15.</p> <p>Over rolling hills, covered with sage brush and native grass.</p>
42.104	<p>The center 1/4 sec. cor. of sec. 15, determined by Brett K. Jefferson, Nevada Professional Land Surveyor No. 8421, monumented with a rebar, 5/8 in. diam., set 3 ins. below the surface of a cultivated field, with an aluminum cap, 2 ins. diam., mkd. "T19N R21E C1/4 S15 PLS 8421 1999", as filed in Washoe County, Nevada, File No. 2305060, Corner Record and is accepted as a careful and faithful determination of the position of the corner.</p> <hr/> <p>N. 0°09'30" E., beginning new measurement.</p>
7.50	<p>Paved road, bears NNE and SSW.</p>
20.209	<p>The C-N 1/16 sec. cor. of sec. 15, determined by Brett K. Jefferson, Nevada Professional Land Surveyor No. 8421, monumented with a rebar, 5/8 in. diam., set flush with the ground with an aluminum cap, 2 ins. diam., mkd. PLS 8421 C-N1/16 S15 1999, as recorded in Storey County, Nevada, File No. 84354, Corner Record and is accepted as a careful and faithful determination of the corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

277

SUBDIVISION OF SECTION 15,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div data-bbox="834 264 997 348" data-label="Text"> <p style="text-align: center;">C N 1/16 S15 C</p> </div> <div data-bbox="899 384 964 407" data-label="Text"> <p style="text-align: center;">2003</p> </div> <div data-bbox="412 445 1062 468" data-label="Text"> <p>Insert rebar in the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> </div> <div data-bbox="412 533 1078 556" data-label="Text"> <p>N. 0°10'00" E., beginning new measurement.</p> </div> <div data-bbox="282 594 1435 648" data-label="Text"> <p>8.330 Point selected for the witness cor. to the special meander cor. of sec. 15, on the N-S center line of sec. 15.</p> </div> <div data-bbox="412 686 1435 770" data-label="Text"> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> </div> <div data-bbox="850 806 980 1005" data-label="Diagram"> </div> <div data-bbox="899 1043 964 1066" data-label="Text"> <p style="text-align: center;">2004</p> </div> <div data-bbox="282 1104 1435 1188" data-label="Text"> <p>8.845 Intersect the adjusted meanders of the right bank of the Truckee River, bears N. 23°20'20" E. and S. 23°20'20" W. Point for the special meander cor. on the N-S center line of sec. 15.</p> </div> <div data-bbox="266 1226 1435 1369" data-label="Text"> <p>13.784 Left bank of the Truckee River, at the line of mean high water, bank bears N. 19°05'10" E. and S. 19°05'10" W., point for the special meander cor., of sec. 15, on the N-S center line of sec. 15, falls on bank where it is impractical to establish a permanent monument.</p> </div> <div data-bbox="266 1407 1435 1461" data-label="Text"> <p>14.193 Point selected for the witness cor. to the special meander cor. on the N-S center line of sec. 15.</p> </div> <div data-bbox="412 1499 1435 1583" data-label="Text"> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> </div> <div data-bbox="883 1619 1021 1797" data-label="Diagram"> </div> <div data-bbox="899 1827 964 1850" data-label="Text"> <p style="text-align: center;">2004</p> </div>
--------	---


SUBDIVISION OF SECTION 15,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
14.541	<p>Intersect a line parallel and concentric with and 200 ft. dist. from the observed centerline of main track of the Union Pacific Railroad, bears N. 39°35'30" E. and S. 39°35'30" W.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>WP</p>  <p>2003</p> </div>
19.315	Union Pacific Railroad, observed centerline of main track.
20.207	<p>The 1/4 sec. cor. of secs. 10 and 15, hereinbefore described.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 14 and 15.</p> <p>N. 89°48'00" W., on the E-W center line of sec. 15.</p> <p>Over rolling hills covered with sagebrush and native grass.</p>
20.959	<p>The C-E 1/16 sec. cor. of sec. 15, determined by person(s) unknown, monumented with a copper pipe, 1/8 in. diam., firmly set in a mound of stone, 3 ft. base. This is accepted as a careful and faithful determination of the position of the corner.</p> <hr/>
20.928	<p>N. 89°45'10" W., beginning new measurement.</p> <p>The center 1/4 sec. cor. of sec. 15.</p> <hr/> <p>N. 89°46'50" W., beginning new measurement.</p> <p>Across bottom land.</p>
2.60	Paved road, bears NNE and SSW.
3.20	Right bank of the Truckee River, bears NNE and SSW.
5.90	Left bank of the Truckee River, bears NNE and SSW.

SUBDIVISION OF SECTION 15,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
19.966	<p>The C-W 1/16 sec. cor. of sec. 15, determined by Brett K. Jefferson, Nevada Professional Land Surveyor No. 8421, monumented with a rebar, firmly set projecting, 3 ins. above the ground, with an aluminum cap, 2 ins. diam. mkd. LS 8421 C-W1/16 S15 1999, as recorded in Washoe County, Nevada, File No. 2305061, Corner Record and is accepted as a careful and faithful determination of the position of the corner.</p> <hr/> <p>N. 89°48'30" W., beginning new measurement.</p>
19.978	<p>The 1/4 sec. cor. of secs. 15 and 16.</p> <hr/> <p>From the N 1/16 sec. cor. of secs. 14 and 15.</p> <p>N. 89°31'30" W., on the E-W center line of the NE1/4 of sec. 15.</p> <p>Over rolling land, covered with sagebrush and native grass.</p>
20.870	<p>The NE 1/16 sec. cor. of sec. 15, determined by person(s) unknown, monumented with a copper pipe, 1/2 in. diam., firmly set in a mound of stone, 3 ft. base. This position has been adopted by various professional land surveyors as indicated on survey records recorded in Storey County, Nevada, and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S15</p> <p style="text-align: center;">2004</p> <p>Insert the copper pipe inside the stainless steel post.</p> <hr/> <p>N. 89°27'30" W., beginning new measurement.</p> <p>Enter bottom land.</p>
18.40	<p>Paved road, bears NNE, and SSW.</p>
20.854	<p>The C-N 1/16 sec. cor. of sec. 15.</p> <hr/> <p>From the C-W 1/16 sec. cor. of sec. 15.</p> <p>N. 0°17'20" W., on the N-S center line of the NW1/4 of sec. 15.</p>

SUBDIVISION OF SECTION 15,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Over gently rolling land, covered with sagebrush and native grass.
15.548	Union Pacific Railroad, observed centerline of main track, bears NE and SW.
20.248	<p>The NW 1/16 sec. cor. of sec. 15, determined by Ronald L. Cooper, Nevada Professional Land Surveyor No. 3919, monumented with a PK nail, firmly set on a granite slab, with a metal washer, 1 in. diam., mkd. 3919, as recorded in Washoe County, Nevada, File No. 516741, Record of Survey and is accepted as a careful and faithful determination of the corner.</p> <p>At the corner point</p> <p>Set a brass tablet, 3 1/2 ins. diam., cemented in drill hole, mkd.</p> <p style="text-align: center;">NW 1/16 S15</p> <p style="text-align: center;">2003</p> <p>Deposit PK nail and washer in drill hole.</p> <hr style="width: 30%; margin-left: auto; margin-right: auto;"/> <p>N. 0°16'30" W., beginning new measurement.</p>
20.265	<p>The W 1/16 sec. cor. of secs. 10 and 15.</p> <hr style="width: 60%; margin-left: 0;"/> <p>From the C-N 1/16 sec. cor. of sec. 15.</p> <p>N. 89°40'20" W., on the E-W center line of the NW1/4 of sec. 15.</p> <p>Over gently rolling land, covered with sagebrush and native grass.</p>
1.512	<p>Point selected for the witness cor. to the special meander cor. of sec. 15, on the E-W center line of the NW1/4 of sec. 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;">  </div> <p style="text-align: center;">2004</p>




SUBDIVISION OF SECTION 15,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
1.657	<p>Point for the special meander cor. for the right bank of the Truckee River, bears N. 12°25'40" E. and SW, on the E-W center line of the NW1/4 of sec. 15, at proportionate distance, based on the position determined by David C. Brown, Nevada Professional Land Surveyor No. 8418, as recorded in Storey County, Nevada, File No. 77077 Record of Survey in 1996. This position is accepted as a careful and faithful determination of the position of the corner. Point falls on bank where it is impractical to establish a permanent monument.</p>
3.391	<p>Left bank of the Truckee River, at the line of mean high water, bank bears N. 7°06'40" E. and SW, point for the special meander cor. of sec. 15, on the E-W center line of the NW1/4 of sec. 15, falls on bank where it is impractical to establish a permanent monument.</p>
3.538	<p>Point selected for a witness cor. to the special meander cor. of sec. 15, on the E-W center line of the NW1/4 of sec. 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="787 993 1068 1140" data-label="Diagram"> <p>The diagram shows a horizontal line representing the E-W center line of the NW1/4 of sec. 15. A point on this line is labeled 'N' and '15'. A line segment labeled 'WC' (Witness Corner) branches off to the right from this point. Another line segment labeled 'SMC' (Special Meander Corner) branches off to the right from the same point. A small 'S' is written above the horizontal line, and a '15' is written below it.</p> </div> <p style="text-align: center;">2004</p>
11.924	<p>Intersect a line parallel and concentric with and 200 ft. dist., from the existing centerline of the observed main track of the Union Pacific Railroad, bears N. 39°35'30" E. and SW.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="836 1476 1052 1623" data-label="Diagram"> <p>The diagram shows a horizontal line representing the E-W center line of the NW1/4 of sec. 15. A point on this line is labeled 'N' and '15'. A line segment labeled 'WP' (Witness Point) branches off to the right from this point. Another line segment labeled 'SMC' (Special Meander Corner) branches off to the right from the same point. A small 'S' is written above the horizontal line, and a '15' is written below it.</p> </div> <p style="text-align: center;">2003</p>
15.837	<p>Union Pacific Railroad, observed centerline of main track, bears NE and SW.</p>
19.790	<p>Intersect a line parallel and concentric with and 200 ft. dist., from the existing centerline of the observed main track of the Union Pacific Railroad, in spiral curve.</p>




SUBDIVISION OF SECTION 15,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<div data-bbox="836 394 1047 604" data-label="Diagram"> </div>
20.123	<p>The NW 1/16 sec. cor. of sec. 15.</p> <hr/> <p>N. 89°38'20" W., beginning new measurement.</p>
20.129	<p>The N 1/16 sec. cor. of secs. 15 and 16.</p> <hr/> <p>SURVEY OF THE AVULSED CHANNEL OF THE TRUCKEE RIVER, IN SECTION 10, T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the point for the special meander cor. of sec. 10, on the right bank of the avulsed channel of the Truckee River, at intersection with the adjusted right bank of the Truckee River, adjusted bank bears N. 50°07'30" E., and S. 50°07'30" W. Falls on bank where it is impractical to establish a permanent monument.</p> <p>S. 76°54'40" E., along the right bank of the avulsed channel of the Truckee River.</p>
0.270	<p>Point selected for the witness cor. to the special meander cor. of sec. 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="868 1539 1015 1749" data-label="Diagram"> </div>
0.926	<p>Point for Angle Point No. 1, sec. 10, on the right bank of the avulsed channel of the Truckee River.</p>

SURVEY OF THE AVULSED CHANNEL OF THE TRUCKEE RIVER,
IN SECTION 10,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA




CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="834 381 1057 555" style="text-align: center;"> <p>RB AP 1</p>  <p>S10</p> <p>2004</p> </div> <hr/> <p>S. 86°10'30" E., on line 1-2, along the right bank of the avulsed channel of the Truckee River.</p> <p>0.003 Intersect the N-S center line of the SE1/4 of sec. 10, from which the SE 1/16 sec. cor., hereinbefore described, bears N. 0°04'40" W., 6.813 chs. dist.</p> <p>1.343 Point for Angle Point No. 2, sec. 10, on the right bank of the avulsed channel of the Truckee River.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="842 1033 974 1207" style="text-align: center;"> <p>RB AP 2</p>  <p>S10</p> <p>2004</p> </div> <hr/> <p>S. 18°06'40" E., on line 2-3, along the right bank of the avulsed channel of the Truckee River.</p> <p>1.367 Point for Angle Point No. 3, sec. 10, on the right bank of the avulsed channel of the Truckee River.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="891 1554 1036 1742" style="text-align: center;"> <p>RB AP 3</p>  <p>S10</p> <p>2004</p> </div> <hr/> <p>S. 73°06'00" E., on line 3-4, along the right bank of the avulsed channel of the Truckee River.</p>
--------	---

SURVEY OF THE AVULSED CHANNEL OF THE TRUCKEE RIVER,
IN SECTION 10,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA




CHAINS	
1.594	<p>Point for Angle Point No. 4, sec. 10, on the right bank of the avulsed channel of the Truckee River.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;">  </div> <hr style="width: 30%; margin: 10px auto;"/> <p>S. 26°44'30" E., on line 4-5, along the right bank of the avulsed channel of the Truckee River.</p>
2.022	<p>Point for Angle Point No. 5, sec. 10, on the right bank of the avulsed channel of the Truckee River.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;">  </div> <hr style="width: 30%; margin: 10px auto;"/> <p>S. 52°31'30" E., on line 5-6, along the right bank of the avulsed channel of the Truckee River.</p>
2.341	<p>Point for Angle Point No. 6, sec. 10, on the right bank of the avulsed channel of the Truckee River.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;">  </div> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 83°58'10" E., on line 6-7, along the right bank of the avulsed channel of the Truckee River.</p>

285

SURVEY OF THE AVULSED CHANNEL OF THE TRUCKEE RIVER,
IN SECTION 10,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA




CHAINS	
2.446	<p>Point for Angle Point No. 7, sec. 10, on the right bank of the avulsed channel of the Truckee River.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;">  <p>RB AP 7 S10 2004</p> </div> <hr/> <p>N. 61°09'00" E., on line 7-8, along the right bank of the avulsed channel of the Truckee River.</p>
2.359	<p>Point for Angle Point No. 8, sec. 10, on the right bank of the avulsed channel of the Truckee River.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;">  <p>RB AP 8 S10 2004</p> </div> <hr/> <p>N. 21°02'30" E., on line 8-9, along the right bank of the avulsed channel of the Truckee River.</p>
1.585	<p>Point for Angle Point No. 9, sec. 10, on the right bank of the avulsed channel of the Truckee River.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;">  <p>RB AP 9 S10 2004</p> </div> <hr/> <p>N. 45°44'10" E., on line 9-10, along the right bank of the avulsed channel of the Truckee River.</p>

SURVEY OF THE AVULSED CHANNEL OF THE TRUCKEE RIVER,
IN SECTION 10,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
3.521	<p>Point for Angle Point No. 10, sec. 10, on the right bank of the avulsed channel of the Truckee River.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;">  </div> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 47°12'30" E., on line 10-11, along the right bank of the avulsed channel of the Truckee River.</p>
2.455	<p>Point for Angle Point No. 11, sec. 10, on the right bank of the avulsed channel of the Truckee River.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;">  </div> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 10°28'40" E., on line 11-12, along the right bank of the avulsed channel of the Truckee River.</p>
0.912	<p>Point for Angle Point No. 12, sec. 10, on the right bank of the avulsed channel of the Truckee River.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;">  </div> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 67°08'10" W., on line 12-13, along the right bank of the avulsed channel of the Truckee River.</p>
0.886	<p>Point for Angle Point No. 13, sec. 10, on the right bank of the avulsed channel of the Truckee River.</p>




287

SURVEY OF THE AVULSED CHANNEL OF THE TRUCKEE RIVER,
IN SECTION 10,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;">  <p>RB AP13 S10</p> <p>2004</p> </div> <hr/> <p>N. 17°29'30" E., on line 13-14, along the right bank of the avulsed channel of the Truckee River.</p> <p>2.699 Point for Angle Point No. 14, sec. 10, on the right bank of the avulsed channel of the Truckee River.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;">  <p>RB AP14 S10</p> <p>2004</p> </div> <hr/> <p>N. 1°32'20" W., on line 14-15, along the right bank of the avulsed channel of the Truckee River.</p> <p>0.932 Intersect the E-W center line of the SW1/4 of sec. 10, from which the S 1/16 sec. cor. of secs. 10 and 11, hereinbefore described, bears S. 89°27'20" E., 4.849 chs. dist.</p> <p>1.117 Point for Angle Point No. 15, sec. 10, on the right bank of the avulsed channel of the Truckee River.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;">  <p>RB AP15 S10</p> <p>2004</p> </div> <hr/> <p>N. 34°42'30" W., on line 15-16, along the right bank of the avulsed channel of the Truckee River.</p> <p>0.749 Point for Angle Point No. 16, sec. 10, on the right bank of the avulsed channel of the Truckee River.</p>
--------	--

288


SURVEY OF THE AVULSED CHANNEL OF THE TRUCKEE RIVER,
IN SECTION 10,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;">  </div> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 0°37'10" E., on line 16-17, along the right bank of the avulsed channel of the Truckee River.</p>
2.580	<p>Point selected for the witness cor. to Angle Point 17.</p> <div style="text-align: center;">  </div>
3.286	<p>Point for Angle Point No. 17, sec. 10, on the right bank of the avulsed channel of the Truckee River, identical with a point on the adjusted right bank of the existing channel of the Truckee River, bears N. 69°00'30" E. and S. 69°00'30" W. Falls in river where it is impractical to establish a permanent monument.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 3°30'00" W., on line 17-18, across existing river, and along the right bank of the avulsed channel of the Truckee River.</p>
1.948	<p>Point for Angle Point No. 18, sec. 10, on the right bank of the avulsed channel of the Truckee River, identical with a point on the left bank of the existing channel of the Truckee River, at the line of mean high water, bank bears N. 69°52'40" E. and S. 69°52'40" W.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;">  </div> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 28°29'50" E., on line 18-19, along the right bank of the avulsed channel of the Truckee River.</p>
2.357	<p>Point for Angle Point No. 19, sec. 10, on the right bank of the avulsed channel of the Truckee River.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

289

SURVEY OF THE AVULSED CHANNEL OF THE TRUCKEE RIVER,
IN SECTION 10,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS




RB
AP19
S10
2004

N. 41°40'20" E., on line 19-20, along the right bank of the avulsed channel of the Truckee River.

1.806 Point for Angle Point No. 20, sec. 10, on the right bank of the avulsed channel of the Truckee River.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.



RB
AP20
S10
2004


N. 42°54'10" E., on line 20-21, along the right bank of the avulsed channel of the Truckee River.

4.400 Angle Point No. 21, sec. 10 identical with Angle Point No. 1, sec. 11, on the right bank of the avulsed channel of the Truckee River, hereinbefore described.

From the point for the special meander cor. of sec. 10, on the left bank of the avulsed channel of the Truckee River, at intersection with the present left bank of the Truckee River, at the line of mean high water, present bank bears N. 54°08'20" E. and S. 54°08'20" W. Falls on bank where it is impractical to establish a permanent monument.



From this point the point selected for the off-line witness cor. to the special meander cor. of sec. 10, bears N. 0°05'30" E., 0.491 chs. dist.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.



WC
SMC
S10
2004

SURVEY OF THE AVULSED CHANNEL OF THE TRUCKEE RIVER,
IN SECTION 10,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA




CHAINS	N. 73°33'50" E., across present river, and along the left bank of the avulsed channel of the Truckee River.
2.506	Intersect the N-S center line of the SE1/4 of sec. 10, from which the SE 1/16 sec. cor. of sec. 10 bears N. 0°04'40" W., 4.632 chs. dist., hereinbefore described.
4.759	Point for Angle Point No. 1, sec. 10, on the left bank of the avulsed channel of the Truckee River, and at intersection with the adjusted right bank of the existing channel of the Truckee River. Falls on bank where it is impractical to establish a permanent monument.
	<hr/> <p>S. 75°47'20" E., on line 1-2, along the left bank of the avulsed channel of the Truckee River, at the apparent line of mean high water.</p>
0.734	<p>Point selected for the witness cor. to Angle Point No. 1, sec. 10, on the left bank of the avulsed channel of the Truckee River.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC S10</p>  <p>AP 1 LB</p> <p>2004</p> </div>
2.042	<p>Point for Angle Point No. 2, sec. 10, on the left bank of the avulsed channel of the Truckee River.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>S10</p>  <p>AP 2 LB</p> <p>2004</p> </div>
	<hr/> <p>S. 88°39'00" E., on line 2-3, along the left bank of the avulsed channel of the Truckee River.</p>
0.597	Point for Angle Point No. 3, sec. 10, on the left bank of the avulsed channel of the Truckee River.

291




SURVEY OF THE AVULSED CHANNEL OF THE TRUCKEE RIVER,
IN SECTION 10,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="824 386 987 562" style="text-align: center;"> <p>S10 AP 3 LB 2004</p> </div> <hr style="width: 30%; margin: 10px auto;"/> <p>S. 24°10'10" E., on line 3-4, along the left bank of the avulsed channel of the Truckee River.</p> <p>0.499 Point for Angle Point No. 4, sec. 10, on the left bank of the avulsed channel of the Truckee River.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="834 903 1013 1041" style="text-align: center;"> <p>LB AP 4 S10 2004</p> </div> <hr style="width: 30%; margin: 10px auto;"/> <p>S. 72°05'30" W., on line 4-5, along the left bank of the avulsed channel of the Truckee River.</p> <p>0.670 Point for Angle Point No. 5, sec. 10, on the left bank of the avulsed channel of the Truckee River.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="850 1407 1013 1549" style="text-align: center;"> <p>LB AP 5 S10 2004</p> </div> <hr style="width: 30%; margin: 10px auto;"/> <p>S. 4°12'00" E., on line 5-6, along the left bank of the avulsed channel of the Truckee River.</p> <p>3.769 Point for Angle Point No. 6, sec. 10, on the left bank of the avulsed channel of the Truckee River.</p>
--------	---

SURVEY OF THE AVULSED CHANNEL OF THE TRUCKEE RIVER,
IN SECTION 10,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p>	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;">  </div> <hr/> <p>S. 25°50'00" E., on line 6-7, along the left bank of the avulsed channel of the Truckee River.</p> <p>1.176 Point for Angle Point No. 7, sec. 10, on the left bank of the avulsed channel of the Truckee River.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;">  </div> <hr/> <p>S. 58°04'20" E., on line 7-8, along the left bank of the avulsed channel of the Truckee River.</p> <p>0.630 Point for Angle Point No. 8, sec. 10, on the left bank of the avulsed channel of the Truckee River.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;">  </div> <hr/> <p>N. 80°31'20" E., on line 8-9, along the left bank of the avulsed channel of the Truckee River.</p> <p>1.679 Point for Angle Point No. 9, sec. 10, on the left bank of the avulsed channel of the Truckee River.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
---------------	--

SURVEY OF THE AVULSED CHANNEL OF THE TRUCKEE RIVER,
IN SECTION 10,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	 <p style="text-align: center;">S10 AP 9 LB 2004</p>
3.098	<p>N. 65°32'30" E., on line 9-10, along the left bank of the avulsed channel of the Truckee River.</p> <p>Point for Angle Point No. 10, sec. 10, on the left bank of the avulsed channel of the Truckee River.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	 <p style="text-align: center;">S10 AP10 LB 2004</p>
3.404	<p>N. 45°44'30" E., on line 10-11 along the left bank of the avulsed channel of the Truckee River.</p> <p>Point for Angle Point No. 11, sec. 10, on the left bank of the avulsed channel of the Truckee River.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	 <p style="text-align: center;">S10 AP11 LB 2004</p>
2.170	<p>N. 35°29'40" E., on line 11-12, along the left bank of the avulsed channel of the Truckee River.</p> <p>Point for Angle Point No. 12, sec. 10, on the left bank of the avulsed channel of the Truckee River.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

294

SURVEY OF THE AVULSED CHANNEL OF THE TRUCKEE RIVER,
IN SECTION 10,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA


CHAINS	<div data-bbox="888 275 1057 447" data-label="Diagram"> </div> <div data-bbox="436 512 1471 569" data-label="Text"> <p>N. 17°47'30" E., on line 12-13, along the left bank of the avulsed channel of the Truckee River.</p> </div> <div data-bbox="307 604 1471 661" data-label="Text"> <p>2.197 Point for Angle Point No. 13, sec. 10, on the left bank of the avulsed channel of the Truckee River.</p> </div> <div data-bbox="436 693 1471 783" data-label="Text"> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> </div> <div data-bbox="888 793 1047 959" data-label="Diagram"> </div> <div data-bbox="436 1024 1471 1081" data-label="Text"> <p>N. 1°39'30" E., on line 13-14, along the left bank of the avulsed channel of the Truckee River.</p> </div> <div data-bbox="307 1117 1471 1203" data-label="Text"> <p>2.392 Angle Point No. 14, sec. 10, on the left bank of the avulsed channel of the Truckee River and the E-W center line of the SE1/4 of sec. 10, hereinbefore described.</p> </div> <div data-bbox="518 1266 1389 1352" data-label="Section-Header"> <hr/> <p style="text-align: center;">SURVEY OF THE RIGHT BANK OF THE AVULSED CHANNEL OF THE TRUCKEE RIVER, IN SECTION 11, T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> </div> <div data-bbox="436 1415 1471 1505" data-label="Text"> <p>From Angle Point No. 1, sec. 11, identical with Angle Point No. 21, sec. 10, on the right bank of the avulsed channel of the Truckee River, hereinbefore described.</p> </div> <div data-bbox="436 1537 1471 1596" data-label="Text"> <p>N. 86°07'40" E., on line 1-2, along the right bank of the avulsed channel of the Truckee River.</p> </div> <div data-bbox="307 1627 1471 1686" data-label="Text"> <p>2.896 Point for Angle Point No. 2, sec. 11, on the right bank of the avulsed channel of the Truckee River.</p> </div> <div data-bbox="436 1717 1471 1808" data-label="Text"> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> </div>
--------	--

SURVEY OF THE RIGHT BANK OF THE AVULSED CHANNEL OF THE
TRUCKEE RIVER, IN SECTION 11,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<div data-bbox="865 304 1003 478" data-label="Diagram"> </div>
1.609	<p>S. 58°29'50" E., on line 2-3, along the right bank of the avulsed channel of the Truckee River.</p> <p>Point for Angle Point No. 3, sec. 11, on the right bank of the avulsed channel of the Truckee River.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="841 846 1011 1020" data-label="Diagram"> </div>
1.368	<p>S. 30°40'40" E., on line 3-4, along the right bank of the avulsed channel of the Truckee River.</p> <p>Point for Angle Point No. 4, sec. 11, on the right bank of the avulsed channel of the Truckee River, at intersection with the present left bank of the Truckee River, bank bears S. 68°11'00" E. and N. 61°32'00" W.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="881 1417 1027 1560" data-label="Diagram"> </div>
1.470	<p>S. 14°30'00" E., on line 4-5, across present river and along the right bank of the avulsed channel of the Truckee River.</p> <p>Point for Angle Point No. 5, sec. 11, on the right bank of the avulsed channel of the Truckee River. Falls in river, not monumented.</p> <p>S. 6°23'20" W., on line 5-6, along the right bank of the avulsed channel of the Truckee River.</p>

296

SURVEY OF THE RIGHT BANK OF THE AVULSED CHANNEL OF THE
TRUCKEE RIVER, IN SECTION 11,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p>	<p>1.385 Point for Angle Point No. 6, sec. 11, on the right bank of the avulsed channel of the Truckee River. Falls in river, not monumented.</p> <hr/> <p>S. 64°49'50" E., on line 6-7, along the right bank of the avulsed channel of the Truckee River.</p> <p>1.345 Point for a special meander cor. of sec. 11, on the right bank of the avulsed channel of the Truckee River, and at intersection with the adjusted right bank of the Truckee River, bank bears N. 57°16'30" E. and S. 57°16'30" W.</p> <p>From this point the off-line witness cor. to the special meander cor. of sec. 11, bears N. 69°16'30" E., 2.454 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;">  <p>WC</p> <p>SMC</p> <p>RB</p> <p>S11</p> <p>2004</p> </div> <hr/> <p style="text-align: center;">SURVEY OF A PORTION OF THE MEANDERS OF THE RIGHT BANK OF THE TRUCKEE RIVER, T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of the meanders of the right bank of the Truckee River surveyed by David C. Brown, Nevada Professional Land Surveyor No. 8418, as recorded in Storey County, Nevada, File No. 77879, Record of Survey in 1996, adjusted by rotation from grid to true north.</p> <hr/> <p>From the true point for the special meander cor., on the E-W center line of the NW1/4 of sec. 15 and the right bank of the Truckee River, hereinbefore described.</p> <p>Thence downstream with the adjusted meanders of the right bank of the Truckee River, in sec. 15.</p> <p>N. 12°25'40" E., 0.553 chs.</p> <p>N. 9°25'10" E., 2.395 chs.</p>
---------------	--

297

SURVEY OF A PORTION OF THE MEANDERS
OF THE RIGHT BANK OF THE TRUCKEE RIVER,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	N. 3°24'30" E., 1.719 chs.
	N. 5°52'30" E., 1.648 chs.
	N. 16°28'30" E., 1.606 chs.
	N. 23°20'20" E., 1.292 chs.
	<p>At 1.129 chs., the true point for the special meander cor. of sec. 15, on the N-S center line of sec. 15, hereinbefore described, from which the C-N 1/16 sec cor. of sec. 15, bears S. 0°10'00" W., 8.845 chs. dist., hereinbefore described.</p>
	N. 22°02'20" E., 2.103 chs.
	N. 21°38'20" E., 2.923 chs.
	N. 23°01'30" E., 1.756 chs.
	N. 30°24'20" E., 2.598 chs.
	N. 36°32'10" E., 3.249 chs.
	<p>At end of course, the meander cor. of secs. 10 and 15, hereinbefore described.</p>
	<hr/>
	Thence in sec. 10.
	N. 36°32'10" E., 2.904 chs.
	N. 37°58'20" E., 2.721 chs.
	N. 35°31'30" E., 1.804 chs.
	N. 40°49'50" E., 2.787 chs.
	N. 50°27'10" E., 1.722 chs.
	N. 51°59'40" E., 1.721 chs.
	N. 55°01'10" E., 2.208 chs.
	N. 56°46'20" E., 1.497 chs.
	N. 53°51'00" E., 1.761 chs.

SURVEY OF A PORTION OF THE MEANDERS
OF THE RIGHT BANK OF THE TRUCKEE RIVER,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>N. 50°07'30" E., 0.366 chs. At end of course, the true point for the special meander cor. of sec. 10, on the right bank of the avulsed channel of the Truckee River, hereinbefore described.</p> <hr/> <p>Continue on an informative traverse of the adjusted right bank of the Truckee River, in sec. 10.</p> <p>N. 50°07'30" E., 2.813 chs. At 1.178 chs., intersect the N-S center line of the SE1/4 of sec. 10, from which the SE 1/16 sec. cor. of sec. 10, bears N. 0°04'40" W., 5.848 chs. dist., hereinbefore described.</p> <p>N. 48°20'10" E., 4.950 chs. At 1.211 chs., the true point for Angle Point No. 1, sec. 10, on the left bank of the avulsed channel of the Truckee River, hereinbefore described.</p> <p>N. 51°52'50" E., 1.904 chs.</p> <p>N. 56°59'20" E., 2.513 chs. At 0.496 chs., intersect the E-W center line of the SE1/4 of sec. 10, from which the SE 1/16 sec. cor. of sec. 10, bears N. 89°27'30" W., 6.873 chs. dist., hereinbefore described.</p> <p>N. 63°54'20" E., 1.771 chs.</p> <p>N. 64°45'10" E., 1.755 chs.</p> <p>N. 67°13'30" E., 1.643 chs.</p> <p>N. 69°00'30" E., 2.554 chs. At 2.078 chs., the true point for Angle Point No. 17, sec. 10, on the right bank of the avulsed channel of the Truckee River, hereinbefore described.</p>
--------	---

SURVEY OF A PORTION OF THE MEANDERS
OF THE RIGHT BANK OF THE TRUCKEE RIVER,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>S. 66°55'20" E., 2.327 chs.</p> <p>S. 83°19'20" E., 1.203 chs.</p> <p>S. 85°47'40" E., 1.071 chs.</p> <p>N. 50°14'30" E., 0.502 chs. At end of course, intersect the line bet. secs. 10 and 11, from which the S 1/16 sec. cor. of secs. 10 and 11, bears S. 0°11'40" E., 3.493 chs. dist., hereinbefore described.</p> <hr/> <p>Continue on an informative traverse of the adjusted right bank of the Truckee River, in sec. 11.</p> <p>N. 50°14'30" E., 1.783 chs.</p> <p>N. 63°35'50" E., 1.633 chs.</p> <p>N. 59°38'50" E., 2.018 chs.</p> <p>N. 57°16'30" E., 2.122 chs. At end of course, the true point for the special meander cor. of sec. 11, on the right bank of the avulsed channel of the Truckee River, hereinbefore described.</p> <hr/> <p>Continue, downstream with the adjusted meanders of the right bank of the Truckee River.</p> <p>N. 57°16'30" E., 0.206 chs.</p> <p>N. 62°45'30" E., 1.588 chs.</p> <p>N. 48°00'00" E., 1.538 chs.</p> <p>N. 28°34'50" E., 1.343 chs.</p> <p>N. 41°42'00" E., 2.983 chs.</p> <p>N. 45°43'10" E., 1.512 chs.</p> <p>N. 37°56'30" E., 1.392 chs.</p> <p>N. 38°39'40" E., 1.589 chs.</p> <p>N. 35°20'50" E., 1.850 chs.</p>
--------	---

SURVEY OF A PORTION OF THE MEANDERS
OF THE RIGHT BANK OF THE TRUCKEE RIVER,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>N. 19°30'10" E., 2.879 chs. At 2.690 chs., the true point for the special meander cor. of sec. 11, on the E-W center line of sec. 11, hereinbefore described, from which the C-W 1/16 sec. cor. of sec. 11, bears S. 89°12'40" E., 3.599 chs. dist., hereinbefore described.</p> <p>N. 32°30'10" E., 1.887 chs.</p> <p>N. 32°46'50" E., 3.081 chs.</p> <p>N. 60°32'40" E., 2.670 chs.</p> <p>N. 73°53'10" E., 1.598 chs.</p> <p>S. 86°14'40" E., 2.454 chs.</p> <p>N. 82°19'20" E., 5.683 chs.</p> <p>N. 61°58'40" E., 2.458 chs.</p> <p>N. 40°26'10" E., 3.529 chs.</p> <p>N. 3°33'40" E., 1.259 chs.</p> <p>N. 21°16'40" E., 3.456 chs.</p> <p>N. 38°17'40" E., 2.189 chs.</p> <p>N. 51°31'10" E., 2.502 chs. At end of course, the true point for the special meander cor. of sec. 11, on the N-S center line of sec. 11, hereinbefore described.</p> <hr/> <p>From the true point for the special meander cor. of sec. 11 on the E-W center line of the NE1/4 of sec. 11, hereinbefore described, thence downstream with the adjusted meanders of the right bank of the Truckee River.</p> <p>N. 57°54'20" E., 2.118 chs.</p> <p>N. 49°32'10" E., 1.325 chs.</p> <p>N. 14°57'20" E., 1.278 chs.</p>
--------	--

301

SURVEY OF A PORTION OF THE MEANDERS
OF THE RIGHT BANK OF THE TRUCKEE RIVER,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

N. 33°11'20" E., 3.167 chs.

N. 31°10'00" E., 4.325 chs.

N. 19°40'30" E., 1.833 chs.

N. 25°49'30" E., 2.265 chs.

N. 17°25'40" E., 3.021 chs.

N. 24°09'40" E., 1.308 chs.

N. 23°40'40" E., 1.559 chs.

N. 11°50'50" E., 1.103 chs.

At end of course, the
true point for the meander
cor. of sec. 11 only,
hereinbefore described.

SURVEY OF A PORTION OF THE MEANDERS
OF THE LEFT BANK OF THE TRUCKEE RIVER,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

The following meanders of the left bank of the Truckee River
represent the mean high water line observed in 2003.

From the true point for the special meander cor. of sec. 15,
on the E-W center line of the NW1/4 of sec. 15, and on the left
bank of the Truckee River, hereinbefore described.

Thence downstream with the meanders of the left bank of the
Truckee River, in sec. 15.

N. 7°06'40" E., 5.093 chs.

N. 17°39'00" E., 4.513 chs.

At 2.984 chs., true point
for a special meander
cor. of sec. 15, at
intersection with the
southwesterly line of a
50 ft. wide strip of land,
hereinafter described.
On this same course at
3.790 chs. dist., true
point for a special
meander cor. of sec. 15,
at intersection with the
northeasterly line of a
50 ft. wide strip of land,
hereinafter described.

SURVEY OF A PORTION OF THE MEANDERS
OF THE LEFT BANK OF THE TRUCKEE RIVER,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>N. 17°08'20" E., 2.610 chs.</p> <p>N. 19°05'10" E., 3.505 chs.</p> <p style="margin-left: 400px;">At 2.028 chs., true point for the special meander cor. of sec. 15, at intersection with the N-S center line of sec. 15, hereinbefore described. On this same course at 3.401 chs. dist., true point for a special meander cor. of sec. 15, on a line parallel and concentric with and 200 ft. dist. on the southeasterly side of the observed centerline of the main track of the railroad, hereinafter described.</p> <p>N. 22°18'10" E., 1.671 chs.</p> <p>N. 34°44'20" E., 4.180 chs.</p> <p style="margin-left: 400px;">At end of course, the true point for the meander cor. of secs. 10 and 15, hereinbefore described.</p> <hr/> <p>Thence in sec. 10.</p> <p>N. 34°44'20" E., 1.044 chs.</p> <p>N. 38°23'50" E., 4.393 chs.</p> <p>N. 38°06'00" E., 1.977 chs.</p> <p>N. 37°07'30" E., 2.499 chs.</p> <p style="margin-left: 400px;">At end of course, the point for the special meander cor. of sec. 10 on the southeasterly right-of-way line of the Union Pacific Railroad, hereinafter described.</p> <hr/> <p>Continue, on an informative traverse, downstream on the present left bank of the Truckee River, at the line of mean high water.</p> <p>N. 37°07'30" E., 1.558 chs.</p> <p>N. 44°59'30" E., 1.412 chs.</p>
--------	---

SURVEY OF A PORTION OF THE MEANDERS
OF THE LEFT BANK OF THE TRUCKEE RIVER,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div data-bbox="396 260 829 287">N. 57°39'10" E., 1.201 chs.</div> <div data-bbox="992 260 1433 531">At end of course, the point for the special meander cor. of sec. 10, on the southeasterly right-of-way line of the Union Pacific Railroad, hereinafter described. End of informative traverse.</div> <hr/> <div data-bbox="396 594 1433 653">Continue down stream with the meanders of the left bank of the Truckee River, at the line of mean high water.</div> <div data-bbox="396 682 824 709">N. 57°39'10" E., 0.982 chs.</div> <div data-bbox="396 741 824 768">N. 60°33'30" E., 2.041 chs.</div> <div data-bbox="396 800 824 827">N. 47°53'30" E., 2.962 chs.</div> <div data-bbox="396 858 824 886">N. 54°08'20" E., 0.943 chs.</div> <div data-bbox="992 865 1433 1073">At end of course, the true point for the special meander cor. of sec. 10, on the left bank of the avulsed channel of the Truckee River, hereinbefore described.</div> <hr/> <div data-bbox="396 1136 1433 1194">Continue on an informative traverse, downstream on the present left bank of the Truckee River, at the line of mean high water.</div> <div data-bbox="396 1224 824 1251">N. 54°08'20" E., 0.742 chs.</div> <div data-bbox="396 1283 824 1310">N. 47°13'00" E., 3.384 chs.</div> <div data-bbox="992 1285 1433 1524">At 2.453 chs. intersect the N-S center line of the SE1/4 of sec. 10, from which the SE 1/16 sec. cor. of sec. 10, bears N. 0°04'40" W., 3.240 chs. dist., hereinbefore described.</div> <div data-bbox="396 1556 824 1583">N. 38°05'20" E., 3.191 chs.</div> <div data-bbox="992 1558 1433 1675">At 2.623 chs. intersect the southeasterly right-of-way line of the Union Pacific Railroad.</div> <div data-bbox="396 1707 824 1734">N. 45°56'20" E., 2.270 chs.</div> <div data-bbox="992 1709 1433 1948">At 0.101 chs. intersect the E-W center line of the SE1/4 of sec. 10, from which the SE 1/16 sec. cor. of sec. 10, hereinbefore described, bears N. 89°27'30" W., 2.728 chs. dist.</div>
--------	--

SURVEY OF A PORTION OF THE MEANDERS
OF THE LEFT BANK OF THE TRUCKEE RIVER,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>N. 63°02'10" E., 1.076 chs.</p> <p>N. 58°16'00" E., 2.234 chs.</p> <p>S. 77°01'30" E., 0.560 chs.</p> <p>N. 65°00'10" E., 1.059 chs.</p> <p>N. 64°02'00" E., 1.729 chs.</p> <p>N. 72°23'00" E., 2.334 chs.</p> <p>N. 74°06'40" E., 0.608 chs.</p> <p>N. 67°28'40" E., 0.788 chs.</p> <p>N. 69°52'40" E., 2.760 chs.</p> <p style="text-align: right;">At 1.416 chs., Angle Point No. 18, sec. 10, on the right bank of the avulsed channel of the Truckee River, hereinbefore described.</p> <p>N. 81°45'10" E., 1.796 chs.</p> <p>N. 15°37'30" E., 1.217 chs.</p> <p>N. 31°53'50" E., 1.315 chs.</p> <p>N. 78°01'10" E., 1.297 chs.</p> <p style="text-align: right;">Intersect the line bet. secs. 10 and 11, from which the 1/4 sec. cor. of secs. 10 and 11, bears N. 0°11'40" W., 11.108 chs. dist., hereinbefore described.</p> <hr/> <p>Continue on an informative traverse of the present left bank of the Truckee River, in sec. 11.</p> <p>N. 78°01'10" E., 0.329 chs.</p> <p>N. 50°14'10" E., 2.297 chs.</p> <p>N. 76°11'40" E., 1.023 chs.</p> <p>N. 87°53'20" E., 1.334 chs.</p> <p>S. 61°32'00" E., 0.608 chs.</p> <p style="text-align: right;">At end of course, Angle Point No. 4, sec. 11, on the right bank of the avulsed channel of the Truckee River, hereinbefore described.</p>
--------	--

SURVEY OF A PORTION OF THE MEANDERS
OF THE LEFT BANK OF THE TRUCKEE RIVER,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	S. 68°11'00" E., 1.786 chs
	N. 47°54'00" E., 2.818 chs.
	N. 42°27'00" E., 2.832 chs.
	N. 35°53'30" E., 2.163 chs.
	N. 34°12'30" E., 1.649 chs.
	N. 32°58'00" E., 2.137 chs.
	N. 27°34'10" E., 2.114 chs.
	At 1.288 chs., intersect the E-W center line of sec. 11, from which the C-W 1/16 sec. cor. of sec. 11, bears S. 89°12'40" E., 5.668 chs. dist., hereinbefore described.
	N. 27°33'20" E., 3.451 chs.
	N. 2°53'20" E., 2.417 chs.
	N. 52°03'40" E., 0.528 chs.
	N. 66°48'30" E., 2.421 chs.
	N. 69°20'10" E., 2.048 chs.
	S. 87°15'00" E., 0.523 chs.
	S. 56°31'00" E., 1.629 chs.
	N. 83°33'40" E., 2.361 chs.
	N. 79°18'40" E., 1.976 chs.
	N. 72°35'30" E., 1.896 chs.
	N. 69°22'10" E., 2.223 chs.
	N. 58°50'10" E., 2.200 chs.
	N. 25°21'50" E., 2.127 chs.
	N. 16°08'10" E., 3.151 chs.
	N. 37°21'50" E., 2.642 chs.
	N. 42°24'50" E., 2.464 chs.
	N. 56°21'40" E., 2.473 chs.

306



SURVEY OF A PORTION OF THE MEANDERS
OF THE LEFT BANK OF THE TRUCKEE RIVER,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>N. 61°49'50" E., 0.898 chs. At 0.156 chs., intersect the N-S center line of sec. 11, from which the 1/4 sec. cor. of secs. 2 and 11, bears N. 0°14'20" W., 19.190 chs. dist., hereinbefore described.</p> <p>N. 35°49'00" E., 2.329 chs.</p> <p>N. 41°20'10" E., 1.635 chs.</p> <p>N. 36°36'40" E., 2.301 chs.</p> <p>N. 32°00'30" E., 3.094 chs.</p> <p>N. 22°05'00" E., 2.004 chs.</p> <p>N. 19°31'00" E., 2.018 chs.</p> <p>N. 26°30'50" E., 2.208 chs.</p> <p>N. 22°50'30" E., 3.609 chs.</p> <p>N. 17°33'40" E., 2.094 chs. At the end of course, intersect the line bet. secs. 2 and 11, from which the 1/4 sec. cor. of secs. 2 and 11, bears N. 88°55'00" W., 10.634 chs. dist., hereinbefore described. End of informative traverse of the present left bank of the Truckee River.</p>
	<hr/> <p style="text-align: center;">METES-AND-BOUNDS-SURVEY OF THE RAILROAD RIGHT-OF-WAY LINES IN SECTION 10, T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>
	<p style="text-align: center;">MEMORANDUM</p> <p>The metes-and-bounds survey of the railroad right-of-way lines are based on parcel descriptions as recorded in the Final Order of Forfeiture entered and served in the U.S. District Court Clerks Office, Reno, Nevada, on March 9, 2001, and recorded in Washoe County, Nevada, on October 16, 2001, as Document No. 2606088 in Official Records and in Storey County, Nevada, on October 18, 2001, as Document No. 090332 in Book 146, beginning at Page 42. The following railroad right-of-way lines were determined at 100 ft. right angle distance from, and parallel with the observed centerline of the main track of</p>

METES-AND-BOUNDS SURVEY OF THE RAILROAD RIGHT-OF-WAY LINES
IN SECTION 10,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>railroad line, utilizing alignment data taken from the Southern Pacific Transportation Company valuation map titled "Right of Way and Track Map, Main Line, Washoe and Storey Counties, Nevada, from Station 469+20.0 to Station 3410+00.0, V-2/3".</p> <hr/> <p>From the witness point, on the line bet. secs. 10 and 15, and at intersection with the southeasterly right-of-way line of the Union Pacific Railroad, on a line 100 ft. right angle distance from, and parallel with the observed centerline of the main track, hereinbefore described.</p> <p>N. 39°35'30" E., on the southeasterly right-of-way line.</p>
1.249	<p>A point at 100 ft. right angle distance from a tangent to spiral curve point on the observed centerline of main railroad track, not monumented.</p> <hr/> <p>Thence, along a line parallel to said spiral curve; the chord of said line bears N. 40°06'20" E., 4.580 chs. dist.</p>
4.580	<p>A point at 100 ft. right angle distance from a spiral to circular curve point on the observed centerline of main railroad track, not monumented.</p> <hr/> <p>Thence, along the arc of a circular curve to the right having a radius of 5535.72 ft.; the chord of said arc bears N. 42°42'40" E., 4.594 chs. dist.</p>
4.595	<p>Point for the special meander cor. of sec. 10, at the intersection of the southeasterly right-of-way line of the Union Pacific Railroad, and the left bank of the Truckee River, at the line of mean high water, not monumented.</p> <hr/> <p>Continue along the arc of a circular curve to the right having a radius of 5535.72 ft., along a blank line, over the Truckee River; the chord of said arc bears N. 45°41'25" E., 4.127 chs. dist.</p>
4.127	<p>Point for the special meander cor. of sec. 10, at the intersection of the southeasterly right-of-way line of the Union Pacific Railroad and the left bank of the Truckee River, at the line of mean high water, not monumented.</p> <hr/> <p>Continue along the arc of a circular curve to the right having a radius of 5535.72 ft.; the chord of said arc bears N. 47°33'35" E., 1.354 chs. dist.</p>
1.354	<p>A point at 100 ft. right angle distance from a circular to spiral curve point on the observed centerline of main railroad track, not monumented.</p> <hr/>

METES-AND-BOUNDS SURVEY OF THE RAILROAD RIGHT-OF-WAY LINES
IN SECTION 10,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Thence, along a line parallel to said spiral curve; the chord of said line bears N. 49°03'40" E., 4.580 chs. dist.</p>
4.580	<p>Point for a witness point at 100 ft. right angle distance from a spiral curve to tangent point on the observed centerline of the main railroad track.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a collar of stone with brass cap mkd.</p> <div style="text-align: center;">  <p>WP S10 2003</p> </div> <p>N. 49°34'30" E., on the tangent of the southeasterly right-of-way line.</p>
4.612	<p>Intersect the N-S center line of the SE1/4 of sec. 10, from which the SE 1/16 sec. cor. of sec. 10, bears N. 0°04'40" E., 2.503 chs. dist., hereinbefore described.</p>
6.972	<p>Point for a witness point at 100 ft. right angle distance from the observed centerline of the main railroad track.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;">  <p>WP S10 2003</p> </div>
7.636	<p>The present left bank of the Truckee River, at the line of mean high water, bank bears N. 38°05'20" E. and S. 38°05'20" W.</p>
8.430	<p>Point of intersection on the E-W center line of the SE1/4 of sec. 10, from which the SE 1/16 sec. cor. bears N. 89°27'30" W., 2.910 chs. dist., hereinbefore described.</p> <hr/> <p>From the witness point, on the N-S center line of sec. 10, at intersection with the northwesterly right-of-way of the Union Pacific Railroad on a line 100 ft. right angle distance from, and parallel with the observed centerline of the main track, hereinbefore described.</p> <p>N. 39°35'30" E., on the northwesterly right-of-way line.</p>

METES-AND-BOUNDS SURVEY OF THE RAILROAD RIGHT-OF-WAY LINES
IN SECTION 10,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
1.774	<p>Point for a witness point at 100 ft. right angle distance from a tangent to spiral curve point on the observed centerline of main railroad track.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <div data-bbox="885 525 1031 651"> <p>WP S10 2003</p> </div> <p>Thence, along a line parallel to said spiral curve; the chord of said line bears N. 40°06'40" E., 4.662 chs. dist.</p>
4.662	<p>Point for a witness point at 100 ft. right angle distance from a spiral to circular curve point on the observed centerline of main railroad track.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a collar of stone with brass cap mkd.</p> <div data-bbox="901 1039 1031 1165"> <p>WP S10 2003</p> </div> <p>Thence, along the arc of a circular curve to the right having a radius of 5735.72 ft.; the chord of said arc bears N. 44°35'00" E., 10.434 chs. dist.</p>
10.440	<p>Point for a witness point at 100 ft. right angle distance from a circular to spiral curve point on the observed centerline of main railroad track.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a collar of stone with brass cap mkd.</p> <div data-bbox="901 1575 1031 1701"> <p>WP S10 2003</p> </div> <p>Thence, along a line parallel to said spiral curve; the chord of said line bears N. 49°03'20" E., 4.662 chs. dist.</p>

METES-AND-BOUNDS SURVEY OF THE RAILROAD RIGHT-OF-WAY LINES
IN SECTION 10,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

4.662

Point for a witness point at 100 ft. right angle distance from a spiral curve to tangent point on the observed centerline of the main railroad track.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a collar of stone with brass cap mkd.

WP
S10
2003

N. 49°34'30" E., on the tangent of the northwesterly right-of-way line.

4.938

The witness point on the E-W center line of the SE1/4 of sec. 10, hereinbefore described.




METES-AND-BOUNDS SURVEY OF LINES PARALLEL AND CONCENTRIC TO THE
CENTERLINE OF THE MAIN TRACK OF RAILROAD IN SECTION 15,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

MEMORANDUM

The metes-and-bounds survey of lines parallel and concentric to the observed centerline of the main railroad track in Section 15 are based on parcel descriptions as recorded in the Final Order of Forfeiture entered and served in the U.S. District Court Clerks Office, Reno, Nevada, on March 9, 2001, and recorded in Washoe County, Nevada on October 16, 2001, as Document No. 2606088 in Official Records and in Storey County, Nevada on October 18, 2001, as Document No. 090332 in Book 146, beginning at Page 42. The following lines were determined parallel and concentric with and 200 ft. distant on each side of the observed centerline of the existing main track of railroad line, utilizing alignment data taken from the Southern Pacific Transportation Company valuation map titled "Right of Way and Track Map, Main Line, Washoe and Storey Counties, Nevada, from Station 469+20.0 to Station 3410+00.0, V-2/3".

From the witness point on the E-W center line of the NW1/4 of sec. 15, and at intersection with a line parallel and concentric with and 200 ft. distant from the main track of railroad line, hereinbefore described.

METES-AND-BOUNDS SURVEY OF LINES PARALLEL AND CONCENTRIC TO THE
CENTERLINE OF THE MAIN TRACK OF RAILROAD IN SECTION 15,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 39°35'30" E., on the southeasterly line parallel and concentric with and 200 ft. dist. from the observed centerline of the main track of the railroad.
12.370	<p>Point for a witness point at intersection with the southwesterly line of a 50 ft. wide strip of land described in a deed recorded November 3, 1975, in Book 928, Page 266, under Filing No. 383964, Official Records, Washoe County, Nevada.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 2 ins. below the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p>  <p>WP</p> <p>S15</p> <p>2004</p>
13.128	<p>Point for a witness point at the intersection with the northeasterly line of a 50 ft. wide strip of land described in a deed recorded November 3, 1975, in Book 928, Page 266, under Filing No. 383964, Official Records, Washoe County, Nevada.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the ground, over a plastic-encased magnet, with brass cap mkd.</p>  <p>WP</p> <p>S15</p> <p>2004</p>
18.780	The witness point on the N-S center line of sec. 15, hereinbefore described.
19.253	<p>Point selected for the witness cor. to the special meander cor. of sec. 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>  <p>WC</p> <p>S15</p> <p>SMC</p> <p>2004</p>




METES-AND-BOUNDS SURVEY OF LINES PARALLEL AND CONCENTRIC TO THE
CENTERLINE OF THE MAIN TRACK OF RAILROAD IN SECTION 15,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
19.481	<p>Intersect the left bank of the Truckee River, at the line of mean high water, bank bears N. 19°05'10" E. and S. 19°05'10" W., point for the special meander cor. of sec. 15, impractical to monument.</p> <hr/> <p>From the witness point on the E-W center line of the NW1/4 of sec. 15, at intersection with a line parallel and concentric with and 200 ft. dist. from the observed centerline of the main track of railroad line.</p> <p>Thence, on the northwesterly line parallel and concentric with and 200 ft. dist. from a portion of a spiral curve on the observed centerline of the main track of railroad concave to the left having a chord bearing N. 40°07'40" E., 3.260 chs. dist. to the point of tangency.</p>
3.260	<p>Point for a witness point 200 ft. dist. from a spiral curve to tangent point on the observed centerline of the main track of railroad.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="867 1045 997 1192" data-label="Diagram"> </div> <hr/> <p>N. 39°35'30" E., on the tangent of said parallel and concentric line.</p>
13.673	<p>Point for a witness point at the intersection with the southwesterly line of a 50 ft. wide strip of land described in a deed recorded November 3, 1975, in Book 928, Page 266, under Filing No. 383964, Official Records, Washoe County, Nevada.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="867 1617 1013 1764" data-label="Diagram"> </div>




METES-AND-BOUNDS SURVEY OF LINES PARALLEL AND CONCENTRIC TO THE
CENTERLINE OF THE MAIN TRACK OF RAILROAD IN SECTION 15,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
14.457	<p>Point for a witness point, at the intersection with the northeasterly line of a 50 ft. wide strip of land described in a deed recorded November 3, 1975, in Book 928, Page 266, under Filing No. 383964, Official Records, Washoe County, Nevada.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a collar of stone, with brass cap mkd.</p> <div data-bbox="885 562 1015 709" data-label="Diagram"> <p>WP S15 2004</p> </div>
22.876	<p>The witness point bet. secs. 10 and 15, hereinbefore described.</p> <hr/> <p>A METES-AND-BOUNDS SURVEY IN SECTION 11, T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From Angle Point No. 1, sec. 11, on the line bet. secs. 10 and 11, hereinbefore described.</p> <p>N. 50°13'10" E., on line 1-2.</p>
7.323	<p>Point for Angle Point No. 2, sec. 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="868 1260 1031 1402" data-label="Diagram"> <p>S11 AP 2 2003</p> </div> <hr/> <p>Thence, N. 40°03'50" E., on line 2-3.</p>
2.498	<p>Point for Angle Point No. 3, sec. 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="852 1701 1047 1852" data-label="Diagram"> <p>S11 AP 3 2003</p> </div> <hr/>

A METES-AND-BOUNDS SURVEY IN SECTION 11,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Thence, N. 60°47'30" E., on line 3-4.
5.785	Point for Angle Point No. 4, sec. 11.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	
	Thence, N. 35°58'50" E., on line 4-5.
2.135	Point for Angle Point No. 5, sec. 11.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	
	Thence, N. 18°09'30" W., on line 5-6.
5.980	Point for Angle Point No. 6, sec. 11.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	
	Thence, N. 41°44'30" E., on line 6-7.
2.268	Intersect the E-W center line of the SW1/4 of sec. 11, at a point from which the SW 1/16 sec. cor. of sec. 11, bears S. 89°09'30" E., 7.026 chs. dist., hereinbefore described.
8.215	Point for Angle Point No. 7, sec. 11.

A METES-AND-BOUNDS SURVEY IN SECTION 11,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA




CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="841 384 1003 531">  </div> <hr data-bbox="654 556 1182 560"/> <p>Thence, N. 41°49'20" E., on line 7-8.</p> <p>4.554 Intersect the N-S center line of the SW1/4 of sec. 11, at a point from which the SW 1/16 sec. cor. of sec. 11, bears S. 0°12'40" E., 7.935 chs. dist., hereinbefore described.</p> <p>9.998 Point for Angle Point No. 8, sec. 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="833 951 995 1098">  </div> <hr data-bbox="654 1123 1182 1127"/> <p>Thence, N. 33°16'10" W., on line 8-9.</p> <p>6.032 Point for Angle Point No. 9, sec. 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="849 1381 1011 1486">  </div> <hr data-bbox="654 1512 1182 1516"/> <p>Thence, N. 57°23'10" E., on line 9-10.</p> <p>6.257 Intersect the E-W center line of sec. 11, at a point from which the C-W 1/16 sec. cor. of sec. 11, bears N. 89°12'40" W., 5.637 chs. dist., hereinbefore described.</p> <p>18.472 Point for Angle Point No. 10, sec. 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
--------	---

316



A METES-AND-BOUNDS SURVEY IN SECTION 11,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div data-bbox="867 260 1013 344" data-label="Diagram"> <p>S11 AP 10</p> </div> <p data-bbox="899 380 964 405">2003</p> <p data-bbox="412 443 1036 468">Thence, S. 32°36'40" E., on line 10-11.</p> <p data-bbox="282 506 1442 560">8.056 Angle Point No. 11, sec. 11, identical with the center 1/4 sec. cor. of sec. 11, hereinbefore described.</p> <hr/> <p data-bbox="493 621 1360 709" style="text-align: center;">METES-AND-BOUNDS SURVEY OF A 50 FT. WIDE STRIP OF LAND LOCATED IN THE NE1/4 OF THE NW1/4 OF SECTION 15, T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p data-bbox="846 772 1008 798" style="text-align: center;">MEMORANDUM</p> <p data-bbox="412 831 1451 1129">The following metes-and-bounds survey of a 50 ft. wide strip of land is based on the Final Order of Forfeiture entered and served in the U.S. District Court Clerks Office, Reno, Nevada, on March 9, 2001, and recorded in Washoe County, Nevada, on October 16, 2001, as Document No. 2606088 in Official Records and in Storey County, Nevada, on October 18, 2001, as Document No. 090332 in Book 146, beginning at Page 42, and further described in a deed recorded November 3, 1975, in Book 928, Page 266, under Filing No. 383964, Official Records, Washoe County, Nevada.</p> <hr/> <p data-bbox="412 1190 1451 1308">From the witness point, on the line bet. secs. 10 and 15, at intersection with an arc of a circular curve to the right on the northeasterly line of a 50 ft. wide strip of land, hereinbefore described, from which a radial line bears S. 55°41'30" W.</p> <p data-bbox="412 1339 1451 1430">Thence, southeasterly along the arc of a circular curve to the right, having a radius of 325 ft.; the chord of said arc bears S. 34°00'10" E., 0.053 chs. dist.</p> <p data-bbox="282 1465 1024 1491">0.053 The point of tangency, not monumented.</p> <hr/> <p data-bbox="412 1554 1105 1579">Thence, S. 33°41'40" E., along the tangent.</p> <p data-bbox="282 1612 1451 1667">2.514 Point for a witness point to a point of curvature of a circular curve to the left.</p> <p data-bbox="412 1703 1451 1793">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
--------	---




METES-AND-BOUNDS SURVEY OF A 50 FT. WIDE STRIP OF LAND
LOCATED IN THE NE1/4 OF THE NW1/4 OF SECTION 15,
T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div data-bbox="883 268 1013 415"> <p>WP</p>  <p>2004</p> </div> <hr/> <p>Thence, southeasterly along the arc of a circular curve to the left, having a radius of 475 ft., the chord of said arc bears S. 51°04'50" E., 4.301 chs. dist.</p> <p>4.368 Point for a witness point to a point of tangency.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="850 781 1000 928"> <p>WP</p>  <p>2004</p> </div> <hr/> <p>S. 68°28'00" E., along the tangent.</p> <p>4.265 Point for a witness point to a point of curvature of a circular curve to the right.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div data-bbox="850 1260 993 1407"> <p>WP</p>  <p>2004</p> </div> <hr/> <p>Thence, southeasterly along the arc of a circular curve to the right, having a radius of 521.19 ft.; the chord of said arc bears S. 66°34'00" E., 0.525 chs. dist.</p> <p>0.525 The witness point, at the intersection of said arc and a line parallel and concentric with and 200 ft. dist. on the northwesterly side of the observed centerline of the main track of the railroad, hereinbefore described.</p> <hr/> <p>From the witness point, on a line parallel and concentric with and 200 ft. dist. on the southeasterly side of the observed centerline of the main track of the railroad, and at intersection with the north line of a 50 ft. wide strip of land, hereinbefore described.</p>
--------	---


METES-AND-BOUNDS SURVEY OF A 50 FT. WIDE STRIP OF LAND
 LOCATED IN THE NE1/4 OF THE NW1/4 OF SECTION 15,
 T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Thence, S. 52°24'20" E., along the tangent.
1.783	<p>Point selected for the witness cor. to a special meander cor. of sec. 15, on the northeasterly side of 50 ft. strip of land.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> 
2.459	<p>The special meander cor. of sec. 15, on the left bank of the Truckee River, at the line of mean high water, bank bears N. 17°39'00" E. and S. 17°39'00" W., hereinbefore described.</p> <hr/> <p>From the witness point, on the line bet. secs. 10 and 15, and at intersection with the arc of a circular curve to the right on the southwesterly line of a 50 ft. wide strip of land, hereinbefore described, from which a radial line bears S. 48°04'40" W.</p> <p>Thence, southeasterly, along the arc of a circular curve to the right, having a radius of 275 ft.; the chord of said arc bears S. 37°48'30" E., 0.598 chs. dist.</p>
0.598	<p>Point for a witness point to the point of tangency.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> 
2.514	<p>S. 33°41'40" E., along tangent.</p> <p>Point for a witness point to a point of curvature of a circular curve to the left.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the ground, over a plastic-encased magnet, with brass cap mkd.</p>

METES-AND-BOUNDS SURVEY OF A 50 FT. WIDE STRIP OF LAND
 LOCATED IN THE NE1/4 OF THE NW1/4 OF SECTION 15,
 T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div data-bbox="868 300 998 435"> <p>WP  2004</p> </div> <hr/> <p>Thence, southeasterly, along the arc of a circular curve to the left, having a radius of 525 ft.; the chord of said arc bears S. 51°04'50" E., 4.754 chs. dist.</p> <p>4.828 Point for a witness point to the point of tangency.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div data-bbox="868 745 998 880"> <p>WP  2004</p> </div> <hr/> <p>S. 68°28'00" E., along the tangent.</p> <p>4.265 Point for a witness to a point of curvature of a circular curve to the right.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="868 1191 998 1326"> <p>WP  2004</p> </div> <hr/> <p>Thence, southeasterly, along the arc of a circular curve to the right, having a radius of 471.19 ft.; the chord of said arc bears S. 67°20'05" E., 0.282 chs. dist..</p> <p>0.282 The witness point on a line parallel and concentric with and 200 ft. dist. on the northwesterly side of the observed centerline of the main track of the railroad, hereinbefore described.</p> <hr/> <p>From the witness point on a line parallel and concentric with and 200 ft. dist. on the southeasterly side of the observed centerline of the main track of the railroad, and at the intersection of the south line of a 50 ft. wide strip of land, hereinbefore described.</p>
--------	---

METES-AND-BOUNDS SURVEY OF A 50 FT. WIDE STRIP OF LAND
 LOCATED IN THE NE1/4 OF THE NW1/4 OF SECTION 15,
 T. 19 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Thence S. 52°24'20" E., along a tangent.
2.027	Point selected for the witness cor. to the special meander cor. of sec. 15, on the southwesterly side of 50 ft. strip of land.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	
2.760	The special meander cor. of sec. 15, on the left bank of the Truckee River, at the line of mean high water, bank bears N. 17°39'00" E. and S. 17°39'00" W., hereinbefore described.
	<p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The average elevation is 4300 feet above mean sea level. Access to the area is by Interstate 80 at the Mustang exit. There are several roads, the main one being a paved road running through sections 10, 11 and 15. The Union Pacific Railroad runs from the SW to the NE through sections 10, 11 and 15. The Truckee River drains NE through sections 10, 11 and 15. There is an active gravel pit located in the SW1/4 of section 11.</p>

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANT

Don R. Aschenbach	Cadastral Surveyor
Mark G. Petrosine	Surveying Technician
Michael A. Derby	Surveying Technician
Jeremiah J. Lee	Surveying Technician
Clive M. Staples	Surveying Technician
Melinda A. Sanstrom	Surveying Technician
Michelle E. Martin	Survey Aid
Gerald A. Stayner	Land Surveyor (Volunteer)

CERTIFICATE OF SURVEY

We, Richard L. Jones, Cadastral Surveyor and Clay W. Morrow, Surveying Technician, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 21st day of April, 2003, and Supplemental and Amended Special Instructions bearing date of the 6th day of August, 2004, we have dependently resurveyed a portion of the subdivisional lines and subdivided sections 10, 11 and 15, surveyed portions of the avulsed channel of the Truckee River in sections 10 and 11, and the meanders of the Truckee River in sections 10, 11 and 15, and executed certain metes-and-bounds surveys in sections 10, 11 and 15, Township 19 North, Range 21 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

August 26, 2004

(Date)

Richard L. Jones
(Cadastral Surveyor)

August 24, 2004

(Date)

Clay W. Morrow
(Surveying Technician)

CERTIFICATE OF APPROVAL

The foregoing field notes of the dependent resurvey of a portion of the subdivisional lines and the subdivision of sections 10, 11 and 15, the survey of portions of the avulsed channel of the Truckee River in sections 10 and 11, and the meanders of the Truckee River in sections 10, 11 and 15, and certain metes-and-bounds surveys in sections 10, 11 and 15, Township 19 North, Range 21 East, Mount Diablo Meridian, Nevada, executed by Richard L. Jones, Cadastral Surveyor and Clay W. Morrow, Surveying Technician, having been critically examined and found correct, are hereby approved.

September 1, 2004

(Date)

Acting

David J. Clark
(Chief Cadastral Surveyor, Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above described surveys in T. 19 N., R. 21 E., M.D.M., Nevada, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor, Nevada)~~