

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF

A PORTION OF THE SUBDIVISIONAL LINES

AND

PORTIONS OF CERTAIN MINERAL SURVEYS,

TOWNSHIP 20 SOUTH, RANGE 65 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATE OF NEVADA

EXECUTED BY

Joseph J. Johnson, Cadastral Surveyor

Lee T. Wilson, Cadastral Surveyor

Under Special Instructions dated August 10, 2015,

and approved August 10, 2015,

which provided for the surveys included under Group No. 952,

and Assignment Instructions dated August 10, 2015,

and Assignment Instructions dated May 10, 2016.

Survey commenced July 31, 2015

Survey completed January 10, 2017

## INDEX DIAGRAM

TOWNSHIP 20 SOUTH, RANGE 65 EAST, MOUNT DIABLO MERIDIAN, NEVADA

|    |    |    |         |                |    |
|----|----|----|---------|----------------|----|
| 6  | 5  | 4  | 3       | 2              | 1  |
| 7  | 8  | 9  | 10      | 11<br>4        | 12 |
| 18 | 17 | 16 | 15<br>5 | 4<br>3 14<br>2 | 13 |
| 19 | 20 | 21 | 22      | 23             | 24 |
| 30 | 29 | 28 | 27      | 26             | 25 |
| 31 | 32 | 33 | 34      | 35             | 36 |

Dependent Resurvey of a Portion of Mineral Survey No. 4502.. pp 5 - 10  
 Dependent Resurvey of a Portion of Mineral Survey No. 4519.. pp 10 - 11  
 Dependent Resurvey of Mineral Survey No. 4539..... pp 12 - 16  
 Dependent Resurvey of Portions of Mineral Survey No. 4540... pp 17 - 18  
 Dependent Resurvey of a Portion of Mineral Survey No. 4837.. pp 19 - 23

## TOWNSHIP 20 SOUTH, RANGE 65 EAST, MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

The following field notes are those providing for the dependent resurvey of a portion of the subdivisional lines and portions of certain mineral surveys, Township 20 South, Range 65 East, Mount Diablo Meridian, Nevada.

The south (Fifth Standard Parallel South), east, west, and north boundaries and the subdivisional lines were surveyed by U.S. Deputy Surveyor, W.H. Myrick, in 1882, under Contract No. 139. The south boundary (Fifth Standard Parallel South) was dependently resurveyed by U.S. Surveyor, R.C. Yundt, and U.S. Cadastral Engineers, C.S. Swanholm and A. Nelson, in 1931, under Group No. 169. The east, west, and north boundaries and the subdivisional lines were independently resurveyed by Surveyor, J.W. Hardison, and Public Land Surveyors, W.M. McConkie and J.G. Dyer, in 1938, under Group No. 237. Mineral Survey No. 4502, Indipendant, Indipendant #1, and Indipendant Fraction lodes, was surveyed by U.S. Mineral Surveyor, F.W. Rodolf, in 1921. Mineral Survey No. 4519, Indipendant #2 lode, was surveyed by U.S. Mineral Surveyor, F.W. Rodolf, in 1922. Mineral Survey No. 4539, Independent #6 and Valley View lodes, was surveyed by U.S. Mineral Surveyor, F.W. Rodolf, in 1922. Mineral Survey No. 4540, Indipendant #13 and Indipendant #14 lodes, was surveyed by U.S. Mineral Surveyor, F.W. Rodolf, in 1922. Mineral Survey No. 4837, Anniversary, Anniversary #1, and Anniversary #2 lodes, was surveyed by Mineral Surveyor, F.W. Millard, in 1954.

Before restoring the corners, the lines of the original surveys were retraced and a diligent search made for any evidence of the original corners and other calls of the original field note record.

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 2009, and the Special Instructions for Group No. 952, dated August 10, 2015.

Measurements were made with Trimble R-8 and R-10 Global Positioning System (GPS) receivers using the real-time kinematic (RTK) method and refer to the true meridian based on geodetic methods. The mean bearing of the lines and horizontal equivalents of ground distances only, are entered into the field notes.

The NAD83 (2011), (EPOCH:2010.0000) geographic position of the following corners was determined by GPS static observations processed by the National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuous Operating Reference Stations (CORS), DJ3669 NVCA CARLTON SQUARE 2 CORS ARP, DI1079 NVLM AMS WT FACILITY CORS ARP and DP2494 NVWS WARM SPRINGS CORS ARP, and carried forward by RTK observations is as follows:

The corner of sections 13, 14, 23 and 24, is as follows:

Latitude: 36°12'10.140" N. Longitude: 114°41'13.184" W.

## TOWNSHIP 20 SOUTH, RANGE 65 EAST, MOUNT DIABLO MERIDIAN, NEVADA

|        |   |
|--------|---|
| CHAINS | <p>The 1/4 section corner of sections 10 and 11, is as follows:</p> <p>Latitude: 36°13'28.317" N.      Longitude: 114°42'17.779" W.</p> <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,<br/>T. 20 S., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of a Portion of the Independent Resurvey<br/>Executed by Surveyor J.W. Hardison and Public Land Surveyors<br/>W.M. McConkie and J.G. Dyer in 1938</p> <hr/> <p>Beginning at the cor. of secs. 13, 14, 23 and 24, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above the ground, with a fiberglass sign post set alongside, with a mound of stone, 3 ft. diam., 2 ft. high, W. of the cor., with brass cap mkd. as described in the field notes of the 1938 independent resurvey of the subdivisional lines, T. 20 S., R. 65 E., executed under Group No. 237.</p> <p>Cor. is located on SE. facing slope, N. of dry wash, drains SW. S. 89°58'30" W., bet. secs. 14 and 23.</p> <p>1.50      Wash, 15 lks. wide, drains SE.</p> <p>8.10      Anniversary Mine Road, asphalt surface, 27 lks. wide, bears SE. and NW.</p> <p>12.00      Wash, 60 lks. wide, drains SE.</p> <p>17.60      Wash, 45 lks. wide, drains NE.</p> <p>27.80      Spur, slopes NNW.</p> <p>34.20      Wash, 75 lks. wide, drains SW.</p> <p>40.086      The 1/4 sec. cor. of secs. 14 and 23, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above the ground, with a mound of stone, 2 ft. diam., 1 ft. high, NE. of the cor., with brass cap mkd. as described in the field notes of the 1938 independent resurvey of the subdivisional lines, T. 20 S., R. 65 E., executed under Group No. 237.</p> <p>Corner is located on NE. facing slope.</p> <p>From this point, a limestone, 12x3 ins. (Record, 14x12x3 ins.), firmly set, projecting 12 ins. above the ground, mkd. 1/4 on the N. face and WP on the S. face, with a scattered mound of stone N. of the cor., bears S. 70°05'00" W., 6.815 chs. dist. This stone was reported as an unofficial corner in the field notes of the 1938 independent resurvey of the subdivisional lines, T. 20 S., R. 65 E., executed under Group No. 237.</p> <p>A second limestone, 28x22x3 ins., mkd. SW. COR QUEE-0 6 PLACER on one side and SE. COR QUEE-0 5 PLACER on the other side, found lying loose alongside.</p> <hr/> |
|--------|---|

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 20 S., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

| CHAINS |  |
|--------|--|
|        | From the cor. of secs. 14, 15, 22 and 23, monumented with an iron post, 2 ins. diam., firmly set, in a mound of stone, 4 ft. diam., 3 ft. high, with brass cap mkd. as described in the field notes of the 1938 independent resurvey of the subdivisional lines, T. 20 S., R. 65 E., executed under Group No. 237.   |
|        | N. 0°02'30" W., bet. secs. 14 and 15.  |
| 1.70   | Top of limestone cliff, bears ESE. and WNW.  |
| 13.40  | Wash, drains E.  |
| 25.30  | Ridge, bears SE. and NW.   |
| 31.30  | Wash, drains SE.   |
| 39.966 | Point for the 1/4 sec. cor. of secs. 14 and 15, at proportionate distance; there is no remaining evidence of the original corner.  |
|        | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.  |
|        | T20S R65E<br>1/4<br>S15 S14<br>2015  |
|        | Cor. is located on E. edge of dry wash, drains S.  |
| 50.20  | Dirt road, 20 lks. wide, bears SE. and NW.   |
| 55.00  | Enter disturbed area.  |
| 61.50  | Leave disturbed area.  |
| 65.60  | Road cut, bears ENE. and WSW.  |
| 67.80  | Road cut, bears NNE. and SSW.  |
| 73.417 | Intersect line 3-4, Mineral Survey No. 4502, Indipendant Fraction lode, at a point from which the true point for Cor. No. 4, Indipendant Fraction lode, hereinafter described, bears S. 42°28'00" W., 8.344 chs. dist.   |
| 77.20  | Spur, slopes SSW.  |
| 79.932 | The cor. of secs. 10, 11, 14 and 15, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above the ground, with a mound of stone, 4 ft. diam., 2 ft. high, W. of the cor., with brass cap mkd. as described in the field notes of the 1938 independent resurvey of the subdivisional lines, T. 20 S., R. 65 E., executed under Group No. 237. |
|        | Cor. is located on steep, loose, N. facing slope above ravine, drains SW.  |


DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 20 S., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

|        |   |
|--------|---|
| CHAINS | <p>From the cor. of secs. 11, 12, 13 and 14, monumented with an iron post, 2 ins. diam., firmly set, in a mound of stone, 3 ft. diam., 1 ft. high, with brass cap mkd. as described in the field notes of the 1938 independent resurvey of the subdivisional lines, T. 20 S., R. 65 E., executed under Group No. 237.</p> <p>S. 89°57'30" W., bet. secs. 11 and 14.</p>   |
| 8.30   | Wash, drains SW.  |
| 32.835 | Intersect line 2-3, Mineral Survey No. 4540, Indipendant #14 lode, at a point from which Cor. No. 2, Indipendant #14 lode, identical with Cor. No. 4, Mineral Survey No. 4502, Indipendant lode, and Cor. No. 1, Mineral Survey No. 4519, Indipendant #2 lode, hereinafter described, bears N. 2°00'00" W., 0.923 chs. dist.  |
| 40.122 | <p>The 1/4 sec. cor. of secs. 11 and 14, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above the ground, with a mound of stone, 3 ft. diam., 1/2 ft. high, N. of the cor., with brass cap mkd. as described in the field notes of the 1938 independent resurvey of the subdivisional lines, T. 20 S., R. 65 E., executed under Group No. 237.</p> <p>Corner is located S. of limestone ridge, bears E. and W.</p> <p>From this point, a limestone, 8x4 ins., firmly set, projecting 8 ins. above the ground, mkd. 1/4 WC on the N. face, with a mound of stone, 2 ft. diam., 2 ft. high, N. of the cor., bears S. 71°38'00" W., 6.593 chs. dist. This stone was reported as an unofficial corner in the field notes of the 1938 independent resurvey of the subdivisional lines, T. 20 S., R. 65 E., executed under Group No. 237.</p> <hr/> <p>S. 89°52'50" W., beginning new measurement.</p> |
| 8.10   | Limestone ridge, bears E. and W.  |
| 34.073 | Intersect line 3-4, Mineral Survey No. 4502, Indipendant Fraction lode, at a point from which Cor. No. 3, Indipendant Fraction lode, hereinafter described, bears N. 42°28'00" E., 5.562 chs. dist.   |
| 38.00  | Spur, slopes NE. and SSW.   |
| 40.052 | The cor. of secs. 10, 11, 14 and 15.  |
|        | <hr/> <p>N. 0°00'30" W., bet. secs. 10 and 11.</p>  |
| 6.947  | Intersect line 1-2, Mineral Survey No. 4502, Indipendant Fraction lode, at a point from which Cor. No. 2, Indipendant Fraction lode, hereinafter described, bears N. 42°28'00" E., 4.488 chs. dist.   |
| 31.50  | Limestone spur, slopes E.   |
| 39.30  | Wash, drains SE.  |

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 20 S., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

|        |  |
|--------|--|
| CHAINS |  |
| 39.884 | <p>The 1/4 sec. cor. of secs. 10 and 11, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above the ground, with brass cap mkd. as described in the field notes of the 1938 independent resurvey of the subdivisional lines, T. 20 S., R. 65 E., executed under Group No. 237.</p> <p>Build a supporting mound of stone, 5 ft. base, to top.</p> <hr/> <p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>N. 89°55'20" W., bet. secs. 10 and 15.</p>   |
| 6.351  | <p>Intersect line 1-2, Mineral Survey No. 4502, Indipendant Fraction lode, at a point from which Cor. No. 1, Indipendant Fraction lode, hereinafter described, bears S. 42°28'00" W., 8.861 chs. dist.</p>   |
| 7.30   | <p>Bottom of canyon, drains S.</p>   |
| 13.737 | <p>Intersect line 4-1, Mineral Survey No. 4539, Valley View lode, at a point from which Cor. No. 1, Valley View lode, hereinafter described, bears S. 2°02'10" E., 4.676 chs. dist.</p>  |
| 20.380 | <p>Intersect line 3-4, Mineral Survey No. 4539, Valley View lode, at a point from which Cor. No. 4, Valley View lode, hereinafter described, bears N. 52°44'00" E., 8.127 chs. dist.</p>   |
| 39.919 | <p>The 1/4 sec. cor. of secs. 10 and 15, monumented with an iron post, 1 in. diam., firmly set, in a mound of stone, 3 ft. diam., 2 ft. high, with brass cap mkd. as described in the field notes of the 1938 independent resurvey of the subdivisional lines, T. 20 S., R. 65 E., executed under Group No. 237.</p> <hr/> <p>DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4502,<br/>T. 20 S., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of Portions of the Survey<br/>Executed by U.S Mineral Surveyor, F.W. Rodolf, in 1921</p> <hr/> <p>Indipendant #1 lode</p> <p>From Cor. No. 2, Mineral Survey No. 4502, Indipendant #1 lode, determined by the method of parallel end lines; there is no remaining evidence of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> |


DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4502,  
T. 20 S., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

| CHAINS |   |
|--------|---|
|        | <p style="text-align: center;">  </p> <p>Cor. is located in dry wash, drains SSW.</p> <p>From this point, Cor. No. 1, Mineral Survey No. 4502, Indipendant #1 lode, identical with, Cor. No 1, Mineral Survey No. 4540, Indipendant #13 lode, hereinafter described, bears S. 2°01'10" E., 9.096 chs. dist.</p> <p>Thence N. 87°59'30" E., on line 2-3, Mineral Survey No. 4502, Indipendant #1 lode.</p> <p>2.908 Intersect line 2-3, Mineral Survey No. 4502, Indipendant Fraction lode, at a point from which Cor. No. 2, Indipendant Fraction lode, hereinafter described, bears N. 47°30'50" W., 2.418 chs. dist.</p> <p>11.51 A mound of stone, 6 ft. diam., 3 ft. high.</p> <p>22.733 True point for Cor. No. 3, Mineral Survey No. 4502, Indipendant #1 lode, identical with, Cor. No. 2, Mineral Survey No. 4502, Indipendant lode, determined at record witness distance and on the extension of the line between Cor. No. 4, Mineral Survey No. 4502, Indipendant #1 lode, identical with Cor. No. 1, Mineral Survey No. 4502, Indipendant lode; Cor. No. 2, Mineral Survey No. 4540, Indipendant #13 lode; and Cor. No. 1, Mineral Survey No. 4540, Indipendant #14 lode and the witness corner for Cor. No. 3, Mineral Survey No. 4502, Indipendant #1 lode, identical with the witness corner for Cor. No. 2, Mineral Survey No. 4502, Indipendant lode, falls on steep, eroding cliff face where it is impracticable to establish a permanent monument; there is no remaining evidence of the marks made by the original surveyor.</p> <p>From this point, the witness corner for Cor. No. 3, Mineral Survey No. 4502, Indipendant #1 lode, identical with the witness corner for Cor. No. 2, Mineral Survey No. 4502, Indipendant lode, monumented with a limestone 30x12x6 ins. (Record, 28x8x6 ins.), firmly set, projecting 16 ins. above the ground, mkd. WC 4502 2-I on the E. face, WC 4502 and other illegible marks on the W. face, and X on top, bears S. 2°01'10" E., 1.864 chs. dist.</p> <p>At the witness corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to solid rock, over a plastic-encased magnet, in a supporting mound of stone, 4 1/2 base, to top, with brass cap mkd.</p> |



DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4502,  
T. 20 S., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS



Bury the mkd. stone in the mound of stone.

Witness cor. is located on top of cliff, bears E. and W.


From this same point, Cor. No. 4, Mineral Survey No. 4502, Indipendant #1 lode, identical with Cor. No. 1, Mineral Survey No. 4502, Indipendant lode; Cor. No. 2, Mineral Survey No. 4540, Indipendant #13 lode; and Cor. No. 1, Mineral Survey No. 4540, Indipendant #14 lode, monumented with a chisled X on a limestone slab with 4502 I #1, 4502 1-I, 2 4540 and other illegible markings chiseled alongside, bears S. 2°01'10" E., 9.096 chs. dist.

Indipendant Fraction lode

From Cor. No. 1, Mineral Survey No. 4502, Indipendant Fraction lode, monumented with a limestone, 30x16x4 ins. (Record, 32x16x6 ins.), firmly set, projecting 12 ins. above the ground, in a mound of stone, 5 ft. diam., 1 ft. high, mkd. 4502 1-IF on a face.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, over a plastic-encased magnet, in a supporting mound of stone, 5 ft. base, to top, with brass cap mkd.





Bury the mkd. stone alongside the stainless steel post.

Thence N. 42°28'00" E., on line 1-2, Mineral Survey No 4502, Indipendant Fraction lode.

2.538

Intersect line 1-2, Mineral Survey No. 4539, Independent #6 lode, at a point from which Cor. No. 1 Independent #6 lode, hereinafter described, bears N. 37°15'50" W. 1.786 chs. dist.

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4502,  
T. 20 S., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

|                 |  |
|-----------------|--|
| CHAINS<br>8.861 | Intersect the line bet. secs. 10 and 15, at a point from which the cor. of secs. 10, 11, 14 and 15, hereinbefore described, bears S. 89°55'20" E., 6.351 chs. dist.  |
| 18.267          | Intersect the line bet. secs. 10 and 11, at a point from which the cor. of secs 10, 11, 14 and 15, hereinbefore described, bears S. 0°00'30" E., 6.947 chs. dist.  |
| 22.755          | Point for Cor. No. 2, Mineral Survey No. 4502, Indipendant Fraction lode, determined by the method of parallel end lines; there is no remaining evidence of the original corner.                                   |
|                 | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.  |
|                 | <p style="text-align: center;">T20S R65E<br/>S11</p>  <p style="text-align: center;">2015</p>                                    |
|                 | Cor. is located in a dry wash, drains SSW.   |
|                 | <hr/> <p>Thence S. 47°30'50" E., on line 2-3, Mineral Survey No. 4502, Indipendant Fraction lode.</p>  |
| 2.418           | Intersect line 2-3, Mineral Survey No. 4502, Indipendant #1 lode, at a point from which, Cor. No. 2, Mineral Survey No. 4502, Indipendant #1 lode, hereinbefore described, bears S. 87°59'30" W., 2.908 chs. dist. |
| 9.093           | Cor. No. 3, Mineral Survey No. 4502, Indipendant Fraction lode, monumented with a limestone, 30x14x4 ins. (Record, 30x14x6 ins.), firmly set, projecting 12 ins. above the ground, mkd. 4502-3-IF on a face.       |
|                 | At the corner point  |
|                 | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.            |
|                 |  <p style="text-align: center;">2015</p>   |

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4502,  
T. 20 S., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA


|        |   |
|--------|---|
| CHAINS | <p>Bury the mkd. stone in the mound of stone.</p> <hr/> <p>Thence S. 42°28'00" W., on line 3-4 of Mineral Survey No. 4502, Indipendant Fraction lode.</p>   |
| 5.562  | Intersect the line bet. secs. 11 and 14, at a point from which the cor. of secs. 10, 11, 14 and 15, hereinbefore described, bears S. 89°52'50" W., 5.979 chs. dist.   |
| 10.944 | Intersect line 4-1, Mineral Survey No. 4540, Indipendant #13 lode, at a point from which Cor. No. 1, Indipendant #13 lode, hereinafter described, bears N. 2°00'40" W., 3.392 chs. dist.  |
| 11.321 | <p>From this point, a mound of stone, 4 ft. diam., 3 ft. high, with a limestone 23x14x1 ins., lying loose on top of the mound, mkd. SSC and other illegible markings, bears North, 1 lk. dist.</p> <p>From this same point, a scattered mound of stone, 4 ft. diam., 1 ft. high, bears N. 49°19' E., 36 lks. dist.</p> <p>From this same point, a mound of stone 4 ft. diam., 3 1/2 ft. high, bears S. 17°17' E., 31 lks. dist.</p> <p>From this same point, a mound of stone, 2 1/2 ft. diam., 1 ft. high, bears S. 30°39' W., 1.00 chs. dist.</p>   |
| 14.411 | Intersect the line bet. secs. 14 and 15, at a point from which the cor. of secs. 10, 11, 14 and 15, hereinbefore described, bears N. 0°02'30" W., 6.515 chs. dist.  |
| 19.80  | Road cut, bears E. and W.   |
| 22.755 | <p>True point for Cor. No. 4, Mineral Survey No. 4502, Indipendant Fraction lode, determined at record witness distance and on the line between Cor. No. 1 and the witness cor. to Cor. No. 4, Mineral Survey No. 4502, Indipendant Fraction lode, falls on a steep slope where it is impracticable to establish a permanent monument.</p> <p>From this point, the original witness corner for Cor. No. 4, Mineral Survey No. 4502, Indipendant Fraction lode, bears S. 47°30'50" E., 0.091 chs. dist., monumented with a limestone, 40x14x5 ins. (Record, 28x12x8 ins.), firmly set, projecting 12 ins. above the ground, in a mound of stone, 2 ft. diam., 1 ft. high, mkd. 4502-4-IF WC.</p> <p>At the witness corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to solid rock, over a plastic-encased magnet, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.</p> |

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4502,  
T. 20 S., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

| CHAINS |  |
|--------|--|
|        | <div data-bbox="873 296 1065 530"> <p>WC<br/>MS4502<br/>IF<br/>4<br/>T20S R65E<br/>S15<br/>2015</p> </div> <p>Bury the mkd. stone alongside the stainless steel post.</p> <hr/> <p>Thence N. 47°30'50" W., on line 4-1, Mineral Survey No. 4502, Indipendant Fraction lode.</p> <p>2.104 Intersect line 2-3, Mineral Survey No. 4539, Independent #6 lode, at a point from which the true point for Cor. No. 2, Independent #6 lode, hereinafter described, bears N. 52°46'20" E., 1.254 chs. dist.</p> <p>9.093 Cor. No. 1, Mineral Survey No. 4502, Indipendant Fraction lode, and point of beginning.</p> <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4519,<br/>T. 20 S., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of a Portion of the Survey<br/>Executed by U.S Mineral Surveyor, F.W. Rodolf, in 1922</p> <hr/> <p>Indipendant #2 lode</p> <p>From Cor. No. 4, Mineral Survey No. 4519, Indipendant #2 lode, monumented with a sandstone, 32x11x4 ins. (Record, limestone, 28x8x5 ins.), firmly set, projecting 11 ins. above the ground, mkd. I#2-4 4519 on the NW. face and X on top, with a metal stake set alongside, with a metal tag mkd. SE CORNER PATENT INDIPENDANT #2, in a mound of stone, 1 ft. diam., 1 ft. high, with a mound of stone, 5 ft. diam., 3 ft. high, S. of the cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.</p> |

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4519,  
T. 20 S., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS




Bury the mkd. stone and metal stake alongside the stainless steel post.

Thence S.  $61^{\circ}29'50''$  W, on line 4-1, Mineral Survey No. 4519, Indipendant #2 lode.

- 11.337 From this point, a mound of stone, 4 1/2 ft. diam., 3 ft. high, with a limestone 16x15x2 ins., loosely set on top, illegibly mkd., bears South, 3 lks. dist.
- 12.625 From this point, a mound of stone, 3 1/2 ft. diam., 3 ft. high, with a limestone, 25x20x1 ins., mkd. NE COR ANNIV LODE #7, lying loose alongside, bears North, 8 lks. dist.
- 22.725 Cor. No. 1, Mineral Survey No. 4519, Indipendant #2 lode, identical with Cor. No. 4, Mineral Survey No. 4502, Indipendant lode, and Cor. No. 2, Mineral Survey No. 4540, Indipendant #14 lode, monumented with a limestone, 20x9x8 ins. (Record, 24x8x6 ins.), firmly set, projecting 8 ins. above the ground, mkd. I#14-2 4540 on a face and X on top, with a metal stake set alongside, with tag mkd. SWC I-2 PATENT CORNER-4 APPROX.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, over a plastic-encased magnet, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.



2015

Bury the mkd. stone and metal stake alongside the stainless steel post.


Corner is located S. of road, bears NE. and SW.

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4539,  
T. 20 S., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

| CHAINS |  |
|--------|--|
|        | <p>Reestablishment of a Portion of the Survey<br/>Executed by U.S Mineral Surveyor, F.W. Rodolf, in 1922</p>   |
|        | <p>Independent #6 lode</p>   |
|        | <p>From Cor. No. 1, Mineral Survey No. 4539, Independent #6 lode, monumented with a limestone, 20x8x8 ins. (Record, 22x8x8 ins.), firmly set, projecting 10 ins. above the ground, in a mound of stone, 4 ft. diam., 2 ft. high, mkd. I#6-1 4539 on a face.</p>                            |
|        | <p>At the corner point</p>   |
|        | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to solid rock, over a plastic-encased magnet, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.</p>   |
|        | <p style="text-align: center;">T20S R65E<br/>S15<br/>I6 1<br/>MS4539<br/>2015</p>  |
|        | <p>Bury the mkd. stone alongside the stainless steel post.</p>   |
|        | <p>Thence S. 37°15'50" E., on line 1-2, Mineral Survey No. 4539, Independent #6 lode.</p>  |
| 1.786  | <p>Intersect line 1-2, Mineral Survey No. 4502, Indipendant Fraction lode, at a point from which Cor. No. 1, Indipendant Fraction lode, hereinbefore described, bears S. 42°28'00" W., 2.538 chs. dist.</p>  |
| 9.117  | <p>True point for Cor. No. 2, Mineral Survey No. 4539, Independent #6 lode, determined by the method of parallel end lines, falls on steep, decomposing cliff face where it is impracticable to establish a permanent monument; there is no remaining evidence of the original corner.</p> |
|        | <p>From this point, the point selected for the witness cor. to Cor. No. 2, bears S. 37°15'50" E., 0.500 chs. dist.</p>   |
|        | <p>At the witness corner point</p>   |
|        | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to solid rock, over a plastic-encased magnet, in a supporting mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p>  |

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4539,  
T. 20 S., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS



Cor. is located on top of ridge, bears NNE. and SSW.


Thence S. 52°46'20" W., on line 2-3, Mineral Survey No. 4539, Independent #6 lode.

1.254 Intersect line 4-1, Mineral Survey No. 4502, Independent Fraction lode, at a point from which the true point for Cor. No. 4, Independent Fraction lode, hereinbefore described, bears S. 47°30'50" E., 2.104 chs. dist.

22.720 Cor. No. 3, Mineral Survey No. 4539, Independent #6 lode, monumented with a limestone, 26x11x5 ins. (Record, 30x9x5 ins.), firmly set, projecting 12 ins. above the ground, mkd. I #6-3 4539 on a face and X on top, with a metal stake set alongside, with a metal tag mkd. Independent #6 SW PAT. ANNIV. #13 SE UNPAT., with a mound of stone, 3 ft. diam., 2 ft. high, W. of the cor.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to solid rock, over a plastic-encased magnet, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.



Bury the mkd. stone and metal stake alongside the stainless steel post.

Thence N. 37°15'50" W., on line 3-4, Mineral Survey No. 4539, Independent #6 lode.

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4539,  
T. 20 S., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA


|                         |  |
|-------------------------|--|
| <p>CHAINS<br/>9.117</p> | <p>Cor. No. 4, Mineral Survey No. 4539, Independent #6 lode, on line 1-2, Mineral Survey No. 4539, Valley View lode, monumented with a limestone, 20x12x4 ins. (Record, 24x12x5 ins.), firmly set, projecting 8 ins. above the ground, mkd. I#6-4-4539 on a face and X on top, with a metal stake set alongside, with metal tag mkd. NWC IND. 6 CORNER 4-6 PATENT. NE CORNER ANNIV-13, with a mound of stone, 3 ft. diam., 2 ft. high, N. of the cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="824 631 1144 839" data-label="Diagram"> </div> <p>Bury the mkd. stone and metal stake alongside the stainless steel post.</p> <hr/> <p>Thence N. 52°46'20" E., on line 4-1, Mineral Survey No. 4539, Independent #6 lode, identical with a portion of line 1-2, Mineral Survey No. 4539, Valley View lode.</p> <p>20.372 Cor. No. 1, Mineral Survey No. 4539, Valley View lode, hereinafter described.</p> <p>22.720 Cor. No. 1, Mineral Survey No. 4539, Independent #6 lode, and point of beginning.</p> <hr/> <p style="text-align: center;">Valley View lode</p> <p>From Cor. No. 4, Mineral Survey No. 4539, Independent #6 lode, on line 1-2, Mineral Survey No. 4539, Valley View lode, hereinbefore described.</p> <p>Thence, S. 52°46'20" W., on a portion of line 1-2, Mineral Survey No. 4539, Valley View lode.</p> <p>1.00 NW. corner of an excavated trench, bears South, 39 lks. dist.</p> <p>2.10 Dirt berm, bears SSE. and NNW.</p> <p>2.365 Cor. No. 2, Mineral Survey No. 4539, Valley View lode, monumented with a metal stake, 2 ft. long, firmly set 11 ins. in the ground, in a mound of stone, 3 ft. diam., 1 ft. high, with a broken limestone 16x14x3 ins. (Record, 30x16x4 ins.), mkd. VV-2-4539 on a face, lying loose alongside. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> |
|-------------------------|--|



DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4539,  
T. 20 S., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, over a plastic-encased magnet, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.



2015

Bury the mkd. stone and metal stake alongside the stainless steel post.

Thence, N. 1°55'40" W., on line 2-3, Mineral Survey No. 4539, Valley View lode.


0.60 Enter dirt berm, bears N. and S. An excavated trench lies W. of the berm.

4.20 Leave dirt berm.

9.604 Cor. No. 3, Mineral Survey No. 4539, Valley View lode, monumented with a limestone, 27x12x5 ins. (Record, 20x10x6 ins.), firmly set, projecting 11 ins. above the ground, mkd. VV-3 4539 on a face, with a mound of stone 3 ft. diam., 3 ft. high, NE. of the cor. and a mound of stone 5 ft. diam., 4 ft. high, E. of the cor.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, over a plastic-encased magnet, in a supporting mound of stone, 6 ft. base, to top, with brass cap mkd.




2015

Bury the mkd. stone alongside the stainless steel post.

From this point, a limestone, 5x5 ins., firmly set, projecting 4 ins. above the ground, mkd. X on top, with a metal stake set alongside, and a mound of stone, 5 ft. diam., 4 ft. high, E. of the stone, bears S. 70°58'20" E., 28.1 lks. dist.

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4539,  
T. 20 S., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

|        |   |
|--------|---|
| CHAINS | Thence, N. 52°44'00" E., on line 3-4, Mineral Survey No. 4539, Valley View lode.  |
| 14.599 | Intersect the line bet. secs. 10 and 15, at a point from which the 1/4 sec. cor. of secs. 10 and 15, hereinbefore described, bears N. 89°55'20" W., 19.539 chs. dist.   |
| 22.726 | Cor. No. 4, Mineral Survey No. 4539, Valley View lode, monumented with a chiseled X and VV-#4 4539, on the face of a limestone cliff.   |
|        | Thence, S. 2°02'10" E., on line 4-1, Mineral Survey No. 4539, Valley View lode.   |
| 4.933  | Intersect the line bet. secs. 10 and 15, at a point from which the cor. of secs. 10, 11, 14 and 15, hereinbefore described, bears S. 89°55'20" E. 13.737 chs. dist.   |
| 9.609  | Cor. No. 1, Mineral Survey No. 4539, Valley View lode, on line 4-1, Mineral Survey No. 4539, Independent #6 lode, monumented with a limestone 22x9x4 ins. (Record, 28x9x5 ins.), projecting 16 ins. above the ground, mkd. VV-1 4539 on a face with X on top. |
|        | At the corner point   |
|        | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.   |
|        |   |
|        | Bury the mkd. stone in the mound of stone.  |

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4540,  
T. 20 S., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

Reestablishment of Portions of the Survey  
Executed by U.S Mineral Surveyor, F.W. Rodolf, in 1922

Indipendant #13 lode

From Cor. No. 4, Mineral Survey No. 4540, Indipendant #13 lode, identical with Cor. No. 4, Mineral Survey No. 4837, Anniversary #1 lode, monumented with a limestone, 27x12x8 ins. (Record, 20x8x4 ins.), firmly set, projecting 12 ins. above the ground, mkd. I#13-4 4540 on N. face, with a mound of stone 4 ft. diam., 2 ft. high, E. of the cor., a mound of stone 3 ft. diam., 1/2 ft. high, SE. of the cor., a scattered mound of stone W. of the cor., and a limestone, 22x16x2 ins., lying loose alongside, mkd. NW. COR ANNIV #1 on one side and SWC IND #13 on the other side.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

|                  |          |
|------------------|----------|
| T20S R65E<br>S14 | I13      |
|                  | 4 MS4540 |
|                  | 4 A1     |
|                  | MS4837   |

2015

Bury the mkd. stone alongside the stainless steel post.

Thence N. 2°00'40" W., on line 4-1, Mineral Survey No. 4540, Indipendant #13 lode.

5.696 Intersect line 3-4, Mineral Survey No. 4502, Indipendant Fraction lode, at a point from which Cor. No. 3, Indipendant Fraction lode, hereinbefore described, bears N. 42°28'00" E., 10.944 chs. dist.

9.088 Cor. No. 1, Mineral Survey No. 4540, Indipendant #13 lode, identical with Cor. No. 1, Mineral Survey No. 4502, Indipendant #1 lode, monumented with a limestone, 23x11x6 ins., firmly set, projecting 11 ins. above the ground, in a mound of stone, 4 ft. diam., 1 ft. high, mkd. 4502 1-I#1 on E. face and I#13 1-4540 on S. face.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, over a plastic-encased magnet, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4540,  
T. 20 S., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

|        |    |                    |
|--------|----|--------------------|
|        | IF | I1<br>1 MS4502     |
| MS4502 |    | 1<br>I13<br>MS4540 |

2015

Bury the mkd. stone alongside the stainless steel post.

---

Indipendant #14 lode

From Cor. No. 2, Mineral Survey No. 4540, Indipendant #14 lode, identical with Cor. No. 4, Mineral Survey 4502, Indipendant lode and Cor. No. 1, Mineral Survey No. 4519, Indipendant #2 lode, hereinbefore described.

Thence S. 2°00'00" E., on line 2-3, Mineral Survey No. 4540, Indipendant #14 lode.

0.923 Intersect the line bet. secs. 11 and 14, at a point from which the 1/4 sec. cor. of secs. 11 and 14, hereinbefore described, bears S. 89°57'30" W., 7.287 chs. dist.

9.092 Cor. No. 3, Mineral Survey No. 4540, Indipendant #14 lode, on line 4-1, Mineral Survey No. 4837, Anniversary lode, monumented with a sandstone, 28x10x8 ins. (Record, limestone, 30x10x6 ins.), firmly set, projecting 16 ins. above the ground, mkd. I#14 3-4540 on a face and X on top, with a mound of stone, 3 ft. diam., 2 ft. high, N. of the cor.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to solid rock, over a plastic-encased magnet, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.

|        |      |
|--------|------|
| I14    | T20S |
| MS4540 | R65E |
| 3      | S14  |

---

A MS4837  
2015

---

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY No. 4837,  
T. 20 S., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

Reestablishment of a Portion of the Survey  
Executed by Mineral Surveyor, F.W. Millard, in 1954

## Anniversary lode

From Cor. No. 2, Mineral Survey No. 4837, Anniversary lode, identical with Cor. No. 2, Mineral Survey No. 4837, Anniversary #1 lode and Cor. No. 1, Mineral Survey No. 4837, Anniversary #2 lode, monumented with a limestone, 11x10x3 ins. (Record, sandstone, 24x11x4 ins.), loosely set in a mound of stone, 2 ft. diam., 1 ft. high, mkd. A-2 A1-2 A2-1 4837, with a metal stake set alongside, with metal tag mkd. NE COR A-2 NW COR A-3.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, over a plastic-encased magnet, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.

|          |           |
|----------|-----------|
| A1       | A         |
|          | MS4837    |
| MS4837 2 | 2         |
| A2 1     | T20S R65E |
| MS4837   | S14       |

2015

Bury the mkd. stone and lay the metal stake alongside the stainless steel post.

Thence N. 88°02'20" E., on line 2-3, Mineral Survey No. 4837, Anniversary lode.

11.391 A mound of stone, 2 ft. diam., 1 ft. high.

22.726 Cor. No. 3, Mineral Survey No. 4837, Anniversary lode, monumented with a metal stake, 2 ft. long, firmly set, projecting 1 1/2 ft. above a mound of stone, 3 ft. diam., 2 ft. high, with metal tag mkd. SEC. ANNIVERSARY PAT. NEC. ANN3 UNPAT., and a limestone, 24x11x9 ins. (Record, sandstone, 24x10x4 ins.), lying loose alongside, mkd. A-3 4837. This is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to solid rock, over a plastic-encased magnet, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY No. 4837,  
T. 20 S., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

A  
MS4837  
3

T20S R65E  
S14

2015

Bury the mkd. stone and metal stake alongside the stainless steel post.

Thence N. 01°50'10" W., on line 3-4, Mineral Survey No. 4837, Anniversary lode.

- 9.101 Cor. No. 4, Mineral Survey No. 4837, Anniversary lode, monumented with a limestone 30x6x6 ins. (Record, sandstone, 24x8x6 ins.), firmly set, projecting 9 ins. above the ground, mkd. A-4 4837 on a face and X on top, with a mound of stone, 4 ft. diam., 2 ft. high, NE. of the cor., with a limestone, 18x14x2 ins., mkd. NE COR. ANNIV. LODE, lying loose on top.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to solid rock, over a plastic-encased magnet, in a supporting mound of stone, 2 ft. base, to top, with brass cap mkd.

T20S R65E

S14

4

A  
MS4837

2015

Bury the mkd. stone alongside the stainless steel post.


Thence S. 86°55'30" W., on a portion of line 4-1, Mineral Survey No. 4837, Anniversary lode.

- 0.343 Cor. No. 3, Mineral Survey No. 4540, Indipendant #14 lode, hereinbefore described.

Anniversary #1 lode

From Cor. No. 3, Mineral Survey No. 4837, Anniversary #1 lode, identical with Cor. No. 4, Mineral Survey No. 4837, Anniversary #2 lode, monumented with a limestone, 24x14x6 ins. (Record, sandstone), firmly set, projecting 10 ins. above the ground, mkd. A1-3 A2-4 4837, with a mound of stone, 4 ft. diam., 2 1/2 ft. high, E. of the cor., a mound of stone, 2 1/2 ft. diam., 1 ft. high, S. of the cor., and a mound of stone 4 ft. diam., 2 ft. high, W. of the cor.

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY No. 4837,  
T. 20 S., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

| CHAINS |   |
|--------|---|
|        | <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;">  <p style="margin-left: 100px;">T20S R65E<br/>S14</p> <p style="margin-left: 150px;">A1<br/>3<br/>MS 4837<br/>4<br/>A2</p> <p style="margin-left: 150px;">2015</p> </div> <p>Bury the mkd. stone alongside the stainless steel post.</p> <p>Thence N. 2°00'10" W, on line 3-4, Mineral Survey No. 4837, Anniversary #1 lode.</p> <p>2.793 From this point, a scattered mound of stone, 3 1/2 ft. diam., 1 1/2 ft. high, with a limestone 15x13x2 ins. lying loose on top, mkd. SEC IND#18, bears West, 0.27 chs. dist.</p> <p>3.555 A limestone, 10x3 ins., firmly set, projecting 11 ins. above the ground, mkd. X on top, with a mound of stone 2 1/2 ft. diam., 3 ft. high, N. of the stone, a mound of stone, 3 ft. diam., 2 1/2 ft. high, NE. of the stone, and a limestone, 20x13x2 ins., mkd. NE Cor ANNIV #6, lying loose nearby.</p> <p>5.20 Road cut, bears, ENE. and WSW.</p> <p>9.091 Cor. No. 4, Mineral Survey No. 4837, Anniversary #1 lode, identical with Cor. No. 4, Mineral Survey No. 4540, Indipendant #13 lode, hereinbefore described.</p> <hr/> <p style="text-align: center;">Anniversary #2 lode</p> <p>From Cor. No. 1, Mineral Survey No. 4837, Anniversary #2 lode, identical with Cor. No. 2, Mineral Survey No. 4837, Anniversary lode and Cor. No. 2, Mineral Survey No. 4837, Anniversary #1 lode, hereinbefore described.</p> <p>Thence S. 2°14'40" E., on line 1-2, Mineral Survey No. 4837, Anniversary #2 lode.</p> <p>4.571 A wood stake, 1 1/2x1 1/2 ins., firmly set, projecting 3 ft. above a mound of stone, 1 1/2 ft. diam., 1/2 ft. high, with metal tag mkd. WE CL ANN3 W Property Line to Ann Claim.</p> <p>9.096 Cor. No. 2, Mineral Survey No. 4837, Anniversary #2 lode, monumented with a sandstone, 26x11x4 ins. (Record, 24x11x6 ins.), firmly set, projecting 4 ins. above the ground, mkd. A2-2 4837, with a mound of stone, 4 ft. diam., 3 ft. high, E. of the cor.</p> <p>At the corner point</p> |

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY No. 4837,  
T. 20 S., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

|        |  |
|--------|--|
| CHAINS | <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>A2<br/>MS4837<br/>2</p> <p>T20S R65E<br/>S14</p> <p>2015</p> </div> <p>Bury the mkd. stone alongside the stainless steel post.</p> <hr/> <p>Thence S. 87°59'00" W., on line 2-3, Mineral Survey No. 4837, Anniversary #2 lode.</p> <p>11.399 From this point, a mound of stone, 3 ft. diam., 3 ft. high, with a limestone, 14x11x1 ins., mkd. NSC ANNIV #5, lying loose on top, with a broken limestone, 18x11x2 ins., mkd. NSC ANNIV #5 lying loose alongside, bears South, 2 lks. dist.</p> <p>11.423 From this point, a mound of stone, 3 1/2 ft. diam., 3 ft. high, with a limestone, 13x11x1 ins., mkd. SSC ANNIV #2, lying loose on top, bears North, 4 lks. dist.</p> <p>16.20 Enter blacktop area, bears N. and S.</p> <p>18.00 Leave blacktop area, bears SE. and NW.</p> <p>19.90 Enter disturbed area.</p> <p>22.732 Cor. No. 3, Mineral Survey No. 4837, Anniversary #2 lode, monumented with a limestone, 25x12x7 ins. (Record, sandstone, 24x9x8 ins.), firmly set, projecting 5 ins. above the ground, mkd. A2-3 4837, with a mound of stone, 4 ft. diam., 1 1/2 ft. high, W. of the cor., with a limestone, 14x12x2 ins., mkd. S.W. COR ANNIV. #2, lying loose on top.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>MS4837<br/>A2<br/>3</p> <p>T20S R65E<br/>S14<br/>2015</p> </div> <p>Bury the mkd. stones alongside the stainless steel post.</p> <hr/> <p>Thence N. 2°01'40" W, on line 3-4, Mineral Survey No. 4837, Anniversary #2 lode.</p> |
|--------|--|



DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY No. 4837,  
T. 20 S., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

|        |   |
|--------|---|
| CHAINS | Through disturbed area.   |
| 1.10   | Leave disturbed area.   |
| 1.511  | A sandstone, 11x4 ins., firmly set, projecting 4 ins. above the ground, mkd. X on top, with a scattered mound of stone, 4 ft. diam., 1 ft. high, W. of the cor.   |
| 2.15   | A scattered mound of stone, 5 ft. diam., 1 ft. high.  |
| 3.30   | Road cut, bears, ENE. and WSW.  |
| 4.40   | Enter disturbed area.   |
| 5.70   | Leave disturbed area.   |
| 9.089  | Cor. No. 4, Mineral Survey No. 4837, Anniversary #2 lode, identical with Cor. No. 3, Mineral Survey No. 4837, Anniversary #1 lode, hereinbefore described.  |
|        | <hr/>   |
|        | GENERAL DESCRIPTION   |
|        | The average elevation is about 2,000 feet. Vegetation consists of creosote and cacti. General drainage is to the south, provided by many dry washes which flow into Lovell Wash. The area has a history of mining, however no active mining was observed during the course of this survey. The area lies between Lake Mead to the south and the Muddy Mountains to the north. |
|        | <hr/>   |

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

|                       |                    |
|-----------------------|--------------------|
| Brock R. Clifford     | Cadastral Surveyor |
| Brandon G. Courtright | Cadastral Surveyor |
| Carlos Gil-Mendoza    | Cadastral Surveyor |
| Wyatt B. Buttler      | Surveying Intern   |
| Lucas T. Beauchamp    | Surveying Intern   |

## CERTIFICATE OF SURVEY

We, Joseph J. Johnson and Lee T. Wilson, Cadastral Surveyors, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 10th day of August, 2015, we have dependently resurveyed a portion of the subdivisional lines and portions of certain mineral surveys, Township 20 South, Range 65 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

MAY 08 2020

(Date)

*Mahmud O. Humming*  
/For Joseph J. Johnson  
(Cadastral Surveyor)

MAY 08 2020

(Date)

*Lee T. Wilson*  
(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Reno, Nevada

The foregoing field notes of the dependent resurvey of a portion of the subdivisional lines and portions of certain mineral surveys, Township 20 South, Range 65 East, of the Mount Diablo Meridian, in the State of Nevada, executed by Joseph J. Johnson and Lee T. Wilson, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

MAY 08 2020

(Date)

*Mahmud O. Humming*  
(Chief Cadastral Surveyor for Nevada)

~~CERTIFICATE OF TRANSCRIPT~~
~~I CERTIFY that the foregoing transcript of the field notes of the above described surveys in Township 20 South, Range 65 East, Mount Diablo Meridian, Nevada, is a true copy of the original field notes.~~
~~(Date)~~
~~(Chief Cadastral Surveyor for Nevada)~~