

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF

A PORTION OF THE SOUTH BOUNDARY OF TOWNSHIP 22 NORTH, RANGE 20 EAST,

A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF SECTIONS 2, 3, 10 AND 29,

TOWNSHIP 21 NORTH, RANGE 20 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATE OF NEVADA

EXECUTED BY

Justin V. Haddon, Cadastral Surveyor

Under Special Instructions dated, June 22, 2017

and approved, June 22, 2017

and Amended Special Instructions dated, June 1, 2018

and approved, June 1, 2018

which provided for the surveys included under Group No. 972,

and Assignment Instructions dated, June 22, 2017.

Survey commenced June 23, 2017

Survey completed June 5, 2018

INDEX DIAGRAM

TOWNSHIP 21 NORTH, RANGE 20 EAST, MOUNT DIABLO MERIDIAN, NEVADA

31	32	33	34	35	36
		4	3	2	
6	5	4 13	3 6	2	1
7	8	9	12 10 11	5 11	12
18 25	17	16 20	10 15	14	13
19	24 20 24	19 21 18	22	23	24
30	22 29 21	17 28 15	9 27	26	25
31	32	33 7	34	35	36

SUBDIVISION OF SECTION 2 pp 26 - 28
 SUBDIVISION OF SECTION 3 pp 28 - 29
 SUBDIVISION OF SECTION 10 p 29
 SUBDIVISION OF SECTION 29 pp 29 - 30

TOWNSHIP 21 NORTH, RANGE 20 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The following field notes are those providing for the dependent resurvey of a portion of the south boundary of Township 22 North, Range 20 East and a portion of the subdivisional lines, and the subdivision of sections 2, 3, 10 and 29, Township 21 North, Range 20 East, Mount Diablo Meridian, Nevada.

The south boundary (Fourth Standard Parallel North) was surveyed by U.S. Deputy Surveyor B. Ives in 1861, under Contract A. The north, east and west boundaries were surveyed by U.S. Deputy Surveyor A.J. Hatch in 1867, under Contract No. 6. A portion of the subdivisional lines were surveyed by U.S. Deputy Surveyors A.J. Hatch and J.C. Smyles in 1872, under Contract No. 50. A portion of the south boundary (Fourth Standard Parallel North), the west and north boundaries and a portion of the subdivisional lines were resurveyed and a portion of the subdivisional lines were surveyed by U.S. Deputy Surveyor J.B. Menardi in 1906, under Contract No. 244. A portion of the south boundary of T. 22 N., R. 20 E. was dependently resurveyed by U.S. Cadastral Engineer E. Voigt in 1924, under Group No. 107. Portions of the east and north boundaries and a portion of the subdivisional lines were dependently resurveyed and a portion of the subdivisional lines were surveyed by Cadastral Engineer C.S. Swanholm in 1935, under Group No. 156. The west boundary was dependently resurveyed by Associate Cadastral Engineer C.S. Swanholm and Assistant Cadastral Engineer J.W. Hardison in 1941-1942, under Group No. 312. A portion of the south boundary (Fourth Standard Parallel North) was dependently resurveyed by Cadastral Surveyors E.W. Sibley and R.K. Baugh in 1976-1977, under Group No. 544. A portion of the south boundary and a portion of the subdivisional lines of T. 22 N., R. 20 E. were dependently resurveyed and sections 4, 9 and 16 of this township were subdivided by Cadastral Surveyor R.A. Pratt in 1987, under Group No. 644. A portion of the subdivisional lines were dependently resurveyed, section 22 was subdivided and lot 11 in section 22 was surveyed by Cadastral Surveyor R.A. Pratt in 1991, under Group No. 696.

Before restoring the corners, the lines of the original surveys were retraced and a diligent search made for any evidence of the original corners and other calls of the original field note record.

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 2009, and the Special Instructions for Group No. 972, dated June 22, 2017, and the Amended Special Instructions dated June 1, 2018.

Measurements were made with Trimble R8 and R10 Global Positioning System (GPS) receivers using the real-time kinematic method and refer to the true meridian based on geodetic methods. The mean bearings of the lines and horizontal equivalents of ground distances, only, are entered into the field notes.

TOWNSHIP 21 NORTH, RANGE 20 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Certain topographic features were scaled using rectified aerial photography.</p> <p>The NAD 1983 (2011) (Epoch:2010.0000) geographic position, of the following corners were determined by GPS static observations processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuous Operating Reference Stations (CORS), DG6525 COF1 FERNLEY COOP CORS ARP, DE6254 RNO1 NW RENO COOP CORS ARP, DE6260 STEA STEAD COOP CORS ARP, and carried forward by RTK observations is as follows:</p> <p>The 1/4 section corner of sections 1 and 2, is as follows:</p> <p>Latitude: 39°42'56.467" N. Longitude: 119°41'43.501" W.</p> <p>The corner of sections 29, 30, 31 and 32, is as follows:</p> <p>Latitude: 39°39'01.791" N. Longitude: 119°46'18.924" W.</p> <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY, T. 22 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor A.J. Hatch in 1867, a Portion of the Survey and Resurvey Executed by U.S. Deputy Surveyor J.B. Menardi in 1906, a Portion of the Dependent Resurvey Executed by U.S. Cadastral Engineer E. Voigt in 1924, and a Portion of the Dependent Resurvey Executed by Cadastral Surveyor R.A. Pratt in 1987</p> <hr/> <p>Beginning at the 1/4 sec. cor. of secs. 2 and 35, monumented with an iron post, 1 in. diam., firmly set, projecting 17 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the boundaries of secs. 27, 34 and 35 of T. 22 N., R. 20 E., executed under Group No. 107. There is no remaining evidence of the 1906 mkd. stone.</p> <p>S. 89°46'10" W., on the S. bdy. of sec. 35.</p> <p>1.4 Spur, slopes S. 45° E.</p> <p>2.8 Ravine, drains S. 25° E.</p> <p>8.3 Spur, slopes E.</p> <p>19.840 The W 1/16 sec. cor. of sec. 2 only, T. 21 N., R. 20 E., hereinafter described.</p> <p>19.967 Point for the W 1/16 sec. cor. of sec. 35 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
--------	---

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 22 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>S35 W 1/16</p> <hr/> <p>2017</p> <p>Point is located on spur, slopes S. 25° E.</p>
25.0	Ravine, drains S. 15° E.
39.934	<p>The cor. of secs. 34 and 35, monumented with a basalt stone, 23x12x6 ins. (1906 Record: 20x10x10 ins.), firmly set, projecting 14 ins. above a mound of stone, 4 ft. diam., 1 ft. high, mkd. with 2 notches on the E. edge and 4 notches on the W. edge, with an iron post, 2 ins. diam., 36 ins. long, lying loose alongside, with brass cap mkd. as described in the field notes of the dependent resurvey of the boundaries of secs. 27, 34 and 35 of T. 22 N., R. 20 E., executed under Group No. 107.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 9 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p>T22N R20E S34 S35</p> <hr/> <p>S 2 T21N R20E</p> <p>2017</p> <p>Bury mkd. stone and iron post alongside stainless steel post.</p> <hr/> <p>N. 89°28'00" W., on the S. bdy. of sec. 34.</p>
1.6	Spur, slopes S. 35° W.
2.425	The closing cor. of secs. 2 and 3, T. 21 N., R. 20 E., hereinafter described.
9.4	Ravine, drains S. 40° W.
19.1	Spur, slopes S. 45° W.
40.049	<p>The 1/4 sec. cor. of sec. 34 only, monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above a mound of stone, 4 ft. diam., 2 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of the boundaries of secs. 27, 34 and 35 of T. 22 N., R. 20 E., executed under Group No. 107, with a basalt stone, 20x12x10 ins. (1906 Record: 18x8x8 ins.), firmly set alongside, projecting 10 ins. above the ground, mkd. 1/4 on the N. face.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 22 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Bury mkd. stone alongside iron post, within mound of stone.</p> <hr/> <p>S. 89°29'50" W., beginning new measurement.</p>
2.540	The 1/4 sec. cor. of sec. 3 only, T. 21 N., R. 20 E., hereinafter described.
3.6	Ravine, drains S. 45° W.
8.1	Spur, slopes S. 45° W.
23.8	Spur, slopes S. 30° W.
25.3	Gulch, drains N. 10° W.
33.9	Gulch, drains N. 15° W.
40.047	<p>The cor. of secs. 33 and 34, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the S. bdy. of T. 22 N., R. 20 E., executed under Group No. 644, with a granite stone, 14x14x9 ins. (1906 Record: 18x8x8 ins.), loosely set, projecting 9 ins. above the ground, mkd. with 2 grooves on the E. face and 3 grooves on the W. face, and an embedded mound of stone, 3 ft. diam., N. of cor.</p> <p>Bury mkd. stone alongside iron post.</p> <hr/> <p>N. 89°47'30" W., on the S. bdy. of sec. 33.</p>
2.657	The closing cor. of secs. 3 and 4, T. 21 N., R. 20 E., hereinafter described.
22.748	<p>The E 1/16 sec. cor. of sec. 4 only, T. 21 N., R. 20 E., monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above a partially embedded mound of stone, 3 ft. diam., 1 ft. high, with aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines of T. 21 N., R. 20 E., executed under Group No. 644.</p> <p>Cor. is located 11 lks. S. of barbed wire fence, bears E. and W.</p>
39.878	<p>The 1/4 sec. cor. of sec. 33 only, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, flush in a partially embedded mound of stone, 4 ft. diam., 1 ft. high, with aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of the S. bdy. of T. 22 N., R. 20 E., executed under Group No. 644.</p> <p>Cor. is located 5 lks. S. of barbed wire fence, bears E. and W.</p> <hr/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyors A.J. Hatch and J.R. Syles in 1872, a Portion of the Survey and Resurvey Executed by U.S. Deputy Surveyor J.B. Menardi in 1906, and a Portion of the Resurvey Executed by Cadastral Surveyor R.A. Pratt in 1987</p> <hr/> <p>Beginning at the 1/4 sec. cor. of secs. 2 and 11, perpetuated by person(s) unknown, monumented with a rebar, 5/8 in. diam., firmly set, flush in a concrete fence corner footing, with hog wire fences extending N. and E. This position correlates well with measurements shown on Survey Map No. 1083, File No. 471400, as recorded in Washoe County, Nevada, and is accepted as a careful and faithful perpetuation of the position of the 1906 corner.</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground for a reference monument, bears S. 32°24'30" W., 98.9 lks. dist., with brass cap mkd. RM S11 1/4 65.3 FT. TO COR. 2017 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground for a reference monument, bears N. 53°30'50" W., 55.8 lks. dist., with brass cap mkd. RM S2 1/4 36.8 FT. TO COR. 2017 and an arrow pointing to the corner.</p> <p>N. 89°56'00" W., on the S. bdy. of sec. 2.</p> <p>14.6 Spur, slopes S.</p> <p>21.5 Ravine, drains S. 25° E.</p> <p>39.083 The closing cor. of secs. 10 and 11, monumented with a basalt stone 12x12 ins., loosely set, projecting 8 ins. above the ground, with 2 grooves on the E. face and CC on the S. face, no other visible marks, with a partially embedded mound of stone, 3 ft. diam., 1 ft. high, S. of cor.</p> <p>44.933 The cor. of secs. 2 and 3, monumented with a lava stone, 16x10x6 ins. (1906 Record: 16x10x8 ins.), firmly set, projecting 9 ins. above the ground, mkd. with 4 grooves on the S. face and 2 grooves on the E. face, with an embedded mound of stone, 4 ft. diam., N. of corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>
--------	---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T21N R20E S 3 S 2 ----- S10 2017</p> <p>Bury mkd. stone alongside stainless steel post and leave embedded mound of stone in place.</p> <hr/> <p>N. 0°03'00" E., bet. secs. 2 and 3.</p> <p>4.7 Ravine, drains E.</p> <p>6.9 Spur, slopes S. 50° E.</p> <p>16.8 Ravine, drains S. 75° E.</p> <p>35.8 Ridge, bears N. 35° E. and S. 35° W.</p> <p>40.668 The 1/4 sec. cor. of secs. 2 and 3, monumented with a basalt stone, 22x10x6 ins. (1906 Record: 24x8x4 ins.), firmly set, projecting 15 ins. above the ground, mkd. 1/4 on the W. face, with a mound of stone, 3 ft. diam., 1 ft. high, W. of corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T21N R20E 1/4 S 3 S 2 2017</p> <p>Bury mkd. stone alongside stainless steel post and leave mound of stone in place.</p> <hr/> <p>N. 0°02'30" W., beginning new measurement.</p> <p>5.6 Head of ravine, drains N. 45° W.</p> <p>16.9 Ravine, drains S. 45° W.</p> <p>23.6 Spur, slopes S. 50° E.</p> <p>44.216 Point for the closing cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div data-bbox="882 304 1030 478" data-label="Text"> <p>T22N R20E S34 <div style="border-top: 1px solid black; width: 100px; margin: 0 auto;"></div> <div style="display: flex; justify-content: space-around; width: 100px; margin: 0 auto;"> S 3 S 2 </div> T21N R20E CC</p> </div> <div data-bbox="923 517 987 538" data-label="Text"> <p>2017</p> </div> <div data-bbox="431 572 1329 649" data-label="Text"> <p>From this point, the cor. of secs. 34 and 35, T. 22 N., R. 20 E., hereinbefore described, bears S. 89°28'00" E., 2.425 chs. dist.</p> </div> <hr/> <div data-bbox="431 708 1447 789" data-label="Text"> <p>The point for the W 1/16 sec. cor. of sec. 2, on the S. bdy. of T. 22 N., R. 20 E., and at proportionate distance in departure on the N. bdy. of sec. 2.</p> </div> <div data-bbox="431 815 1430 895" data-label="Text"> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> </div> <div data-bbox="865 981 1030 1006" data-label="Text"> <p> <div style="border-top: 1px solid black; width: 100px; margin: 0 auto;"></div> W 1/16 S 2 </p> </div> <div data-bbox="923 1044 987 1066" data-label="Text"> <p>2017</p> </div> <div data-bbox="431 1100 1329 1181" data-label="Text"> <p>From this point, the cor. of secs. 34 and 35, T. 22 N., R. 20 E., hereinbefore described, bears S. 89°46'10" W., 20.094 chs. dist.</p> </div> <hr/> <div data-bbox="431 1240 1447 1372" data-label="Text"> <p>From the 1/4 sec. cor. of secs. 33 and 34, determined at record bearing and distance, from an accessory recovered by Michael A. Wade, Nevada Professional Land Surveyor No. 4431, in 1995, as recorded in Washoe County, Nevada, Subdivision Tract Map No. 3130, File No. 1880896.</p> </div> <div data-bbox="431 1398 981 1427" data-label="Text"> <p>from which the recovered accessory</p> </div> <div data-bbox="541 1453 1392 1559" data-label="Text"> <p style="padding-left: 40px;">A rebar, 5/8 in. diam., 18 ins. long, firmly set, bent over flush with the ground, bears WEST, 1.2 lks. dist., with an aluminum cap, badly damaged, mkd. Robert. N. W.C.</p> </div> <div data-bbox="431 1585 736 1615" data-label="Text"> <p>At the corner point</p> </div> <div data-bbox="431 1640 1409 1696" data-label="Text"> <p>Set a copper coated steel stake, 24 ins. long, 1/2 in. diam., 30 ins. in the ground, with brass cap mkd.</p> </div>
--------	---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">BLM T21N R20E 1/4 S33 S34 2017</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 40°18'00" W., 196.2 lks. dist., with brass cap mkd. RM S33 129.5 FT. TO COR. 2018 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 67°59'40" W., 180.0 lks. dist., with brass cap mkd. RM S33 118.8 FT. TO COR. 2018 and an arrow pointing to the corner.</p> <p>Bury rebar alongside the stainless steel post set as the Northwesterly reference monument.</p> <p>Cor. is located in center of dirt road, 40 lks. wide, bears E. and W.</p> <p>N. 0°11'00" W., bet. secs. 33 and 34.</p> <p>39.948 Point for the cor. of secs. 27, 28, 33 and 34, reestablished by the method of three-point control; utilizing information contained within Subdivision Tract Map No. 3130, File No. 1880896, Survey Map No. 1226, File No. 552773, and Parcel Map No. 2476, File No. 1441454, all filed in Washoe County, Nevada. There is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 34 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T21N R20E S28 S27 S33 S34 2018</p> <p>from which</p> <p>XBO, chiseled into concrete canal, 8 lks. wide, drains S., for a bearing object, bears N. 3°00'50" E., 243.8 lks. dist.</p>
--------	---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 27 ins. in the ground for a reference monument, bears N. 71°33'20" W., 227.0 lks. dist., with brass cap mkd. RM S28 149.8 FT. TO COR. 2017 and an arrow pointing to the corner.</p> <p>Cor. is located on E. edge of dirt road, 45 lks. wide, bears N. and S., and 4 lks. W. of barbed wire fence, bears N. and S.</p> <hr/> <p>N. 0°11'00" W., bet. secs. 27 and 28.</p>
14.30	Eagle Canyon Road, 45 lks. wide, bears S. 80° E., and N. 80° W.
39.870	<p>Point for the 1/4 sec. cor. of secs. 27 and 28, at proportionate distance by the irregular boundary adjustment method, utilizing information contained within Parcel Map No. 2476, File No. 1441454, filed in Washoe County, Nevada. This point is occupied by a rebar, no record found, 5/8 in. diam., 18 ins. long, firmly set, 6 ins. below surface of the ground, with plastic cap mkd. ODYSSEY ENG PLS 10839. There is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T21N R20E 1/4 S28 S27 2018</p> <p>Bury rebar alongside stainless steel post.</p> <p>Cor. is located 4 lks. W. of concrete canal, 15 lks. wide, drains S.</p> <hr/> <p>N. 0°00'40" W., beginning new measurement.</p>
24.7	Corner of vinyl fences, extending N. and E.
34.2	Corner of vinyl fences, extending E. and S.
39.41	Gravel road, 20 lks. wide, bears N. 75° E. and S. 75° W.
40.017	<p>The cor. of secs. 21, 22, 27 and 28, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 9 ins. above a mound of stone, 3 ft. diam., 1/2 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines of T. 21 N., R. 20 E., executed under Group No. 696.</p> <p>Cor. is located in a corner of barbed wire fences, extending N. and W.</p> <hr/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the cor. of secs. 16 and 21, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines of T. 21 N., R. 20 E., executed under Group No. 644, with a granite stone, 24x12x12 ins., lying loose alongside, mkd. with 3 notches on an edge, 3 notches on another edge, R20E on a face and T21N on another face.</p> <p>Cor. is located in the corner of barbed wire fences, extending N., S. and W.</p> <p>From this cor., the closing corner of secs. 15 and 22, bears S. 0°03'18" E., 0.906 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines of T. 21 N., R. 20 E., executed under Group No. 696.</p> <p>N. 0°00'50" W., on the E. bdy. of sec. 16.</p>
14.5	Ravine, drains E.
20.047	<p>The S 1/16 sec. cor. of secs. 15 and 16, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines of T. 21 N., R. 20 E., executed under Group No. 644. This cor. will now refer to sec. 16 only. Modify cap markings to refer to sec. 16 only and add 2017 to aluminum cap.</p> <p>Cor. is located in barbed wire fence, bearing N. and S.</p> <hr/> <p>N. 0°00'10" W., beginning new measurement.</p>
7.90	Trail road with barbed wire gate, 10 lks. wide, bears S. 85° E. and N. 85° W., in the bottom of Stormy Canyon, drains S. 85° E.
8.87	Trail road with barbed wire gate, 10 lks. wide, bears S. 55° E. and N. 55° W.
20.059	<p>The 1/4 sec. cor. of secs. 15 and 16, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines of T. 21 N., R. 20 E., executed under Group No. 644.</p> <p>Cor. is located in barbed wire fence, bearing N. and S.</p> <hr/> <p>N. 0°01'40" E., beginning new measurement.</p>
10.5	Ravine, drains S. 30° E.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.020	<p>The N 1/16 sec. cor. of secs. 15 and 16, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines of T. 21 N., R. 20 E., executed under Group No. 644.</p> <p>Cor. is located in barbed wire fence, bearing N. and S.</p> <hr/> <p>N. 0°01'40" E., beginning new measurement.</p>
0.13	<p>Trail road, 12 lks. wide, bears N. 65° E. and S. 65° W.</p>
20.020	<p>The cor. of secs. 9, 10, 15 and 16, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above an embedded mound of stone, 3 ft. diam., with aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines of T. 21 N., R. 20 E., executed under Group No. 644, with a rhyolite stone, 10x10 ins., firmly set alongside, projecting 6 ins., mkd. with 4 grooves on S. face, and 3 grooves on E. face.</p> <p>from which the 1906 bearing tree</p> <p style="padding-left: 40px;">Remains of a juniper, dead and downed, no visible blaze, bears N. 78°16' E., 52.0 lks. dist. (Record: N. 80°15' E., 54 lks. dist.)</p> <p>Cor. is located in barbed wire fence, bearing N. and S.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 10 and 15, monumented with a basalt stone, 18x12x8 ins. (Record: 20x14x10 ins.), firmly set, projecting 10 ins. above the ground, mkd. 1/4 on the N. face, with a mound of stone, 4 ft. diam., 1 ft. high, N. of corner.</p> <p>from which the 1906 bearing trees</p> <p style="padding-left: 40px;">A juniper, 10 ins. diam., bears N. 0°15' E., 67.2 lks. dist. (Record: N. 1° E., 64 lks. dist.), with an open blaze, clearly mkd. 1/4 S10 BT.</p> <p style="padding-left: 40px;">A juniper, 24 ins. diam., bears S. 62°26' W., 77.7 lks. dist. (Record: S. 60° W., 82 lks. dist.), with the marks 1/4 visible on a damaged blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>T21N R20E S10 1/4 — S15</p> <p>2017</p> <p>Bury mkd. stone alongside stainless steel post and leave mound of stone in place.</p> <p>N. 89°56'50" W., bet. secs. 10 and 15.</p>
2.6	Ridge, bears N. 25° E. and S. 25° W.
3.9	Descend, steep W. facing slope.
17.6	Ravine, drains N. 40° W.
25.9	Spur, slopes S. 25° W.
28.13	Trail road, 15 lks. wide, bears N. 25° E. and S. 25° W., in the bottom of a gulch, drains S. 25° W.
39.991	The cor. of secs. 9, 10, 15 and 16.
	<hr/> <p>From the cor. of secs. 2 and 3.</p> <p>S. 89°56'00' W., on the S. bdy. of sec. 3</p>
19.964	<p>Point for the E 1/16 sec. cor. of sec. 3 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p>E 1/16 S 3</p> <hr/> <p>2017</p> <p>Point located on crest of ridge, bears N. 15° E. and S. 15° W.</p>
35.9	Ravine, drains S. 10° W.
39.928	<p>The 1/4 sec. cor. of secs. 3 and 10, monumented with a basalt stone, 22x12x5 ins. (Record: 20x10x6 ins.), firmly set, projecting 10 ins. above the ground, mkd. 1/4 on the N. face, with a mound of stone, 3 ft. diam., 1 ft. high, N. of corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>T21N R20E S 3 1/4 — S10</p> <p>2017</p> <p>Bury mkd. stone alongside stainless steel post and leave mound of stone in place.</p> <hr/> <p>N. 89°58'50" W., beginning new measurement.</p>
9.0	Ridge, bears N. 30° E. and S. 30° W.
40.322	<p>The cor. of secs. 3, 4, 9 and 10, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines of T. 21 N., R. 20 E., executed under Group No. 644, with an embedded mound of stone, 3 ft. diam., W. of cor.</p> <p>Cor. is located in a barbed wire fence, bearing N. and S.</p> <hr/> <p>N. 0°02'40" W., bet. secs. 3 and 4.</p>
10.5	Ravine, drains W.
13.5	Spur, slopes N. 65° W.
17.7	Ravine, drains N. 55° W.
19.945	<p>The S 1/16 sec. cor. of secs. 3 and 4, determined at a chiseled X in bedrock, in the center of a mound of stone, 3 ft. diam., 2 ft. high, with aluminum post, 2 1/2 ins. diam., 28 ins. long, lying loose alongside, aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines of T. 21 N., R. 20 E., executed under Group No. 644, with a steel fence post firmly set alongside. Reset the aluminum post over the chiseled X, rebuild the mound of stone, 4 ft. base, to top, and add the marks 2017 to aluminum cap, leave steel fence post lying loose alongside.</p> <p>Cor. is located in a barbed wire fence, bearing N. and S.</p> <hr/> <p>N. 0°03'30' W., beginning new measurement.</p>
2.2	Spur, slopes N. 70° W.
10.5	Ravine, drains S. 55° W.
13.5	Spur, slopes S. 55° W.
19.2	Ravine, drains N. 60° W.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
19.945	<p>Point for the 1/4 sec. cor. of secs. 3 and 4, at proportionate distance by the irregular boundary adjustment method; the 1987 aluminum post, 2 1/2 ins. diam., 28 ins. long, found lying loose, position indeterminate, with aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines of T. 21 N., R. 20 E., executed under Group No. 644.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T21N R20E 1/4 S 4 S 3</p> <p style="text-align: center;">2017</p> <p>Bury aluminum post alongside stainless steel post.</p> <p>Cor. is located in a barbed wire fence, bearing N. and S.</p> <hr/> <p>N. 0°04'30" W., beginning new measurement.</p>
19.755	<p>The N 1/16 sec. cor. of secs. 3 and 4, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 9 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines of T. 21 N., R. 20 E., executed under Group No. 644, with a steel fence post firmly set alongside.</p> <p>Cor. is located in a barbed wire fence, bearing N. and S.</p> <hr/> <p>N. 0°04'10" W., beginning new measurement.</p>
4.2	Ravine, drains W.
17.04	Trail road, 12 lks. wide, bears S. 85° E. and N. 85° W.
25.184	<p>A rebar, of unknown origin, 5/8 in. diam., firmly set flush with ground at the position for the amended closing cor. of secs. 3 and 4, with the original amended monument, a basalt stone, 12x11x6 ins. (Record, 20x10x10 ins.), lying loose alongside, in a corner of barbed wire fences extending E., W., and S., mkd. with 6 grooves and CC on a face, and AM on another face.</p> <p>Bury mkd. stone alongside rebar.</p>
25.284	<p>The closing cor. of secs. 3 and 4, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 9 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines of T. 21 N., R. 20 E., executed under Group No. 644.</p> <p>Cor. located in a corner of barbed wire fences, extending E., W. and S.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From this cor., the corner of secs. 33 and 34, T. 22 N., R. 20 E., bears S. 89°47'30" E., 2.657 chs. dist., hereinbefore described.</p> <hr/> <p>The point for the 1/4 sec. cor. of sec. 3 only, on the S. bdy. of T. 22 N., R. 20 E., and at midpoint in departure on the N. bdy. of sec. 3.</p> <p>Set a stainless steel post, 2 1/2 ins. diam., 28 ins. long, 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T22N R20E</p> <hr style="width: 10%; margin: 0 auto;"/> <p>1/4 S 3</p> <p>T21N R20E</p> <p>2017</p> </div> <p>From this point, the cor. of secs. 33 and 34, T. 22 N., R. 20 E., bears S. 89°29'50" W., 37.507 chs. dist., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>S. 89°58'50" W., bet. secs. 28 and 33.</p> <p>3.05 Dirt road, 10 lks. wide, bears N. 30° E. and S. 30° W.</p> <p>20.045 The E 1/16 sec. cor. of secs. 28 and 33, determined by Robert N. Caldwell, Nevada Registered Land Surveyor No. 4233, in 1978, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, flush with ground, with an aluminum cap mkd. Robert N. Caldwell, RLS 4233, as recorded in Washoe County, Nevada, Survey Map No. 1226, File No. 552773. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 2 1/2 ins. diam., 28 ins. long, 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>S28</p> <p>E 1/16 —</p> <p>S33</p> <p>2017</p> </div> <p>Insert rebar inside stainless steel post.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>S. 89°58'20" W., beginning new measurement.</p>
--------	---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS							
20.033	<p>The 1/4 sec. cor. of secs. 28 and 33, reestablished by Robert N. Caldwell, Nevada Registered Land Surveyor No. 4233, in 1978, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, bent over and flush with ground, with a damaged aluminum cap with legible markings of N. Caldwell, RLS 4233, as recorded in Washoe County, Nevada, Survey Map No. 1226, File No. 552773. This is accepted as a careful and faithful reestablishment of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 2 1/2 ins. diam., 28 ins. long, 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T21N R20E</p> <p>S28</p> <p>1/4 —</p> <p>S33</p> <p>2017</p> </div> <p>Bury rebar alongside stainless steel post.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>S. 89°51'50" W., beginning new measurement.</p>						
11.4	Ravine, drains S. 70° E.						
34.22	Dirt road, 10 lks. wide, bears N. 10° E and S. 10° W.						
40.517	<p>The cor. of secs. 28, 29, 32 and 33, perpetuated by Robert N. Caldwell, Nevada Registered Land Surveyor No. 4233, in 1978, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 4 ins. above an embedded mound of stone, 4 ft. diam., with a damaged aluminum cap, with legible marks of N. Caldwell, RLS 4233, as recorded in Washoe County, Nevada, Survey Map No. 1226, File No. 552773. This is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 2 1/2 ins. diam., 28 ins. long, 20 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T21N R20E</p> <table style="margin: auto;"> <tr> <td>S29</td><td>S28</td></tr> <tr> <td colspan="2"><hr style="width: 100%;"/></td></tr> <tr> <td>S32</td><td>S33</td></tr> </table> <p>2017</p> </div> <p>Insert rebar inside stainless steel post.</p>	S29	S28	<hr style="width: 100%;"/>		S32	S33
S29	S28						
<hr style="width: 100%;"/>							
S32	S33						

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Cor. is located 12 lks. N. of a trail road, 12 lks. wide, bears E. and W.</p> <hr/> <p>N. 0°07'00" E., bet. secs. 28 and 29.</p>
37.3	Ravine, drains E.
39.820	<p>The 1/4 sec. cor. of secs. 28 and 29, monumented with a granite stone, 20x11x11 ins. (Record: 24x14x10 ins.), firmly set, projecting 10 ins. above a mound of stone, 3 ft. diam., 1 ft. high, mkd. 1/4 on the W. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T21N R20E 1/4 S29 S28</p> <p>2017</p> </div> <p>Bury mkd. stone alongside stainless steel post.</p> <hr/> <p>N. 0°15'00" W., beginning new measurement.</p>
8.0	Spur, slopes N. 80° E.
12.0	Ravine, drains N. 70° E.
17.9	Spur, slopes N. 40° E.
20.0	Ravine, drains N. 20° E.
35.58	Power line, bears E. and W.
36.32	Eagle Canyon Road, 45 lks. wide, bears S. 55° E. and N. 55° W.
37.40	Trail road, 10 lks. wide, bears S. 50° E. and N. 50° W.
40.033	<p>The cor. of secs. 20, 21, 28 and 29, perpetuated by William W. Grimm, Nevada Registered Land Surveyor No. 737, in 1999, no record found, monumented with an iron rod, 3/4 in. diam., 20 ins. long, firmly set, flush in a scattered mound of stone, with a brass cap, 2 1/2 ins. diam., mkd. T21N R20E 20 21 28 and 29 LS 737 1999, with a basalt stone, 18x10x6 ins., lying loose alongside, mkd. with 4 grooves on a face, and 2 grooves on another face. This position is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>At the corner point</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T21N R20E</p> <table border="1"> <tr> <td>S20</td><td>S21</td></tr> <tr> <td>S29</td><td>S28</td></tr> </table> <p>2017</p> </div> <p>Insert iron rod in stainless steel post and bury mkd. stone alongside.</p> <p>Cor. is located 15 lks. E. of a trail road, 15 lks. wide, bearing S. 50° E. and N. 50° W.</p> <hr/> <p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>S. 89°57'30" W., bet. secs. 21 and 28.</p> <p>5.0 Ravine, drains S. 50° E.</p> <p>39.8 Ridge, bears S. 35° E. and N. 35° W.</p> <p>40.404 The 1/4 sec. cor. of secs. 21 and 28, perpetuated by William W. Grimm, Nevada Registered Land Surveyor No. 737, in 1998, no record found, monumented with an iron rod, 3/4 in. diam., 30 ins. long, firmly set, projecting 6 ins. above the ground, with a brass cap, 2 1/2 ins. diam., mkd. T21N R20E 1/4 S21 S28 LS 737 1998, with a granite stone, 12x12x12 ins. (Record: 18x12x12 ins.), lying loose alongside, mkd. 1/4 on a face, and a mound of stone, 3 ft. diam., 1 ft. high, N. of corner. This position is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T21N R20E</p> <p>S21</p> <p>1/4 —</p> <p>S28</p> <p>2017</p> </div> <p>Bury iron rod and mkd. stone alongside stainless steel post.</p> <p>Cor. is located in a barbed wire fence, bearing E. and W.</p> <hr/> <p>S. 89°50'00" W., beginning new measurement.</p>	S20	S21	S29	S28
S20	S21				
S29	S28				

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
6.6	Ravine, drains S. 30° E.
12.6	Ridge, bears S. 55° E. and N. 55° W.
16.3	Ravine, drains S. 55° E.
24.3	Ridge, bears S. 60° E. and N. 60° W.
40.133	The cor. of secs. 20, 21, 28 and 29.
	<hr/>
	N. 0°08'50" W., bet. secs. 20 and 21.
8.1	Ravine, drains N. 80° E.
16.1	Ridge, bears S. 70° E. and N. 70° W.
25.0	Ravine, drains S. 75° E.
32.2	Ridge, bears S. 80° E. and N. 80° W.
40.039	The 1/4 sec. cor. of secs. 20 and 21, reestablished by George G. Lindesmith, Nevada Professional Land Surveyor No. 6306, in 2005, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 2 ins. above the ground, with plastic cap mkd. TRI STATE PLS 6306, as recorded in Washoe County, Nevada, Land Map No. 215, File No. 3313893. This is accepted as a careful and faithful reestablishment of the position of the original corner.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T21N R20E 1/4 S20 S21
	2017
	Insert rebar inside stainless steel post.
	Cor. is located in a ravine, drains N. 75° E.
	<hr/>
	N. 0°08'50" W., beginning new measurement.
2.7	Ridge, bears E. and W.
20.51	Trail road, 10 lks. wide, bears S. 55° E. and N. 55° W.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS							
40.039	<p>The cor. of secs. 16, 17, 20 and 21, perpetuated by person(s) unknown, no record found, monumented with an iron rod, 3/4 in. diam., 20 ins. long, firmly set, projecting 4 ins. above the ground, with a brass cap, 2 1/2 ins. diam., no visible markings, with a granite stone, 18x10x10 ins., lying loose alongside, mkd. with 4 grooves on a face, and 3 grooves on another face, and a mound of stone, 3 ft. diam., 1 ft. high, W. of cor. This is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T21N</td><td>R20E</td></tr> <tr> <td>S17</td><td>S16</td></tr> <tr> <td>S20</td><td>S21</td></tr> </table> <p>2017</p> </div> <p>Bury iron rod and mkd. stone alongside stainless steel post.</p> <p>Cor. is located 2 lks. W. of a corner of barbed wire fences, extending N., S. and E.</p>	T21N	R20E	S17	S16	S20	S21
T21N	R20E						
S17	S16						
S20	S21						
	<hr/> <p>From the cor. of secs. 16 and 21.</p> <p>S. 89°58'50" W., bet. secs. 16 and 21.</p>						
20.119	<p>The E 1/16 sec. cor. of secs. 16 and 21, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines of T. 21 N., R. 20 E., executed under Group No. 644, with a steel fence post firmly set alongside.</p> <p>Cor. is located in a barbed wire fence, bearing E. and W.</p>						
20.119	<hr/> <p>S. 89°58'50" W., beginning new measurement.</p> <p>The 1/4 sec. cor. of secs. 16 and 21, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines of T. 21 N., R. 20 E., executed under Group No. 644, with a mound of stone, 3 ft. diam., 2 ft. high, N. of cor.</p> <p>Cor. is located in a barbed wire fence, bearing E. and W.</p> <hr/> <p>S. 89°58'10" W., beginning new measurement.</p>						

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
14.5	Spur, slopes S.
20.191	<p>The W 1/16 sec. cor. of secs. 16 and 21, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 9 ins. above a mound of stone, 3 ft. diam., 1 ft. high, with aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines of T. 21 N., R. 20 E., executed under Group No. 644, with a steel fence post firmly set alongside.</p> <p>Cor. is located 5 lks. S. of a barbed wire fence, bears E. and W.</p> <hr/> <p>S. 89°54'50" W., beginning new measurement.</p>
1.6	Wash, 30 lks. wide, 4 ft. deep, drains S.
17.3	Ridge, bears S. 25° E. and N. 25° W.
20.206	<p>The cor. of secs. 16, 17, 20 and 21.</p> <hr/> <p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>S. 89°51'20" W., bet. secs. 29 and 32.</p>
12.0	Spur, slopes S. 50° E.
19.980	<p>Point for the E 1/16 sec. cor. of secs. 29 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>S29</p> <p>E 1/16 —</p> <p>S32</p> <p>2017</p> </div>
29.5	Head of ravine, drains S. 55 E.
39.960	<p>The 1/4 sec. cor. of secs. 29 and 32, monumented with a granite stone, 15x13x10 ins. (Record: 16x12x12 ins.), firmly set, projecting 8 ins. above a mound of stone, 3 ft. diam., 1 ft. high, mkd. 1/4 on the W. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 17 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>T21N R20E S29 1/4 — S32</p> <p>2017</p> <p>Bury mkd. stone alongside stainless steel post.</p> <hr/> <p>S. 89°51'20" W., beginning new measurement.</p> <p>3.0 High ridge, bears N. 35° E. and S. 35° W.</p> <p>4.8 Head of ravine, drains N. 5° E.</p> <p>27.8 Ridge, bears N. and S.</p> <p>34.1 Head of ravine, drains N. 10° E.</p> <p>38.7 Ridge, bears N. and S.</p> <p>39.854 The cor. of secs. 29, 30, 31 and 32, monumented with a granite stone, 18x12x12 ins., firmly set, projecting 8 ins. above the ground, with 5 grooves on the E. face, and 1 groove on the S. face, with a mound of stone, 5 ft. diam., 1 ft. high, W. of cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p>T21N R20E S30 S29 — — S31 S32</p> <p>2017</p> <p>Bury mkd. stone alongside stainless steel post and leave mound of stone in place.</p> <hr/> <p>N. 0°07'40" E., bet. secs. 29 and 30.</p> <p>9.0 Spur, slopes S. 80° W.</p> <p>16.6 Ravine, drains N. 75° W.</p> <p>23.1 Spur, slopes N. 60° W.</p> <p>31.2 Ravine, drains N. 55° W.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.088	<p>The 1/4 sec. cor. of secs. 29 and 30, monumented with a granite stone, 17x9x6 ins. (Record: 18x18x8 ins.), firmly set, projecting 12 ins. above the ground, mkd. 1/4 the on the W. face, with a mound of stone, 3 ft. diam., 1 ft. high, W. of cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T21N R20E 1/4 S30 S29</p> <p style="text-align: center;">2017</p> <p>Bury mkd. stone alongside stainless steel post and destroy witness mound.</p> <hr/> <p>N. 0°19'50" W., beginning new measurement.</p>
8.6	Spur, slopes N. 55° W.
17.7	Ravine, drains N. 85° W.
27.6	Spur, slopes N. 81° W.
33.2	Ravine, drains N. 55° W.
37.35	Power line, bears E. and W.
39.749	<p>The cor. of secs. 19, 20, 29 and 30, monumented with a granite stone, 18x12x6 ins. (Record: 20x10x8 ins.), firmly set, projecting 12 ins. above the ground, with 2 grooves on the S. face, and 5 grooves on the E. face, with a mound of stone, 3 ft. diam., 1 ft. high, W. of cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T21N R20E S19 S20 — — S30 S29</p> <p style="text-align: center;">2017</p> <p>Bury mkd. stone alongside stainless steel post and leave mound of stone in place.</p> <hr/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	From the cor. of secs. 20, 21, 28 and 29.
	S. 89°50'40" W., bet. secs. 20 and 29.
5.07	Eagle Canyon Road, 45 lks. wide, bears S. 55° E. and N. 55° W.
14.1	Descend, W. facing slope.
15.5	Trail road, 18 lks. wide, bears N. 50° E. and S. 50° W., in the bottom of a ravine, drains N. 50° E.
19.961	Point for the E 1/16 sec. cor. of secs. 20 and 29.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.
	<div style="text-align: center;"> S20 E 1/16 ——— S29 2017 </div>
27.9	Ridge, bears N. 15° W.
39.922	Point for the 1/4 sec. cor. of secs. 20 and 29, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<div style="text-align: center;"> T21N R20E S20 1/4 ——— S29 2017 </div>
47.2	Ridge, bears N. and S.
51.8	Ravine, drains N. 10° E.
72.3	Ridge, bears N. and S.
79.844	The cor. of secs. 19, 20, 29 and 30.
	<hr/> N. 0°08'20" E., bet. secs. 19 and 20.
3.3	Spur, slopes N. 35° W.
12.5	Ravine, drains N. 40° W.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.897	<p>The 1/4 sec. cor. of secs. 19 and 20, monumented with a granite stone, 20x12x10 ins. (Record: 24x12x10 ins.), firmly set, projecting 10 ins. above the ground, mkd. 1/4 on the W. face, with a mound of stone, 3 ft. diam., 1 ft. high, W. of cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T21N R20E 1/4 S19 S20</p> <p style="text-align: center;">2017</p> <p>Bury mkd. stone alongside stainless steel post and leave mound of stone in place.</p> <hr/> <p>N. 0°07'50" W., beginning new measurement.</p>
10.5	Ravine, drains N. 30 E.
20.0	Ridge, bears N. 75° E. and S. 75° W.
25.4	Ravine, drains N. 80° W.
39.272	<p>The cor. of secs. 17, 18, 19 and 20, monumented with a basalt stone, 18x12x12 ins. (Record: 18x14x14 ins.), firmly set, with 3 grooves on the S. face, and 5 grooves on the E. face, with a mound of stone, 3 ft. diam., 1 ft. high, W. of cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T21N R20E S18 S17 <hr/>S19 S20</p> <p style="text-align: center;">2017</p> <p>Bury mkd. stone alongside stainless steel post and leave mound of stone in place.</p> <hr/> <p>S. 89°54'10" W., bet. secs. 18 and 19.</p>
19.2	Low spur, slopes N. 35° W.
36.15	Old dirt road, 20 lks. wide, bears N. 7° E. and S. 7° W.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.119	<p>Point for the 1/4 sec. cor. of secs. 18 and 19, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a rebar, 18 ins. long, 5/8 in. diam., 6 ins. below the surface of a dirt road, with aluminum cap mkd.</p> <p style="text-align: center;">BLM T21N R20E S18 1/4 — S19</p> <p style="text-align: center;">2017</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground for a reference monument, bears N. 38°36'24" E., 165.86 lks. dist., with brass cap mkd. RM 1/4 S18 109.5 FT. TO COR. 2017 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground for a reference monument, bears N. 40°59'06" W., 164.24 lks. dist., with brass cap mkd. RM 1/4 S18 108.4 FT. TO COR. 2017 and an arrow pointing to the corner.</p> <p>Cor. is located in a dirt road, 35 lks. wide, bears N. 78° E and S. 78° W.</p>
49.84	Dirt road, 20 lks. wide, bears N. 20° E. and S. 20° W.
77.931	<p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the E. bdy. of T. 21 N., R. 19 E., executed under Group No. 312.</p>
	<p style="text-align: center;">SUBDIVISION OF SECTION 2, T. 21 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA</p>
	From the 1/4 sec. cor. of secs. 2 and 11.
	N. 1°43'10" W., on the N-S center line of sec. 2.
10.048	Corner of barbed wire fences, extending E. and S.

SUBDIVISION OF SECTION 2,
T. 21 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.154	<p>The center 1/4 sec. cor. of sec. 2, determined by Thomas A. Foote, Nevada Registered Land Surveyor No. 3736, in 1977, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, flush with ground, as recorded in Washoe County, Nevada, Survey Map No. 1083, File No. 471400. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T21N R20E C 1/4 S 2</p> <p style="text-align: center;">2017</p> <p>Bury rebar alongside stainless steel post.</p> <hr/> <p>N. 1°43'50" W., beginning new measurement.</p>
44.958	<p>The 1/4 sec. cor. of secs. 2 and 35, on the S. bdy. of T. 22 N., R. 20 E.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 1 and 2, monumented with an iron post, 1 in. diam., firmly set, flush in a concrete encasement, 1 ft. diam., 1 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivision of T. 21 N., R. 20 E., executed under Group No. 156.</p> <p>N. 89°14'20" W., on the E-W center line of sec. 2.</p>
1.77	<p>Nevada State Route 445, 45 lks. wide, bears N. 20° E. and S. 20° W.</p>
42.288	<p>The center 1/4 sec. cor. of sec. 2.</p> <hr/> <p>N. 89°14'10" W., beginning new measurement.</p>
19.783	<p>Point for the C-W 1/16 sec. cor. of sec. 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">W 1/16 C ——— C S 2</p> <p style="text-align: center;">2017</p>
43.691	<p>The 1/4 sec. cor. of secs. 2 and 3.</p> <hr/>

SUBDIVISION OF SECTION 2,
T. 21 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the C-W 1/16 sec. cor. of sec. 2.</p> <p>N. 1°49'10" W., on the N-S center line of the NW1/4 of sec. 2.</p>
44.616	<p>The W 1/16 sec. cor. of sec. 2, on the S. bdy. of T. 22 N., R. 20 E.</p> <hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 3, T. 21 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 3 and 10.</p> <p>N. 0°09'40" W., on the N-S center line of sec. 3.</p>
40.309	<p>Point for the center 1/4 sec. cor. of sec. 3, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T21N R20E C 1/4 S 3</p> <p style="text-align: center;">2017</p>
85.257	<p>The 1/4 sec. cor. of sec. 3, on the S. bdy. of T. 22 N., R. 20 E.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 2 and 3.</p> <p>S. 89°25'20" W., on the E-W center line of sec. 3.</p>
20.038	<p>Point for the C-E 1/16 sec. cor. of sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 9 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">E 1/16 C ——— C S 3</p> <p style="text-align: center;">2017</p>
40.076	<p>The center 1/4 sec. cor. of sec. 3.</p>
80.316	<p>The 1/4 sec. cor. of secs. 3 and 4.</p> <hr/> <p>From the E 1/16 sec. cor. of sec. 3.</p> <p>N. 0°03'20" W., on the N-S center line of the SE1/4 of sec. 3.</p>

SUBDIVISION OF SECTION 3,
T. 21 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.488	The C-E 1/16 sec. cor. of sec. 3.
	<hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 10, T. 21 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>
	From the 1/4 sec. cor. of secs. 10 and 15.
	N. 0°09'50" E., on the N-S center line of sec. 10.
80.011	The 1/4 sec. cor. of secs. 3 and 10.
	<hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 29, T. 21 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>
	From the 1/4 sec. cor. of secs. 29 and 32.
	N. 0°02'40" W., on the N-S center line of sec. 29.
39.954	Point for the center 1/4 sec. cor. of sec. 29, at intersection with the E-W center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T21N R20E C 1/4 S29
	2017
76.38	Power line, bears E. and W.
79.844	The 1/4 sec. cor. of secs. 20 and 29.
	<hr/>
	From the 1/4 sec. cor. of secs. 28 and 29.
	N. 89°57'10" W., on the E-W center line of sec. 29.
20.034	Point for the C-E 1/16 sec. cor. of sec. 29.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.
	E 1/16 C ——— C S29
	2017
40.068	The center 1/4 sec. cor. of sec. 29.

SUBDIVISION OF SECTION 29,
T. 21 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
79.797	The 1/4 sec. cor. of secs. 29 and 30.
	<hr/>
	From the C-E 1/16 sec. cor. of sec. 29.
	N. 0°08'50" W., on the N-S center line of the NE1/4 of sec. 29.
36.01	Power line, bears E. and W.
39.961	The E 1/16 sec. cor. of secs. 20 and 29.
	<hr/>
	From the E 1/16 sec. cor. of secs. 29 and 32.
	N. 0°02'10" E., on the N-S center line of the SE1/4 of sec. 29.
39.887	The C-E 1/16 sec. cor. of sec. 29.
	<hr/>
	GENERAL DESCRIPTION
	The lands contained within the scope of this survey are located in Washoe County, Nevada, in and around the community of Spanish Springs, Nevada. The land is generally mountainous, with areas of level ground, at an average elevation of 5300 ft. above sea level. The vegetation is primarily sagebrush and grass, with areas of scattered juniper. Access is gained primarily by way of Eagle Canyon Rd. and various paved and dirt roads.
	<hr/>

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS


Brandon G. Courtright	Cadastral Surveyor
Bradley F. Dillon	Sup. Cadastral Surveyor
Brandon K. Grace	Cadastral Surveyor
Stephen R. Lambeth	Contractor Employee
Griffin B. Dekker	Student Trainee
Kenneth W. Tynan	Student Trainee

CERTIFICATE OF SURVEY

I, Justin V. Haddon, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 22nd day of June, 2017, and amended special instructions bearing date of the 1st day of June, 2018, I have dependently resurveyed a portion of the south boundary of Township 22 North, Range 20 East, a portion of the subdivisional lines, and the subdivision of sections 2, 3, 10 and 29 of Township 21 North, Range 20 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

APR 23 2019

(Date)


(Cadastral Surveyor)


CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of the dependent resurvey of a portion of the south boundary of Township 22 North, Range 20 East, a portion of the subdivisional lines, and the subdivision of sections 2, 3, 10 and 29 of Township 21 North, Range 20 East, Mount Diablo Meridian, Nevada, executed by, Justin V. Haddon, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

APR 23 2019

(Date)


(Chief Cadastral Surveyor for Nevada)~~CERTIFICATE OF TRANSCRIPT~~

I CERTIFY That the foregoing transcript of the field notes of the above described surveys in Township 21 North, Range 20 East, and Township 22 North, Range 20 East, Mount Diablo Meridian, Nevada, is a true copy of the original field notes.

APR 24 2019

(Date)


(Chief Cadastral Surveyor for Nevada)