UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

THE FOURTH STANDARD PARALLEL NORTH
THROUGH A PORTION OF RANGE 32 EAST,
THE EAST AND WEST BOUNDARIES,

AND

A PORTION OF THE SUBDIVISIONAL LINES

OF

TOWNSHIP 21 NORTH, RANGE 32 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATE OF NEVADA

#### EXECUTED BY

Lance A. Barney, Cadastral Surveyor

Under Special Instructions dated April 9, 2008,

and approved April 9, 2008,

which provided for the surveys included under Group No. 862,

and Assignment Instructions dated June 11, 2008.

Survey commenced June 11, 2008 Survey completed March 27, 2009

#### INDEX DIAGRAM

TOWNSHIP 21 NORTH, RANGE 32 EAST, MOUNT DIABLO MERIDIAN, NEVADA

					T		<del></del>		
11	6	5	4	3	23	<i>2</i> 22	17	<i>1</i> 17	7
11	7	8	9	10	22	<i>11</i> 21	16	<i>12</i>	7
10	18	17	16	15	21	<i>14</i>	15	<i>13</i>	6
10	19	20	21	22	20	<i>23</i>	14	24 14	5
9	30	29	28	27	19		13	25 13	4
8	31	32	33	34	17	<i>35</i>	12	36 2	3

#### TOWNSHIP 21 NORTH, RANGE 32 EAST, MOUNT DIABLO MERIDIAN, NEVADA

#### CHAINS

The following field notes are those of the dependent resurvey of the Fourth Standard Parallel North through a portion of Range 32 East, the east and west boundaries, and a portion of the subdivisional lines of Township 21 North, Range 32 East, Mount Diablo Meridian, Nevada.

The south boundary (Fourth Standard Parallel North) was surveyed by Deputy Surveyor W. Epler in 1865 under Contract "I". The west boundary was surveyed by U.S. Deputy Surveyors T.K. Stewart and G.W. Conkling in 1881 under Contract No. 132. The north and east boundaries, and subdivisional lines were surveyed by U.S. Deputy Surveyors T.K. Stewart and G.W. Conkling in 1882 under Contract No. 146. A portion of the south boundary (Fourth Standard Parallel North) was dependently resurveyed by Cadastral Surveyor S.R. Lambeth in 1992 under Group No. 719. The north boundary was dependently resurveyed, and the west boundary and a portion of the south boundary (Fourth Standard Parallel North) were retraced by Cadastral Surveyor R.A. Pratt in 1992 under Group No. 728. A portion of the south boundary (Fourth Standard Parallel North) was retraced by Cadastral Surveyor D.J. Clark and Survey Technician C.W. Morrow in 2005 under Group No. 831.

Before restoring the corners, the lines of the original surveys were retraced and a diligent search made for any evidence of the original corners and other calls of the original field note record.

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 862, dated April 9, 2008.

Measurements were made with Trimble R-8 Global Positioning System (GPS) receivers using the real-time kinematic (RTK) method and refer to the true meridian based on geodetic methods. The mean bearings of the lines and horizontal equivalents of ground distances only are entered in the field notes.

The NAD 1983 (CORS 96) geographic position of the standard corner of Townships 21 North, Ranges 32 and 33 East, as determined by survey grade GPS receivers during the course of this survey, from National Geodetic Survey control stations "UPSAL HOGBACK", "TUNGSTEN" and "GABBS" and carried forward by RTK observations is as follows:

Latitude: 39°38'10.960" N. Longitude: 118°19'26.615" W.

The 1969 mean magnetic declination is 17  $1/2^{\circ}$  E., as shown on U.S.G.S. 7 1/2 minute quadrangle map "COX CANYON, NEV." dated 1969.

# DEPENDENT RESURVEY OF THE FOURTH STANDARD PARALLEL NORTH THROUGH A PORTION OF RANGE 32 EAST, MOUNT DIABLO MERIDIAN, NEVADA

	MOUNT DIABLO MERIDIAN, NEVADA
CHAINS	Reestablishment of a Portion of the Survey Executed by Deputy Surveyor W. Epler in 1865
	Beginning at the standard cor. of Tps. 21 N., Rs. 32 and 33 E., monumented with a conglomerate sandstone, 22x12x5 ins., firmly set, projecting 12 ins. above the ground, plainly mkd. with 6 notches on W. edge, with a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, alongside the cor.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	SC T21N R32E R33E S36 S31
	2008
	Deposit mkd. stone alongside the stainless steel post.
	S. 89°48'40" W., on the S. bdy. of sec. 36.
	Descend over nearly level land through scattered sagebrush.
40.250	Point for the standard 1/4 sec. cor. of sec. 36, at proportional distance; there is no remaining evidence of the original corner
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	SC T21N R32E 1/4 S36
	2008
80.500	Point for the standard cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	SC T21N R32E S35 S36
	2008

# DEPENDENT RESURVEY OF THE FOURTH STANDARD PARALLEL NORTH THROUGH A PORTION OF RANGE 32 EAST, MOUNT DIABLO MERIDIAN, NEVADA

	MOUNT DIABLO MERIDIAN, NEVADA
CHAINS	S. 89°48'40" W., on the S. bdy. of sec. 35.
	Over nearly level land through scattered sagebrush.
33.90	Bladed dirt road, 40 lks. wide, bears NE. and SW.
40.250	Point for the standard 1/4 sec. cor. of sec. 35, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	SC T21N R32E 1/4 S35
	2008
80.500	The standard cor. of secs. 34 and 35, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the Fourth Standard Parallel North, through a portion of Range 32 East, executed under Group No. 719.
	From this corner, the cor. of fences extending N. and W., bears S. 45° E., 5 lks. dist.
	DEPENDENT RESURVEY OF THE EAST BOUNDARY, T. 21 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA
	Reestablishment of the Survey Executed by U.S. Deputy Surveyors T.K. Stewart and G.W. Conkling in 1882 and a Portion of the Dependent Resurvey Executed by Cadastral Surveyor R.A. Pratt in 1992
	From the standard cor. of Tps. 21 N., Rs. 32 and 33 E., hereinbefore described.
	N. 0°15'20" E., bet. secs. 31 and 36.
	Over rolling land, descending slightly through scattered sagebrush.
16.20	Dry channel, 10 lks. wide, drains W.
40.669	The 1/4 sec. cor. of secs. 31 and 36, monumented with a trapstone, 24x18x12 ins., firmly set, projecting 18 ins. above the ground, mkd. 1/4 on the W. face.
	At the corner point

	1. 21 N., R. 32 E., MOUNI DIABLO MERIDIAN, NEVADA
CHAINS	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.
	T21N
	1/4
	R32E R33E
	S36  S31
	2008
	Denosit mld stone alongside the stainless stool nest
	Deposit mkd. stone alongside the stainless steel post.
	N. 0°10'40" E., beginning new measurement
40.568	The cor. of secs. 25, 30, 31 and 36, monumented with a granite stone, 18x12x10 ins., firmly set, projecting 12 ins. above the ground, mkd. with 1 notch on the S. edge and 5 notches on the N. edge.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T21N
	R32E R33E
	S25 S30
	S36 S31
	'
	2008
	Deposit mkd. stone alongside the stainless steel post.
	N. 0°23'10" E., bet. secs. 25 and 30.
	Over nearly level land, through scattered sagebrush.
11.60	Trail road, bears E. and W.
40.622	The 1/4 sec. cor. of secs. 25 and 30, monumented with a granite stone, 16x10x8 ins., firmly set, projecting 9 ins. above the ground, and in a mound of stone, 3 ft. base, 1/2 ft. high, mkd. 1/4 on the W. face.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.
	T21N
	1/4
	R32E R33E S25 S30
	323   330
	2008

CHAINS	
3	Deposit mkd. stone alongside the stainless steel post.
	N. 0°18'10" E., beginning new measurement.
40.592	The cor. of secs. 19, 24, 25 and 30, monumented with a granite stone, 24x8x7 ins., firmly set in a mound of stone, 3 ft. base, 1 ft. high, mkd. with 2 notches on the S. edge and 4 notches on the N. edge, with a rebar of unknown origin, 3/4 in. diam., 18 ins. long, firmly set alongside the stone, projecting 3 ins. above the ground, with a mound of stone, 3 ft. base, 1 ft. high, E. of the corner.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.
	T21N R32E R33E S24 S19 S25 S30
	2008
	Insert rebar inside the stainless steel post and deposit mkd. stone alongside.
	N. 0°11'50" E., bet. secs. 19 and 24.
	Over nearly level land, through scattered sagebrush.
40.618	The 1/4 sec. cor. of secs. 19 and 24, monumented with a sandstone, 16x10x8 ins., firmly set, projecting 8 ins. above the ground, mkd. 1/4 on the W. face, with a rebar of unknown origin, 5/8 in. diam., 24 ins. long, firmly set alongside the sandstone, projecting 8 ins. above the ground.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. the ground, over a plastic-encased magnet, with brass cap mkd.
	T21N
	1/4 R32E R33E S24 S19
	2008
	Insert rebar inside the stainless steel post and deposit mkd. sandstone alongside.
	N. 0°08'00" E., beginning new measurement.

	1. 21 N., R. 32 E., MOUNI DIABLO MERIDIAN, NEVADA
CHAINS	
9.70	Bladed dirt road, bears NE. and SW.
40.453	The cor. of secs. 13, 18, 19 and 24, monumented with a sandstone, 18x10x5 ins., firmly set, projecting 10 ins. above the ground, mkd. with 1 notch on the S. edge and 5 notches on the N. edge, with a rebar of unknown origin, 5/8 in. diam., 18 ins. long, firmly set alongside the sandstone, projecting 6 ins. above the ground.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T21N R32E R33E S13 S18
	S24 S19
	2008
	Insert rebar inside the stainless steel post and deposit mkd. stone alongside.
	N. 0°12'00" W., bet. secs. 13 and 18.
	Over nearly level land, through scattered sagebrush.
40.638	Point for the 1/4 sec. cor. of secs. 13 and 18, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T21N 1/4 R32E R33E S13 S18
	2008
81.276	The cor. of secs. 7, 12, 13 and 18, monumented with a sandstone, 17x14x10 ins., firmly set, projecting 8 ins. above the ground, mkd. with 2 notches on the S. edge and 4 notches on the N. edge.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
l	

CHAINS	T21N R32E R33E S12 S 7
	S13 S18
	2008
	Deposit mkd. stone alongside the stainless steel post.
	N. 0°17'10" W., bet. secs. 7 and 12.
	Over nearly level land, through scattered sagebrush.
12.00	Trail road, bears WSW. and ENE.
28.20	Enter playa.
40.631	Point for the 1/4 sec. cor. of secs. 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T21N 1/4 R32E R33E S12 S 7
	2008
81.262	The cor. of secs. 1, 6, 7 and 12, monumented with a granite stone, 9x8x7 ins., firmly set in mound of stone, 2 1/2 ft. base, 1 ft. high, mkd. with 5 notches on the S. edge.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T21N R32E R33E S 1 S 6
	S12 S 7
	2008
	Deposit mkd. stone alongside the stainless steel post and raise mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N. of cor.
	N. 0°13'10" W., bet. secs. 1 and 6.
	Across playa.
40.742	Point for the 1/4 sec. cor. of secs. 1 and 6, at proportionate
30.742	distance, there is no remaining evidence of the original corner.

CHAINS

Set a stainless steel post, 28 ins. long,  $2\ 1/2$  ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

T21N 1/4 R32E R33E S 1 S 6

2008

81.484

The cor. of Tps. 21 and 22 N., Rs. 32 and 33 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the south boundary of T. 22 N., R. 32 E., executed under Group No. 728.

DEPENDENT RESURVEY OF THE WEST BOUNDARY, T. 21 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by U.S. Deputy Surveyors T.K. Stewart and G.W. Conkling in 1881, the Retracement Executed by Cadastral Surveyor R.A. Pratt in 1992 and the Dependent Resurvey Executed by D.J. Clark and C.W. Morrow in 2005-07

From the point for the standard cor. of Tps.  $21 \, \text{N.}$ , Rs.  $31 \, \text{and} \, 32 \, \text{E.}$ , at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

SC T21N R31E R32E S36 S31

2008

From this point, the standard cor. of secs. 32 and 33, T. 21 N., R. 32 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the south boundary of T. 22 N., R. 32 E., executed under Group No. 728, bears S. 89°51'50" E., 160.944 chs. dist.

The control line was fully retraced, and no evidence of intervening corners was found.

From this same point, the witness point on the S. bdy. of sec. 36, T. 21 N., R. 31 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the Fourth Standard Parallel North, through a Portion of Range 31 East, T. 20 N., R. 31 E., executed under Group No. 831, bears N. 89°51'50" W., 21.558 chs. dist.

_	<del> </del>
CHAINS	From this same point, a rebar of unknown origin, 5/8 in. diam., firmly set, projecting 14 ins. above the ground, with aluminum cap mkd. illegible, bears S. 88°53'30" W., 3.067 chs. dist., not utilized during the course of this survey.
	N. 0°04'20" E., bet. secs. 31 and 36.
	Over marsh land.
27.60	Trail road, bears N. 72° W. and S. 72° E.
40.186	Point for the 1/4 sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T21N 1/4
	R31E R32E S36 S31
	2008
80.372	Point for the cor. of secs. 25, 30, 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T21N R31E R32E S25 S30
	S36 S31
	2008
	N. 0°04'20" E., bet. secs. 25 and 30.
	Over marsh land.
15.10	Trail road, bears N. 86° W. and S. 86° E.
40.186	Point for the 1/4 sec. cor. of secs. 25 and 30, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T21N 1/4
	R31E R32E S25 S30
	2008
67.70	Leave marsh, enter playa.

<u></u>	1. 21 N., K. 32 E., MOONI DIADLO MERIDIAN, NEVADA
CHAINS	
80.372	Point for the cor. of secs. 19, 24, 25 and 30, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T21N
	R31E R32E S24 S19
	S25 S30
	2008
	N. 0°04'20" E., bet. secs. 19 and 24.
	Over playa.
40.186	Point for the 1/4 sec. cor. of secs. 19 and 24, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T21N
	1/4 R31E R32E
	S24 S19
	2008
80.372	Point for the cor. of secs. 13, 18, 19 and 24, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T21N
	R31E R32E S13 S18
	S24 S19
	2008
	N. 0°04'20" E., bet. secs. 13 and 18.
	Over playa.
40.186	Point for the 1/4 sec. cor. of secs. 13 and 18, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<u> </u>

	T. 21, N. 32 2., Noon Stribe in Alberta, No. 12
CHAINS	T21N 1/4 R31E   R32E S13   S18
	2008
42.40	Leave playa, enter sand dunes with sparse sagebrush.
80.372	Point for the cor. of secs. 7, 12, 13 and 18, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T21N
	R31E R32E S12 S 7
	S13 S18
	2008
	2000
	N. 0°04'20" E., bet. secs. 7 and 12.
	Over sand dunes with sparse sagebrush.
40.186	Point for the 1/4 sec. cor. of secs. 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T21N
	1/4 R31E R32E
	S12   S 7
	2008
80.372	Point for the cor. of secs. 1, 6, 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T21N
	R31E R32E S 1 S 6
	S12 S 7
	'
	2008
	N. 0°04'20" E., bet. secs. 1 and 6.
	Over sand dunes with sparse sagebrush.

	· · · · · · · · · · · · · · · · · · ·
CHAINS	
40.186	Point for the 1/4 sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T21N
	1/4 R31E R32E
	S 1 S 6
	2008
80.372	The cor. of Tps. 21 and 22 N., Rs. 31 and 32 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the south boundary of T. 22 N., R. 32 E., executed under Group No. 728.
	DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 21 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA
	Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyors T.K. Stewart and G.W. Conkling in 1882
	From the standard cor. of secs. 35 and 36, on the S. bdy. of the Tp., hereinbefore described.
	N. 0°14'10" E., bet. secs. 35 and 36.
	Over nearly level land, through scattered sagebrush.
10.00	Trail road, bears NW. and SE.
40.626	Point for the 1/4 sec. cor. of secs. 35 and 36, at proportionate distance, there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T21N R32E
	1/4 S35 S36
	'
	2008
58.90	Bladed dirt road, bears NE. and SW.
81.252	Point for the cor. of secs. 25, 26, 35 and 36, at proportionate distance, there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

CHAINS	T21N R32E S26 S25
	S35 S36
	2008
	From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., hereinbefore described.
	S. 89°49'20" W., bet. secs. 25 and 36.
	Over nearly level land, through scattered sagebrush.
40.228	Point for the 1/4 sec. cor. of secs. 25 and 36, at proportional distance, there is no remaining evidence of the original corner
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with bras cap mkd.
	T21N R32E
	1/4 <del></del>
	S36
	2008
67.50	Bladed dirt road, bears NE. and SW.
80.456	The cor. of secs. 25, 26, 35 and 36.
	N. 0°21'20" E., bet. secs. 25 and 26.
	Over nearly level land, through scattered sagebrush.
22.20	From this point, a windmill bears E. at 5.00 chs. dist.
40.627	Point for the $1/4$ sec. cor. of secs. 25 and 26, at proportional distance, there is no remaining evidence of the original corner
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with bras cap mkd.
	T21N R32E 1/4 S26 S25
	2008
81.254	Point for the cor. of secs. 23, 24, 25 and 26, at proportionate distance, there is no remaining evidence of the original corner
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with bras cap mkd.

CHAINS	T21N R32E S23 S24
	S26 S25
	2008
	From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., hereinbefore described.
	S. 89°51'10" W., bet. secs. 24 and 25.
	Over nearly level land, through scattered sagebrush.
21.40	Bladed dirt road, bears NE. and SW.
40.211	Point for the 1/4 sec. cor. of secs. 24 and 25, at proportionate distance, there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T21N R32E
	1/4 = 324
	S25
	2008
80.422	The cor. of secs. 23, 24, 25 and 26.
	N. 0°03'00" E., bet. secs. 23 and 24.
	Over nearly level land, through scattered sagebrush.
40.626	Point for the 1/4 sec. cor. of secs. 23 and 24, at proportionate distance, there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T21N R32E
	1/4 S23 S24
	2008
70.60	Enter playa.
76.60	Leave playa, enter sand dunes.
81.252	Point for the cor. of secs. 13, 14, 23 and 24, at proportionate distance, there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

CHAINS	T21N R32E
	S14 S13 S23 S24
	2008
	From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., hereinbefore described.
	S. 89°59'00" W., bet. secs. 13 and 24.
	Over nearly level land, through scattered sagebrush.
40.285	Point for the $1/4$ sec. cor. of secs. 13 and 24, at proportionate distance, there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T21N R32E
	$1/4 = \frac{\$13}{\$234}$
	S24
52.20	2008
	Enter playa.
56.70	Leave playa, enter sand dunes.
80.570	The cor. of secs. 13, 14, 23 and 24.
	N. 0°09'30" W., bet. secs. 13 and 14.
	Over sand dunes, through sparse sagebrush.
9.30	Enter playa.
40.626	Point for the 1/4 sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T21N R32E
	1/4 S14 S13
	2008
81.252	Point for the cor. of secs. 11, 12, 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

CHAINS	1. 21 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA
CHAINS	T21N R32E S11   S12
	S14   S13
	2008
	From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., hereinbefore described.
	S. 89°57'50" W., bet. secs. 12 and 13.
	Over nearly level land, through scattered sagebrush.
5.00	Enter playa.
40.247	Point for the 1/4 sec. cor. of secs. 12 and 13, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T21N R32E
	1/4 = 1/4
	S13
	2008
80.494	The cor. of secs. 11, 12, 13 and 14.
:	N. 0°23'10" W., bet. secs. 11 and 12.
	Over playa.
40.627	Point for the 1/4 sec. cor. of secs. 11 and 12, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T21N R32E 1/4
	S11   S12
	2008
81.254	Point for the cor. of secs. 1, 2, 11 and 12, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

CHAINS	T21N R32E S 2 S 1
	S11 S12
	2008
	From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., hereinbefore described.
	S. 89°57'30" W., bet. secs. 1 and 12.
	Over playa.
40.310	Point for the 1/4 sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T21N R32E S 1
	$\frac{1/4}{512}$
	2008
80.620	
00.020	The cor. of secs. 1, 2, 11 and 12.
	N. 0°12'10" E., bet. secs. 1 and 2.
	Over playa.
40.626	Point for the 1/4 sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T21N R32E 1/4 S 2 S 1
	2008
81.171	The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the south boundary of T. 22 N., R. 32 E., executed under Group No. 728.
	From the standard cor. of secs. 34 and 35, on the S. bdy. of the Tp., hereinbefore described.
	N. 0°07'40" E., bet. secs. 34 and 35.

CHAINS	Over nearly level land, through scattered sagebrush and along fence.
40.562	Point for the 1/4 sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T21N R32E 1/4 S34 S35
	2008
48.30	Dirt road, 18 lks. wide, bears SE. and NW.
50.40	Fence, bears SE. and NW.
81.124	Point for the cor. of secs. 26, 27, 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T21N R32E S27 S26
	S34 S35
	2008
	From this point, the cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., bears S. 89°59'50" W., 321.888 chs. dist., hereinbefore described.
	The control line was fully retraced and no evidence of intervening corners was found.
	From the cor. of secs. 25, 26, 35 and 36.
	S. 89°43'20" W., bet. secs. 26 and 35.
	Over nearly level land, through scattered sagebrush.
40.318	Point for the 1/4 sec. cor. of secs. 26 and 35, at proportionate distance, there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T21N R32E
	S26 1/4 <del></del>
	S35
	2008

	1. 21 N., K. 32 E., MOONI DIADEO MERIDIAN, NEVADA
CHAINS	
80.636	The cor. of secs. 26, 27, 34 and 35.
	N. 0°14'20" E., bet. secs. 26 and 27.
	Over sand dunes, through sparse sagebrush.
36.20	Enter playa.
40.562	Point for the 1/4 sec. cor. of secs. 26 and 27, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T21N R32E 1/4 S27 S26
	2008
81.124	Point for the cor. of secs. 22, 23, 26 and 27, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T21N R32E S22 S23
	S27 S26
	2008
	From this point, the cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., bears S. 89°51'50" W., 322.058 chs. dist., hereinbefore described.
	The control line was fully retraced and no evidence of intervening corners was found.
	From the cor. of secs. 23, 24, 25 and 26.
	S. 89°37'50" W., bet. secs. 23 and 26.
	Over nearly level land, through scattered sagebrush.
26.20	Enter playa.
40.393	Point for the 1/4 sec. cor. of secs. 23 and 26, at proportionate distance, there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

80.786  The cor. of secs. 22, 23, 26 and 27.  N. 0°06'40" E., bet. secs. 22 and 23.  Over playa.  Point for the 1/4 sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.  T21N R32E  1/4  822   S23  2008  81.124  Point for the cor. of secs. 14, 15, 22 and 23, at proportionate distance, there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.  T21N R32E  S15   S14  S22   S23  2008  From this point, the cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., bears S. 89°43'50" W., 322.049 chs. dist., hereinbefore described.  The control line was fully retraced and no evidence of intervening corners was found.  From the cor. of secs. 13, 14, 23 and 24.  S. 89°32'10" W., bet. secs. 14 and 23.		
1/4 — S26 2008  80.786 The cor. of secs. 22, 23, 26 and 27.  N. 0°06'40" E., bet. secs. 22 and 23.  Over playa.  Point for the 1/4 sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.  T21N R32E 1/4 S22 S23 2008  81.124 Point for the cor. of secs. 14, 15, 22 and 23, at proportionate distance, there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.  T21N R32E S15  S14 S22 S23 2008  From this point, the cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., bears S. 89°43'50" W., 322.049 chs. dist., hereinbefore described.  The control line was fully retraced and no evidence of intervening corners was found.  From the cor. of secs. 13, 14, 23 and 24. S. 89°32'10" W., bet. secs. 14 and 23.	CHAINS	·
2008  80.786 The cor. of secs. 22, 23, 26 and 27.  N. 0°06'40" E., bet. secs. 22 and 23.  Over playa.  40.562 Point for the 1/4 sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.  T21N R32E 1/4 822   S23 2008  81.124 Point for the cor. of secs. 14, 15, 22 and 23, at proportionate distance, there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.  T21N R32E S15   S14 S22   S23 2008  From this point, the cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., bears S. 89°43'50" W., 322.049 chs. dist., hereinbefore described.  The control line was fully retraced and no evidence of intervening corners was found.  From the cor. of secs. 13, 14, 23 and 24.  S. 89°32'10" W., bet. secs. 14 and 23.		
80.786 The cor. of secs. 22, 23, 26 and 27.  N. 0°06'40" E., bet. secs. 22 and 23.  Over playa.  40.562 Point for the 1/4 sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.  T21N R32E 1/4 S22 S23 2008  81.124 Point for the cor. of secs. 14, 15, 22 and 23, at proportionate distance, there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.  T21N R32E S15  S14 S22 S23 2008  From this point, the cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., bears S. 89°43'50" W., 322.049 chs. dist., hereinbefore described.  The control line was fully retraced and no evidence of intervening corners was found.  From the cor. of secs. 13, 14, 23 and 24. S. 89°32'10" W., bet. secs. 14 and 23.		S26
N. 0°06'40" E., bet. secs. 22 and 23.  Over playa.  Point for the 1/4 sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.  T21N R32E  1/4  822   S23  2008  81.124  Point for the cor. of secs. 14, 15, 22 and 23, at proportionate distance, there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.  T21N R32E  S15   S14  S22   S23  2008  From this point, the cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., bears S. 89°43'50" W., 322.049 chs. dist., hereinbefore described.  The control line was fully retraced and no evidence of intervening corners was found.  From the cor. of secs. 13, 14, 23 and 24.  S. 89°32'10" W., bet. secs. 14 and 23.		2008
Over playa.  Point for the 1/4 sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.  T21N R32E  1/4  S22   S23  2008  81.124  Point for the cor. of secs. 14, 15, 22 and 23, at proportionate distance, there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.  T21N R32E  S15   S14  S22   S23  2008  From this point, the cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., bears S. 89°43'50" W., 322.049 chs. dist., hereinbefore described.  The control line was fully retraced and no evidence of intervening corners was found.  From the cor. of secs. 13, 14, 23 and 24.  S. 89°32'10" W., bet. secs. 14 and 23.	80.786	The cor. of secs. 22, 23, 26 and 27.
Point for the 1/4 sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.  T21N R32E  1/4  S22   S23  2008  81.124  Point for the cor. of secs. 14, 15, 22 and 23, at proportionate distance, there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.  T21N R32E  S15   S14  S22   S23  2008  From this point, the cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., bears S. 89°43'50" W., 322.049 chs. dist., hereinbefore described.  The control line was fully retraced and no evidence of intervening corners was found.  From the cor. of secs. 13, 14, 23 and 24.  S. 89°32'10" W., bet. secs. 14 and 23.		N. 0°06'40" E., bet. secs. 22 and 23.
distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.  T21N R32E  1/4  S22   S23  2008  81.124  Point for the cor. of secs. 14, 15, 22 and 23, at proportionate distance, there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.  T21N R32E  S15   S14  S22   S23  2008  From this point, the cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., bears S. 89°43'50" W., 322.049 chs. dist., hereinbefore described.  The control line was fully retraced and no evidence of intervening corners was found.  From the cor. of secs. 13, 14, 23 and 24.  S. 89°32'10" W., bet. secs. 14 and 23.		Over playa.
24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.  T21N R32E  1/4  S22   S23  2008  81.124  Point for the cor. of secs. 14, 15, 22 and 23, at proportionate distance, there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.  T21N R32E  S15   S14  S22   S23  2008  From this point, the cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., bears S. 89°43'50" W., 322.049 chs. dist., hereinbefore described.  The control line was fully retraced and no evidence of intervening corners was found.  From the cor. of secs. 13, 14, 23 and 24.  S. 89°32'10" W., bet. secs. 14 and 23.	40.562	
2008  81.124 Point for the cor. of secs. 14, 15, 22 and 23, at proportionate distance, there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.  T21N R32E  S15 S14  S22 S23  2008  From this point, the cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., bears S. 89°43'50" W., 322.049 chs. dist., hereinbefore described.  The control line was fully retraced and no evidence of intervening corners was found.  From the cor. of secs. 13, 14, 23 and 24.  S. 89°32'10" W., bet. secs. 14 and 23.		24 ins. in the ground, over a plastic-encased magnet, with brass
2008  81.124 Point for the cor. of secs. 14, 15, 22 and 23, at proportionate distance, there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.  T21N R32E  S15 S14  S22 S23  2008  From this point, the cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., bears S. 89°43'50" W., 322.049 chs. dist., hereinbefore described.  The control line was fully retraced and no evidence of intervening corners was found.  From the cor. of secs. 13, 14, 23 and 24.  S. 89°32'10" W., bet. secs. 14 and 23.		T21N R32E
Point for the cor. of secs. 14, 15, 22 and 23, at proportionate distance, there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.  T21N R32E S15 S14 S22 S23  2008  From this point, the cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., bears S. 89°43'50" W., 322.049 chs. dist., hereinbefore described.  The control line was fully retraced and no evidence of intervening corners was found.  From the cor. of secs. 13, 14, 23 and 24.  S. 89°32'10" W., bet. secs. 14 and 23.		
Point for the cor. of secs. 14, 15, 22 and 23, at proportionate distance, there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.  T21N R32E S15 S14 S22 S23  2008  From this point, the cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., bears S. 89°43'50" W., 322.049 chs. dist., hereinbefore described.  The control line was fully retraced and no evidence of intervening corners was found.  From the cor. of secs. 13, 14, 23 and 24.  S. 89°32'10" W., bet. secs. 14 and 23.		'
distance, there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.  T21N R32E  S15 S14  S22 S23  2008  From this point, the cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., bears S. 89°43'50" W., 322.049 chs. dist., hereinbefore described.  The control line was fully retraced and no evidence of intervening corners was found.  From the cor. of secs. 13, 14, 23 and 24.  S. 89°32'10" W., bet. secs. 14 and 23.		
24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.  T21N R32E S15 S14 S22 S23  2008  From this point, the cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., bears S. 89°43'50" W., 322.049 chs. dist., hereinbefore described.  The control line was fully retraced and no evidence of intervening corners was found.  From the cor. of secs. 13, 14, 23 and 24.  S. 89°32'10" W., bet. secs. 14 and 23.	81.124	
S15 S14 S22 S23  2008  From this point, the cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., bears S. 89°43'50" W., 322.049 chs. dist., hereinbefore described.  The control line was fully retraced and no evidence of intervening corners was found.  From the cor. of secs. 13, 14, 23 and 24.  S. 89°32'10" W., bet. secs. 14 and 23.		24 ins. in the ground, over a plastic-encased magnet, with brass
From this point, the cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., bears S. 89°43'50" W., 322.049 chs. dist., hereinbefore described.  The control line was fully retraced and no evidence of intervening corners was found.  From the cor. of secs. 13, 14, 23 and 24.  S. 89°32'10" W., bet. secs. 14 and 23.		
From this point, the cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., bears S. 89°43'50" W., 322.049 chs. dist., hereinbefore described.  The control line was fully retraced and no evidence of intervening corners was found.  From the cor. of secs. 13, 14, 23 and 24.  S. 89°32'10" W., bet. secs. 14 and 23.		S22 S23
From this point, the cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., bears S. 89°43'50" W., 322.049 chs. dist., hereinbefore described.  The control line was fully retraced and no evidence of intervening corners was found.  From the cor. of secs. 13, 14, 23 and 24.  S. 89°32'10" W., bet. secs. 14 and 23.		'
bdy. of the Tp., bears S. 89°43'50" W., 322.049 chs. dist., hereinbefore described.  The control line was fully retraced and no evidence of intervening corners was found.  From the cor. of secs. 13, 14, 23 and 24.  S. 89°32'10" W., bet. secs. 14 and 23.		
From the cor. of secs. 13, 14, 23 and 24.  S. 89°32'10" W., bet. secs. 14 and 23.		bdy. of the Tp., bears S. 89°43'50" W., 322.049 chs. dist.,
S. 89°32'10" W., bet. secs. 14 and 23.		
		From the cor. of secs. 13, 14, 23 and 24.
		S. 89°32'10" W., bet. secs. 14 and 23.
Over sand dunes.		Over sand dunes.
3.30 Enter playa.	3 30	Enter plays
page page		
40.341 Point for the 1/4 sec. cor. of secs. 14 and 23, at proportionate distance, there is no remaining evidence of the original corner.	40.341	

CHAINS	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T21N R32E
	1/4 —
	S23
	2008
80.682	The cor. of secs. 14, 15, 22 and 23.
	N. 0°06'40" W., bet. secs. 14 and 15.
	Over playa.
40.562	Point for the 1/4 sec. cor. of secs. 14 and 15, at proportionate distance, there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T21N R32E 1/4 S15 S14
	2008
81.124	Point for the cor. of secs. 10, 11, 14 and 15, at proportionate distance, there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T21N_R32E
	<u>\$10   \$11  </u>
	S15   S14
	2008
	From this point, the cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., bears S. 89°35'50" W., 321.730 chs. dist., hereinbefore described.
	The control line was fully retraced and no evidence of intervening corners was found.
	From the cor. of secs. 11, 12, 13 and 14.
	S. 89°26'50" W., bet. secs. 11 and 14.
	Over playa.
40.299	Point for the 1/4 sec. cor. of secs. 11 and 14, at proportionate distance, there is no remaining evidence of the original corner.

CHAINS	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T21N R32E
	1/4 <del></del>
	S14
	2008
80.598	The cor. of secs. 10, 11, 14 and 15.
	N. 0°16'00" W., bet. secs. 10 and 11.
	Over playa.
40.562	Point for the $1/4$ sec. cor. of secs. 10 and 11, at proportionate distance, there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T21N R32E 1/4 S10 S11
	2008
81.124	Point for the cor. of secs. 2, 3, 10 and 11, at proportionate distance, there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T21N R32E
	S 3 S 2
	S10   S11
	2008
	From this point, the cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., bears S. 89°27'40" W., 321.190 chs. dist., hereinbefore described.
	The control line was fully retraced and no evidence of intervening corners was found.
	From the cor. of secs. 1, 2, 11 and 12.
	S. 89°21'20" W., bet. secs. 2 and 11.
	Over playa.
40.206	Point for the 1/4 sec. cor. of secs. 2 and 11, at proportionate distance, there is no remaining evidence of the original corner.

	T. 21 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA
CHAINS	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T21N R32E
	S 2
	1/4 <del></del>
	2008
80.412	The cor. of secs. 2, 3, 10 and 11.
	N. 0°08'10" E., bet. secs. 2 and 3.
	Over playa.
40.562	Point for the 1/4 sec. cor. of secs. 2 and 3, at proportionate distance, there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T21N R32E
	1/4 S 3 S 2
	2008
81.143	The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the south boundary of T. 22 N., R. 32 E., executed under Group No. 728.
	GENERAL DESCRIPTION
	The lands included in the survey are located in Churchill County, Nevada, approximately 27 miles northeast of Fallon, Nevada, on the Stillwater National Wildlife Refuge.
	The area is nearly level, located on the east edge of the Carson Sink and the Forty Mile Desert, with a large portion of the township being playa (salt flat). Big Water, an inundated depression caused by spring runoff covers almost half of the township. The elevation ranges from about 3875 to 4200 feet above sea level.
	There is a windmill with an adjacent corral located in section 25.

24

# UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

#### FIELD ASSISTANT

Edward J. Graham Jr.

Surveying Technician

#### CERTIFICATE OF SURVEY

I, Lance A. Barney, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 9th day of April, 2008, I have dependently resurveyed the Fourth Standard Parallel North through a portion of Range 32 East, the east and west boundaries, and a portion of the subdivisional lines of Township 21 North, Range 32 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

December 3, 2009 (Date)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT Reno, Nevada

The foregoing field notes of a dependent survey the Fourth Standard Parallel North through a portion of Range 32 East, the east and west boundaries, and a portion of the subdivisional lines of Township 21 North, Range 32 East, Mount Diablo Meridian, Nevada, executed by Lance A. Barney, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

December 8, 2009

(Date)

(Chief Cadastral Surveyor, Nevada)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 21 N., R. 32 E., Mount Diablo Meridian, Nevada, is a true copy of the original field notes.

(Date

(Chief Gadastral Surveyor, Nevada)