

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

THE FOURTH STANDARD PARALLEL NORTH,
THROUGH A PORTION OF RANGE 38 EAST,

A PORTION OF THE EAST BOUNDARY

AND

A PORTION OF THE SUBDIVISIONAL LINES

OF

TOWNSHIP 21 NORTH, RANGE 38 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATE OF NEVADA

EXECUTED BY

Don R. Aschenbach, Cadastral Surveyor

Under Special Instructions dated May 23, 2011,

and approved May 23, 2011,

which provided for the surveys included under Group No. 904,

and Assignment Instructions dated July 18, 2011.

Survey commenced August 2, 2011

Survey completed September 20, 2011

INDEX DIAGRAM

TOWNSHIP 21 NORTH, RANGE 38 EAST, MOUNT DIABLO MERIDIAN, NEVADA

6	5	4	3	2	1	15
7	8	9	10	11	15 12	14
18	17	16	15	20 14	13 13	12
19	20	28 21	24 22	18 23	11 24 8	11
30	29	27 28	22 27	17 26	10 25 7	10
31	32	25 33	21 34	16 35	9 36 7	2
		6	5	4		

TOWNSHIP 21 NORTH, RANGE 38 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The following field notes are those of the dependent resurvey of the Fourth Standard Parallel North, through a portion of Range 38 East, a portion of the east boundary and a portion of the subdivisional lines of Township 21 North, Range 38 East, Mount Diablo Meridian, Nevada.

The south boundary (Fourth Standard Parallel North) was surveyed by U.S. Deputy Surveyor W. Epler in 1865 under Contract I. The east boundary and portions of the north boundary and subdivisional lines were surveyed by D.H. Barker and E.C. McClellan in 1879 under Contract No. 89. The west boundary and a portion of the north boundary was surveyed by U.S. Deputy Surveyor T.K. Stewart in 1881 under Contract No. 132. The east boundary was dependently resurveyed by Cadastral Surveyors E.W. Sibley and R.A. Pratt in 1970 under Group No. 476. The south boundary (Fourth Standard Parallel North) was dependently resurveyed by Cadastral Surveyors D.R. Beck and E.W. Sibley in 1970-71 under Group No. 476.

Before restoring the corners, the lines of prior surveys were retraced and a diligent search made for any evidence of all the corners and other calls of record.

The rules of proportionate measurement and record distance were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions (2009) and the Special Instructions for Group No. 904, dated May 23, 2011.

Measurements were made with Trimble R8 Global Positioning System (GPS) receivers using the real-time kinematic (RTK) method and refer to the true meridian based on geodetic methods. The mean bearings of the lines and horizontal equivalents of ground distances only are entered in the field notes.

The NAD 1983 (CORS 96) (2002) geographic position of the following corners were determined from GPS static observations processed by the National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) AI1410 TUNGSTEN CORS ARP, AI8808 GARL GARLIC CORS ARP, and AI8814 UPSAL HOGBACK CORS ARP, and were carried forward by RTK observations.

The geographic position for the corner of sections 1, 6, 7 and 12, on the east boundary of the township is as follows:

Latitude: 39°42'30.692" N. Longitude: 117°38'43.976" W.

The geographic position for the standard corner of Townships 21 North, Ranges 38 and 39 East is as follows:

Latitude: 39°38'09.169" N. Longitude: 117°38'42.937" W.

TOWNSHIP 21 NORTH, RANGE 38 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The mean magnetic declination is 15°30' E., as shown on U.S.G.S. 7 1/2 minute quadrangle map "TUNGSTEN MTN.", dated 1990.

DEPENDENT RESURVEY OF THE
FOURTH STANDARD PARALLEL NORTH
THROUGH A PORTION OF RANGE 38 EAST,
MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of a Portion of the Survey Executed by
U.S. Deputy Surveyor W. Epler in 1865,
and a Portion of the Dependent Resurvey Executed by
Cadastral Surveyors D.R. Beck and E.W. Sibley
in 1970-71

Beginning at the point for the standard cor. of Tps. 21 N.,
Rs. 38 E. and 39 E., at proportionate distance; there is no
remaining evidence of the 1970-71 corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, over a plastic-encased magnet, with brass
cap mkd.

SC
T21N
R38E | R39E
S36 | S31
T20N R38E
S 1
2011

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

From this point, the standard cor. of secs. 31 and 32,
T. 21 N., R 39 E., bears N. 89°53'40" E., 80.712 chs. dist.,
monumented with an iron post, 2 1/2 ins. diam., firmly set,
projecting 6 ins. above ground, with brass cap mkd. as described
in the field notes of the dependent resurvey of the south
boundary of T. 21 N., R 39 E., executed under Group No. 476,
with a mound of stone, N.

This control line was fully retraced and a careful search was
made for evidence of the intervening corner, none of which was
recovered.

S. 89°53'40" W., on the S. bdy. of sec. 36.

Over dry lake bed.

28.559 Point for the N. 1/4 sec. cor. of sec. 1, T. 20 N., R. 38 E., at
proportionate distance; there is no remaining evidence of the
1970-71 corner.

DEPENDENT RESURVEY OF THE
FOURTH STANDARD PARALLEL NORTH,
THROUGH A PORTION OF RANGE 38 EAST,
MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T21N R38E <hr/>1/4 S 1 T20N R38E</p> <p style="text-align: center;">2011</p>
40.356	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.</p> <p>Point for the standard 1/4 sec. cor. of sec. 36, on the S. bdy. Of the Tp., at proportionate distance; there is no remaining evidence of the 1970-71 corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">SC T21N R38E 1/4 S36 <hr/></p> <p style="text-align: center;">2011</p>
68.750	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>Point for the closing cor. of secs. 1 and 2, T. 20 N., R. 38 E., at proportionate distance; there is no remaining evidence of the 1970-71 corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T21N R38E S 36 <hr/>S 2 S 1 T20N R38E CC</p> <p style="text-align: center;">2011</p>
80.712	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>Point for the standard cor. of secs. 35 and 36, on the S. bdy. Of the Tp., at proportionate distance; there is no remaining evidence of the 1970-71 corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF THE
FOURTH STANDARD PARALLEL NORTH,
THROUGH A PORTION OF RANGE 38 EAST,
MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">SC T21N R38E <u>S35</u> <u>S36</u> T20N R38E S 2</p> <p style="text-align: center;">2011</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <hr/>
28.244	<p>S. 89°53'40" W., on the S. bdy. of sec. 35.</p> <p>Over dry lake bed.</p> <p>Point for the N. 1/4 sec. cor. of sec. 2, T. 20 N., R. 38 E., at proportionate distance; there is no remaining evidence of the 1970-71 corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
40.356	<p style="text-align: center;">T21N R38E <u> </u> 1/4 S 2 T20N R38E</p> <p style="text-align: center;">2011</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.</p> <p>Point for the standard 1/4 sec. cor. of sec. 35, at proportionate distance; there is no remaining evidence of the 1970-71 corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
68.450	<p style="text-align: center;">SC T21N R38E <u>1/4 S35</u></p> <p style="text-align: center;">2011</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>Point for the closing cor. of secs. 2 and 3, T. 20 N., R. 38 E., at proportionate distance; there is no remaining evidence of the 1970-71 corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF THE
FOURTH STANDARD PARALLEL NORTH,
THROUGH A PORTION OF RANGE 38 EAST,
MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T21N R38E S 35 ----- S 3 S 2 T20N R38E CC 2011</p>
80.712	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.</p> <p>Point for the standard cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the 1970-71 corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">SC T21N R38E S34 S35 ----- T20N R38E S 3 2011</p>
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <hr/> <p>S. 89°53'40" W., on the S. bdy. of sec. 34.</p> <p>Over dry lake bed.</p>
27.914	<p>Point for the N. 1/4 sec. cor. of sec. 3, T. 20 N., R. 38 E., at proportionate distance; there is no remaining evidence of the 1970-71 corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T21N R38E ----- 1/4 S 3 T20N R38E 2011</p>
30.50	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.</p> <p>Leave lake bed, edge bears NNE. and SSW.; thence over nearly level land covered with greasewood, shadscale and sagebrush.</p>
38.10	<p>Fence, bears NE. and SW.</p>

DEPENDENT RESURVEY OF THE
FOURTH STANDARD PARALLEL NORTH,
THROUGH A PORTION OF RANGE 38 EAST,
MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.356	<p>The standard 1/4 sec. cor. of sec. 34, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the Fourth Standard Parallel North, through Range 38 East, executed under Group No. 476, with a mound of stone, N.</p> <hr/> <p>From the standard cor. of secs. 33 and 34, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the Fourth Standard Parallel North, through Range 38 E., executed under Group No. 476, with a mound of stone, N.</p> <p>N. 89°39'00" W., on the S. bdy. of sec. 33.</p> <p>Over nearly level land covered with greasewood, shadscale and sagebrush.</p>
20.111	<p>Point for the standard E. 1/16 sec. cor. of sec. 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>SC S33 E 1/16</p> <hr style="width: 50px; margin: 0 auto;"/> <p>2011</p> </div>
28.328	<p>The N. 1/4 sec. cor. of sec. 4, T. 20 N., R. 38 E., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 20 N., R 38 E., executed under Group No. 476, with a mound of stone, S.</p>
40.222	<p>The standard 1/4 sec. cor. of sec. 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the Fourth Standard Parallel North, through Range 38 East, executed under Group No. 476, with a mound of stone, N.</p>

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 21 N., R. 38 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyors D.H. Barker and E.C. McClellan in 1879, and a Portion of the Dependent Resurvey Executed by Cadastral Surveyors E.W. Sibley and R.A. Pratt in 1970</p> <hr/> <p>From the standard cor. of Tps. 21 N., Rs. 38 and 39 E., hereinbefore described.</p> <p>N. 0°07'30" W., bet. secs. 31 and 36.</p> <p>Over dry lake bed.</p>
40.165	<p>Point for the 1/4 sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the 1970 corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T21N R38E R39E 1/4 S36 S31</p> <p style="text-align: center;">2011</p>
80.330	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Point for the cor. of secs. 25, 30, 31 and 36, at proportionate distance; the 1970 resurvey iron post was found lying loose on the ground surface, severely rusted and the true position could not be determined.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T21N R38E R39E S25 S30 ----- S36 S31</p> <p style="text-align: center;">2011</p>
40.165	<p>Bury the iron post alongside the stainless steel post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <hr/> <p>N. 0°07'30" W., bet. secs. 25 and 30.</p> <p>Over dry lake bed.</p> <p>Point for the 1/4 sec. cor. of secs. 25 and 30, at proportionate distance; there is no remaining evidence of the 1970 corner.</p>

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 21 N., R. 38 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p> <p>80.330</p> <p>40.165</p> <p>74.00</p>	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T21N R38E R39E 1/4 S25 S30</p> <p style="text-align: center;">2011</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>Point for the cor. of secs. 19, 24, 25 and 30, at proportionate distance; there is no remaining evidence of the 1970 corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T21N R38E R39E S24 S19 ----- S25 S30</p> <p style="text-align: center;">2011</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <hr/> <p>N. 0°07'30" W., bet. secs. 19 and 24.</p> <p>Over dry lake bed.</p> <p>Point for the 1/4 sec. cor. of secs. 19 and 24, at proportionate distance; there is no remaining evidence of the 1970 corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T21N R38E R39E 1/4 S24 S19</p> <p style="text-align: center;">2011</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Leave lake bed, edge NE. and SW.; thence over nearly level land covered with greasewood, shadescale and sagebrush.</p>
--	--

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 21 N., R. 38 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
80.330	<p>The cor. of secs. 13, 18, 19 and 24, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the west boundary of T. 21 N., R. 39 E., executed under Group No. 476, with a mound of stone, W. of cor.</p>
	<hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 21 N., R. 38 E., MOUNT DIABLO MERIDIAN</p> <hr/>
	<p>Reestablishment of a Portion of the Survey Executed by U.S Deputy Surveyors D.H. Barker and E.C. McClellan, in 1879</p> <hr/>
	<p>From the standard cor. of secs. 35 and 36, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°14'20" W., bet. secs. 35 and 36.</p> <p>Over dry lake bed.</p>
39.869	<p>Point for the 1/4 sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T21N R38E 1/4 S35 S36 2011</p>
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>
79.738	<p>Point for the cor. of secs. 25, 26, 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T21N R38E S26 S25 ----- S35 S36 2011</p>
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <hr/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 38 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., hereinbefore described.</p>
	<p>S. 89°28'30" W., bet. secs. 25 and 36.</p>
	<p>Over dry lake bed.</p>
40.427	<p>Point for the 1/4 sec. cor. of secs. 25 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T21N R38E S25 1/4 — S36</p>
	<p style="text-align: center;">2011</p>
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>
80.854	<p>The cor. of secs. 25, 26, 35 and 36.</p> <hr/>
	<p>N. 0°14'50" W., bet. secs. 25 and 26.</p>
	<p>Over dry lake bed.</p>
39.869	<p>Point for the 1/4 sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T21N R38E 1/4 S26 S25</p>
	<p style="text-align: center;">2011</p>
	<p>Raise a mound of stone, 3 ft. base, 2 ft., high, W. of cor.</p>
63.00	<p>Leave lake bed, edge bears NE. and SW.; thence over nearly level land covered with greasewood, shadscale and sagebrush.</p>
79.738	<p>Point for the cor. of secs. 23, 24, 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 38 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T21N R38E S23 S24 S26 S25 2011
	<hr/> From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., hereinbefore described. S. 89°03'30" W., bet. secs. 24 and 25. Over dry lake bed.
40.506	Point for the 1/4 sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T21N R38E S24 1/4 — S25 2011
60.759	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor. Point for the W. 1/16 sec. cor. of secs. 24 and 25. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	S24 W 1/16 — S25 2011
62.00	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor. Leave lake bed, edge bears NE. and SW.; thence over nearly level land covered with greasewood, shadscale and sagebrush.
81.012	The cor. of secs. 23, 24, 25 and 26.
	<hr/> N. 0°46'10" E., bet. secs. 23 and 24. Over dry lake bed.
19.936	Point for the S. 1/16 sec. cor. of secs. 23 and 24.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 38 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S23 S24</p> <p style="text-align: center;">2011</p>
39.872	<p>The 1/4 sec. cor. of secs. 23 and 24, monumented with a sandstone, 13X6X5 ins., firmly set, projecting 6 ins. above ground, mkd. 1/4 on E. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T21N R38E 1/4 S23 S24</p> <p style="text-align: center;">2011</p> <p>Bury the original corner stone alongside the stainless steel post.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 0°35'50" E., beginning new measurement.</p>
42.211	<p>The cor. of secs. 13, 14, 23 and 24, monumented with a granite stone, 17X10X7 ins., firmly set, projecting 8 ins. above the ground, mkd. with 1 notch on E. edge and 2 notches on S. edge.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T21N R38E S14 S13 <hr style="width: 50%; margin: 0 auto;"/>S23 S24</p> <p style="text-align: center;">2011</p> <p>Bury the original corner stone alongside the stainless steel post.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°05'40" W., bet. secs. 13 and 24.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 38 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Over nearly level land covered with greasewood, shadscale and sagebrush.</p> <p>39.643 The 1/4 sec. cor. of secs. 13 and 24, monumented with a basalt stone, 14X6X4 ins., firmly set, projecting 4 ins. above ground, mkd. 1/4 on S. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T21N R38E S13 1/4 — S24</p> <p style="text-align: center;">2011</p> <p>Bury the original corner stone alongside the stainless steel post.</p> <p>From this cor., a seep spring, 40 lks. diam., bears S. 9 1/2° E., 28.50 chs. dist.</p> <p>From this same cor., a seep spring, 40 lks. diam., bears S. 1 1/2° E., 34.00 chs. dist.</p> <hr/> <p>S. 89°42'00" W., beginning new measurement.</p>
40.194	<p>The cor. of secs. 13, 14, 23 and 24.</p> <hr/> <p>N. 0°11'10" W., bet. secs. 13 and 14.</p>
14.90	<p>Over nearly level land covered with greasewood, shadscale and sagebrush.</p> <p>Graveled road, 30 lks. wide, bears NE. and SW.</p>
40.194	<p>The 1/4 sec. cor. of secs. 13 and 14, monumented with a limestone, 11X9X7 ins., firmly set, projecting 6 ins. above ground, mkd. 1/4 on E. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T21N R38E 1/4 S14 S13 2011</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 38 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Bury the original corner stone alongside the stainless steel post.</p> <hr/> <p>N. 1°26'20" W., beginning new measurement.</p>				
20.40	Toe of slope, bears NE. and SW., ascend.				
31.90	Top of ridge, bears NE. and SW.				
39.894	<p>Point for the cor. of secs. 11, 12, 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T21N R38E</td></tr> <tr><td>S11 S12</td></tr> <tr><td>S14 S13</td></tr> </table> <p>2011</p> </div> <hr/> <p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the west boundary of T. 21 N., R 39 E., executed under Group No. 476, with a mound of stone, W. of cor.</p> <p>N. 89°43'30" W., bet. secs. 12 and 13.</p> <p>Over nearly level land covered with cheat grass and sagebrush.</p>	T21N R38E	S11 S12	S14 S13	
T21N R38E					
S11 S12					
S14 S13					
39.50	Dry wash, 40 lks. wide, drains SE.				
40.150	<p>Point for the 1/4 sec. cor. of secs. 12 and 13, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T21N R38E</td></tr> <tr><td>S12</td></tr> <tr><td>1/4 —</td></tr> <tr><td>S13</td></tr> </table> <p>2011</p> </div>	T21N R38E	S12	1/4 —	S13
T21N R38E					
S12					
1/4 —					
S13					
56.00	Toe of slope, bears NE. and SW., ascend.				
72.90	Top of ascent.				
80.300	The cor. of secs. 11, 12, 13 and 14.				

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 38 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°04'40" E., bet. secs. 11 and 12.
	Over low hills covered with cheat grass and sagebrush.
31.20	Dry wash, 30 lks. wide, drains SE.
39.882	Point for the 1/4 sec. cor. of secs. 11 and 12, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.
	T21N R38E 1/4 S11 S12
	2011
79.764	The cor. of secs. 1, 2, 11 and 12, monumented with a limestone, 15X8X8 ins., firmly set, projecting 6 ins. above ground, mkd. with 1 notch on E. edge and 5 notches on S. edge.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.
	T21N R38E S 2 S 1 S11 S12
	2011
	Bury the original corner stone alongside the stainless steel post.
	From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the west boundary of T. 21 N., R 39 E., executed under Group No. 476, with a mound of stone, W. of cor.
	S. 89°36'20" W., bet. secs. 1 and 12.
	Over low hills covered with cheat grass and sagebrush.
29.90	Dry wash, 20 lks. wide, drains SE.
40.070	The 1/4 sec. cor. of secs. 1 and 12, monumented with a granite stone, 16X11X3 ins., firmly set, projecting 6 ins. above ground, mkd. 1/4 on S. face.
	At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 38 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T21N R38E S 1 1/4 — S12</p> <p style="text-align: center;">2011</p> <hr style="width: 30%; margin: auto;"/> <p>N. 89°18'50" W., beginning new measurement.</p> <p>6.40 Top of ridge, bears SE. and NW.</p> <p>40.059 The cor. of secs. 1, 2, 11 and 12.</p> <hr style="width: 30%; margin: auto;"/> <p>From the standard cor. of secs. 34 and 35, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°50'20" W., bet. secs. 34 and 35.</p> <p>Over dry lake bed.</p> <p>36.50 Leave lake bed, edge bears NNE. and SW.; thence over nearly level land covered with greasewood, shadscale and sagebrush.</p> <p>40.397 The 1/4 sec. cor. of secs. 34 and 35, monumented with a basalt stone, 12X5X4 ins., firmly set, projecting 6 ins. above ground, mkd. 1/4 on E. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T21N R38E 1/4 S34 S35</p> <p style="text-align: center;">2011</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <hr style="width: 30%; margin: auto;"/> <p>N. 0°48'40" E., beginning new measurement.</p> <p>40.164 Point for the cor. of secs. 26, 27, 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
--------	---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 38 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T21N R38E $\frac{S27}{S34} \frac{S26}{S35}$ 2011</p>
	<p>From the cor. of secs. 25, 26, 35 and 36. N. 89°31'40" W., bet. secs. 26 and 35. Over dry lake bed.</p>
40.194	<p>Point for the 1/4 sec. cor. of secs. 26 and 35, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T21N R38E S26 $\frac{1/4}{S35}$ 2011</p>
50.00	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor. Leave lake bed, edge bears NE. and SW.; thence over nearly level land covered with greasewood, shadscale and sagebrush.</p>
80.388	<p>The cor. of secs. 26, 27, 34 and 35.</p>
	<p>N. 0°24'20" W., bet. secs. 26 and 27. Over nearly level land covered with greasewood, shadscale and sagebrush.</p>
40.161	<p>Point for the 1/4 sec. cor. of secs. 26 and 27, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T21N R38E 1/4 $\frac{S27}{S26}$ 2011</p>
80.322	<p>The cor. of secs. 22, 23, 26 and 27, monumented with a limestone, 13X6X5 ins., firmly set, projecting 6 ins. above ground, mkd. with 2 grooves on E. face and 2 grooves on S. face.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 38 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS									
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1" data-bbox="878 436 1027 537"> <tr><td>T21N</td><td>R38E</td></tr> <tr><td>S22</td><td>S23</td></tr> <tr><td>S27</td><td>S26</td></tr> </table> <p>2011</p> </div> <p>Bury the original corner stone alongside the stainless steel post.</p>	T21N	R38E	S22	S23	S27	S26		
T21N	R38E								
S22	S23								
S27	S26								
40.303	<hr/> <p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>N. 89°06'50" W., bet. secs. 23 and 26.</p> <p>Over nearly level land covered with greasewood, shadscale and sagebrush.</p> <p>Point for the 1/4 sec. cor. of secs. 23 and 26, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1" data-bbox="878 1108 1027 1226"> <tr><td>T21N</td><td>R38E</td></tr> <tr><td>S23</td><td>—</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S26</td><td>—</td></tr> </table> <p>2011</p> </div>	T21N	R38E	S23	—	1/4	—	S26	—
T21N	R38E								
S23	—								
1/4	—								
S26	—								
80.606	<hr/> <p>The cor. of secs. 22, 23, 26 and 27.</p> <hr/> <p>N. 0°05'20" W., bet. secs. 22 and 23.</p> <p>Over nearly level land covered with greasewood, shadscale and sagebrush.</p>								
21.20	<p>Graveled road, 30 lks. wide, bears NE. and SW.</p>								
40.078	<p>The 1/4 sec. cor. of secs. 22 and 23, monumented with a basalt stone, 16X6X6 ins., firmly set, projecting 6 ins. above ground, mkd. 1/4 on E. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p>								

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 38 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">T21N R38E 1/4 S22 S23</p> <p style="text-align: center;">2011</p> <p>Bury the original corner stone alongside the stainless steel post.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 1°55'00" E., beginning new measurement.</p> <p>9.50 Trail road, 20 lks. wide, bears NE. and SW.</p> <p>28.20 Toe of slope, bears E. and W., ascend.</p> <p>40.022 Point for the cor. of secs. 14, 15, 22 and 23, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T21N R38E S15 S14 S22 S23</p> <p style="text-align: center;">2011</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>S. 89°27'40" W., bet. secs. 14 and 23.</p> <p>Over nearly level land covered with greasewood, shadscale and sagebrush.</p> <p>14.50 Graveled road, 30 lks. wide, bears NE. and SW.</p> <p>40.142 Point for the 1/4 sec. cor. of secs. 14 and 23, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T21N R38E S14 1/4 — S23</p> <p style="text-align: center;">2011</p> <p>62.90 Toe of slope, bears SE. and NW., ascend.</p>
--------	---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 38 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
80.284	The cor. of secs. 14, 15, 22 and 23.
	<hr/>
	N. 0°45'00" W., bet. secs. 14 and 15.
	Over low rolling hills covered with greasewood, shadscale and sagebrush.
11.10	Dry wash, 30 lks. wide, drains E.
12.00	Toe of slope, bears NE. and SW., ascend.
39.00	Ridge, bears E. and W.
40.003	Point for the 1/4 sec. cor. of secs. 14 and 15, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.
	T21N R38E 1/4 S15 S14
	2011
70.60	Creek, 6 lks. wide, 1 ft. deep, course SE.; ascend.
80.006	Point for the cor. of secs. 10, 11, 14 and 15, determined latitudinally at record distance from the 1/4 sec. cor. of secs. 22 and 23 and longitudinally at record distance from the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp.; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	T21N R38E S10 S11 S15 S14
	2011
	<hr/>
	From the cor. of secs. 11, 12, 13 and 14.
	S. 89°24'20" W., bet. secs. 11 and 14.
	Over low rolling hills covered with greasewood, shadscale and sagebrush.
8.20	Ridge, bears NE. and SW.
23.30	Dry wash, 20 lks. wide, drains SE.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 38 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.092	<p>Point for the 1/4 sec. cor. of secs. 11 and 14, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T21N R38E S11 1/4 — S14</p> <p style="text-align: center;">2011</p>
61.50	Ridge, bears SE. and NW.
80.184	The cor. of secs. 10, 11, 14 and 15.
	<hr/> <p>From the standard cor. of secs. 33 and 34, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°01'10" E., bet. secs. 33 and 34.</p> <p>Across meadow covered with native grasses.</p>
14.80	Leave meadow; thence over nearly level land covered with greasewood, shadscale and sagebrush.
34.30	Fence, bears NE. and SW.
40.222	<p>The 1/4 sec. cor. of secs. 33 and 34, monumented with a basalt stone, 14X7X4 ins., firmly set, projecting 6 ins. above ground, mkd. 1/4 on E. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T21N R38E 1/4 S33 S34</p> <p style="text-align: center;">2011</p>
	<p>Bury the original corner stone alongside the stainless steel post.</p> <hr/>
	N. 0°02'10" W., beginning new measurement.
39.20	Graveled road, 30 lks. wide, bears NE. and SW.
40.088	Point for the cor. of secs. 27, 28, 33 and 34, at proportionate

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 38 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T21N R38E S28 S27 ----- S33 S34</p> <p style="text-align: center;">2011</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <hr/>
40.506	<p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>S. 89°54'30" W., bet. secs. 27 and 34.</p> <p>Over nearly level land covered with greasewood, shadscale and sagebrush.</p> <p>The 1/4 sec. cor. of secs. 27 and 34, monumented with a basalt stone, 12X6X4 ins., firmly set, projecting 6 ins. above ground, mkd. 1/4 on S. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T21N R38E S27 1/4 — S34</p> <p style="text-align: center;">2011</p> <p>Bury the original corner stone alongside the stainless steel post.</p> <hr/>
39.40	<p>N. 89°59'50" W., beginning new measurement.</p> <p>Graveled road, 30 lks. wide, bears NE. and SW.</p>
40.060	<p>The cor. of secs. 27, 28, 33 and 34.</p> <hr/>
20.40	<p>N. 0°04'50" W., bet. secs. 27 and 28.</p> <p>Over nearly level land covered with greasewood, shadscale and sagebrush.</p>
40.088	<p>Trail road, 20 lks. wide, bears SE. and NW.</p>
	<p>Point for the 1/4 sec. cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of the original corner.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 38 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T21N R38E 1/4 S28 S27</p> <p style="text-align: center;">2011</p>
80.176	<p>The cor. of secs. 21, 22, 27 and 28, monumented with a basalt stone, 15X7X7 ins., firmly set, projecting 6 ins. above ground, mkd. with 3 grooves on E. face and 2 grooves on S. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T21N R38E S21 S22 S28 S27</p> <p style="text-align: center;">2011</p> <p>Bury the original corner stone alongside the stainless steel post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>From this cor., a well, with a 10 in. casing, exposed 1 ft. above the ground, in a wood and sheet metal structure, 7 ft. square, bears N. 39°16'E., 14.80 chs. dist.</p>
	<p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>S. 89°52'10" W., bet. secs. 22 and 27.</p> <p>Over nearly level land covered with greasewood, shadscale and sagebrush.</p>
17.90	Graveled road, 30 lks. wide, bears NE. and SW.
39.960	<p>The 1/4 sec. cor. of secs. 22 and 27, monumented with a slate stone, 21X10X3 ins., firmly set, projecting 4 ins. above ground, mkd. 1/4 on S. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 38 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T21N R38E S22 1/4 ——— S27 2011
	<hr/> S. 89°50'00" W., beginning new measurement.
15.80	Trail road, 20 lks. wide, bears N. and S.
40.130	The cor. of secs. 21, 22, 27 and 28.
	<hr/> N. 1°14'10" E., bet. secs. 21 and 22. Over nearly level land covered with greasewood, shadscale and sagebrush.
18.80	Trail road, 20 lks. wide, bears SE. and NW.
38.60	Trail road, 20 lks. wide, bears NE. and SW.
40.009	Point for the 1/4 sec. cor. of secs. 21 and 22, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	T21N R38E 1/4 S21 S22 2011
46.30	Toe of slope, bears NE. and SW., ascend.
80.018	Point for the cor. of secs. 15, 16, 21 and 22, determined latitudinally at record latitude from the cor. of secs. 21, 22, 27 and 28 and longitudinally at record departure from the cor. of secs. 13, 14, 23 and 24; there is no remaining evidence of the original corner. Set a brass tablet, 3 1/4 ins. diam., 3 in. stem, cemented flush in drill hole on granite outcrop, with top mkd.
	T21N R38E S16 S15 <hr style="width: 50%; margin: 0 auto;"/> S21 S22 2011
	Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 38 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>S. 89°47'40" W., bet. secs. 15 and 22.</p> <p>Over hills covered with sagebrush.</p>
8.90	Dry wash, 20 lks. wide, drains S.
34.00	Ridge, bears NE. and SW.
39.810	<p>Point for the 1/4 sec. cor. of secs. 15 and 22, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T21N R38E S15 1/4 — S22</p> <p style="text-align: center;">2011</p>
52.20	Creek, 6 lks. wide, 1 ft. deep, course SW.
53.40	Trail road, 20 lks. wide, bears NE. and SW.
79.620	The cor. of secs. 15, 16, 21 and 22.
	<hr/> <p>From the standard cor. of secs. 32 and 33, on the S. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the Fourth Standard Parallel North, through Range 38 East, executed under Group No. 476, with a mound of stone, N. of cor.</p> <p>N. 0°25'00" E., bet. secs. 32 and 33.</p> <p>Over nearly level land covered with greasewood, shadscale and sagebrush.</p>
40.145	<p>Point for the 1/4 sec. cor. of secs. 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T21N R38E 1/4 S32 S33</p> <p style="text-align: center;">2011</p>
61.10	Dry wash, 30 lks. wide, drains SE.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 38 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS									
80.290	<p>The cor. of secs. 28, 29, 32 and 33, monumented with a limestone, 18X10X7 ins., firmly set, projecting 10 ins. above ground, mkd. with 4 grooves on E. face and 1 groove on S. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T21N</td><td>R38E</td></tr> <tr><td>S29</td><td>S28</td></tr> <tr><td>S32</td><td>S33</td></tr> </table> <p style="text-align: center;">2011</p> <p>From this cor., a rebar, determined to be a reference monument to the original cor., set by Lowell D. Emery, Nevada Professional Land Surveyor No. 1251, 5/8 in. diam., firmly set, projecting 6 ins. above the ground, with brass tag mkd. RLS 1251, bears WEST, 0.005 chs. dist.</p> <p>Bury the original corner stone and rebar alongside the stainless steel post.</p>	T21N	R38E	S29	S28	S32	S33		
T21N	R38E								
S29	S28								
S32	S33								
40.140	<p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>S. 89°58'30" W., bet. secs. 28 and 33.</p> <p>Over nearly level land covered with greasewood, shadscale and sagebrush.</p> <p>The 1/4 sec. cor. of secs. 28 and 33, monumented with a sandstone, 13X5X3 ins., firmly set, projecting 6 ins. above ground, mkd. 1/4 on S. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T21N</td><td>R38E</td></tr> <tr><td>S28</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S33</td><td></td></tr> </table> <p style="text-align: center;">2011</p> <p>Bury the original corner stone alongside the stainless steel post.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/> <p>N. 89°45'40" W., beginning new measurement.</p>	T21N	R38E	S28		1/4	—	S33	
T21N	R38E								
S28									
1/4	—								
S33									

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 38 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.071	The cor. of secs. 28, 29, 32 and 33.
	N. 0°09'40" E., bet. secs. 28 and 29.
	Over nearly level land covered with greasewood, shadscale and sagebrush.
23.90	Dry wash, 30 lks. wide, drains SE.
39.912	Point for the 1/4 sec. cor. of secs. 28 and 29, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.
	T21N R38E
	1/4
	S29 S28
	2011
51.20	Dry wash, 20 lks. wide, drains SE.
68.00	Toe of slope, bears NE. and SW., ascend.
79.824	The cor. of secs. 20, 21, 28 and 29, monumented with a basalt stone, 16X8X7 ins., firmly set, projecting 6 ins. above ground, mkd. with 4 notches on E. edge and 2 notches on S. edge.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	T21N R38E
	S20 S21
	S29 S28
	2011
	Bury the original corner stone alongside the stainless steel post.
	From the cor. of secs. 21, 22, 27 and 28.
	S. 89°51'20" W., bet. secs. 21 and 28.
	Over nearly level land covered with greasewood, shadscale and sagebrush.
5.20	Dry wash, 20 lks. wide, drains SE.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 38 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.930	<p>Point for the 1/4 sec. cor. of secs. 21 and 28, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 6 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T21N R38E S21 1/4 — S28</p> <p style="text-align: center;">2011</p>
48.20	Trail road, 20 lks. wide, bears SE. and NW.
79.860	The cor. of secs. 20, 21, 28 and 29.
	<hr/> <p>N. 0°46'00" E., bet. secs. 20 and 21.</p>
	Over hills covered with native grasses, pinon pine and cedar trees.
7.40	Dry wash, 20 lks. wide, drains SE.
19.50	Spur, slopes SE.
39.70	Spur, slopes E.
40.003	<p>Point for the 1/4 sec. cor. of secs. 20 and 21, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T21N R38E 1/4 S20 S21</p> <p style="text-align: center;">2011</p>
46.20	Dry wash, 20 lks. wide, drains SE.
51.80	Spur, slopes E.
63.00	Toe of slope, bears SE. and NW.
63.30	Creek, 10 lks. wide, 1 ft. deep, course SE.
63.60	Toe of slope, bears SE. and NW., ascend.
80.006	<p>Point for the cor. of secs. 16, 17, 20 and 21, determined latitudinally at record latitude from the cor. of secs. 20, 21, 28 and 29 and longitiudinally at record depature from the cor.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 21 N., R. 38 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>of secs. 13, 14, 23 and 24; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2">T21N R38E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S17</td> <td style="padding: 0 5px;">S16</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S20</td> <td style="padding: 0 5px;">S21</td> </tr> </table> <p>2011</p> <hr/> <p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>S. 89°51'20" W., bet. secs. 16 and 21.</p> <p>Over mountainous land covered with native grasses, pinon pine and cedar trees.</p> <p>13.20 Spur, slopes SE.</p> <p>38.20 Jeep trail, 20 lks. wide, bears NE. and SW.</p> <p>39.00 Jeep trail, 20 lks. wide, bears NE. and SW.</p> <p>40.250 Point for the 1/4 sec. cor. of secs. 16 and 21, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2">T21N R38E</td> </tr> <tr> <td colspan="2">S16</td> </tr> <tr> <td style="padding: 0 5px;">1/4</td> <td style="border-bottom: 1px solid black; padding: 0 5px;">—</td> </tr> <tr> <td colspan="2">S21</td> </tr> </table> <p>2011</p> </div> <p>41.50 Ridge, bears NE. and SW.</p> <p>80.500 The cor. of secs. 16, 17, 20 and 21.</p> <hr/> </div>	T21N R38E		S17	S16	S20	S21	T21N R38E		S16		1/4	—	S21	
T21N R38E															
S17	S16														
S20	S21														
T21N R38E															
S16															
1/4	—														
S21															

TOWNSHIP 21 NORTH, RANGE 38 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	GENERAL DESCRIPTION
	<p>The land within Township 21 North, Range 38 East, lies mostly in Edwards Creek Valley and ranges from about 5100 to 7000 ft. above sea level. The land goes from a level dry lake bed to steep mountains covered with juniper and pinon pine trees. The soil varies from a clay loam to very sandy. The mountainous area is very rocky. Areas in sections 21 and 22 show evidence of mining activity.</p> <p>The area drains to the east into a dry lake bed. There are several seep springs which provide water for the wildlife and cattle.</p> <p>Access into the area is provided by U.S. Highway No. 50 and supplemented by numerous trail roads. The principal use of the area is ranching and mining.</p> <hr/>

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Daniel R. Helmricks

Surveying Technician

CERTIFICATE OF SURVEY

I, Don R. Aschenbach, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 23rd day of May, 2011, I have dependently resurveyed the Fourth Standard Parallel North, through a portion of Range 38 East, a portion of the east boundary and a portion of the subdivisional lines of Township 21 North, Range 38 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

May 8, 2012

Date

Don R. Aschenbach
Cadastral Surveyor

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of the dependent resurvey of the Fourth Standard Parallel North, through a portion of Range 38 East, a portion of the east boundary and a portion of the subdivisional lines of Township 21 North, Range 38 East, Mount Diablo Meridian, Nevada, executed by Don R. Aschenbach, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

May 10, 2012

Date

David P. Morla
Chief Cadastral Surveyor for Nevada

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above described surveys in T. 21 N., R. 38 E., Mount Diablo Meridian, Nevada, is a true copy of the original field notes.~~

~~_____~~
Date

~~_____~~
Chief Cadastral Surveyor for Nevada