

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF THE

FIFTH STANDARD PARALLEL SOUTH, ON THE SOUTH BOUNDARY OF TOWNSHIP 20 SOUTH,

THROUGH A PORTION OF RANGE 62 EAST;

AND THE

DEPENDENT RESURVEY

OF

A PORTION OF THE SUBDIVISIONAL LINES

AND

A PORTION OF THE SUBDIVISION-OF-SECTION LINES OF SECTION 2,

THE FURTHER SUBDIVISION OF SECTION 2,

AND

METES-AND-BOUNDS SURVEYS IN SECTION 2,

TOWNSHIP 21 SOUTH, RANGE 62 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATE OF NEVADA

EXECUTED BY

Brent K. Layton, Nevada Professional Land Surveyor

Under Contract No. NDC060022,

Special Instructions dated January 22, 2007,

and approved January 22, 2007,

which provided for the surveys included under Group No. 843,

and Assignment Instructions dated March 27, 2007.

Survey commenced April 2, 2007

Survey completed July 26, 2007

INDEX DIAGRAM

TOWNSHIP 21 SOUTH, RANGE 62 EAST, MOUNT DIABLO MERIDIAN, NEVADA

|    |    |    |    |        |    |   |
|----|----|----|----|--------|----|---|
|    |    |    |    | 3      | 2  |   |
| 6  | 5  | 4  | 3  | 5<br>4 | 2  | 1 |
| 7  | 8  | 9  | 10 | 11     | 12 |   |
| 18 | 17 | 16 | 15 | 14     | 13 |   |
| 19 | 20 | 21 | 22 | 23     | 24 |   |
| 30 | 29 | 28 | 27 | 26     | 25 |   |
| 31 | 32 | 33 | 34 | 35     | 36 |   |

Dependent Resurvey of a Portion of the  
 Subdivision-of-Section Lines of Section 2 ..... pp. 6 - 8.  
 Further Subdivision of Section 2 ..... pp. 8 - 9.  
 Metes-and-Bounds Survey of a Portion of the  
 Centerline of Hollywood Boulevard in Section 2 ..... pp. 10 - 11.  
 Metes-and-Bounds Survey of a Portion of the  
 Centerline of American Beauty Road in Section 2 ..... pp. 12 - 13.

## TOWNSHIP 21 SOUTH, RANGE 62 EAST, MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

The following field notes are those of the dependent resurvey of the Fifth Standard Parallel South, on the south boundary of Township 20 South, through a portion of Range 62 East; and the dependent resurvey of a portion of the subdivisional lines and a portion of the subdivision-of-section lines of section 2, the further subdivision of section 2, and metes-and-bounds surveys in section 2, Township 21 South, Range 62 East, Mount Diablo Meridian, Nevada.

The north boundary (Fifth Standard Parallel South), the east, south and west boundaries and subdivisional lines were surveyed by U.S. Deputy Surveyors J.M. Brunt and W.H. Proctor in 1881 under Contract No. 127.

The north boundary (Fifth Standard Parallel South), the east, south and west boundaries and subdivisional lines were dependently resurveyed by Associate Cadastral Engineer E. Voigt and Assistant Cadastral Engineer J.W. Hardison in 1943 under Group No. 336.

A portion of the north boundary (Fifth Standard Parallel South), a portion of the east boundary and a portion of the subdivisional lines were dependently resurveyed, and sections 1, 2, 11 and 12 were subdivided by Cadastral Surveyor R.A. Pratt in 1991 through 1994 under Group No. 708.

Before restoring the corners, the lines of the original surveys were retraced and diligent search made for any evidence of the original corners and other calls of the original field note record.

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 843, dated January 22, 2007.

Measurements were made with Trimble 5800 Global Positioning System (GPS) receivers using the real-time kinematic (RTK) method and refer to the true meridian based on geodetic methods. The mean bearings of the lines and horizontal equivalents of ground distances only are entered in the field notes.

The NAD 83 (CORS 96) geographic position of the 1/4 sec. cor. of secs. 2 and 11, determined from Global Positioning System (GPS) static observations processed by the National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) KING KINGMAN CORS ARP, LVWD LAS VEGAS VALLEY CORS ARP, and NVLM AMS WT FACILITY CORS ARP, in 2007, is as follows:

Latitude: 36°08'40.167" N.

Longitude: 115°01'12.471" W.

The April 2, 2007, mean magnetic declination was determined to be 12°44' E. from the National Oceanic and Atmospheric Administration's National Geophysical Data Center declination calculator.

DEPENDENT RESURVEY OF THE FIFTH STANDARD PARALLEL SOUTH,  
ON THE SOUTH BOUNDARY OF TOWNSHIP 20 SOUTH,  
THROUGH A PORTION OF RANGE 62 EAST, MOUNT DIABLO MERIDIAN, NEVADA

| CHAINS |   |
|--------|---|
|        | <p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyors J.M. Brunt and W.H. Proctor in 1881, a Portion of the Dependent Resurvey Executed by Associate Cadastral Engineer E. Voigt and Assistant Cadastral Engineer J.W. Hardison in 1943, and a Portion of the Dependent Resurvey Executed by Cadastral Surveyor R.A. Pratt in 1991-1994</p> <hr/>   |
|        | <p>Beginning at the standard cor. of secs. 35 and 36, T. 20 S., R. 62 E., monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 21 S., R. 62 E., executed under Group No. 336.</p> <p>N. 89°00'00" W., on the S. bdy. of sec. 35.</p> <p>Descend over SW. slope.</p>  |
| 12.977 | <p>The closing cor. of secs. 1 and 2, T. 21 S., R. 62 E., perpetuated by James H. Turner, Nevada Professional Land Surveyor No. 10356, monumented with a brass cap, 2 ins. diam., firmly set in a concrete cylinder, 6 ins. diam., 24 ins. below ground, mkd. 1996 T20S R62E S35 CC S1 S2 T21S PLS 10356, as recorded in Clark County, Nevada, File 87, Page 79 of Surveys. This is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>Gradually descend, along the center of Charleston Boulevard (dirt).</p>  |
| 40.119 | <p>Point for the standard 1/4 sec. cor. of sec. 35, at proportionate distance, based on the official record of 1994 bet. the standard cor. of secs. 35 and 36 and the standard W 1/16 sec. cor. of sec. 35, falls in road under construction where it is impracticable to occupy and set a durable article and also not suitable for reference monuments; there is no remaining evidence of the local corner described in the field notes of dependent resurvey of T. 21 S., R. 62 E., executed under Group No. 708.</p> <hr/> <p>N. 88°59'20" W., beginning new measurement.</p> <p>Gradually descend, along the center of Charleston Boulevard.</p> |
| 13.999 | <p>The 1/4 sec. cor. of sec. 2, T. 21 S., R. 62 E., hereinafter described.</p>  |
| 20.044 | <p>The standard W 1/16 sec. cor. of sec. 35, determined by person(s) unknown, monumented with a magnetic nail, 1/2 in. long, firmly set flush with the asphalt. This is accepted as the best available evidence of the position of the local corner described in the field notes of the dependent resurvey of T. 21 S., R. 62 E., executed under Group No. 708, from which accessories established by person(s) unknown</p>   |

DEPENDENT RESURVEY OF THE FIFTH STANDARD PARALLEL SOUTH,  
ON THE SOUTH BOUNDARY OF TOWNSHIP 20 SOUTH,  
THROUGH A PORTION OF RANGE 62 EAST, MOUNT DIABLO MERIDIAN, NEVADA

|        |  |
|--------|--|
| CHAINS | <p>An aluminum tablet, 2 ins. diam., firmly set in the top of concrete curb, mkd. RM 79.65, bears N. 18°46' E., 120.7 lks. dist., located at the NE. cor. of Charleston Boulevard and Radwick Street, near the point of curvature on Radwick Street.</p> <p>An aluminum tablet, 2 ins. diam., firmly set in the top of concrete curb, mkd. RM 63.25, bears N. 32°16' E., 95.8 lks. dist., located at the NE. cor. of Charleston Boulevard and Radwick Street, near the midpoint of the curve.</p> <p>An aluminum tablet, 2 ins. diam., firmly set in the top of concrete curb, mkd. RM 72.27, bears N. 52°33' E., 109.5 lks. dist., located at the NE. cor. of Charleston Boulevard and Radwick Street near the point of curvature on Charleston Boulevard.</p> <p>At the corner point</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, in a drill hole in asphalt, over a plastic-encased magnet, with top mkd.</p> <p style="text-align: center;">SC<br/>S35<br/><u>W 1/16</u></p> <p style="text-align: center;">2007</p> <p>Remove and dispose of the magnetic nail.</p> <p>Cor. is located at the intersection of Charleston Boulevard bears E. and W. and Radwick Street, bears N.</p> <hr/> <p>N. 88°59'40" W., beginning new measurement.</p> <p>Gradually descend, along the center of Charleston Boulevard (asphalt).</p> <p>14.525 The W 1/16 sec. cor. of sec. 2 only, T. 21 S., R. 62 E., hereinafter described.</p> <p>20.042 The standard cor. of secs. 34 and 35, monumented with a brass cap, 2 ins. diam., firmly set in concrete, 8 ins. below the surface of the asphalt and in a monument well, mkd. as described in the field notes of the dependent resurvey of T. 21 S., R. 62 E., executed under Group No. 708.</p> <p>Cor. is located at the intersection of Charleston Boulevard, bears E. and W. and Hollywood Boulevard, bears N. and S.</p> <hr/> <p>N. 88°03'10" W., on the S. bdy. of sec. 34.</p> <p>Gradually descend, along the center of Charleston Boulevard (asphalt).</p> |
|--------|--|

DEPENDENT RESURVEY OF THE FIFTH STANDARD PARALLEL SOUTH,  
ON THE SOUTH BOUNDARY OF TOWNSHIP 20 SOUTH,  
THROUGH A PORTION OF RANGE 62 EAST, MOUNT DIABLO MERIDIAN, NEVADA

| CHAINS  |   |
|---|---|
| 15.059  | The closing cor. of secs. 2 and 3, T. 21 S., R. 62 E., hereinafter described.   |
| 42.610  | The standard 1/4 sec. cor. of sec. 34, monumented with a brass cap, 2 ins. diam., firmly set in concrete, 8 ins. below the surface of the asphalt and in a monument well, mkd. as described in the field notes of the dependent resurvey of T. 21 S., R. 62 E., executed under Group No. 708.   |
|   | Cor. is located at the intersection of Charleston Boulevard, bears E. and W. and Fog Street, bears N.   |
| <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,<br/>T. 21 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>  |   |
| <p>Reestablishment of a Portion of the Survey Executed by<br/>U.S. Deputy Surveyors J.M. Brunt and W.H. Proctor in 1881,<br/>a Portion of the Dependent Resurvey Executed by<br/>Associate Cadastral Engineer E. Voigt<br/>and Assistant Cadastral Engineer J.W. Hardison in 1943,<br/>and a Portion of the Dependent Resurvey Executed by<br/>Cadastral Surveyor R.A. Pratt in 1991-1994</p> <hr/> |   |
|   | From the 1/4 sec. cor. of secs. 2 and 11, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 21 S., R. 62 E., executed under Group No. 708.  |
|   | N. 89°56'20" W., bet. secs. 2 and 11.   |
|   | Over open, rolling land.  |
| 20.116  | Point for the W 1/16 sec. cor. of secs. 2 and 11, at proportionate distance, based on a private survey conducted by James H. Turner, Nevada Professional Land Surveyor No. 10356, as recorded in Clark County, Nevada, File 87, Page 79 of Surveys, falls in road under construction where it is impracticable to occupy and set a durable article and also not suitable for reference monuments; there is no remaining evidence of the 1991-94 corner.   |
|   | <hr/> <p>N. 89°57'00" W., beginning new measurement.</p>  |
| 20.114  | The cor. of secs. 2, 3, 10 and 11, determined by Danny L. Rider, Nevada Professional Land Surveyor No. 7169, unrecorded, monumented with a brass cap, 2 ins. diam., firmly set 6 ins. below the surface of the asphalt and in a monument well, mkd. 1994 T21S R62E 2 3 10 11 PLS 7169, as shown on map filed March 4, 1997, the survey conducted by James H. Turner, Professional Land Surveyor No. 10356, and recorded in Clark County, Nevada, File 87, Page 79 of Surveys. This is accepted as the best available evidence of the position of the local corner described in the field notes of the dependent resurvey of T. 21 S., R. 62 E., executed under Group No. 708, from which accessories established by person(s) unknown |

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 21 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

|               |  |
|---------------|--|
| <p>CHAINS</p> | <p>A brass tablet, 1 1/2 ins. diam., firmly set in the top of concrete curb, mkd. RM 99.77, bears N. 62°24' W., 151.2 lks. dist., located at the NW. cor. of Hollywood Boulevard and Sahara Avenue, on the tangent of Sahara Avenue.</p> <p>A brass tablet, 1 1/2 ins. diam., firmly set in the top of concrete curb, mkd. RM 90.20, bears N. 59°16' W., 136.7 lks. dist., located at the NW. cor. of Hollywood Boulevard and Sahara Avenue, near the point of curvature of Sahara Avenue.</p> <p>A brass tablet, 1 1/2 ins. diam., firmly set in the top of concrete curb, mkd. RM 90.60, bears N. 30°01' W., 137.3 lks. dist., located at the NW. cor. of Hollywood Boulevard and Sahara Avenue, near the point of curvature of Hollywood Boulevard.</p> <p>A brass tablet, 1 1/2 ins. diam., firmly set in the top of concrete curb, mkd. RM 99.98, bears N. 27°00' W., 151.5 lks. dist., located at the NW. cor. of Hollywood Boulevard and Sahara Avenue, on the tangent of Hollywood Boulevard.</p> <p>Cor. is located at the intersection of Hollywood Boulevard, bears N. and S. and Sahara Avenue, bears E. and W.</p> <hr/> <p>N. 0°24'00" W., bet. secs. 2 and 3.</p> <p>Over open, rolling land, along the center of Hollywood Boulevard (asphalt).</p> <p>20.316 The S 1/16 sec. cor. of secs. 2 and 3, determined by Kay L. Adams, Nevada Professional Land Surveyor No. 2050, in 1980, as recorded in Clark County, Nevada, File 36, Page 6 of Surveys. This point subsequently determined by Timothy M. Dobbins, Nevada Professional Land Surveyor No. 11180, unrecorded, monumented with a brass cap, 2 ins. diam., firmly set in concrete, flush with the asphalt, mkd. PLS 11180. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>Cor. is located at the intersection of Hollywood Boulevard, bears N. and S. and Wildcat Way, bears W.</p> <hr/> <p>N. 0°24'00" W., beginning new measurement.</p> <p>Over nearly level land, on the centerline of Hollywood Boulevard (asphalt).</p> <p>1.515 The point for a witness point and point of curvature and intersection of the centerline of Hollywood Boulevard with the line bet. secs. 2 and 3, hereinafter described.</p> <p>Leave centerline of Hollywood Boulevard curving NE.; continue over nearly level land.</p> |
|---------------|--|

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 21 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

| CHAINS |   |
|--------|---|
| 20.316 | <p>The original 1/4 sec. cor. of secs. 2 and 3, recovered by Frederick W. Orban, Nevada Professional Land Surveyor No. 4541, in 1993, as recorded in Clark County, Nevada, Book 73, Page 61 of Plats. This point subsequently perpetuated by Frederick W. Orban, monumented with a concrete nail and brass tag, firmly set in concrete footing on the east side of a north-south block wall, mkd. PLS 4541, as recorded in Clark County, Nevada, File 97, Page 62 of Surveys. This is accepted as a careful and faithful perpetuation of the position of the original corner.</p>       |
|        | <p>_____</p> <p>N. 0°26'30" W., beginning new measurement.</p> <p>Over nearly level land.</p>   |
| 7.456  | <p>The point for a witness point and intersection of the centerline of American Beauty Road with the line bet. secs. 2 and 3, hereinafter described.</p>  |
| 21.498 | <p>The N 1/16 sec. cor. of secs. 2 and 3, determined by Kay L. Adams, Nevada Professional Land Surveyor No. 2050, in 1980, as recorded in Clark County, Nevada, File 36, Page 6 of Surveys. This point subsequently determined by Robert M. Mcentee, Nevada Professional Land Surveyor No. 12998, unrecorded, monumented with a concrete nail and brass tag, firmly set in concrete footing on the east side of a north-south block wall, mkd. PLS 12998. This is accepted as a careful and faithful determination of the position of the corner.</p>                                   |
|        | <p>_____</p> <p>N. 0°27'00" W., beginning new measurement.</p>  |
| 19.521 | <p>Intersect the Fifth Standard Parallel South.</p> <p>The closing cor. of secs. 2 and 3, monumented with a brass cap, 2 ins. diam., firmly set in concrete; 8 ins. below the surface of the asphalt and in a monument well, mkd. as described in the field notes of the dependent resurvey of T. 21 S., R. 62 E., executed under Group No. 708.</p> <p>Cor. is located in the center of Charleston Boulevard, bears E. and W.</p> <p>From this corner, the standard cor. of secs. 34 and 35, T. 20 S., R. 62 E., bears S. 88°03'10" E., 15.059 chs. dist., hereinbefore described.</p> |
|        | <p>_____</p> <p>DEPENDENT RESURVEY OF A PORTION OF THE<br/>SUBDIVISION-OF-SECTION LINES OF SECTION 2,<br/>T. 21 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <p>_____</p>  |
|        | <p>Reestablishment of a Portion of the Subdivision Executed by<br/>Cadastral Surveyor R.A. Pratt in 1991-1994</p> <p>_____</p>  |
|        | <p>From the 1/4 sec. cor. of secs. 2 and 11.</p> <p>N. 0°14'00" E., on the N-S center line of sec. 2.</p>   |



DEPENDENT RESURVEY OF A PORTION OF THE  
 SUBDIVISION-OF-SECTION LINES OF SECTION 2,  
 T. 21 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

|        |  |
|--------|--|
| CHAINS | Over open, gently rolling land.  |
| 20.118 | Point for the center S 1/16 sec. cor. of sec. 2.   |
|        | NOT MONUMENTED   |
| 40.236 | The center 1/4 sec. cor. of sec. 2, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above the ground and in a collar of stone, with brass cap mkd. as described in the field notes of the subdivision of section 2, T. 21 S., R. 62 E., executed under Group No. 708. |
|        | Cor. is located 3 ft. NE. of a fence corner, fence line bears N. and E., and 25 ft. E. of another fence corner, fence line bears N. and W.   |
|        | N. 0°12'10" E., beginning new measurement.   |
|        | Over open, gently rolling land.  |
| 21.123 | Point for the center N 1/16 sec. cor. of sec. 2, at proportionate distance, falls at the corner of a block wall, 7 ft. high, topped with pigeon spikes, wall bears N. and W., where it is impracticable to establish a permanent monument; there is no remaining evidence of the 1991-94 corner.               |
|        | from which   |
|        | A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 8 ins. in the ground and in a mound of stone, 3 ft. base to top, over plastic-encased magnet, for a reference monument, bears S. 89° 37' E., 31.2 lks. dist., with brass cap mkd. RM C-N 1/16 S2   |
|        | 20.6 FT TO COR 2007 and an arrow pointing to the corner.   |
|        | A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 18 ins. in the ground and in a mound of stone, 3 ft. base to top, over plastic-encased magnet, for a reference monument, bears S. 2° 59' W., 25.3 lks. dist., with brass cap mkd. RM C-N 1/16 S2   |
|        | 16.7 FT TO COR 2007 and an arrow pointing to the corner.   |
| 40.482 | Point for the 1/4 sec. cor. of sec. 2, on the N. bdy. of sec. 2, at proportionate distance, based on the official record of 1994 bet. the standard 1/4 sec. cor. of sec. 35 and the standard W 1/16 sec. cor. of sec. 35; there is no remaining evidence of the 1991-94 corner.                                |
|        | Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, in a drill hole in asphalt, over a plastic-encased magnet, with top mkd.   |
|        | <u>T20S R62E</u>   |
|        | 1/4 S 2  |
|        | T21S R62E  |
|        | 2007   |

DEPENDENT RESURVEY OF A PORTION OF THE  
SUBDIVISION-OF-SECTION LINES OF SECTION 2,  
T. 21 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

|        |   |
|--------|---|
| CHAINS | <p>Cor. is located at the west side of Whitewind Lane, bears N. and in the center of Charleston Boulevard, bears E. and W.</p> <p>From this corner, the standard W 1/16 sec. cor. of sec. 35, T. 20 S., R. 62 E., bears N. 88°59'20" W., 6.045 chs. dist., hereinbefore described.</p> <hr/> <p>From the center 1/4 sec. cor. of sec. 2.</p> <p>N. 89°23'10" W., on a portion of the E-W center line of sec. 2.</p> <p>Over open, gently rolling land.</p> <p>20.339 Point for the center W 1/16 sec. cor. of sec. 2.</p> <p>NOT MONUMENTED</p> <p>33.208 The point for a witness point and intersection of the centerline of Hollywood Boulevard with the E-W center line of sec. 2, hereinafter described.</p> <p>40.678 The 1/4 sec. cor. of secs. 2 and 3.</p> <hr/> <p style="text-align: center;">FURTHER SUBDIVISION OF SECTION 2,<br/>T. 21 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the point for the W 1/16 sec. cor. of secs. 2 and 11.</p> <p>N. 0°05'00" W., on the N-S center line of the SW1/4 of sec. 2.</p> <p>Over open, gently rolling land.</p> <p>20.217 Point for the SW 1/16 sec. cor. of sec. 2, at intersection with the E-W center line of the SW1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SW 1/16<br/>S 2<br/>2007</p> <p>40.433 The point for the center W 1/16 sec. cor. of sec. 2.</p> <hr/> <p>From the point for the center S 1/16 sec. cor. of sec. 2.</p> <p>N. 89°39'50" W., on the E-W center line of the SW1/4 of sec. 2.</p> <p>Over open, gently rolling land.</p> <p>20.227 The SW 1/16 sec. cor. of sec. 2.</p> <p>40.452 The S 1/16 sec. cor. of secs. 2 and 3.</p> <hr/> |
|--------|---|



FURTHER SUBDIVISION OF SECTION 2,  
T. 21 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

|        |   |
|--------|---|
| CHAINS | <p>From the point for the center W 1/16 sec. cor. of sec. 2.</p>  |
|        | <p>N. 0°07'20" W., on the N-S center line of the NW1/4 of sec. 2.</p>   |
|        | <p>Over open, gently rolling land.</p>  |
|        |   |
| 21.310 | <p>Point for the NW 1/16 sec. cor. of sec. 2, at intersection with the E-W center line of the NW1/4.</p>  |
|        | <p>NOT MONUMENTED</p>   |
|        | <p>Enter a residential subdivision.</p>   |
|        |   |
| 40.626 | <p>The W 1/16 sec. cor. of sec. 2 only, on the N. bdy. of sec. 2, determined by Gregory D. Rivero, Nevada Professional Land Surveyor No. 6902, monumented with an aluminum cap, 1 1/2 ins. diam., firmly set flush with the asphalt, mkd. VPOINT PLS 6902, as recorded in Clark County, Nevada, File 120, Page 33 of Surveys. This is accepted as a careful and faithful determination of the position of the corner, from which accessories established by Gregory D. Rivero</p> |
|        | <p>An aluminum tablet, 2 ins. diam., firmly set in the top of concrete curb, mkd. VPOINT RM 42.81 PLS 6902, bears S. 34°47' E., 64.9 lks. dist., located on the south side of Charleston Boulevard.</p>   |
|        | <p>An aluminum tablet, 2 ins. diam., firmly set in the top of concrete curb, mkd. VPOINT RM 35.45 PLS 6902, bears S. 11°52' E., 53.7 lks. dist., located on the south side of Charleston Boulevard.</p>   |
|        | <p>An aluminum tablet, 2 ins. diam., firmly set in the top of concrete curb, mkd. VPOINT RM 38.97 PLS 6902, bears S. 28°40' W., 59.0 lks. dist., located on the south side of Charleston Boulevard.</p>   |
|        | <p>An aluminum tablet, 2 ins. diam., firmly set in the top of concrete curb, mkd. VPOINT RM 50.85 PLS 6902, bears S. 48°15' W., 77.0 lks. dist., located on the south side of Charleston Boulevard.</p>   |
|        | <p>From this corner, the standard cor. of secs. 34 and 35, T. 20 S., R. 62 E., bears N. 88°59'40" W., 5.517 chs. dist., hereinbefore described.</p>   |
|        | <hr/>   |
|        | <p>From the point for the center N 1/16 sec. cor. of sec. 2.</p>  |
|        | <p>N. 88°52'00" W., on the E-W center line of the NW1/4 of sec. 2.</p>  |
|        | <p>Over open, gently rolling land.</p>  |
| 20.461 | <p>The point for the NW 1/16 sec. cor. of sec. 2.</p>   |
| 25.989 | <p>The point for a witness point and intersection of the centerline of Hollywood Boulevard with the E-W center line of the NW1/4 of sec. 2, hereinafter described.</p>  |
| 40.921 | <p>The N 1/16 sec. cor. of secs. 2 and 3.</p>   |
|        | <hr/>   |


METES-AND-BOUNDS SURVEY OF A PORTION OF THE  
CENTERLINE OF HOLLYWOOD BOULEVARD IN SECTION 2,  
T. 21 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

|               |  |
|---------------|--|
| <p>CHAINS</p> | <p>The centerline of Hollywood Boulevard was based on a private survey conducted by James P. Stacy, Nevada Professional Land Surveyor No. 7004, as shown on map filed November 26, 1997, and recorded in Clark County, Nevada, File 92, Page 57 of Surveys.</p> <hr/> <p>From a local Point of Curvature, now also utilized in this survey as a witness point at the intersection of the centerline of Hollywood Boulevard with the line bet. secs. 2 and 3, established by James P. Stacy, Nevada Professional Land Surveyor No. 7004, monumented with an aluminum cap, 1 1/2 ins. diam., firmly set flush with the asphalt, mkd. 1999 PT PLS 7004, as recorded in Clark County, Nevada, File 92, Page 57 of Surveys.</p> <p>From this point, the S 1/16 sec. cor. of secs. 2 and 3, bears S. 0°24'00" E., 1.515 chs. dist., hereinbefore described.</p> <p>Thence along the arc of a circular curve to the right, having a radius of 1500.00 ft.; long chord of said arc bears N. 15°12'40" E., 12.232 chs. dist.</p> <p>12.385 Point of Tangency, now also utilized in this survey as a witness point, established by James P. Stacy, Nevada Professional Land Surveyor No. 7004, monumented with an aluminum cap, 1 1/2 ins. diam., firmly set flush with the asphalt, mkd. 1999 PC PLS 7004, as recorded in Clark County, Nevada, File 92, Page 57 of Surveys, from which accessories established by James P. Stacey</p> <p style="padding-left: 40px;">An aluminum tablet, 2 ins. diam., firmly set in the top of concrete curb, mkd. RM 73.98 PLS 7004, bears S. 57°35' W., 112.1 lks. dist.</p> <p style="padding-left: 40px;">An aluminum tablet, 2 ins. diam., firmly set in the top of concrete curb, mkd. RM 54.82 PLS 7004, bears N. 8°25' W., 83.1 lks. dist.</p> <hr/> <p>Thence, N. 30°49'20" E., on the centerline of Hollywood Boulevard, beginning new measurement.</p> <p>8.055 A local centerline point, now also utilized in this survey as a witness point at the intersection of the centerline of Hollywood Boulevard with the E-W center line of sec. 2, established by Paul Burn, Nevada Professional Land Surveyor No. 11174, monumented with an aluminum cap, 1 1/2 ins. diam., firmly set flush with the asphalt, mkd. P Burn PLS 11174, as recorded in Clark County, Nevada, File 113, Page 29 of Surveys.</p> <p>14.850 The point for a witness point and intersection of the centerline of Hollywood Boulevard with the centerline of American Beauty Road, hereinafter described.</p> <p>15.980 Point of Curvature, now also utilized in this survey as a witness point, established by James P. Stacy, Nevada Professional Land Surveyor No. 7004, monumented with an aluminum cap, 1 1/2 ins. diam., firmly set flush with the asphalt, mkd. 1999 PT PLS 7004, as recorded in Clark County, Nevada, File 92, Page 57 of Surveys.</p> |
|---------------|--|

METES-AND-BOUNDS SURVEY OF A PORTION OF THE  
CENTERLINE OF HOLLYWOOD BOULEVARD IN SECTION 2,  
T. 21 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

|                             |   |
|-----------------------------|---|
| <p>CHAINS</p> <p>12.030</p> | <p>Thence along the arc of a circular curve to the left, having a radius of 1500.00 ft.; long chord of said arc bears N. 15°39'30" E., 11.890 chs. dist.</p> <p>Point of Tangency and also a witness point.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, in a drill hole in asphalt, over a plastic-encased magnet, with top mkd.</p> <div style="text-align: center;">  </div> <p>from which an accessory established by James P. Stacey, Nevada Professional Land Surveyor No. 7004</p> <p>An aluminum tablet, 2 ins. diam., firmly set in the top of concrete curb, mkd. RM 75.72 PLS 7004, bears S. 28°59' W., 114.7 lks. dist.</p>  |
| <p>3.027</p>                | <p>Thence N. 0°29'40" E., on the centerline of Hollywood Boulevard, beginning new measurement.</p> <p>Point for a witness point at the intersection of the centerline of Hollywood Boulevard with the E-W center line of the NW1/4 of sec. 2.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, in a drill hole in asphalt, over a plastic-encased magnet, with top mkd.</p> <div style="text-align: center;">  </div> <p>from which unrecorded accessories established by Stephen P. Gurlides, Nevada Professional Land Surveyor No. 9105</p> <p>An aluminum tablet, 2 ins. diam., firmly set in the top of concrete curb, mkd. VTN RM 43.19 PLS 9105, bears N. 54°19' E., 65.4 lks. dist.</p> <p>An aluminum tablet, 2 ins. diam., firmly set in the top of concrete curb, mkd. VTN RM 44.35 PLS 9105, bears S. 51°26' E., 67.2 lks. dist.</p> <p>An aluminum tablet, 2 ins. diam., firmly set in the top of concrete curb, mkd. VTN RM 43.29 PLS 9105, bears S. 54°03' W., 65.6 lks. dist.</p> <p>An aluminum tablet, 2 ins. diam., firmly set in the top of concrete curb, mkd. VTN RM 44.48 PLS 9105, bears N. 50°57' W., 67.4 lks. dist.</p> |

METES-AND-BOUNDS SURVEY OF A PORTION OF THE  
 CENTERLINE OF AMERICAN BEAUTY ROAD IN SECTION 2,  
 T. 21 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

|        |  |
|--------|--|
| CHAINS | <p>The centerline of American Beauty Road was based on a private survey conducted by Paul Burn, Nevada Professional Land Surveyor No. 11174, as shown on map filed March 27, 2001, and recorded in Clark County, Nevada, File 115, Page 21 of Surveys.</p> <hr/> <p>From the point for a witness point at the intersection of Hollywood Boulevard with the centerline of American Beauty Road.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, in a drill hole in asphalt, over a plastic-encased magnet, with top mkd.</p> <div style="text-align: center;">  <p>2007</p> </div> <p>From this point, the witness point at Point of Curvature of a circular curve to the left having a radius of 1500.00 ft., bears N. 30°49'20" E., 1.130 chs. dist., hereinbefore described.</p> <p>Thence N. 59°10'40" W., on the centerline of American Beauty Road.</p> <p>1.108 Point of Curvature.</p> <p>NOT MONUMENTED</p> <p>Thence along the arc of circular curve to the left, having a radius of 550.00 ft.; long chord of said arc bears N. 74°48'35" W., 4.491 chs. dist.</p> <p>4.547 Point of Tangency.</p> <p>NOT MONUMENTED</p> <hr/> <p>Thence S. 89°33'30" W., on the centerline of American Beauty Road, beginning new measurement.</p> <p>5.722 Point for a witness point at the intersection of the centerline of American Beauty Road with the line bet. secs. 2 and 3.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, in a drill hole in asphalt, over a plastic-encased magnet, with top mkd.</p> <div style="text-align: center;"> <p>WP</p> <p>S 3   S 2</p> <p>2007</p> </div> <p>from which unrecorded accessories established by Frederick W. Orban, Nevada Professional Land Surveyor No. 4541</p> <p>An aluminum tablet, 2 ins. diam., firmly set in the top of concrete curb, mkd. RM 25.02 PLS 4541, bears S. 9°22' W., 37.9 lks. dist., located on the south side of American Beauty Road.</p> |
|--------|--|

METES-AND-BOUNDS SURVEY OF A PORTION OF THE  
 CENTERLINE OF AMERICAN BEAUTY ROAD IN SECTION 2,  
 T. 21 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

|               |   |
|---------------|---|
| <p>CHAINS</p> | <p>An aluminum tablet, 2 ins. diam., firmly set in the top of concrete curb, mkd. RM 48.32 PLS 4541, bears S. 59°00' W., 73.2 lks. dist., located on the south side of American Beauty Road.</p> <p>An aluminum tablet, 2 ins. diam., firmly set in the top of concrete curb, mkd. RM 26.14 PLS 4541, bears N. 19°45' W., 39.6 lks. dist., located on the north side of American Beauty Road.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The area resurveyed within Township 21 South, Range 62 East, is situated in Clark County. The land is ascending to the east towards Sunrise Mountain, with soil being gravely and rocky. There are subdivisions to the north, east and south of section 2. The average elevation is approximately 1810 feet above sea level.</p> <p>Access into the area is provided by the following paved streets: East Charleston Boulevard, Hollywood Boulevard and East Sahara Avenue.</p> <hr/> |
|---------------|---|

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

|                    |  |
|--------------------|--|
| George H. McGovern | Surveying Technician (Horizon Surveys) |
| Ryan J. Mulhall    | Survey Aid (Horizon Surveys)           |



## CERTIFICATE OF SURVEY

I, Brent K. Layton, Nevada Professional Land Surveyor, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 22nd day of January, 2007, I have dependently resurveyed the Fifth Standard Parallel South, on the south boundary of Township 20 South, through a portion of Range 62 East; and dependently resurveyed a portion of the subdivisional lines and a portion of the subdivision-of-section lines of section 2, further subdivided section 2, and surveyed by metes and bounds in section 2, Township 21 South, Range 62 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

September 22, 2008

(Date)

B.K. Layton  
(Nevada Professional Land Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Reno, Nevada

The foregoing field notes of the dependent resurvey of the Fifth Standard Parallel South, on the south boundary of Township 20 South, through a portion of Range 62 East; and the dependent resurvey of a portion of the subdivisional lines and a portion of the subdivision-of-section lines of section 2, the further subdivision of section 2, and metes-and-bounds surveys in section 2, Township 21 South, Range 62 East, Mount Diablo Meridian, Nevada, executed by Brent K. Layton, Nevada Professional Land Surveyor, having been critically examined and found correct, are hereby approved.

September 25, 2008

(Date)

David W. Moran  
(Chief Cadastral Surveyor, Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above described surveys in T. 21 S., R. 62 E., Mount Diablo Meridian, Nevada, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor, Nevada)~~